Listing of Claims:

1. A method for indicating a position of a synchronous signal block, applied to a network apparatus, comprising:

determining a transmission position of a synchronous signal block of at least one first type of cell; and

sending, by a signaling, the transmission position of the synchronous signal block of the at least one first type of cell to a terminal apparatus; wherein the terminal apparatus is located within a range of a second type of cell managed by the network apparatus, and the first type of cell is a neighboring cell of a cell where the terminal apparatus is located, and wherein the signaling is broadcast signaling or radio resource control (RRC) dedicated signaling,

wherein, the sending, by the signaling, the transmission position of the synchronous signal block of the at least one first type of cell to the terminal apparatus, comprises:

generating a bitmap based on the transmission position of the synchronous signal block of the at least one first type of cell, and sending the bitmap to the terminal apparatus by the signaling,

wherein the bitmap is used to notify the actual transmission position of the synchronous signal block of the neighboring cell;

wherein the bitmap comprises a plurality of bits, each bit corresponds to a candidate position of the synchronous signal block, and a value of each bit is used to indicate whether the synchronous signal block is actually transmitted at the corresponding candidate position; and

wherein each bit has a value of 1 or 0, wherein a value of 1 indicates that the synchronous signal block is transmitted at its corresponding candidate position, and a value of 0 indicates no synchronous signal block is transmitted at the corresponding candidate position.

2. The method according to claim 1, wherein the number of the candidate positions is 8.

3. The method according to claim 1, further comprising:

sending, to the terminal apparatus, a synchronous relationship between the at least one first type of cell and a cell managed by the network apparatus;

wherein, the synchronous relationship comprises: a synchronous state between the first type of cell and the cell managed by the network apparatus; or, a synchronous deviation between the first type of cell and the cell managed by the network apparatus.

4. The method according to claim 1, wherein, the generating the bitmap based on the transmission position of the synchronous signal block of the at least one first type of cell, and sending the bitmap to the terminal apparatus by the signaling, comprises:

when at least one first type of cell is in a synchronous state with the cell managed by the network apparatus, generating the bitmap of the transmission position of the synchronous signal block comprising all the first type of cell based on the transmission position of the synchronous signal block of all the first type of cell; and

sending, by the signaling, the bitmap comprising the transmission position of the synchronous signal block of all the first type of cell to the terminal apparatus.

5. A method for indicating a position of a synchronous signal block, applied to a terminal apparatus, comprising:

receiving a signaling which indicates a transmission position of a synchronous signal block of at least one first type of cell from a network apparatus, wherein the terminal apparatus is located in a cell managed by the network device, and the first type of cell is a neighboring cell of the cell where the terminal apparatus is located, and wherein the signaling is broadcast signaling or radio resource control (RRC) dedicated signaling; and

measuring the synchronous signal block of the at least one first type of cell based on the transmission position of the synchronous signal block of the at least one first type of cell,

wherein, the receiving the signaling which indicates the transmission position of the

synchronous signal block of the at least one first type of cell from the network apparatus, comprises:

receiving a signaling from the network apparatus; and acquiring a bitmap from the signaling, and acquiring, by the bitmap, the transmission position of the synchronous signal block of the at least one first type of cell,

wherein the bitmap is used to notify the actual transmission position of the synchronous signal block of the neighboring cell,

wherein the bitmap comprises a plurality of bits, each bit corresponds to a candidate position of the synchronous signal block, and a value of each bit is used to indicate whether the synchronous signal block is actually transmitted at the corresponding candidate position; and

wherein each bit has a value of 1 or 0, wherein a value of 1 indicates that the synchronous signal block is transmitted at its corresponding candidate position, and a value of 0 indicates no synchronous signal block is transmitted at the corresponding candidate position.

6. The method according to claim 5, wherein the number of the candidate positions is 8.

7. The method according to claim 5, further comprising:

receiving a synchronous relationship between the at least one first type of cell sent by the network apparatus and a cell managed by the network apparatus;

wherein, the synchronous relationship comprises: a synchronous state between the first type of cell and the cell managed by the network apparatus; or, a synchronous deviation between the first type of cell and the cell managed by the network apparatus.

8. The method according to claim 7, wherein the acquiring the bitmap from the signaling, and acquiring, by the bitmap, the transmission position of the synchronous signal block of the at least one first type of cell, comprises:

when the at least one first type of cell is in the synchronous state with the cell managed by the network apparatus, acquiring, from the bitmap, the transmission position of the synchronous signal block of all the at least one first type of cell.

9. A network apparatus, comprising:

a processing unit, configured to determine a transmission position of a synchronous signal block of at least one first type of cell; and control to send the transmission position of the synchronous signal block of the at least one first type of cell to a terminal apparatus by a signaling; wherein, the terminal apparatus is located within a range of a second type of cell managed by the network apparatus, and the first type of cell is a neighboring cell of a cell where the terminal apparatus is located, wherein the signaling is broadcast signaling or radio resource control (RRC) dedicated signaling; and

a communication unit, configured to send the signaling to the terminal apparatus,

wherein the processing unit is configured to generate a bitmap based on the transmission position of the synchronous signal block of the at least one first type of cell, and control the communication unit to send the bitmap to the terminal apparatus by the signaling,

wherein the bitmap is used to notify the actual transmission position of the synchronous signal block of the neighboring cell;

wherein the bitmap comprises a plurality of bits, each bit corresponds to a candidate position of the synchronous signal block, and a value of each bit is used to indicate whether the synchronous signal block is actually transmitted at the corresponding candidate position; and

wherein each bit has a value of 1 or 0, wherein a value of 1 indicates that the synchronous signal block is transmitted at its corresponding candidate position, and a value of 0 indicates no synchronous signal block is transmitted at the corresponding candidate position.

10. The network apparatus according to claim 9, wherein the number of the candidate positions is 8.

11. The network apparatus according to claim 9, wherein, the communication unit is configured to send, to the terminal apparatus, a synchronous relationship between the at least one first type of cell and the cell managed by the network apparatus;

wherein, the synchronous relationship comprises: a synchronous state between the first type of cell and the cell managed by the network apparatus; or, a synchronous deviation between the first type of cell and the cell managed by the network apparatus.

12. A terminal apparatus, comprising:

an information receiving unit, configured to receive a transmission position of a synchronous signal block of at least one first type of cell sent by a network apparatus via a signaling, wherein the terminal apparatus is located in a cell managed by the network device, and the first type of cell is a neighboring cell of the cell where the terminal apparatus is located, and wherein the signaling is broadcast signaling or radio resource control (RRC) dedicated signaling; and

a measuring unit, configured to measure the synchronous signal block of the at least one first type of cell based on the transmission position of the synchronous signal block of the at least one first type of cell,

wherein, the information receiving unit is configured to receive the signaling sent from the network apparatus,

the measuring unit is configured to acquire a bitmap from the signaling, and acquire, by the bitmap, the transmission position of the synchronous signal block of the at least one first type of cell,

wherein the bitmap is used to notify the actual transmission position of the synchronous signal block of the neighboring cell,

wherein the bitmap comprises a plurality of bits, each bit corresponds to a candidate position of the synchronous signal block, and a value of each bit is used to indicate whether the

synchronous signal block is actually transmitted at the corresponding candidate position; and

wherein each bit has a value of 1 or 0, wherein a value of 1 indicates that the synchronous signal block is transmitted at its corresponding candidate position, and a value of 0 indicates no synchronous signal block is transmitted at the corresponding candidate position.

13. The terminal apparatus according to claim 12, wherein, the number of the candidate positions is 8.

14. The terminal apparatus according to claim 12, wherein, the information receiving unit is configured to receive a synchronous relationship between the at least one first type of cell sent by the network apparatus and a cell managed by the network apparatus sent from the network apparatus;

wherein, the synchronous relationship comprises: a synchronous state between the first type of cell and the cell managed by the network apparatus; or, a synchronous deviation between the first type of cell and the cell managed by the network apparatus.

15. The terminal apparatus according to claim 14, wherein, the measuring unit is configured to, when the at least one first type of cell is in the synchronous state with the cell managed by the network apparatus, acquire, from the bitmap, the transmission position of the synchronous signal block of all the first type of cell.