

Exit pupil expander

Field of the Invention

The invention relates to diffractive display technology. In particular, the invention relates to lightguide-based diffractive display elements comprising an exit pupil expander (EPE).

- 5 Such display elements can be used in personal displays, such as head-mounted displays (HMDs), for example near-to-eye displays (NEDs), and head-up displays (HUDs).

Background of the Invention

- HMDs and HUDs can be implemented using waveguide technology. Light can be coupled to a waveguide, redirected therein and coupled out of the waveguide using diffraction
- 10 gratings. In one conventional display design, light is directed from a projector to an in-coupling grating, which diffracts the incoming light into the waveguide, where it propagates via total internal reflections towards an out-coupling grating via an EPE grating to extend the viewable area of the display laterally. EPEs typically comprise a grating which has grating lines oblique with respect to the grating line orientation of the in-
- 15 coupling grating and the propagation direction of light incoming from the in-coupling grating.

Like all gratings, also EPE gratings generally cause losses and disturbances. This decreases the brightness and uniformity of the final image formed and causes image imperfections, such as colour imbalance.

- 20 Thus, there is a need for improved exit pupil expansion solutions and improved waveguide displays.

Summary of the Invention

- It is an aim of the invention to increase the image quality of waveguide displays. Particular aims are to increase the brightness (total efficiency), uniformity and/or color balance of
- 25 waveguide displays. One aim is to provide an EPE solution that relieves geometric constraints of EPE shapes.

The aim is achieved by the what is stated in the independent claims.

According to one aspect, there is provided an exit pupil expander (EPE) for use in a diffractive display, the EPE comprising a plurality of diffractive zones (grating zones) on a waveguide and a plurality of non-diffractive zones (non-grating zones) between at least
5 some of the diffractive zones. The diffractive zones and non-diffractive zones can be arranged as an irregular or regular two-dimensional pattern.

In other words, there is provided an EPE having an area containing a plurality of diffractive zones and "voids" at which no diffraction, but only total internal reflection from a surface of the waveguide takes place.

10 According to one aspect, there is provided a diffractive display element for personal displays, the element comprising a waveguide, an in-coupling region for diffractively coupling an image into the waveguide body, an out-coupling region for diffractively coupling the image out of the waveguide body, and an exit pupil expander (EPE) region of the presently disclosed kind between the in-coupling region and the out-coupling region
15 for expanding the exit pupil of the image on the out-coupling region.

According to one aspect, there is provided a personal display device, such as a head-mounted display (HMD) or head-up display (HUD), comprising a diffractive display element of the above kind.

EPE herein means a region in the lateral plane of the waveguide that has the property of
20 extending the exit pupil of light incoming from one lateral direction and outgoing to another lateral direction.

The invention offers significant benefits. The inclusion of voids inside and on the peripheral boundary of the EPE region enables the optimization of geometrically more complex EPEs. Typically, the EPE shape is calculated by simple geometrical calculations
25 using rays propagating with extreme angles inside the waveguide. This leads to a non-optimal solution. The present invention helps to find EPE solutions via numerical optimization that exhibit better performance in terms of color balance and efficiency than the EPE shapes calculated by simple geometrical calculations. The approach can be used also to find EPE structures that allow more compact form factor for the waveguide.
30 Especially, large field of view (> 40 deg) EPEs tend to grow so large that the total waveguide size is too big for wearable displays with compact form factor.

The dependent claims are directed to selected embodiments of the invention.

- In some embodiments there is at least one first non-diffractive zone is positioned between two diffractive zones in a first direction and at least one second non-diffractive zone is positioned between two diffractive zones in a second direction orthogonal to the first direction. In some embodiments there are at least 10 different (separate) diffractive zones and at least 10 different (separate) non-diffractive zones.

In some embodiments there are at least two diffractive zones and/or at least two non-diffractive zones with different sizes or shapes.

- In some embodiments the diffractive zones comprise at least two zones with different grating properties. This allows for performing even more complex EPE functions.

In some embodiments the diffractive zones and non-diffractive zones are dividable in the surface plane of the waveguide into equally shaped unit zones.

In some embodiments at least 20% of the total area of the EPE is formed of non-diffractive zones.

- In some embodiments the zones are positioned such that it is possible to draw at least two different cross-sectional lines in along both main optical axes thereof so that the diffractive/non-diffractive profile along those lines is different.

- In some embodiments, in the present waveguide element the diffractive zones and non-diffractive zones of the EPE are configured so that at least a majority of light incoming from the in-coupling region is diffracted by at least one diffractive zone, bounced by total internal reflection in at least one non-diffractive zone, and again diffracted by at least one diffractive zone, typically different from the first diffractive zone, before exiting the EPE towards the out-coupling region.

- In some embodiments the non-diffractive zones of the EPE are provided therein for increasing the brightness, uniformity or color balance of the display element, compared with a situation where the non-diffractive zones were replaced with diffractive zones.

In some embodiments, the EPE has a width which is at least the same as the width of the out-coupling region.

Next, embodiments of the invention and advantages thereof are discussed in more detail with reference to the attached drawings.

Brief Description of the Drawings

Fig. 1 shows an network of ray pats formed inside an EPE structure due to a single
5 incident ray.

Fig. 2A shows an exemplary EPE in accordance with the invention, positioned optically between an in-coupler and an out-coupler.

Fig. 2B shows a detail view of a portion of the EPE of Fig. 2A.

Detailed Description of Embodiments

10 When a light ray propagates through EPE, a complex network of ray paths is formed, in which energy flows typically along two directions. An exemplary network is shown in Fig 1. The dots show the locations where the rays, generated due to diffraction from the incident ray 11, hit the grating surface. The network structure allows energy transport along multiple ray paths between the points inside the network. Two example paths are shown
15 by dashed lines from the point A to B. As all possible paths are not needed for energy transport, the operation of the EPE structure can be enhanced by allowing also empty regions (voids) to be formed inside EPE and on the peripheral boundary of EPE during numerical optimization.

Fig. 2A shows an in-coupling grating 22 to which light is directed from a projector, typically
20 essentially perpendicular to the image plane of the figure. Light is diffracted and propagates in the waveguide to the EPE 24 comprising diffractive zones 24A and non-diffractive zones (voids) 24B. The non-diffractive zones 24B are typically simply regions without a grating pattern therein, whereas the diffractive zones comprise a grating. The non-diffractive zones therefore serve as an ordinary waveguide zone, where light rays
25 bounce via total internal reflections without diffraction.

The diffractive zones 24A typically comprise a linear (one-dimensional) grating pattern. The orientation of grating lines and period of grating between each diffractive zones 24A is typically the same, while the microfeature profile, including in particular fill factor and/or height of microfeatures, may differ between the zones.

The diffractive zones 24A may be unit zones, for example rectangular unit zones like shown in Fig. 2A, or arbitrarily shaped zones without unitary grating lines therein (that is, without the inner boundaries drawn in Figs. 2A and 2B).

5 The invention is not restricted to orthogonal geometry as concerns the shapes of the diffractive zones 24A and non-diffractive zones 24B. They can have oblique or curved outer shapes of practically any complexity.

The positioning of the diffractive zones and non-diffractive zones can be determined and optimized using computational techniques known *per se* for diffractive optical design.

10 The in-coupling grating 22, EPE 24 and out-coupling grating are typically arranged on a planar waveguide element. The waveguide can be a planar piece of transparent material, typically plastic or glass, having two parallel main surfaces. All gratings and diffractive zones discussed here can be fabricated for example as surface relief gratings (SRGs) or by providing additional material onto the surface as diffractive features, or other diffractive optical elements (DOEs). In one example, the gratings comprise linear features made of
15 at least one oxide or nitride material, such as TiO_2 , Si_3N_4 , and HfO_2 , on a glass waveguide.

It should be noted that the invention is applicable also in various other display geometries and configurations.

20 In the case of multilayer waveguides, each layer carrying for example a different wavelength band, embodiments of the invention can be applied separately to each layer.

Embodiments of the invention are usable both with broadband illumination and narrowband (including narrow multi-band) illumination and projectors.

Claims

1. A diffractive display element for displaying an image, comprising
 - a waveguide,
 - an in-coupling region for diffractively coupling an image into the waveguide body,
 - 5 – an out-coupling region for diffractively coupling the image out of the waveguide body,
 - an exit pupil expander (EPE) region between the in-coupling region and out-coupling region for expanding the exit pupil of the image on the out-coupling region,
- 10 wherein the EPE region comprises a plurality of diffractive zones arranged on a surface of a waveguide and a plurality of non-diffractive zones between the diffractive zones, and
the EPE region comprises at least 10 different diffractive zones and at least 10 different non-diffractive zones positioned such that at least one first non-diffractive zone is
positioned between two diffractive zones in a first direction and at least one second non-
15 diffractive zone is positioned between two diffractive zones in a second direction
orthogonal to the first direction.
2. The element according to claim 1, wherein the diffractive zones and non-diffractive zones are arranged as an irregular two-dimensional pattern.
3. The element according to claim 1, wherein the diffractive zones and non-diffractive
20 zones are arranged as a regular two-dimensional pattern.
4. The element according to any of the preceding claims, comprising at least two diffractive zones and/or at least two non-diffractive zones with different sizes or shapes.
5. The element according to any of the preceding claims, wherein the diffractive zones comprise at least two grating zones with different grating properties.
- 25 6. The element according to any of the preceding claims, wherein the diffractive zones and non-diffractive zones are dividable in the surface plane of the waveguide into equally shaped unit zones.
7. The element according to any of the preceding claims, wherein at least 20% of the total area of the EPE is formed of non-diffractive zones.

8. The element according to any of the preceding claims, wherein the diffractive and non-diffractive zones are positioned such that it is possible to draw at least two different cross-sectional lines in along both main optical axes thereof so that the diffractive/non-diffractive profile along those lines is different.
- 5 9. The element according to any of the preceding claims, wherein the diffractive zones and non-diffractive zones of the EPE region are configured so that at least a majority of light incoming from the in-coupling region is diffracted by at least one diffractive zone, bounced by total internal reflection in at least one non-diffractive zone, and again
10 diffracted by at least one diffractive zone, typically different from the first diffractive zone, before exiting the EPE towards the out-coupling region.
10. The element according to any of the preceding claims, wherein the non-diffractive zones of the EPE region are provided therein for increasing the brightness, uniformity or color balance of the display element, compared with a situation where the non-diffractive zones were replaced with diffractive zones.
- 15 11. The element according to any of the preceding claims, wherein the EPE region has a width which is at least the same as the width of the out-coupling region.
12. A personal display device, such as a head-mounted display (HMD) or head-up display (HUD), comprising a diffractive display element according to any of the preceding claims.