

Dec 1981

Many types of tool sets have been devised over the years. For example, tool sets which provide multiple sizes of open-end wrenches, or tool sets which provide various size sockets together with a socket drive and ratchet, or which provide multiple types and sizes of screwdrivers, or various size allen wrenches or the like are common in the art. Frequently when a person is engaged in work, it is convenient or necessary to have different types and sizes of wrenches, screwdrivers or other such hand tools available. For example, at times, it may be necessary to use selected combinations of tools for certain jobs. However, this requires carrying a large number of tools, which is both inconvenient and sometimes impractical. Furthermore, often it is difficult to keep track of the various tools provided with a set, with the result that sometimes parts to the set become lost. Nothing can be more frustrating than not being able to find a particular size tool when it is needed for a job.

In summary, while it is convenient and often necessary to have various types of tool sets readily available on the job so that different sizes and kinds of tools such as wrenches, screwdrivers and the like will be readily accessible, it is inconvenient to have to carry numerous tools and it is also frequently difficult to keep track of the tools. Another problem frequently encountered is the difficulty required in changing from one tool to another within a given set. This often requires disconnecting and reconnecting parts, which may be cumbersome and time consuming.

US-A-1, 464, 132 describes a tool set comprising a plurality of at least three tools, linking means for linking each said tool to one or to two adjacent tools, and connecting means for connecting said linking means such that each end of each linking means is pivotally connected to not more than one adjacent linking means, so as to form a chained tool set capable of being manipulated so that any selected one of the tools is available for use on a workpiece while the remaining tools form a handle for the selected tool. Each tool in the set is a socket opening (as in a wrench) that is formed in the linking means, and the set is not capable of carrying other types of tool. When certain of the socket openings are selected for use then the handle that is formed may be difficult to use, and the available leverage may be limited.

The invention seeks to provide a more versatile tool set which provides in a single hand piece a plurality of tools which can be changed in rapid succession from one tool to the other.

According to the invention a tool set as set forth in Claim 1 is characterised in that each working section is a working tip connected to a side of its associated linking means so that each working tip is or can be arranged in a first plane parallel to, and laterally offset from, the plane of its associated linking means and each working tip is or can be further arranged so that it extends in said first plane beyond an end of its associated linking means, and in

that said linking means and connecting means are such as to allow all adjacent linking means to be folded to form a substantially rigid handle incorporating all the linking means arranged in two parallel rows, with at least one working tip extending from the handle, so as to be operable on a workpiece.

A chained tool set according to the invention may thus comprise a set of tools consisting of any desired working tips such as an open-end wrench, a box-end wrench, fractional or metric wrenches, socket drives, spline drives, spanner wrenches, screwdrivers of all styles, tools such as taps, easy outs, allen wrenches or other similar tools. All such working tips can be present as in the operative position, the working tip of the selected tool extends from the handle. Each tool is formed as part of a link and each link is joined to an adjacent tool link. When using one of the tools, the chain can be collapsed to form a rigid and strong handle which can be used to apply the torque or other force necessary to operate the tool. The chained tool set is preferably designed so that if desired any or all of the tool links can be disconnected one from the other so that new or different size tools can be added into the chain, or so that worn tools can be removed and replaced.

The invention can be better understood from the following description of preferred embodiments of tool set, given by way of example and with reference to the accompanying drawings in which:

Figure 1 is a perspective view in which a portion of a chained tool set constructed in accordance with the present invention has been depicted in order to illustrate the basic inventive concept of the present invention.

Figure 2 is a perspective view of a complete chained tool set with the chain in an open configuration.

Figure 3 is a perspective view showing the chained tool set of Figure 2 in a configuration wherein the chain has been collapsed to form a hand piece which can be used to operate a selected tool.

Figure 4 is a perspective view similar to Figure 1 wherein one of the tool links and connecting pins has been shown in exploded perspective to more fully illustrate the manner in which the various tool links are connected to form the chained tool set of the present invention.

Figures 5-7 are enlarged perspective views showing portions of a tool link which have been broken away to more fully illustrate alternative structures for linking the chain such that tool links can be disconnected one from the other for purposes of adding or replacing tool links in the chain.

Figure 8 is an exploded perspective view with portions broken away so as to illustrate yet another embodiment of a tool link that may be used in the present invention.

Figure 9 is a perspective view illustrating still another embodiment of the chained tool set of the present invention in which different types of tools have been linked together to form the chain.

Figure 10 is a cross-sectional view taken along line 10-10 of Figure 9.

Figure 11 is an exploded perspective view illustrating still another embodiment of the present invention.

Referring first to Figures 1 and 2, one presently preferred embodiment of the chained tool set of the present invention is generally designated at 20. As shown in Figure 2, the chained tool set 20 may be linked together to form an endless loop. In the alternative, the chained tool set 20 may be disconnected between a pair of adjacent links so as to form simply a straight chain, a portion of which is illustrated in Figure 1. Either configuration is within the scope of the present invention.

As shown best in Figures 1 and 2, the chained tool set 20 comprises a plurality of tool links generally designated at 22a-22f. Each of the tool links 22 may be similarly formed so as to provide the same type of tool with each tool having a different size, such as the open-end wrench set illustrated in Figures 1 and 2, or as hereinafter more fully described, each tool link 22 may be formed so as to provide a different type of tool such as illustrated in Figures 9 and 10 discussed below. The tool links 22 can be manufactured using any suitable method, such as casting, machining, drop forging, investment casting or centrifugal casting. The tools can be constructed of any material suitable for a particular job or application such as steel with a finish of chrome, zinc, nickel or the like. Plastics may be used in forming the tool links when they are to be used in applications such as assembling childrens' plastic toys or the like. In cases where factors such as strength and weight govern over cost considerations, materials such as titanium or high strength polymer materials may be used.

With reference to Figures 1, 2 and 4, each tool link 22 comprises two side members 24 and 25 which are attached to and formed as an integral part of the working tip of a tool. For example, as shown in Figures 1-4 each tool link 22 comprises a tool which is configured as a open-end wrench. Each tool has a working tip 28 which, in the case of Figures 1-4 consists of the mouth of the open-end wrench and a shank 26 attached at the base of the working tip 28. As shown in Figure 1, the shank of an adjacent tool is designed in terms of its length, width and height so that it interlocks with the mouth of an adjacent tool. As hereinafter more fully described, this arrangement helps to provide strength and rigidity when the chain is folded or collapsed and used as a hand piece for purposes of applying torque or other force to a selected tool, since the torsional bending moment on the connecting pins 34 is thereby reduced.

With reference again to Figures 1, 2 and 4 each tool link 22 is pivotally connected to an adjacent tool link by means of connecting links 32 and pins 34. As shown best in Figure 4, the pins 34 are inserted through holes 35 which are provided at the ends of side members 24 and 25 of each tool link 22. The connecting links 32 are designed to be inserted in the space provided between side members 24 and 25, and connecting links 32 are also provided with corresponding holes 36 which receive the connect-

ing pins 34. Pins 34 are constructed with a diameter which is large enough to provide a snug friction fit when inserted in the holes 35 and 36 of tool links 22 and connecting links 32. As hereinafter more fully described, pins 34 may be removed when it is desired to add additional tools into the chain and/or when it is desired to remove and replace worn tools.

As shown in Figure 1, the working tip 28 of each tool extends from the end of one tool link and overlaps the end of an adjacent tool link. This helps to ensure that when the tool links 22 are connected together the pivoting action will be restrained so that the tool links will only be able to pivot in one direction. This helps to provide rigidity when using the chained tool set, particularly if the chained tool set is used in a configuration such as that illustrated in Figure 1 where the chain is straight rather than forming a loop as in the case of Figure 2. Thus, with the embodiment of Figure 1, if the chained tool set 20 is held so that the open-end wrench of each tool link 22 faces downwardly, the chain will maintain a rigid, linear configuration since the tool links cannot rotate downwardly when the chained tool set 20 is in that position.

When the chained tool set 20 is connected to form an endless loop as in the case of Figure 2, each tool link can be pivoted so as to open the chain as illustrated in Figure 2. When a particular tool is selected the chain can then be folded or collapsed as shown in Figure 3 to form two parallel rows of tool links which serve as a rigid hand piece that is very strong and which can be firmly grasped when applying the torque or other force necessary to operate the tool. It will also be appreciated as illustrated in Figure 3 that when so collapsed, the tool 22f and 22c at either end of the collapsed chain may be in a working position similar to a conventional open-end wrench. Another advantage provided by the hand piece which is formed when the chain is collapsed as shown in Figure 3 arises from the fact that the hand piece typically has a thickness much greater than a typical wrench and therefore is much easier to grip so that greater force can be applied. It should also be noted that in the embodiment of Figure 1 wherein the chain is straight rather than being connected as a loop, the chain can still be folded over to form a hand piece having at least two parallel rows of tool links as depicted in Figure 3.

Figure 5, 6 and 7 each illustrate alternative ways in which adjacent tool links 22 can be connected. As shown in Figure 5, the pin 34a may be threaded at one end 29 and provided with a slot 27 at the other end thereof so that the pin 34a can be screwed into one of the side members 25. When it is desired to add additional tool links or to replace worn tools the pin 34a can then be unscrewed and removed so as to disconnect the tool links.

An alternative arrangement for connecting adjacent tool links is shown in Figure 6. As there illustrated, each connecting pin 34b is provided with a notch 31 and each connecting link 32' is provided with a corresponding slot 33 so that a retainer clip 37 can be clipped onto the connecting link 32' to engage the notch 31 of each connecting pin 34b. Retaining clip 37 is formed on its sides so that the lead-

ing 23 are bent inwardly whereas the middle portion 21 of the sides are bowed out, thus providing a compression or spring-like action which holds the retaining clip 37 in place once the portions 21 engage the notches 31 of connecting pins 34b. The retaining clip 37 can then be removed when it is desired to remove the connecting pins 34b for purposes of adding or replacing tools in the chain.

In the alternative embodiment shown in Figure 7, the connecting pin 34c is designed so as to permanently connect adjacent tool links. Connecting pin 34c comprises enlarged head members 39 at opposite ends thereof which may be formed after insertion of the pin by any of several techniques which are common in the art. Thus, in the embodiment of Figure 7, once the tool links are connected to form the chain, they may not be removed or replaced. It will therefore be appreciated that the chained tool set of the present invention may be provided with links which are either capable of being disconnected or which are permanently attached to one another.

As mentioned in the background portion of this specification, at times it may be necessary or desirable to use selected combinations of tools for certain jobs. For example, it may be desirable to provide a customized tool set which would be particularly suitable for cyclists. Included in such a tool set would be items such as a spoke wrench, bearing spanner wrenches, a box-end wrench for pedal crank hubs and so forth. As will be appreciated, using the connecting pin arrangement as illustrated in Figures 1-4 or as shown in Figures 5 and 6, it is possible to easily change or replace the type of tools provided on the chain wrench so that a customized tool set can be provided. In some applications, it may also be desirable to provide customized tool sets for use in assembling and/or maintaining certain types of machinery or equipment. In those instances, specially designed tool sets may be provided using embodiments of the present invention which either provide for interchangeability of tool links as in the case of the embodiments of Figures 1-6, or using tool links which are permanently joined and are not interchangeable as in the case of the embodiment of Figure 7. In either case, it is within the scope of the present invention to provide chained tool sets which comprise either the same type of tool with the size of the tools varying or a combination of different types of tools as shown and as described more fully below in connection with the embodiments illustrated in Figures 9-10.

Reference is next made to Figure 8. Figure 8 illustrates another embodiment of a tool link which can be used to increase the rigidity and strength of the hand piece that is formed when the chain is collapsed as shown in Figure 3. In Figure 8, two tool links are generally designated at 40a and 40b. Each tool link 40 comprises a working tip 28, which in Figure 8 is shown as an open-end wrench as illustrated at 28a and 28b, respectively. As in the case of the previously described embodiments, each tool link 40 is formed as an integral piece. However, unlike the embodiments described above, in Figure 8 each tool link 40 is constructed so that the side members

24 and 25 are joined to each other by a support member 41 formed toward the middle and between side members 24 and 25. The support member 41 has a semicircular slot 44 formed in it.

As shown in connection with tool link 40a which is illustrated to the left in Figure 8, a circular disk 52 may be provided in the slot 44 of every other tool link 40. The circular disk 52 is secured within the slot 44 by means of a retaining pin 48 which is received through holes 46 formed in the top and bottom of the semicircular slot 44, as shown best in tool link 40b of Figure 8. Retaining pin 48 may comprise a compression type pin constructed of spring steel with a seam-like gap 50 formed along its length which allows the retaining pin 48 to be compressed and inserted into the holes 46 provided at the top and bottom of the semicircular slot 44 as well as the corresponding hole provided in the disk 52.

The disk 52 functions as a key which engages the semicircular slot 44 of an adjacent tool link. Accordingly, as shown best in the cross-sectional view of Figure 10, when the chain is collapsed to form the hand piece which is gripped for purposes of operating a tool, the disk 52 engages the semicircular slot 44 of the adjacent tool link which then serves to hold the adjacent tool links so as to prevent them from slipping either longitudinally or laterally with respect to one another. As will be appreciated, this serves to provide additional strength and rigidity to the hand piece when using a selected tool. Moreover, the additional support member 41 which connects the side members 24 and 25 of each tool link 40 serves to provide additional strength and rigidity.

In the embodiment of Figures 9 and 10, each tool link 60a-60f of the chained tool set is similar to the tool links 40a and 40b described in Figure 8, except with respect to the manner in which the working tips 62a-62f are secured to the tool links. In the embodiment of Figures 9 and 10, each tool link 60 is provided with a pair of arms 64 and 65 which extend outwardly and are formed as integral parts of the side members 24 and 25 of each link. The arms 64 and 65 are each provided with holes at their forward ends which receive a pivot pin 68 which is used to secure the tool between the arms 64 and 65. Thus, each tool comprises a suitable base 66 which has a bore through the base for receiving the pivot pin 68. Extending from the base 66a of each tool is the working tip 62a for the particular type of tool desired. Thus, as shown in Figure 9 tool 62a is a conventional screwdriver tip, tool 62b is a conventional socket drive, tool 62c has a working tip formed as a conventional allen wrench, tool 62e (Figure 10) is a philips screwdriver tip and tool 62f has a working tip formed as a box-end wrench. In each case the base 66 of the tool is designed to swivel about the pivot pin 68 which secures the tool base 66 between the arms 64 and 65 of the tool link 60. Thus, as illustrated by the phantom line position for allen wrench 62c in Figure 9, each tool may be positioned in one of several positions when using the tool to perform work.

As shown best in Figure 10, the position for each tool is secured by means of the pivot pin 68, which

is provided with a plurality of detents 70 about its periphery. The detents 70 are engaged by a ball 72 that is held by a spring 74. Spring 74 in turn is secured by a threaded plug 76 which may be screwed into a bore 78 provided along the length of the arms 64 and 65. Accordingly, each tool will click into position as it is swiveled about the pivot pin 68 to a point where the ball 72 will engage one of the detents 70 provided on the pivot pin 68. As will be appreciated, the embodiment of Figure 9 therefore has the added advantage that any tool provided on the chained tool set can be moved to a working position rather than having to move the particular tool to the end of the chain as in the case of the embodiments previously described. Thus, for example, screwdriver 62a could also be swiveled about the pivot pin 68 to the same position shown by allen wrench 62c so that either tool could be used without having to move the screwdriver 62a to the end of the chain.

In the embodiment of Figure 11, each tool link 60 is essentially the same as the tool links described in Figures 9 and 10 except that in the embodiment of Figure 11 the arms 86 and 88 to which the working tips 62 are secured are mounted to the tool link by means of screws 90. As shown in Figure 11, the arms 86 and 88 between which the base 66 of the tool is pivotally secured by pin 68 are formed as part of a c-shaped member 82. Member 82 is provided with holes 84 through which the screws 90 engage threaded holes 92 provided on the side members 24 and 25 of the tool link. This embodiment thus provides an alternative arrangement which permits different types of tools to be quickly and easily changed on the chain.

From the foregoing, it should be appreciated that the present invention thus provides a versatile tool set comprised of tool links connected together to form a chain which provides in a single hand piece a plurality of tools which can be changed in rapid succession from one tool to the other. The chained tool set of the present invention is compact and versatile in that the various tools can be replaced and/or additional tools can be added to the chain, and is convenient since there are no loose parts in the tool set which can be lost or misplaced. In use, any tool can be selected and used without the need for removing, reconnecting or replacing parts on the hand piece. Selected combinations of tools may be attached to the chain for purposes of providing specific tool sets for any given application which requires a combination of tools.

The invention which is defined in claim 1 may be embodied in other specific forms. The described embodiments are to be considered in all respects only as illustrative and not restrictive.

Claims

1. A tool set comprising a plurality of at least three tools (22), each tool of said plurality of tools having a working section (28) and an associated linking means (24, 25) for linking that tool to one or to two adjacent tools, the tool set further comprising connecting means (32, 34) for connecting said link-

ing means such that each end of each linking means is pivotally connected to not more than one adjacent linking means, so as to form a chained tool set capable of being manipulated so that any selected one of the tools is available for use on a workpiece while the remaining tools are incorporated in a handle for the selected tool characterised in that each working section is a working tip connected to a side of its associated linking means so that each working tip is or can be arranged in a first plane parallel to, and laterally offset from, the plane of its associated linking means and each working tip is or can be further arranged so that it extends in said first plane beyond an end of its associated linking means, and in that said linking means and connecting means are such as to allow all adjacent linking means to be folded to form a substantially rigid handle incorporating all the linking means arranged in two parallel rows, with at least one working tip extending from the handle, so as to be operable on a workpiece.

2. A tool set as claimed in claim 1 wherein each tool further comprises a shank (26) attached to said working tip (28), the shank of each tool being adapted to interlock with the working tip of an adjacent tool when said chained tool set is folded to form the handle.

3. A tool set as claimed in claim 1 or claim 2 wherein each working tip (28) is the same type of working tip and differs from the other working tips only in size.

4. A tool set as claimed in claim 1 or claim 2 wherein said tools comprise a plurality of different types of working tips (62) for performing different tasks.

5. A tool set as claimed in any one of the preceding claims wherein each linking means comprises a tool link comprising first and second side members (24, 25) spaced one from the other at the ends thereof and substantially parallel one with the other.

6. A tool set as claimed in claim 5 wherein each said tool link (24, 25) is integrally joined to an associated one of said working tips (28).

7. A tool set as claimed in claim 5 and including pivot means (64 to 68) for pivotally mounting at least one of said working tips to the tool link associated therewith.

8. A tool set as claimed in claim 7 wherein said pivot means comprises a pair of arms (64, 65) extending from said side members (24, 25) and a pivot pin (68), extending between said arms, said pivotally mounted working tips (62) each comprising a base (66) mounted on said pivot pin.

9. A tool set as claimed in claim 7 wherein said pivot means comprises a bracket (80) comprising two arms (86, 88) and a pin (68) extending between said arms, each said pivotally mounted working tip (62) comprising a base (66) which is mounted on said pin, said bracket further comprising means (90, 92) for mounting said bracket to the tool link associated with the respective working tip.

10. A tool set as claimed in claim 8 or claim 9 and including means (70 to 78) for retaining said pivot pin in one of a plurality of positions as said working tip is rotated with said pivot pin.

11. A tool set as claimed in claim 10 wherein said means for securing said position of said pivot pin as

is provided with a plurality of detents 70 about its periphery. The detents 70 are engaged by a ball 72 that is held by a spring 74. Spring 74 in turn is secured by a threaded plug 76 which may be screwed into a bore 78 provided along the length of the arms 64 and 65. Accordingly, each tool will click into position as it is swiveled about the pivot pin 68 to a point where the ball 72 will engage one of the detents 70 provided on the pivot pin 68. As will be appreciated, the embodiment of Figure 9 therefore has the added advantage that any tool provided on the chained tool set can be moved to a working position rather than having to move the particular tool to the end of the chain as in the case of the embodiments previously described. Thus, for example, screwdriver 62a could also be swiveled about the pivot pin 68 to the same position shown by allen wrench 62c so that either tool could be used without having to move the screwdriver 62a to the end of the chain.

In the embodiment of Figure 11, each tool link 60 is essentially the same as the tool links described in Figures 9 and 10 except that in the embodiment of Figure 11 the arms 86 and 88 to which the working tips 62 are secured are mounted to the tool link by means of screws 90. As shown in Figure 11, the arms 86 and 88 between which the base 66 of the tool is pivotally secured by pin 68 are formed as part of a c-shaped member 82. Member 82 is provided with holes 84 through which the screws 90 engage threaded holes 92 provided on the side members 24 and 25 of the tool link. This embodiment thus provides an alternative arrangement which permits different types of tools to be quickly and easily changed on the chain.

From the foregoing, it should be appreciated that the present invention thus provides a versatile tool set comprised of tool links connected together to form a chain which provides in a single hand piece a plurality of tools which can be changed in rapid succession from one tool to the other. The chained tool set of the present invention is compact and versatile in that the various tools can be replaced and/or additional tools can be added to the chain, and is convenient since there are no loose parts in the tool set which can be lost or misplaced. In use, any tool can be selected and used without the need for removing, reconnecting or replacing parts on the hand piece. Selected combinations of tools may be attached to the chain for purposes of providing specific tool sets for any given application which requires a combination of tools.

The invention which is defined in claim 1 may be embodied in other specific forms. The described embodiments are to be considered in all respects only as illustrative and not restrictive.

Claims

1. A tool set comprising a plurality of at least three tools (22), each tool of said plurality of tools having a working section (28) and an associated linking means (24, 25) for linking that tool to one or to two adjacent tools, the tool set further comprising connecting means (32, 34) for connecting said link-

ing means such that each end of each linking means is pivotally connected to not more than one adjacent linking means, so as to form a chained tool set capable of being manipulated so that any selected one of the tools is available for use on a workpiece while the remaining tools are incorporated in a handle for the selected tool characterised in that each working section is a working tip connected to a side of its associated linking means so that each working tip is or can be arranged in a first plane parallel to, and laterally offset from, the plane of its associated linking means and each working tip is or can be further arranged so that it extends in said first plane beyond an end of its associated linking means, and in that said linking means and connecting means are such as to allow all adjacent linking means to be folded to form a substantially rigid handle incorporating all the linking means arranged in two parallel rows, with at least one working tip extending from the handle, so as to be operable on a workpiece.

2. A tool set as claimed in claim 1 wherein each tool further comprises a shank (26) attached to said working tip (28), the shank of each tool being adapted to interlock with the working tip of an adjacent tool when said chained tool set is folded to form the handle.

3. A tool set as claimed in claim 1 or claim 2 wherein each working tip (28) is the same type of working tip and differs from the other working tips only in size.

4. A tool set as claimed in claim 1 or claim 2 wherein said tools comprise a plurality of different types of working tips (62) for performing different tasks.

5. A tool set as claimed in any one of the preceding claims wherein each linking means comprises a tool link comprising first and second side members (24, 25) spaced one from the other at the ends thereof and substantially parallel one with the other.

6. A tool set as claimed in claim 5 wherein each said tool link (24, 25) is integrally joined to an associated one of said working tips (28).

7. A tool set as claimed in claim 5 and including pivot means (64 to 68) for pivotally mounting at least one of said working tips to the tool link associated therewith.

8. A tool set as claimed in claim 7 wherein said pivot means comprises a pair of arms (64, 65) extending from said side members (24, 25) and a pivot pin (68), extending between said arms, said pivotally mounted working tips (62) each comprising a base (66) mounted on said pivot pin.

9. A tool set as claimed in claim 7 wherein said pivot means comprises a bracket (80) comprising two arms (86, 88) and a pin (68) extending between said arms, each said pivotally mounted working tip (62) comprising a base (66) which is mounted on said pin, said bracket further comprising means (90, 92) for mounting said bracket to the tool link associated with the respective working tip.

10. A tool set as claimed in claim 8 or claim 9 and including means (70 to 78) for retaining said pivot pin in one of a plurality of positions as said working tip is rotated with said pivot pin.

11. A tool set as claimed in claim 10 wherein said means for securing said position of said pivot pin as



said working tip is rotated comprises a ball (72) adapted to engage one of a plurality of detents (70) formed on said pivot pin (68), said ball being secured by a spring (74) mounted in a bore (78) formed in at least one of said arms, said spring being secured in said bore by a plug member (76).

12. A tool set as defined in any one of claims 5 to 11 wherein said connecting means comprises a plurality of connecting links (32) each secured at opposite ends thereof between said side members (24, 25) by a connecting pin (34) extending between said side members and through said connecting link.

13. A tool set as claimed in claim 12 and including means (29 or 31) for releasably securing at least some of said connecting pins so that at least some of said tool links can be disconnected from said chain.

14. A tool set as claimed in claim 13 wherein said means for releasably securing said connecting pins comprises a threaded end (29) provided on one or more of said connecting pins so that said connecting pins with said threaded ends can be screwed into or out of a, corresponding threaded bore in one of said side members of said tool links.

15. A tool set as claimed in claim 13 wherein said means for releasably securing said connecting pins comprises a notch (31) formed on one or more of said connecting pins, a slot (33) formed on a corresponding connecting link and a spring clip (37) for engaging said notch through said slot.

16. A tool set as claimed in any one of claims 5 to 15 wherein each said tool link comprises a support member (41) integrally joined between said first and second side members (24, 25) each support member having a slot (44) formed in a face thereof, and every alternate one of said tool links includes means (52) for engaging one of said slots when said tool links are folded to form two parallel rows of linking means.

17. A tool set as claimed in claim 16 wherein said means for engaging said slot comprises a key (52) secured in the slot of every alternate tool link.

18. A tool set as claimed in any one of the preceding claims wherein said linking means (24, 25) are connected by said connecting means (32, 34) to form an endless loop.

Patentansprüche

1. Werkzeug-Gerätesatz bestehend aus mindestens drei Einzelwerkzeugen (22) mit jeweils einem Arbeits-Abschnitt (28) und zugehörigem Verbindungsglied (24, 25) zur Verbindung jedes Einzelwerkzeugs mit einem oder zwei benachbarten Einzelwerkzeugen, mit Zwischenstücken (32, 34) zur drehbeweglichen Verbindung der Enden der Verbindungsglieder mit nur jeweils einem benachbarten Verbindungsglied zwecks Bildung eines kettengliedartigen Gerätesatzes, von dem jeweils ein bestimmtes Einzelwerkzeug für den Einsatz an einem Werkstück anwählbar ist, während die übrigen Einzelwerkzeuge zu einem Griff des ausgewählten Werkzeuges zusammengefaßt sind, dadurch ge-

kennzeichnet, daß jeder Arbeits-Abschnitt einen Werkzeugkopf bildet und mit einer Seite des zugehörigen Verbindungsgliedes derart verbunden ist, daß jeder Werkzeugkopf in einer ersten Ebene angeordnet ist oder angeordnet werden kann und radial in Bezug auf diese Ebene seines zugehörigen Verbindungsgliedes parallel versetzt ist, daß jeder Werkzeugkopf weiterhin derart angeordnet ist oder angeordnet werden kann, daß er sich in der ersten Ebene über ein Ende seines zugehörigen Verbindungsgliedes hinaus erstreckt, und daß die Anordnung zwischen Verbindungsgliedern und Zwischenstücken ein Zusammenfallen aller benachbarten Verbindungsglieder zu einem im wesentlichen starren alle Verbindungsglieder in zwei parallel zueinander liegenden Reihen enthaltenden Griffes ermöglicht, wobei mindestens ein Werkzeugkopf über den Griff zum Ansetzen an einem Werkstück übersteht.

2. Werkzeug-Gerätesatz nach Anspruch 1, dadurch gekennzeichnet, daß jedes Einzelwerkzeug aus einem mit dem Werkzeugkopf (28) verbundenen Schaft (26) besteht, der mit dem Werkzeugkopf eines benachbarten Einzelwerkzeugs beim Zusammenlegen der Verbindungsglieder zu einem Griff koppelbar ist.

3. Werkzeug-Gerätesatz nach Anspruch 1 oder 2, dadurch gekennzeichnet, daß die Werkzeugköpfe (28) jeweils gleichartig, aber von unterschiedlicher Größe sind.

4. Werkzeug-Gerätesatz nach Anspruch 1 oder 2, gekennzeichnet durch mehrere Werkzeugköpfe (62) unterschiedlichen Typs zur Durchführung unterschiedlicher Arbeiten.

5. Werkzeug-Gerätesatz nach einem der vorhergehenden Ansprüche, dadurch gekennzeichnet, daß jedes Verbindungsglied eine aus einem ersten und zweiten seitlichen Laschenglied (24, 25) bestehende Werkzeugverbindung ist, deren Laschenglieder mit ihren Enden im Abstand voneinander und im wesentlichen parallel zueinander liegen.

6. Werkzeug-Gerätesatz nach Anspruch 5, dadurch gekennzeichnet, daß jedes Verbindungsglied (24, 25) mit dem zugeordneten Werkzeugkopf einstückig verbunden ist.

7. Werkzeug-Gerätesatz nach Anspruch 5, gekennzeichnet durch eine Drehverbindung (64-68) zur drehbeweglichen Anordnung mindestens eines der Werkzeugköpfe an dem zugehörigen Verbindungsglied.

8. Werkzeug-Gerätesatz nach Anspruch 7, dadurch gekennzeichnet, daß die Drehverbindung aus zwei Flanschen (64, 65) besteht, die zwischen den beiden seitlichen Laschengliedern (24, 25) liegen und über einen Drehzapfen (68) verbunden sind, wobei jeder drehbar angeordnete Werkzeugkopf jeweils einen auf dem Drehzapfen angeordneten Basiskörper (66) aufweist.

9. Werkzeug-Gerätesatz nach Anspruch 7, dadurch gekennzeichnet, daß die Drehverbindung einen Steg (80) mit zwei Flanschen (86, 88) und einen Stift (68) beinhaltet, der beide Flansche durchsetzt und daß jeder drehbeweglich angeordnete Werkzeugkopf (62) einen am Drehzapfen angeordneten Basiskörper (66) aufweist, daß der Steg ferner Mittel (90, 92) zur Befestigung des Stegs an dem einem



bestimmten Werkzeugkopf zugehörnden Verbindungsmitglied aufweist.

10. Werkzeug-Gerätesatz nach den Ansprüchen 8 oder 9, gekennzeichnet durch Mittel (70-78) zur Festlegung des Drehzapfens in einer von mehreren Positionen bei Verdrehung des Werkzeugkopfes mit dem Drehzapfen.

11. Werkzeug-Gerätesatz nach Anspruch 10, gekennzeichnet durch Mittel zur Festlegung des Drehzapfens bei Verdrehung des Werkzeugkopfes, bestehend aus einer in eine von einer Vielzahl von Kerben im Drehzapfen einrastbaren Kugel (72), die durch eine Feder (74) in einer Bohrung (78) in mindestens einem der Flansche beaufschlagt ist, wobei die Feder in der Bohrung durch einen Stopfen (76) gehalten ist.

12. Werkzeug-Gerätesatz nach einem der Ansprüche 5 bis 11, dadurch gekennzeichnet, daß das Zwischenstück aus einer Vielzahl von Verbindungsstücken (32) besteht, von denen jedes an einander gegenüberliegenden Enden zwischen den seitlichen Laschengliedern (24, 25) über einen Verbindungsstift (34) befestigt ist, der die seitlichen Laschenglieder und das Zwischenstück durchsetzt.

13. Werkzeug-Gerätesatz nach Anspruch 12, gekennzeichnet durch Mittel (29 oder 31) zur lösbaren Befestigung von mindestens einigen der Verbindungsstifte derart, daß mindestens einige der Werkzeugglieder von dem Werkzeug-Gerätesatz lösbar sind.

14. Werkzeug-Gerätesatz nach Anspruch 13, dadurch gekennzeichnet, daß das Mittel zur lösbaren Befestigung der Verbindungsstifte jeweils ein Gewindeende (29) an einem oder an mehreren der Verbindungsstifte ist, und daß eine Schraubverbindung der Stifte mit einer jeweils entsprechenden Gewindebohrung in einem der seitlichen Laschenglieder die Werkzeugverbindungen ermöglicht.

15. Werkzeug-Gerätesatz nach Anspruch 13, dadurch gekennzeichnet, daß das Mittel zur lösbaren Befestigung der Verbindungsstifte eine in einem oder in mehreren der Verbindungsstifte angeordnete Kerbe (31) ist, der oder denen ein Schlitz (33) in dem korrespondierenden Zwischenstück und ein Federring (37) zum Einrasten in die Kerbe durch den Schlitz zugeordnet ist.

16. Werkzeug-Gerätesatz nach einem der Ansprüche 5 bis 15, dadurch gekennzeichnet, daß jedes Verbindungsmitglied ein zwischen dem ersten und zweiten seitlichen Laschenglied angeformtes Basisstück (41) aufweist, das jeweils in einer Fläche eine Nut (44) aufweist und daß jede zweite Werkzeugverbindung ein Mittel (52) aufweist, das in einen der Nuten beim Zusammenlegen der Verbindungsmitglieder zur Bildung der zwei parallelen Reihen eingreift.

17. Werkzeug-Gerätesatz nach Anspruch 16, dadurch gekennzeichnet, daß die in die Nut eingreifenden Mittel eine in der Nut jedes benachbarten Verbindungsmitglied befestigte Federzapfen (52) besteht.

18. Werkzeug-Gerätesatz nach einem der vorhergehenden Ansprüche, dadurch gekennzeichnet, daß die Verbindungsmitglieder (24, 25) mit den Zwischenstücken (32, 34) eine Endlosschleife bilden.

Revendications

1. Jeu d'outils comprenant une pluralité d'au moins trois outils (22), chaque outil de ladite pluralité d'outils comprenant un élément de travail (28) et un élément de liaison associé (24, 25) pour relier cet outil à un ou deux outils adjacents, le jeu d'outils comprenant en outre des moyens de connexion (32, 34) pour connecter lesdits éléments de liaison de sorte que chaque extrémité de chaque élément de liaison est connectée de façon pivotante à au plus un élément de liaison adjacent, de manière à constituer un jeu d'outils en chaîne pouvant être manipulé de sorte qu'un outil choisi quelconque est disponible pour l'utilisation sur une pièce à traiter tandis que les outils restants sont associés en une poignée pour l'outil choisi, caractérisé en ce que chaque élément de travail est un embout de travail relié à un côté de son élément de liaison associé de sorte que chaque embout de travail est ou peut être disposé dans un premier plan parallèle au plan de son élément de liaison associé, et latéralement décalé de celui-ci, et chaque embout de travail est ou peut être en outre disposé de sorte qu'il s'étend dans ledit premier plan au-delà d'une extrémité de son élément de liaison associé, et en ce que lesdits éléments de liaison et les moyens de connexion sont tels qu'ils permettent de replier tous les éléments de liaison adjacents pour constituer une poignée sensiblement rigide incorporant tous les éléments de liaison agencés en deux rangées parallèles, au moins un embout de travail faisant saillie par rapport à la poignée de façon à pouvoir agir sur une pièce à traiter.

2. Jeu d'outils suivant la revendication 1, dans lequel chaque outil comprend en outre une queue (26) attachée audit embout de travail (28), la queue de chaque outil étant prévue pour se verrouiller avec l'embout de travail d'un outil adjacent lorsque ledit jeu d'outils en chaîne est replié pour former la poignée.

3. Jeu d'outils suivant la revendication 1 ou la revendication 2, dans lequel chaque embout de travail (28) est du même type d'embout de travail et diffère des autres embouts de travail seulement en dimension.

4. Jeu d'outils suivant la revendication 1 ou la revendication 2, dans lequel lesdits outils comprennent une pluralité de différents types d'embouts de travail (62) pour effectuer des travaux différents.

5. Jeu d'outils suivant l'une quelconque des revendications précédentes, dans lequel chaque élément de liaison comprend un élément d'outil comportant une première et une deuxième parties latérales (24, 25) espacées l'une de l'autre à leurs extrémités et sensiblement parallèles l'une à l'autre.

6. Jeu d'outils suivant la revendication 5, dans lequel chaque dit élément de liaison d'outil (24, 25) est d'une pièce avec un embout associé parmi lesdits embouts de travail (28).

7. Jeu d'outils suivant la revendication 5 comportant des moyens d'articulation (64 à 68) pour monter de façon pivotante au moins l'un desdits embouts de travail sur l'élément de liaison d'outil qui lui est associé.



8. Jeu d'outils suivant la revendication 7, dans lequel lesdits moyens d'articulation comprennent deux bras (64, 65) s'étendant à partir desdites parties latérales (24, 25) et un axe de pivot (68) s'étendant entre lesdits bras, lesdits embouts de travail montés de façon pivotante (62) comprenant chacun une base (66) montée sur ledit axe de pivot.

9. Jeu d'outils suivant la revendication 7, dans lequel lesdits moyens d'articulation comprennent un support (80) comportant deux bras (86, 88) et un axe (68) s'étendant entre lesdits bras, chaque dit embout de travail monté de façon pivotante (62) comportant une base (66) qui est montée sur ledit axe, ledit support comprenant en outre des moyens (90, 92) pour monter ledit support sur l'élément de liaison d'outil associé à l'embout de travail respectif.

10. Jeu d'outils suivant la revendication 8 ou la revendication 9 comprenant des moyens (70 à 78) de retenue dudit axe de pivot dans l'une d'une pluralité de positions lorsque ledit embout de travail tourne avec ledit axe de pivot.

11. Jeu d'outils suivant la revendication 10, dans lequel lesdits moyens de retenue de ladite position dudit axe de pivot lorsqu'on fait tourner ledit embout de travail comprennent une bille (72) qui peut s'engager dans l'un d'une pluralité de crans (70) formés sur ledit axe de pivot (68), ladite bille étant retenue par un ressort (74) monté dans un trou (78) ménagé dans au moins un desdits bras, ledit ressort étant retenu dans ledit trou par un bouchon (76).

12. Jeu d'outils suivant l'une quelconque des revendications 5 à 11, dans lequel lesdits moyens de connexion comprennent une pluralité de maillons de connexion (32) fixés chacun, à leurs extrémités opposées, entre lesdites parties latérales (24, 25) par un axe de connexion (34) s'étendant entre lesdites parties latérales et à travers ledit maillon de connexion.

13. Jeu d'outils suivant la revendication 12, comprenant des moyens (29 ou 31) pour fixer de façon libérable au moins certains desdits axes de connexion, de sorte qu'au moins certains desdits éléments d'outil peuvent être démontés de ladite chaîne.

14. Jeu d'outils suivant la revendication 13, dans lequel lesdits moyens de fixation libérable desdits axes de connexion comprennent une extrémité filetée (29) prévue sur un ou plusieurs desdits axes de connexion de sorte que lesdits axes de connexion à dites extrémités filetées peuvent être vissés, ou dévissés, dans un trou taraudé correspondant prévu dans l'une desdites parties latérales desdits éléments de liaison d'outil.

15. Jeu d'outils suivant la revendication 13, dans lequel lesdits moyens de fixation libérable desdits axes de connexion comprennent une gorge (31) ménagée sur un ou plusieurs desdits axes de connexion, une rainure (33) prévue dans un maillon de connexion correspondant, et une pince élastique (35) pour venir en prise dans ladite gorge à travers ladite rainure.

16. Jeu d'outils suivant l'une quelconque des revendications 5 à 15, dans lequel chaque dit élément de liaison d'outil comprend un support (41) relié solidement entre lesdites première et deuxième par-

ties latérales (24, 25), chaque support comportant une rainure (44) formée dans une des faces de support, et un sur deux desdits éléments de liaison d'outil comprend des moyens (52) pour venir en prise avec l'une desdites rainures lorsque lesdits éléments de liaison d'outil sont repliés pour former deux rangées parallèles d'éléments de liaison.

17. Jeu d'outils suivant la revendication 16, dans lequel lesdits moyens venant en prise avec ladite rainure comprennent une clavette (52) fixée dans la rainure d'un sur deux des éléments de liaison d'outil.

18. Jeu d'outils suivant l'une quelconque des revendications précédentes, dans lequel lesdits éléments de liaison (24, 25) sont connectés par lesdits moyens de connexion (32, 34) pour former une boucle sans fin.



* C L N S *