

Description

The present invention relates to a syringe. More particularly, it relates to a syringe such as a dentist's syringe having good handling properties which can readily apply a medicament to a diseased part with minimum loss of the medicament.

Hitherto, a syringe for applying a medicament to a limited diseased part such as that in the oral cavity has been known (see, for example, Japanese Design Publication Nos. 464190 and 681235). Such a syringe comprises a barrel fitted with a plunger and a nozzle. Usually, a barrel has a hollow cylindrical portion and a tubular portion which is thinner than the cylindrical portion and connected to one end of the cylindrical portion. The other end of the cylindrical portion is an open end and has a flange. The cylindrical portion may be slightly tapered from its open end to the tubular portion and the tubular portion is connected to the nozzle. The plunger has a gasket on one end of its piston rod to be pushed in the barrel through its open end. The outer diameter of the gasket is substantially the same as the inner diameter of the cylindrical portion. The other end of the plunger is pushed to insert the plunger into the barrel. A medicament is filled in the barrel and, when it is applied to the diseased part, the plunger is fully inserted into the barrel to push out the medicament through the nozzle toward the diseased part. The plunger has a shoulder portion formed on an appropriate position of the side wall of the plunger and, as the plunger is inserted into the barrel, the shoulder portion is brought into contact with the flange of the cylindrical portion to limit the insertion.

And, in order to fill a medicament having high viscosity into the barrel, it is filled through the open end of the barrel with a filler nozzle, while the barrel is set upright so that the open end is at the top thereof because it is difficult to suck the medicament into the barrel through the nozzle of the syringe. In this case, the filler nozzle tip is firstly located in the bottom of the barrel and then the filler nozzle is moved toward the open end, while filling of the medicament is continued with preventing inclusion of air. The medicament is filled up to the level of the flange of the cylindrical portion. This filling manner is necessary to prevent inclusion of air between the gasket and the medicament when the plunger is pushed into the barrel.

However, in this case, since the medicament is filled up to the level of the flange of the cylindrical portion, the medicament is overflowed from the barrel when the plunger is pushed in the barrel to smear the flange and thereabout. Further, it is necessary that the plunger moves a certain distance toward the inside of the barrel to make the plunger in a self-supporting state prior to the use of

the syringe for application of the medicament. In this case, a volume of the medicament corresponding to the movement of the gasket in the barrel is pushed out through the nozzle and discarded without utilizing it. This is uneconomic and, even if it can be recovered, it is very difficult to return it to the filler with maintaining an aseptic state.

Further, in the case of a dentist's syringe, the diseased part is located in the inner part of the oral cavity and therefore the barrel should have a certain length so that the nozzle reaches to the diseased part. Naturally, this rules the length of the plunger which is inserted into the barrel. That is, the plunger should also have a corresponding length. However, from the viewpoint of handling properties, it is preferred that the plunger has a relatively shorter length, and the requirement for making the plunger shorter is inconsistent with the requirement for making the barrel as long as possible. It has been requested to solve this inconsistent matter. And, even when the barrel is longer, the medicament should be also filled up to the level of the flange of the cylindrical portion to prevent inclusion of air, which makes the volume of the medicament to be filled much larger in comparison with that required for actual application. The excess amount of the medicament is discarded without utilization. This is uneconomic and, particularly, in the case that a syringe in which a medicament has been already filled is marketed, the excess amount of the medicament reflects the increase in the production cost of the syringe.

One object of the present invention is to provide an improved syringe, particularly, a dentist's syringe in which a medicament even having high viscosity can be readily filled.

Another object of the present invention is to provide an improved syringe having good handling properties which can readily apply a medicament to a diseased part with minimum loss of the medicament.

Still another object of the present invention is to provide a medicament containing improved syringe which can be marketed as it is.

These objects as well as other objects and advantages of the present invention are achieved by the features of the claims and will become apparent to those skilled in the art from the following description with reference to the accompanying drawings.

Figures 1 (A) and (B) illustrate a preferred embodiment of the syringe of the present invention. Figure 1 (A) is a longitudinal section of the plunger.

Figure 1(B) is a longitudinal cross section of a barrel of a preferred embodiment of the syringe of the present invention.

Figure 2 is a longitudinal section of both plung-

er and barrel of a known syringe.

In order to fill a medicament having high viscosity in the syringe of the present invention, the medicament is filled through the open end of the barrel with a filler nozzle, while the barrel is set upright so that the open end is at the top thereof. The filler nozzle tip is firstly located at the bottom of the barrel and then the filler nozzle is moved toward the open end, while filling of the medicament is continued with preventing inclusion of air. The medicament is filled up to the level about the enlarged diameter part at the cylindrical portion adjacent to the open end (hereinafter merely referred to as open end part). Then, one end of the plunger is pushed into the barrel through the open end to bring contact with the top surface of the medicament and further the plunger is pushed a certain distance into the barrel to complete filling of the medicament.

When the plunger is pushed into the barrel, air present between the end of the plunger and the top surface of the medicament vents through the enlarged diameter part to prevent inclusion of air. Further, the medicament overflowed by pushing the plunger into the barrel is kept in the enlarged diameter part to prevent smearing the flange. Furthermore, since the plunger can be inserted into the barrel beyond the enlarged diameter part from the beginning, the length of the plunger outside the barrel can be made shorter in comparison with a known syringe, while maintaining a desired length of the barrel. This improves handling properties of the syringe. In addition, the amount of the medicament to be filled in the barrel can be controlled by adjusting the size and the length of the enlarged diameter part without change of the length of the barrel, which saves the production cost of the medicament containing syringe.

The shape and material of the syringe of the present invention are not limited to specific ones. They may be the same as those of a known syringe.

Further, a medicament to be filled in the syringe of the present invention is not limited to a specific one but, a paste composition having high viscosity is preferred in view of handling properties of the syringe of the present invention. Particularly, in the case of a dentist's syringe, it is preferred to use the aqueous minocycline paste as disclosed in EP-A-0 184 389 which comprises minocycline or a pharmaceutically acceptable salt thereof and a base composed of a polyhydric alcohol containing a magnesium compound.

Now referring to the drawings, the present invention is further illustrated in detail.

As shown in Figure 2, a known syringe comprises a barrel (a) fitted with a plunger (b) and a nozzle (f). Usually, the barrel has a hollow cylin-

drical portion (c) and a tubular portion (e) which is thinner than the cylindrical portion and connected to one end of the cylindrical portion. The other end of the cylindrical portion is an open end and has a flange (d). The tubular portion is connected to the nozzle. The plunger has a gasket (h) on one end of its piston rod (g) to be pushed in the barrel through its open end. The outer diameter of the gasket is about the same as the inner diameter of the cylindrical portion. The other end of the plunger is pushed to insert the plunger into the barrel. A medicament (j) is filled in the barrel and, when it is applied to a diseased part, the plunger is inserted into the barrel to push out the medicament through the nozzle toward the diseased part. The plunger has a shoulder portion (i) formed on a appropriate position of the side wall of the plunger and, as the plunger is inserted into the barrel, the shoulder portion is brought into contact with the flange of the cylindrical portion to limit the insertion.

In this case, since the medicament (j) is filled up to the level of the flange (d) of the cylindrical portion (c), the medicament is overflowed from the barrel when the plunger is pushed in the barrel to smear the flange and thereabout. Further, although it is necessary to move the plunger a certain distance toward the inside of the barrel to make the plunger in a self-supporting state prior to use, a certain volume of the medicament corresponding to movement of the gasket in the barrel is pushed out through the nozzle and discarded without utilization. This is uneconomic and, even if it can be recovered, it is very difficult to return it to the filler with maintaining an aseptic state.

On the other hand the syringe of the present invention has the enlarged diameter part at the open end part of the barrel to solve these problems.

Figures 1 (A) and (B) show a preferred embodiment of the syringe of the present invention. This syringe comprises the barrel 1, the plunger 2 and the bent nozzle 10. As seen from Figure 1 (B), the barrel comprises a hollow cylindrical portion 1 and a tubular portion 8 which is thinner than the cylindrical portion and connected to one end of the cylindrical portion via a shoulder part 9. The other end of said cylindrical portion is an open end 5 and has a flange 7. The nozzle is connected to the portion 8.

As well seen from Figure 1 (B), there is a longitudinally extending position 5 on the inside wall at the open end part of the cylindrical portion 3 which is served as the enlarged diameter part of the present invention to vent air present between the end of the plunger and the top surface of a medicament in the barrel. A medicament is filled in the part 3 of the cylindrical portion below the lower end of portion 5. The position of the lower end of

portion 5, that is, the length of the portion 5 is determined by the required amount of a medicament to be filled and, by varying the length of the portion 5, the amount of the medicament to be filled can be adjusted without changing the length of the barrel.

As seen from Figure 1 (A), the plunger 2 has a piston rod 11 and a gasket 12 provided on one end of the piston rod. The gasket 12 is made of an elastic material the outer diameter of which has substantially the same as the inner diameter of the cylindrical portion 3 of the barrel. The other end of the plunger has a flange 13 to facilitate insertion of the plunger. Further, the plunger has a shoulder portion 14 which is brought into contact with the flange 7 of the cylindrical portion to limit the insertion. The position of the shoulder portion 14 is chosen in such a manner that the length (L) of the piston rod is substantially the same as the length of the cylindrical portion 3 so that the end of the gasket 12 can reach to the bottom of the cylindrical portion 3.

Further, in order to improve mechanical strength of the wall about the portion 5, the outer surface of the wall corresponding to the portion 5 can be raised to form ribs.

Although Figure 1 (B) does not show, the barrel may have a notch on an appropriate part of the inside wall adjacent to the open end part to prevent slipping out of the plunger after insertion. In addition, the nozzle may be a hollow needle for applying a liquid medicament such as a disinfectant solution or other medicaments having relatively low viscosity.

In the case of a medicament having relatively high viscosity, the medicament is filled as described in the following.

That is, the medicament is filled through the open end of the barrel with a filler nozzle, while the barrel is set upright so that the open end is at the top thereof. In this case, the filler nozzle tip is firstly located at the bottom of the part 3 of the barrel and then the filler nozzle is moved toward the open end, while filling of the medicament is continued with preventing inclusion of air. The medicament is filled up to the level just above the beginning of portion 5. The medicament flows down into the nozzle 10 by its own weight but a little space remains at the tip of the nozzle 10 because the medicament has relatively high viscosity.

In this state, the plunger 2 is pushed into the barrel through the open end thereof to bring the gasket 12 contact with the top surface of the medicament. In this case, the air present between the gasket 12 and the top surface of the medicament is vented through portion 5 to facilitate pushing the plunger into the barrel. Further, since the medica-

ment is filled only up to the level just above the lower end of portion 5, the plunger 12 is pushed into the barrel without overflow of the medicament to prevent smearing of the flange 7. On the other hand, as the plunger 2 is pushed into the barrel, the medicament is pushed down to fill the space at the tip of the nozzle 10 and to remove the air in that space. Thus, the air in the barrel 1 is completely exhausted.

In the case of filling a medicament having much higher viscosity such as that in the form of a paste, a somewhat different filling manner is employed. That is, in this case, the filler nozzle tip is firstly located somewhat above the bottom of the part 3 and then the filler nozzle is moved toward the open end, while filling of the medicament is continued. The medicament 15 pushed out into the part 3 does not flow down due to high viscosity and a space containing air remains below the part 3. After filling, the plunger 2 is pushed to the top surface of the medicament to exhaust the air in the part 8 and the nozzle 10. According to this filling manner, it is possible to push down the top surface within a distance corresponding to the volume of the air remained below the part 3. Therefore, when a required amount of the medicament is small, that is, there is no need to fill the medicament within the part 3 entirely, such a manner further saves the amount of the medicament to be used. In addition, since air remains below the part 3, it is possible to push the plunger 2 a relatively larger distance into the barrel 1 to facilitate the control of pushing down of the plunger 2.

In Figure 1(B) the barrel 1 has the open end portion 5 which serves as the enlarged diameter part of the present invention. The inner diameter of the open end portion 5 is larger than that of the cylindrical portion 3, while the outer diameter of the former is the same as that of the latter.

After filling in the syringe of the present invention, the medicament can be immediately applied to a diseased part according to the same manner as in a known syringe, for example, by pushing the flange 13 of the plunger 2 with the thumb, while supporting the flange 7 with the forefinger and the middle finger. Alternatively, after filling the medicament in the syringe of the present invention, the medicament containing syringe can be marketed, for example, by closing the tip of the nozzle 10 with a cap or heat-sealing, subjecting the syringe to sterilization and then packing the syringe.

In the syringe of the present invention, by adjusting the size and the length of the enlarged diameter part, the length of the barrel can be appropriately determined regardless of the amount of the medicament to be filled. Therefore, for example, in the case of applying the medicament to a diseased part in the oral cavity, it is possible

to make the length of the barrel long to facilitate application of the medicament to the diseased part. Further, due to the presence of the enlarged diameter part, the length of the plunger outside the barrel can be made shorter without increase in the amount of the medicament to be discarded. This saves the amount of the medicament and improves handling properties of the syringe.

As described hereinabove, by providing the enlarged diameter part in which no medicament is filled to the open end part of the barrel according to the present invention, air present between the end of the plunger and the top surface of the medicament vents through it to prevent inclusion of air, which results in improvement of chemical stability of the medicament. Further, the medicament overflowed by pushing the plunger into the barrel is kept in the enlarged diameter part to prevent smearing the flange. Further, the amount of the medicament to be filled can be controlled by appropriately determining the size and length of the enlarged diameter part, which minimizes the loss of the medicament and saves the production cost. Furthermore, since the length of the barrel can be chosen regardless of the amount of the medicament, it can be determined mainly from the viewpoint of handling properties. In addition, the length of the plunger outside the barrel can make shorter by the length corresponding to that of the enlarged diameter part. This improves handling properties of the syringe.

Claims

1. A syringe, comprising:

- a) a barrel (1), said barrel (1) comprising:
 - a1) a first hollow cylindrical portion (3) having a first and a second end and an inner and an outer diameter;
 - a2) a second hollow cylindrical portion (5) having an inner and an outer diameter, the first end of said second hollow cylindrical portion (5) being connected to the first end of said first cylindrical portion (3) and said inner diameter of said second hollow cylindrical portion (5) being larger than the inner diameter of said first cylindrical portion (3);
 - a3) a tubular portion (8) of smaller diameter than said first cylindrical portion (3), said tubular portion (8) being connected to the second end of said first cylindrical portion (3);
- b) a nozzle (10) connected to said tubular portion (8); and
- c) a plunger (2) which is insertable into said first cylindrical portion (3);

characterized in that

- the outer diameter of the first hollow cylindrical portion (3) is the same as the outer diameter of the second hollow cylindrical portion (5), and
- the second end of said second hollow cylindrical portion (5) is an open end.

2. The syringe according to claim 1, characterized in that the syringe is a dentist's syringe.

Revendications

1. Seringue comprenant :

- a) un corps (1), ledit corps (1) comprenant :
 - a1) une première partie cylindrique creuse (3) possédant une première extrémité et une deuxième extrémité et un diamètre extérieur et un diamètre intérieur ;
 - a2) une deuxième partie cylindrique creuse (5) ayant un diamètre intérieur et un diamètre extérieur, la première extrémité de ladite deuxième partie cylindrique creuse (5) étant raccordée à la première extrémité de ladite première partie cylindrique (3) et ledit diamètre intérieur de ladite deuxième partie cylindrique creuse (5) étant plus grand que le diamètre intérieur de ladite première partie cylindrique (3) ;
 - a3) une partie tubulaire (8) de diamètre inférieur à celui de la première partie cylindrique (3), ladite partie tubulaire (8) étant raccordée à la deuxième extrémité de ladite première partie cylindrique (3) ;
- b) un embout (10) raccordé à ladite partie tubulaire (8) ; et
- c) un piston (2) qui peut être enfoncé dans ladite première partie cylindrique (3);

caractérisée en ce que

- le diamètre extérieur de la première partie cylindrique creuse (3) est égal au diamètre extérieur de la deuxième partie cylindrique creuse (5), et
- la deuxième extrémité de ladite deuxième partie cylindrique creuse (5) est une extrémité ouverte.

2. Seringue selon la revendication 1, caractérisée en ce que la seringue est une seringue de dentiste.

Patentansprüche

1. Spritze mit:

to make the length of the barrel long to facilitate application of the medicament to the diseased part. Further, due to the presence of the enlarged diameter part, the length of the plunger outside the barrel can be made shorter without increase in the amount of the medicament to be discarded. This saves the amount of the medicament and improves handling properties of the syringe.

As described hereinabove, by providing the enlarged diameter part in which no medicament is filled to the open end part of the barrel according to the present invention, air present between the end of the plunger and the top surface of the medicament vents through it to prevent inclusion of air, which results in improvement of chemical stability of the medicament. Further, the medicament overflowed by pushing the plunger into the barrel is kept in the enlarged diameter part to prevent smearing the flange. Further, the amount of the medicament to be filled can be controlled by appropriately determining the size and length of the enlarged diameter part, which minimizes the loss of the medicament and saves the production cost. Furthermore, since the length of the barrel can be chosen regardless of the amount of the medicament, it can be determined mainly from the viewpoint of handling properties. In addition, the length of the plunger outside the barrel can be made shorter by the length corresponding to that of the enlarged diameter part. This improves handling properties of the syringe.

Claims

1. A syringe, comprising:

- a) a barrel (1), said barrel (1) comprising:
 - a1) a first hollow cylindrical portion (3) having a first and a second end and an inner and an outer diameter;
 - a2) a second hollow cylindrical portion (5) having an inner and an outer diameter, the first end of said second hollow cylindrical portion (5) being connected to the first end of said first cylindrical portion (3) and said inner diameter of said second hollow cylindrical portion (5) being larger than the inner diameter of said first cylindrical portion (3);
 - a3) a tubular portion (8) of smaller diameter than said first cylindrical portion (3), said tubular portion (8) being connected to the second end of said first cylindrical portion (3);
- b) a nozzle (10) connected to said tubular portion (8); and
- c) a plunger (2) which is insertable into said first cylindrical portion (3);



characterized in that

- the outer diameter of the first hollow cylindrical portion (3) is the same as the outer diameter of the second hollow cylindrical portion (5), and
- the second end of said second hollow cylindrical portion (5) is an open end.

2. The syringe according to claim 1, characterized in that the syringe is a dentist's syringe.

Revendications

1. Seringue comprenant :

- a) un corps (1), ledit corps (1) comprenant :
 - a1) une première partie cylindrique creuse (3) possédant une première extrémité et une deuxième extrémité et un diamètre extérieur et un diamètre intérieur ;
 - a2) une deuxième partie cylindrique creuse (5) ayant un diamètre intérieur et un diamètre extérieur, la première extrémité de ladite deuxième partie cylindrique creuse (5) étant raccordée à la première extrémité de ladite première partie cylindrique (3) et ledit diamètre intérieur de ladite deuxième partie cylindrique creuse (5) étant plus grand que le diamètre intérieur de ladite première partie cylindrique (3) ;
 - a3) une partie tubulaire (8) de diamètre inférieur à celui de la première partie cylindrique (3), ladite partie tubulaire (8) étant raccordée à la deuxième extrémité de ladite première partie cylindrique (3) ;
- b) un embout (10) raccordé à ladite partie tubulaire (8) ; et
- c) un piston (2) qui peut être enfoncé dans ladite première partie cylindrique (3);

caractérisée en ce que

- le diamètre extérieur de la première partie cylindrique creuse (3) est égal au diamètre extérieur de la deuxième partie cylindrique creuse (5), et
- la deuxième extrémité de ladite deuxième partie cylindrique creuse (5) est une extrémité ouverte.

2. Seringue selon la revendication 1, caractérisée en ce que la seringue est une seringue de dentiste.

Patentansprüche

1. Spritze mit:

a) einem Hohlkörper (1), wobei der Hohlkörper (1) aufweist:

a1) einen ersten hohlzylindrischen Abschnitt (3) mit einem ersten und einem zweiten Ende und einem inneren und einem äußeren Durchmesser, 5

a2) einen zweiten hohlzylindrischen Abschnitt (5) mit einem inneren und einem äußeren Durchmesser, wobei das erste Ende des zweiten hohlzylindrischen Abschnitts (5) mit dem ersten Ende des ersten zylindrischen Abschnitts (3) verbunden ist und der innere Durchmesser des zweiten hohlzylindrischen Abschnitts (5) größer ist als der innere Durchmesser des ersten zylindrischen Abschnitts (3); 10 15

a3) einen rohrförmigen Abschnitt (8) mit kleinerem Durchmesser als der erste zylindrische Abschnitt (3), wobei der rohrförmige Abschnitt (8) mit dem zweiten Ende des ersten zylindrischen Abschnitts (3) verbunden ist, 20

b) einer mit dem rohrförmigen Abschnitt (8) verbundenen Düse (10), und

c) einem Kolben (2), der in den ersten zylindrischen Abschnitt (3) einführbar ist, 25

dadurch gekennzeichnet, daß

- der äußere Durchmesser des ersten hohlzylindrischen Abschnitts (3) dem äußeren Durchmesser des zweiten hohlzylindrischen Abschnitts (5) gleicht, und 30
- das zweite Ende des zweiten hohlzylindrischen Abschnitts (5) ein offenes Ende ist. 35

2. Spritze nach Anspruch 1, dadurch gekennzeichnet, daß die Spritze eine zahnmedizinische Spritze ist. 40

45

50

55

6

