FIG. 1



100
201
F
E
D
C
B
A
274
273
272
244
221
236
202
210
213
212
233
215
245a
245
211
217a
276
268
217c
240
234
250c
252c
253c
232c
250b
252b
253b
232b
243a
232
238
217
275
200
217b
239
266
250a
252a
253a
232a
237
235
223
203
214
231
242
243b
246

FIG. 2




FIG. 3



221
221a
CPU
221b
RAM
221c
Memory device
221d
I/O port
221e
223
External memory device
222
Input/output device
MFC
252a~252c
Valve
253a~253c, 243a, 243b
APC valve
242
Vacuum pump
246
High-frequency power supply
273
Matching device
274
Variable impedance mechanism
275
Heater power adjustment mechanism
276
Susceptor elevation mechanism
268

FIG. 4



Start
Substrate loading step
S110
Heating/vacuum-exhausting step
S120
Reaction gas supplying step
S130
Plasma processing step
S140
Vacuum-exhausting step
S150
Substrate unloading step
S160
End

FIG. 5A




FIG. 5B




FIG. 6

W grain size (nm)	(A) Reference	(B) 100%	(C) 80%	(D) 65%
Minimum value	4	8	9	9
Maximum value	18	25	46	47
Average value	10	15	19	21

FIG. 7




Sheet resistance value
(after process/before process(Initial)) [ratio]
1.6
1.4
1.2
1.0
0.8
0.6
0
20
40
60
80
100
Flow rate ratio H2/(H2+O2) [%]

FIG. 8


Sheet resistance value
(after process/before process(Initial)) [ratio]
1.6
1.4
1.2
1.0
0.8
0.6
0
20
40
60
80
100
Flow rate ratio H2/(H2+O2) [%]