



(51) International Patent Classification:

B01D 3/00 (2006.01) **C07C 15/00** (2006.01)
B01D 3/32 (2006.01) **B01D 1/28** (2006.01)
C07C 7/04 (2006.01)

(21) International Application Number:

PCT/IB2011/002388

(22) International Filing Date:

11 October 2011 (11.10.2011)

(25) Filing Language:

Italian

(26) Publication Language:

English

(30) Priority Data:

PI2010A000114 11 October 2010 (11.10.2010) IT

(71) Applicant (for all designated States except US): **SIME SRL** [IT/IT]; Via Caduti di Nassiriya, Località Le Morelline 2, I-57013 Rosignano Solva LI (IT).

(72) Inventors; and

(75) Inventors/Applicants (for US only): **FAVILLI, Stefano** [IT/IT]; Via Catalani, 44, I-57016 Rosignano Marittimo (IT). **SCIBOLA, Luciano** [IT/IT]; Via Crispi, 58, I-26013 Crema CR (IT).

(74) Agent: **CELESTINO, Marco**; ABM Agenzia Brevetti & Marchi, Viale Giovanni Pisano, 31, I-56123 Pisa (IT).


(81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AO, AT, AU, AZ, BA, BB, BG, BH, BR, BW, BY, BZ, CA, CH, CL, CN, CO, CR, CU, CZ, DE, DK, DM, DO, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, GT, HN, HR, HU, ID, IL, IN, IS, JP, KE, KG, KM, KN, KP, KR, KZ, LA, LC, LK, LR, LS, LT, LU, LY, MA, MD, ME, MG, MK, MN, MW, MX, MY, MZ, NA, NG, NI, NO, NZ, OM, PE, PG, PH, PL, PT, QA, RO, RS, RU, RW, SC, SD, SE, SG, SK, SL, SM, ST, SV, SY, TH, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, ZA, ZM, ZW.

(84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LR, LS, MW, MZ, NA, RW, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AL, AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HR, HU, IE, IS, IT, LT, LU, LV, MC, MK, MT, NL, NO, PL, PT, RO, RS, SE, SI, SK, SM, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Published:

— without international search report and to be republished upon receipt of that report (Rule 48.2(g))

(54) Title: PROCESS AND EQUIPMENT FOR SEPARATING 1,2,4 TRIMETHYLBENZENE (PSEUDOCUMENE) FROM A MIXTURE CONTAINING AROMATIC HYDROCARBONS



(57) Abstract: A method and an apparatus (7') for separating 1,2,4-Trimethylbenzene by fractional distillation of a mixture (31) that contains C9 or C9+ aromatic hydrocarbons, and possibly hydrocarbons with less than nine carbon atoms. According to an aspect of the invention, a first distillation step and a second distillation step are provided and are carried out in respective distillation chambers (75,75') defined by a cylindrical vertical container 501 and by an inner partition wall (85) of the container. According to another aspect of the invention, a means is provided for compressing (64) at least one part (65) of an overhead vapour fraction extracted from the first distillation chamber and/or from the second distillation chamber, in order to increase the condensation temperature of the overhead vapour above the boiling temperature of a bottom fraction (38,38') that is extracted from the first second distillation and/or from the second distillation chamber, and a condensation is also provided of the compressed overhead vapour (66) in the reboiler (70') associated to the first chamber and/or to the second chamber, so that the condensation latent heat provides the evaporation heat for a respective portion (39') of the bottom fraction. In a particular exemplary embodiment, the compression means (64) of the fraction (65) that is extracted from the first chamber is operated by an expansion means (764) for expanding an aeriform substance (761), and is used in the reboiler (70') associated with the second chamber (75'), and the apparatus (7') comprises a steam (764) generation means (71) that is associated with an externally heated reboiler (70) associated with the first distillation chamber (75). In another particular exemplary embodiment, at least one part (52) of the overhead vapour of the first chamber (75), which contains Pseudocumene, is fed to the second distillation chamber (75') through a passageway (86) that is defined within the inner partition wall (86).