

PCT

WORLD INTELLECTUAL PROPERTY ORGANIZATION
International Bureau



INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification 6 : H01R 13/518	A1	(11) International Publication Number: WO 99/63628 (43) International Publication Date: 9 December 1999 (09.12.99)
(21) International Application Number: PCT/US99/11120 (22) International Filing Date: 20 May 1999 (20.05.99) (30) Priority Data: 09/092,545 5 June 1998 (05.06.98) US (71) Applicant: ADC TELECOMMUNICATIONS, INC. [US/US]; 12501 Whitewater Drive, Minnetonka, MN 55343 (US). (72) Inventor: FOLLINGSTAD, Michael, Jay; 5825 York Avenue South, Edina, MN 55410 (US). (74) Agent: BRUESS, Steven, C.; Merchant & Gould P.C., 3100 Norwest Center, 90 South Seventh Street, Minneapolis, MN 55402-4131 (US).		(81) Designated States: AB, AL, AM, AT, AT (Utility model), AU, AZ, BA, BB, BG, BR, BY, CA, CH, CN, CU, CZ, CZ (Utility model), DE, DE (Utility model), DK, DK (Utility model), EE, EE (Utility model), ES, FI, FI (Utility model), GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SK (Utility model), SL, TJ, TM, TR, TT, UA, UG, UZ, VN, YU, ZA, ZW, ARIPO patent (GH, GM, KE, LS, MW, SD, SL, SZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GW, ML, MR, NE, SN, TD, TG). Published <i>With international search report. Before the expiration of the time limit for amending the claims and to be republished in the event of the receipt of amendments.</i>
(54) Title: TELECOMMUNICATIONS PATCH PANEL WITH ANGLED CONNECTOR MODULES AND METHOD OF ASSEMBLING SUCH A PANEL (57) Abstract A telecommunications patch panel is provided having a plurality of connector modules rotatably mounted to a frame member. Each connector module has a front face and an opposite facing rear face, and each front face includes a plurality of connector jacks. Each rear face includes a plurality of wire termination blocks. The wire termination blocks are electrically connected to the connector jacks. Each connector module is rotatable about a rotation axis relative to the frame member. A lock selectively locks each connector module to the frame member as desired. The connector jacks and the connector modules are arranged in linear arrays perpendicular to the axis of rotation.		