

DESCRIPTION

GAS TREATING DEVICE

TECHNICAL FIELD

5 The present invention relates to gas treating devices for the removal of dust, odors, and other matter in the air by causing discharge to take place.

BACKGROUND ART

 As one type of conventionally-known gas treating device, there is an air purifying
10 device for removing airborne dust, odors, and other matter by discharge. One such gas
treating device is disclosed in JP, 2001-218828, A. This air purifying device is provided
with a dust collecting filter and a plasma generating device. The plasma generating
device has a plasma generating electrode plate and a counter electrode plate. And, by
application of discharge voltage to both the electrode plates the streamer discharge takes
15 place, wherein a plasma is generated.

 In the above-described air purifying device, the dust collecting filter entraps and
collects dust in the air. In addition, in the plasma generating device, unpleasant odorous
components in the air are decomposed and removed by a substance of high reactivity (such
as an activated species) contained the plasma generated by the streamer discharge. And,
20 the clean air, after removal of such dust and unpleasant odorous components, is released to
outside the air purifying device as a stream of supply air.

PROBLEMS THAT THE INVENTION INTENDS TO SOLVE

 As described above, in the air purifying device disclosed in the patent gazette,
dust is removed by filtration with the aid of the dust collecting filter. On the other hand,
25 as a means for removing airborne dust, a so-called electrical dust collecting technique is

known. That is, there is a generally-known dust collecting method in which dust in the air is electrically charged by corona discharge and the electrically charged dust is collected by means of an electrostatic filter as an electrical dust collecting member. By the employment of such an electrical dust collecting method, it becomes possible to remove
5 dust of smaller size in comparison with the case where air is simply filtered by a dust collecting filter. The dust collecting capability of the air purifying device of the patent gazette may possibly be enhanced if it employs that electrical dust collecting technique.

In reality, if gas treating devices making utilization of plasmas for deodorization et cetera employ an electrical dust collection technique, this leads to the problems of
10 increasing the device size. In this regard, the description will be made. For the case where the electrical dust collecting technique is employed, discharge and counter electrodes for corona discharge to cause dust to be electrically charged have to be provided in an air passageway, in addition to the provision of discharge and counter electrodes for streamer discharge to generate a plasma. In other words, it is required that discharge and
15 counter electrodes be arranged in two sets. This requires an extra space for the installation of discharge and counter electrodes for causing dust to be electrically charged, therefore increasing the size of the gas treating device proportionally to that extra space.

With these problems in mind, the present invention was made. Accordingly, an object of the present invention is to accomplish downsizing of a gas treating device which
20 performs a so-called electrical dust collecting operation and decomposes odors and other matter by plasma.

DISCLOSURE OF THE INVENTION

A first invention is directed to a gas treating device for entrapping and collecting
25 dust present in a gas to be treated, and for decomposing a component to be treated present

in the gas to be treated. The gas treating device of the first invention comprises: a counter electrode (36); a first discharge electrode (35) for causing discharge to take place between the first discharge electrode (35) and the counter electrode (36) so that the dust in the gas to be treated is electrically charged; an electrical dust collecting member (33) for entrapping and collecting the electrically charged dust in the gas to be treated; and a second discharge electrode (41) for causing discharge to take place between the second discharge electrode (41) and the counter electrode (36) so that a plasma for decomposing the component to be treated is generated.

A second invention according to the gas treating device of the first invention is characterized in that the electrical dust collecting member (33) is formed by an electrostatic filter.

A third invention according to the gas treating device of the first invention is characterized in that a plasma catalyst is provided which is activated by a plasma generated by discharge between the second discharge electrode (41) and the counter electrode (36) and which promotes the decomposition of the component to be treated. Here, preferably the plasma catalyst has adsorption capability for the component to be treated present in the gas to be treated. More preferably, the plasma catalyst is capable of adsorption/decomposition of activated species such as ozone produced with the generation of the plasma.

A fourth invention according to the gas treating device of the first invention is characterized in that the first discharge electrode (35) is formed into a linear shape extending along the counter electrode (36) and that the second discharge electrode (41) is electrically connected to a position somewhere midway in the first discharge electrode (35), and is disposed such that the distance between the second discharge electrode (41) and the counter electrode (36) is shorter than the distance between the first discharge electrode (35)

and the counter electrode (36).

A fifth invention according to the gas treating device of the first invention is characterized in that the counter electrode (36) is shaped like a column having a cross section in the shape of a Japanese *katakana* character "コ", and that at least the second
5 discharge electrode (41) is disposed inside the counter electrode (36).

A sixth invention according to the gas treating device of the first invention is characterized in that an electrode member (37) which is shaped like a corrugated plate and which constitutes the counter electrode (36) is provided, that the first discharge electrode (35) is disposed on the side of one surface of the electrode member (37) and the second
10 discharge electrode (41) is disposed on the side of the other surface of the electrode member (37), and that the first discharge electrode (35) and the second discharge electrode (41) are disposed, respectively, inside concave portions of the corrugated plate-like electrode member (37).

A seventh invention according to the gas treating device of the first invention is
15 characterized in that a photosemiconductor catalyst is provided which is activated by a plasma generated by discharge between the second discharge electrode (41) and the counter electrode (36) and which promotes the decomposition of the component to be treated.

An eighth invention according to the gas treating device of the seventh invention
20 is characterized in that the photosemiconductor catalyst is supported on the electrical dust collecting member (33).

A ninth invention according to the gas treating device of the third invention is characterized in that the plasma catalyst is disposed downstream of the second discharge electrode (41) and the counter electrode (36), that the electrical dust collecting member
25 (33) supports thereon a photosemiconductor catalyst which is activated by a plasma

generated by discharge between the second discharge electrode (41) and the counter electrode (36) and which promotes the decomposition of the component to be treated, and that the electrical dust collecting member (33) is disposed between the second discharge electrode (41) and the counter electrode (36), and the plasma catalyst.

5 WORKING OPERATION

In the first and second inventions, the counter electrode (36) is shared between the first discharge electrode (35) and the second discharge electrode (41). When voltage is applied between the first discharge electrode (35) and the counter electrode (36), the discharge takes place between these electrodes. Dust in the gas to be treated is electrically charged by such discharge. And, the electrical dust collecting member (electrostatic filter) (33) entraps and collects the electrically charged dust.

On the other hand, when voltage is applied between the second discharge electrode (41) and the counter electrode (36), the discharge takes place between these electrodes, thereby generating a plasma. And, in the gas treating device, the generated plasma is used to decompose harmful substances and odorous substances which are treatment-target components present in the gas to be treated.

As described above, the discharge between the first discharge electrode (35) and the counter electrode (36) and the discharge between the second discharge electrode (41) and the counter electrode (36) are different types, and the dust and treatment-target components in the gas to be treated are removed.

In the third invention, the gas treating device is provided with a plasma catalyst. The plasma catalyst is activated by a plasma generated by discharge taking place between the second discharge electrode (41) and the counter electrode (36). The decomposition of the component to be treated in the gas to be treated is promoted by the activated plasma catalyst.

In the fourth invention, the second discharge electrode (41) is electrically connected to a position somewhere midway in the linearly-formed first discharge electrode (35). In other words, electrical conduction is established between the first discharge electrode (35) and the second discharge electrode (41), and they are equal in electrical potential at the time of voltage application.

In this invention, the distance between the second discharge electrode (41) and the counter electrode (36) is shorter than the distance between the first discharge electrode (35) and the counter electrode (36). As a result of such arrangement, although the first and second discharge electrodes (35, 41) are identical in electrical potential with each other, the electrical field intensity between the second discharge electrode (41) and the counter electrode (36) is greater than the electrical field intensity between the first discharge electrode (35) and the counter electrode (36). Consequently, the discharge taking place between the second discharge electrode (41) and the counter electrode (36) is greater in intensity than that taking place between the first discharge electrode (35) and the counter electrode (36).

In the fifth invention, at least the second discharge electrode (41) is positioned inside the columnlike counter electrode (36) having a cross section in the shape of a *katakana* character "コ". The discharge is caused to take place between the second discharge electrode (41) and the inner side surface of the counter electrode (36). In addition, besides the second discharge electrode (41) the first discharge electrode (35) may be disposed inside the counter electrode (36).

In the sixth invention, the gas treating device is provided with the electrode member (37). The electrode member (37) is shaped like a corrugated plate comprising an alternating pattern of "mountain" portions and "valley" portions. In addition, the waves in the electrode member (37) may be in any shape including sine-wave shape, rectangular

wave shape, triangular wave shape et cetera.

The first discharge electrode (35) is disposed on the side of one surface of the electrode member (37) while on the other hand the second discharge electrode (41) is disposed on the side of the other surface of the electrode member (37) opposite to the one surface. The first discharge electrode (35) is positioned in a "valley" portion as viewed from the side of the one surface of the electrode member (37), in other words it is positioned inside a concave portion. On the other hand, the second discharge electrode (41) is positioned in a "valley" portion as viewed from the side of the other surface of the electrode member (37), in other words it is positioned inside a concave portion. And, the discharge takes place between the first discharge electrode (35) and the electrode member (37) and between the second discharge electrode (41) and the electrode member (37), respectively.

In the seventh invention, the gas treating device is provided with a photosemiconductor catalyst. Photosemiconductor catalyst is generally used as a "photocatalyst" which is activated when illuminated with light. The photosemiconductor catalyst of the present invention, however, is activated by a plasma generated by discharge taking place between the second discharge electrode (41) and the counter electrode (36), even when the luminous source is not being illuminated. The decomposition of the component to be treated present in the gas to be treated is promoted by the activated photosemiconductor catalyst.

Here, photosemiconductor catalyst has properties that impede the adhesion of contaminants thereto. Therefore, the deterioration in activation operation of the photosemiconductor catalyst due to the adhesion of dust or other matter in the gas to be treated to the surface of the photosemiconductor catalyst is suppressed.

In the eighth invention, the electrical dust collecting member (33) supports

thereon a photosemiconductor catalyst. And, the photosemiconductor catalyst is activated by a plasma generated by discharge taking place between the second discharge electrode (41) and the counter electrode (36). The decomposition of the component to be treated present in the gas to be treated is expedited by the activated photosemiconductor catalyst.

5 In addition, the component to be treated which is deposited on the electrical dust collecting member (33), for example such as cigarette tar and allergen, can be decomposed by the photosemiconductor catalyst. Furthermore, the photosemiconductor catalyst suppresses the growth of fungus in the electrical dust collecting member (33).

10 In the ninth invention, the electrical dust collecting member (33) with a photosemiconductor catalyst supported thereon is positioned downstream of the second discharge electrode (41) and the counter electrode (36). Furthermore, positioned downstream of the electrical dust collecting member (33) is a plasma catalyst. As a result of such arrangement, both the photosemiconductor catalyst of the electrical dust collecting member (33) and the plasma catalyst are activated by a plasma generated by discharge
15 taking place between the second discharge electrode (41) and the counter electrode (36). And, the decomposition of the component to be treated present in the gas to be treated is effectively promoted by the activated photosemiconductor catalyst and by the activated plasma catalyst.

Here, if the photosemiconductor catalyst and the plasma catalyst have different
20 activation properties, this makes it possible to effectively decompose the component to be treated which contains therein a combined odorous component.

In addition, if the plasma catalyst has adsorption capability for the component to be treated present in the gas to be treated, this makes it possible for the plasma catalyst to adsorb and remove the component to be treated which has not been decomposed by
25 activation of the photosemiconductor catalyst and the plasma catalyst.

Furthermore, if the plasma catalyst has the capability to adsorb and decompose activated species such as ozone which is generated during plasma discharge, this makes it possible for the plasma catalyst to adsorb, decompose, and eliminate activated species such as ozone.

5 EFFECTS

In the present invention, the counter electrode (36) is shared between the first discharge electrode (35) and the second discharge electrode (41), and dust and components to be treated, present in a treatment-target gas, are removed. In other words, the first and second discharge electrodes (35, 41) do not cause discharge against their respective counter
10 electrodes, but they do so against their common counter electrode (36). Therefore, in accordance with the present invention, by sharing the counter electrode (36) between the first discharge electrode (35) and the second discharge electrode (41), the space required to install them can be reduced, thereby making it possible to downsize the gas treating device.

In accordance with the third invention, the component to be treated present in the
15 treatment-target gas is decomposed by a plasma generated as a result of discharge between the second discharge electrode (41) and the counter electrode (36), and its decomposition is expedited by the plasma catalyst. Accordingly, the present invention is able to enhance the processing capability of the gas treating device.

In the fourth invention, the second discharge electrode (41) is electrically
20 connected to a position somewhere midway in the first discharge electrode (35), thereby eliminating the need for individual voltage application to both the first and second discharge electrodes (35, 41). This makes it possible to apply voltage to both the first and second electrodes (35, 41), for example, by just connecting the first discharge electrode (35) to the power supply source. Therefore, the present invention provides a simplified
25 voltage-application configuration.

In the sixth invention, the first discharge electrode (35) is positioned inside a concave portion on the side of one surface of the electrode member (37) shaped like a corrugated plate while on the other hand the second discharge electrode (41) is positioned inside a concave portion on the side of the other surface of the electrode member (37).

5 Such arrangement allows both the first and second discharge electrodes (35, 41) to be stowed in place within the thickness of the corrugated plate-like electrode member (37). Therefore, in accordance with the present invention, the installation of the first and second discharge electrodes (35, 41) requires less space, thereby making it possible to further downsize the gas treating device.

10 In accordance with the seventh invention, the decomposition of the component to be treated by plasma discharge is promoted by activation of the photosemiconductor catalyst, thereby making it possible to enhance the processing capability of the gas treating device.

15 In addition, the photosemiconductor catalyst has properties that impede the adhesion of contaminants thereto. Therefore, the deterioration in activation operation of the photosemiconductor catalyst due to the adhesion of contaminants present in the gas to be treated to the surface of the photosemiconductor catalyst is suppressed. Therefore, it is possible to stabilize the processing capability of the gas treating device.

20 In accordance with the eighth invention, the electrical dust collecting member (33) supports thereon a photosemiconductor catalyst, so that the activation operation of the photosemiconductor catalyst can be given to the electrical dust collecting member (33). Therefore, the effect of entrapping and collecting dust by the electrical dust collecting member (33) and the effect of promoting decomposition by the photosemiconductor catalyst can be obtained by a compact configuration.

25 In addition, the arrangement that the electrical dust collecting member (33)

supports thereon a photosemiconductor catalyst provides the effect of decomposition of odorous components adsorbed on the electrical dust collecting member (33) or the effect of bacteria elimination in the electrical dust collecting member (33). Accordingly, the operational life span of the electrical dust collecting member (33) is extended.

5 In accordance with the ninth invention, the electrical dust collecting member (33) supporting thereon a photosemiconductor catalyst and the plasma catalyst are disposed downstream of the second discharge electrode (41) and the counter electrode (36), and by activating both the photosemiconductor catalyst and the plasma catalyst the action of decomposing the component to be treated is promoted. Accordingly, the processing
10 capability of the gas treating device is enhanced effectively.

Here, if the photosemiconductor catalyst and the plasma catalyst have different activation properties, this makes it possible to effectively decompose the component to be treated which contains therein a combined odorous component. Accordingly, the gas treating device's capability to treat the gas to be treated which contains a combined odorous
15 component can be enhanced.

In addition, if the plasma catalyst has adsorption capability for the component to be treated, this makes it possible for the plasma catalyst to adsorb and remove the component to be treated which has still remained undecomposed/unremoved after treatment by plasma discharge. Accordingly, it is possible to obtain processing capability
20 following the variation in density load of the odorous component, thereby making it possible to enhance the reliability of the gas treating device.

Furthermore, if the plasma catalyst has the capability to adsorb and decompose activated species such as ozone generated as a result of plasma discharge, this makes it possible for the plasma catalyst to decompose and eliminate activated species such as
25 ozone. This prevents activated species (by-product matters) generated in the device by

plasma discharge from being emitted to outside the device, thereby making it possible to further improve the reliability of the gas treating device.

BRIEF DESCRIPTION OF THE DRAWINGS

5 Figure 1 is an exploded perspective view of an air purifying device according to a first embodiment of the present invention;

 Figure 2 is a perspective view illustrating in enlarged manner a major section of an ionization part in the air purifying device of the first embodiment;

 Figure 3 is a perspective view illustrating in enlarged manner a major section of
10 an ionization part in the air purifying device of the first embodiment;

 Figure 4 is a perspective view illustrating in enlarged manner a major section of an ionization part in the air purifying device of the first embodiment;

 Figure 5 is a perspective view illustrating in enlarged manner a major section of an ionization part in an air purifying device of a second embodiment of the present
15 invention;

 Figure 6 is a schematic view showing the arrangement of an ionization part in an air purifying device of a third embodiment of the present invention;

 Figure 7 is a schematic view showing the arrangement of an ionization part in an air purifying device of the third embodiment; and

20 Figure 8 is a perspective view illustrating in enlarged manner a major section of an ionization part in an air purifying device of another embodiment of the present invention.

BEST MODE FOR CARRYING OUT THE INVENTION

25 Hereinafter, embodiments of the present invention are described in detail with

reference to the drawings. Each embodiment relates to a gas treating device which is an air purifying device (10) for general household use or for use in small-scale stores.

FIRST EMBODIMENT OF THE INVENTION

As shown in Figure 1, the air purifying device (10) of the present embodiment has
 5 a casing (20) made up of a box-like casing main body (21) one end of which is opened and a front plate (22) which is mounted to the open end. Formed in both side surfaces of the casing (20) on the front plate's (22) side are air suction openings (23). In addition, the casing main body (21) has an air blowout opening (24) which is formed in an area of the top plate close to the back plate.

10 Formed within the casing (20) is an air passageway (25) through which room air as a gas to be treated flows from the air suction openings (23) to the air blowout opening (24). Arranged, in sequence from the upstream side of the flow of air, along the air passageway (25) are a functional section (30) including various components for air cleaning, and a centrifugal air blower (26) for distribution of room air through the air
 15 passageway (25).

Disposed, in sequence from the front plate's (22) side, in the functional section (30) are a pre-filter (31), an ionization part (32), an electrostatic filter (33) as an electrical dust collecting member, and a catalytic filter (34). A plasma generating device (40) for generating a plasma of low temperature is integrally incorporated into the ionization part
 20 (32).

The pre-filter (31) is disposed to entrap and collect dust of relatively large size present in the room air.

The ionization part (32) causes dust of relatively small size present in the room air passing through the pre-filter (31) to be electrically charged. The electrically charged
 25 dust is entrapped and collected by the electrostatic filter (33) positioned downstream of the

ionization part (32).

The ionization part (32) is provided with a negative electrode member (37) as an electrode member. The negative electrode member (37) is a metal plate which is shaped like a corrugated plate by press forming, and is disposed in an upright position within the casing (20). More specifically, the negative electrode member (37) is shaped like a corrugated plate whose wave shape is rectangular. In other words, in the negative electrode member (37), columnar portions having a cross section in the shape of a *katakana* character "コ" and extending vertically, and rectangular plate-like portions which are vertically elongated are alternately formed in horizontal direction. And, the negative electrode member (37) is oriented, such that the open side of each of the cross-sectionally "コ"-shaped columnar portions faces towards the electrostatic filter (33), in other words the open side faces downstream of the airflow therethrough.

In the negative electrode member (37), each cross-sectionally "コ"-shaped columnar portion constitutes a respective counter electrode (36). In the columnar portion, portions orthogonal to the opening side of the columnar portion constitute a pair of side surface portions (37b), and a portion orthogonal to the side surface portions (37b) and situated on the side of the pre-filter (31) constitutes a front surface portion (37a). On the other hand, in the negative electrode member (37), a rectangular portion sandwiched between adjoining columnar portions constitutes a back surface portion (37c). With reference to Figure 2, a large number of air apertures (50) are opened at the back surface portion (37c). Likewise, a large number of air apertures (50) are opened in a specific area of the side surface portion (37b) near the back surface portion (37c).

An ionization line (35) serving as a first discharge electrode is provided in a plural number in the ionization part (32). The ionization line (35) is arranged inside a concave portion when viewing the negative electrode member (37) from the pre-filter's (31) side, in

other words the ionization line (35) is arranged interior to a portion enclosed on three sides by a pair of side surface portions (37b) and a back surface portion (37c). In addition, the ionization line (35) extends across the ionization part (32) from the top end to the bottom end. At its lower end, the ionization line (35) strides across the counter electrode (36).

5 Each ionization line (35) is located on a single virtual surface in parallel with the electrostatic filter (33), being evenly spaced apart from the other.

The plasma generating device (40) is provided with a discharge electrode (41) serving as a second discharge electrode, and shares the counter electrode (36) with the ionization line (35).

10 As shown in Figure 2, the discharge electrode (41) is arranged inside a concave portion when viewing the negative electrode member (37) from the electrostatic filter's (33) side, in other words the discharge electrode (41) is arranged interior to a portion enclosed on three sides by a front surface portion (37a) and a pair of side surface portions (37b). In other words, the discharge electrode (41) is disposed inside the cross-
15 sectionally "□"-shaped counter electrode (36). More specifically, a columnar electrode holding member (43) having a square cross section and extending vertically is disposed inside the counter electrode (36). Of the side surfaces of the electrode holding member (43), a side surface on the front surface portion's (37a) side is provided with a plurality of securing members (44) which are vertically evenly spaced apart from each other. Each
20 securing member (44) is provided with a respective discharge electrode (41). That is to say, the discharge electrode (41) is secured to the electrode holding member (43) by the securing member (44). The discharge electrode (41) is an electrode in the form of a line or rod. The discharge electrode (41) is arranged such that its portion projecting from the securing member (44) runs substantially parallel with the front surface portion (37a).

25 Additionally, the electrode holding member (43) and the securing member (44) are

formed of the same type of metal as the discharge electrode (41). The discharge electrode (41) and the electrode holding member (43) electrically conduct with each other through the securing member (44).

The ionization part (32) is provided with a high-voltage direct-current power source (45) for applying voltage between the ionization line (35) and the counter electrode (36). The DC power source (45) serves also as a power source for the plasma generating device (40). Upon the application of a voltage to the ionization line (35) and to the discharge electrode (41) by the DC power source (45), ions are generated around the ionization line (35) and streamer discharges are generated from the leading end of the discharge electrode (41) towards the counter electrode (36). Although the ionization line (35) and the discharge electrode (41) are fed a high voltage of the same potential (for example, 5 kV), the action of generating ions in the ionization part (32) is designed to take place simultaneously with the action of causing streamer discharge to take place in the plasma generating device (40) by making a difference in electric field intensity by setting the distance between the ionization line (35) and the counter electrode (36) and the distance between the discharge electrode (41) and the counter electrode (36), for example, at 10 mm and at 5 mm, respectively.

The electrostatic filter (33) is disposed downstream of the plasma generating device (40) made up of the discharge electrode (41) and the counter electrode (36). The electrostatic filter (33) entraps and collects, at its upstream side surface, dust of relatively small size electrically charged by the ionization part (32). The downstream side surface of the electrostatic filter (33) supports thereon a photosemiconductor catalyst to form a photosemiconductor catalyst layer (38). The photosemiconductor catalyst of the photosemiconductor catalyst layer (38) further activates substances (activated species such as electron, ion, ozone, radical etc.) of high reactivity present in the low-temperature

plasma generated by discharge between the discharge electrode (41) and the counter electrode (36), and promotes the decomposition of harmful substances and odorous substances which are components to be treated present in room air. As the photosemiconductor catalyst, for example titanium dioxide and zinc oxide, or oxides of tungsten and cadmium sulfide may be used.

The catalytic filter (34) is disposed downstream of the electrostatic filter (33). The catalytic filter (34) is formed, for example, by a honeycomb- structure substrate which supports on its surface a plasma catalyst. This plasma catalyst, like the aforesaid photosemiconductor catalyst, further activates substances (activated species such as electron, ion, ozone, radical etc.) of high reactivity present in the low-temperature plasma generated as a result of discharge between the discharge electrode (41) and the counter electrode (36), and promotes the decomposition of harmful substances and odorous substances which are components to be treated in the room air. As the plasma catalyst, for example a catalyst of the manganese family, a catalyst of the precious metal family, or a catalyst formed by addition of an adsorbent, e.g., activated carbon, to such catalysts may be used.

RUNNING OPERATION

Next, the running operation of the air purifying device (10) is described.

When the air purifying device (10) is in operation, the centrifugal air blower (26) is started, and room air which is a gas to be treated flows and passes through the air passageway (25) within the casing (20). In addition, in this state, high voltage is applied, by the DC power source (45), to the ionization part (32) and to the plasma generating device (40).

When a stream of room air is introduced into the casing (20), dust of relatively large size is removed by the pre-filter (31). After passage through the pre-filter (31), the

room air flows to the ionization part (32). In the ionization part (32), dust of relatively small size present in the room air is electrically charged by discharge between the ionization line (35) and the counter electrode (36). The room air containing the electrically charged dust passes through the air apertures (50) provided in the side and back surface portions (37b, 37c) and then flows into the electrostatic filter (33). The electrostatic filter (33) entraps and collects the electrically charged dust.

In the plasma generating device (40) integrally incorporated into the ionization part (32), a low-temperature plasma is being generated by streamer discharge between the discharge electrode (41) and the counter electrode (36). On the other hand, during discharge, an ion wind is generated. The ion wind is reflected from the front surface portion (37a), flowing downstream of the airflow, as indicated by broken line of Figure 2. And, the generated low-pressure plasma rides on the ion wind, passes through the ionization part (32), and flows downstream together with the room air.

The low-temperature plasma contains therein a substance (activated species) of high reactivity. And, when coming into contact with room air flowing through the air passageway (25), the high-reactivity substance decomposes harmful substances and odorous substances present in the room air. In addition, when the activated species reaches the electrostatic filter (33), it is activated to a further extent by the photosemiconductor catalyst supported on the photosemiconductor catalyst layer (38) of the electrostatic filter (33), as a result of which the harmful and odorous substances in the room air are decomposed to a further extent. And, when the activated species reaches the catalytic filter (34), it is further activated, as a result of which the harmful and odorous substances in the room air are decomposed to a still further extent.

The room air, purified by removal of dust, harmful substances, and odorous substances, is taken into the centrifugal air blower (26) and is blown out into the room

through the air blowout opening (24).

EFFECTS OF FIRST EMBODIMENT

In the present embodiment, the counter electrode (36) is shared between the ionization part (32) and the plasma generating device (40). In other words, the ionization line (35) and the discharge electrode (41) do not discharge, respectively, to individual counter electrodes but to their common counter electrode (36). Therefore, in accordance with the present embodiment, the counter electrode (36) is common to the ionization line (35) and the discharge electrode (41), thereby making it possible to reduce their installation space. Therefore, it is possible to downsize the air purifying device (10).

In accordance with the present embodiment, harmful substances and odorous substances present in room air are decomposed by a plasma generated by discharge between the discharge electrode (41) and the counter electrode (36) and, in addition, the plasma catalyst expedites the decomposition of harmful substances and odorous substances present in room air. Therefore, in accordance with the present embodiment, it is possible to enhance the processing capability of the air purifying device (10).

In addition, in the present embodiment, the discharge electrode (41) is arranged interior to the cross-sectionally "□"-shaped counter electrode (36). As a result of such arrangement, an ion wind generated by discharge is not diffused outwardly of the counter electrode (36) but flows downstream of the airflow. This allows the plasma, generated by discharge between the discharge electrode (41) and the counter electrode (36), to be supplied, together with the ion wind, to the catalytic filter (34) without fail. Therefore, in accordance with the present embodiment, the decomposition of harmful substances and odorous substances present in room air is promoted to a further extent, thereby making it possible to further enhance the processing capability of the air purifying device (10).

Additionally, in accordance with the present embodiment, because of the

arrangement that the discharge electrode (41) is positioned downstream of the counter electrode (36), the amount of dust or other matter in room air adhering to the discharge electrode (41) can be reduced considerably. Therefore, it becomes possible to cause stable streamer discharge to continuously take place between the discharge electrode (41) and the counter electrode (36), thereby making it possible to continuously maintain the processing capability of the air purifying device (10).

Furthermore, in the present embodiment, the ionization line (35) is arranged inside a concave portion on the side of one surface of the negative electrode member (37) shaped like a corrugated plate while on the other hand the discharge electrode (41) is arranged inside a concave portion on the side of the other surface of the negative electrode member (37). Because of such arrangement, both the ionization line (35) and the discharge electrode (41) can be stowed in place within the range of the thickness of the corrugated plate-like negative electrode member (37). Therefore, in accordance with the present embodiment, the installation space of the ionization line (35) and the discharge electrode (41) is further reduced, thereby making it possible to downsize the air purifying device (10) to a further extent.

In addition, in accordance with the present embodiment, the electrostatic filter (33) supports thereon a photosemiconductor catalyst, thereby making it possible to promote the decomposition of harmful substances and odorous substances in the room air with the aid of plasma. This therefore enhances the processing capability of the air purifying device (10). In addition, the electrostatic filter (33) integrally incorporates therein a photosemiconductor catalyst, thereby making it possible to reduce the thickness of the air purifying device (10), and the size of the air purifying device (10) is reduced accordingly.

Furthermore, the arrangement that the electrostatic filter (33) supports thereon a

photosemiconductor catalyst provides the effect of decomposition of odorous components adsorbed on the electrostatic filter (33) or the effect of bacteria elimination in the electrostatic filter (33). Accordingly, the operational life span of the electrostatic filter (33) is extended.

5 VARIATIONS OF FIRST EMBODIMENT

With respect to the air purifying device (10) of the first embodiment, the change in configuration of the plasma generating device (40) in the ionization part (32) may be made.

In a first variation of the first embodiment (Figure 3), the discharge electrode (41) is attached to the electrode holding member (43) of the plasma generating device (40).

10 The discharge electrode (41) is a small piece shaped like a triangular plate and is provided such that it stands on a side surface of the electrode holding member (43) on the front surface portion's (37a) side. And, upon application of voltage, streamer discharges are generated towards the counter electrode (36) from the leading end of the discharge electrode (41).

15 In a second variation of the first embodiment (Figure 4), the electrode holding member (43) of the plasma generating device (40) comprises a portion which serves as the discharge electrode (41). In other words, the discharge electrode (41) is retained not by the electrode holding member (43), and portions of the electrode holding member (43) serve as discharge electrodes (41) which are projections evenly spaced apart from each
20 other.

More specifically, the electrode holding member (43) is shaped like a vertically long, elongated flat plate, being arranged in parallel with the side surface portion (37b). A side surface of the electrode holding member (43) situated on the front surface portion's (37a) side is provided with a plurality of triangular projections uniformly spaced apart
25 from each other. Each projection serves as a respective discharge electrode (41). And,

upon application of voltage, streamer discharges are generated towards the counter electrode (36) from the leading end of the discharge electrode (41).

SECOND EMBODIMENT OF THE INVENTION

A second embodiment of the present invention is similar to the first embodiment, with the exception of modifications in the configuration of the ionization part (32). The difference between the first embodiment and the present embodiment is described below.

With reference to Figure 5, in the air purifying device (10) of the present embodiment, the front surface portion (37a) of the ionization part (32) is provided with a plurality of circular vent holes (51). Each vent hole (51) is formed, such that its opening lies at the approximately same level as that of the intermediate point between adjoining securing members (44) mounted on the electrode holding member (43). A part of the room air after passage through the pre-filter (31) flows, through the vent holes (51), into the ionization part (32), as indicated by solid line of Figure 5.

Meanwhile, in the plasma generating device (40), a plasma of low temperature is being generated by streamer discharge between the discharge electrode (41) and the counter electrode (36). The activated species contained in the low-temperature plasma rides on a flow of room air after passage through the vent holes (51) and flows towards the catalytic filter (34) while being diffused all over the air passageway (25). In the catalytic filter (34), its plasma catalyst is activated further, thereby further promoting the decomposition of harmful substances and odorous substances present in the room air. Therefore, the present embodiment ensures that harmful substances and odorous substances present in room air flowing through the air passageway (25) are decomposed, thereby making it possible to enhance the processing capability of the air purifying device (10).

THIRD EMBODIMENT OF THE INVENTION

A third embodiment of the present invention is similar to the first embodiment, with the exception of modifications in the configuration of the ionization part (32). With reference to Figure 6, the difference between the first embodiment and the present embodiment is described below. Figure 6(A) is a top plan view. Figure 6(B) is an illustration as viewed from upstream of the airflow. Figure 7(A) is a top plan view. Figure 7(B) is an illustration as viewed from upstream of the airflow.

In the air purifying device (10) of the present embodiment, the back surface portion (37c) of the ionization part (32) is provided with a plurality of insulators (60) for insulation. The insulators (60) are used to insulate electrical continuity and are evenly spaced apart from each other in the vertical direction of the negative electrode member (37). Attached to a side surface of each insulator (60) on the pre-filter's (31) side is a conducting member (61). The conducting member (61) conducts electricity.

The discharge electrode (41) is attached, through the securing member (44), to the side surfaces of the conducting member (61) that is situated on the side surface portion (37b). In addition, the ionization line (35) is arranged on a side surface of the conducting member (61) on the pre-filter's (31) side. The ionization line (35) is supported on the conducting member (61). In other words, the ionization line (35) and the discharge electrode (41) electrically conduct with each other through the conducting member (61).

Upon the application of a discharge voltage to either one of the ionization line (35) and the discharge electrode (41), the ionization line (35) and the discharge electrode (41) become identical in potential with each other. And, the discharge takes place between the ionization line (35) and the counter electrode (36) of the side surface portion (37b) and between the discharge electrode (41) and the counter electrode (36) of the side surface portion (37b).

Here, the distance between the discharge electrode (41) and the counter electrode

(36) is sufficiently shorter than the distance between the ionization line (35) and the counter electrode (36), thereby producing a difference in electric field intensity between them. Consequently, the streamer discharge takes place between the discharge electrode (41) and the counter electrode (36) and, as a result, a plasma is generated, whereby harmful substances and odorous substances present in the room air are decomposed and removed. In addition, dust present in the room air is electrically charged by discharge taking place between the ionization line (35) and the counter electrode (36).

VARIATION OF THE THIRD EMBODIMENT

In the air purifying device (10) of the third embodiment, the ionization part (32) may be changed in configuration. The difference between the third embodiment and the present variation is described below.

As shown in Figure 7, in the air purifying device (10) of the present variation, a plurality of discharge electrodes (41) are disposed at respective positions somewhere midway in the ionization line (35), such that they are evenly separated apart from each other. That is to say, the ionization line (35) and each discharge electrode (41) electrically conduct with each other. The discharge electrode (41) has a cross section in the shape of a rhombus as viewed from upstream of the airflow, and is arranged to be symmetrical about the center of the ionization line (35). And, the discharge takes place between the ionization line (35) and the counter electrode (36) of the side surface portion (37b) and between the discharge electrode (41) and the counter electrode (36) of the side surface portion (37b).

In the present variation, the discharge electrode (41) is electrically connected to a position somewhere midway in the ionization line (35), thereby eliminating the need for individual voltage application to the ionization line (35) and to the discharge electrode (41).

As a result of such arrangement, it becomes possible to apply voltage to both the ionization

line (35) and the discharge electrode (41), for example, by just connecting the ionization line (35) to the power supply source. Therefore, the present variation provides a simplified voltage application configuration.

OTHER EMBODIMENTS

5 FIRST VARIATION

In the air purifying device (10) of the first or second embodiment, the ionization part (32) may be changed in configuration.

As shown in Figure 8, in the air purifying device (10) of the present variation, the air apertures (50) are formed only in the side surface portion (37b) of the negative electrode member (37) of the ionization part (32). Stated another way, the back surface portion (37c) has no air apertures (50). All the inflow of room air into the ionization part (32) passes through the air apertures (50) of the side surface portion (37b) and then flows downstream from the opening side of the counter electrode (36) arranged in the shape of the *katakana* character "コ".

On the other hand, in the plasma generating device (40), a plasma of low temperature is being generated by streamer discharge taking place between the discharge electrode (41) and the counter electrode (36). An activated species contained in the low-temperature plasma rides on a flow of room air after passage through the vent holes (51) and flows towards the catalytic filter (34) while being diffused all over the air passageway (25). In the catalytic filter (34), the plasma catalyst is further activated, thereby further promoting the decomposition of harmful substances and odorous substances present in the room air. Therefore, the present variation ensures that harmful substances and odorous substances present in the room air flowing through the air passageway (25) are decomposed, thereby making it possible to enhance the processing capability of the air purifying device (10).

In addition, in the present variation, it may be arranged such that the portion constituting the back surface portion (37c), and the portion constituting the front and side surface portions (37a, 37b) are formed of different members, and that these members are disposed, such that there is a gap therebetween. In this case, the member constituting the back surface portion (37c) operates as a baffle plate, and the inflow of room air into the ionization part (32) passes through the gap defined between the member constituting the front and side surface portions (37a, 37b) and the member constituting the back surface portion (37c) and flows downstream.

SECOND VARIATION

In the air purifying device (10) of each of the first to third embodiments, the ionization part (32) may be changed in configuration. In the ionization part (32) of the present variation, the wave shape in the negative electrode member (37) is not limited to be rectangular, in other words the negative electrode member (37) may employ, as its wave shape, any shape including sine-wave shape, triangular wave shape et cetera. In the negative electrode member (37), the ionization line (35) is provided on one surface of the negative electrode member (37) situated on the pre-filter's (31) side, and the discharge electrode (41) is provided on another surface of the negative electrode member (37) on the catalytic filter's (34) side situated opposite to the one surface. The ionization line (35) is disposed at a "valley" portion when viewing the negative electrode member (37) from the pre-filter's (31) side, in other words the ionization line (35) is disposed inside a concave portion. On the other hand, the discharge electrode (41) is disposed at a "valley" portion when viewing the negative electrode member (37) from the electrostatic filter's (33) side, in other words the discharge electrode (41) is disposed inside a concave portion.

THIRD VARIATION

In the foregoing embodiments, the electrostatic filter (33) is used as an electrical

dust collecting member. Alternatively, instead of using an electrostatic filter, a duct collecting plate, such as an electrode plate, may be used as an electrical dust collecting member.

FOURTH VARIATION

5 Furthermore, in the foregoing embodiments, the catalytic filter (34), whose substrate supports thereon a plasma catalyst such as a catalyst of the manganese family, a catalyst of the precious metal family etc., is disposed downstream of the plasma generating device (40). However, instead of using the catalytic filter (34), an adsorptive processing member, whose substrate supports thereon an adsorbent such as activated carbon, zeolite
10 etc., may be disposed downstream of the plasma generating device (40).

INDUSTRIAL APPLICABILITY

As has been described above, the present invention is useful with gas treating devices for removing dust, odors etc. present in the air by causing discharge to take place.

CLAIMS**WHAT IS CLAIMED IS:**

1. A gas treating device for entrapping and collecting dust present in a gas to be treated,
5 and for decomposing a component to be treated present in the gas to be treated, the gas
treating device comprising:
 - a counter electrode (36);
 - a first discharge electrode (35) for causing discharge to take place between the
first discharge electrode (35) and the counter electrode (36) so that the dust in the gas to be
10 treated is electrically charged;
 - an electrical dust collecting member (33) for entrapping and collecting the
electrically charged dust in the gas to be treated; and
 - a second discharge electrode (41) for causing discharge to take place between the
second discharge electrode (41) and the counter electrode (36) so that a plasma for
15 decomposing the component to be treated is generated.
2. The gas treating device of claim 1, wherein the electrical dust collecting member (33)
is formed by an electrostatic filter.
- 20 3. The gas treating device of claim 1, wherein a plasma catalyst is provided which is
activated by a plasma generated by discharge between the second discharge electrode (41)
and the counter electrode (36) and which promotes the decomposition of the component to
be treated.
- 25 4. The gas treating device of claim 1, wherein the first discharge electrode (35) is formed

into a linear shape extending along the counter electrode (36), and wherein the second discharge electrode (41) is electrically connected to a position somewhere midway in the first discharge electrode (35), and is disposed such that the distance between the second discharge electrode (41) and the counter electrode (36) is shorter than the distance between
5 the first discharge electrode (35) and the counter electrode (36).

5. The gas treating device of claim 1, wherein the counter electrode (36) is shaped like a column having a cross section in the shape of a Japanese *katakana* character "コ", and wherein at least the second discharge electrode (41) is disposed inside the counter electrode
10 (36).

6. The gas treating device of claim 1, wherein an electrode member (37) which is shaped like a corrugated plate and which constitutes the counter electrode (36) is provided, wherein the first discharge electrode (35) is disposed on the side of one surface of the
15 electrode member (37) and the second discharge electrode (41) is disposed on the side of the other surface of the electrode member (37), and wherein the first discharge electrode (35) and the second discharge electrode (41) are disposed, respectively, inside concave portions of the corrugated plate-like electrode member (37).

20 7. The gas treating device of claim 1, wherein a photosemiconductor catalyst is provided which is activated by a plasma generated by discharge between the second discharge electrode (41) and the counter electrode (36) and which promotes the decomposition of the component to be treated.

25 8. The gas treating device of claim 7, wherein the photosemiconductor catalyst is

supported on the electrical dust collecting member (33).

9. The gas treating device of claim 3, wherein the plasma catalyst is disposed downstream of the second discharge electrode (41) and the counter electrode (36), wherein
- 5 the electrical dust collecting member (33) supports thereon a photosemiconductor catalyst which is activated by a plasma generated by discharge between the second discharge electrode (41) and the counter electrode (36) and which promotes the decomposition of the component to be treated, and wherein the electrical dust collecting member (33) is disposed between the second discharge electrode (41) and the counter electrode (36), and
- 10 the plasma catalyst.

* * * * *