20000479Q-2

PCT

WORLD INTELLECTUAL PROPERTY ORGANIZATION
International Bureau

INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification 6: H01L 51/20, 27/146 | A1

(11) International Publication Number: WO 99/39395

(43) International Publication Date: 5 August 1999 (05.08.99)

(21) International Application Number: PCT/US99/02247

(22) International Filing Date: 2 February 1999 (02.02.99)

(30) Priority Data:
(1) 60/073,346 2 February 1998 (02.02.98) US
(1)

(71) Applicant: UNIAX CORPORATION [US/US]; 6780 Cortona Drive, Santa Barbara, CA 93117 (US).

(72) Inventors: YU, Gang; 667 Camino Campana, Santa Barbara, CA 93111 (US). CAO, Yong; 436 Pomona Court, Goleta, CA 93117 (US).

(74) Agent: BENZ, William, H.; Burns, Doane, Swecker & Mathis, L.L.P., P.O. Box 1404, Alexandria, VA 22313-1404 (US).

(81) Designated States: AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, CA, CH, CN, CU, CZ, DE, DK, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, UA, UG, UZ, VN, YU, ZW, ARIPO patent (GH, GM, KE, LS, MW, SD, SZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GW, ML, MR, NE, SN, TD, TG).


Published

With international search report.

Before the expiration of the time limit for amending the claims and to be republished in the event of the receipt of amendments.

1 PD.

(54) Title: ORGANIC DIODES WITH SWITCHABLE PHOTOSENSITIVITY



(57) Abstract

Organic photodetectors with switchable photosensitivity are achieved using organic photoactive layers in electrode/organic/electrode structures. The photosensitivity can be switched on and off by the biasing voltage across the detectors. The photocurrent can be probed with a read-out circuit in the loop. These photodetectors can be arranged in linear arrays or in two-dimensional matrices that function as high performance, linear or two-dimensional image sensors. These image sensors can achieve full color or selected color detection capability.