



9610012-8

IPO's

copy

95-291 SG

SPECIFICATIONFLAT CABLE CONNECTORTHIS SHEET HAS BEEN
REPLACEDField of the Invention

5 This invention generally relates to the art of electrical connectors and, particularly, to an electrical connector for terminating a flat cable, such as a flat flexible cable, printed circuit board or the like, without requiring any insertion force.

Background of the Invention

10 There are a wide variety of zero insertion force electrical connectors particularly adapted for terminating flat cables, such as flexible flat cables, flexible printed circuit boards and the like. These electrical connectors conventionally have a housing mounting a plurality of terminals in a generally parallel array. An actuator, such
15 as a pressure member, is used to press the flexible flat cable, flexible printed circuit board or the like against contact portions of the terminals.

Heretofore, some actuators have been designed to be pushed in and pulled out of the connector housings.
20 Such designs require the application of insertion forces to the flat cables. In addition, such designs have inevitably resulted in an increase in the overall size of the connectors.

Consequently, some zero insertion force electrical connectors for flat cables have been designed with actuators or pressure members which are rotatably or pivotally mounted on the housing for movement between first, open positions allowing free insertion of the cables into the connector housings, and second, closed positions
30 for clamping the flat cables against the contact portions of the terminals.

One of the problems with prior connectors having rotatable actuators or pressure members is the tendency of

moving the pressure member back toward its open position when undesired external forces are applied to the flexible flat cable. The flat cable tends to raise and rotate the pressure member, thereby releasing the flat cable from the connector. The present invention is directed to solving this problem and preventing undesired releasing or decoupling of the flat cable from the connector when certain external forces are applied to the cable.

Summary of the Invention

10 An object, therefore, of the invention is to provide a new and improved zero insertion force electrical connector for flat electrical cables, of the character described.

15 In the exemplary embodiment of the invention, the electrical connector includes a dielectric housing mounting a plurality of terminals in a generally parallel array transversely of the connector. The housing has opposite sides and a front end, with an opening between the sides for receiving an end of the flat cable in engagement with
20 contact portions of the terminals. A pressure member is rotatably mounted on the housing for movement between a first position allowing insertion of the flat cable into the opening and a second position pressing conductors of the flat cable against the contact portions of the
25 terminals. Generally, stop means are provided on the housing to prevent release of the flat cable from the electrical connector in the event undesired external forces are applied to the cable which would tend to bias the pressure member back toward its first position.

30 More particularly, the stop means are provided by overhanging extensions projecting inwardly from the opposite sides of the housing. The pressure member includes an actuating portion having a width sized to fit between the overhanging extensions at the opposite sides of
35 the housing. A pair of pivots rotatably mount the pressure member on the housing at opposite sides of the pressure



95-291 SG

member. The pivots are located rearwardly of the overhanging extensions. Lastly, the pressure member includes a stepped lower surface at the front thereof defining a generally triangular space between the pressure member and the flat cable when the pressure member is in its second position.

Other objects, features and advantages of the invention will be apparent from the following detailed description taken in connection with the accompanying drawings.

This Sheet Has Been Replaced


Brief Description of the Drawings

The features of this invention which are believed to be novel are set forth with particularity in the appended claims. The invention, together with its objects and the advantages thereof, may be best understood by reference to the following description taken in conjunction with the accompanying drawings, in which like reference numerals identify like elements in the figures and in which:

FIGURE 1 is a front-to-rear vertical section through the flat cable connector of the invention, with the front of the pressure member broken away;

FIGURE 2 is a top plan view of the housing of the connector;

FIGURE 3 is a front elevational view of the housing of the connector;

FIGURE 4 is a side elevational view of the housing of the connector;

FIGURE 5 is a top plan view of the pressure member;

FIGURE 6 is a front elevational view of the pressure member;

FIGURE 7 is a side elevational view of the pressure member;

FIGURE 8 is an enlarged vertical section taken generally along line H-H in Figure 6;

FIGURE 9 is an enlarged vertical section taken generally along line K-K in Figure 6;

FIGURE 10 is an enlarged vertical section taken generally along line J-J in Figure 6;

FIGURE 11 is a side elevational view of another embodiment of a flat cable connector, with the pressure member in its open position; and

FIGURE 12 is a front-to-rear vertical section through the flat cable connector of Figure 12.

This Sheet Has Been Replaced



Detailed Description of the Preferred Embodiments

Referring to the drawings in greater detail, Figure 1 shows a first embodiment of a flexible flat cable connector according to the invention. The connector includes a housing 1 mounting a plurality of terminals 2 in a generally parallel array. The housing rotatably mounts an actuator or cable pressure member 3. Details of the housing are shown in Figures 2-4, and details of the cable pressure member are shown in Figures 5-10.

Referring to Figures 2-4 in conjunction with Figure 1, housing 1 is unitarily molded of dielectric material such as plastic or the like. The housing includes a base 5 having a plurality of terminal slots 4 formed therein, opposite side walls 6 molded integrally to opposite lateral edges of base 5, and a top wall 7 extending transversely between opposite side walls 6. Each side wall has a cam slot or track 9 facing upwardly toward top wall 7. As described in greater detail hereinafter, cable pressure member 3 has a counter cam on each opposite side thereof for cooperating with cam slot 9 for guiding the cable pressure member between its rotatable positions.

As seen in Figures 2 and 3, top wall 7 extends short of the front end of housing 1, thereby leaving a space or opening 8 at the front of the housing. The opening coincides with a cable insertion opening, generally designated 21, into which a flexible flat cable 22 can be inserted in the direction of arrow 23 (Fig. 3). Lastly, housing 1 includes stop means in the form of a pair of overhanging extensions 24 projecting inwardly from opposite side walls 6 and overhanging the opposite edges 22a of flexible flat cable 22 as best seen in Figure 3.

Each terminal 2 is stamped from sheet metal material in a bifurcated shape as best seen in Figure 1. The bifurcated shape defines a relatively short upper support leg 10 and a relatively long lower contact leg 11. Support leg 10 has a barb 12, and the terminal is fixed in a respective one of the terminal slots 4 by barb 12 of



support leg 10 biting into an intermediate shelf 1a of the housing. Contact leg 11 has a contact portion 13 projecting from the free end of the leg upwardly toward support leg 10. An L-shaped soldering tail 14 extends rearwardly of the terminal and outwardly of housing 1. The bottom of the L-shaped soldering tail 14 is flush with the bottom surface of base 5 of the housing for soldering to a circuit trace on an appropriate printed circuit board.

Referring to Figures 5-10 in conjunction with Figures 1-4, cable pressure member 3 is unitarily molded of dielectric material, such as plastic or the like. The pressure member includes a major flat plate 15 which is wide enough to span the opening 8 at the front of housing 1. Triangular flanges 16 are molded integrally at opposite sides of flat plate 15. Each triangular flange 16 has a counter cam 17 at the front thereof. Each triangular flange 16 is positioned so that its counter cam 17 confronts the cam slot or track 9 (Fig. 4) in a respective one of the side walls of the housing.

Major flat plate 15 of cable pressure member 3 has a width sized to fit in the space between the opposite overhanging extensions 24 of housing 1 as the cable pressure member moves from a first open position allowing insertion of flat cable 22 into opening 8 in the housing, and a second closed position pressing conductors of the flat cable against contact portions 13 of terminals 2 as shown in Figure 1. As seen in Figures 8 and 10, major flat plate 15 of cable pressure member 3 has a stepped lower surface 25 at the front thereof. In addition, the cable pressure member has projections 18 (Figs. 5-7) projecting outwardly of its opposite sides. Each projection 18 fits into an L-shaped slot 19 (Fig. 2) in the inner surface of one of the side walls 6 of the housing. The cable pressure member also has rounded side projections 20 which form detents to snap over the inside edges of overhanging extensions 24 when the pressure member is moved between its open and closed positions.



Cam slots or tracks 9 on housing 1 and counter
cams 17 on cable pressure member 3 cooperate functionally
to guide the cable pressure between its rotatable
positions. Specifically, when the cable pressure member is
5 moved toward its closed position shown in Figure 1, a rear
end 15a (Fig. 8) of the cable pressure member moves under
a comb-like support arrangement defined by the bottom
surfaces 26 (Fig. 1) of support legs 10 of terminals 2. By
this action, flat cable 22 is pinched between the
10 undersurface of the cable pressure member and contact
portions 13 of terminals 2.

Referring back to Figure 1 wherein flexible flat
cable 22 has been inserted into the connector, assume that
the flat cable is pulled upwardly as shown in broken lines
15 by undesired external forces applied to the cable. In a
conventional electrical connector structure, the cable
pressure member would be rotated toward its open position
in the direction indicated by arrow 27. However, according
to the concepts of the present invention in the electrical
20 connector structure shown herein, the flat cable 22 will
move or bend the cable pressure member upwardly only a
small degree until the flat cable is stopped by the
overhanging extensions 24 extending inwardly from the
opposite sides of the housing. Further upward pulling on
25 the cable is prevented and the cable pressure member will
not move toward its open position. Therefore, undesired
release or decoupling of the flat cable from the connector
is stopped. It can be seen that a triangular space 28
(Fig. 1) is formed beneath overhanging extensions 24 which,
30 in effect, defines the limit of movement of the flat cable
in the event that undesired upward forces are applied
thereto.

In the electrical connector described above in
relation to the embodiment of Figures 1-10, housing 1 is
35 provided with cam slots 9 and cable pressure member 3 is
provided with counter cams 17 for assuring a smooth
rotation and displacement of the cable pressure member



95-291 SG

toward its closed, cable pinching position. However, such cam means can be omitted as shown in the embodiment of Figures 11 and 12. In other words, pressure member 3 in Figures 11 and 12 is movable from its open position, as shown, about pivots 29 between opposite sides of the cable pressure member and the insides of the side walls of the housing, but no cam means are provided.

Lastly, it should be understood that the supporting undersurfaces 26 of the support legs 10 of terminals 2 can be readily replaced by a transversely extending portion of housing 1. Still further, soldering tails 14 of terminals 2 may comprise pin-like projections for insertion into appropriate holes in a printed circuit board and for soldering to appropriate circuit traces on the board and/or in the holes.

It will be understood that the invention may be embodied in other specific forms without departing from the spirit or central characteristics thereof. The present examples and embodiments, therefore, are to be considered in all respects as illustrative and not restrictive, and the invention is not to be limited to the details given herein.

This Sheet Has Been Replaced



CLAIMS:

1. An electrical connector for a flat cable (22), comprising:

5 a housing (1) mounting a plurality of terminals (2) in a generally parallel array, the housing having opposite sides (6) and a front end with an opening (8,21) between the sides for receiving an end of the flat cable (22) in engagement with contact portions (13) of the terminals;

10 a pressure member (3) rotatably mounted on the housing (1) for movement between a first position allowing insertion of the flat cable (22) into the opening (8,21) and a second position pressing conductors of the flat cable against the contact portions (13) of the terminals (2); and

15 stop means (24) on the housing (1) preventing release of the flat cable (22) from the electrical connector in the event undesired external forces are applied to the cable which would tend to bias the pressure member (3) toward its first position.

20 2. The electrical connector of claim 1 wherein said stop means comprise overhanging extensions (24) projecting inwardly from the opposite sides (6) of the housing (1).

25 3. The electrical connector of claim 1 wherein said stop means (24) are located on said opposite sides (6) of the housing (1).



This Sheet Has Been Replaced



95-291 SG

4. The electrical connector of claim 3 wherein said pressure member (3) includes an actuating portion (15) having a width sized to fit between the stop means (24) on the opposite sides of the housing.

5 5. The electrical connector of claim 1, including pivot means (9,17,29) rotatably mounting the pressure member (3) on the housing (1), the pivot means being located rearwardly of said stop means (24).

10 6. The electrical connector of claim 5 wherein said pivot means comprise a pair of pivots (9,17,29) between opposite sides of the pressure member (3) and said opposite sides (6) of the housing (1).

15 7. The electrical connector of claim 1 wherein said pressure member (3) includes a stepped lower surface (25) at the front thereof defining a generally triangular space between the pressure member and the flat cable (22) when the pressure member is in its second position.



This Sheet Has Been Replaced



ABSTRACT:

THIS SHEET HAS BEEN REPLACED


FLAT CABLE CONNECTOR

5 An electrical connector is provided for
terminating a flat cable (22). The connector includes a
housing (1) mounting a plurality of terminals (2) in a
generally parallel array. The housing has opposite sides
(6) and a front end, with an opening (8,21) between the
sides for receiving an end of the flat cable (22) in
engagement with contact portions (13) of the terminals (2).
10 A pressure member (3) is rotatably mounted on the housing
for movement between a first position allowing insertion of
the flat cable (22) into the opening (8,21) and a second
position pressing conductors of the flat cable against the
contact portions (13) of the terminals (2). Overhanging
15 extensions (24) project inwardly from the opposite sides
(6) of the housing (1) to prevent release of the flat cable
(22) from the connector in the event undesired external
forces are applied to the cable which would tend to bias
the pressure member (3) toward its first position.

This Sheet Has Been Replaced



FIG. 1



This Sheet Has Been Replaced



THIS SHEET HAS BEEN

FIG. 2




FIG. 3





FIG. 4



This Sheet Has Been Replaced



THIS SHEET HAS BEEN
REPLACED




FIG. 6





FIG. 7



This Sheet Has Been Replaced



(4-5)

THIS SHEET HAS BEEN
REPLACED

FIG. 8




FIG. 9





FIG. 10



This Sheet Has Been Replaced



(5-5)

THIS SHEET HAS BEEN
REPLACED

FIG. 11






FIG. 12




This Sheet Has Been Replaced



96100128

1
SPECIFICATION

FLAT CABLE CONNECTOR



Field of the Invention

This invention generally relates to the art of electrical connectors and, particularly, to an electrical connector for terminating a flat cable, such as a flat flexible cable, printed circuit board or the like, without requiring any insertion force.

Background of the Invention

There are a wide variety of zero insertion force electrical connectors particularly adapted for terminating flat cables, such as flexible flat cables, flexible printed circuit boards and the like. These electrical connectors conventionally have a housing mounting a plurality of terminals in a generally parallel array. An actuator, such as a pressure member, is used to press the flexible flat cable, flexible printed circuit board or the like against contact portions of the terminals.

Heretofore, some actuators have been designed to be pushed in and pulled out of the connector housings. Such designs require the application of insertion forces to the flat cables. In addition, such designs have inevitably resulted in an increase in the overall size of the connectors.

Consequently, some zero insertion force electrical connectors for flat cables have been designed with actuators or pressure members which are rotatably or pivotally mounted on the housing for movement between first, open positions allowing free insertion of the cables into the connector housings, and second, closed positions for clamping the flat cables against the contact portions of the terminals.

One of the problems with prior connectors having rotatable actuators or pressure members is the tendency of

05 FEB 1997

2

moving the pressure member back toward its open position when undesired external forces are applied to the flexible flat cable. The flat cable tends to raise and rotate the pressure member, thereby releasing the flat cable from the connector. The present invention is directed to solving this problem and preventing undesired releasing or decoupling of the flat cable from the connector when certain external forces are applied to the cable.

Summary of the Invention

An object, therefore, of the invention is to provide a new and improved zero insertion force electrical connector for flat electrical cables, of the character described.

In the exemplary embodiment of the invention, the electrical connector includes a dielectric housing mounting a plurality of terminals in a generally parallel array transversely of the connector. The housing has opposite sides and a front end, with an opening between the sides for receiving an end of the flat cable in engagement with contact portions of the terminals. A pressure member is rotatably mounted on the housing for movement between a first position allowing insertion of the flat cable into the opening and a second position pressing conductors of the flat cable against the contact portions of the terminals. Generally, stop means are provided on the housing to prevent release of the flat cable from the electrical connector in the event undesired external forces are applied to the cable which would tend to bias the pressure member back toward its first position.


More particularly, the stop means are provided by overhanging extensions projecting inwardly from the opposite sides of the housing. The pressure member includes an actuating portion having a width sized to fit between the overhanging extensions at the opposite sides of the housing. A pair of pivots rotatably mount the pressure member on the housing at opposite sides of the pressure

O F F R 1997

3

member. The pivots are located rearwardly of the
overhanging extensions. Lastly, the pressure member
includes a stepped lower surface at the front thereof
defining a generally triangular space between the pressure
5 member and the flat cable when the pressure member is in
its second position.

Other objects, features and advantages of the
invention will be apparent from the following detailed
description taken in connection with the accompanying
10 drawings.



Brief Description of the Drawings

The features of this invention ~~which are~~ believed to be novel are set forth with particularity in the appended claims. The invention, together with its objects and the advantages thereof, may be best understood by reference to the following description taken in conjunction with the accompanying drawings, in which like reference numerals identify like elements in the figures and in which:

FIGURE 1 is a front-to-rear vertical section through the flat cable connector of the invention, with the front of the pressure member broken away;

FIGURE 2 is a top plan view of the housing of the connector;

FIGURE 3 is a front elevational view of the housing of the connector;

FIGURE 4 is a side elevational view of the housing of the connector;

FIGURE 5 is a top plan view of the pressure member;

FIGURE 6 is a front elevational view of the pressure member;

FIGURE 7 is a side elevational view of the pressure member;

FIGURE 8 is an enlarged vertical section taken generally along line H-H in Figure 6;

FIGURE 9 is an enlarged vertical section taken generally along line K-K in Figure 6;

FIGURE 10 is an enlarged vertical section taken generally along line J-J in Figure 6;

FIGURE 11 is a side elevational view of another embodiment of a flat cable connector, with the pressure member in its open position; and

FIGURE 12 is a front-to-rear vertical section through the flat cable connector of Figure 12.

05 FEB 1997

Detailed Description of the Preferred Embodiments

Referring to the drawings in greater detail, Figure 1 shows a first embodiment of a flexible flat cable connector according to the invention. The connector includes a housing 1 mounting a plurality of terminals 2 in a generally parallel array. The housing rotatably mounts an actuator or cable pressure member 3. Details of the housing are shown in Figures 2-4, and details of the cable pressure member are shown in Figures 5-10.

Referring to Figures 2-4 in conjunction with Figure 1, housing 1 is unitarily molded of dielectric material such as plastic or the like. The housing includes a base 5 having a plurality of terminal slots 4 formed therein, opposite side walls 6 molded integrally to opposite lateral edges of base 5, and a top wall 7 extending transversely between opposite side walls 6. Each side wall has a cam slot or track 9 facing upwardly toward top wall 7. As described in greater detail hereinafter, cable pressure member 3 has a counter cam on each opposite side thereof for cooperating with cam slot 9 for guiding the cable pressure member between its rotatable positions.

As seen in Figures 2 and 3, top wall 7 extends short of the front end of housing 1, thereby leaving a space or opening 8 at the front of the housing. The opening coincides with a cable insertion opening, generally designated 21, into which a flexible flat cable 22 can be inserted in the direction of arrow 23 (Fig. 3). Lastly, housing 1 includes stop means in the form of a pair of overhanging extensions 24 projecting inwardly from opposite side walls 6 and overhanging the opposite edges 22a of flexible flat cable 22 as best seen in Figure 3.

Each terminal 2 is stamped from sheet metal material in a bifurcated shape as best seen in Figure 1. The bifurcated shape defines a relatively short upper support leg 10 and a relatively long lower contact leg 11. Support leg 10 has a barb 12, and the terminal is fixed in a respective one of the terminal slots 4 by barb 12 of

support leg 10 biting into an intermediate shelf 1a of the housing. Contact leg 11 has a contact portion 13 projecting from the free end of the leg upwardly toward support leg 10. An L-shaped soldering tail 14 extends rearwardly of the terminal and outwardly of housing 1. The bottom of the L-shaped soldering tail 14 is flush with the bottom surface of base 5 of the housing for soldering to a circuit trace on an appropriate printed circuit board.

Referring to Figures 5-10 in conjunction with Figures 1-4, cable pressure member 3 is unitarily molded of dielectric material, such as plastic or the like. The pressure member includes a major flat plate 15 which is wide enough to span the opening 8 at the front of housing 1. Triangular flanges 16 are molded integrally at opposite sides of flat plate 15. Each triangular flange 16 has a counter cam 17 at the front thereof. Each triangular flange 16 is positioned so that its counter cam 17 confronts the cam slot or track 9 (Fig. 4) in a respective one of the side walls of the housing.

Major flat plate 15 of cable pressure member 3 has a width sized to fit in the space between the opposite overhanging extensions 24 of housing 1 as the cable pressure member moves from a first open position allowing insertion of flat cable 22 into opening 8 in the housing, and a second closed position pressing conductors of the flat cable against contact portions 13 of terminals 2 as shown in Figure 1. As seen in Figures 8 and 10, major flat plate 15 of cable pressure member 3 has a stepped lower surface 25 at the front thereof. In addition, the cable pressure member has projections 18 (Figs. 5-7) projecting outwardly of its opposite sides. Each projection 18 fits into an L-shaped slot 19 (Fig. 2) in the inner surface of one of the side walls 6 of the housing. The cable pressure member also has rounded side projections 20 which form detents to snap over the inside edges of overhanging extensions 24 when the pressure member is moved between its open and closed positions.

05 FEB 1997

7

Cam slots or tracks 9 on housing 1 and counter
cams 17 on cable pressure member 3 cooperate functionally
to guide the cable pressure between its rotatable
positions. Specifically, when the cable pressure member is
5 moved toward its closed position shown in Figure 1, a rear
end 15a (Fig. 8) of the cable pressure member moves under
a comb-like support arrangement defined by the bottom
surfaces 26 (Fig. 1) of support legs 10 of terminals 2. By
this action, flat cable 22 is pinched between the
10 undersurface of the cable pressure member and contact
portions 13 of terminals 2.

Referring back to Figure 1 wherein flexible flat
cable 22 has been inserted into the connector, assume that
the flat cable is pulled upwardly as shown in broken lines
15 by undesired external forces applied to the cable. In a
conventional electrical connector structure, the cable
pressure member would be rotated toward its open position
in the direction indicated by arrow 27. However, according
to the concepts of the present invention in the electrical
connector structure shown herein, the flat cable 22 will
20 move or bend the cable pressure member upwardly only a
small degree until the flat cable is stopped by the
overhanging extensions 24 extending inwardly from the
opposite sides of the housing. Further upward pulling on
the cable is prevented and the cable pressure member will
25 not move toward its open position. Therefore, undesired
release or decoupling of the flat cable from the connector
is stopped. It can be seen that a triangular space 28
(Fig. 1) is formed beneath overhanging extensions 24 which,
30 in effect, defines the limit of movement of the flat cable
in the event that undesired upward forces are applied
thereto.

In the electrical connector described above in
relation to the embodiment of Figures 1-10, housing 1 is
35 provided with cam slots 9 and cable pressure member 3 is
provided with counter cams 17 for assuring a smooth
rotation and displacement of the cable pressure member

HOWEVER, 1997

toward its closed, cable pinching position. cam means can be omitted as shown in the embodiment of Figures 11 and 12. In other words, pressure member 3 in Figures 11 and 12 is movable from its open position, as shown, about pivots 29 between opposite sides of the cable pressure member and the insides of the side walls of the housing, but no cam means are provided.

5
10
15
Lastly, it should be understood that the supporting undersurfaces 26 of the support legs 10 of terminals 2 can be readily replaced by a transversely extending portion of housing 1. Still further, soldering tails 14 of terminals 2 may comprise pin-like projections for insertion into appropriate holes in a printed circuit board and for soldering to appropriate circuit traces on the board and/or in the holes.

20
It will be understood that the invention may be embodied in other specific forms without departing from the spirit or central characteristics thereof. The present examples and embodiments, therefore, are to be considered in all respects as illustrative and not restrictive, and the invention is not to be limited to the details given herein.

THIS SHEET HAS BEEN
REPLACED

9

REPLACEMENT SHEET

05 FEB 1997

CLAIMS:

1. An electrical connector for a flat cable (22), comprising:

5 a housing (1) mounting a plurality of terminals (2) in a generally parallel array, the housing having opposite sides (6) and a front end with an opening (8,21) between the sides for receiving an end of the flat cable (22) in engagement with contact portions (13) of the terminals;

10 a pressure member (3) rotatably mounted on the housing (1) for movement between a first position allowing insertion of the flat cable (22) into the opening (8,21) and a second position pressing conductors of the flat cable against the contact portions (13) of the terminals (2); and

15 stop means (24) on the housing (1) preventing release of the flat cable (22) from the electrical connector in the event undesired external forces are applied to the cable which would tend to bias the pressure member (3) toward its first position.

20 2. The electrical connector of claim 1 wherein said stop means comprise overhanging extensions (24) projecting inwardly from the opposite sides (6) of the housing (1).

25 3. The electrical connector of claim 1 wherein said stop means (24) are located on said opposite sides (6) of the housing (1).



This Sheet Has Been Replaced



THIS SHEET HAS BEEN
REPLACED

10

REPLACEMENT SHEET

05 FEB 1997

4. The electrical connector of claim 3 wherein said pressure member (3) includes an actuating portion (15) having a width sized to fit between the stop means (24) on the opposite sides of the housing.

5 5. The electrical connector of claim 1, including pivot means (9,17,29) rotatably mounting the pressure member (3) on the housing (1), the pivot means being located rearwardly of said stop means (24).


10 6. The electrical connector of claim 5 wherein said pivot means comprise a pair of pivots (9,17,29) between opposite sides of the pressure member (3) and said opposite sides (6) of the housing (1).

15 7. The electrical connector of claim 1 wherein said pressure member (3) includes a stepped lower surface (25) at the front thereof defining a generally triangular space between the pressure member and the flat cable (22) when the pressure member is in its second position.



This Sheet Has Been Replaced





ABSTRACT:

FLAT CABLE CONNECTOR

5 An electrical connector is provided for
terminating a flat cable (22). The connector includes a
housing (1) mounting a plurality of terminals (2) in a
generally parallel array. The housing has opposite sides
(6) and a front end, with an opening (8,21) between the
sides for receiving an end of the flat cable (22) in
engagement with contact portions (13) of the terminals (2).
10 A pressure member (3) is rotatably mounted on the housing
for movement between a first position allowing insertion of
the flat cable (22) into the opening (8,21) and a second
position pressing conductors of the flat cable against the
contact portions (13) of the terminals (2). Overhanging
15 extensions (24) project inwardly from the opposite sides
(6) of the housing (1) to prevent release of the flat cable
(22) from the connector in the event undesired external
forces are applied to the cable which would tend to bias
the pressure member (3) toward its first position.

2

FIG. 2




FIG. 3









FIG. 4







4

FIG. 8




FIG. 9




FIG. 10




FIG. 11





FIG. 12



9610012-8

9

REPLACEMENT SHEET

09 NOV 1999

CLAIMS:

1. An electrical connector for a flat cable (22), comprising:

a housing (1) mounting a plurality of terminals (2) in a generally parallel array, the housing having a cammed slot (9) in opposite side walls (6) and a front end with an opening (8,21) between the sides for receiving an end of the flat cable (22) in engagement with contact portions (13) of the terminals;

a pressure member (3) rotatably mounted on the housing (1) and forced against the cammed slot (9) for movement between a first position allowing insertion of the flat cable (22) into the opening (8,21) and a second position pressing conductors of the flat cable against the contact portions (13) of the terminals (2); and

stop means (24) on the housing (1) comprising overhanging extensions (24) projecting inwardly from the opposite walls (6) of the housing and said pressure member (3) positioned in said cammed slot between said front end and said overhanging extensions and adapted to engage edges (22a) of the end of the flat cable preventing release of the flat cable (22) from the electrical connector in the event undesired external forces are applied to the cable which would tend to bias the pressure member (3) toward its first position.



* C L M S *

9610012-8

9/11/99

09 NOV 1999

2. The electrical connector of claim 1, including pivot means (9,17,29) rotatably mounting the pressure member (3) on the housing (1), the pivot means being located rearwardly of said stop means (24).

3. The electrical connector of claim 2 wherein said pivot means comprise a pair of pivots (9,17,29) between opposite sides of the pressure member (3) and said opposite sides (6) of the housing (1).

4. The electrical connector of claim 1 wherein said pressure member (3) includes a stepped lower surface (25) at the front thereof defining a generally triangular space between the pressure member and the flat cable (22) when the pressure member is in its second position.

