



(51) International Patent Classification:

F04D 25/08 (2006.01) *F04F 5/46* (2006.01)
F04F 5/16 (2006.01)

(21) International Application Number:

PCT/GB2012/052742

(22) International Filing Date:

5 November 2012 (05.11.2012)

(25) Filing Language:

English

(26) Publication Language:

English

(30) Priority Data:

1119500.5 11 November 2011 (11.11.2011) GB
1205576.0 29 March 2012 (29.03.2012) GB

(71) Applicant: **DYSON TECHNOLOGY LIMITED**

[GB/GB]; Intellectual Property Department, Dyson Technology Limited, Tetbury Hill, Malmesbury, Wiltshire SN16 0RP (GB).

(72) Inventors: **DOS REIS, David**; c/o Dyson Technology

Limited, Tetbury Hill, Malmesbury, Wiltshire SN16 0RP (GB). **COWEN, Daniel**; c/o Dyson Technology Limited, Tetbury Hill, Malmesbury, Wiltshire SN16 0RP (GB).

GAMMACK, Peter; c/o Dyson Technology Limited, Tetbury Hill, Malmesbury, Wiltshire SN16 0RP (GB).

(74) **Agents: BOOTH, Andrew** et al.; Dyson Technology Limited, Intellectual Property Department, Tetbury Hill, Malmesbury, Wiltshire SN16 0RP (GB).

(81) **Designated States** (*unless otherwise indicated, for every kind of national protection available*): AE, AG, AL, AM, AO, AT, AU, AZ, BA, BB, BG, BH, BN, BR, BW, BY, BZ, CA, CH, CL, CN, CO, CR, CU, CZ, DE, DK, DM, DO, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, GT, HN, HR, HU, ID, IL, IN, IS, JP, KE, KG, KM, KN, KP, KR, KZ, LA, LC, LK, LR, LS, LT, LU, LY, MA, MD, ME, MG, MK, MN, MW, MX, MY, MZ, NA, NG, NI, NO, NZ, OM, PA, PE, PG, PH, PL, PT, QA, RO, RS, RU, RW, SC, SD, SE, SG, SK, SL, SM, ST, SV, SY, TH, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, ZA, ZM, ZW.

(84) **Designated States** (*unless otherwise indicated, for every kind of regional protection available*): ARIPO (BW, GH, GM, KE, LR, LS, MW, MZ, NA, RW, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, RU, TJ, TM), European (AL, AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HR, HU, IE, IS, IT, LT, LU, LV,

[Continued on next page]

(54) Title: A FAN ASSEMBLY




FIG. 2

(57) **Abstract:** A nozzle for a fan assembly has an air inlet, an annular air outlet, and an interior passage for conveying air from the air inlet to the air outlet. The interior passage is located between an annular inner wall, and an outer wall extending about the inner wall. The inner wall at least partially defines a bore through which air from outside the nozzle is drawn by air emitted from the air outlet. The inner wall is eccentric with respect to the bore. The variation in the cross-sectional area of the interior passage can control the direction in which air is emitted from around the air outlet to reduce turbulence in the air flow generated by the fan assembly.



MC, MK, MT, NL, NO, PL, PT, RO, RS, SE, SI, SK,
SM, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ,
GW, ML, MR, NE, SN, TD, TG).

— *before the expiration of the time limit for amending the
claims and to be republished in the event of receipt of
amendments (Rule 48.2(h))*

Published:

— *with international search report (Art. 21(3))*

(88) Date of publication of the international search report:

14 November 2013