



(43) International Publication Date
11 April 2013 (11.04.2013)

(10) International Publication Number
WO 2013/052008 A1

- (51) International Patent Classification:
G06F 3/033 (2013.01) *H01H 25/04* (2006.01)
- (21) International Application Number:
PCT/SG2012/000205
- (22) International Filing Date:
6 June 2012 (06.06.2012)
- (25) Filing Language: English
- (26) Publication Language: English
- (30) Priority Data:
PCT/SG2011/000350
7 October 2011 (07.10.2011) SG
- (72) Inventor; and
- (71) Applicant : QUEK, Joo Hai [SG/SG]; 60, Joon Hiang Road, Singapore 548347 (SG).
- (74) Agent: PYPRUS PTE LTD; 30 Bideford Road, #07-01 Thongsia Building, Singapore 229922 (SG).
- (81) Designated States (*unless otherwise indicated, for every kind of national protection available*): AE, AG, AL, AM,

AO, AT, AU, AZ, BA, BB, BG, BH, BR, BW, BY, BZ, CA, CH, CL, CN, CO, CR, CU, CZ, DE, DK, DM, DO, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, GT, HN, HR, HU, ID, IL, IN, IS, JP, KE, KG, KM, KN, KP, KR, KZ, LA, LC, LK, LR, LS, LT, LU, LY, MA, MD, ME, MG, MK, MN, MW, MX, MY, MZ, NA, NG, NI, NO, NZ, OM, PE, PG, PH, PL, PT, QA, RO, RS, RU, RW, SC, SD, SE, SG, SK, SL, SM, ST, SV, SY, TH, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, ZA, ZM, ZW.

- (84) Designated States (*unless otherwise indicated, for every kind of regional protection available*): ARIPO (BW, GH, GM, KE, LR, LS, MW, MZ, NA, RW, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, RU, TJ, TM), European (AL, AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HR, HU, IE, IS, IT, LT, LU, LV, MC, MK, MT, NL, NO, PL, PT, RO, RS, SE, SI, SK, SM, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Published:

— with international search report (Art. 21(3))

(54) Title: SELF-CENTERING TACTILE THUMB JOYSTICK FOR USE ON A TOUCH SCREEN




FIG. 4A

(57) Abstract: The present invention provides a self-centering, tactile thumb joystick (100, 100a - 100k, 100m-100p) for use to control a virtual directional pad displayed on a touch screen of an electronic gadget. The thumb joystick (100, 100a - 100k, 100m-100p) is removably mounted on the touch screen so that movement of a puck (140, 140a, 140d, 400) via a stem (141) and a button (110) operates the virtual directional pad to control a software running in the electronic gadget. A resilient member, in the form of an annular spring (150) or garter spring (150a), biasing inwardly against a wall element (126, 126a) formed around an opening (121) of a hollow housing (120) of the thumb joystick (100, 100a - 100k, 100m-100p) centres the puck (140) when a user releases activating the button (110).



WO 2013/052008 A1