



(51) International Patent Classification:
H01G 9/155 (2006.01)

(21) International Application Number:
PCT/RU2011/000251

(22) International Filing Date:
19 April 2011 (19.04.2011)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
2010116079 23 April 2010 (23.04.2010) RU

(71) Applicant (for all designated States except US): **UG INVESTMENT LTD.**; Vanterpool Plaza, 2 Floor, Wickhams Cay I, Road Town, Tortola, 1463603 (VG).

(72) Inventors; and

(75) Inventors/Applicants (for US only): **GINATULIN, Yuriy Midhatovich** [KZ/KZ]; ul. Myrzagalieva, 55b, mkm., Taugul 3, Almaty, 050052 (KZ). **DESYATOV, Andrey Viktorovich** [RU/RU]; ul. B. Akademicheskaya, 37-2-10, Moscow, 125008 (RU). **ASSEYEV, Anton Vladimirovich** [KZ/KZ]; Suyunbaya pr., 263/3-5, Almaty, 050054 (KZ). **KUBYSHKIN, Aleksandr Petrovich** [RU/RU]; Marshala Borzova pr., 11A-38, Shatura, Moskovskaya obl., 140704 (RU). **SIROTIN, Sergey Ivanovich** [RU/RU]; ul. Marshala Tuhachevskogo, 58-1-57, Moscow, 123103 (RU). **BULIBEKOVA, Lyubov Vladimirovna** [KZ/KZ]; ul. Kirpichnozavodskaya, 10-98, Almaty, 050059 (KZ). **LI, Lyubov Densunovna** [KZ/KZ]; ul. Tadzhijskaya, 4, Almaty, 050061 (KZ).

(74) Agent: **POPLEVINA, Nataliya Vasilevna**; P.O. Box 9, Moscow, 123298 (RU).

(81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AO, AT, AU, AZ, BA, BB, BG, BH, BR, BW, BY, BZ, CA, CH, CL, CN, CO, CR, CU, CZ, DE, DK, DM, DO, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, GT, HN, HR, HU, ID, IL, IN, IS, JP, KE, KG, KM, KN, KP, KR, KZ, LA, LC, LK, LR, LS, LT, LU, LY, MA, MD, ME, MG, MK, MN, MW, MX, MY, MZ, NA, NG, NI, NO, NZ, OM, PE, PG, PH, PL, PT, RO, RS, RU, SC, SD, SE, SG, SK, SL, SM, ST, SV, SY, TH, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, ZA, ZM, ZW.

(84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LR, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AL, AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HR, HU, IE, IS, IT, LT, LU, LV, MC, MK, MT, NL, NO, PL, PT, RO, RS, SE, SI, SK, SM, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Published:

- with international search report (Art. 21(3))
- before the expiration of the time limit for amending the claims and to be republished in the event of receipt of amendments (Rule 48.2(h))

(54) Title: A MULTI-ELEMENT ELECTROCHEMICAL CAPACITOR AND A METHOD FOR MANUFACTURING THE SAME

(57) Abstract: The invention relates to electrical engineering. The multi-element electrochemical capacitor of this invention comprises at least one layer of electrical insulation film with alternating opposite-polarity electrode films placed thereon in succession and interspaced by a porous ion-permeable separator, coiled into a roll. Each electrode sheet is a substrate of nonwoven polymer material at a high pore ratio, with at least one electrode in the form of an electrochemically active layer attached to one side or both sides thereof, or embedded within the same. The capacitor also comprises contact electrodes. The method for manufacturing a multi-element electrochemical capacitor comprises preparing electrode mixtures; making opposite-polarity electrode sheets by applying an electrode mixture thereto; placing the opposite-polarity electrode sheets successively on the electrical insulation film layer; coiling the electrode sheets and film layer into a roll around a central electrode; connecting the outer surface of the roll to a peripheral electrode; and impregnating the roll with electrolyte. The technical effect consists in improved specific characteristics of the electrochemical electric energy storage, stability of the specific characteristics, and a longer service life of the capacitor.

