CLAIMS

1. A method of decoding video data, the method comprising:

determining (350) a first block of video data is coded in an inter prediction mode;

determining (352) a first motion vector for the first block of video data;

performing (354) motion vector refinement on the first motion vector for the first block to determine a refined motion vector for the first block of video data, wherein performing the motion vector refinement on the first motion vector for the first block comprises:

determining that a decoder-side motion vector derivation, DMVD, mode is enabled for the first block of video data; and

performing the motion vector refinement on the first motion vector for the first block in accordance with the DMVD mode;

locating (356) a first reference block in a first reference picture using the refined motion vector;

generating (358) a first predictive block for the first block of video data based on the first reference block;

determining that a second block of video data is coded in a mode that utilizes a motion vector associated with the first block as a motion vector predictor;

in response to determining that the second block of video data is coded in the mode that utilizes the motion vector associated with the first block as a motion vector predictor and in response to performing the motion vector refinement on the first motion vector for the first block,

using a different motion vector than the first refined motion vector as the motion vector predictor associated with the first block if the second block is within the same picture as the first block, the different motion vector comprising the first motion vector or a default motion vector; and

using the first refined motion vector as the motion vector predictor associated with the first block if the second block is in a picture following the picture of the first block;

based on the motion vector used as the motion vector predictor associated with the first block, determining (362) a second motion vector for the second block;

locating (364) a second reference block in a second reference picture using the second motion vector; and

decoding a picture of video data based on the first reference block and the second reference block.

2. The method of claim 1, wherein the DMVD mode comprises one of frame-rate up conversion, FRUC, template matching, FRUC bilateral matching, and bilateral template matching.

3. The method of claim 1, further comprising:

determining that the second block is coded in a merge mode;

generating a candidate list for the second block, wherein generating the candidate list for the second block comprises, in response to determining that the first block is coded using bilateral template matching, adding the different motion vector to the candidate list.

4. The method of claim 1, wherein:

determining the first motion vector for the first block of video data comprises determining a first motion vector prediction and a first motion vector difference;

performing motion vector refinement on the first motion vector for the first block comprises refining the first motion vector predictor to determine a first refined motion vector predictor;

setting the refined motion vector for the first block of video data equal to the first refined motion vector predictor plus the first motion vector difference; and

setting the motion vector predictor equal to the first motion vector predictor plus the first motion vector difference.

5. The method of claim 1, further comprising:

adding first residual data to the first predictive block to generate a first reconstructed block of video data;

processing the first reconstructed block of video data to generate a first decoded block of video data;

using the second motion vector, locating a second reference block in a second reference picture;

generating a second predictive block for the second block of video data based on the second reference block;

adding second residual data to the second predictive block to generate a second reconstructed block of video data;

processing the second reconstructed block of video data to generate a second decoded block of video data; and

outputting a picture comprises the first decoded block of video data and the second decoded block of video data.

6. The method of claim 5, wherein outputting the picture comprises one or both of:

storing a copy of the picture in a decoded picture buffer for use as reference picture in decoding subsequent pictures of video data; and

outputting the picture to a display device.

7. The method of claim 1, wherein the method of decoding is performed as part of a reconstruction loop of a video encoding process.

8. A device for decoding video data, the device comprising:

a memory configured to store video data;

one or more processors configured to:

determine (350) a first block of the video data is coded in an inter prediction mode;

determine (352) a first motion vector for the first block of the video data;

perform (354)motion vector refinement on the first motion vector for the first block to determine a refined motion vector for the first block of the video data, wherein performing the motion vector refinement on the first motion vector for the first block comprises:

determining that a decoder-side motion vector derivation, DMVD, mode is enabled for the first block of video data; and

performing the motion vector refinement on the first motion vector for the first block in accordance with the DMVD mode;

locate (356) a first reference block in a first reference picture using the refined motion vector;

generate (358) a first predictive block for the first block of the video data based on the first reference block;

determine that a second block of the video data is coded in a mode that utilizes a motion vector associated with the first block as a motion vector predictor;

in response to determining that the second block of the video data is coded in the mode that utilizes the motion vector associated with the first block as a motion vector predictor and in response to performing the motion vector refinement on the first motion vector for the first block,

use a different motion vector than the first refined motion vector as the motion vector predictor associated with the first block if the second block is within the same picture as the first block, the different motion vector comprising the first motion vector or a default motion vector; and

use the first refined motion vector as the motion vector predictor associated with the first block if the second block is in a picture following the picture of the first block;

based on the motion vector used as the motion vector predictor associated with the first block, determine (362) a second motion vector for the second block; and

locate (364) a second reference block in a second reference picture using the second motion vector; and

decode a picture of the video data based on the first reference block and the second reference block.

9. The device of claim 8, wherein the DMVD mode comprises one of frame-rate up conversion, FRUC, template matching, FRUC bilateral matching, and bilateral template matching.

10. The device of claim 8, wherein the one or more processors are further configured to:

determine the first motion vector for the first block of the video data comprises determining a first motion vector prediction and a first motion vector difference;

perform motion vector refinement on the first motion vector for the first block comprises refining the first motion vector predictor to determine a first refined motion vector predictor;

set the refined motion vector for the first block of the video data equal to the first refined motion vector predictor plus the first motion vector difference; and

set the motion vector predictor equal to the first motion vector predictor plus the first motion vector difference.

11. The device of claim 8, wherein the device comprises a wireless communication device, further comprising a receiver configured to receive encoded video data.

12. The device of claim 11, wherein the wireless communication device comprises a telephone handset and wherein the receiver is configured to demodulate, according to a wireless communication standard, a signal comprising the encoded video data.

13. The device of claim 8, wherein the device comprises a wireless communication device, further comprising a transmitter configured to transmit encoded video data.

14. The device of claim 13, wherein the wireless communication device comprises a telephone handset and wherein the transmitter is configured to modulate, according to a wireless communication standard, a signal comprising the encoded video data.

15. A computer-readable storage medium storing instructions that when executed by one or more processors causes the one or more processors to perform the method according to any one of claims 1 to 7.

16. A method of decoding video data, the method comprising:

determining (350) a first block of video data is coded in an inter prediction mode;

determining (352) a first motion vector for the first block of video data;

performing (354) motion vector refinement on the first motion vector for the first block to determine a refined motion vector for the first block of video data, wherein performing the motion vector refinement on the first motion vector for the first block comprises: determining that a decoder-side motion vector derivation, DMVD, mode is enabled for the first block of video data; and performing the motion vector refinement on the first motion vector for the first block in accordance with the DMVD mode;

locating (356) a first reference block in a first reference picture using the refined motion vector;

storing the first motion vector as a motion vector predictor associated with the first block;

generating (358) a first predictive block for the first block of video data based on the first reference block;

determining that a second block of video data is coded in a mode that utilizes motion vectors associated with previously coded blocks as motion vector predictors, the second block being within the same picture as the first block;

in response to determining that the second block of video data is coded in the mode that utilizes motion vectors associated with previously coded blocks as motion vector predictors,

using the first motion vector as the motion vector predictor associated with the first block;

based on the motion vector used as the motion vector predictor associated with the first block, determining (362) a second motion vector for the second block;

locating (364) a second reference block in a second reference picture using the second motion vector; and

decoding a picture of video data based on the first reference block and the second reference block.

17. The method of claim 16, wherein the DMVD mode comprises one of frame-rate up conversion, FRUC, template matching, FRUC bilateral matching, and bilateral template matching.

18. The method of claim 16, further comprising:

generating a candidate list for the second block, wherein generating the candidate list for the second block comprises, in response to determining that the first block is coded using bilateral template matching, adding the first motion vector to the candidate list.

19. The method of claim 16, wherein:

determining the refined motion vector for the first block of video data comprises determining a first motion vector predictor and a first motion vector difference;

performing the motion vector refinement on the first motion vector for the first block comprises refining the first motion vector predictor to determine a first refined motion vector predictor; and

setting the refined motion vector for the first block of video data equal to the first refined motion vector predictor plus the first motion vector difference.

20. The method of claim 16, further comprising receiving an index value indicative of the first motion vector associated with the first block.

21. The method of claim 20, wherein outputting the picture comprises one or both of:

storing a copy of the picture in a decoded picture buffer for use as reference picture in decoding subsequent pictures of video data; and

outputting the picture to a display device.

22. The method of claim 16, wherein the method of decoding is performed as part of a reconstruction loop of a video encoding process.

23. A device for decoding video data, the device comprising:
a memory configured to store video data;
one or more processors configured to:

determine (350) a first block of the video data is coded in an inter prediction mode;

determine (352) a first motion vector for the first block of the video data;

perform (354) motion vector refinement on the first motion vector for the first block to determine a refined motion vector for the first block of the video data, wherein performing the motion vector refinement on the first motion vector for the first block comprises:

determining that a decoder-side motion vector derivation, DMVD, mode is enabled for the first block of the video data; and performing the motion vector refinement on the first motion vector for the first block in accordance with the DMVD mode;

locate (356) a first reference block in a first reference picture using the refined motion vector;

store the first motion vector as a motion vector predictor associated with the first block;

generate (358) a first predictive block for the first block of the video data based on the first reference block;

determine that a second block of the video data is coded in a mode that utilizes motion vectors associated with previously coded blocks as motion vector predictors, the second block being within the same picture as the first block;

in response to determining that the second block of the video data is coded in the mode that utilizes motion vectors associated with previously coded blocks as motion vector predictors,

use the first motion vector as the motion vector predictor associated with the first block;

based on the motion vector used as the motion vector predictor associated with the first block, determine (362) a second motion vector for the second block; and

locate (364) a second reference block in a second reference picture using the second motion vector; and

decode a picture of the video data based on the first reference block and the second reference block.

24. The device of claim 23, wherein the DMVD mode comprises one of frame-rate up conversion, FRUC, template matching, FRUC bilateral matching, and bilateral template matching.

25. The device of claim 23, wherein the one or more processors are further configured to:

determine the first motion vector for the first block of the video data comprises determining a first motion vector prediction and a first motion vector difference;

perform motion vector refinement on the first motion vector for the first block comprises refining the first motion vector predictor to determine a first refined motion vector predictor;

set the refined motion vector for the first block of the video data equal to the first refined motion vector predictor plus the first motion vector difference; and

set the motion vector predictor equal to the first motion vector predictor plus the first motion vector difference.

26. The device of claim 23, wherein the device comprises a wireless communication device, further comprising a receiver configured to receive encoded video data.

27. The device of claim 23, wherein the wireless communication device comprises a telephone handset and wherein the receiver is configured to demodulate, according to a wireless communication standard, a signal comprising the encoded video data.

28. The device of claim 23, wherein the device comprises a wireless communication device, further comprising a transmitter configured to transmit encoded video data.

29. The device of claim 28, wherein the wireless communication device comprises a telephone handset and wherein the transmitter is configured to modulate, according to a wireless communication standard, a signal comprising the encoded video data.

30. A computer-readable storage medium storing instructions that when executed by one or more processors causes the one or more processors to perform the method according to any one of claims 16 to 22.