

Description

Title of Invention: TERMINAL BLOCK UNIT, AND MONITORING
SYSTEM USING THE SAME

Technical Field

[0001]

The present invention relates to a novel terminal block unit obtained by combining a data input/output device (a measuring instrument) and a terminal block, and a monitoring system using the terminal block unit.

Background Art

[0002]

In general, in a measurement system, a configuration is adopted in which signal lines connected to many sensors are collected to a "signal input/output apparatus" via a terminal block. The "terminal block" is also used as contact terminals (output ports) for sending control signals to control target apparatuses (hereinafter referred to as "apparatuses to be controlled") based on data acquired from the sensors. That is, many signal lines connected to the sensors and the apparatuses to be controlled are collected to the terminal block provided with the many contact terminals, and the signal lines are connected to the signal input/output apparatus via the terminal block. The

signal input/output apparatus has a function of recording data acquired by the sensors, as a measuring instrument (a data logger), and is connected to a small-sized dedicated terminal (a measurement terminal) for recording measurement data and controlling the apparatuses to be controlled, or a calculator (such as a general-purpose computer in which a data processing program is installed) for processing the recorded data, via an input/output interface.

[0003]

That is, when the general physical connection configuration of a measurement system is simplified, with "sensors or apparatuses to be controlled" as the lower side, and the calculator as the upper side, the configuration can be indicated as:

(a) [sensors or apparatuses to be controlled]-[terminal block]-[signal input/output apparatus]-[measurement terminal]-[calculator]; or

(b) [sensors or apparatuses to be controlled]-[terminal block]-[signal input/output apparatus]-[calculator].

[0004]

Figure 11(A) is a diagram (a picture) showing an appearance shape of a conventional signal input/output apparatus 200. As shown in Figure 11(A), the signal input/output apparatus 200 is configured with an apparatus main body 202, a plurality of terminal units 204 each of which has a plurality of contact terminals.

Figure 11(B) is a diagram schematically showing a state in which contact terminals of the terminal units 204 of the conventional signal input/output apparatus 200 and contact terminals of a terminal block 300 are electrically connected, respectively, by physical signal lines. Terminals of a terminal unit 204 connected with the signal input/output apparatus 200 and terminals 302a on the upper side of the terminal block 300 are connected in order by electrical wires. The terminals 302a on the upper side of the terminal block 300 are installed, facing terminals 302b on the lower side, and the terminals 302b on the lower side are electrically connected to terminals of sensors or apparatuses to be controlled not shown.

[0005]

Figure 12(A) is a diagram showing an example of an electrical wiring diagram in an electric enclosure. In actual connection work, work of connecting terminals by electrical wires according to such a wiring diagram is required. A label has to be attached to each of signal lines connected to the terminals so that all the signal lines are connected to appropriate terminals. Naturally, as the number of signal lines connected to the terminal block increases, wiring is more complicated.

Figure 12(B) is a picture showing a terminal block where a label is attached to each of signal lines connected to terminals.

[0006]

In the case of conducting an experiment on a small scale in a laboratory or the like, a configuration may be adopted in which "stripped signal lines" are directly connected to a signal input/output apparatus without a terminal block. In the case of assuming continuous operation including maintenance work, however, the configuration in which signal lines are connected to many terminals provided on a terminal block first, and wiring is performed from the terminals of the terminal block to input terminals of a signal input/output apparatus, respectively, is common as described above. As described above, many signal lines are connected to the terminal block and the signal input/output apparatus, and wiring can be very complicated. Since these apparatuses are used being accompanied by equipment, for example, a power source, a breaker, a lightning arrestor (an SPD), and an AC adapter that are required according to a system configuration, a configuration in which wiring is installed in one box-shaped casing called an electric enclosure is common.

[0007]

Figure 5(B) is a diagram (a picture) showing an internal configuration of a 64-point measurement electric enclosure shown as a configuration example, the diagram showing the inside of an electric enclosure configured with a commercially available signal input/output

apparatus (R3 Series made by M-System Co., Ltd.) A state is shown in which many wires are physically connected between terminals in an electric enclosure.

Citation List

Patent Literature

[0008]

Patent Literature 1

International Publication No. WO 2020/203672

Summary of Invention

Technical Problem

[0009]

Thus, in the conventional configuration, signal lines are stripped in an electric enclosure, and installation work, maintenance work, reconfiguration work accompanying addition and installation of apparatuses, and the like are accompanied by labor at a work site.

[0010]

Further, since a signal input/output apparatus equipped with general-purpose functions, which can be used for various purposes, is used in the conventional configuration, there may be useless functions that are not used at all, depending on purposes. That is, such over-specifications cause increase in installation, operation, and maintenance costs.

[0011]

For example, for the purpose of only to monitoring physical quantities (temperature, power generation, and the like) measured by sensors without necessity of control, the required functions of an input/output device are only functions as those of a measuring instrument (a data logger) for recording data acquired by the sensors. Further, the function required for the measuring instrument differs depending on whether data acquired by each sensor is an "analog signal" or a "digital signal". In the case of the acquired data being an analog signal, an A/D converter with minimum specifications required according to each purpose is required. In the case of the acquired data being a digital signal, the digital signal can be entered to a measuring instrument as it is. Furthermore, as the conventional example described above, some conventional signal input/output apparatuses can cope in some extent with the case that the number of contact terminals increases, by installing additional terminal units, but the number of terminal units that can be connected is limited.

[0012]

The technical subject that the present invention is to provide a terminal block unit capable of reducing wiring work and wiring mistakes in a terminal block to save labor of installation work, flexibly providing necessary functions and, even if the number of contact terminals increases, flexibly providing the necessary

functions, with high expandability, and provide a monitoring system using such a terminal block unit.

Solution to Problem

[0013]

A terminal block unit according to the present invention is terminal block unit to be a minimum unit for constructing a measurement system using a sensor, or a control system for an apparatus to be monitored and/or controlled, using the measurement system, wherein

the terminal block unit is used, intervening between the sensor or the apparatus to be controlled, which is connected lower than the terminal block unit, and a host apparatus connected higher than the terminal block unit;

the terminal block unit includes a plurality of contact terminals and is electrically connected to the sensor or the apparatus to be controlled, through any of the contact terminals; and

the terminal block unit is configured so that direct connection is possible between the terminal block unit and another terminal block unit and between the terminal block unit and the host apparatus through a common bus.

[0014]

Here, the host apparatus is a small-sized dedicated terminal (a measurement terminal) for recording measurement data acquired by the sensor and controlling an apparatus to be controlled, or a calculator (such as a

general-purpose computer in which a data processing program is installed) for processing the recorded data.

[0015]

The terminal block unit according to the present invention is configured with at least any one of three types of basic units (Type X, Type Y, and Type Z in embodiments described later), and terminal block units are combined and used according to purposes. However, such expandability is provided that, if another basic configuration is further designed, the basic configuration can be added. The basic units can be combined and used according to purposes.

[0016]

In the above configuration, the terminal block unit and the other terminal unit may be configured so that power is supplied from the common bus. This is because, even when a plurality of terminal block units are installed in a switchboard, the necessity of separately preparing a power source is eliminated. If the number of connected terminal block units increases, and power is not sufficient only by power supply from the bus, then a configuration is also possible in which power is supplied from the outside by an AC adapter or the like.

[0017]

In the above configuration, the terminal block unit may be configured to include a plurality of indicators corresponding to the contact terminals, respectively.

This is because, since each contact terminal of the terminal block unit has a function of any of a signal input terminal or output terminal, usability is enhanced by being able to visually grasp the state of each contact by an indicator.

[0018]

In the above configuration, the terminal block unit may be configured to include a connector directly connectable to the other terminal block unit not via wiring. This is because, since wiring is unnecessary, there is an advantage of simplifying installation work and the like.

[0019]

In the above configuration, the terminal block unit may be configured to include a control circuit for, in response to a non-voltage contact output of the sensor connected lower for the host apparatus connected higher, lighting up an indicator corresponding to an input state, and transmitting an input value as digitized data by communication via the bus, according to control from the measurement device. This is a configuration that is applied to a terminal block unit of a type of inputting an output signal from a sensor as a digital signal (Type X).

[0020]

In the above configuration, the terminal block unit may be configured to include a function of receiving an

output value of the sensor as an analog value of a current or voltage, for the host apparatus connected higher to light up an indicator of color or illuminance corresponding to the received input value, and a control circuit for converting the input value to digitized data according to control from the host apparatus to transmit the data to the host apparatus by communication via the bus. This is a configuration that is applied to a terminal block unit of a type of inputting an output signal from a sensor as an analog signal (Type Y).

[0021]

In the above configuration, the terminal block unit may be configured to include a control circuit for performing open-drain non-voltage contact output to the apparatus to be controlled, and lighting up an indicator according to a state of the contact output, by control from the host apparatus connected higher through communication via the bus. This is a configuration that is applied to a terminal block unit of a type of outputting a control signal from a host apparatus to an apparatus to be controlled (Type Z).

[0022]

An electric enclosure according to the present invention is an electric enclosure connecting one or more connected terminal block units and a host apparatus, each of the connected terminal block units and the host apparatus being the terminal block unit and the host

apparatus that are described in any of the above paragraphs, wherein the host apparatus is a measurement terminal, the measurement terminal having a function of recording data outputted from the terminal block unit or the terminal block units. It is not necessarily required to be installed in the electric enclosure. By using the terminal block units according to the present invention in the electric enclosure, the necessity of conventional complicated wiring work is eliminated, and an electric enclosure that looks simple is obtained.

[0023]

A monitoring system according to the present invention is a monitoring system for acquiring states of an electrical circuit provided at a remote place, by a sensor, and collectively displaying the states of the electrical circuit, wherein

the sensor, the terminal block unit and the host apparatus that are described above are installed in a monitoring target area; and

data collected to the host apparatus is received via a telecommunications line.

[0024]

Since it is possible to efficiently collect data of each base by using a terminal block unit of the present invention, it becomes possible to easily construct a monitoring system that is applicable to various purposes.

Advantageous Effects of Invention

[0025]

A terminal block signal input/output apparatus according to the present invention has many advantages such as:

- (1) the measurement unit itself is inexpensive;
 - (2) units other than the measurement unit are unnecessary;
 - (3) it is not necessary to separately provide a terminal block;
 - (4) the electric enclosure is compact;
 - (5) wiring labor costs and cable costs are significant reduced; and
 - (6) cost reduction can be realized by packaging.
- Since unnecessary functions are omitted, significant cost reduction is enabled in comparison with a conventional signal input/output apparatus that is often used with over-specifications.

Brief Description of Drawings

[0026]

[Figure 1] Figures 1(A) to 1(C) are diagrams showing an appearance shape of a casing of a terminal block unit. (A), (B), and (C) show a perspective view, a front view, and a rear view, respectively.

[Figure 2] Both of Figures 2(A) and 2(B) show a state in which a plurality of terminal block units are connected.

[Figure 3] Both of Figures 3(A) and 3(B) show a state in which a host apparatus is connected to the other end of a bus cable 24 that is connected to a terminal block unit.

[Figure 4] Figure 4 is a diagram showing change in color of an indicator 20.

[Figure 5] Figure 5(A) shows an example of configuring a conventional 64-point measurement switchboard (Figure 5(B)) configured with a signal input/output apparatus 200 and a terminal block 300 described with reference to Figure 11, with a terminal block unit 10 shown in the present embodiment without changing the number of measurement points.

Figure 5(B) is a diagram (a picture) showing an internal configuration of a 64-point measurement electric enclosure shown as a configuration example, the diagram showing the inside of an electric enclosure configured with a commercially available signal input/output apparatus (R3 Series made by M-System Co., Ltd.)

[Figure 6] Figure 6 is a diagram showing a system diagram screen applied to remote monitoring of a photovoltaic power generation system configured with a contact input (Type X) terminal block unit.

[Figure 7] Figure 7 is a conceptual diagram showing an example of, by arranging a set of measurement equipment provided with a measurement or monitoring/control system constructed using a terminal block unit of the present invention in various places, constructing a system in

which necessary data is transmitted to a cloud data management server from each base to enable data viewing from a remote place.

[Figure 8] Figure 8 is a diagram showing an example of applying a monitoring system of the present embodiment to a monitoring system in a vinyl house.

[Figure 9] Figure 9(A) is a diagram showing an example of applying the monitoring system of the present embodiment to a central monitoring system in a building. Figure 9(B) is a diagram showing an example of applying the monitoring system of the present embodiment to a restroom use situation monitoring system.

[Figure 10] Figure 10(A) is a diagram showing an example of applying the monitoring system of the present embodiment to a corrosion monitoring system. Figure 10(B) is a diagram showing an example of applying the monitoring system of the present embodiment to an inventory monitoring system.

[Figure 11] Figure 11(A) is a diagram (a picture) showing an appearance shape of a conventional signal input/output apparatus 200. Figure 11(B) is a diagram schematically showing a state in which contact terminals of the terminal units 204 of the conventional signal input/output apparatus 200 and contact terminals of a terminal block 300 are electrically connected, respectively, by physical signal lines.

[Figure 12] Figure 12(A) is a diagram showing an example of an electrical wiring diagram in an electric enclosure. Figure 12(B) is a picture showing a terminal block where a label is attached to each of signal lines connected to terminals.

Description of Embodiments

[0027]

Embodiments of the present invention will be described below with reference to drawings. Any of the embodiments below, however, does not give limited interpretation in recognition of the spirit of the present invention. The same or the same kind of members will be given the same reference sign, and description thereof may be omitted.

[0028]

(First embodiment)

Figures 1(A) to 1(C) are diagrams showing an appearance shape of a casing of a terminal block unit. (A), (B), and (C) show a perspective view, a front view, and a rear view, respectively.

The terminal block unit 10 has a plurality of contact terminals 12 on the front. On the left and right side faces of the casing, common connectors 14 and 16 are provided. On the upper face side, an electrification lamp 18 showing being electrified and a plurality of indicators 20 showing states of the terminals are

provided. The number of contact terminals differs according to design. The example of Figure 1 is a type with sixteen contact terminals.

[0029]

Though there are a plurality of types of terminal block units depending on functions thereof, casings of all the types can be common to have the same appearance shape. Therefore, manufacturing costs are lowered, and, when terminal block units having a plurality of functions are combined and used, simple and unified design is realized as a whole. For example, the casing can be configured, with a size of 150 mm in width (not including a connector portion), 60 mm in depth, and 32 mm in height.

[0030]

As shown in Figure 1(C), a USB-C connector is provided on the back face of the casing. The transmission speed of USB-C is faster than the speeds of other conventional USB standards, and is superior in the power supply control function. Therefore, it can be used for a power source of the terminal block unit 10. However, USB-C is an example, and other bus connectors are not excluded. This bus connector 22 can be used to be connected to a higher host apparatus via a predetermined cable.

[0031]

Here, the plurality of types of terminal block units 10 will be described. The following is a list showing the types of the terminal block units 10.

[0032]

[Types of terminal block units]

(I) Type X: 16-point contact signal measurement type

(II) Type Y: 8-point analog signal measurement type

(III) Type X: 16-point contact signal output type

[0033]

Type X has a function of receiving input of a digital signal (a contact signal) at each of sixteen points, sixteen being is the number of contacts. Type Y has a function of receiving eight analog signals (currents or voltages). Type Z has a function of outputting a control signal (a contact signal) at each of sixteen points, sixteen being the number of contacts.

[0034]

<I. Contact input type (Type X)>

Type X includes a control circuit for, in response to a non-voltage contact output of a sensor connected lower for a host apparatus connected higher, lighting up an indicator corresponding to an input state, and transmitting an input value as digitized data by communication via the bus, according to control from the measurement device. This is a configuration that is applied to a terminal block unit of a type of inputting

an output signal from a sensor as a digital signal (Type X).

[0035]

"Type X" that accepts a digital input signal is provided, for example, with a 32-bit MCU as a control circuit, and can receive digital signals of sixteen channels. There is no conduction among the channels, and one common terminal is provided. An input signal of the control circuit is a non-voltage contact input as described above, and a digital input circuit with an internal power supply of 3.75 V and 3 mA, an ON-current of 0.3 mA or above and an OFF-current of 0.3 mA or below as threshold currents, an ON-voltage of 3 V or below and an OFF-voltage of 4 V or above as threshold voltages, and an input cycle of 10 msec is used.

[0036]

<II. Analog input type (Type Y)>

Type Y may be configured to include a function of receiving an output value of the sensor as an analog value of a current or voltage, for a host apparatus connected higher to light up an indicator of color or illuminance corresponding to the received input value, and a control circuit for converting the input value to digitized data according to control from the host apparatus to transmit the data to the host apparatus by communication via the bus. This is a configuration

applied to a terminal block unit of a type of inputting an output from a sensor as an analog signal (Type Y).

[0037]

"Type Y" that accepts an analog input signal is provided with a 32-bit MCU as a control circuit and an 8-channel A/D converter is provided. As for input of an analog value, 4-20 mA currents or 1-5 V voltages are possible. In Type Y for analog input, it is possible not only to express presence/absence of a signal by blinking but also to express the magnitude of the signal by color or brightness on the indicator 20 corresponding to each terminal.

[0038]

Figure 4 is a diagram showing change in color of the indicator 20. In this example, the indicator 20 is configured so that the color becomes bluer as the current or voltage becomes closer to the lower limit (4 mA/1 V), becomes redder changing from purple as the current or voltage value increases, becomes red or orange in the middle, becomes yellower as the current or voltage becomes closer to the upper limit (20 mA/5 V), and becomes white at the maximum. The indicator 20 may be configured so that not the color but the brightness (illuminance) changes according to the magnitude of the current or voltage.

[0039]

In the case of a photovoltaic power generation system, Type Y can be used for the purpose of acquiring a value of a sensor (a measurement device) that outputs an analog value, for example, a pyranometer or a thermometer. By performing display together with a digital value acquired by Type X, such as an amount of photovoltaic power generation, it is possible to monitor whether a value of power generation is reasonable for solar radiation or not.

[0040]

Since values of solar radiation and temperature are also important in the field of agriculture, Type Y is usable not only for photovoltaic power generation systems but also in other industrial fields. In addition, other typical sensors that acquire data as analog values include: a hygrometer, a water-temperature gauge, a water level meter, a wind vane, a compass, a gyro sensor, a strain gauge, a distance sensor, a barometer, a pressure sensor, an illuminometer, a rain sensor, a rain gauge, a tensiometer, an anemometer, a gas concentration meter, a vibroscope, and an accelerometer but are not limited thereto.

[0041]

<III. Contact output type (Type Z)>

Type Z may be configured to include a control circuit for performing open-drain non-voltage contact output to the apparatus to be controlled, and lighting up

an indicator according to a state of the contact output, by control from a host apparatus connected higher through communication via the bus. This is a configuration applied to a terminal block unit of a type of outputting a control signal from a host apparatus to an apparatus to be controlled (Type Z).

[0042]

In the case of "Type Z" that outputs a digital signal, for example, a 32-bit MCU is provided as a control circuit, and digital signals of sixteen channels can be transmitted. There is no conduction among the channels, and one common terminal is provided. An output signal of the control circuit is an open-drain output (maximum DC of 30 V; total of 1.3 W; maximum output rating of, for example, 0.005 A or below at 24 V, 0.1 A or below at 12 V, and 0.26 A or below at 5 V), and a digital output circuit with an on-resistance of 20 m Ω or below is used. In this example, up to thirty-two units can be connected.

[0043]

For example, it is possible to perform on/off control of a power generation control apparatus (a PCS) used in a photovoltaic power generation system by a Type-Z terminal block unit 10. In a photovoltaic power generation system, "power control rules" for controlling generated power according to an instruction by a power company exist. Therefore, the Type-Z terminal block unit

10 can be used as an apparatus for remotely controlling the PCS.

[0044]

Of course, it is possible to control any apparatus that can be controlled by a contact signal. A different type of terminal block unit may be developed.

[0045]

(Second embodiment)

Both of Figures 2(A) and 2(B) show a state in which a plurality of terminal block units are connected. At the time of connecting terminal block units, different types of terminal block units can be connected by a connection unit C. In the drawings, Type- means "type". As shown in the drawings, connection to a higher host apparatus can be performed using an appropriate bus cable 24.

[0046]

The number of connections, types of connected apparatuses, and order of connection are not restricted, and the apparatuses can be freely connected. When the apparatuses cannot be connected side by side due to constraints of the space in a switchboard, connectors of adjacent apparatuses (the connectors 14 and 16 in Figure 1) may be connected by a connector connecting cable 26. The maximum number of connections is determined by the number of bits of an MCU, or the like. In the case of a 32-bit MCU, up to thirty-two apparatuses can be connected.

In the case of digital input/output, up to 16 channels×32 apparatuses can be connected. In the case of analog input, up to 8 channels×32 apparatuses can be connected.
[0047]

Both of Figures 3(A) and 3(B) show a state in which a host apparatus is connected to the other end of the bus cable 24 that is connected to a terminal block unit. Figure 3(A) shows a state in which the bus cable 24 is connected to a measurement terminal 28, and, beyond the measurement terminal 28, a computer 30 or a smartphone 32 is connected. The smartphone and the measurement terminal are connected via a wireless communication standard such as wireless LAN or Bluetooth (registered trademark).
[0048]

The measurement terminal is a small-sized terminal that is specialized in a function of mainly performing recording of data at a place near a measurement base, like the inside of an electric enclosure, and it is common to perform processing of acquired data in a computer or the like connected higher. However, the bus cable 24 can be connected not to the measurement terminal but directly to the computer 30 as shown in Figure 3(B). In this case, not only data processing but all processing including recording of data is performed on the computer side.
[0049]

Figure 5(A) shows an example of configuring a conventional 64-point measurement switchboard (Figure 5(B)) configured with the signal input/output apparatus 200 and the terminal block 300 described with reference to Figure 11, with the terminal block unit 10 shown in the present embodiment without changing the number of measurement points. Four terminal block units 10 of Type X (16-point digital inputs) are connected. Since each terminal block unit 10 is provided with only a function required for digital measurement, among functions of the signal input/output apparatus 200 (a data logger), the signal input/output apparatus 200 is unnecessary. Further, since each terminal block unit 10 also has a function of connecting signal lines from sensor apparatuses, as a terminal block, the terminal block units 10 are in a simple and compact configuration as a whole and can be stored in an electric enclosure smaller than a conventional one.

[0050]

Figure 6 is a diagram showing a system diagram screen applied to remote monitoring of a photovoltaic power generation system configured with a contact input (Type X) terminal block unit. The system diagram screen is configured to acquire states of a relay and a breaker, which are components for protecting an electrical circuit, and collectively display a state of the electrical circuits. On the electrical circuit, the relay has a

role of detecting an overload/overcurrent/overvoltage or the like and breaking the circuit by the breaker. By collectively monitoring these, it is possible to easily grasp the state of the electrical circuit at a glance even if the number of contacts is huge. It is just like monitoring train operation.

[0051]

It is thought that monitoring of an electrical circuit is in demand not only for photovoltaic power generation systems but also in a wide range of fields. Therefore, from the point of view of monitoring a state of an electrical circuit or a whole system using a sensor, it is also possible to apply a monitoring system configured using a terminal block unit of the present embodiment to technical fields other than the photovoltaic power generation system field.

[0052]

(Third embodiment)

Figure 7 is a conceptual diagram showing an example of, by arranging a set of measurement equipment provided with a measurement or monitoring/control system constructed using a terminal block unit of the present invention in various places, constructing a system in which necessary data is transmitted to a cloud data management server from each base to enable data viewing from a remote place. Since data collected by many sensors is collected to a higher calculator as described

above, it is easy to transmit the data to the cloud data management server through a telecommunications line such as the Internet.

[0053]

(Fourth embodiment) Application examples

- Application example 1 (Monitoring system in vinyl house) -

Figure 8 is a diagram showing an example of applying the monitoring system of the present embodiment to a monitoring system in a vinyl house. An example is shown in which, by arranging a pyranometer, thermometers (four), a CO₂ concentration meter, soil moisture meters (four), and EC meters (three) and connecting two analog-input terminal block units (Type Y), a monitoring system for measuring analog data at thirteen points and causing a monitoring screen in a remote place to perform display through a measurement terminal is configured.

[0054]

- Application example 2 (Central monitoring of building) -

Figure 9(A) is a diagram showing an example of applying the monitoring system of the present embodiment to a central monitoring system in a building. For example, a central monitoring system for a building is constructed with three terminal block units of the analog input type (Type Y) and seven terminal block units of the contact input type (Type Z). In this example, 64 contact

monitoring points (40 points for breakers, 10 points for security, 14 points for door opening/closing), 16 analog monitoring points (8 points for CT power consumption, 8 points for room temperature monitoring) are to be monitored for measurement for the first floor; and 32 contact monitoring points (20 points for breakers, 10 points for security, 2 points for door opening/closing), 8 analog monitoring points (4 points for CT power consumption, 4 points for room temperature monitoring)) are to be monitored for measurement for the second floor.

[0055]

- Application example 3 (Congestion situation monitoring system for restroom) -

Figure 9(B) is a diagram showing an example of applying the monitoring system of the present embodiment to a restroom use situation monitoring system. By arranging human sensors in a restroom, a use situation can be visualized.

[0056]

- Application example 4 (Corrosion monitoring system) -

Figure 10(A) is a diagram showing an example of applying the monitoring system of the present embodiment to a corrosion monitoring system. It has been performed to mount implantable sensors in a structure such as a bridge. It is possible to, by collecting data of the sensor for each base, perform maintenance on

infrastructure before deterioration of buildings progresses.

[0057]

- Application example 5 (Optimization of store inventory)

-

Figure 10(B) is a diagram showing an example of applying the monitoring system of the present embodiment to an inventory monitoring system. If sensors are arranged on product shelves in a store to continuously monitor product inventory, it will lead to reduction of inventory work.

Reference Signs List

[0058]

- 10 Terminal block unit
- 12 Contact terminal
- 14 Connector
- 16 Connector
- 18 Electrification lamp
- 20 Indicator
- 22 Bus connector
- 24 Bus cable
- 26 Connector connecting cable
- 28 Measurement terminal
- 30 Computer
- 32 Smartphone

Claims

[Claim 1]

A terminal block unit to be a minimum unit for constructing a measurement system using a sensor, or a control system for an apparatus to be monitored and/or controlled, using the measurement system, wherein

the terminal block unit is used, intervening between the sensor or the apparatus to be controlled, which is connected lower than the terminal block unit, and a host apparatus connected higher than the terminal block unit;

the terminal block unit comprises a plurality of contact terminals and is electrically connected to the sensor or the apparatus to be controlled, through any of the contact terminals; and

the terminal block unit is configured so that direct connection is possible between the terminal block unit and another terminal block unit and between the terminal block unit and the host apparatus through a common bus.

[Claim 2]

The terminal block unit according to claim 1, wherein the terminal block unit and the other terminal unit are configured so that power is supplied from the common bus.

[Claim 3]

The terminal block unit according to claim 1 or 2, wherein the terminal block unit comprises a plurality of

indicators corresponding to the contact terminals, respectively.

[Claim 4]

The terminal block unit according to any one of claims 1 to 3, comprising a connector directly connectable to the other terminal block unit not via wiring.

[Claim 5]

The terminal block unit according to any one of claim 1 to 4, comprising a control circuit for, in response to a non-voltage contact output of the sensor connected lower for the host apparatus connected higher, lighting up an indicator corresponding to an input state, and transmitting an input value as digitized data by communication via the bus, according to control from the measurement device.

[Claim 6]

The terminal block unit according to any one of claim 1 to 4, having a function of receiving an output value of the sensor as an analog value of a current or voltage, for the host apparatus connected higher to light up an indicator of color or illuminance corresponding to the received input value, and a control circuit for converting the input value to digitized data according to control from the host apparatus to transmit the data to the host apparatus by communication via the bus.

[Claim 7]

The terminal block unit according to any one of claim 1 to 4, comprising a control circuit for performing open-drain non-voltage contact output to the apparatus to be controlled, and lighting up an indicator according to a state of the contact output, by control from the host apparatus connected higher through communication via the bus.

[Claim 8]

An electric enclosure connecting one or more connected terminal block units and a host apparatus, each of the connected terminal block units and the host apparatus being the terminal block unit and the host apparatus according to claim 5 or 6, wherein

the host apparatus is a measurement terminal, the measurement terminal having a function of recording data outputted from the terminal block or the terminal block units.

[Claim 9]

A monitoring system for acquiring states of an electrical circuit provided at a remote place, by a sensor, and collectively displaying the states of the electrical circuit, wherein

the sensor, the terminal block unit and the host apparatus according to claim 5 or 6 are installed in a monitoring target area; and

data collected to the host apparatus is received via a telecommunications line.