

IN-FLIGHT AZIMUTH DETERMINATION

FIELD OF THE PRESENTLY DISCLOSED SUBJECT MATTER

The presently disclosed subject matter relates to moving platform navigation systems.

5 BACKGROUND

In various applications it is desired to determine an azimuth of a moving platform. One common technique of achieving this involves an inertial measurement unit (IMU) incorporated as part of an inertial navigation system (INS). A common IMU configuration includes one accelerometer and one gyro per each of the three
10 platform axes: pitch, roll and yaw. The IMU detects linear acceleration in each axis using the accelerometers and rotation rate in each axis using the gyroscopes. Some IMUs also include magnetometers (likewise, one per each axis) which are used for determining a magnetic field in each axis. The INS utilizes the raw IMU measurements to calculate navigation data including for example, position, velocity
15 and attitude (including azimuth) relative to a reference frame (coordinate system).

GENERAL DESCRIPTION

Azimuth of a platform can be determined on the ground (herein "pre-flight") before launch/takeoff or during flight (herein "in-flight"). For pre-flight azimuth determination, gyrocompassing can be used as known in the art. After completion of
20 the gyrocompassing process, the IMU onboard the platform is aligned with a navigation reference frame related to Earth. For in-flight azimuth determination, an onboard GNSS (e.g. GPS) receiver can be used.

However, in some cases, for various reasons both gyrocompassing and GNSS are unavailable, or their use is undesirable. For example, the use of gyrocompassing
25 as well as GNSS may be avoided in order to reduce costs. Specifically, gyrocompassing is a process that requires an accurate and therefore costly IMU. Furthermore, in some cases GNSS signals may not be available due to signal jamming or signal interference.

-2-

Using other azimuth determination techniques which employ devices external to the platform (e.g. transfer alignment) may also be undesirable as such techniques may introduce various errors during the azimuth determination process, which may be hard to track and/or costly.

5 Further azimuth determination techniques involve using magnetometers. Magnetometers are sensitive to various distortions, which deflect their measurements, causing them to be unreliable. Some distortions result from ground environmental influences which include for example, magnetic fields existing at the launching area, including those created by the launching device. These types of
10 distortions may prevent using a magnetometer for determining azimuth on the ground.

According to the presently disclosed subject it is assumed that initial alignment (alignment between IMU reference frame and navigation reference frame) is not performed. Accordingly a respective transformation matrix between
15 IMU frame and navigation frame is thus not available. Thus, azimuth of the platform cannot be determined by directly transforming IMU measurements to navigation reference frame.

The presently disclosed subject matter includes a method and system directed for calculating azimuth of an airborne platform during flight based on IMU
20 measurements, without using GNSS data, gyrocompassing or magnetometers operating on the ground for determining the azimuth.

Furthermore, according to the presently disclosed subject matter the azimuth of the platform can be determined in case the IMU is aligned with respect to the platform as well as in case the IMU is not mount-aligned with respect to the
25 platform.

According to an aspect of the presently disclosed subject matter there is provided a computer implemented method of in-flight determination of azimuth of an aerial platform, the platform comprising an IMU operatively connected to at least one computer device, the method comprising:

-3-

defining an auxiliary frame (coordinate system) comprising an axis X_{AF} being a projection of an IMU sensor frame axis on a plane defined by two of a navigation frame axes, wherein ψ_s is an angle on the plane, between the projection X_{AF} and a predefined direction on the plane;

5 obtaining data indicative of Earth's magnetic field at the flight area of the aerial platform;

using the at least one computer device for calculating flight direction of a platform in the IMU sensor frame based on IMU acceleration measurements;

during an in-flight phase:

10 using IMU magnetometers for obtaining magnetic field measurements in sensor frame and using the at least one computer device for calculating magnetic field values in the auxiliary reference frame based on the magnetic field values in sensor frame;

15 using the at least one computer device for calculating angle ψ_s based on magnetic field measurements in the auxiliary reference frame and Earth's magnetic field in the flight area, and thereby obtaining a transformation matrix from sensor frame to navigation frame C_{SF}^{NF} ; and

20 using the at least one computer device for calculating azimuth of the platform based on the flight direction in IMU sensor frame, IMU in-flight gyro measurements and the transformation matrix C_{SF}^{NF} .

In addition to the above features, the method according to this aspect of the presently disclosed subject matter can optionally comprise one or more of features (i) to (xiii) below, in any technically possible combination or permutation:

25 i. wherein the navigation frame is a local reference frame with respect to Earth and the plane is a horizontal plane.

ii. wherein the predefined direction is north direction.

iii. wherein the navigation frame is North-East-Down.

-4-

iv. the computer implemented method further comprising storing Earth MF in a data-storage onboard the platform.

v. wherein the sensor frame is not aligned with the platform frame, and the platform is positioned in a substantially vertical orientation, the method further comprising, using IMU accelerometers while on the ground for determining flight direction in the sensor frame based on gravitational vector.

vi. wherein the IMU frame is not aligned with the platform frame, and the platform is positioned in a non-vertical orientation, the method further comprising , using IMU accelerometers immediately after launch for determining flight direction in the sensor frame based on acceleration measurements vector.

vii. wherein the sensor frame is not aligned with the platform frame, the method further comprising:

using IMU accelerometers while on the ground for determining flight direction in the sensor frame based on gravitational vector; and

using IMU accelerometers immediately after launch for determining flight direction in the sensor frame based on the acceleration measurements vector.

viii. wherein calculating magnetic field values in the auxiliary reference frame further comprises:

transforming measured magnetic field values in the sensor frame to the initial sensor frame; and transforming measured magnetic field values in the initial sensor frame to the auxiliary reference frame.

ix. wherein for rectifying distortions in in-flight magnetic field measurements, the method further comprises:

using IMU magnetometers for performing multiple in-flight magnetic field measurements at different times; generating equations, each equation is based on a respective magnetic field measurement, wherein the minimal number of equations is dependent on the number of distortions which are being rectified; and solving the plurality of equations for calculating angle Ψ_s .

-5-

x. The method further comprising:

comparing between IMU orientations at the time of different magnetic field measurements; and confirming that there are sufficient in-flight magnetic field measurements, each taken while IMU assumes a different orientation.

5 xi. wherein distortions include one or more of: bias, scale factor, hard iron distortions; and soft iron distortions.

xii. the method further comprising controlling flight of the platform based on the calculated azimuth.

10 xiii. the method further comprising, controlling flight of the platform based on the calculated azimuth for the purpose of maintaining the platform within a predetermined flight area.

According to another aspect of the presently disclosed subject matter there is provided a navigation system mountable on an aerial platform and configured for in-flight determination of an azimuth of the platform, the navigation system comprising
15 an IMU fixed to the platform and being operatively connected to at least one computer device comprising at least one processor, the navigation system being configured to:

utilize the at least one computer device to define an auxiliary frame (coordinate system) comprising an axis X_{AF} being a projection of an IMU sensor
20 frame axis on a plane defined by two of a navigation frame axes, wherein ψ_g is an angle on the plane, between the projection X_{AF} and a predefined direction on the plane;

obtain data indicative of Earth's magnetic field at the flight area of the aerial platform;

25 utilize IMU accelerometer to measure IMU acceleration and utilize the at least one computer device to calculate flight direction of platform in IMU sensor frame based on the IMU acceleration measurements;

during an in-flight phase:

-6-

utilize IMU magnetometers for obtaining magnetic field measurements in the sensor frame and utilize the at least one computer device to calculate magnetic field values in the auxiliary reference frame based on the magnetic field values in the sensor frame;

- 5 utilize the at least one computer device to calculate angle ψ_s based on magnetic field measurements in the auxiliary reference frame and the Earth's magnetic field in the flight area, and thereby obtain a transformation matrix from the sensor frame to navigation frame C_{SF}^{NF} ; and

- 10 utilize the at least one computer device to calculate azimuth of the platform based on the flight direction in IMU sensor frame, IMU in-flight gyro measurements and the transformation matrix C_{SF}^{NF} .

According to another aspect of the presently disclosed subject matter there is provided a non-transitory program storage device readable by a computer, tangibly embodying a program of instructions executable by the computer to perform a method of in-flight determination of an azimuth of an aerial platform, the platform comprising an IMU operatively connected to at least one computer device; the method comprising:

- 20 defining an auxiliary frame (coordinate system) comprising an axis X_{AF} being a projection of an IMU sensor frame axis on a plane defined by two of a navigation frame axes, wherein ψ_s is an angle on the plane, between the projection X_{AF} and a predefined direction on the plane;

obtaining data indicative of Earth's magnetic field at the flight area of the aerial platform; calculating flight direction of platform in IMU sensor frame based on IMU acceleration measurements;

- 25 during an in-flight phase:

obtaining from IMU magnetometers for magnetic field measurements in the sensor frame and calculating magnetic field values in the auxiliary reference frame based on the magnetic field values in the sensor frame;

-7-

calculating angle Ψ_s based on magnetic field measurements in the auxiliary reference frame and Earth's magnetic field in the flight area, and thereby obtaining a transformation matrix from the sensor frame to navigation frame C_{SF}^{NF} ; and

calculating azimuth of the platform based on the flight direction in the IMU sensor frame, IMU in-flight gyro measurements and the transformation matrix C_{SF}^{NF} .

According to another aspect of the presently disclosed subject matter there is provided a platform comprising a navigation system as described above.

The system, the program storage device, and the platform disclosed herein according to various aspects, can optionally further comprise one or more of features (i) to (xiii) listed above, mutatis mutandis, in any technically possible combination or permutation.

BRIEF DESCRIPTION OF THE DRAWINGS

In order to understand the presently disclosed subject matter and to see how it may be carried out in practice, the subject matter will now be described, by way of non-limiting examples only, with reference to the accompanying drawings, in which:

Fig. 1 is a block diagram schematically illustrating a system, in accordance with some examples of the presently disclosed subject matter;

Fig. 2 is a schematic illustration of a platform comprising a navigation system, in accordance with some examples of the presently disclosed subject matter;

Fig. 3 is a flowchart illustrating operations carried out for calculating platform flight azimuth in accordance with some examples of the presently disclosed subject matter; and

Fig. 4 is a flowchart illustrating operations carried out for calculating platform flight azimuth, assuming distortions in magnetic field measurements cannot be neglected, in accordance with an example of the presently disclosed subject matter.

DETAILED DESCRIPTION

In the drawings and descriptions set forth, identical reference numerals indicate those components that are common to different embodiments or configurations. Components in the drawings are not necessarily drawn to scale.

5 Unless specifically stated otherwise, as apparent from the following discussions, it is appreciated that throughout the specification discussions utilizing terms such as "defining", "obtaining", "calculating", "transforming", "determining" or the like, include action and/or processes of a computer that manipulate and/or transform data into other data, said data represented as physical quantities, e.g.
10 such as electronic quantities, and/or said data representing the physical objects.

The terms "computer", "computer device", "control unit", or the like as disclosed herein should be broadly construed to include any kind of electronic device with data processing circuitry, which includes a computer processing device configured and operable to execute computer instructions stored, for example, on a
15 computer memory being operatively connected thereto. Examples of such a device include: a digital signal processor (DSP), a microcontroller, a field programmable gate array (FPGA), an application specific integrated circuit (ASIC), a laptop computer, a personal computer, a smartphone, etc.

As used herein, the phrase "for example," "such as", "for instance" and
20 variants thereof describe non-limiting embodiments of the presently disclosed subject matter. Reference in the specification to "one case", "some cases", "other cases" or variants thereof means that a particular feature, structure or characteristic described in connection with the embodiment(s) is included in at least one embodiment of the presently disclosed subject matter. Thus the appearance of the
25 phrase "one case", "some cases", "other cases" or variants thereof does not necessarily refer to the same embodiment(s).

It is appreciated that certain features of the presently disclosed subject matter, which are, for clarity, described in the context of separate embodiments, may also be provided in combination in a single embodiment. Conversely, various

features of the presently disclosed subject matter, which are, for brevity, described in the context of a single embodiment, may also be provided separately or in any suitable sub-combination.

In embodiments of the presently disclosed subject matter, fewer, more
5 and/or different stages than those shown in Figs. 3 and 4 may be executed. In
embodiments of the presently disclosed subject matter, one or more stages
illustrated in Figs. 3 and 4 may be executed in a different order and/or one or more
groups of stages may be executed simultaneously. For example, operations
described with reference to blocks 305 and 309 in Fig. 3 can be combined into a
10 combined output (one transformation matrix) and the resulting output can be used
in the calculation of block 315, i.e. multiplying the resulting matrix by the measured
magnetic field vector.

Fig. 1 illustrates a general schematic of the functional layout of the system
architecture in accordance with examples of the presently disclosed subject matter.
15 Components in Fig. 1 can be made up of any combination of software and hardware
and/or firmware that performs the functions as defined and explained herein.
Components in Fig. 1 can be in some examples centralized in one location and in
other examples dispersed over more than one location. In other examples of the
presently disclosed subject matter, the system may comprise fewer, more, and/or
20 different components than those shown in Fig. 1. For example, while Fig. 1 shows a
single computer device, platform (body) 100 as well as system 200 specifically, can
include a plurality of computers (which can be at least partly interconnected), each
dedicated for executing certain operations.

The terms "IMU frame", "IMU sensor frame" and "sensor frame" are used
25 herein interchangeably.

The term "navigation reference frame" is used herein to include any frame of
reference with respect to Earth (e.g. ECEF). For simplicity, in the following
description it is suggested to use a local reference frame with respect to Earth, such
as North-East-Down (NED) or North-West-Up (NWU), however this should not be

-10-

construed as limiting, as transformation from one reference frame to another reference frame is possible, as is well known in the art. It is noted that any reference made to NED in the following description is done by way of example only and should not be construed as limiting.

5 It is noted that any assignment of directions in a coordinate system to X,Y and Z axis is arbitrary and an alternative assignment of the axes can be likewise implemented. E.g. where a first direction is assigned as Y axis instead of X axis, a second direction is assigned as Z axis instead of Y axis and a third direction is assigned as X axis instead of Z axis.

10 Attention is now drawn to **Fig. 1** showing a block diagram schematically illustrating a platform comprising a navigation system, in accordance with some examples of the presently disclosed subject matter. Platform **100** schematically represents various types of airborne vehicles which are capable of being directed to fly in a certain direction, e.g. towards a target. Platform **100** can be for example, a
15 missile, a rocket, some other projectile or an aircraft (e.g. unmanned aerial vehicle).

Platform **100** comprises navigation system **200** configured and operable in general to determine navigation data, the navigation data including azimuth of the platform. According to some examples of the presently disclosed subject matter the navigation system **200** comprises IMU **210**, which comprises in turn IMU
20 subcomponents including: accelerometers **201**, gyros **203** and magnetometers **205**. Each of these IMU subcomponents can be a triple-axis (three-dimensional) device having three respective components, one for each axis, to provide a 9 degree of freedom IMU device.

In those cases where IMU is mount-aligned with the platform (i.e. IMU
25 attitude with respect to a carrying platform is known) IMU measurements can be transformed to the platform frame (based on a suitable transformation matrix as known in the art).

According to some examples of the presently disclosed subject matter, IMU **210** is fixed to platform **100** (e.g. installed inside the platform) without mount-

-11-

aligning the IMU relative to the platform (referred to herein as "non-aligned IMU"). According to other examples, IMU **210** is mount-aligned with respect to the platform.

In some cases it may be desired to refrain from executing a mount-alignment process for determining transformation between the IMU frame and the platform frame. This allows in some cases to use a less accurate IMU (which otherwise may have been required for the mount-alignment process) and a much simpler and cheaper installation process of the IMU device in the platform. In addition, some IMU mount-alignment methods involve the use of external alignment devices. Using such devices may introduce, during the alignment process various misalignment errors, which may be hard to track. Therefore, It may be desired to refrain from IMU alignment using external alignment devices, in order to avoid such potential errors.

Navigation system **200** can comprise or be otherwise operatively connected to one or more (two, three, four, etc.) computer processing devices **220** comprising a processing circuitry configured and operable to calculate navigation data from received IMU data input. Specifically, according to the presently disclosed subject matter, computer processing device **220** is configured and operable to determine a flight azimuth of platform **100** based on measurements received from IMU **210**, where the IMU can be either mount-aligned or non-aligned.

Computer processing device **220** can comprise for example azimuth determination module **224** configured and operable for calculating azimuth of platform **100** based on IMU measurements. According to some examples computer processing device **220** can further comprise or be otherwise operatively connected to platform maneuvering controller **226** configured and operable to generate maneuvering instructions directed for controlling the heading of the platform to maintain its course in a desired direction based on the calculated azimuth. Instructions generated by platform maneuvering controller **226** can be provided to one or more platform control sub-systems **230** (including for example a tail rudder or other movable platforms) configured and operable, responsive to the instructions, to maneuver the platform to a desired direction.

It is noted that Fig. 1 is functional block diagram showing only functional components which are relevant to the presently disclosed subject matter. In reality, platform 100 comprises many other components related to other functionalities of the platforms (e.g. structural system, power source, various sensors, etc.) which are not described for the sake of simplicity and brevity.

Fig. 3 is a flowchart illustrating operations related to a flight azimuth calculation process, in accordance with an example of the presently disclosed subject matter. Operations described with reference to Fig. 3 (as well as Fig. 4 below) can be executed, for example, with the help of system 200 described above with reference to Fig. 1. Specifically, calculations made as part of the flow in Fig. 3 (and Fig. 4) can be executed for example by computer processing device 220 (e.g. by azimuth determination module 224). It is noted however that any description of operations which is made with reference to at least some of the components in Fig. 1, is done by way of example and for the purpose of illustration only and should not be construed as limiting in any way.

At block 301 an IMU (including 9 DOF sensors) is provided on an aerial platform at a fixed attitude with respect to the platform. This operation can be carried out for example at the factory at the time of manufacturing, where during installation or configuration of the platform, an IMU is mounted on the platform (e.g. firmly installed within the platform or otherwise attached thereto). As mentioned above, according to the presently disclosed subject matter transformation matrix from IMU reference frame (herein below "sensor frame", abbreviated "SF") to navigation reference frame (abbreviated "NF") is not known at this stage.

At block 303 magnetic field values (in 3-axis) relative to the NF (MF_{NF} ; herein below also "Earth MF"), at the flight area are obtained. As is well-known in the art, a magnetic field at a certain location on Earth can be obtained based on measurements or based on well-known models. Thus, given a flight area the respective magnetic field at that location on Earth can be obtained. Notably, the MF_{NF} which is used is selected according to the expected flight area, and it can be assumed that Earth's magnetic field does not significantly change during flight.

According to one example, this information can be made accessible to computer processing device **220** designated to operate at a certain area on Earth. MF_{NF} data can be stored for example within computer memory **222**. According to another example, this information can be provided to system **200** at some time after manufacturing, e.g. before launch at a designated location on Earth. In some examples, system **200** can further comprise a communication module of some sort configured and operable to communicate with an external information resource which provides the magnetic field values.

In the following, azimuth of the platform is determined during flight. The azimuth is calculated based on a projection of one axis of initial sensor frame ("ISF", i.e. IMU-sensor frame before launch) on a plane **P** and calculation of an angle Ψ_s between the projection and a predefined direction on the plane. According to one example, plane **P** is a horizontal plane at the launch site and the predefined direction is north direction, however this should not be construed as limiting.

According to some examples of the presently disclosed subject matter, a reference frame is defined (referred to herein below as "auxiliary frame" and abbreviated "AF"). Auxiliary frame is explained with reference to Fig. 2, which shows a schematic illustration of an IMU within a platform positioned before launch. IMU frame is indicated by axes X_{SF} , Y_{SF} , and Z_{SF} . Auxiliary frame is indicated by axes X_{AF} , Y_{AF} and Z_{AF} . Note that X_{AF} axis of the auxiliary frame represents a projection of X_{ISF} (X of ISF) on a horizontal plane of NF. In the current examples NF is North-East-Down (NED), where horizontal plane is X, Y plane in NED. As the leveling angles can be determined, the transformation matrix from AF to NF includes only a single unknown variable, i.e. angle Ψ_s , angle between the X_{AF} and X_{NF} (in the current example north direction). Notably, Z axis direction in auxiliary frame (Z_{AF}) coincides with apparent gravitation direction indicated by axis Z in navigation frame, NED (Z_{NF}).

A transformation matrix between the auxiliary frame and the initial sensor frame (ISF) is determined based on acceleration measurements (by IMU **210**) taken before launch and gravitation (block **305**). Transformation matrix from ISF to AF is determined and the transpose matrix from AF to ISF is determined as well. Notably,

-14-

as the operation of determining a transpose matrix is a well-known mathematical operation, in the following description any calculation of a matrix assumes that the transpose matrix is available as well. Examples of calculation of transformation matrix from AF to ISF are provided below.

5 Equation 1.1:

$$C_{AF}^{ISF} = \begin{bmatrix} 1 & 0 & 0 \\ 0 & \cos(\varphi) & \sin(\varphi) \\ 0 & -\sin(\varphi) & \cos(\varphi) \end{bmatrix} \begin{bmatrix} \cos(\vartheta) & 0 & -\sin(\vartheta) \\ 0 & 1 & 0 \\ \sin(\vartheta) & 0 & \cos(\vartheta) \end{bmatrix}$$

Wherein φ, ϑ — roll and pitch Euler angles in accordance with aircraft Euler angles order convention, and can be calculated as follows:

Equation 1.2 and 1.3:

$$\begin{aligned} 10 \quad g \cdot \sin(\vartheta) &= a_x \\ g \cdot \cos(\vartheta) \cdot \sin(\varphi) &= -a_y \end{aligned}$$

Where:

a_x, a_y, a_z - accelerometers measurements in SF

Apparent gravitation value g can be calculated by equation 1.4:

$$g = \sqrt{a_x^2 + a_y^2 + a_z^2}$$

15 Alternatively, g can be stored and obtained from computer memory 222.

At block 307 flight direction with respect to SF is calculated . Notably, in Figs. 3 and 4 operation 307 is associated with the in-flight phase (assuming non-vertical orientation). However, as shown below in some examples where platform assumes vertical orientation, this operation can be executed during the pre-flight phase.

20 Platform flight direction in IMU frame can be determined based on IMU acceleration measurements provided by accelerometers 201. Notably, it is generally assumed that the platform (e.g. missile) advances such that the platforms nose and the flight direction sufficiently coincide (in the requested accuracy). In case the

-15-

platform is positioned in a substantially vertical orientation, flight direction with respect to SF can be calculated before flight and can be expressed by:

Equation 2.1, flight direction unit vector in SF:

$$\vec{u} = \begin{bmatrix} \frac{a_x}{g} & \frac{a_y}{g} & \frac{a_z}{g} \end{bmatrix}^T$$

5 Note equation 1.4 above where: $g = \sqrt{a_x^2 + a_y^2 + a_z^2}$

In case the platform is positioned in a non-vertical orientation, this can be performed at the initial stage of flight immediately after launch (e.g. less than several seconds) and can be expressed by:

Equation 2.2 flight direction unit vector in SF:

$$10 \quad \vec{u} = \begin{bmatrix} \frac{a_x(t)}{a(t)} & \frac{a_y(t)}{a(t)} & \frac{a_z(t)}{a(t)} \end{bmatrix}^T$$

Where t is time of measurement, and where

$$a(t) = \sqrt{a_x(t)^2 + a_y(t)^2 + a_z(t)^2}$$

Notably, additional IMU measurements are performed in case of a non-vertical orientation.

15 According to some examples, information indicating whether or not the platform is placed in a vertical orientation before launch can be stored in computer memory **222** and used at the time of calculation.

20 In some examples, in the event that the platform is positioned in vertical orientation, both acceleration measurements before and after takeoff can be implemented, e.g. for the purpose of validating the determined flight direction and/or improving accuracy. It is noted that IMU acceleration measurements taken before launch or immediately after launch can be stored and the actual calculation can be made at later stages of the process before the calculation of flight direction with respect to NF is performed.

-16-

If the IMU is mount-aligned with the platform (body) i.e. C_{Body}^{SF} is known, flight direction in sensor frame can be determined by:

Equation 2.3 flight direction unit vector in SF:

$$\vec{u} = C_{Body}^{SF} \begin{bmatrix} 1 \\ 0 \\ 0 \end{bmatrix}$$

5 Calculations according to equations 2.1 and 2.2 can also be implemented when IMU is mount-aligned, e.g. for the purpose of accuracy and/or confirmation.

While the platform is airborne, transformation matrix from ISF (SF before takeoff) to a current SF (SF at a time instant t during flight) is calculated (block 309). As known in the art, this can be accomplished based on IMU angular velocity
10 measurements (measured by IMU gyros 203).

Further during flight, magnetic field in sensor frame (MF_{SF}) values at a time instant t are measured by magnetometers 205 (Block 311). These measurements are made at least once, and as explained further below, in some cases it is repeated multiple times during flight, at multiple time instances. Note that unlike the MF_{NF}
15 values at the flight area, which are provided in NF (see block 303 above), here the MF_{SF} measurements are measured and provided in SF.

As mentioned above, magnetometers suffer from distortions which deflect their measurements. In addition to the distortions mentioned above resulting from ground environmental influences at the launching area, other distortions which
20 influence magnetic field measurements are caused inside the platform (including hard iron distortion and soft iron distortion as known in the art). Furthermore, magnetometers may suffer from an internal error (e.g. sensors biases, scale factor errors, etc.).

Distortions resulting from environmental influences on the ground (e.g. at
25 the launching area) are attenuated in magnetometers operating in a platform after launch while airborne. Furthermore, at least some of the other distortions can be

-17-

estimated and/or attenuated in other ways. Therefore, the MF_{SF} measurements obtained during flight can be rectified and then used as disclosed herein. The following process assumes negligible distortions in MF_{SF} measurements. A variation of this process, which assumes distortions in MF_{SF} measurements cannot be neglected is described below with reference to Fig. 4.

At block 313 the MF in ISF (MF_{ISF}) is calculated based on measured MF_{SF} at time t. This can be accomplished based on the transformation matrix from current SF to ISF expressed by C_{SF}^{ISF} , which has been determined earlier (see block 309), and its multiplication by the measured MF_{SF} at time t (matrix vector multiplication). It is noted that the calculation of transformation matrix from current SF to ISF is performed repeatedly (e.g. at time t when magnetic field MF_{SF} values are measured) and used during the calculation of MF in ISF.

Calculation of magnetic field values in ISF can be expressed by equation 3:

$$\begin{bmatrix} h_X^{ISF}(t) \\ h_Y^{ISF}(t) \\ h_Z^{ISF}(t) \end{bmatrix} = C_{SF}^{ISF} \begin{bmatrix} h_X^{SF}(t) \\ h_Y^{SF}(t) \\ h_Z^{SF}(t) \end{bmatrix}$$

Wherein:

$h_X^{SF}(t), h_Y^{SF}(t), h_Z^{SF}(t)$ - magnetic field measurements (MF_{SF}); and

$h_X^{ISF}(t), h_Y^{ISF}(t), h_Z^{ISF}(t)$ - magnetic field values (MF_{ISF}).

At block 315 MF_{AF} at time t in auxiliary frame AF are calculated based on calculated MF_{ISF} values at time t in ISF and the transformation matrix from ISF to AF determined earlier (see block 305).

Calculating of magnetic field values in AF can be expressed by equation 4:

$$\begin{bmatrix} h_X^{AF}(t) \\ h_Y^{AF}(t) \\ h_Z^{AF}(t) \end{bmatrix} = C_{ISF}^{AF} \begin{bmatrix} h_X^{ISF}(t) \\ h_Y^{ISF}(t) \\ h_Z^{ISF}(t) \end{bmatrix}$$

Where $h_X^{AF}(t), h_Y^{AF}(t), h_Z^{AF}(t)$ - magnetic field values (MF_{AF}).

-18-

At block **317** a transformation matrix from NF to AF is calculated based on MF in AF (known from previous operation **315**) and MF in NF obtained earlier (see block **303**). As mentioned above, the transformation matrix from AF to NF includes a single unknown variable, i.e. angle ψ_s .

5 Expression of transformation matrix from NF to AF can be expressed by:

$e_X^{NF}, e_Y^{NF}, e_Z^{NF}$ - obtained Earth magnetic field values (MF_{NF}).

Equation 5.1:

$$C_{NF}^{AF} = \begin{bmatrix} \cos(\psi_s) & \sin(\psi_s) & 0 \\ -\sin(\psi_s) & \cos(\psi_s) & 0 \\ 0 & 0 & 1 \end{bmatrix}$$

Equation 5.2:

10
$$\begin{bmatrix} h_X^{AF}(t) \\ h_Y^{AF}(t) \\ h_Z^{AF}(t) \end{bmatrix} = C_{NF}^{AF} \begin{bmatrix} e_X^{NF} \\ e_Y^{NF} \\ e_Z^{NF} \end{bmatrix}$$

Equation 5.3:

$$\begin{bmatrix} h_X^{AF}(t) \\ h_Y^{AF}(t) \\ h_Z^{AF}(t) \end{bmatrix} = \begin{bmatrix} \cos(\psi_s) & \sin(\psi_s) & 0 \\ -\sin(\psi_s) & \cos(\psi_s) & 0 \\ 0 & 0 & 1 \end{bmatrix} \begin{bmatrix} e_X^{NF} \\ e_Y^{NF} \\ e_Z^{NF} \end{bmatrix}$$

ψ_s can be now calculated.

At block **319** the transformation matrix from NF to SF is calculated based on
15 the output obtained from operation described above with reference to **305**, **309**,
317.

Calculation of a transformation matrix from NF to SF is expressed by equation
6:

$$C_{NF}^{SF} = C_{ISF}^{SF} C_{AF}^{ISF} C_{NF}^{AF}$$

-19-

Once the transformation matrix from NF to SF is known, flight direction with respect to NF is calculated (block **321**). This can be accomplished by transforming the calculated flight direction in SF, to NF using transformation matrix calculated in **319**.

Calculation of flight direction with respect to NF is expressed by equation 7:

$$5 \quad \begin{bmatrix} u_N \\ u_E \\ u_D \end{bmatrix} = C_{SF}^{NF} \begin{bmatrix} u_x \\ u_y \\ u_z \end{bmatrix}$$

At block **323** azimuth of platform is calculated based on flight direction in NF, which can be calculated for example by equation 8:

$$\text{Azimuth} = \text{atan2}(u_E, u_N)$$

10 In some examples, the calculated azimuth can be used for generating maneuvering instructions for controlling the platform and directing its flight in a desired direction (e.g. by platform maneuvering controller **226** providing instructions to platform control sub-system **230**). In other examples, the platform can be destroyed or diverted in case the azimuth indicates deflection of the platform from an allowed flight area e.g. for safety reasons.

15 As mentioned above various distortions of magnetic field measurements can be estimated in order to reduce their negative effect on the calculated result.

Because the magnetic field measurements may be not accurate (i.e. suffer from different errors such as: biases, scale factors, hard and soft iron distortions as was mentioned above) a plurality of magnetic field measurements can be used at
20 different times to generate a plurality of equations which can be solved to enable rectification of errors.

Fig. 4 is a flowchart illustrating operations carried out for calculating platform flight azimuth assuming distortions in MF_{SF} measurements cannot be neglected, in accordance with an example of the presently disclosed subject matter. Notably, the
25 following is an example aiming to rectify some of the possible distortions. Additional measurements can be used for likewise rectifying additional distortions.

-20-

Operations mentioned with respect to blocks 301, 303, 305, 307, 309 in Fig. 4 are executed in the same manner as described above with reference to Fig. 3.

At block 401 magnetic field (MF_{SF}) values are measured at multiple time instances to obtain multiple MF_{SF} measurements and corresponding equations are
5 generated for a respective measurement.

According to some examples, multiple MF_{SF} measurements are stored in computer memory 222. When the number of measurements is sufficient for the azimuth calculation, the measured MF_{SF} values stored in the computer memory are used for calculating the azimuth. In some examples, the orientations during different
10 MF_{SF} measurements are compared (e.g. based on transformation matrix C_{ISF}^{SF}) in order to confirm that there are sufficient MF_{SF} measurements taken at different orientations to provide the needed independent equations for calculation.

The following is one non-limiting example of a calculation of Ψ_s while taking into consideration various magnetic field errors (distortions).

15 Magnetic field measurements in MF_{SF} before rectification of errors:

$$h_{X_{Meas}}^{SF}(t), h_{Y_{Meas}}^{SF}(t), h_{Z_{Meas}}^{SF}(t)$$

Actual magnetic field in sensor frame (i.e. real magnetic field inside body):

$$h_{X_{Act}}^{SF}(t), h_{Y_{Act}}^{SF}(t), h_{Z_{Act}}^{SF}(t)$$

20 Earth magnetic field values outside of platform (i.e. without influence of errors induced inside body) in sensor frame is expressed by:

$$h_{X_{Earth}}^{SF}(t), h_{Y_{Earth}}^{SF}(t), h_{Z_{Earth}}^{SF}(t)$$

Magnetometers biases:

$$b_X, b_Y, b_Z$$

Magnetometers scale factors:

-21-

$$k_{S_X}, k_{S_Y}, k_{S_Z}$$

Platform magnetic field attenuation factors:

$$k_{B_X}, k_{B_Y}, k_{B_Z}$$

Platform magnetic field:

$$5 \quad d_X, d_Y, d_Z$$

Equation 9.1 shows a relation between actual magnetic field inside platform (body) in sensor frame and measured magnetic field in sensor frame:

$$\begin{bmatrix} h_{X_{Meas}}^{SF}(t) \\ h_{Y_{Meas}}^{SF}(t) \\ h_{Z_{Meas}}^{SF}(t) \end{bmatrix} = \begin{bmatrix} k_{S_X} & 0 & 0 \\ 0 & k_{S_Y} & 0 \\ 0 & 0 & k_{S_Z} \end{bmatrix} \begin{bmatrix} h_{X_{Act}}^{SF}(t) \\ h_{Y_{Act}}^{SF}(t) \\ h_{Z_{Act}}^{SF}(t) \end{bmatrix} + \begin{bmatrix} b_X \\ b_Y \\ b_Z \end{bmatrix}$$

10 Influence of biases b_X, b_Y, b_Z and scale factors $k_{S_X}, k_{S_Y}, k_{S_Z}$, which are internally induced, are considered in equation 9.1.

Equation 9.2 shows a relation between actual magnetic field inside platform (body) in sensor frame and magnetic field outside platform is sensor frame:

$$15 \quad \begin{bmatrix} h_{X_{Act}}^{SF}(t) \\ h_{Y_{Act}}^{SF}(t) \\ h_{Z_{Act}}^{SF}(t) \end{bmatrix} = \begin{bmatrix} k_{B_X} & 0 & 0 \\ 0 & k_{B_Y} & 0 \\ 0 & 0 & k_{B_Z} \end{bmatrix} \begin{bmatrix} h_{X_{Earth}}^{SF}(t) \\ h_{Y_{Earth}}^{SF}(t) \\ h_{Z_{Earth}}^{SF}(t) \end{bmatrix} + \begin{bmatrix} d_X \\ d_Y \\ d_Z \end{bmatrix}$$

Influence of attenuation by body $k_{B_X}, k_{B_Y}, k_{B_Z}$ and constant magnetic field

d_X, d_Y, d_Z , which are internally induced (inside body) are considered in equation 9.2.

Based on equations 9.1 and 9.2, equation 9.3 shows a relation between a
20 measured magnetic field in sensor frame and Earth's magnetic field in sensor frame:

-22-

$$\begin{bmatrix} h_{X_{Meas}}^{SF}(t) \\ h_{Y_{Meas}}^{SF}(t) \\ h_{Z_{Meas}}^{SF}(t) \end{bmatrix} = \begin{bmatrix} k_{S_X} & 0 & 0 \\ 0 & k_{S_Y} & 0 \\ 0 & 0 & k_{S_Z} \end{bmatrix} \left(\begin{bmatrix} k_{B_X} & 0 & 0 \\ 0 & k_{B_Y} & 0 \\ 0 & 0 & k_{B_Z} \end{bmatrix} \begin{bmatrix} h_{X_{Earth}}^{SF}(t) \\ h_{Y_{Earth}}^{SF}(t) \\ h_{Z_{Earth}}^{SF}(t) \end{bmatrix} + \begin{bmatrix} d_X \\ d_Y \\ d_Z \end{bmatrix} \right) + \begin{bmatrix} b_X \\ b_Y \\ b_Z \end{bmatrix}$$

Expression of actual magnetic field on the right side of equation 9.1 is replaced with actual magnetic field inside platform in equation 9.2

5

Designate:

$$\begin{bmatrix} k_X \\ k_Y \\ k_Z \end{bmatrix} = \begin{bmatrix} k_{B_X} \cdot k_{S_X} \\ k_{B_Y} \cdot k_{S_Y} \\ k_{B_Z} \cdot k_{S_Z} \end{bmatrix} \quad \begin{bmatrix} kd_X \\ kd_Y \\ kd_Z \end{bmatrix} = \begin{bmatrix} k_{S_X} \cdot d_X \\ k_{S_Y} \cdot d_Y \\ k_{S_Z} \cdot d_Z \end{bmatrix} \quad \begin{bmatrix} kdb_X \\ kdb_Y \\ kdb_Z \end{bmatrix} = \begin{bmatrix} kd_X \\ kd_Y \\ kd_Z \end{bmatrix} + \begin{bmatrix} b_X \\ b_Y \\ b_Z \end{bmatrix}$$

Rewriting equation 9.3 and generating equation 9.4:

$$\begin{bmatrix} h_{X_{Meas}}^{SF}(t) \\ h_{Y_{Meas}}^{SF}(t) \\ h_{Z_{Meas}}^{SF}(t) \end{bmatrix} = \begin{bmatrix} k_X & 0 & 0 \\ 0 & k_Y & 0 \\ 0 & 0 & k_Z \end{bmatrix} \begin{bmatrix} h_{X_{Earth}}^{SF}(t) \\ h_{Y_{Earth}}^{SF}(t) \\ h_{Z_{Earth}}^{SF}(t) \end{bmatrix} + \begin{bmatrix} kdb_X \\ kdb_Y \\ kdb_Z \end{bmatrix}$$

10

Designate:

$$k1_X = 1/k_X \quad k1_Y = 1/k_Y \quad k1_Z = 1/k_Z$$

$$kdb1_X = kdb_X / k_X \quad ksb1_Y = ksb_Y / k_Y \quad kdb1_Z = kdb_Z / k_Z$$

Rewriting equation 9.4 and generating equation 9.5:

$$\begin{bmatrix} k1_X & 0 & 0 \\ 0 & k1_Y & 0 \\ 0 & 0 & k1_Z \end{bmatrix} \begin{bmatrix} h_{X_{Meas}}^{SF}(t) \\ h_{Y_{Meas}}^{SF}(t) \\ h_{Z_{Meas}}^{SF}(t) \end{bmatrix} = \begin{bmatrix} h_{X_{Earth}}^{SF}(t) \\ h_{Y_{Earth}}^{SF}(t) \\ h_{Z_{Earth}}^{SF}(t) \end{bmatrix} + \begin{bmatrix} kdb1_X \\ kdb1_Y \\ kdb1_Z \end{bmatrix}$$

Rewriting equation 9.5 with NF magnetic field

-23-

$$\begin{bmatrix} k1_X & 0 & 0 \\ 0 & k1_Y & 0 \\ 0 & 0 & k1_Z \end{bmatrix} \begin{bmatrix} h_{X_{Meas}}^{SF}(t) \\ h_{Y_{Meas}}^{SF}(t) \\ h_{Z_{Meas}}^{SF}(t) \end{bmatrix} = C_{ISF}^{SF} C_{AF}^{ISF} C_{NF}^{AF} \begin{bmatrix} e_X^{NF} \\ e_Y^{NF} \\ e_Z^{NF} \end{bmatrix} + \begin{bmatrix} kdb1_X \\ kdb1_Y \\ kdb1_Z \end{bmatrix}$$

As explained above with respect to equation 5.1:

$$C_{NF}^{AF} = \begin{bmatrix} \cos(\psi_S) & \sin(\psi_S) & 0 \\ -\sin(\psi_S) & \cos(\psi_S) & 0 \\ 0 & 0 & 1 \end{bmatrix}$$

and

5 Calculation of C_{ISF}^{SF} is explained with reference to block 309

Calculation of C_{AF}^{ISF} is explained with reference to block 305

Equation 5.1 is merged into equation 9.5 expressed by equation 9.6:

$$\begin{bmatrix} k1_X & 0 & 0 \\ 0 & k1_Y & 0 \\ 0 & 0 & k1_Z \end{bmatrix} \begin{bmatrix} h_{X_{Meas}}^{SF}(t) \\ h_{Y_{Meas}}^{SF}(t) \\ h_{Z_{Meas}}^{SF}(t) \end{bmatrix} = C_{ISF}^{SF} C_{AF}^{ISF} \begin{bmatrix} \cos(\psi_S) & \sin(\psi_S) & 0 \\ -\sin(\psi_S) & \cos(\psi_S) & 0 \\ 0 & 0 & 1 \end{bmatrix} \begin{bmatrix} e_X^{NF} \\ e_Y^{NF} \\ e_Z^{NF} \end{bmatrix} + \begin{bmatrix} kdb1_X \\ kdb1_Y \\ kdb1_Z \end{bmatrix}$$

10

Operations described above with respect to blocks 313 to 317 for ψ_S calculation are expressed by equation 9.6.

The number of required MF_{SF} measurements depends on the number of unknowns, which dictates a minimal number of equations of the type 9.6 which are needed. Notably, assuming a change in orientation is observed between
15 measurements, each MF measurement can provide for three equations, each based on a respective sensor frame axis.

The process described above enables to determine the number of unknowns and accordingly to estimate the number of required MF_{SF} measurements. In the current examples where there are 7 variables (

$k1_x, k1_y, k1_z, kdb1_x, kdb1_y, kdb1_z, \Psi_s)$ at least three MF_{SF} measurements are needed, each taken at a different sensor frame orientation. It is noted that increasing the number of measurements and the number of respective equations can improve the accuracy of calculations. Therefore, in some examples a redundancy
 5 of measurements and respective equations can be used.

At block 403 the set of equations is solved to determine Ψ_s .

Once Ψ_s is calculated, transformation matrix from NF to SF is determined as described above with reference to block 319 in Fig. 3, using Equation 6. Flight direction in NF and azimuth are calculated as described above with reference to
 10 blocks 321 and 323 to determine the flight azimuth.

It will also be understood that the system according to the presently disclosed subject matter may be a suitably programmed computer. Likewise, the presently disclosed subject matter contemplates a computer program being readable by a computer for executing the method of the presently disclosed subject
 15 matter. The presently disclosed subject matter further contemplates a machine-readable non-transitory memory tangibly embodying a program of instructions executable by the machine for executing the method of the presently disclosed subject matter.

It is to be understood that the presently disclosed subject matter is not
 20 limited in its application to the details set forth in the description contained herein or illustrated in the drawings. The presently disclosed subject matter is capable of other embodiments and of being practiced and carried out in various ways. Hence, it is to be understood that the phraseology and terminology employed herein are for the purpose of description and should not be regarded as limiting. As such, those
 25 skilled in the art will appreciate that the conception upon which this disclosure is based may readily be utilized as a basis for designing other structures, methods, and systems for carrying out the several purposes of the present presently disclosed subject matter.

Claims:

1. A computer implemented method of in-flight determination of an azimuth of an aerial platform, the platform comprising an IMU operatively connected to at least one computer device; the method comprising:

5 defining an auxiliary frame comprising an axis X_{AF} being a projection of an IMU sensor frame axis on a plane defined by two of a navigation frame axes, wherein ψ_s is an angle on the plane, between the projection X_{AF} and a predefined direction on the plane;

obtaining data indicative of Earth magnetic field (M_{NF}) at the flight area of
10 the aerial platform;

using the at least one computer device for calculating flight direction of platform in IMU sensor frame based on IMU acceleration measurements;

during an in-flight phase:

15 using IMU magnetometers for obtaining magnetic field measurements in sensor frame and using the at least one computer device for calculating magnetic field values in the auxiliary reference frame based on the magnetic field values in sensor frame;

20 using the at least one computer device for calculating angle ψ_s based on magnetic field measurements in the auxiliary reference frame and Earth's magnetic field in the flight area, and thereby obtaining a transformation matrix from sensor frame to navigation frame C_{SF}^{NF} ; and

using the at least one computer device for calculating azimuth of the platform based on the flight direction in IMU sensor frame, IMU in-flight gyro measurements and the transformation matrix C_{SF}^{NF} .

25 2. The method of claim 1, wherein the navigation frame is a local reference frame with respect to Earth and the plane is a horizontal plane.

3. The method of any one of claims 1 or 2, wherein the predefined direction is north direction.

4. The method of claim 3, wherein the navigation frame is North-East-Down.

5. The method of any one of the preceding claims further comprising storing Earth MF in a data-storage onboard the platform.

5 6. The method of any one of the preceding claims, wherein the sensor frame is not aligned with the platform frame, and the platform is positioned in a substantially vertical orientation, the method further comprising, using IMU accelerometers while on the ground for determining flight direction in sensor frame based on gravitation.

10 7. The method of any one of the preceding claims, wherein the IMU frame is not aligned with the platform frame, and the platform is positioned in a non-vertical orientation, the method further comprising, using IMU accelerometers immediately after launch for determining flight direction in sensor frame based on acceleration measurements vector.

15 8. The method of any one of the preceding claims, wherein the sensor frame is not aligned with the platform frame, the method further comprising:

using IMU accelerometers while on the ground for determining flight direction in sensor frame based on gravitational vector; and

20 using IMU accelerometers immediately after launch for determining flight direction in sensor frame based on acceleration measurements vector.

9. The method of any one of the preceding claims, wherein calculating magnetic field values in the auxiliary reference frame further comprises:

transforming measured magnetic field values in sensor frame to initial sensor frame; and transforming magnetic field values in initial sensor frame to auxiliary
25 reference frame.

10. The method of any one of the preceding claims, wherein for rectifying distortions in in-flight magnetic field measurements, the method further comprises:

-27-

using IMU magnetometers for performing multiple in-flight magnetic field measurements at different times; generating equations, each equation is based on a respective magnetic field measurement, wherein the minimal number of equations is dependent on the number of distortions which are being rectified; and solving the
5 plurality of equations for calculating angle ψ_s .

11. The method of claim 10 further comprising:

comparing between IMU orientations at the time of different magnetic field measurements; and confirming that there are sufficient in-flight magnetic field measurements, each taken while IMU is at a different orientation.

10 12. The method of claim 10, wherein distortions include one or more of: bias; scale factor; hard iron distortions; and soft iron distortions.

13. The method of any one of the preceding claims further comprising controlling flight of the platform based on the calculated azimuth.

14. A navigation system mountable on an aerial platform and configured
15 for in-flight determination of an azimuth of the platform, the navigation system comprising an IMU fixed to the platform and being operatively connected to at least one computer device comprising at least one processor, the navigation system is configured to:

utilize the at least one computer device to define an auxiliary frame
20 comprising an axis X_{AF} being a projection of an IMU sensor frame axis on a plane defined by two of a navigation frame axes, wherein ψ_s is an angle on the plane, between the projection X_{AF} and a predefined direction on the plane;

obtain data indicative of Earth magnetic field at the flight area of the aerial platform;

25 utilize an IMU accelerometer to measure IMU acceleration and utilize the at least one computer device to calculate flight direction of a platform in IMU sensor frame based on the IMU acceleration measurements;

during an in-flight phase:

-28-

utilize IMU magnetometers for obtaining magnetic field measurements in sensor frame and utilize the at least one computer device to calculate magnetic field values in the auxiliary reference frame based on the magnetic field values in sensor frame;

5 utilize the at least one computer device to calculate angle Ψ_s based on magnetic field measurements in the auxiliary reference frame and Earth's magnetic field in the flight area, and thereby obtain a transformation matrix from sensor frame to navigation frame C_{SF}^{NF} ; and

 utilize the at least one computer device to calculate azimuth of the platform
10 based on the flight direction in IMU sensor frame, IMU in-flight gyro measurements and the transformation matrix C_{SF}^{NF} .

15. The navigation system of claim 14, wherein the navigation frame is a local reference frame with respect to Earth and the plane is a horizontal plane.

16. The navigation system of any one of claims 14 or 15, wherein the
15 predefined direction is north direction.

17. The navigation system of claim 16, wherein the navigation frame is North-East-Down.

18. The navigation system of any one of claims 14 to 17 further comprising a data-storage device configured for storing Earth MF in a data-storage
20 onboard the platform.

19. The navigation system of any one of claims 14 to 18, wherein the sensor frame is not aligned with the platform frame, and the platform is positioned in a substantially vertical orientation; the system is further configured to utilize IMU accelerometers while on the ground for determining flight direction in sensor frame
25 based on gravitational vector.

20. The navigation system of any one of claims 14 to 19, wherein the IMU frame is not aligned with the platform frame, and the platform is positioned in a non-vertical orientation; the system is further configured to utilize IMU

-29-

accelerometers immediately after launch for determining flight direction in sensor frame based on acceleration measurements vector.

21. The navigation system of any one of claims 14 to 20, wherein the sensor frame is not aligned with the platform frame, the system is further configured
5 to:

use IMU accelerometers while on the ground for determining flight direction in sensor frame based on gravitational vector; and

use IMU accelerometers immediately after launch for determining flight direction in sensor frame based on acceleration measurements vector.

10 22. The navigation system of any one of claims 14 to 21 is further configured for calculating magnetic field values in the auxiliary reference frame, to:

utilize the at least one computer device for transforming measured magnetic field values in sensor frame to initial sensor frame and for transforming measured magnetic field values initial sensor frame to auxiliary reference frame.

15 23. The navigation system of any one of claims 14 to 22 is further configured for rectifying distortions in in-flight magnetic field measurements, to:

utilize IMU magnetometers for performing multiple in-flight magnetic field measurements at different times; and the at least computer device is configured to:

20 generate equations, each equation is based on a respective magnetic field measurement, wherein the minimal number of equations is dependent on the number of distortions which are being rectified; and solve the equations to thereby calculate angle ψ_s .

24. The system of claim 23, where the at least one computer device is further configured to compare between IMU orientations at the time of different
25 magnetic field measurements and confirm that there are sufficient in-flight magnetic field measurements, each taken while IMU assumes a different orientation.

25. A non-transitory program storage device readable by a computer, tangibly embodying a program of instructions executable by the computer to

—30—

perform a method of in-flight determination of an azimuth of an aerial platform, the platform comprising an IMU operatively connected to at least one computer device; the method comprising:

5 defining an auxiliary frame comprising an axis X_{AF} being a projection of an IMU sensor frame axis on a plane defined by two of a navigation frame axes, wherein ψ_s is an angle on the plane, between the projection X_{AF} and a predefined direction on the plane;

obtaining data indicative of Earth magnetic field at the flight area of the aerial platform;

10 calculating flight direction of platform in IMU sensor frame based on IMU acceleration measurements;

during an in-flight phase:

obtaining from IMU magnetometers for magnetic field measurements in sensor frame and calculating magnetic field values in the auxiliary reference frame
15 based on the magnetic field values in sensor frame;

calculating angle ψ_s based on magnetic field measurements in the auxiliary reference frame and Earth's magnetic field in the flight area, and thereby obtaining a transformation matrix from sensor frame to navigation frame C_{SF}^{NF} ; and

20 calculating azimuth of the platform based on the flight direction in IMU sensor frame, IMU in-flight gyro measurements and the transformation matrix C_{SF}^{NF} .