

METHODS AND SYSTEMS FOR SORTING DROPLETS AND BEADS

CROSS-REFERENCE

[0001] This application claims the benefit of U.S. Provisional Patent Application No. 62/508,219, filed May 18, 2017, which application is entirely incorporated herein by reference.

BACKGROUND

[0002] A sample may be processed for various purposes, such as identification of a type of moiety within the sample. The sample may be a biological sample. Biological samples may be processed, such as for detection of a disease (e.g., cancer) or identification of a particular species. There are various approaches for processing samples, such as polymerase chain reaction (PCR) and sequencing.

[0003] Biological samples may be processed using various reaction environments, such as partitions. Partitions may be wells or droplets. Droplets or wells may enable biological samples to be partitioned and processed separately. For example, such droplets may be fluidically isolated from other droplets, enabling accurate control of respective environments in the droplets.

[0004] A plurality of droplets can be generated such that one or more droplets include cells and/or particles. The cells and/or particles can be of interest for use in various (e.g., single cell) applications, such as nucleic acid amplification and/or sequencing applications.

SUMMARY

[0005] As recognized herein, when a plurality of droplets is generated, some droplets may not include any particles, such as cells and beads. A particle may be a bead, such as a gel bead and/or a cell bead. A particle may be a biological particle, such as a cell or cell derivative. A particle, such as a gel bead, may have a molecular barcode coupled thereto. Thus, recognized herein is a need to sort the plurality of droplets into a first subset of droplets that include particles and a second subset of droplets that do not. In some instances, when a plurality of cell beads is generated, some particles generated with the plurality of cell beads may not include any cells (e.g., non-cell bead). Recognized herein is a need to isolate the plurality of cell beads, such as by sorting a plurality of particles into a first subset of particles that include cells (e.g., cell beads) and a second subset of particles that do not.

[0006] In some examples, the systems and methods for sorting described herein may yield an output comprising mostly singularly occupied droplets (containing a single particle of interest). For example, at least about 90%, 95%, 96%, 97%, 98%, 99%, or more of a plurality of droplets may be singularly occupied droplets. Droplets may be sorted, such as by (i) introducing field-attractable particles (e.g., magnetic particles) into the droplets and subjecting the droplets to a

field (e.g., magnetic field), (ii) subjecting the droplets to a pressure pulse and separating the droplets based on hydrodynamic forces, and/or (iii) directing the droplets to interface physical structures (e.g., having apertures) in a flow path of the droplets and separating the droplets based on mechanical properties (e.g., deformability) of the droplets.

[0007] In some examples, the systems and methods for sorting described herein may yield an output comprising mostly singularly occupied cell beads (containing a single cell). For example, at least about 90%, 95%, 96%, 97%, 98%, 99%, or more of a population of beads (or particles) may be singularly occupied cell beads. Cell beads may be isolated (or sorted), such as by (i) generating cell beads with field-attractable particles (e.g., magnetic particles), such as by polymerizing the droplets containing the field-attractable particles, and subjecting the cell beads to a field (e.g., magnetic field), (ii) subjecting the cell beads to a pressure pulse and separating the cell beads via hydrodynamic forces, and/or (iii) directing the cell beads to interface physical structures (e.g., having apertures) in a flow path of the cell beads and separating the cell beads based on mechanical properties (e.g., deformability) of the cell beads. In some cases, already sorted droplets, which are mostly singularly occupied droplets (e.g., containing a single cell), may be polymerized to generate cell beads that are mostly singularly occupied. In some cases, a plurality of droplets may be selectively polymerized, such that mostly (or only) singularly occupied droplets are polymerized to generate cell beads that are mostly singularly occupied.

[0008] Provided herein are methods and systems for sorting droplets that can isolate droplets that include biological particles (e.g., a cell) and/or other particles (e.g., gel beads, cell beads, etc.) from droplets that do not include biological particles and/or other particles. The methods and systems may isolate droplets that are singularly occupied from droplets that are non-singularly occupied, such as from unoccupied droplets or multiply occupied droplets. In another example, provided herein are methods and systems that can isolate particles that include cells (e.g., cell beads) from particles that do not include cells. The methods and systems may isolate cell beads that are singularly occupied from particles that are non-singularly occupied, such as from unoccupied particles or multiply occupied cell beads. The isolated droplets (that include biological particles and/or other particles) and/or isolated cell beads (that include cells) can be subject to further applications, such as nucleic acid amplification and/or sequencing. Beneficially, such pre-sorting may increase efficiency of downstream applications by significantly saving time and resources (e.g., valuable reagents).

[0009] The methods and systems generally operate by generating a plurality of droplets such that each of the plurality of droplets comprises field-attractable particles. A given droplet in the plurality of droplets may or may not include one or more particles (e.g., biological particles, beads, etc.). Thus, the plurality of droplets comprising field attractable particles can comprise a

first subset of droplets that include one or more particles and a second subset of droplets that do not include any particles. A given droplet in the first subset of droplets that include one or more particles can comprise a sufficiently discrepant number or concentration of field-attractable particles than a given droplet in the second subset of droplets that do not include any particles such that when the plurality of droplets is subject to an electric or magnetic field, the first subset of droplets and the second subset of droplets are separated from each other. In some cases, when the plurality of droplets is subjected to an electric or magnetic field, singularly occupied droplets may be separated from unoccupied droplets and otherwise multiply occupied droplets.

[0010] In some instances, a plurality of particles may be generated with field-attractable particles, such as by polymerizing the plurality of droplets comprising the field-attractable particles. A given particle may or may not include a cell. Thus, the plurality of particles comprising field attractable particles may comprise a first subset of particles (e.g., cell beads) that include cells and a second subset of particles that does not include cells. A given cell bead in the first subset of particles can comprise a sufficiently discrepant number or concentration of field-attractable particles than a given particle in the second subset of particles, such that when the plurality of particles is subject to an electric or magnetic field, the first subset of particles and the second subset of particles are separated from each other. In some cases, when the plurality of particles is subjected to an electric or magnetic field, singularly occupied cell beads may be separated from unoccupied particles and otherwise multiply occupied cell beads.

[0011] In some instances, a plurality of droplets can be generated without field-attractable particles. A given droplet in the plurality of droplets may or may not include one or more particles. Thus, the plurality of droplets can comprise a first subset of droplets that include one or more particles and a second subset of droplets that do not include any particles. The plurality of droplets can be subject to a pressure pulse and the first subset of droplets and the second subset of droplets can be separated from each other via hydrodynamic forces. In some cases, the plurality of droplets can be subject to an electric field, and the first subset and the second subset of droplets can be separated via dielectrophoresis. In some cases, singularly occupied droplets may be separated from unoccupied droplets and otherwise multiply occupied droplets.

[0012] In some instances, a plurality of particles can be generated without field-attractable particles. A given particle in the plurality particles may or may not include one or more cells. Thus, the plurality of particles can comprise a first subset of particles (e.g., cell beads) that include one or more cells and a second subset of particles that do not include any cells. The plurality of particles can be subject to a pressure pulse and the first subset of particles and the second subset of particles can be separated from each other via hydrodynamic forces. In some cases, the plurality of particles can be subject to an electric field, and the first subset and the

second subset can be separated via dielectrophoresis. In some cases, singularly occupied cell beads may be separated from unoccupied particles and otherwise multiply occupied cell beads.

[0013] In some instances, a plurality of droplets comprising a first subset of droplets that include one or more particles and a second subset of droplets that do not include any particles can be sorted via a passive mechanism based on mechanical properties of the droplets, such as the respective deformability properties of the droplets. When the plurality of droplets is directed to pass through one or more apertures, each aperture having a size smaller than a minimum dimension of a droplet, only deforming droplets may pass through the apertures and non-deforming droplets may be trapped on the apertures. Unoccupied droplets may have higher deformability and/or lower surface tension properties compared to occupied droplets, thus allowing occupied droplets to be trapped on one or more apertures, and allowing unoccupied droplets to pass through the one or more apertures, thereby separating the first subset and second subset of droplets from the plurality of droplets.

[0014] In some instances, a plurality of particles comprising a first subset of particles (e.g., cell beads) that include one or more cells and a second subset of particles that do not include any particles can be sorted via a passive mechanism based on mechanical properties of the particles, such as the respective deformability properties (or rigidity) of the particles. When the plurality of particles is directed to pass through one or more apertures, each aperture having a size smaller than a minimum dimension of a particle, only deforming particles may pass through the apertures and non-deforming particles may be trapped on the apertures. Unoccupied particles (e.g., not having cells or their derivatives) may have higher deformability and/or lower surface tension properties compared to cell beads, thus allowing cell beads to be trapped on one or more apertures, and allowing unoccupied particles to pass through the one or more apertures, thereby separating the first subset and second subset of particles from the plurality of particles.

[0015] In an example, provided is a method for sorting droplets, comprising: (a) bringing a first phase in contact with a second phase to generate a plurality of droplets, wherein the first phase and second phase are immiscible, wherein the plurality of droplets comprises field-attractable particles and wherein (i) a first subset of the plurality of droplets includes biological particles or particles having coupled thereto molecular barcodes, and (ii) a second subset of the plurality of droplets does not include the biological particles; (b) directing the plurality of droplets along a first channel towards an intersection of the first channel with a second channel and a third channel; and (c) subjecting the plurality of droplets comprising the field-attractable particles to an electric or magnetic field under conditions sufficient to separate at least a portion of the first subset of the plurality of droplets from at least a portion of the second subset of the plurality of droplets, wherein upon separation, the at least the portion of the first subset of the

plurality of droplets flows along the second channel and the at least the portion of the second subset of the plurality of droplets flows along the third channel.

[0016] In some examples, the second subset of the plurality of droplets does not include the particles having coupled thereto molecular barcodes.

[0017] In some examples, a concentration of the field-attractable particles in the second subset of the plurality of droplets is substantially uniform.

[0018] In some examples, each droplet of the first subset of the plurality of droplets comprises less field attractable particles than each droplet of the second subset of the plurality of droplets. In some examples, wherein the electric or magnetic field induces forces on the second subset of the plurality of droplets that is greater than forces induced on the first subset of the plurality of droplets.

[0019] In some examples, the field-attractable particles are magnetic-field attractable particles. In some examples, the field-attractable particles are paramagnetic particles.

[0020] In some examples, the field-attractable particles are electric-field attractable particles. In some examples, the field-attractable particles are conductive particles.

[0021] In some examples, the first subset of the plurality of droplets includes biological particles and the particles having coupled thereto molecular barcodes. In some examples, the particles having coupled thereto molecular barcodes are beads. In some examples, the beads are gel beads.

[0022] In some examples, the method further comprises, subsequent to (c), subjecting nucleic acid molecules derived from the biological particles in the first subset to nucleic acid sequencing. In some examples, the method further comprises, subsequent to (c), subjecting the first subset of the plurality of droplets to nucleic acid amplification conditions to yield amplification products of the nucleic acid molecules from the biological particles in the first subset. In some examples, the method further comprises subjecting the amplification products to nucleic acid sequencing.

[0023] In some examples, the conditions of the electric or magnetic field sufficient to separate the at least the portion of the first subset of the plurality of droplets and the at least the portion of the second subset of the plurality of droplets are determined based at least in part on a ratio between sizes of the plurality of droplets and sizes of the biological particles and/or particles having coupled thereto molecular barcodes in the first subset of the plurality of droplets.

[0024] In some examples, the plurality of droplets is directed along the first channel using a pressure pulse.

[0025] In some examples, the molecular barcodes are releasably coupled to the particles.

[0026] In some examples, the method further comprises subjecting individual droplets of the first subset of the plurality of droplets to a stimulus to facilitate polymerization in the biological particles. In some examples, the stimulus is an optical stimulus. In some examples, the optical stimulus is a laser or ultraviolet light. In some examples, the stimulus is a chemical stimulus. In some examples, the stimulus is applied prior to the intersection. In some examples, the stimulus is applied along the first channel. In some examples, the stimulus is applied along the second channel. In some examples, the method further comprises (i) detecting the individual droplets and (ii) subjecting the individual droplets to the stimulus upon detecting the individual droplets.

[0027] In some examples, the biological particles are cells enclosed within or comprising a gel or polymer matrix.

[0028] In some examples, the first subset comprises a third subset of droplets each comprising a single biological particle and a fourth subset of droplets each comprising multiple biological particles, the method further comprising: directing the first subset of the plurality of droplets along the second channel towards a second intersection of the second channel with a fourth channel and a fifth channel, and subjecting the first subset to an electric or magnetic field under conditions sufficient to separate at least a portion of the third subset from at least a portion of the fourth subset, wherein upon separation, the at least the portion of the third subset of droplets flows along a fourth channel and the at least the portion of the fourth subset of droplets flows along a fifth channel.

[0029] In another example, provided is a system for sorting droplets, comprising: a fluid flow path comprising a first channel, a second channel and a third channel; a fluid flow unit that is configured to subject a plurality of droplets to flow along the first channel, wherein the plurality of droplets is generated upon bringing a first phase in contact with a second phase, wherein the first phase and second phase are immiscible, wherein the plurality of droplets comprises field-attractable particles, and wherein (i) a first subset of the plurality of droplets includes biological particles or particles having coupled thereto molecular barcodes, and (ii) a second subset of the plurality of droplets does not include the biological particles; a field application unit that is configured to apply an electric or magnetic field; and a controller operatively coupled to the fluid flow unit and the field application unit, wherein the controller is programmed to (i) direct the fluid flow unit to subject the plurality of droplets to flow along the first channel to an intersection of the first channel with the second channel and the third channel, and (ii) direct the field application unit to subject the plurality of droplets comprising the field-attractable particles to the electric or magnetic field under conditions sufficient to separate at least a portion of the first subset of the plurality of droplets from at least a portion of the second subset of the plurality of

droplets, wherein upon separation, the at least the portion of the first subset of the plurality of droplets flows along the second channel and the at least the portion of the second subset of the plurality of droplets flows along the third channel.

[0030] In some examples, the second subset of the plurality of droplets does not include the particles having coupled thereto molecular barcodes.

[0031] In some examples, the field application unit is configured to apply the electric field. In some examples, the field application unit is configured to apply the magnetic field. In some examples, the field application unit is configured to apply the electric field and magnetic field.

[0032] In some examples, the field-attractable particles are magnetic-field attractable particles. In some examples, the field-attractable particles are paramagnetic particles.

[0033] In some examples, the field-attractable particles are electric-field attractable particles. In some examples, the field-attractable particles are conductive particles.

[0034] In some examples, the fluid flow unit includes at least one pump that is configured to provide negative pressure. In some examples, the fluid flow unit includes at least one compressor that is configured to provide positive pressure.

[0035] In some examples, the fluid flow unit is configured to apply a pressure pulse to direct the plurality of droplets along the first channel.

[0036] In some examples, the fluid flow unit is configured to apply a pressure pulse to direct the first or second subset of the plurality of droplets along the second channel or third channel, respectively.

[0037] In some examples, the controller is programmed to direct the fluid flow unit to subject the first subset of the plurality of droplets to a pressure pulse at the intersection to subject the first subset of the plurality of droplets to flow along the second channel.

[0038] In some examples, the fluid flow unit includes an actuator that is configured to subject the plurality of droplets to flow.

[0039] In some examples, the controller is programmed to determine the conditions of the electric or magnetic field sufficient to separate the at least the portion of the first subset of the plurality of droplets and the at least the portion of the second subset of the plurality of droplets based at least in part on a ratio between sizes of the plurality of droplets and/or sizes of the biological particles or particles having coupled thereto molecular barcodes in the first subset of the plurality of droplets.

[0040] In some examples, each droplet of the first subset of the plurality of droplets comprises less field attractable particles than each droplet of the second subset of the plurality of droplets. In some examples, wherein the electric or magnetic field induces forces on the

second subset of the plurality of droplets that is greater than forces induced on the first subset of the plurality of droplets.

[0041] In some examples, the biological particles are cells enclosed within or comprising a gel or polymer matrix.

[0042] In another example, provided is a non-transitory computer-readable medium comprising machine-executable code that, upon execution by one or more computer processors, implements a method for sorting droplets, comprising: (a) bringing a first phase in contact with a second phase to generate a plurality of droplets, wherein the first phase and second phase are immiscible, wherein the plurality of droplets comprises field-attractable particles, and wherein (i) a first subset of the plurality of droplets includes biological particles or particles having coupled thereto molecular barcodes, and (ii) a second subset of the plurality of droplets does not include the biological particles; (b) directing the plurality of droplets along a first channel towards an intersection of the first channel with a second channel and a third channel; and (c) subjecting the plurality of droplets comprising the field-attractable particles to an electric or magnetic field under conditions sufficient to separate at least a portion of the first subset of the plurality of droplets from at least a portion of the second subset of the plurality of droplets, wherein upon separation, the at least the portion of the first subset of the plurality of droplets flows along the second channel and the at least the portion of the second subset of the plurality of droplets flows along the third channel.

[0043] In another example, provided is a method for sorting droplets, comprising: (a) bringing a first phase in contact with a second phase to generate a plurality of droplets, wherein the first phase and second phase are immiscible, and wherein (i) a first subset of the plurality of droplets includes biological particles or particles, which particles comprise molecular barcodes coupled thereto, and (ii) a second subset of the plurality of droplets does not include the biological particles; (b) directing the plurality of droplets along a first channel towards an intersection of the first channel with a second channel and a third channel; and (c) at the intersection, subjecting the plurality of droplets to a pressure pulse under conditions sufficient to separate at least a portion of the first subset of the plurality of droplets from at least a portion of the second subset of the plurality of droplets, wherein upon separation, the at least the portion of the first subset of the plurality of droplets flows along the second channel and the at least the portion of the second subset of the plurality of droplets flows along the third channel.

[0044] In some examples, the second subset of the plurality of droplets does not include the particles having coupled thereto molecular barcodes.

[0045] In some examples, the pressure pulse induces forces on the second subset of the plurality of droplets that is greater than forces induced on the first subset of the plurality of droplets.

[0046] In some examples, the first subset of the plurality of droplets includes biological particles and the particles having coupled thereto molecular barcodes. In some examples, the particles having coupled thereto molecular barcodes are beads. In some examples, the beads are gel beads.

[0047] In some examples, the method further comprises, subsequent to (c), subjecting nucleic acid molecules derived from the biological particles in the first subset to nucleic acid sequencing. In some examples, the method further comprises, subsequent to (c), subjecting the first subset of the plurality of droplets to nucleic acid amplification conditions to yield amplification products of the nucleic acid molecules from the biological particles in the first subset. In some examples, the method further comprises subjecting the amplification products to nucleic acid sequencing.

[0048] In some examples, the molecular barcodes are releasably coupled to the particles.

[0049] In some examples, the method further comprises subjecting individual droplets of the first subset of the plurality of droplets to a stimulus to facilitate polymerization in the biological particles. In some examples, the method further comprises (i) detecting the individual droplets and (ii) subjecting the individual droplets to the stimulus upon detecting the individual droplets.

[0050] In some examples, the biological particles are cells enclosed within or comprising a gel or polymer matrix.

[0051] In another example, provided is a system for sorting droplets, comprising: a fluid flow path comprising a first channel, a second channel and a third channel; a fluid flow unit that is configured to subject a plurality of droplets to flow along the first channel, wherein the plurality of droplets is generated upon bringing a first phase in contact with a second phase, wherein the first phase and second phase are immiscible, and wherein (i) a first subset of the plurality of droplets includes biological particles or particles having coupled thereto molecular barcodes, and (ii) a second subset of the plurality of droplets does not include the biological particles; a pressure application unit that is configured to apply a pressure pulse; and a controller operatively coupled to the fluid flow unit and the pressure application unit, wherein the controller is programmed to (i) direct the fluid flow unit to subject the plurality of droplets to flow along the first channel to an intersection of the first channel with the second channel and the third channel, and (ii) direct the pressure application unit to subject the plurality of droplets to the pressure pulse under conditions sufficient to separate at least a portion of the first subset of the plurality of

droplets from at least a portion of the second subset of the plurality of droplets, wherein upon separation, the at least the portion of the first subset of the plurality of droplets flows along the second channel and the at least the portion of the second subset of the plurality of droplets flows along the third channel.

[0052] In another example, provided is a non-transitory computer-readable medium comprising machine-executable code that, upon execution by one or more computer processors, implements a method for sorting droplets, comprising: (a) bringing a first phase in contact with a second phase to generate a plurality of droplets, wherein the first phase and second phase are immiscible, and wherein (i) a first subset of the plurality of droplets includes biological particles or particles having coupled thereto molecular barcodes, and (ii) a second subset of the plurality of droplets does not include the biological particles; (b) directing the plurality of droplets along a first channel towards an intersection of the first channel with a second channel and a third channel; and (c) subjecting the plurality of droplets to a pressure pulse under conditions sufficient to separate at least a portion of the first subset of the plurality of droplets from at least a portion of the second subset of the plurality of droplets, wherein upon separation, the at least the portion of the first subset of the plurality of droplets flows along the second channel and the at least the portion of the second subset of the plurality of droplets flows along the third channel.

[0053] In another example, provided is a method for droplet processing, comprising: (a) bringing a first phase in contact with a second phase to generate a plurality of droplets, wherein the first phase and second phase are immiscible, wherein (i) a first subset of the plurality of droplets includes biological particles, and (ii) a second subset of the plurality of droplets does not include the biological particles; (b) directing the plurality of droplets along a first channel towards an intersection of the first channel with a second channel and a third channel; (c) prior to the intersection, selectively subjecting individual droplets of the first subset of the plurality of droplets to a stimulus to facilitate polymerization in the biological particles; and (d) separating at least a portion of the first subset of the plurality of droplets from at least a portion of the second subset of the plurality of droplets at the intersection, wherein upon separation, the at least the portion of the first subset of the plurality of droplets flows along the second channel and the at least the portion of the second subset of the plurality of droplets flows along the third channel.

[0054] In some examples, the first subset of the plurality of droplets include particles having coupled thereto molecular barcodes.

[0055] In some examples, the second subset of the plurality of droplets does not include the particles having coupled thereto molecular barcodes.

[0056] In some examples, the method further comprises (i) detecting the individual droplets and (ii) selectively subjecting the individual droplets to the stimulus upon detecting the individual droplets.

[0057] In another example, provided is a method for sorting droplets, comprising: (a) bringing a first phase in contact with a second phase to generate a plurality of droplets, wherein the first phase and second phase are immiscible, wherein the plurality of droplets comprises field-attractable particles and wherein the plurality of droplets comprises (i) a first subset of droplets each including, and not more than, one biological particle, and (ii) a second subset of droplets each either not including any biological particle or including more than one biological particle; (b) directing the plurality of droplets along a first channel towards an intersection of the first channel with a second channel and a third channel; and (c) subjecting the plurality of droplets comprising the field-attractable particles to an electric or magnetic field under conditions sufficient to separate at least a portion of the first subset of the plurality of droplets from at least a portion of the second subset of the plurality of droplets, wherein upon separation, the at least the portion of the first subset of the plurality of droplets flows along the second channel and the at least the portion of the second subset of the plurality of droplets flows along the third channel.

[0058] In some examples, the first subset of the plurality of droplets include particles having coupled thereto molecular barcodes. In some examples, the particles having coupled thereto molecular barcodes are beads. In some examples, the beads are gel beads.

[0059] In some examples, a concentration of the field-attractable particles in droplets of the second subset which do not include any biological particle is substantially uniform.

[0060] In some examples, each droplet of the first subset of the plurality of droplets comprises (i) less field attractable particles than each droplet of the second subset of the plurality of droplets which do not include any biological particle, and (ii) more field attractable particles than each droplet of the second subset of the plurality of droplets which includes more than one biological particle. In some examples, forces induced by the electric or magnetic field on droplets of the second subset which do not include any biological particle is greater than forces induced on the first subset, which forces induced on the first subset are greater than forces induced on droplets of the second subset which includes more than one biological particle.

[0061] In some examples, the field-attractable particles are magnetic-field attractable particles. In some examples, the field-attractable particles are paramagnetic particles.

[0062] In some examples, the field-attractable particles are electric-field attractable particles. In some examples, the field-attractable particles are conductive particles.

[0063] In some examples, the method further comprises, subsequent to (c), subjecting nucleic acid molecules derived from the biological particles in the first subset to nucleic acid sequencing.

[0064] In some examples, the method further comprises, subsequent to (c), subjecting the first subset of the plurality of droplets to nucleic acid amplification conditions to yield amplification products of the nucleic acid molecules from the biological particles in the first subset. In some examples, the method further comprises subjecting the amplification products to nucleic acid sequencing.

[0065] In some examples, the conditions of the electric or magnetic field sufficient to separate the at least the portion of the first subset of the plurality of droplets and the at least the portion of the second subset of the plurality of droplets are determined based at least in part on a ratio between sizes of the plurality of droplets and sizes of the biological particles in the first subset of the plurality of droplets.

[0066] In some examples, the plurality of droplets is directed along the first channel using a pressure pulse.

[0067] In some examples, the method further comprises subjecting individual droplets of the first subset of the plurality of droplets to a stimulus to facilitate polymerization in the biological particles. In some examples, the stimulus is applied prior to the intersection. In some examples, the method further comprises (i) detecting the individual droplets and (ii) subjecting the individual droplets to the stimulus upon detecting the individual droplets.

[0068] In some examples, the biological particles are cells enclosed within or comprising a gel or polymer matrix.

[0069] In another example, provided is a method for sorting droplets, comprising: (a) bringing a first phase in contact with a second phase to generate a plurality of droplets, wherein the first phase and second phase are immiscible, wherein the plurality of droplets comprises (i) a first subset of droplets each including, and not more than, one biological particle, and (ii) a second subset of droplets each either not including any biological particle or including more than one biological particle; (b) directing the plurality of droplets along a first channel towards an intersection of the first channel with a second channel and a third channel; and (c) subjecting the plurality of droplets to a pressure pulse under conditions sufficient to separate at least a portion of the first subset of the plurality of droplets from at least a portion of the second subset of the plurality of droplets, wherein upon separation, the at least the portion of the first subset of the plurality of droplets flows along the second channel and the at least the portion of the second subset of the plurality of droplets flows along the third channel.

[0070] In some examples, the first subset of the plurality of droplets include particles having coupled thereto molecular barcodes. In some examples, the particles having coupled thereto molecular barcodes are beads. In some examples, the beads are gel beads.

[0071] In some examples, forces induced by the pressure pulse on droplets of the second subset which do not include any biological particle is greater than forces induced on the first subset, which forces induced on the first subset are greater than forces induced on droplets of the second subset which includes more than one biological particle.

[0072] In some examples, the method further comprises, subsequent to (c), subjecting nucleic acid molecules derived from the biological particles in the first subset to nucleic acid sequencing. In some examples, the method further comprises, subsequent to (c), subjecting the first subset of the plurality of droplets to nucleic acid amplification conditions to yield amplification products of the nucleic acid molecules from the biological particles in the first subset. In some examples, the method further comprises subjecting the amplification products to nucleic acid sequencing.

[0073] In some examples, the method further comprises subjecting individual droplets of the first subset of the plurality of droplets to a stimulus to facilitate polymerization in the biological particles. In some examples, the method further comprises (i) detecting the individual droplets and (ii) subjecting the individual droplets to the stimulus upon detecting the individual droplets.

[0074] In some examples, the biological particles are cells enclosed within or comprising a gel or polymer matrix.

[0075] In another example, provided is a method for sorting particles, comprising: (a) providing a plurality of particles, wherein the plurality of particles comprises (i) a first subset of particles each including a biological particle from or contents of a plurality of cells and (ii) a second subset of particles each not including a biological particle from or contents of the plurality of cells; and (b) sorting the plurality of particles, thereby isolating at least a portion of the first subset of particles from at least a portion of the second subset of particles.

[0076] In some examples, the first subset of particles comprises a third subset of particles each including, but not more than, one biological particle from the plurality of cells and a fourth subset of particles each including more than one biological particle from the plurality of cells. In some examples, the method further comprises sorting the first subset of particles, thereby isolating at least a portion of the third subset of particles from at least a portion of the fifth subset of particles.

[0077] In some examples, (b) comprises subjecting the plurality of particles to a magnetic or electric field. In some examples, each particle of the plurality of particles comprises field-attractable particles.

[0078] In some examples, wherein (b) comprises subjecting the plurality of particles to a pressure pulse.

[0079] In another example, provided is a method for sorting particles, comprising: (a) providing a plurality of particles generated from a plurality of cells, wherein the plurality of particles comprises (i) a first subset of particles each including, but not more than, one biological particle from or contents of a single cell from the plurality of cells and (ii) a second subset of particles each either not including a biological particle from or contents of the plurality of cells or including more than one biological particle from or contents of the plurality of cells; and (b) sorting the plurality of particles, thereby isolating at least a portion of the first subset of particles from at least a portion of the second subset of particles.

[0080] In some examples, (b) comprises subjecting the plurality of particles to a magnetic or electric field. In some examples, each particle of the plurality of particles comprises field-attractable particles.

[0081] In some examples, (b) comprises subjecting the plurality of particles to a pressure pulse.

[0082] In another example, provided is a method for processing droplets. The method can comprise: providing a plurality of gel beads in a first phase, wherein the plurality of gel beads comprise (i) molecular barcodes and (ii) field-attractable particles; and subjecting the plurality of gel beads comprising the field-attractable particles to an electric or magnetic field under conditions sufficient to separate the plurality of gel beads from at least 50% of the first phase, thereby providing the plurality of gel beads in a second phase that is immiscible with respect to the first phase.

[0083] In some examples, the plurality of gel beads can be separated from at least 60% of the first phase. In some examples, the plurality of gel beads can be separated from at least 80% of the first phase. In some examples, the plurality of gel beads can be separated from at least 90% of the first phase.

[0084] In some examples, the first phase can be an oil phase. In some examples, the second phase can be an aqueous phase.

[0085] In another example, provided is a method for sorting gel beads, comprising: processing a plurality of droplets to generate a plurality of gel beads, wherein the plurality of droplets comprises field-attractable particles and wherein (i) a first subset of the plurality of gel beads includes biological particles or particles having coupled thereto molecular barcodes, and (ii) a

second subset of the plurality of gel beads does not include the biological particles, directing the plurality of gel beads along a first channel towards an intersection of the first channel with a second channel and a third channel; and subjecting the plurality of gel beads to an electric or magnetic field under conditions sufficient to separate the first subset of the plurality of gel beads from the second subset of the plurality of gel beads, wherein upon separation, the first subset of the plurality of gel beads flows along the second channel and the second subset of the plurality of gel beads flows along the third channel.

[0086] In some examples, the processing comprises polymerizing the plurality of droplets.

[0087] In another example, provided is a method for sorting gel beads, comprising: processing a plurality of droplets to generate a plurality of gel beads, wherein (i) a first subset of the plurality of gel beads includes biological particles or particles having coupled thereto molecular barcodes, and (ii) a second subset of the plurality of gel beads does not include the biological particles, directing the plurality of gel beads along a first channel towards an intersection of the first channel with a second channel and a third channel; and at the intersection, subjecting the plurality of gel beads to a pressure pulse under conditions sufficient to separate the first subset of the plurality of gel beads from the second subset of the plurality of gel beads, wherein upon separation, the first subset of the plurality of gel beads flows along the second channel and the second subset of the plurality of gel beads flows along the third channel.

[0087a] In one aspect, the present disclosure refers to a method for sorting droplets, comprising: (a) bringing a first phase in contact with a second phase immiscible with said first phase, to generate a plurality of droplets, wherein said plurality of droplets comprises field attractable particles, and wherein said plurality of droplets comprises (i) a first subset of droplets each including, and not more than, one biological particle, and (ii) a second subset of droplets each having more than one biological particle, wherein said biological particle is a cell, a derivative of a cell, or a constituent of a cell, wherein each droplet of said first subset comprises more field attractable particles than each droplet of said second subset having more than one biological particle; (b) directing said plurality of droplets along a first channel towards an intersection of said first channel with at least a second channel and a third channel; and (c) subjecting said plurality of droplets to an electric or magnetic field under conditions sufficient to separate at least a portion of said first subset of said plurality of droplets from at least a portion of said second subset of said plurality of droplets, wherein upon separation, said at least said portion of said first subset of said plurality of droplets flows along said second channel and said at least said portion of said second subset of said plurality of droplets flows along said third channel.

[0088] Additional examples and advantages of the present disclosure will become readily apparent to those skilled in this art from the following detailed description, wherein only illustrative examples of the present disclosure are shown and described. As will be realized, the present disclosure is capable of other and different examples, and its several details are capable of modifications in various obvious respects, all without departing from the disclosure. Accordingly, the drawings and description are to be regarded as illustrative in nature, and not as restrictive.

INCORPORATION BY REFERENCE

[0089] All publications, patents, and patent applications mentioned in this specification are herein incorporated by reference to the same extent as if each individual publication, patent, or patent application was specifically and individually indicated to be incorporated by reference. To the extent publications and patents or patent applications incorporated by reference contradict the disclosure contained in the specification, the specification is intended to supersede and/or take precedence over any such contradictory material.

BRIEF DESCRIPTION OF THE DRAWINGS

[0090] The novel features of the invention are set forth with particularity in the appended claims. A better understanding of the features and advantages of the present invention will be obtained by reference to the following detailed description that sets forth illustrative embodiments, in which the principles of the invention are utilized, and the accompanying drawings (also “Figure” and “FIG.” herein), of which:

[0091] **FIG. 1** shows an example of a microfluidic channel structure for partitioning individual biological particles.

[0092] **FIG. 2A** shows an example of a microfluidic channel structure for separating occupied droplets from unoccupied droplets.

[0093] **FIG. 2B** shows an example of a multi-stage microfluidic channel structure for separating singularly occupied droplets.

[0094] **FIG. 3** shows another example of a microfluidic channel structure for separating occupied droplets from unoccupied droplets.

[0095] **FIG. 4** shows an example of a microfluidic channel structure for selective polymerization of partitions based on occupancy.

[0096] **FIG. 5** shows another example of a microfluidic channel structure for selective polymerization of partitions based on occupancy.

[0097] **FIG. 6** shows an example of a microfluidic channel structure for selective polymerization of partitions based on droplet size.

[0098] **FIG. 7** shows a flowchart for a method of sorting occupied droplets and unoccupied droplets.

[0099] **FIG. 8** shows a flowchart for another method of sorting occupied droplets and unoccupied droplets.

[00100] **FIG. 9** shows a flowchart for a method of selectively polymerizing occupied droplets.

[00101] **FIG. 10** shows a flowchart for a method of selectively polymerizing appropriately sized droplets.

[00102] **FIG. 11** shows an example of a microfluidic channel structure for separating occupied droplets from unoccupied droplets.

[00103] **FIG. 12** shows an example of a microfluidic channel structure for delivering barcode carrying beads to droplets.

[00104] **FIG. 13** shows an example of a microfluidic channel structure for co-partitioning biological particles and reagents.

[00105] FIG. 14 shows an example of a microfluidic channel structure for the controlled partitioning of beads into discrete droplets.

[00106] FIG. 15 shows an example of a microfluidic channel structure for increased droplet generation throughput.

[00107] FIG. 16 shows another example of a microfluidic channel structure for increased droplet generation throughput.

[00108] FIG. 17A shows a cross-section view of another example of a microfluidic channel structure with a geometric feature for controlled partitioning. FIG. 17B shows a perspective view of the channel structure of FIG. 17A.

[00109] FIG. 18 shows an example computer control system that is programmed or otherwise configured to implement methods provided herein.

[00110] FIG. 19 illustrates an example of a barcode carrying bead.

DETAILED DESCRIPTION

[00111] While various embodiments of the invention have been shown and described herein, it will be obvious to those skilled in the art that such embodiments are provided by way of example only. Numerous variations, changes, and substitutions may occur to those skilled in the art without departing from the invention. It should be understood that various alternatives to the embodiments of the invention described herein may be employed.

[00112] Where values are described as ranges, it will be understood that such disclosure includes the disclosure of all possible sub-ranges within such ranges, as well as specific numerical values that fall within such ranges irrespective of whether a specific numerical value or specific sub-range is expressly stated.

[00113] The term “barcode,” as used herein, generally refers to a label, or identifier, that conveys or is capable of conveying information about an analyte. A barcode can be part of an analyte. A barcode can be independent of an analyte. A barcode can be a tag attached to an analyte (e.g., nucleic acid molecule) or a combination of the tag in addition to an endogenous characteristic of the analyte (e.g., size of the analyte or end sequence(s)). A barcode may be unique. Barcodes can have a variety of different formats. For example, barcodes can include: polynucleotide barcodes; random nucleic acid and/or amino acid sequences; and synthetic nucleic acid and/or amino acid sequences. A barcode can be attached to an analyte in a reversible or irreversible manner. A barcode can be added to, for example, a fragment of a deoxyribonucleic acid (DNA) or ribonucleic acid (RNA) sample before, during, and/or after sequencing of the sample. Barcodes can allow for identification and/or quantification of individual sequencing-reads.

[00114] The term “real time,” as used herein, can refer to a response time of less than about 1 second, a tenth of a second, a hundredth of a second, a millisecond, or less. The response time may be greater than 1 second. In some instances, real time can refer to simultaneous or substantially simultaneous processing, detection or identification.

[00115] The term “subject,” as used herein, generally refers to an animal, such as a mammal (e.g., human) or avian (e.g., bird), or other organism, such as a plant. For example, the subject can be a vertebrate, a mammal, a rodent (e.g., a mouse), a primate, a simian or a human. Animals may include, but are not limited to, farm animals, sport animals, and pets. A subject can be a healthy or asymptomatic individual, an individual that has or is suspected of having a disease (e.g., cancer) or a pre-disposition to the disease, and/or an individual that is in need of therapy or suspected of needing therapy. A subject can be a patient. A subject can be a microorganism or microbe (e.g., bacteria, fungi, archaea, viruses).

[00116] The term “genome,” as used herein, generally refers to genomic information from a subject, which may be, for example, at least a portion or an entirety of a subject’s hereditary information. A genome can be encoded either in DNA or in RNA. A genome can comprise coding regions (e.g., that code for proteins) as well as non-coding regions. A genome can include the sequence of all chromosomes together in an organism. For example, the human genome ordinarily has a total of 46 chromosomes. The sequence of all of these together may constitute a human genome.

[00117] The terms “adaptor(s)”, “adapter(s)” and “tag(s)” may be used synonymously. An adaptor or tag can be coupled to a polynucleotide sequence to be “tagged” by any approach, including ligation, hybridization, or other approaches.

[00118] The term “sequencing,” as used herein, generally refers to methods and technologies for determining the sequence of nucleotide bases in one or more polynucleotides. The polynucleotides can be, for example, nucleic acid molecules such as deoxyribonucleic acid (DNA) or ribonucleic acid (RNA), including variants or derivatives thereof (e.g., single stranded DNA). Sequencing can be performed by various systems currently available, such as, without limitation, a sequencing system by Illumina®, Pacific Biosciences (PacBio®), Oxford Nanopore®, or Life Technologies (Ion Torrent®). Alternatively or in addition, sequencing may be performed using nucleic acid amplification, polymerase chain reaction (PCR) (e.g., digital PCR, quantitative PCR, or real time PCR), or isothermal amplification. Such systems may provide a plurality of raw genetic data corresponding to the genetic information of a subject (e.g., human), as generated by the systems from a sample provided by the subject. In some examples, such systems provide sequencing reads (also “reads” herein). A read may include a string of nucleic acid bases corresponding to a sequence of a nucleic acid molecule that has been

sequenced. In some situations, systems and methods provided herein may be used with proteomic information.

[00119] The term “bead,” as used herein, generally refers to a particle. The bead may be a solid or semi-solid particle. The bead may be a gel bead. The gel bead may include a polymer matrix (e.g., matrix formed by polymerization or cross-linking). The polymer matrix may include one or more polymers (e.g., polymers having different functional groups or repeat units). Polymers in the polymer matrix may be randomly arranged, such as in random copolymers, and/or have ordered structures, such as in block copolymers. Cross-linking can be via covalent, ionic, or inductive, interactions, or physical entanglement. The bead may be a macromolecule. The bead may be formed of nucleic acid molecules bound together. The bead may be formed via covalent or non-covalent assembly of molecules (e.g., macromolecules), such as monomers or polymers. Such polymers or monomers may be natural or synthetic. Such polymers or monomers may be or include, for example, nucleic acid molecules (e.g., DNA or RNA). The bead may be formed of a polymeric material. The bead may be magnetic or non-magnetic. The bead may be rigid. The bead may be flexible and/or compressible. The bead may be disruptable or dissolvable. The bead may be a solid particle (e.g., a metal-based particle including but not limited to iron oxide, gold or silver) covered with a coating comprising one or more polymers. Such coating may be disruptable or dissolvable.

[00120] The term “sample,” as used herein, generally refers to a biological sample of a subject. The biological sample may comprise any number of macromolecules, for example, cellular macromolecules. The sample may be a cell sample. The sample may be a cell line or cell culture sample. The sample can include one or more cells. The sample can include one or more microbes. The biological sample may be a nucleic acid sample or protein sample. The biological sample may also be a carbohydrate sample or a lipid sample. The biological sample may be derived from another sample. The sample may be a tissue sample, such as a biopsy, core biopsy, needle aspirate, or fine needle aspirate. The sample may be a fluid sample, such as a blood sample, urine sample, or saliva sample. The sample may be a skin sample. The sample may be a cheek swab. The sample may be a plasma or serum sample. The sample may be a cell-free or cell free sample. A cell-free sample may include extracellular polynucleotides. Extracellular polynucleotides may be isolated from a bodily sample that may be selected from the group consisting of blood, plasma, serum, urine, saliva, mucosal excretions, sputum, stool and tears.

[00121] The term “biological particle,” as used herein, generally refers to a discrete biological system derived from a biological sample. The biological particle may be a macromolecule. The biological particle may be a small molecule. The biological particle may

be a virus. The biological particle may be a cell or derivative of a cell. The biological particle may be an organelle. The biological particle may be a rare cell from a population of cells. The biological particle may be any type of cell, including without limitation prokaryotic cells, eukaryotic cells, bacterial, fungal, plant, mammalian, or other animal cell type, mycoplasmas, normal tissue cells, tumor cells, or any other cell type, whether derived from single cell or multicellular organisms. The biological particle may be a constituent of a cell. The biological particle may be or may include DNA, RNA, organelles, proteins, or any combination thereof. The biological particle may be or may include a matrix (e.g., a gel or polymer matrix) comprising a cell or one or more constituents from a cell (e.g., cell bead), such as DNA, RNA, organelles, proteins, or any combination thereof, from the cell. The biological particle may be obtained from a tissue of a subject. The biological particle may be a hardened cell. Such hardened cell may or may not include a cell wall or cell membrane. The biological particle may include one or more constituents of a cell, but may not include other constituents of the cell. An example of such constituents is a nucleus or an organelle. A cell may be a live cell. The live cell may be capable of being cultured, for example, being cultured when enclosed in a gel or polymer matrix, or cultured when comprising a gel or polymer matrix.

[00122] The term “macromolecular constituent,” as used herein, generally refers to a macromolecule contained within or from a biological particle. The macromolecular constituent may comprise a nucleic acid. In some cases, the biological particle may be a macromolecule. The macromolecular constituent may comprise DNA. The macromolecular constituent may comprise RNA. The RNA may be coding or non-coding. The RNA may be messenger RNA (mRNA), ribosomal RNA (rRNA) or transfer RNA (tRNA), for example. The RNA may be a transcript. The RNA may be small RNA that are less than 200 nucleic acid bases in length, or large RNA that are greater than 200 nucleic acid bases in length. Small RNAs may include 5.8S ribosomal RNA (rRNA), 5S rRNA, transfer RNA (tRNA), microRNA (miRNA), small interfering RNA (siRNA), small nucleolar RNA (snoRNAs), Piwi-interacting RNA (piRNA), tRNA-derived small RNA (tsRNA) and small rDNA-derived RNA (srRNA). The RNA may be double-stranded RNA or single-stranded RNA. The RNA may be circular RNA. The macromolecular constituent may comprise a protein. The macromolecular constituent may comprise a peptide. The macromolecular constituent may comprise a polypeptide.

[00123] The term “molecular tag,” as used herein, generally refers to a molecule capable of binding to a macromolecular constituent. The molecular tag may bind to the macromolecular constituent with high affinity. The molecular tag may bind to the macromolecular constituent with high specificity. The molecular tag may comprise a nucleotide sequence. The molecular tag may comprise a nucleic acid sequence. The nucleic acid sequence may be at least a portion or

an entirety of the molecular tag. The molecular tag may be a nucleic acid molecule or may be part of a nucleic acid molecule. The molecular tag may be an oligonucleotide or a polypeptide. The molecular tag may comprise a DNA aptamer. The molecular tag may be or comprise a primer. The molecular tag may be, or comprise, a protein. The molecular tag may comprise a polypeptide. The molecular tag may be a barcode.

[00124] The term “partition,” as used herein, generally, refers to a space or volume that may be suitable to contain one or more species or conduct one or more reactions. A partition may be a physical compartment, such as a droplet or well. The partition may isolate space or volume from another space or volume. The droplet may be a first phase (e.g., aqueous phase) in a second phase (e.g., oil) immiscible with the first phase. The droplet may be a first phase in a second phase that does not phase separate from the first phase, such as, for example, a capsule or liposome in an aqueous phase. A partition may comprise one or more other (inner) partitions. In some cases, a partition may be a virtual compartment that can be defined and identified by an index (e.g., indexed libraries) across multiple and/or remote physical compartments. For example, a physical compartment may comprise a plurality of virtual compartments.

[00125] The efficiency of many single cell applications can increase by improving cell throughput. For example, this can be achieved by sorting a plurality of droplets that may or may not contain cells and/or particles therein to collect only the droplets that contain the cells and/or particles therein. The plurality of droplets may be sorted to isolate singularly occupied droplets from non-singularly occupied droplets (e.g., unoccupied, multiply occupied, etc.). In another example, higher efficiency can be achieved by isolating a plurality of cell beads from a plurality of particles that may or may not contain cells therein. The plurality of particles may be sorted to isolate singularly occupied cell beads (e.g., particles containing cells or their derivatives) from non-singularly occupied cell beads (e.g., unoccupied particles, multiply occupied cell beads, etc.). The isolated population of droplets that contain (e.g., singularly contain) the cells and/or particles therein, and/or cell beads that contain (e.g., singularly contain) the cells therein, can then be subject to further applications, such as nucleic acid amplification and/or sequencing applications.

[00126] Provided are methods and systems for sorting droplets. The methods and systems generally operate by generating a plurality of droplets such that each of the plurality of droplets comprises field-attractable particles. A given droplet in the plurality of droplets may or may not include therein one or more cells and/or other particles (e.g., cell beads, gel beads, etc.). In some cases, the other particles (e.g., gel beads) may have molecular barcodes coupled thereto. Thus, the plurality of droplets comprising field attractable particles can comprise a first subset of droplets that include one or more cells and/or other particles and a second subset of droplets that

do not include any cells and/or other particles. A given droplet in the first subset of droplets that includes one or more cells and/or other particles can comprise a sufficiently discrepant number or concentration of field-attractable particles than a given droplet in the second subset of droplets that does not include any cells and/or other particles such that when the plurality of droplets is subject to an electric or magnetic field, the first subset of droplets and the second subset of droplets are separated from each other. In some cases, when the plurality of droplets is subjected to an electric or magnetic field, singularly occupied droplets may be separated from unoccupied droplets and otherwise multiply occupied droplets.

[00127] In some instances, a plurality of droplets can be generated with or without field-attractable particles. A given droplet in the plurality of droplets may or may not include one or more cells and/or particles. Thus, the plurality of droplets can comprise a first subset of droplets that include one or more cells and/or particles and a second subset of droplets that do not include any cells and/or particles. The plurality of droplets can be subject to a pressure pulse and the first subset of droplets and the second subset of droplets can be separated from each other via hydrodynamic forces. In some cases, singularly occupied droplets may be separated from unoccupied droplets and otherwise multiply occupied droplets.

[00128] In an aspect, the methods and systems described herein provide for the compartmentalization, depositing, or partitioning of macromolecular constituent contents of individual biological particles from a sample material containing biological particles into discrete compartments or partitions (referred to interchangeably herein as partitions), where each partition maintains separation of its own contents from the contents of other partitions. The partition can be a droplet in an emulsion. The partition can be a well. The partition can be a bead, such as a gel bead and/or a cell bead. A partition may or may not contain biological particles and/or macromolecular constituents thereof. In accordance with some embodiments, each partition may contain at least some field attractable particles. The amount and/or concentration of field attractable particles in each partition can vary depending on whether the partition contains biological particles (or other particles, such as beads). In accordance with some other embodiments, a partition may not contain field attractable particles.

[00129] In some instances, unique identifiers, such as barcodes, may be previously, subsequently or concurrently delivered to the partitions that hold the compartmentalized or partitioned biological particle, in order to allow for the later attribution of the characteristics of the individual biological particle to the particular partition. Barcodes may be delivered, for example on an oligonucleotide, to a partition via any suitable mechanism. Barcoded oligonucleotides can be delivered to a partition via a microcapsule. In some cases, barcoded oligonucleotides can be initially associated with the microcapsule and then released from the

microcapsule upon application of a stimulus which allows the oligonucleotides to dissociate or to be released from the microcapsule.

[00130] A microcapsule, in some instances, can comprise a bead. In some cases, a bead may be porous, non-porous, solid, semi-solid, semi-fluidic, fluidic, and/or a combination thereof. In some instances, a bead may be dissolvable, disruptable, and/or degradable. In some cases, a bead may not be degradable. In some cases, the bead may be a gel bead. A gel bead may be a hydrogel bead. A gel bead may be formed from molecular precursors, such as a polymeric or monomeric species. A semi-solid bead may be a liposomal bead. Solid beads may comprise metals including iron oxide, gold, and silver. In some cases, the bead may be a silica bead. In some cases, the bead can be rigid. In other cases, the bead may be flexible and/or compressible.

[00131] In some instances, the bead may contain molecular precursors (e.g., monomers or polymers), which may form a polymer network via polymerization of the precursors. In some cases, a precursor may be an already polymerized species capable of undergoing further polymerization via, for example, a chemical cross-linkage. In some cases, a precursor can comprise one or more of an acrylamide or a methacrylamide monomer, oligomer, or polymer. In some cases, the bead may comprise prepolymers, which are oligomers capable of further polymerization. For example, polyurethane beads may be prepared using prepolymers. In some cases, the bead may contain individual polymers that may be further polymerized together. In some cases, beads may be generated via polymerization of different precursors, such that they comprise mixed polymers, co-polymers, and/or block co-polymers.

[00132] A bead may comprise natural and/or synthetic materials. For example, a polymer can be a natural polymer or a synthetic polymer. In some cases, a bead can comprise both natural and synthetic polymers. Examples of natural polymers include proteins and sugars such as deoxyribonucleic acid, rubber, cellulose, starch (e.g., amylose, amylopectin), proteins, enzymes, polysaccharides, silks, polyhydroxyalkanoates, chitosan, dextran, collagen, carrageenan, ispaghula, acacia, agar, gelatin, shellac, sterculia gum, xanthan gum, Corn sugar gum, guar gum, gum karaya, agarose, alginic acid, alginate, or natural polymers thereof. Examples of synthetic polymers include acrylics, nylons, silicones, spandex, viscose rayon, polycarboxylic acids, polyvinyl acetate, polyacrylamide, polyacrylate, polyethylene glycol, polyurethanes, polylactic acid, silica, polystyrene, polyacrylonitrile, polybutadiene, polycarbonate, polyethylene, polyethylene terephthalate, poly(chlorotrifluoroethylene), poly(ethylene oxide), poly(ethylene terephthalate), polyethylene, polyisobutylene, poly(methyl methacrylate), poly(oxyethylene), polyformaldehyde, polypropylene, polystyrene, poly(tetrafluoroethylene), poly(vinyl acetate), poly(vinyl alcohol), poly(vinyl chloride), poly(vinylidene dichloride), poly(vinylidene difluoride), poly(vinyl fluoride) and/or

combinations (e.g., co-polymers) thereof. Beads may also be formed from materials other than polymers, including lipids, micelles, ceramics, glass-ceramics, material composites, metals, other inorganic materials, and others.

[00133] In some cases, a chemical cross-linker may be a precursor used to cross-link monomers during polymerization of the monomers and/or may be used to attach oligonucleotides (e.g., barcoded oligonucleotides) to the bead. In some cases, polymers may be further polymerized with a cross-linker species or other type of monomer to generate a further polymeric network. Non-limiting examples of chemical cross-linkers (also referred to as a “crosslinker” or a “crosslinker agent” herein) include cystamine, glutaraldehyde, dimethyl suberimidate, N-Hydroxysuccinimide crosslinker BS3, formaldehyde, carbodiimide (EDC), SMCC, Sulfo-SMCC, vinylsilane, N,N'-diallyltartardiamide (DATD), N,N'-Bis(acryloyl)cystamine (BAC), or homologs thereof. In some cases, the crosslinker used in the present disclosure contains cystamine.

[00134] Crosslinking may be permanent or reversible, depending upon the particular crosslinker used. Reversible crosslinking may allow for the polymer to linearize or dissociate under appropriate conditions. In some cases, reversible cross-linking may also allow for reversible attachment of a material bound to the surface of a bead. In some cases, a cross-linker may form disulfide linkages. In some cases, the chemical cross-linker forming disulfide linkages may be cystamine or a modified cystamine.

[00135] In some cases, disulfide linkages can be formed between molecular precursor units (e.g., monomers, oligomers, or linear polymers) or precursors incorporated into a bead and oligonucleotides. Cystamine (including modified cystamines), for example, is an organic agent comprising a disulfide bond that may be used as a crosslinker agent between individual monomeric or polymeric precursors of a bead. Polyacrylamide may be polymerized in the presence of cystamine or a species comprising cystamine (e.g., a modified cystamine) to generate polyacrylamide gel beads comprising disulfide linkages (e.g., chemically degradable beads comprising chemically-reducible cross-linkers). The disulfide linkages may permit the bead to be degraded (or dissolved) upon exposure of the bead to a reducing agent.

[00136] In some cases, chitosan, a linear polysaccharide polymer, may be crosslinked with glutaraldehyde via hydrophilic chains to form a bead. Crosslinking of chitosan polymers may be achieved by chemical reactions that are initiated by heat, pressure, change in pH, and/or radiation.

[00137] In some cases, the bead may comprise covalent or ionic bonds between polymeric precursors (e.g., monomers, oligomers, linear polymers), oligonucleotides, primers, and other entities. In some cases, the covalent bonds can be carbon-carbon bonds or thioether bonds.

[00138] In some cases, a bead may comprise an acrydite moiety, which in certain aspects may be used to attach one or more oligonucleotides (e.g., barcode sequence, barcoded oligonucleotide, primer, or other oligonucleotide) to the bead. In some cases, an acrydite moiety can refer to an acrydite analogue generated from the reaction of acrydite with one or more species, such as, the reaction of acrydite with other monomers and cross-linkers during a polymerization reaction. Acrydite moieties may be modified to form chemical bonds with a species to be attached, such as an oligonucleotide (e.g., barcode sequence, barcoded oligonucleotide, primer, or other oligonucleotide). Acrydite moieties may be modified with thiol groups capable of forming a disulfide bond or may be modified with groups already comprising a disulfide bond. The thiol or disulfide (via disulfide exchange) may be used as an anchor point for a species to be attached or another part of the acrydite moiety may be used for attachment. In some cases, attachment can be reversible, such that when the disulfide bond is broken (e.g., in the presence of a reducing agent), the attached species is released from the bead. In other cases, an acrydite moiety can comprise a reactive hydroxyl group that may be used for attachment.

[00139] Functionalization of beads for attachment of oligonucleotides may be achieved through a wide range of different approaches, including activation of chemical groups within a polymer, incorporation of active or activatable functional groups in the polymer structure, or attachment at the pre-polymer or monomer stage in bead production.

[00140] For example, precursors (e.g., monomers, cross-linkers) that are polymerized to form a bead may comprise acrydite moieties, such that when a bead is generated, the bead also comprises acrydite moieties. The acrydite moieties can be attached to a nucleic acid molecule (e.g., oligonucleotide), which may include a priming sequence (e.g., a primer for amplifying target nucleic acids, random primer, primer sequence for messenger RNA) and/or one or more barcode sequences. The one more barcode sequences may include sequences that are the same for all nucleic acid molecules coupled to a given bead and/or sequences that are different across all nucleic acid molecules coupled to the given bead. The nucleic acid molecule may be incorporated into the bead.

[00141] In some cases, the nucleic acid molecule can comprise a functional sequence, for example, for attachment to a sequencing flow cell, such as, for example, a P5 sequence for Illumina® sequencing. In some cases, the nucleic acid molecule or derivative thereof (e.g., oligonucleotide or polynucleotide generated from the nucleic acid molecule) can comprise another functional sequence, such as, for example, a P7 sequence for attachment to a sequencing flow cell for Illumina sequencing. In some cases, the nucleic acid molecule can comprise a barcode sequence. In some cases, the primer can further comprise a unique molecular identifier (UMI). In some cases, the primer can comprise an R1 primer sequence for Illumina sequencing.

In some cases, the primer can comprise an R2 primer sequence for Illumina sequencing. Examples of such nucleic acid molecules (e.g., oligonucleotides, polynucleotides, etc.) and uses thereof, as may be used with compositions, devices, methods and systems of the present disclosure, are provided in U.S. Patent Pub. Nos. 2014/0378345 and 2015/0376609, each of which is entirely incorporated herein by reference.

[00142] FIG. 19 illustrates an example of a barcode carrying bead. A nucleic acid molecule **1902**, such as an oligonucleotide, can be coupled to a bead **1904** by a releasable linkage **1906**, such as, for example, a disulfide linker. The same bead **1904** may be coupled (e.g., via releasable linkage) to one or more other nucleic acid molecules **1918**, **1920**. The nucleic acid molecule **1902** may be or comprise a barcode. As noted elsewhere herein, the structure of the barcode may comprise a number of sequence elements. The nucleic acid molecule **1902** may comprise a functional sequence **1908** that may be used in subsequent processing. For example, the functional sequence **1908** may include one or more of a sequencer specific flow cell attachment sequence (e.g., a P5 sequence for Illumina® sequencing systems) and a sequencing primer sequence (e.g., a R1 primer for Illumina® sequencing systems). The nucleic acid molecule **1902** may comprise a barcode sequence **1910** for use in barcoding the sample (e.g., DNA, RNA, protein, etc.). In some cases, the barcode sequence **1910** can be bead-specific such that the barcode sequence **1910** is common to all nucleic acid molecules (e.g., including nucleic acid molecule **1902**) coupled to the same bead **1904**. Alternatively or in addition, the barcode sequence **1910** can be partition-specific such that the barcode sequence **1910** is common to all nucleic acid molecules coupled to one or more beads that are partitioned into the same partition. The nucleic acid molecule **1902** may comprise a specific priming sequence **1912**, such as an mRNA specific priming sequence (e.g., poly-T sequence), a targeted priming sequence, and/or a random priming sequence. The nucleic acid molecule **1902** may comprise an anchoring sequence **1914** to ensure that the specific priming sequence **1912** hybridizes at the sequence end (e.g., of the mRNA). For example, the anchoring sequence **1914** can include a random short sequence of nucleotides, such as a 1-mer, 2-mer, 3-mer or longer sequence, which can ensure that a poly-T segment is more likely to hybridize at the sequence end of the poly-A tail of the mRNA.

[00143] The nucleic acid molecule **1902** may comprise a unique molecular identifying sequence **1916** (e.g., unique molecular identifier (UMI)). In some cases, the unique molecular identifying sequence **1916** may comprise from about 5 to about 8 nucleotides. Alternatively, the unique molecular identifying sequence **1916** may compress less than about 5 or more than about 8 nucleotides. The unique molecular identifying sequence **1916** may be a unique sequence that varies across individual nucleic acid molecules (e.g., **1902**, **1918**, **1920**, etc.) coupled to a single

bead (e.g., bead **1904**). In some cases, the unique molecular identifying sequence **1916** may be a random sequence (e.g., such as a random N-mer sequence). For example, the UMI may provide a unique identifier of the starting mRNA molecule that was captured, in order to allow quantitation of the number of original expressed RNA. As will be appreciated, although **FIG. 19** shows three nucleic acid molecules **1902**, **1918**, **1920** coupled to the surface of the bead **1904**, an individual bead may be coupled to any number of individual nucleic acid molecules, for example, from one to tens to hundreds of thousands or even millions of individual nucleic acid molecules. The respective barcodes for the individual nucleic acid molecules can comprise both common sequence segments or relatively common sequence segments (e.g., **1908**, **1910**, **1912**, etc.) and variable or unique sequence segments (e.g., **1916**) between different individual nucleic acid molecules coupled to the same bead.

[00144] In operation, a biological particle (e.g., cell, DNA, RNA, etc.) can be co-partitioned along with a barcode bearing bead **1904**. The barcoded nucleic acid molecules **1902**, **1918**, **1920** can be released from the bead **1904** in the partition. By way of example, in the context of analyzing sample RNA, the poly-T segment (e.g., **1912**) of one of the released nucleic acid molecules (e.g., **1902**) can hybridize to the poly-A tail of a mRNA molecule. Reverse transcription may result in a cDNA transcript of the mRNA, but which transcript includes each of the sequence segments **1908**, **1910**, **1916** of the nucleic acid molecule **1902**. Because the nucleic acid molecule **1902** comprises an anchoring sequence **1914**, it will more likely hybridize to and prime reverse transcription at the sequence end of the poly-A tail of the mRNA. Within any given partition, all of the cDNA transcripts of the individual mRNA molecules may include a common barcode sequence segment **1910**. However, the transcripts made from the different mRNA molecules within a given partition may vary at the unique molecular identifying sequence **1912** segment (e.g., UMI segment). Beneficially, even following any subsequent amplification of the contents of a given partition, the number of different UMIs can be indicative of the quantity of mRNA originating from a given partition, and thus from the biological particle (e.g., cell). As noted above, the transcripts can be amplified, cleaned up and sequenced to identify the sequence of the cDNA transcript of the mRNA, as well as to sequence the barcode segment and the UMI segment. While a poly-T primer sequence is described, other targeted or random priming sequences may also be used in priming the reverse transcription reaction. Likewise, although described as releasing the barcoded oligonucleotides into the partition, in some cases, the nucleic acid molecules bound to the bead (e.g., gel bead) may be used to hybridize and capture the mRNA on the solid phase of the bead, for example, in order to facilitate the separation of the RNA from other cell contents.

[00145] In some cases, precursors comprising a functional group that is reactive or capable of being activated such that it becomes reactive can be polymerized with other precursors to generate gel beads comprising the activated or activatable functional group. The functional group may then be used to attach additional species (e.g., disulfide linkers, primers, other oligonucleotides, etc.) to the gel beads. For example, some precursors comprising a carboxylic acid (COOH) group can co-polymerize with other precursors to form a gel bead that also comprises a COOH functional group. In some cases, acrylic acid (a species comprising free COOH groups), acrylamide, and bis(acryloyl)cystamine can be co-polymerized together to generate a gel bead comprising free COOH groups. The COOH groups of the gel bead can be activated (e.g., via 1-Ethyl-3-(3-dimethylaminopropyl)carbodiimide (EDC) and N-Hydroxysuccinimide (NHS) or 4-(4,6-Dimethoxy-1,3,5-triazin-2-yl)-4-methylmorpholinium chloride (DMTMM)) such that they are reactive (e.g., reactive to amine functional groups where EDC/NHS or DMTMM are used for activation). The activated COOH groups can then react with an appropriate species (e.g., a species comprising an amine functional group where the carboxylic acid groups are activated to be reactive with an amine functional group) comprising a moiety to be linked to the bead.

[00146] Beads comprising disulfide linkages in their polymeric network may be functionalized with additional species via reduction of some of the disulfide linkages to free thiols. The disulfide linkages may be reduced via, for example, the action of a reducing agent (e.g., DTT, TCEP, etc.) to generate free thiol groups, without dissolution of the bead. Free thiols of the beads can then react with free thiols of a species or a species comprising another disulfide bond (e.g., via thiol-disulfide exchange) such that the species can be linked to the beads (e.g., via a generated disulfide bond). In some cases, free thiols of the beads may react with any other suitable group. For example, free thiols of the beads may react with species comprising an acrydite moiety. The free thiol groups of the beads can react with the acrydite via Michael addition chemistry, such that the species comprising the acrydite is linked to the bead. In some cases, uncontrolled reactions can be prevented by inclusion of a thiol capping agent such as N-ethylmaleimide or iodoacetate.

[00147] Activation of disulfide linkages within a bead can be controlled such that only a small number of disulfide linkages are activated. Control may be exerted, for example, by controlling the concentration of a reducing agent used to generate free thiol groups and/or concentration of reagents used to form disulfide bonds in bead polymerization. In some cases, a low concentration (e.g., molecules of reducing agent:gel bead ratios of less than or equal to about 1:100,000,000,000, less than or equal to about 1:10,000,000,000, less than or equal to about 1:1,000,000,000, less than or equal to about 1:100,000,000, less than or equal to about

1:10,000,000, less than or equal to about 1:1,000,000, less than or equal to about 1:100,000, less than or equal to about 1:10,000) of reducing agent may be used for reduction. Controlling the number of disulfide linkages that are reduced to free thiols may be useful in ensuring bead structural integrity during functionalization. In some cases, optically-active agents, such as fluorescent dyes may be coupled to beads via free thiol groups of the beads and used to quantify the number of free thiols present in a bead and/or track a bead.

[00148] In some cases, addition of moieties to a gel bead after gel bead formation may be advantageous. For example, addition of an oligonucleotide (e.g., barcoded oligonucleotide) after gel bead formation may avoid loss of the species during chain transfer termination that can occur during polymerization. Moreover, smaller precursors (e.g., monomers or cross linkers that do not comprise side chain groups and linked moieties) may be used for polymerization and can be minimally hindered from growing chain ends due to viscous effects. In some cases, functionalization after gel bead synthesis can minimize exposure of species (e.g., oligonucleotides) to be loaded with potentially damaging agents (e.g., free radicals) and/or chemical environments. In some cases, the generated gel may possess an upper critical solution temperature (UCST) that can permit temperature driven swelling and collapse of a bead. Such functionality may aid in oligonucleotide (e.g., a primer) infiltration into the bead during subsequent functionalization of the bead with the oligonucleotide. Post-production functionalization may also be useful in controlling loading ratios of species in beads, such that, for example, the variability in loading ratio is minimized. Species loading may also be performed in a batch process such that a plurality of beads can be functionalized with the species in a single batch.

[00149] In some cases, beads can be non-covalently loaded with one or more reagents. The beads can be non-covalently loaded by, for instance, subjecting the beads to conditions sufficient to swell the beads, allowing sufficient time for the reagents to diffuse into the interiors of the beads, and subjecting the beads to conditions sufficient to de-swell the beads. The swelling of the beads may be accomplished, for instance, by placing the beads in a thermodynamically favorable solvent, subjecting the beads to a higher or lower temperature, subjecting the beads to a higher or lower ion concentration, and/or subjecting the beads to an electric field. The swelling of the beads may be accomplished by any swelling method as is known to one having skill in the art. The de-swelling of the beads may be accomplished, for instance, by transferring the beads in a thermodynamically unfavorable solvent, subjecting the beads to lower or high temperatures, subjecting the beads to a lower or higher ion concentration, and/or removing an electric field. The de-swelling of the beads may be accomplished by any de-swelling method as is known to one having skill in the art. Transferring the beads may cause pores in the bead to shrink. The

shrinking may then hinder reagents within the beads from diffusing out of the interiors of the beads. The hindrance may be due to steric interactions between the reagents and the interiors of the beads. The transfer may be accomplished microfluidically. For instance, the transfer may be achieved by moving the beads from one co-flowing solvent stream to a different co-flowing solvent stream. The swellability and/or pore size of the beads may be adjusted by changing the polymer composition of the bead.

[00150] In some cases, an acrydite moiety linked to precursor, another species linked to a precursor, or a precursor itself comprises a labile bond, such as chemically, thermally, or photo-sensitive bonds e.g., disulfide bonds, UV sensitive bonds, or the like. Once acrydite moieties or other moieties comprising a labile bond are incorporated into a bead, the bead may also comprise the labile bond. The labile bond may be, for example, useful in reversibly linking (e.g., covalently linking) species (e.g., barcodes, primers, etc.) to a bead. In some cases, a thermally labile bond may include a nucleic acid hybridization based attachment, e.g., where an oligonucleotide is hybridized to a complementary sequence that is attached to the bead, such that thermal melting of the hybrid releases the oligonucleotide, e.g., a barcode containing sequence, from the bead or microcapsule.

[00151] The addition of multiple types of labile bonds to a gel bead may result in the generation of a bead capable of responding to varied stimuli. Each type of labile bond may be sensitive to an associated stimulus (e.g., chemical stimulus, light, temperature, etc.) such that release of species attached to a bead via each labile bond may be controlled by the application of the appropriate stimulus. Such functionality may be useful in controlled release of species from a gel bead. In some cases, another species comprising a labile bond may be linked to a gel bead after gel bead formation via, for example, an activated functional group of the gel bead as described above. As will be appreciated, barcodes that are releasably, cleavably or reversibly attached to the beads described herein include barcodes that are released or releasable through cleavage of a linkage between the barcode molecule and the bead, or that are released through degradation of the underlying bead itself, allowing the barcodes to be accessed or accessible by other reagents, or both.

[00152] The barcodes that are releasable as described herein may sometimes be referred to as being activatable, in that they are available for reaction once released. Thus, for example, an activatable barcode may be activated by releasing the barcode from a bead (or other suitable type of partition described herein). Other activatable configurations are also envisioned in the context of the described methods and systems.

[00153] In addition to thermally cleavable bonds, disulfide bonds and UV sensitive bonds, other non-limiting examples of labile bonds that may be coupled to a precursor or bead include

an ester linkage (e.g., cleavable with an acid, a base, or hydroxylamine), a vicinal diol linkage (e.g., cleavable via sodium periodate), a Diels-Alder linkage (e.g., cleavable via heat), a sulfone linkage (e.g., cleavable via a base), a silyl ether linkage (e.g., cleavable via an acid), a glycosidic linkage (e.g., cleavable via an amylase), a peptide linkage (e.g., cleavable via a protease), or a phosphodiester linkage (e.g., cleavable via a nuclease (e.g., DNAase)).

[00154] Species that do not participate in polymerization may also be encapsulated in beads during bead generation (e.g., during polymerization of precursors). Such species may be entered into polymerization reaction mixtures such that generated beads comprise the species upon bead formation. In some cases, such species may be added to the gel beads after formation. Such species may include, for example, oligonucleotides, reagents for a nucleic acid amplification reaction (e.g., primers, polymerases, dNTPs, co-factors (e.g., ionic co-factors)) including those described herein, reagents for enzymatic reactions (e.g., enzymes, co-factors, substrates), or reagents for a nucleic acid modification reactions such as polymerization, ligation, or digestion. Trapping of such species may be controlled by the polymer network density generated during polymerization of precursors, control of ionic charge within the gel bead (e.g., via ionic species linked to polymerized species), or by the release of other species. Encapsulated species may be released from a bead upon bead degradation and/or by application of a stimulus capable of releasing the species from the bead.

[00155] Beads may be of uniform size or heterogeneous size. In some cases, the diameter of a bead may be at least about 1micrometers (μm), $5\mu\text{m}$, $10\mu\text{m}$, $20\mu\text{m}$, $30\mu\text{m}$, $40\mu\text{m}$, $50\mu\text{m}$, $60\mu\text{m}$, $70\mu\text{m}$, $80\mu\text{m}$, $90\mu\text{m}$, $100\mu\text{m}$, $250\mu\text{m}$, $500\mu\text{m}$, 1mm , or greater. In some cases, a bead may have a diameter of less than about $1\mu\text{m}$, $5\mu\text{m}$, $10\mu\text{m}$, $20\mu\text{m}$, $30\mu\text{m}$, $40\mu\text{m}$, $50\mu\text{m}$, $60\mu\text{m}$, $70\mu\text{m}$, $80\mu\text{m}$, $90\mu\text{m}$, $100\mu\text{m}$, $250\mu\text{m}$, $500\mu\text{m}$, 1mm , or less. In some cases, a bead may have a diameter in the range of about $40\text{-}75\mu\text{m}$, $30\text{-}75\mu\text{m}$, $20\text{-}75\mu\text{m}$, $40\text{-}85\mu\text{m}$, $40\text{-}95\mu\text{m}$, $20\text{-}100\mu\text{m}$, $10\text{-}100\mu\text{m}$, $1\text{-}100\mu\text{m}$, $20\text{-}250\mu\text{m}$, or $20\text{-}500\mu\text{m}$.

[00156] In certain aspects, beads can be provided as a population or plurality of beads having a relatively monodisperse size distribution. Where it may be desirable to provide relatively consistent amounts of reagents within partitions, maintaining relatively consistent bead characteristics, such as size, can contribute to the overall consistency. In particular, the beads described herein may have size distributions that have a coefficient of variation in their cross-sectional dimensions of less than 50%, less than 40%, less than 30%, less than 20%, and in some cases less than 15%, less than 10%, less than 5%, or less.

[00157] Beads may be of any suitable shape. Examples of bead shapes include, but are not limited to, spherical, non-spherical, oval, oblong, amorphous, circular, cylindrical, and variations thereof.

[00158] In addition to, or as an alternative to the cleavable linkages between the beads and the associated molecules, such as barcode containing oligonucleotides, described above, the beads may be degradable, disruptable, or dissolvable spontaneously or upon exposure to one or more stimuli (e.g., temperature changes, pH changes, exposure to particular chemical species or phase, exposure to light, reducing agent, etc.). In some cases, a bead may be dissolvable, such that material components of the beads are solubilized when exposed to a particular chemical species or an environmental change, such as a change temperature or a change in pH. In some cases, a gel bead can be degraded or dissolved at elevated temperature and/or in basic conditions. In some cases, a bead may be thermally degradable such that when the bead is exposed to an appropriate change in temperature (e.g., heat), the bead degrades. Degradation or dissolution of a bead bound to a species (e.g., a oligonucleotide, e.g., barcoded oligonucleotide) may result in release of the species from the bead.

[00159] A degradable bead may comprise one or more species with a labile bond such that, when the bead/species is exposed to the appropriate stimuli, the bond is broken and the bead degrades. The labile bond may be a chemical bond (e.g., covalent bond, ionic bond) or may be another type of physical interaction (e.g., van der Waals interactions, dipole-dipole interactions, etc.). In some cases, a crosslinker used to generate a bead may comprise a labile bond. Upon exposure to the appropriate conditions, the labile bond can be broken and the bead degraded. For example, upon exposure of a polyacrylamide gel bead comprising cystamine crosslinkers to a reducing agent, the disulfide bonds of the cystamine can be broken and the bead degraded.

[00160] A degradable bead may be useful in more quickly releasing an attached species (e.g., an oligonucleotide, a barcode sequence, a primer, etc) from the bead when the appropriate stimulus is applied to the bead as compared to a bead that does not degrade. For example, for a species bound to an inner surface of a porous bead or in the case of an encapsulated species, the species may have greater mobility and accessibility to other species in solution upon degradation of the bead. In some cases, a species may also be attached to a degradable bead via a degradable linker (e.g., disulfide linker). The degradable linker may respond to the same stimuli as the degradable bead or the two degradable species may respond to different stimuli. For example, a barcode sequence may be attached, via a disulfide bond, to a polyacrylamide bead comprising cystamine. Upon exposure of the barcoded-bead to a reducing agent, the bead degrades and the barcode sequence is released upon breakage of both the disulfide linkage between the barcode sequence and the bead and the disulfide linkages of the cystamine in the bead.

[00161] A degradable bead may be introduced into a partition, such as a droplet of an emulsion or a well, such that the bead degrades within the partition and any associated species (e.g., oligonucleotides) are released within the droplet when the appropriate stimulus is applied.

The free species (e.g., oligonucleotides) may interact with other reagents contained in the partition. For example, a polyacrylamide bead comprising cystamine and linked, via a disulfide bond, to a barcode sequence, may be combined with a reducing agent within a droplet of a water-in-oil emulsion. Within the droplet, the reducing agent breaks the various disulfide bonds resulting in bead degradation and release of the barcode sequence into the aqueous, inner environment of the droplet. In another example, heating of a droplet comprising a bead-bound barcode sequence in basic solution may also result in bead degradation and release of the attached barcode sequence into the aqueous, inner environment of the droplet.

[00162] As will be appreciated from the above disclosure, while referred to as degradation of a bead, in many instances as noted above, that degradation may refer to the disassociation of a bound or entrained species from a bead, both with and without structurally degrading the physical bead itself. For example, entrained species may be released from beads through osmotic pressure differences due to, for example, changing chemical environments. By way of example, alteration of bead pore sizes due to osmotic pressure differences can generally occur without structural degradation of the bead itself. In some cases, an increase in pore size due to osmotic swelling of a bead can permit the release of entrained species within the bead. In other cases, osmotic shrinking of a bead may cause a bead to better retain an entrained species due to pore size contraction.

[00163] Where degradable beads are provided, it may be desirable to avoid exposing such beads to the stimulus or stimuli that cause such degradation prior to the desired time, in order to avoid premature bead degradation and issues that arise from such degradation, including for example poor flow characteristics and aggregation. By way of example, where beads comprise reducible cross-linking groups, such as disulfide groups, it will be desirable to avoid contacting such beads with reducing agents, e.g., DTT or other disulfide cleaving reagents. In such cases, treatment to the beads described herein will, in some cases be provided free of reducing agents, such as DTT. Because reducing agents are often provided in commercial enzyme preparations, it may be desirable to provide reducing agent free (or DTT free) enzyme preparations in treating the beads described herein. Examples of such enzymes include, e.g., polymerase enzyme preparations, reverse transcriptase enzyme preparations, ligase enzyme preparations, as well as many other enzyme preparations that may be used to treat the beads described herein. The terms “reducing agent free” or “DTT free” preparations can refer to a preparation having less than about 1/10th, less than about 1/50th, or even less than about 1/100th of the lower ranges for such materials used in degrading the beads. For example, for DTT, the reducing agent free preparation can have less than about 0.01 millimolar (mM), 0.005 mM, 0.001 mM DTT, 0.0005

mM DTT, or even less than about 0.0001 mM DTT. In many cases, the amount of DTT can be undetectable.

[00164] Numerous chemical triggers may be used to trigger the degradation of beads. Examples of these chemical changes may include, but are not limited to pH-mediated changes to the integrity of a component within the bead, degradation of a component of a bead via cleavage of cross-linked bonds, and depolymerization of a component of a bead.

[00165] In some embodiments, a bead may be formed from materials that comprise degradable chemical crosslinkers, such as BAC or cystamine. Degradation of such degradable crosslinkers may be accomplished through a number of mechanisms. In some examples, a bead may be contacted with a chemical degrading agent that may induce oxidation, reduction or other chemical changes. For example, a chemical degrading agent may be a reducing agent, such as dithiothreitol (DTT). Additional examples of reducing agents may include β -mercaptoethanol, (2S)-2-amino-1,4-dimercaptobutane (dithiobutylamine or DTBA), tris(2-carboxyethyl) phosphine (TCEP), or combinations thereof. A reducing agent may degrade the disulfide bonds formed between gel precursors forming the bead, and thus, degrade the bead. In other cases, a change in pH of a solution, such as an increase in pH, may trigger degradation of a bead. In other cases, exposure to an aqueous solution, such as water, may trigger hydrolytic degradation, and thus degradation of the bead.

[00166] Beads may also be induced to release their contents upon the application of a thermal stimulus. A change in temperature can cause a variety of changes to a bead. For example, heat can cause a solid bead to liquefy. A change in heat may cause melting of a bead such that a portion of the bead degrades. In other cases, heat may increase the internal pressure of the bead components such that the bead ruptures or explodes. Heat may also act upon heat-sensitive polymers used as materials to construct beads.

[00167] The methods, compositions, devices, and kits of this disclosure may be used with any suitable agent to degrade beads. In some embodiments, changes in temperature or pH may be used to degrade thermo-sensitive or pH-sensitive bonds within beads. In some embodiments, chemical degrading agents may be used to degrade chemical bonds within beads by oxidation, reduction or other chemical changes. For example, a chemical degrading agent may be a reducing agent, such as DTT, wherein DTT may degrade the disulfide bonds formed between a crosslinker and gel precursors, thus degrading the bead. In some embodiments, a reducing agent may be added to degrade the bead, which may or may not cause the bead to release its contents. Examples of reducing agents may include dithiothreitol (DTT), β -mercaptoethanol, (2S)-2-amino-1,4-dimercaptobutane (dithiobutylamine or DTBA), tris(2-carboxyethyl) phosphine (TCEP), or combinations thereof. The reducing agent may be present at a concentration of about

0.1mM, 0.5mM, 1mM, 5mM, 10mM. The reducing agent may be present at a concentration of at least about 0.1mM, 0.5mM, 1mM, 5mM, 10mM, or greater than 10 mM. The reducing agent may be present at concentration of at most about 10mM, 5mM, 1mM, 0.5mM, 0.1mM, or less.

[00168] Any suitable number of molecular tag molecules (e.g., primer, barcoded oligonucleotide) can be associated with a bead such that, upon release from the bead, the molecular tag molecules (e.g., primer, e.g., barcoded oligonucleotide) are present in the partition at a pre-defined concentration. Such pre-defined concentration may be selected to facilitate certain reactions for generating a sequencing library, e.g., amplification, within the partition. In some cases, the pre-defined concentration of the primer can be limited by the process of producing oligonucleotide bearing beads.

[00169] The compartments or partitions can be flowable within fluid streams. The partitions may comprise, for example, micro-vesicles that have an outer barrier surrounding an inner fluid center or core. In some cases, the partitions may comprise a porous matrix that is capable of entraining and/or retaining materials within its matrix. The partitions can comprise droplets of aqueous fluid within a non-aqueous continuous phase, e.g., an oil phase. The partitions can comprise droplets of a first phase within a second phase, wherein the first and second phases are immiscible. A variety of different vessels are described in, for example, U.S. Patent Application Publication No. 2014/0155295, which is entirely incorporated herein by reference for all purposes. Emulsion systems for creating stable droplets in non-aqueous or oil continuous phases are described in detail in, e.g., U.S. Patent Application Publication No. 2010/0105112, which is entirely incorporated herein by reference for all purposes.

[00170] In the case of droplets in an emulsion, allocating individual biological particles to discrete partitions may generally be accomplished by introducing a flowing stream of biological particles in an aqueous fluid into a flowing stream of a non-aqueous fluid, such that droplets are generated at the junction of the two streams. By providing the aqueous stream at a certain concentration of biological particles, the occupancy of the resulting partitions (e.g., number of biological particles per partition) can be controlled. Where single biological particle partitions are desired, the relative flow rates of the immiscible fluids can be selected such that, on average, the partitions contain less than one biological particle per partition, in order to ensure that those partitions that are occupied, are primarily singularly occupied. In some embodiments, the relative flow rates of the fluids can be selected such that a majority of partitions are occupied, e.g., allowing for only a small percentage of unoccupied partitions. The flows and channel architectures can be controlled as to ensure a desired number of singularly occupied partitions, less than a certain level of unoccupied partitions and/or less than a certain level of multiply occupied partitions.

[00171] The systems and methods described herein can be operated such that a majority of occupied partitions include no more than one biological particle per occupied partition. In some cases, the partitioning process is conducted such that fewer than 25% of the occupied partitions contain more than one biological particle, and in many cases, fewer than 20% of the occupied partitions have more than one biological particle. In some cases, fewer than 10% or even fewer than 5% of the occupied partitions include more than one biological particle per partition.

[00172] In some cases, it is desirable to avoid the creation of excessive numbers of empty partitions. For example, from a cost perspective and/or efficiency perspective, it may be desirable to minimize the number of empty partitions. However, while this may be accomplished by providing sufficient numbers of biological particles into the partitioning zone, the Poissonian distribution may expectedly increase the number of partitions that may include multiple biological particles. As such, at most about 95%, 90%, 85%, 80%, 75%, 70%, 65%, 60%, 55%, 50%, 45%, 40%, 35%, 30%, 25%, 20%, 15%, 10%, 5% or less of the generated partitions can be unoccupied. In some cases, the flow of one or more of the cells, or other fluids directed into the partitioning zone can be conducted such that, in many cases, no more than about 50% of the generated partitions, no more than about 25% of the generated partitions, or no more than about 10% of the generated partitions are unoccupied. These flows can be controlled so as to present non-Poissonian distribution of single occupied partitions while providing lower levels of unoccupied partitions. The above noted ranges of unoccupied partitions can be achieved while still providing any of the single occupancy rates described above. For example, in many cases, the use of the systems and methods described herein creates resulting partitions that have multiple occupancy rates of less than about 25%, less than about 20%, less than about 15%, less than about 10%, and in many cases, less than about 5%, while having unoccupied partitions of less than about 50%, less than about 40%, less than about 30%, less than about 20%, less than about 10%, less than about 5%, or less.

[00173] After the partitions are generated, comprising in part singularly occupied partitions, in part multiply occupied partitions, and/or in part unoccupied partitions, the occupied partitions can be sorted from the unoccupied partitions. In some cases, singularly occupied partitions may be isolated from non-singularly occupied partitions (e.g., multiply occupied partitions and unoccupied partitions). Such sorting can be achieved by including field attractable particles during the generation of droplets in an emulsion. For example, a flowing stream of aqueous fluid containing biological particles and field attractable particles can be introduced into a flowing stream of a non-aqueous fluid, such that droplets are generated at the junction of the two streams.

[00174] As will be appreciated, the above-described occupancy rates are also applicable to partitions that include both biological particles and additional reagents, including, but not limited to, microcapsules carrying barcoded oligonucleotides. The occupied partitions (e.g., at least about 10%, 20%, 30%, 40%, 50%, 60%, 70%, 80%, 90%, 95%, or 99% of the occupied partitions) can include both a microcapsule (e.g., bead) comprising barcoded oligonucleotides and a biological particle.

[00175] Although described in terms of providing substantially singularly occupied partitions, above, in certain cases, it is desirable to provide multiply occupied partitions, e.g., containing two, three, four or more cells and/or microcapsules (e.g., beads) comprising barcoded oligonucleotides within a single partition. Accordingly, as noted above, the flow characteristics of the biological particle and/or bead containing fluids and partitioning fluids may be controlled to provide for such multiply occupied partitions. In particular, the flow parameters may be controlled to provide a desired occupancy rate at greater than about 50% of the partitions, greater than about 75%, and in some cases greater than about 80%, 90%, 95%, or higher.

[00176] In some cases, additional microcapsules are used to deliver additional reagents to a partition. In such cases, it may be advantageous to introduce different beads into a common channel or droplet generation junction, from different bead sources, i.e., containing different associated reagents, through different channel inlets into such common channel or droplet generation junction. In such cases, the flow and frequency of the different beads into the channel or junction may be controlled to provide for the desired ratio of microcapsules from each source, while ensuring the desired pairing or combination of such beads into a partition with the desired number of biological particles.

[00177] The partitions described herein may comprise small volumes, e.g., less than about 10 microliters (μL), 5 μL , 1 μL , 900 picoliters (pL), 800 pL, 700 pL, 600 pL, 500 pL, 400pL, 300 pL, 200 pL, 100pL, 50 pL, 20 pL, 10 pL, 1 pL, 500 nanoliters (nL), 100 nL, 50 nL, or less.

[00178] For example, in the case of droplet based partitions, the droplets may have overall volumes that are less than about 1000 pL, 900 pL, 800 pL, 700 pL, 600 pL, 500 pL, 400pL, 300 pL, 200 pL, 100pL, 50 pL, 20 pL, 10 pL, 1 pL, or less. Where co-partitioned with microcapsules, it will be appreciated that the sample fluid volume, e.g., including co-partitioned biological particles, within the partitions may be less than about 90% of the above described volumes, less than about 80%, less than about 70%, less than about 60%, less than about 50%, less than about 40%, less than about 30%, less than about 20%, or less than about 10% the above described volumes.

[00179] As is described elsewhere herein, partitioning species may generate a population or plurality of partitions. In such cases, any suitable number of partitions can be generated to

generate the plurality of partitions. For example, in a method described herein, a plurality of partitions may be generated that comprises at least about 1,000 partitions, at least about 5,000 partitions, at least about 10,000 partitions, at least about 50,000 partitions, at least about 100,000 partitions, at least about 500,000 partitions, at least about 1,000,000 partitions, at least about 5,000,000 partitions at least about 10,000,000 partitions, at least about 50,000,000 partitions, at least about 100,000,000 partitions, at least about 500,000,000 partitions, at least about 1,000,000,000 partitions, or more. Moreover, the plurality of partitions may comprise both unoccupied partitions (e.g., empty partitions) and occupied partitions.

[00180] Microfluidic channel networks can be utilized to generate partitions as described herein. Alternative mechanisms may also be employed in the partitioning of individual biological particles, including porous membranes through which aqueous mixtures of cells are extruded into non-aqueous fluids.

[00181] **FIG. 1** shows an example of a microfluidic channel structure for partitioning individual biological particles. As described elsewhere herein, in some cases, the majority of occupied partitions can include no more than one biological particle per occupied partition and, in some cases, some of the generated partitions can be unoccupied (of any biological particle). In some cases, though, some of the occupied partitions may include more than one biological particle. In some cases, the partitioning process may be controlled such that fewer than about 25% of the occupied partitions contain more than one biological particle, and in many cases, fewer than about 20% of the occupied partitions have more than one biological particle, while in some cases, fewer than about 10% or even fewer than about 5% of the occupied partitions include more than one biological particle per partition.

[00182] As shown in **FIG. 1**, the channel structure can include channel segments **102**, **104**, **106** and **108** communicating at a channel junction **110**. In operation, a first aqueous fluid **112** that includes suspended biological particles (e.g., cells) **114** and suspended field-attractable particles **115**, may be transported along channel segment **102** into junction **110**, while a second fluid **116** that is immiscible with the aqueous fluid **112** is delivered to the junction **110** from each of channel segments **104** and **106** to create discrete droplets **118**, **120** of the first aqueous fluid **112** flowing into channel segment **108**, and flowing away from junction **110**. A discrete droplet generated may include an individual biological particle **114** and field-attractable particles **115** (such as droplets **118**). A discrete droplet generated may include more than one individual biological particle **114** and field-attractable particles **115** (not shown in **FIG. 1**). A discrete droplet may contain field-attractable particles **115** but no biological particle **114** (such as droplet **120**).

[00183] The field-attractable particles **115** may be paramagnetic particles. In some cases, the field-attractable particles may be superparamagnetic particles. For example, the field-attractable particles can comprise polystyrene magnetic particles (e.g., polystyrene core particle coated with at least a layer of magnetite (e.g., iron oxide) and polystyrene), amino magnetic particles, carboxyl magnetic particles, dimethylamino magnetic particles, hydroxyethyl magnetic particles, and/or a combination of the above. A paramagnetic particle can comprise a polymer matrix of amine silane, glucuronic acid, bromoacetyl, chitosan, carboxymethyldextran, citric acid, starch, DEAE-starch, phosphate-starch, dextran, dextran-sulfate, lipid, oleic acid, diphosphate, polyaspartic acid, polyacrylamide, polyacrylic acid, polydimethylamine, polyethylene glycole alpha-methoxy-omega-amine, polyethylene glycol alpha-,omega-diphosphate, poly(maleic acid-co-olefin), polystyrenesulfonate, polyvinyl alcohol, poly(4-vinylpyridine), poly-diallyldimethylamin, uncoated magnetite, and/or other matrices. A paramagnetic particle may have micrometer or nanometer size. For example, a paramagnetic particle can have a maximum dimension (e.g., width, length, height, diameter, etc.) of at most about 20 micrometers (μm), 10 μm , 9 μm , 8 μm , 7 μm , 6 μm , 5 μm , 4 μm , 3 μm , 2 μm , 1 μm , 0.5 μm , or less. The paramagnetic particle can have a maximum dimension of at most about 500 nanometer (nm), 400 nm, 300 nm, 200 nm, 100 nm, 50 nm, 40 nm, 30 nm, 20 nm, 10 nm, 9 nm, 8 nm, 7 nm, 6 nm, 5 nm, 4 nm, 3 nm, 2 nm, 1 nm, or less. Alternatively, a paramagnetic particle can have a maximum dimension that is greater than about 20 μm . The paramagnetic particles may be responsive when exposed to magnetic fields. In some cases, the paramagnetic particles can be smooth surface particles, wherein a thick polymer layer coats the magnetite (e.g., iron oxide) layer. The smooth surface can shield the magnetite from interfering with enzyme activities or other undesirable effects with other particles or cells caused by exposure to the magnetite. In some cases, the paramagnetic particles can be cross-linked particles, wherein the particles are coated with cross-linked polymer on the surfaces of the iron oxide crystals. The cross-linked polymer can render the paramagnetic particle resistant to common organic solvents, such as acetone, acetonitrile, dimethylformamide (DMF) and chloroform. The magnetite content on each paramagnetic particle can be adjusted (e.g., to have higher or lower percentage) to be more responsive or less responsive to the same magnetic field. In some cases, the field-attractable particles can be diamagnetic particles or ferromagnetic particles.

[00184] In some cases, the field-attractable particles **115** may be conductive particles. A conductive particle may have micrometer or nanometer size. For example, a conductive particle can have a maximum dimension (e.g., width, length, height, diameter, etc.) of at most about 20 micrometers (μm), 10 μm , 9 μm , 8 μm , 7 μm , 6 μm , 5 μm , 4 μm , 3 μm , 2 μm , 1 μm , 0.5 μm , or less. The conductive particle can have a maximum dimension of at most about 500 nanometer

(nm), 400 nm, 300 nm, 200 nm, 100 nm, 50 nm, 40 nm, 30 nm, 20 nm, 10 nm, 9 nm, 8 nm, 7 nm, 6 nm, 5 nm, 4 nm, 3 nm, 2 nm, 1 nm, or less. Alternatively, a conductive particle can have a maximum dimension that is greater than about 20 μm . A conductive particle can have a substantially spherical shape. Alternatively, a conductive particle can have a different shape. The conductive particles may be responsive when exposed to electric fields. The conductive (e.g., metal) content on each conductive particle can be adjusted (e.g., to have higher or lower percentage) to be more responsive or less responsive to the same electric field. In some cases, the field-attractable particles **115** can comprise both paramagnetic and conductive particles.

[00185] The first aqueous fluid **112** can have a substantially uniform concentration of field-attractable particles **115** as the first aqueous fluid **112** is introduced into junction **110**. For example, the concentration of the field-attractable particles **115** in the first aqueous fluid **112** in the channel segment **102** at time x can be substantially uniform with the concentration of field-attractable particles **115** in the first aqueous fluid **112** in the channel segment **102** at time $x+\delta$ (where x and δ are positive). In some instances, the concentration of field-attractable particles **115** can be substantially uniform in only the volume of the first aqueous fluid **112**, that is, the volume not including the volume of each of the biological particles **114** suspended in the first aqueous fluid **112**.

[00186] This second fluid **116** can comprise an oil, such as a fluorinated oil, that includes a fluorosurfactant for stabilizing the resulting droplets, e.g., inhibiting subsequent coalescence of the resulting droplets. Examples of particularly useful partitioning fluids and fluorosurfactants are described for example, in U.S. Patent Application Publication No. 2010/0105112, which is entirely incorporated herein by reference for all purposes.

[00187] The generated droplets may comprise two subsets of droplets: (1) occupied droplets **118**, containing one or more biological particles **114**, and (2) unoccupied droplets **120**, not containing any biological particles **114**. Each droplet generated, occupied or unoccupied, may contain some number and/or concentration of field-attractable particles **115**. In some instances, the concentration of the field-attractable particles **115** in each of the unoccupied droplets **120** can be substantially uniform, wherein the concentration is a number of field-attractable particles per total droplet volume (and not just the volume of the first aqueous fluid **112** in the droplet). In some instances, the concentration of the field-attractable particles **115** in each of the occupied droplets **118** can be substantially uniform, wherein the concentration is a number of field-attractable particles per total droplet volume. In other instances, as can be easily appreciated, the concentration of the field-attractable particles **115** in each of the occupied droplets **118** can vary with size and/or the number of biological particles **114** contained in the droplet. In any case, the concentration of field-attractable particles in any of the unoccupied droplets **120** can be greater

than the concentration of field-attractable particles in any of the occupied droplets **118** to account for the volume occupied by the biological particle **114** in the occupied droplets **118**. In most cases, the concentration of field-attractable particles in a droplet from the unoccupied droplets **120** can be greater than the concentration of field-attractable particles in a droplet from the occupied droplets **118** to account for the volume occupied by the biological particle **114** in the occupied droplets **118**.

[00188] For example, assuming that (i) the droplet is spherical and has the radius R_D , (ii) a biological particle is spherical and has the radius R_+ , and (iii) the concentration of field-attractable particles in the volume of aqueous fluid is substantially uniform, the ratio of a number of field-attractable particles in a singularly occupied droplet (N_+) to a number of field-attractable particles in an unoccupied droplet (N_-) will be:

$$\frac{N_+}{N_-} = 1 - \left(\frac{R_+}{R_D}\right)^3$$

[00189] As can be appreciated, the above ratio may change with deviations from the above assumptions. For example, an occupied droplet containing three biological particles can have a ratio of about: $1 - 3\left(\frac{R_+}{R_D}\right)^3$.

[00190] In another aspect, in addition to or as an alternative to droplet based partitioning, biological particles may be encapsulated within a microcapsule, such as a cell bead, that comprises an outer shell or layer or porous matrix in which is entrained one or more individual biological particles or small groups of biological particles, and may include other reagents. Encapsulation of biological particles may be performed by a variety of processes. Such processes combine an aqueous fluid containing the biological particles and also containing the field-attractable particles to be analyzed with a polymeric precursor material that may be capable of being formed into a gel or other solid or semi-solid matrix upon application of a particular stimulus to the polymer precursor. Such stimuli include, e.g., thermal stimuli (either heating or cooling), photo-stimuli (e.g., through photo-curing), chemical stimuli (e.g., through crosslinking, polymerization initiation of the precursor (e.g., through added initiators), or the like.

[00191] Preparation of microcapsules comprising biological particles may be performed by a variety of methods. For example, air knife droplet or aerosol generators may be used to dispense droplets of precursor fluids into gelling solutions in order to form microcapsules that include individual biological particles or small groups of biological particles. Likewise, membrane based encapsulation systems may be used to generate microcapsules comprising encapsulated biological particles as described herein. Microfluidic systems of the present disclosure, such as that shown in **FIG. 1**, may be readily used in encapsulating cells as described herein, such as to generate a plurality of particles, each particle comprising field-attractable particles. The

plurality of particles may comprise a first subset of particles occupied by biological particles (e.g., cell beads) and a second subset of particles unoccupied by biological particles. In particular, and with reference to **FIG. 1**, the aqueous fluid comprising (i) the biological particles **114**, (ii) the field-attractable particles **115**, and (ii) the polymer precursor material (not shown) is flowed into channel junction **110**, where it is partitioned into droplets **118** or **120** comprising or not comprising the individual biological particles **114**, respectively, but always comprising the field-attractable particles **115**, through the flow of non-aqueous fluid **116**. In the case of encapsulation methods, non-aqueous fluid **116** may also include an initiator to cause polymerization and/or crosslinking of the polymer precursor to form the microcapsule that includes the entrained biological particles. Examples of polymer precursor/initiator pairs include those described in U.S. Patent Application Publication No. 2014/0378345, which is entirely incorporated herein by reference for all purposes.

[00192] For example, in the case where the polymer precursor material comprises a linear polymer material, e.g., a linear polyacrylamide, PEG, or other linear polymeric material, the activation agent may comprise a cross-linking agent, or a chemical that activates a cross-linking agent within the formed droplets. Likewise, for polymer precursors that comprise polymerizable monomers, the activation agent may comprise a polymerization initiator. For example, in certain cases, where the polymer precursor comprises a mixture of acrylamide monomer with a N,N'-bis-(acryloyl)cystamine (BAC) comonomer, an agent such as tetraethylmethylenediamine (TEMED) may be provided within the second fluid streams in channel segments **104** and **106**, which initiates the copolymerization of the acrylamide and BAC into a cross-linked polymer network or, hydrogel.

[00193] Upon contact of the second fluid stream **116** with the first fluid stream **112** at junction **110** in the formation of droplets, the TEMED may diffuse from the second fluid **116** into the aqueous first fluid **112** comprising the linear polyacrylamide, which will activate the crosslinking of the polyacrylamide within the droplets, resulting in the formation of the gel, e.g., hydrogel, microcapsules (e.g., droplet **118**, **120**), as solid or semi-solid beads or particles entraining the cells **114**. Although described in terms of polyacrylamide encapsulation, other 'activatable' encapsulation compositions may also be employed in the context of the methods and compositions described herein. For example, formation of alginate droplets followed by exposure to divalent metal ions, e.g., Ca^{2+} , can be used as an encapsulation process using the described processes. Likewise, agarose droplets may also be transformed into capsules through temperature based gelling, e.g., upon cooling, or the like. In some cases, encapsulated biological particles can be selectively releasable from the microcapsule, e.g., through passage of time, or upon application of a particular stimulus, that degrades the microcapsule sufficiently to allow the

cell, or its contents to be released from the microcapsule, e.g., into a partition, such as a droplet. For example, in the case of the polyacrylamide polymer described above, degradation of the microcapsule may be accomplished through the introduction of an appropriate reducing agent, such as DTT or the like, to cleave disulfide bonds that cross link the polymer matrix (See, e.g., U.S. Patent Application Publication No. 2014/0378345, which is entirely incorporated herein by reference for all purposes).

[00194] Encapsulated biological particles (e.g., cell beads) can provide certain potential advantages of being storable, and more portable than droplet based partitioned biological particles. Furthermore, in some cases, it may be desirable to allow biological particles to be analyzed to incubate for a select period of time, in order to characterize changes in such biological particles over time, either in the presence or absence of different stimuli. In such cases, encapsulation of individual biological particles may allow for longer incubation than partitioning in emulsion droplets, although in some cases, droplet partitioned biological particles may also be incubated for different periods of time, e.g., at least 10 seconds, at least 30 seconds, at least 1 minute, at least 5 minutes, at least 10 minutes, at least 30 minutes, at least 1 hour, at least 2 hours, at least 5 hours, or at least 10 hours or more. The encapsulation of biological particles may constitute the partitioning of the biological particles into which other reagents are co-partitioned. Alternatively, encapsulated biological particles may be readily deposited into other partitions, e.g., droplets, as described above.

[00195] In accordance with certain aspects, the biological particles may be partitioned along with lysis reagents in order to release the contents of the biological particles within the partition. In such cases, the lysis agents can be contacted with the biological particle suspension concurrently with, or immediately prior to the introduction of the biological particles into the partitioning junction/droplet generation zone, e.g., through an additional channel or channels upstream of channel junction 110. Examples of lysis agents include bioactive reagents, such as lysis enzymes that are used for lysis of different cell types, e.g., gram positive or negative bacteria, plants, yeast, mammalian, etc., such as lysozymes, achromopeptidase, lysostaphin, labiase, kitalase, lyticase, and a variety of other lysis enzymes available from, e.g., Sigma-Aldrich, Inc. (St Louis, MO), as well as other commercially available lysis enzymes. Other lysis agents may additionally or alternatively be co-partitioned with the biological particles to cause the release of the biological particles' contents into the partitions. For example, in some cases, surfactant based lysis solutions may be used to lyse cells, although these may be less desirable for emulsion based systems where the surfactants can interfere with stable emulsions. In some cases, lysis solutions may include non-ionic surfactants such as, for example, TritonX-100 and Tween 20. In some cases, lysis solutions may include ionic surfactants such as, for example,

sarcosyl and sodium dodecyl sulfate (SDS). Electroporation, thermal, acoustic or mechanical cellular disruption may also be used in certain cases, e.g., non-emulsion based partitioning such as encapsulation of biological particles that may be in addition to or in place of droplet partitioning, where any pore size of the encapsulate is sufficiently small to retain nucleic acid fragments of a desired size, following cellular disruption.

[00196] In addition to the lysis agents co-partitioned with the biological particles described above, other reagents can also be co-partitioned with the biological particles, including, for example, DNase and RNase inactivating agents or inhibitors, such as proteinase K, chelating agents, such as EDTA, and other reagents employed in removing or otherwise reducing negative activity or impact of different cell lysate components on subsequent processing of nucleic acids. In addition, in the case of encapsulated biological particles, the biological particles may be exposed to an appropriate stimulus to release the biological particles or their contents from a co-partitioned microcapsule. For example, in some cases, a chemical stimulus may be co-partitioned along with an encapsulated biological particle to allow for the degradation of the microcapsule and release of the cell or its contents into the larger partition. In some cases, this stimulus may be the same as the stimulus described elsewhere herein for release of oligonucleotides from their respective microcapsule (e.g., bead). In alternative aspects, this may be a different and non-overlapping stimulus, in order to allow an encapsulated biological particle to be released into a partition at a different time from the release of oligonucleotides into the same partition.

[00197] Additional reagents may also be co-partitioned with the biological particles, such as endonucleases to fragment a biological particle's DNA, DNA polymerase enzymes and dNTPs used to amplify the biological particle's nucleic acid fragments and to attach the barcode molecular tags to the amplified fragments. Additional reagents may also include reverse transcriptase enzymes, including enzymes with terminal transferase activity, primers and oligonucleotides, and switch oligonucleotides (also referred to herein as "switch oligos" or "template switching oligonucleotides") which can be used for template switching. In some cases, template switching can be used to increase the length of a cDNA. In some cases, template switching can be used to append a predefined nucleic acid sequence to the cDNA. In an example of template switching, cDNA can be generated from reverse transcription of a template, e.g., cellular mRNA, where a reverse transcriptase with terminal transferase activity can add additional nucleotides, e.g., polyC, to the cDNA in a template independent manner. Switch oligos can include sequences complementary to the additional nucleotides, e.g., polyG. The additional nucleotides (e.g., polyC) on the cDNA can hybridize to the additional nucleotides (e.g., polyG) on the switch oligo, whereby the switch oligo can be used by the reverse transcriptase as template to further extend the cDNA. Template switching oligonucleotides may

comprise a hybridization region and a template region. The hybridization region can comprise any sequence capable of hybridizing to the target. In some cases, as previously described, the hybridization region comprises a series of G bases to complement the overhanging C bases at the 3' end of a cDNA molecule. The series of G bases may comprise 1 G base, 2 G bases, 3 G bases, 4 G bases, 5 G bases or more than 5 G bases. The template sequence can comprise any sequence to be incorporated into the cDNA. In some cases, the template region comprises at least 1 (e.g., at least 2, 3, 4, 5 or more) tag sequences and/or functional sequences. Switch oligos may comprise deoxyribonucleic acids, ribonucleic acids; modified nucleic acids including 2-Aminopurine, 2,6-Diaminopurine (2-Amino-dA), inverted dT, 5-Methyl dC, 2'-deoxyInosine, Super T (5-hydroxybutynl-2'-deoxyuridine), Super G (8-aza-7-deazaguanosine), locked nucleic acids (LNAs), unlocked nucleic acids (UNAs, e.g., UNA-A, UNA-U, UNA-C, UNA-G), Iso-dG, Iso-dC, 2' Fluoro bases (e.g., Fluoro C, Fluoro U, Fluoro A, and Fluoro G), or any combination.

[00198] In some cases, the length of a switch oligo may be 2, 3, 4, 5, 6, 7, 8, 9, 10, 11, 12, 13, 14, 15, 16, 17, 18, 19, 20, 21, 22, 23, 24, 25, 26, 27, 28, 29, 30, 31, 32, 33, 34, 35, 36, 37, 38, 39, 40, 41, 42, 43, 44, 45, 46, 47, 48, 49, 50, 51, 52, 53, 54, 55, 56, 57, 58, 59, 60, 61, 62, 63, 64, 65, 66, 67, 68, 69, 70, 71, 72, 73, 74, 75, 76, 77, 78, 79, 80, 81, 82, 83, 84, 85, 86, 87, 88, 89, 90, 91, 92, 93, 94, 95, 96, 97, 98, 99, 100, 101, 102, 103, 104, 105, 106, 107, 108, 109, 110, 111, 112, 113, 114, 115, 116, 117, 118, 119, 120, 121, 122, 123, 124, 125, 126, 127, 128, 129, 130, 131, 132, 133, 134, 135, 136, 137, 138, 139, 140, 141, 142, 143, 144, 145, 146, 147, 148, 149, 150, 151, 152, 153, 154, 155, 156, 157, 158, 159, 160, 161, 162, 163, 164, 165, 166, 167, 168, 169, 170, 171, 172, 173, 174, 175, 176, 177, 178, 179, 180, 181, 182, 183, 184, 185, 186, 187, 188, 189, 190, 191, 192, 193, 194, 195, 196, 197, 198, 199, 200, 201, 202, 203, 204, 205, 206, 207, 208, 209, 210, 211, 212, 213, 214, 215, 216, 217, 218, 219, 220, 221, 222, 223, 224, 225, 226, 227, 228, 229, 230, 231, 232, 233, 234, 235, 236, 237, 238, 239, 240, 241, 242, 243, 244, 245, 246, 247, 248, 249, 250 nucleotides or longer.

[00199] In some cases, the length of a switch oligo may be at least 2, 3, 4, 5, 6, 7, 8, 9, 10, 11, 12, 13, 14, 15, 16, 17, 18, 19, 20, 21, 22, 23, 24, 25, 26, 27, 28, 29, 30, 31, 32, 33, 34, 35, 36, 37, 38, 39, 40, 41, 42, 43, 44, 45, 46, 47, 48, 49, 50, 51, 52, 53, 54, 55, 56, 57, 58, 59, 60, 61, 62, 63, 64, 65, 66, 67, 68, 69, 70, 71, 72, 73, 74, 75, 76, 77, 78, 79, 80, 81, 82, 83, 84, 85, 86, 87, 88, 89, 90, 91, 92, 93, 94, 95, 96, 97, 98, 99, 100, 101, 102, 103, 104, 105, 106, 107, 108, 109, 110, 111, 112, 113, 114, 115, 116, 117, 118, 119, 120, 121, 122, 123, 124, 125, 126, 127, 128, 129, 130, 131, 132, 133, 134, 135, 136, 137, 138, 139, 140, 141, 142, 143, 144, 145, 146, 147, 148, 149, 150, 151, 152, 153, 154, 155, 156, 157, 158, 159, 160, 161, 162, 163, 164, 165, 166, 167, 168, 169, 170, 171, 172, 173, 174, 175, 176, 177, 178, 179, 180, 181, 182, 183, 184, 185, 186, 187, 188, 189, 190, 191, 192, 193, 194, 195, 196, 197, 198, 199, 200, 201, 202, 203, 204, 205, 206,

207, 208, 209, 210, 211, 212, 213, 214, 215, 216, 217, 218, 219, 220, 221, 222, 223, 224, 225, 226, 227, 228, 229, 230, 231, 232, 233, 234, 235, 236, 237, 238, 239, 240, 241, 242, 243, 244, 245, 246, 247, 248, 249 or 250 nucleotides or longer.

[00200] In some cases, the length of a switch oligo may be at most 2, 3, 4, 5, 6, 7, 8, 9, 10, 11, 12, 13, 14, 15, 16, 17, 18, 19, 20, 21, 22, 23, 24, 25, 26, 27, 28, 29, 30, 31, 32, 33, 34, 35, 36, 37, 38, 39, 40, 41, 42, 43, 44, 45, 46, 47, 48, 49, 50, 51, 52, 53, 54, 55, 56, 57, 58, 59, 60, 61, 62, 63, 64, 65, 66, 67, 68, 69, 70, 71, 72, 73, 74, 75, 76, 77, 78, 79, 80, 81, 82, 83, 84, 85, 86, 87, 88, 89, 90, 91, 92, 93, 94, 95, 96, 97, 98, 99, 100, 101, 102, 103, 104, 105, 106, 107, 108, 109, 110, 111, 112, 113, 114, 115, 116, 117, 118, 119, 120, 121, 122, 123, 124, 125, 126, 127, 128, 129, 130, 131, 132, 133, 134, 135, 136, 137, 138, 139, 140, 141, 142, 143, 144, 145, 146, 147, 148, 149, 150, 151, 152, 153, 154, 155, 156, 157, 158, 159, 160, 161, 162, 163, 164, 165, 166, 167, 168, 169, 170, 171, 172, 173, 174, 175, 176, 177, 178, 179, 180, 181, 182, 183, 184, 185, 186, 187, 188, 189, 190, 191, 192, 193, 194, 195, 196, 197, 198, 199, 200, 201, 202, 203, 204, 205, 206, 207, 208, 209, 210, 211, 212, 213, 214, 215, 216, 217, 218, 219, 220, 221, 222, 223, 224, 225, 226, 227, 228, 229, 230, 231, 232, 233, 234, 235, 236, 237, 238, 239, 240, 241, 242, 243, 244, 245, 246, 247, 248, 249 or 250 nucleotides.

[00201] Once the contents of the cells are released into their respective partitions, the macromolecular components (e.g., macromolecular constituents of biological particles, such as RNA, DNA, or proteins) contained therein may be further processed within the partitions. In accordance with the methods and systems described herein, the macromolecular component contents of individual biological particles can be provided with unique identifiers such that, upon characterization of those macromolecular components they may be attributed as having been derived from the same biological particle or particles. The ability to attribute characteristics to individual biological particles or groups of biological particles is provided by the assignment of unique identifiers specifically to an individual biological particle or groups of biological particles. Unique identifiers, e.g., in the form of nucleic acid barcodes, can be assigned or associated with individual biological particles or populations of biological particle, in order to tag or label the biological particle's macromolecular components (and as a result, its characteristics) with the unique identifiers. These unique identifiers can then be used to attribute the biological particle's components and characteristics to an individual biological particle or group of biological particles. In some aspects, this is performed by co-partitioning the individual biological particle or groups of biological particles with the unique identifiers. In some aspects, the unique identifiers are provided in the form of oligonucleotides that comprise nucleic acid barcode sequences that may be attached to or otherwise associated with the nucleic acid contents of individual biological particle, or to other components of the biological particle, and

particularly to fragments of those nucleic acids. The oligonucleotides are partitioned such that as between oligonucleotides in a given partition, the nucleic acid barcode sequences contained therein are the same, but as between different partitions, the oligonucleotides can, and do, have differing barcode sequences, or at least represent a large number of different barcode sequences across all of the partitions in a given analysis. In some aspects, only one nucleic acid barcode sequence can be associated with a given partition, although in some cases, two or more different barcode sequences may be present.

[00202] The nucleic acid barcode sequences can include from 6 to about 20 or more nucleotides within the sequence of the oligonucleotides. In some cases, the length of a barcode sequence may be 6, 7, 8, 9, 10, 11, 12, 13, 14, 15, 16, 17, 18, 19, 20 nucleotides or longer. In some cases, the length of a barcode sequence may be at least 6, 7, 8, 9, 10, 11, 12, 13, 14, 15, 16, 17, 18, 19, 20 nucleotides or longer. In some cases, the length of a barcode sequence may be at most 6, 7, 8, 9, 10, 11, 12, 13, 14, 15, 16, 17, 18, 19, 20 nucleotides or shorter. These nucleotides may be completely contiguous, i.e., in a single stretch of adjacent nucleotides, or they may be separated into two or more separate subsequences that are separated by 1 or more nucleotides. In some cases, separated barcode subsequences can be from about 4 to about 16 nucleotides in length. In some cases, the barcode subsequence may be 4, 5, 6, 7, 8, 9, 10, 11, 12, 13, 14, 15, 16 nucleotides or longer. In some cases, the barcode subsequence may be at least 4, 5, 6, 7, 8, 9, 10, 11, 12, 13, 14, 15, 16 nucleotides or longer. In some cases, the barcode subsequence may be at most 4, 5, 6, 7, 8, 9, 10, 11, 12, 13, 14, 15, 16 nucleotides or shorter.

[00203] The co-partitioned oligonucleotides can also comprise other functional sequences useful in the processing of the nucleic acids from the co-partitioned biological particles. These sequences include, e.g., targeted or random/universal amplification primer sequences for amplifying the genomic DNA from the individual biological particles within the partitions while attaching the associated barcode sequences, sequencing primers or primer recognition sites, hybridization or probing sequences, e.g., for identification of presence of the sequences or for pulling down barcoded nucleic acids, or any of a number of other potential functional sequences. Other mechanisms of co-partitioning oligonucleotides may also be employed, including, e.g., coalescence of two or more droplets, where one droplet contains oligonucleotides, or microdispensing of oligonucleotides into partitions, e.g., droplets within microfluidic systems.

[00204] In an example, microcapsules, such as beads (e.g., see **FIG. 19**), are provided that each includes large numbers of the above described barcoded oligonucleotides releasably attached to the beads, where all of the oligonucleotides attached to a particular bead will include the same nucleic acid barcode sequence, but where a large number of diverse barcode sequences are represented across the population of beads used. In some embodiments, hydrogel beads, e.g.,

comprising polyacrylamide polymer matrices, are used as a solid support and delivery vehicle for the oligonucleotides into the partitions, as they are capable of carrying large numbers of oligonucleotide molecules, and may be configured to release those oligonucleotides upon exposure to a particular stimulus, as described elsewhere herein. In some cases, the population of beads will provide a diverse barcode sequence library that includes at least about 1,000 different barcode sequences, at least about 5,000 different barcode sequences, at least about 10,000 different barcode sequences, at least about 50,000 different barcode sequences, at least about 100,000 different barcode sequences, at least about 1,000,000 different barcode sequences, at least about 5,000,000 different barcode sequences, or at least about 10,000,000 different barcode sequences, or more. Additionally, each bead can be provided with large numbers of oligonucleotide molecules attached. In particular, the number of molecules of oligonucleotides including the barcode sequence on an individual bead can be at least about 1,000 oligonucleotide molecules, at least about 5,000 oligonucleotide molecules, at least about 10,000 oligonucleotide molecules, at least about 50,000 oligonucleotide molecules, at least about 100,000 oligonucleotide molecules, at least about 500,000 oligonucleotides, at least about 1,000,000 oligonucleotide molecules, at least about 5,000,000 oligonucleotide molecules, at least about 10,000,000 oligonucleotide molecules, at least about 50,000,000 oligonucleotide molecules, at least about 100,000,000 oligonucleotide molecules, and in some cases at least about 1 billion oligonucleotide molecules, or more.

[00205] Moreover, when the population of beads is partitioned, the resulting population of partitions can also include a diverse barcode library that includes at least about 1,000 different barcode sequences, at least about 5,000 different barcode sequences, at least about 10,000 different barcode sequences, at least at least about 50,000 different barcode sequences, at least about 100,000 different barcode sequences, at least about 1,000,000 different barcode sequences, at least about 5,000,000 different barcode sequences, or at least about 10,000,000 different barcode sequences. Additionally, each partition of the population can include at least about 1,000 oligonucleotide molecules, at least about 5,000 oligonucleotide molecules, at least about 10,000 oligonucleotide molecules, at least about 50,000 oligonucleotide molecules, at least about 100,000 oligonucleotide molecules, at least about 500,000 oligonucleotides, at least about 1,000,000 oligonucleotide molecules, at least about 5,000,000 oligonucleotide molecules, at least about 10,000,000 oligonucleotide molecules, at least about 50,000,000 oligonucleotide molecules, at least about 100,000,000 oligonucleotide molecules, and in some cases at least about 1 billion oligonucleotide molecules.

[00206] In some cases, it may be desirable to incorporate multiple different barcodes within a given partition, either attached to a single or multiple beads within the partition. For example, in

some cases, a mixed, but known barcode sequences set may provide greater assurance of identification in the subsequent processing, e.g., by providing a stronger address or attribution of the barcodes to a given partition, as a duplicate or independent confirmation of the output from a given partition.

[00207] The oligonucleotides are releasable from the beads upon the application of a particular stimulus to the beads. In some cases, the stimulus may be a photo-stimulus, e.g., through cleavage of a photo-labile linkage that releases the oligonucleotides. In other cases, a thermal stimulus may be used, where elevation of the temperature of the beads environment will result in cleavage of a linkage or other release of the oligonucleotides from the beads. In still other cases, a chemical stimulus is used that cleaves a linkage of the oligonucleotides to the beads, or otherwise results in release of the oligonucleotides from the beads. In one case, such compositions include the polyacrylamide matrices described above for encapsulation of biological particles, and may be degraded for release of the attached oligonucleotides through exposure to a reducing agent, such as DTT.

[00208] For example, in **FIG. 1**, concurrent to the stream of the first aqueous fluid **112** flowing through channel **102** towards the junction **110**, a second aqueous stream comprising barcode carrying beads suspended in a third fluid can be flowed through another channel (not shown in **FIG. 1**) towards the junction **110**. The third fluid can be the same fluid material as the first aqueous fluid **112**. A non-aqueous partitioning fluid **116** is introduced into channel junction **110** from each of side channels **104** and **106**, and the combined streams are flowed into outlet channel **108**. Within channel junction **110**, the two combined aqueous streams from channel segments **102** and the other channel carrying the third fluid are combined, and partitioned into droplets **118**, **120**. The occupied droplets may contain either one or more biological particles, either one or more barcode carrying beads, or both at least a biological particle and at least a barcode carrying bead. The unoccupied droplets may contain neither biological particles nor barcode carrying beads. However, all droplets, both occupied and unoccupied droplets, can comprise at least some concentration of field-attractable particles **115**. As noted previously, by controlling the flow characteristics of each of the fluids combining at channel junction **110**, as well as controlling the geometry of the channel junction, partitioning can be optimized to achieve a desired occupancy level of beads, biological particles, or both, within the partitions that are generated.

[00209] In some cases, assuming that (i) the droplet is spherical and has the radius R_D , (ii) a biological particle is spherical and has the radius R_+ , (iii) a barcode carrying bead is spherical and has the radius R_B and (iv) the concentration of field-attractable particles in the volume of aqueous fluid is substantially uniform, the ratio of a number of field-attractable particles in a

singularly occupied droplet ($N_{+,B}$) (containing one of each of a biological particle and a barcode carrying bead) to a number of field-attractable particles in an unoccupied droplet (N_-) will be:

$$\frac{N_{+,B}}{N_-} = 1 - \left(\frac{R_+}{R_D}\right)^3 - \left(\frac{R_B}{R_D}\right)^3$$

[00210] FIG. 2A shows an example of a microfluidic channel structure for separating occupied droplets from unoccupied droplets. As described elsewhere herein, when droplets are generated, there may be a first subset population of occupied droplets containing one or more biological particles and a second subset population of unoccupied droplets not containing any biological particles. In some cases, the droplets may additionally contain one or more barcode carrying beads. For example, a droplet may have only a biological particle, a droplet may have only a barcode carrying bead, a droplet may have both a biological particle and a barcode carrying bead, or a droplet may have neither biological particles nor barcode carrying beads. In some cases, the majority of occupied partitions can include no more than one biological particle per occupied partition and, in some cases, some of the generated partitions can be unoccupied (of any biological particle). In some cases, though, some of the occupied partitions may include more than one biological particle. In some cases, the partitioning process may be controlled such that fewer than 25% of the occupied partitions contain more than one biological particle, and in many cases, fewer than 20% of the occupied partitions have more than one biological particle, while in some cases, fewer than 10% or even fewer than 5% of the occupied partitions include more than one biological particle per partition.

[00211] As shown in FIG. 2A, the channel structure can include channel segments 202, 204, and 206 meeting at a channel intersection 211. In some instances, the outflow channel 108 of the emulsion carrying the generated droplets in FIG. 1 can be upstream of the channel segment 202, such that the generated droplets are directed to flow to the channel intersection 211 for subsequent sorting. A controller 220 can be operatively coupled to a fluid flow unit 218, to facilitate flow of fluid in the channel structure, and a field application unit 216, to apply one or more fields to the channel structure.

[00212] In operation, a plurality of discrete droplets, each comprising a first aqueous fluid 210 can flow as emulsions in a second fluid 208, wherein the second fluid 208 is immiscible to the first aqueous fluid 210. The droplets being transported along channel segment 202 into intersection 211 can comprise a first subset of droplets 214 that are each occupied with at least a biological particle and/or a barcode carrying bead and a second subset of droplets 212 that are each unoccupied. Every droplet, including occupied and unoccupied droplets, can comprise some concentration of field-attractable particles. As described above, a given unoccupied droplet can have a higher concentration of field-attractable particles than a given occupied

droplet to account for the volume occupied by a biological particle and/or a barcode bead in an occupied droplet.

[00213] After sorting at or near the intersection **211**, the first subset of droplets **214** can be directed to flow along channel segment **206** and away from the intersection **211**, and the second subset of droplets **212** can be directed to flow along channel segment **204** and away from the intersection **211**.

[00214] The fluid flow unit **218** can be configured to subject the second fluid **208** containing a plurality of droplets, including both occupied droplets and unoccupied droplets, to flow along the channel **202** towards the intersection **211**. The fluid flow unit **218** can be configured to subject the second fluid **208** containing a plurality of droplets, wherein a majority of the droplets is unoccupied droplets, to flow along the channel **204** away from the intersection **211**. The fluid flow unit **218** can be configured to subject the second fluid **208** containing a plurality of droplets, wherein a majority of the droplets is occupied droplets, to flow along the channel **206** away from the intersection **211**. Alternatively, the fluid flow unit **218** can be configured to subject the second fluid **208** containing a plurality of droplets, wherein a majority of the droplets is unoccupied droplets, to flow along the channel **206** away from the intersection **211**, and configured to subject the second fluid **208** containing a plurality of droplets, wherein a majority of the droplets is occupied droplets, to flow along the channel **204** away from the intersection **211**. The fluid flow unit **218** can be operatively coupled to the controller **220**. For example, the fluid flow unit **218** may receive instructions from the controller **220** regarding fluid pressure and/or velocity.

[00215] In some instances, the fluid flow unit **218** may comprise a compressor to provide positive pressure at an upstream location to direct the fluid from the upstream location to flow to a downstream location. In some instances, the fluid flow unit **218** may comprise a pump to provide negative pressure at a downstream location to direct the fluid from an upstream location to flow to the downstream location. In some instances, the fluid flow unit **218** may comprise both a compressor and a pump, each at different locations. In some instances, the fluid flow unit **218** may comprise different devices at different locations. The fluid flow unit **218** may comprise an actuator. While **FIG. 2A** depicts one fluid flow unit **218**, it may be appreciated that there may be a plurality of fluid flow units **218**, each in communication with the controller **220** and/or with each other. For example, there can be a separate fluid flow unit to direct the fluid in channel **202** towards the intersection **211**, a separate fluid flow unit to direct the fluid in channel **204** away from the intersection **211**, and a separate fluid flow unit to direct the fluid in channel **206** away from the intersection **211**.

[00216] The field application unit **216** can be configured to apply a force field to the channel structure. In some instances, the field application unit **216** can be configured to apply a force field at or near the intersection **211** such that the second subset of droplets (unoccupied droplets) are generally directed along the channel segment **204** and away from the intersection **211**, and the first subset of droplets (occupied droplets) are generally directed along the channel segment **206** and away from the intersection **211**, thereby isolating the two subsets of droplets.

[00217] For example, the field application unit **216** can apply a magnetic field at or near the intersection **211**. The field application unit **216** can be a magnet and/or a circuit (e.g., current carrying device) configured to generate a magnetic field. On account of each droplet containing field-attractable particles (e.g., paramagnetic particles), each droplet may be attracted (e.g., due to paramagnetic particles) or repelled (e.g., due to diamagnetic particles) to or away, respectively, from the magnetic field. The degree of attraction (or repulsion) can be proportional to a number (and/or a concentration) of field-attractable particles in each droplet. That is, the magnetic force acting on a droplet, from the same magnetic field, can be proportional to a number (and/or a concentration) of field-attractable particles in the droplet. As previously described above, assuming that (i) the droplet is spherical and has the radius R_D , (ii) a biological particle is spherical and has the radius R_+ , and (iii) the concentration of field-attractable particles in the volume of aqueous fluid is substantially uniform, the ratio of a number of field-attractable particles in a singularly occupied droplet (N_+) (wherein the occupied droplet contains a single biological particle) to a number of field-attractable particles in an unoccupied droplet (N_-) will be, and thus the ratio of a magnetic force acting on a singularly occupied droplet (F_{M+}) to a magnetic force acting on an unoccupied droplet (F_{M-}) will be:

$$\frac{N_+}{N_-} = \frac{F_{M+}}{F_{M-}} = 1 - \left(\frac{R_+}{R_D}\right)^3$$

[00218] That is, there may be a stronger (differential) force acting on a given unoccupied droplet than a given occupied droplet. As can be appreciated, the above ratio may change with deviations from the above assumptions (e.g., non-spherical biological particle, non-spherical droplet, non-uniform concentration of field-attractable particles in volume of aqueous fluid, etc.).

[00219] In another example, the field application unit **216** can apply an electric field at or near the intersection **211**. On account of each droplet containing field-attractable particles (e.g., conductive particles), each droplet may be attracted or repelled to or away, respectively, from the electric field. The degree of attraction (or repulsion) can be proportional to a number (and/or a concentration) of field-attractable particles in each droplet. That is, the electric force acting on a droplet, from the same electric field, can be proportional to a number (and/or a concentration) of field-attractable particles in the droplet. As previously described above, assuming that (i) the

droplet is spherical and has the radius R_D , (ii) a biological particle is spherical and has the radius R_+ , and (iii) the concentration of field-attractable particles in the volume of aqueous fluid is substantially uniform, the ratio of a number of field-attractable particles in a singularly occupied droplet (N_+) (wherein the occupied droplet contains a single biological particle) to a number of field-attractable particles in an unoccupied droplet (N_-) will be, and thus the ratio of an electric force acting on a singularly occupied droplet (F_{E+}) to an electric force acting on an unoccupied droplet (F_{E-}) will be:

$$\frac{N_+}{N_-} = \frac{F_{E+}}{F_{E-}} = 1 - \left(\frac{R_+}{R_D}\right)^3$$

[00220] As can be appreciated, the above ratio may change with deviations from the above assumptions (e.g., non-spherical biological particle, non-spherical droplet, non-uniform concentration of field-attractable particles in volume of aqueous fluid, etc.). In some instances, the fluid flow unit **218** can apply both an electric field and a magnetic field.

[00221] The field application unit **216** can be operatively coupled to the controller **220**. For example, the field application unit **216** may receive instructions from the controller **220** regarding force field strength, orientation, frequency, and/or other variables. While **FIG. 2A** depicts one field application unit **216**, it may be appreciated that there may be a plurality of field application units **216**, each in communication with the controller **220**, other controllers, and/or with each other. For example, there can be a plurality of field application units, each located at a different location. The controller **220** may instruct the field application unit **216** to apply a force field sufficiently strong and in a sufficiently targeted direction towards the mixed (occupied and unoccupied) droplets such as to direct the unoccupied droplets in one channel and direct the occupied droplets to another channel. In an example, the field application unit **216** can be placed in a location closer to a first channel (e.g., channel **204**) than a second channel (e.g., channel **206**) to direct the unoccupied droplets (which are subject to a stronger force from the same field) to the first channel, assuming that the field is strongest when closest to the field application unit **216**. The stronger a force from the field acts on a droplet, the more likely that the droplet will deviate from an initial flow direction (e.g., direction of flow in channel **202**) into another channel having another direction. In some instances, the field application unit may be located at least in part downstream, from the intersection **211**, of a channel intended to isolate unoccupied droplets (e.g., channel **204**).

[00222] For example, a force field applied can be strong enough to direct the unoccupied droplets to flow to a first channel but weak enough to direct (or leave be) the occupied droplets to flow to a second channel. In some instances, a magnetic field applied by the field application unit **216** can have a magnetic flux density range from at least about 10^{-5} Teslas (T) to about 1 T.

Alternatively, the magnetic flux density can be less than or equal to about 10^{-5} T and/or greater than or equal to about 1 T. In some instances, an electric field applied by the field application unit **216** can have an electric field strength of at least about 1 volt per meter (V/m), 2 V/m, 3 V/m, 4 V/m, 5 V/m, 10 V/m, or more. Alternatively, the electric field strength can be less than about 10 V/m, 5 V/m, 4 V/m, 3 V/m, 2 V/m, 1 V/m, or less.

[00223] FIG. 2B shows an example of a multi-stage microfluidic channel structure for separating singularly occupied droplets. As described elsewhere herein, when droplets are generated, there may be a first subset population of occupied droplets containing a single biological particle (e.g., cell), a second subset population of unoccupied droplets not containing any biological particles, and a third subset population of occupied droplets containing multiple (e.g., two or more) biological particles. In some cases, the droplets may additionally contain one or more barcode carrying beads. For example, a droplet may have only biological particle(s), a droplet may have only barcode carrying bead(s), a droplet may have both biological particle(s) and barcode carrying bead(s), or a droplet may have neither biological particle(s) nor barcode carrying bead(s). The generated droplets may be sorted to isolate the first subset population, second subset population, and third subset population in multiple stages.

[00224] As shown in FIG. 2B, the channel structure can include channel segments **222**, **224**, **226**, **244**, and **246**. Channel segments **222**, **224**, and **226** may meet at channel intersection **231**. Channel segments **226**, **244**, and **246** may meet at channel intersection **233**. In some instances, the outflow channel **108** of the emulsion carrying the generated droplets in FIG. 1 can be upstream of the channel segment **222**, such that the generated droplets are directed to flow to the channel intersection **231** for subsequent sorting. The generated droplets may comprise a first subset population of singularly occupied droplets (e.g., **230A**), a second subset population of unoccupied droplets (e.g., **230B**), and a third subset population of multiply occupied droplets (e.g., **230C**). A first controller **240** can be operatively coupled to a fluid flow unit **238**, to facilitate flow of fluid in the channel structure, and a first field application unit **236**, to apply one or more fields to the channel structure. A second controller **241** can be operatively coupled to a second field application unit **237**, to apply one or more fields to the channel structure.

[00225] In operation, a plurality of discrete droplets can flow as emulsions in a fluid **228**. The droplets being transported along channel segment **222** into intersection **231** can comprise the first subset population of singularly occupied droplets (e.g., **230A**), the second subset population of unoccupied droplets (e.g., **230B**), and the third subset population of multiply occupied droplets (e.g., **230C**). Every droplet, including singularly occupied, multiply occupied, and unoccupied droplets, can comprise some concentration of field-attractable particles. As described above, a given unoccupied droplet can have a higher concentration of field-attractable

particles than a given occupied droplet to account for the volume occupied by a biological particle and/or a barcode bead in an occupied droplet. Within occupied droplets, a given singly occupied droplet can have a higher concentration of field-attractable particles than a given multiply occupied droplet to account for the differential volume occupied by the different numbers of biological particles (and/or barcode beads) in the droplet.

[00226] After a first stage of sorting at or near the intersection **231**, the first and third subsets of droplets (e.g., **230A**, **C**) can be directed to flow along channel segment **226** and away from the intersection **231**, and the second subset of droplets **230B** can be directed to flow along channel segment **224** and away from the intersection **231**.

[00227] The fluid flow unit **238** can be configured to subject the fluid **228** containing a plurality of droplets including the occupied and/or unoccupied droplets (e.g., as emulsion suspensions) to or from intersections **231**, **233** along channel segments **222**, **224**, **226**, **244**, and **246**. The fluid flow unit **238** can be operatively coupled to the first controller **240**. For example, the fluid flow unit **238** may receive instructions from the first controller **240** regarding fluid pressure and/or velocity.

[00228] In some instances, the fluid flow unit **238** may comprise a compressor to provide positive pressure at an upstream location to direct the fluid from the upstream location to flow to a downstream location. In some instances, the fluid flow unit **238** may comprise a pump to provide negative pressure at a downstream location to direct the fluid from an upstream location to flow to the downstream location. In some instances, the fluid flow unit **238** may comprise both a compressor and a pump, each at different locations. In some instances, the fluid flow unit **238** may comprise different devices at different locations. The fluid flow unit **238** may comprise an actuator. While **FIG. 2B** depicts one fluid flow unit **238**, it may be appreciated that there may be a plurality of fluid flow units **238**, each in communication with the first controller **240**, other controllers (e.g., second controller **241**), and/or with each other. For example, there can be a separate fluid flow unit to direct the fluid in channel **222** towards the intersection **231**, a separate fluid flow unit to direct the fluid in channel **224** away from the intersection **231**, and a separate fluid flow unit to direct the fluid in channel **226** away from the intersection **231**.

[00229] The first field application unit **236** can be configured to apply a force field to the channel structure. In some instances, the field application unit **236** can be configured to apply a force field at or near the intersection **231** such that the second subset of droplets (unoccupied droplets) are generally directed along the channel segment **224** and away from the intersection **231**, and the first and third subset of droplets (occupied droplets) are generally directed along the channel segment **226** and away from the intersection **231**, thereby separating the subsets of droplets. For example, as described elsewhere herein, the first field application unit **236** may

apply a magnetic field at or near the intersection **231**. On account of each droplet containing field-attractable particles (e.g., paramagnetic particles), each droplet may be attracted (e.g., due to paramagnetic particles) or repelled (e.g., due to diamagnetic particles) to or away, respectively, from the magnetic field. The degree of attraction (or repulsion) can be proportional to a number (and/or a concentration) of field-attractable particles in each droplet. That is, the magnetic force acting on a droplet, from the same magnetic field, can be proportional to a number (and/or a concentration) of field-attractable particles in the droplet. As described above, assuming that (i) the droplet is spherical and has the radius R_D , (ii) a biological particle is spherical and has the radius R_+ , and (iii) the concentration of field-attractable particles in the volume of aqueous fluid is substantially uniform, the ratio of a number of field-attractable particles in a singularly occupied droplet (N_+) (wherein the occupied droplet contains a single biological particle) to a number of field-attractable particles in an unoccupied droplet (N_-) will be, and thus the ratio of a magnetic force acting on a singularly occupied droplet (F_{M+}) to a magnetic force acting on an unoccupied droplet (F_{M-}) will be:

$$\frac{N_+}{N_-} = \frac{F_{M+}}{F_{M-}} = 1 - \left(\frac{R_+}{R_D}\right)^3$$

Similarly, the ratio of a number of field-attractable particles in a doubly occupied droplet (N_{2+}) (wherein the occupied droplet contains two biological particles) to a number of field-attractable particles in an unoccupied droplet (N_-) will be, and thus the ratio of a magnetic force acting on a doubly occupied droplet ($F_{M,2+}$) to a magnetic force acting on an unoccupied droplet (F_{M-}) will be:

$$\frac{N_{2+}}{N_-} = \frac{F_{M,2+}}{F_{M-}} = 1 - 2\left(\frac{R_+}{R_D}\right)^3$$

[00230] That is, there may be a stronger (differential) force acting on a given unoccupied droplet than a given occupied droplet. Between occupied droplets, there may be a stronger (differential) force acting on a given singularly occupied droplet than a given doubly occupied droplet. Similarly, the more occupied a droplet is (with more biological particles), the less it will be affected by the magnetic field. As can be appreciated, the above ratios may change with deviations from the above assumptions (e.g., non-spherical biological particle, non-spherical droplet, non-uniform concentration of field-attractable particles in volume of aqueous fluid, etc.).

[00231] In another example, as described elsewhere herein, the first field application unit **236** can apply an electric field at or near the intersection **231**. On account of each droplet containing field-attractable particles (e.g., conductive particles), each droplet may be attracted or repelled to or away, respectively, from the electric field. The degree of attraction (or repulsion) can be proportional to a number (and/or a concentration) of field-attractable particles in each

droplet. That is, the electric force acting on a droplet, from the same electric field, can be proportional to a number (and/or a concentration) of field-attractable particles in the droplet.

[00232] The first field application unit **236** can be operatively coupled to the first controller **240**. For example, the first field application unit **236** may receive instructions from the first controller **240** regarding force field strength, orientation, frequency, and/or other variables. The first controller **240** may instruct the first field application unit **236** to apply a force field sufficiently strong and in a sufficiently targeted direction towards the mixed (occupied and unoccupied) droplets such as to direct the unoccupied droplets in one channel and direct the occupied droplets to another channel. In an example, the first field application unit **236** can be placed in a location closer to a first channel (e.g., channel **224**) than a second channel (e.g., channel **226**) to direct the unoccupied droplets (which are subject to a stronger force from the same field) to the first channel, assuming that the field is strongest when closest to the first field application unit **236**. The stronger a force from the field acts on a droplet, the more likely that the droplet will deviate from an initial flow direction (e.g., direction of flow in channel **222**) into another channel having another direction. In some instances, the field application unit may be located at least in part downstream, from the intersection **231**, of a channel intended to isolate unoccupied droplets (e.g., channel **224**).

[00233] For example, a force field applied can be strong enough to direct the unoccupied droplets to flow to a first channel but weak enough to direct (or leave be) the occupied droplets (whether singularly, doubly, or otherwise multiply occupied) to flow to a second channel. In some instances, a magnetic field applied by the field application unit **236** can have a magnetic flux density range from at least about 10^{-5} Teslas (T) to about 1 T. Alternatively, the magnetic flux density can be less than or equal to about 10^{-5} T and/or greater than or equal to about 1 T. In some instances, an electric field applied by the field application unit **236** can have an electric field strength of at least about 1 volt per meter (V/m), 2 V/m, 3 V/m, 4 V/m, 5 V/m, 10 V/m, or more. Alternatively, the electric field strength can be less than about 10 V/m, 5 V/m, 4 V/m, 3 V/m, 2 V/m, 1 V/m, or less.

[00234] The first and third sets of droplets (e.g., **230A**, **C**) isolated to channel **226** may be subjected to a second stage of sorting at or near the intersection **233**. After the second stage of sorting at or near the intersection **233**, the third subset of droplets (e.g., **230C**) can be directed to flow along channel segment **246** and away from the intersection **233**, and the first subset of droplets **230A** can be directed to flow along channel segment **244** and away from the intersection **233**. Thus, the singularly occupied droplets (first subset of droplets) may be isolated from both the unoccupied droplets and the multiply occupied droplets.

[00235] The second field application unit **237** can be configured to apply a force field to the channel structure. In some instances, the field application unit **237** can be configured to apply a force field at or near the intersection **233** such that the first subset of droplets (singularly occupied droplets) are generally directed along the channel segment **244** and away from the intersection **233**, and the third subset of droplets (multiply occupied droplets) are generally directed along the channel segment **246** and away from the intersection **233**, thereby separating the first and third subsets of droplets. For example, as described elsewhere herein, the second field application unit **237** may apply a magnetic field at or near the intersection **233**. As described elsewhere herein, as between occupied droplets, there may be a stronger (differential) force acting on a given singularly occupied droplet than a given doubly occupied droplet. Similarly, the more occupied a droplet is (with more biological particles), the less it will be affected by the magnetic field. In another example, as described elsewhere herein, the second field application unit **237** can apply an electric field at or near the intersection **233**.

[00236] The second field application unit **237** can be operatively coupled to the second controller **241**. For example, the second field application unit **237** may receive instructions from the second controller **241** regarding force field strength, orientation, frequency, and/or other variables. The second controller **241** may instruct the second field application unit **237** to apply a force field sufficiently strong and in a sufficiently targeted direction towards the mixed (singularly occupied and multiply occupied) droplets such as to direct the singularly droplets in one channel and direct the multiply occupied droplets to another channel. In an example, the second field application unit **237** can be placed in a location closer to a first channel (e.g., channel **244**) than a second channel (e.g., channel **246**) to direct the singularly occupied droplets (which are subject to a stronger force from the same field than multiply occupied droplets) to the first channel, assuming that the field is strongest when closest to the second field application unit **237**. The stronger a force from the field acts on a droplet, the more likely that the droplet will deviate from an initial flow direction (e.g., direction of flow in channel **226**) into another channel having another direction. In some instances, the field application unit may be located at least in part downstream, from the intersection **233**, of a channel intended to isolate singularly occupied droplets (e.g., channel **244**). Alternatively or in addition to, the second field application unit **236** can be operatively coupled to the first controller **240**.

[00237] For example, a force field applied can be strong enough to direct the singularly occupied droplets to flow to a first channel but weak enough to direct (or leave be) the multiply occupied droplets (whether singularly, doubly, or otherwise multiply occupied) to flow to a second channel. In some instances, the force field applied by the second field application unit **237** may be stronger than the force field applied by the first field application unit **236**. In some

instances, a magnetic field applied by the second field application unit **237** can have a magnetic flux density range from at least about 10^{-5} Teslas (T) to about 1 T. Alternatively, the magnetic flux density can be less than or equal to about 10^{-5} T and/or greater than or equal to about 1 T. In some instances, an electric field applied by the field application unit **236** can have an electric field strength of at least about 1 volt per meter (V/m), 2 V/m, 3 V/m, 4 V/m, 5 V/m, 10 V/m, or more. Alternatively, the electric field strength can be less than about 10 V/m, 5 V/m, 4 V/m, 3 V/m, 2 V/m, 1 V/m, or less.

[00238] The systems and methods described with respect to **FIGS. 2A-B** may be used to isolate cell beads from particles unoccupied with biological particles, and/or separate singularly occupied cell beads from unoccupied and multiply occupied cell beads. As described elsewhere herein, a plurality of particles may comprise a first subset of particles (e.g., cell beads) occupied by biological particles (e.g., cells) and a second subset of particles unoccupied by biological particles. Both occupied and unoccupied particles may comprise field-attractable particles. Occupied particles may include singularly occupied cell beads, each containing a single biological particle, and multiply occupied cell beads, each containing two or more biological particles. For example, such particles comprising the field-attractable particles may be generated from polymerizing the plurality of droplets comprising the field-attractable particles (e.g., in **FIG. 1**). In a channel structure including channel segments **202**, **204**, and **206** meeting at a channel intersection **211**, the plurality of particles may be directed to flow (e.g., as suspensions in a fluid, e.g., aqueous fluid) to the channel intersection **211** for subsequent sorting. A controller **220** can be operatively coupled to a fluid flow unit **218**, to facilitate flow of fluid in the channel structure, and a field application unit **216**, to apply one or more fields to the channel structure.

[00239] In operation, a plurality of discrete particles, including both cell beads and unoccupied particles, can be directed to flow along channel segment **202** into intersection **211**. The plurality of particles can comprise a first subset of particles (e.g., cell beads) that are each occupied with at least a biological particle and a second subset of particles that are each unoccupied. Every particle, including cell beads and unoccupied particles, can comprise some concentration of field-attractable particles. As described with respect to the relative concentrations of field-attractable particles in occupied and unoccupied droplets, a given unoccupied particle can have a higher concentration of field-attractable particles than a given cell bead (e.g., a given occupied particle) to account for the volume occupied by a biological particle in a cell bead.

[00240] After sorting at or near the intersection **211**, the first subset of particles (e.g., cell beads) can be directed to flow along channel segment **206** and away from the intersection **211**,

and the second subset of particles can be directed to flow along channel segment **204** and away from the intersection **211**.

[00241] The fluid flow unit **218** can be configured to subject the second fluid **208** containing the plurality of particles, including both cell beads and unoccupied particles, to flow along the channel **202** towards the intersection **211**. The fluid flow unit **218** can be configured to subject the second fluid **208** containing a plurality of particles, wherein a majority of the particles is unoccupied, to flow along the channel **204** away from the intersection **211**. The fluid flow unit **218** can be configured to subject the second fluid **208** containing a plurality of particles, wherein a majority of the particles is cell beads (e.g., occupied particles), to flow along the channel **206** away from the intersection **211**. Alternatively, the fluid flow unit **218** can be configured to subject the second fluid **208** containing a plurality of particles wherein a majority of the particles is unoccupied particles, to flow along the channel **206** away from the intersection **211**, and configured to subject the second fluid **208** containing a plurality of particles, wherein a majority of the particles is cell beads, to flow along the channel **204** away from the intersection **211**. The fluid flow unit **218** can be operatively coupled to the controller **220**. For example, the fluid flow unit **218** may receive instructions from the controller **220** regarding fluid pressure and/or velocity.

[00242] The field application unit **216** can be configured to apply a force field to the channel structure. In some instances, the field application unit **216** can be configured to apply a force field at or near the intersection **211** such that the second subset of particles (unoccupied particles) is generally directed along the channel segment **204** and away from the intersection **211**, and the first subset of particles (cell beads) is generally directed along the channel segment **206** and away from the intersection **211**, thereby isolating the two subsets of particles.

[00243] For example, the field application unit **216** can apply a magnetic field at or near the intersection **211**. The field application unit **216** can be a magnet and/or a circuit (e.g., current carrying device) configured to generate a magnetic field. On account of each particle containing field-attractable particles (e.g., paramagnetic particles), each particle may be attracted (e.g., due to paramagnetic particles) or repelled (e.g., due to diamagnetic particles) to or away, respectively, from the magnetic field. The degree of attraction (or repulsion) can be proportional to a number (and/or a concentration) of field-attractable particles in each particle. That is, the magnetic force acting on a particle, from the same magnetic field, can be proportional to a number (and/or a concentration) of field-attractable particles in the particle. For example, assuming that (i) the particle is spherical and has the radius R_{CB} , (ii) a biological particle is spherical and has the radius R_+ , and (iii) the concentration of field-attractable particles in the particle is substantially uniform, the ratio of a number of field-attractable particles in a

singularly occupied cell bead (N_+) (wherein the cell bead contains a single biological particle) to a number of field-attractable particles in an unoccupied particle (N_-) will be, and thus the ratio of a magnetic force acting on a singularly occupied cell bead (F_{M+}) to a magnetic force acting on an unoccupied particle (F_{M-}) will be:

$$\frac{N_+}{N_-} = \frac{F_{M+}}{F_{M-}} = 1 - \left(\frac{R_+}{R_{CB}}\right)^3$$

[00244] That is, there may be a stronger (differential) force acting on a given unoccupied particle than a given cell bead. As can be appreciated, the above ratio may change with deviations from the above assumptions (e.g., non-spherical biological particle, non-spherical particle, non-uniform concentration of field-attractable particles in volume of particle, etc.).

[00245] In another example, the field application unit **216** can apply an electric field at or near the intersection **211**. On account of each particle containing field-attractable particles (e.g., conductive particles), each particle may be attracted or repelled to or away, respectively, from the electric field. The degree of attraction (or repulsion) can be proportional to a number (and/or a concentration) of field-attractable particles in each particle. That is, the electric force acting on a particle, from the same electric field, can be proportional to a number (and/or a concentration) of field-attractable particles in the particle. As previously described above, assuming that (i) the particle is spherical and has the radius R_{CB} , (ii) a biological particle is spherical and has the radius R_+ , and (iii) the concentration of field-attractable particles in the volume of a particle is substantially uniform, the ratio of a number of field-attractable particles in a singularly occupied cell bead (N_+) (wherein the cell bead contains a single biological particle) to a number of field-attractable particles in an unoccupied particle (N_-) will be, and thus the ratio of an electric force acting on a singularly occupied cell bead (F_{E+}) to an electric force acting on an unoccupied particle (F_{E-}) will be:

$$\frac{N_+}{N_-} = \frac{F_{E+}}{F_{E-}} = 1 - \left(\frac{R_+}{R_D}\right)^3$$

[00246] As can be appreciated, the above ratio may change with deviations from the above assumptions (e.g., non-spherical biological particle, non-spherical particle, non-uniform concentration of field-attractable particles in volume of a particle, etc.). In some instances, the fluid flow unit **218** can apply both an electric field and a magnetic field.

[00247] The field application unit **216** can be operatively coupled to the controller **220**. For example, the field application unit **216** may receive instructions from the controller **220** regarding force field strength, orientation, frequency, and/or other variables. The controller **220** may instruct the field application unit **216** to apply a force field sufficiently strong and in a sufficiently targeted direction towards the mixed (occupied and unoccupied) particles such as to

direct the unoccupied particles in one channel and direct the occupied particles to another channel. In an example, the field application unit **216** can be placed in a location closer to a first channel (e.g., channel **204**) than a second channel (e.g., channel **206**) to direct the unoccupied particles (which are subject to a stronger force from the same field) to the first channel, assuming that the field is strongest when closest to the field application unit **216**. The stronger a force from the field acts on a particle, the more likely that the particle will deviate from an initial flow direction (e.g., direction of flow in channel **202**) into another channel having another direction. In some instances, the field application unit may be located at least in part downstream, from the intersection **211**, of a channel intended to isolate unoccupied particles (e.g., channel **204**).

[00248] For example, a force field applied can be strong enough to direct the unoccupied particles to flow to a first channel but weak enough to direct (or leave be) the occupied particles to flow to a second channel. In some instances, a magnetic field applied by the field application unit **216** can have a magnetic flux density range from at least about 10^{-5} Teslas (T) to about 1 T. Alternatively, the magnetic flux density can be less than or equal to about 10^{-5} T and/or greater than or equal to about 1 T. In some instances, an electric field applied by the field application unit **216** can have an electric field strength of at least about 1 volt per meter (V/m), 2 V/m, 3 V/m, 4 V/m, 5 V/m, 10 V/m, or more. Alternatively, the electric field strength can be less than about 10 V/m, 5 V/m, 4 V/m, 3 V/m, 2 V/m, 1 V/m, or less.

[00249] Similarly, singularly occupied cell beads may be sorted from unoccupied particles and multiply occupied cell beads by using the systems and methods described with respect to **FIG. 2B** but introducing a plurality of particles (comprising a first subset of singularly occupied cell beads, a second subset of unoccupied particles, and a third subset of multiply occupied cell beads), each particle comprising field attractable particles, in place of the plurality of droplets comprising the field attractable particles.

[00250] While **FIG. 2A** and **FIG. 2B** each depicts a channel structure wherein a second channel (e.g., channel **204**) branches off a first channel (e.g., channel **202**) at a sorting intersection (e.g., intersection **211**) such that a third channel (channel **204**) continues in the same direction as the first channel, it can be appreciated that the systems and methods disclosed herein may be application to different channel structures. For example, the third channel can be at a different angle (e.g., not 180°) than the first channel. In some examples, the channel structure may have more than two channels branching off the first channel, wherein the field application unit **216** is configured to separate the droplets into unoccupied droplets, droplets containing only one biological particle, droplets containing more than one biological particles, droplets containing only barcode carrying beads, droplets containing both a biological particle and barcode carrying beads, or other variations. In some examples, the channel structure may have

more than two channels branching off the first channel, wherein the field application unit **216** is configured to separate the particles into unoccupied particles, particles containing only one biological particle, particles containing more than one biological particles, particles containing only barcode carrying beads, particles containing both a biological particle and barcode carrying beads, or other variations. For example, the more volume of a droplet or a particle is occupied by one or more biological particles and/or one or more barcode carrying beads contained therein, the weaker can be the force acting on the droplet or the particle by the field applied by the field application unit **216**, and thus the less the deviation in direction of flow relative to the direction of flow in the first channel. That is, upon application of a force field, the unoccupied droplets or particles may be capable of deviating the most (e.g., to a channel closest to the field application unit), a droplet or particle containing a single biological particle (e.g., singularly occupied cell bead) may be capable of deviating but not as much as the unoccupied droplets or particles (e.g., to a channel second closest to the field application unit), and a droplet or particle containing both a biological particle and a barcode carrying bead may be capable of deviating the least of the three types of droplets or particles (e.g., to a channel farthest from the field application unit).

[00251] While **FIGS. 2A-2B** depict narrow channels allowing for the flow of droplets and/or particles only in single file, the systems and methods disclosed herein may be applicable to channels having a broader width (e.g., diameter) that allows for the flow of droplets and/or particles in more than single file.

[00252] While **FIG. 2A** depicts one controller **220** operatively coupled to both the fluid flow unit **218** and the field application unit **216**, a separate controller can be coupled to the fluid flow unit **218** and a separate controller can be coupled to the field application unit **216**. The two separate controllers may or may not be in communication with each other. In some instances, there may be a plurality of controllers (e.g., two controllers to a fluid flow unit **218**), wherein each controller may or may not be in communication with each other. The controller **220** may send instructions to the fluid flow unit **218** and/or the field application unit **216** via wired connection and/or wireless connection (e.g., Wi-Fi, Bluetooth, NFC, etc.).

[00253] **FIG. 3** shows another example of a microfluidic channel structure for separating occupied droplets from unoccupied droplets. As described elsewhere herein, when droplets are generated, there may be a first subset population of occupied droplets containing one or more biological particles and a second subset population of unoccupied droplets not containing any biological particles. In some cases, the droplets may additionally contain one or more barcode carrying beads. For example, a droplet may have only a biological particle, a droplet may have only a barcode carrying bead, a droplet may have both a biological particle and a barcode carrying bead, or a droplet may have neither biological particles nor barcode carrying beads. In

some cases, the majority of occupied partitions can include no more than one biological particle per occupied partition and, in some cases, some of the generated partitions can be unoccupied (of any biological particle). In some cases, though, some of the occupied partitions may include more than one biological particle. In some cases, the partitioning process may be controlled such that fewer than about 25% of the occupied partitions contain more than one biological particle, and in many cases, fewer than about 20% of the occupied partitions have more than one biological particle, while in some cases, fewer than about 10% or even fewer than about 5% of the occupied partitions include more than one biological particle per partition.

[00254] As shown in **FIG. 3**, the channel structure can include channel segments **302**, **304**, and **306** meeting at a channel intersection **311**. In some instances, the outflow channel **108** of the emulsion carrying the generated droplets in **FIG. 1** can be upstream of the channel segment **302**, such that the generated droplets are directed to flow to the channel intersection **211** for subsequent sorting. A controller **322** can be operatively coupled to a fluid flow unit **318**, to facilitate flow of fluid in the channel structure, a sensor **320**, to detect at least a characteristic of a droplet or a plurality of droplets, and a pressure application unit **316**, to apply a pressure pulse to the channel structure.

[00255] In operation, a plurality of discrete droplets, each comprising a first aqueous fluid **310** can flow as emulsions in a second fluid **308**, wherein the second fluid **308** is immiscible to the first aqueous fluid **310**. The droplets being transported along channel segment **302** into intersection **311** can comprise a first subset of droplets **314** that are each occupied with at least a biological particle and/or a barcode carrying bead and a second subset of droplets **312** that are each unoccupied. Every droplet, including occupied and unoccupied droplets, may or may not comprise some concentration of field-attractable particles. Although **FIG. 3** depicts each droplet as comprising field-attractable particles **315**, this is not required.

[00256] After sorting at or near the intersection **311**, the first subset of droplets **314** can be directed to flow along channel segment **306** and away from the intersection **311**, and the second subset of droplets **312** can be directed to flow along channel segment **304** and away from the intersection **311**.

[00257] The fluid flow unit **318** can be configured to subject the second fluid **308** containing a plurality of droplets, including both occupied droplets and unoccupied droplets, to flow along the channel **302** towards the intersection **311**. The fluid flow unit **318** can be configured to subject the second fluid **308** containing a plurality of droplets, wherein a majority of the droplets is unoccupied droplets, to flow along the channel **304** away from the intersection **311**. The fluid flow unit **318** can be configured to subject the second fluid **308** containing a plurality of droplets, wherein a majority of the droplets is occupied droplets, to flow along the channel **306** away from

the intersection **311**. Alternatively, the fluid flow unit **318** can be configured to subject the second fluid **308** containing a plurality of droplets, wherein a majority of the droplets is unoccupied droplets, to flow along the channel **306** away from the intersection **311**, and configured to subject the second fluid **308** containing a plurality of droplets, wherein a majority of the droplets is occupied droplets, to flow along the channel **304** away from the intersection **311**. The fluid flow unit **318** can be operatively coupled to the controller **322**. For example, the fluid flow unit **318** may receive instructions from the controller **322** regarding fluid pressure and/or velocity.

[00258] In some instances, the fluid flow unit **318** may comprise a compressor to provide positive pressure at an upstream location to direct the fluid from the upstream location to flow to a downstream location. In some instances, the fluid flow unit **318** may comprise a pump to provide negative pressure at a downstream location to direct the fluid from an upstream location to flow to the downstream location. In some instances, the fluid flow unit **318** may comprise both a compressor and a pump, each at different locations. In some instances, the fluid flow unit **318** may comprise different devices at different locations. The fluid flow unit **318** may comprise an actuator. While **FIG. 3** depicts one fluid flow unit **318**, it may be appreciated that there may be a plurality of fluid flow units **318**, each in communication with the controller **322** and/or with each other. For example, there can be a separate fluid flow unit to direct the fluid in channel **302** towards the intersection **311**, a separate fluid flow unit to direct the fluid in channel **304** away from the intersection **311**, and a separate fluid flow unit to direct the fluid in channel **306** away from the intersection **311**.

[00259] The sensor **320** can be configured to sense at least a characteristic of a droplet or a plurality of droplets in the first channel segment **302**. In some instances, the sensor **320** may detect the characteristic of a droplet as the droplet passes the sensor **320**. The sensor **320** may be located upstream of the intersection **311**. One or more characteristics detected by the sensor **320** of a droplet can be indicative of the type of droplet, such as whether the droplet is occupied or unoccupied, or whether the droplet contains a biological particle and/or a barcode carrying bead. In some instances, the sensor **320** can be an impedance sensor configured to measure bulk impedance when droplets pass by the sensor **320**. In some instances, a higher impedance can be measured for occupied droplets than for unoccupied droplets (e.g., due to mass and/or weight distribution of occupied droplet, etc.). In some instances, the sensor **320** can be an optical sensor configured to measure optical properties of a droplet, such as to distinguish whether the droplet is occupied or unoccupied. The optical sensor and/or a supporting device may be configured to emit a detection signal configured to probe one or more droplets, including for example an electromagnetic signal (e.g., in any wavelength) and/or an acoustic signal. In some instances, the

optical sensor and/or a supporting device may comprise an illumination source configured to illuminate the droplet or droplets with one or more types of electromagnetic radiation. In some instances, the electromagnetic radiation can include illumination in one or more of the visible spectrum, infrared spectrum, the ultraviolet spectrum, and ionizing radiation spectrum. In some instances, the ionizing radiation can include x-rays. Alternatively the sensor **320** may be one or more devices that are configured to provide one or more of optical sensing, thermal sensing, laser imaging, infrared imaging, capacitance sensing, mass sensing, vibration sensing across at least a portion of the electromagnetic spectrum, and magnetic induction sensing. The sensor **320** can be operatively coupled to the controller **322**. For example, the sensor **320** may transmit sensor data (e.g., on one or more characteristics of a droplet or a plurality of droplets) to the controller **322**. The controller **322** may then use such data to determine whether the droplet is occupied or unoccupied.

[00260] While **FIG. 3** depicts one sensor **320**, it may be appreciated that there may be a plurality of sensors, each in communication with the controller **322** and/or with each other. For example, there can be a plurality of sensors upstream of the intersection **311** at different locations, for example, detecting one or more characteristics of a droplet or a plurality of droplets at different angles.

[00261] The pressure application unit **316** can be configured to apply a pressure pulse to the channel structure. In some instances, the pressure application unit **316** can be configured to apply a pressure pulse at or near the intersection **311** such that, via hydrodynamic forces, the second subset of droplets (unoccupied droplets) are generally directed along the channel segment **304** and away from the intersection **311**, and the first subset of droplets (occupied droplets) are generally directed along the channel segment **306** and away from the intersection **311**, thereby isolating the two subsets of droplets.

[00262] In some instances, the pressure application unit **316** may comprise a compressor to provide positive pressure pulses at an upstream location to direct the fluid from the upstream location to flow to a downstream location. In some instances, the pressure application unit **316** may comprise a pump to provide negative pressure pulses at a downstream location to direct the fluid from an upstream location to flow to the downstream location. In some instances, the pressure application unit **316** may comprise both a compressor and a pump, each at different locations. In some instances, the pressure application unit **316** may comprise different devices at different locations. The pressure application unit **316** may comprise an actuator. While **FIG. 3** depicts one pressure application unit **316**, it may be appreciated that there may be a plurality of pressure application units, each in communication with the controller **322** and/or with each other. In some instances, the pressure application unit **316** and a fluid flow unit **318** may be the same

device or same devices. In some instances, the pressure application unit **316** may be, entirely or at least in part, external to the microfluidic structure (e.g., microfluidic channels), as illustrated in **FIG. 3**. In some instances, the pressure application unit **316** may be, entirely or at least in part, internal to and/or integral to the microfluidic structure. For example, a pressure pulse may be generated by deflection of membranes. In some instances, a pressure pulse may be generated from generation of air bubbles, wherein expansion of the bubble may displace fluid parcels.

[00263] Occupied droplets and unoccupied droplets may respond differently to a pressure pulse, for example due to varying predetermined particle and fluid characteristics. In some instances, singularly occupied droplets and multiply occupied droplets may respond differently to a pressure pulse. The predetermined particle and fluid characteristics can include size of a droplet, mass of a droplet, viscosity of droplet suspension in the emulsion, deformability, and other characteristics. That is, a given singularly occupied droplet, a multiply occupied droplet, and an unoccupied droplet may respond differently when subject to hydrodynamic forces triggered by the pressure pulses. In some instances, the controller **322** may, based on a determination made from data received from the sensor **320** (e.g., determination on whether droplet is occupied or unoccupied), instruct the pressure application unit **316** to apply different pressure pulses, for example, by varying frequency of the pulses and/or changing pressure differential. For example, the pressure application unit **316** may apply a first type of pressure pulse when an occupied droplet is approaching the intersection **311** and a second type of pressure pulse when an unoccupied droplet is approaching the intersection **311**. Alternatively, the same pressure pulse can be applied for any type of droplet approaching the intersection **311**, and the droplet may react (or respond) differently (e.g., deviating from a fluid flow direction at different angles) depending on whether the droplet is occupied or unoccupied.

[00264] The pressure application unit **316** can be operatively coupled to the controller **320**. For example, the pressure application unit **316** may receive instructions from the controller **322** regarding pressure pulse strength, frequency, and/or other variables.

[00265] The systems and methods described with respect to **FIG. 3** may be used to separate occupied particles from unoccupied particles. As described elsewhere herein, a plurality of particles may comprise a first subset of particles (e.g., cell beads) occupied by biological particles (e.g., cells) and a second subset of particles unoccupied by biological particles. In a channel structure including channel segments **302**, **304**, and **306** meeting at a channel intersection **311**, the plurality of particles may be directed to flow (e.g., as suspensions in a fluid, e.g., aqueous fluid) to the channel intersection **311** for subsequent sorting. A controller **322** can be operatively coupled to a fluid flow unit **318**, to facilitate flow of fluid in the channel structure,

a sensor **320**, to detect at least a characteristic of a particle or a plurality of particles, and a pressure application unit **316**, to apply a pressure pulse to the channel structure.

[00266] After sorting at or near the intersection **311**, the first subset of particles (e.g., cell beads) can be directed to flow along channel segment **306** and away from the intersection **311**, and the second subset of particles can be directed to flow along channel segment **304** and away from the intersection **311**.

[00267] The fluid flow unit **318** can be configured to subject the second fluid **308** containing a plurality of particles, including both cell beads and unoccupied particles, to flow along the channel **302** towards the intersection **311**. The fluid flow unit **318** can be configured to subject the second fluid **308** containing a plurality of particles, wherein a majority of the particles is unoccupied particles, to flow along the channel **304** away from the intersection **311**. The fluid flow unit **318** can be configured to subject the second fluid **308** containing a plurality of particles, wherein a majority of the particles is occupied particles, to flow along the channel **306** away from the intersection **311**. Alternatively, the fluid flow unit **318** can be configured to subject the second fluid **308** containing a plurality of particles, wherein a majority of the particles is unoccupied particles, to flow along the channel **306** away from the intersection **311**, and configured to subject the second fluid **308** containing a plurality of particles, wherein a majority of the particles is occupied particles, to flow along the channel **304** away from the intersection **311**. The fluid flow unit **318** can be operatively coupled to the controller **322**. For example, the fluid flow unit **318** may receive instructions from the controller **322** regarding fluid pressure and/or velocity.

[00268] The sensor **320** can be configured to sense at least a characteristic of a particle or a plurality of particles in the first channel segment **302**. In some instances, the sensor **320** may detect the characteristic of a particle as the particle passes the sensor **320**. The sensor **320** may be located upstream of the intersection **311**. One or more characteristics detected by the sensor **320** of a particle can be indicative of the type of particle, such as whether the particle is occupied or unoccupied, or whether the particle contains a biological particle and/or a barcode carrying bead. In some instances, the sensor **320** can be an impedance sensor configured to measure bulk impedance when particles pass by the sensor **320**. In some instances, a higher impedance can be measured for occupied particles than for unoccupied particles (e.g., due to mass and/or weight distribution of occupied particle, etc.). In some instances, the sensor **320** can be an optical sensor configured to measure optical properties of a particle, such as to distinguish whether the particle is occupied or unoccupied. The optical sensor and/or a supporting device may be configured to emit a detection signal configured to probe one or more particles, including for example an electromagnetic signal (e.g., in any wavelength) and/or an acoustic signal. In some

instances, the optical sensor and/or a supporting device may comprise an illumination source configured to illuminate the particle or particles with one or more types of electromagnetic radiation. In some instances, the electromagnetic radiation can include illumination in one or more of the visible spectrum, infrared spectrum, the ultraviolet spectrum, and ionizing radiation spectrum. In some instances, the ionizing radiation can include x-rays. Alternatively the sensor **320** may be one or more devices that are configured to provide one or more of optical sensing, thermal sensing, laser imaging, infrared imaging, capacitance sensing, mass sensing, vibration sensing across at least a portion of the electromagnetic spectrum, and magnetic induction sensing. The sensor **320** can be operatively coupled to the controller **322**. For example, the sensor **320** may transmit sensor data (e.g., on one or more characteristics of a particle or a plurality of particles) to the controller **322**. The controller **322** may then use such data to determine whether the particle is occupied or unoccupied.

[00269] While **FIG. 3** depicts one sensor **320**, it may be appreciated that there may be a plurality of sensors, each in communication with the controller **322** and/or with each other. For example, there can be a plurality of sensors upstream of the intersection **311** at different locations, for example, detecting one or more characteristics of a particle or a plurality of particles at different angles.

[00270] The pressure application unit **316** can be configured to apply a pressure pulse to the channel structure. In some instances, the pressure application unit **316** can be configured to apply a pressure pulse at or near the intersection **311** such that, via hydrodynamic forces, the second subset of particles (unoccupied particles) are generally directed along the channel segment **304** and away from the intersection **311**, and the first subset of particles (cell beads) are generally directed along the channel segment **306** and away from the intersection **311**, thereby isolating the two subsets of particles.

[00271] Occupied particles and unoccupied particles may respond differently to a pressure pulse, for example due to varying predetermined particle and fluid characteristics. The predetermined particle and fluid characteristics can include size of a particle, mass of a particle, viscosity of particle suspension in the fluid, deformability, and other characteristics. That is, a given singularly occupied cell bead, multiply occupied cell bead, and an unoccupied particle may respond differently when subject to hydrodynamic forces triggered by the pressure pulses. In some instances, the controller **322** may, based on a determination made from data received from the sensor **320** (e.g., determination on whether particle is occupied or unoccupied), instruct the pressure application unit **316** to apply different pressure pulses, for example, by varying frequency of the pulses and/or changing pressure differential. For example, the pressure application unit **316** may apply a first type of pressure pulse when an occupied particle is

approaching the intersection **311** and a second type of pressure pulse when an unoccupied particle is approaching the intersection **311**. Alternatively, the same pressure pulse can be applied for any type of particle approaching the intersection **311**, and the particle may react (or respond) differently (e.g., deviating from a fluid flow direction at different angles) depending on whether the particle is occupied or unoccupied. In some instances, different pressure pulses may be applied as between occupied and unoccupied droplets, occupied and unoccupied particles, singularly occupied and multiply occupied droplets, and/or singularly occupied and multiply occupied cell beads.

[00272] The pressure application unit **316** can be operatively coupled to the controller **320**. For example, the pressure application unit **316** may receive instructions from the controller **322** regarding pressure pulse strength, frequency, and/or other variables.

[00273] While **FIG. 3** depicts a channel structure wherein a second channel (channel **304**) branches off a first channel (channel **302**) such that a third channel (channel **304**) continues in the same direction as the first channel, it can be appreciated that the systems and methods disclosed herein may be application to different channel structures. For example, the third channel can be at a different angle (e.g., not 180°) than the first channel. In some examples, the channel structure may have more than two channels branching off the first channel, wherein the pressure application unit **316** is configured to separate the droplets into unoccupied droplets, droplets containing only one biological particle, droplets containing more than one biological particles, droplets containing only barcode carrying beads, droplets containing both a biological particle and barcode carrying beads, or other variations. The pressure application unit **316** can be configured to separate particles into unoccupied particles, particles containing only one biological particle, particles containing more than one biological particle, particles containing only barcode carrying beads, particles containing both a biological particle and barcode carrying beads, or other variations. For example, upon application of a pressure pulse, the unoccupied droplets or particles may be capable of deviating the most (e.g., to a first channel), a droplet or particle containing a single biological particle may be capable of deviating but not as much as the unoccupied droplets or particles (e.g., to a second channel), and a droplet or particle containing both a biological particle and a barcode carrying bead may be capable of deviating the least of the three types of droplets or particles (e.g., to a third channel).

[00274] While **FIG. 3** depicts narrow channels allowing for the flow of droplets or particles only in single file, the systems and methods disclosed herein may be applicable to channels having a broader width (e.g., diameter) that allows for the flow of droplets or particles in more than single file.

[00275] While **FIG. 3** depicts one controller **322** operatively coupled to all of the fluid flow unit **318**, the sensor **320**, and the pressure application unit **316**, a separate controller can be coupled to the fluid flow unit **318**, a separate controller can be coupled to the sensor **320**, and a separate controller can be coupled to the pressure application unit **216**. The three separate controllers may or may not be in communication with each other. In some instances, there may be a plurality of controllers (e.g., two controllers to a fluid flow unit **318**), wherein each controller may or may not be in communication with each other. The controller **322** may send instructions to the fluid flow unit **318**, sensor **320**, and/or the pressure application unit **316** via wired connection and/or wireless connection (e.g., Wi-Fi, Bluetooth, NFC, etc.). The controller **322** may receive data from the fluid flow unit **318**, sensor **320**, and/or the pressure application unit **316** via wired connection and/or wireless connection (e.g., Wi-Fi, Bluetooth, NFC, etc.). In some instances, the components can be directly or indirectly be in communication with each other, with or without going through the controller **322**. For example, the sensor **320** may be directly coupled to the pressure application unit **316**.

[00276] The separation systems and methods disclosed herein may achieve super Poisson loading. For example, the droplets can be separated into two subsets such that at least about 5%, 10%, 15%, 20%, 25%, 30%, 40%, 50%, 60%, 70%, 80%, 90%, 95%, 96%, 97%, 98%, 99%, or greater of a first subset of droplets that is isolated are occupied droplets (e.g., containing at least one biological particle). Such occupancy may be greater than or equal to 1%, 2%, 3%, 4%, 5%, 10%, 20%, 30%, 40%, 50%, 60%, 70%, 80%, 90%, 95%, or higher. Alternatively, less than about 97% of the first subset of droplets can be occupied droplets. In some instances, at least about 97%, 98%, 99%, or a higher percentage of a second subset of droplets that is isolated can be unoccupied droplets (e.g., not containing any biological particle and not containing any barcode carrying beads). Alternatively, less than about 97% of the second subset of droplets can be unoccupied droplets. For example, the particles can be separated into two subsets such that at least about 5%, 10%, 15%, 20%, 25%, 30%, 40%, 50%, 60%, 70%, 80%, 90%, 95%, 96%, 97%, 98%, 99%, or greater of a first subset of particles that is isolated are cell beads (e.g., containing at least one biological particle). Such occupancy may be greater than or equal to 1%, 2%, 3%, 4%, 5%, 10%, 20%, 30%, 40%, 50%, 60%, 70%, 80%, 90%, 95%, or higher. Alternatively, less than about 97% of the first subset of particles can be occupied particles (e.g., cell beads). In some instances, at least about 97%, 98%, 99%, or a higher percentage of a second subset of particles that is isolated can be unoccupied particles (e.g., not containing any biological particle and not containing any barcode carrying beads). Alternatively, less than about 97% of the second subset of particles can be unoccupied particles.

[00277] The channel networks, e.g., as described herein above or further below, can be fluidly coupled to appropriate fluidic components. For example, the inlet channel segments (e.g., channel segment **202** in **FIG. 2A**, channel segments **102**, **104**, **106** in **FIG. 1**) are fluidly coupled to appropriate sources of the materials they are to deliver to a channel junction (e.g., intersection **211** in **FIG. 2A**, junction **110** in **FIG. 1**). For example, channel segment **202** will be fluidly coupled to a source of an aqueous suspension of biological particles (e.g., biological particles **114** in **FIG. 1**) to be analyzed and field-attractable particles (e.g., field-attractable particles **115** in **FIG. 1**). Channel segments **104** and **106** may then be fluidly connected to one or more sources of the non-aqueous (or other immiscible) fluid. These sources may include any of a variety of different fluidic components, from simple reservoirs defined in or connected to a body structure of a microfluidic device, to fluid conduits that deliver fluids from off-device sources, manifolds, fluid flow units (e.g., actuators, pumps, compressors) or the like. Likewise, the outlet channel segment **206** may be fluidly coupled to a receiving vessel or conduit for the partitioned cells for subsequent processing. Again, this may be a reservoir defined in the body of a microfluidic device, or it may be a fluidic conduit for delivering the partitioned cells to a subsequent process operation, instrument or component.

[00278] In some instances, a plurality of droplets not containing any field-attractable particles, may also be sorted using dielectrophoresis. For example, occupied droplets and unoccupied droplets can have different dielectric properties. When an electric field is applied, such as via methods described elsewhere herein (e.g., with reference to **FIG. 2A**), to a plurality of droplets comprising both occupied droplets and unoccupied droplets, such as at an intersection wherein a first channel branches off into a second channel and a third channel, the occupied droplets may be directed to flow through the first channel and unoccupied droplets may be directed to flow through the second channel, due at least in part to the varying interactions with (or influence of) the electric field of the occupied droplets and the unoccupied droplets having different dielectric properties. Such systems and methods for dielectrophoresis may also be used to sort a plurality of particles into a first subset of occupied particles (e.g., cell beads) and a second subset of unoccupied particles.

[00279] The biological particle can be subjected to conditions sufficient to polymerize or gel the precursors. The conditions sufficient to polymerize or gel the precursors may comprise exposure to heating, cooling, electromagnetic radiation, or light. The conditions sufficient to polymerize or gel the precursors may comprise any conditions sufficient to polymerize or gel the precursors. Following polymerization or gelling, a polymer or gel may be formed around the biological particle. The polymer or gel may be diffusively permeable to chemical or biochemical reagents. The polymer or gel may be diffusively impermeable to macromolecular constituents of

the biological particle. In this manner, the polymer or gel may act to allow the biological particle to be subjected to chemical or biochemical operations while spatially confining the macromolecular constituents to a region of the droplet defined by the polymer or gel. The polymer or gel may include one or more of disulfide cross-linked polyacrylamide, agarose, alginate, polyvinyl alcohol, polyethylene glycol (PEG)-diacrylate, PEG-acrylate, PEG-thiol, PEG-azide, PEG-alkyne, other acrylates, chitosan, hyaluronic acid, collagen, fibrin, gelatin, or elastin. The polymer or gel may comprise any other polymer or gel.

[00280] The polymer or gel may be functionalized to bind to targeted analytes, such as nucleic acids, proteins, or other analytes. The polymer or gel may be polymerized or gelled via a passive mechanism. The polymer or gel may be stable in alkaline conditions or at elevated temperature. The polymer or gel may have mechanical properties similar to the mechanical properties of the bead. For instance, the polymer or gel may be of a similar size to the bead. The polymer or gel may have a mechanical strength (e.g. tensile strength) similar to that of the bead. The polymer or gel may be of a lower density than an oil. The polymer or gel may be of a density that is roughly similar to that of a buffer. The polymer or gel may have a tunable pore size. The pore size may be chosen to, for instance, retain denatured nucleic acids. The pore size may be chosen to maintain diffusive permeability to exogenous chemicals such as sodium hydroxide (NaOH) and/or endogenous chemicals such as inhibitors. The polymer or gel may be biocompatible. The polymer or gel may maintain or enhance cell viability. The polymer or gel may be biochemically compatible. The polymer or gel may be polymerized and/or depolymerized thermally, chemically, enzymatically, and/or optically.

[00281] The polymer may comprise poly(acrylamide-co-acrylic acid) crosslinked with disulfide linkages. The preparation of the polymer may comprise a two-step reaction. In the first activation step, poly(acrylamide-co-acrylic acid) may be exposed to an acylating agent to convert carboxylic acids to esters. For instance, the poly(acrylamide-co-acrylic acid) may be exposed to 4-(4,6-dimethoxy-1,3,5-triazin-2-yl)-4-methylmorpholinium chloride (DMTMM). The polyacrylamide-co-acrylic acid may be exposed to other salts of 4-(4,6-dimethoxy-1,3,5-triazin-2-yl)-4-methylmorpholinium. In the second cross-linking step, the ester formed in the first step may be exposed to a disulfide crosslinking agent. For instance, the ester may be exposed to cystamine (2,2'-dithiobis(ethylamine)). Following the two steps, the biological particle may be surrounded by polyacrylamide strands linked together by disulfide bridges. In this manner, the biological particle may be encased inside of or comprise a gel or matrix (e.g., polymer matrix) to form a "cell bead." A cell bead can contain biological particles (e.g., a cell) or macromolecular constituents (e.g., RNA, DNA, proteins, etc.) of biological particles. A cell bead may include a single cell or multiple cells, or a derivative of the single cell or multiple

cells. For example after lysing and washing the cells, inhibitory components from cell lysates can be washed away and the macromolecular constituents can be bound as cell beads. Systems and methods disclosed herein can be applicable to both cell beads (and/or droplets or other partitions) containing biological particles and cell beads (and/or droplets or other partitions) containing macromolecular constituents of biological particles. In some cases, the cell bead may further comprise one or more field-attractable particles (e.g., paramagnetic particles, conductive particles, etc.), such as via the systems and methods described elsewhere herein, for facilitating subsequent sorting and/or solvent exchange. The field-attractable particles may be trapped in the gel matrix. In some instances, the field-attractable particles may be trapped evenly throughout the gel matrix. In some instances, the field-attractable particles may be trapped throughout the gel matrix such as to subject the whole of the cell bead evenly to a force (e.g., magnetic, electric) field.

[00282] In another aspect, provided herein are systems and methods for selective polymerization of partitions (or cells therein). In some instances, the partitions may be selectively polymerized based on occupancy. In some instances, the partitions may be selectively polymerized based on size.

[00283] **FIG. 4** shows an example of a microfluidic channel structure for selective polymerization of partitions based on occupancy. As described elsewhere herein, in some cases, the majority of occupied partitions can include no more than one biological particle per occupied partition and, in some cases, some of the generated partitions can be unoccupied (of any biological particle). In some cases, though, some of the occupied partitions may include more than one biological particle. In some cases, the partitioning process may be controlled such that fewer than 25% of the occupied partitions contain more than one biological particle, and in many cases, fewer than 20% of the occupied partitions have more than one biological particle, while in some cases, fewer than 10% or even fewer than 5% of the occupied partitions include more than one biological particle per partition.

[00284] The emulsion mechanism of **FIG. 4** can largely parallel that of **FIG. 1**. As shown in **FIG. 4**, the channel structure can include channel segments **401**, **402**, **404**, **406** and **408**. Channel segments **401** and **402** can communicate at a channel junction **409**. Channel segments **402**, **404**, **406**, and **408** can communicate at a channel junction **410**. In operation, a first aqueous fluid **412** can be delivered to junction **409** from each of channel segments **402** and **401**. Cells **414** can be introduced into the junction **409** via the channel segment **401** as suspensions in the first aqueous fluid **412** flowing along the channel segment **401**. The first aqueous fluid **412** may or may not contain suspended field-attractable particles **115**. As described elsewhere herein, occupied droplets and unoccupied droplets may be sorted via the field-attractable particles **115**.

A second fluid **416** that is immiscible with the aqueous fluid **412** is delivered to the junction **410** from each of channel segments **404** and **406** to create discrete droplets **418**, **420** of the first aqueous fluid **412** flowing into channel segment **408**, and flowing away from junction **410**. A discrete droplet generated may or may not include biological particles **414**.

[00285] The second fluid **416** can comprise an oil, such as a fluorinated oil, and a surfactant, such as a fluorosurfactant for stabilizing the resulting droplets, e.g., inhibiting subsequent coalescence of the resulting droplets. Examples of particularly useful partitioning fluids and fluorosurfactants are described for example, in U.S. Patent Application Publication No. 2010/0105112, which is entirely incorporated herein by reference for all purposes.

[00286] The generated droplets may comprise two subsets of droplets: (1) occupied droplets **418**, containing one or more biological particles **414**, and (2) unoccupied droplets **420**, not containing any biological particles **414**.

[00287] A photo polymerization light source **424**, such as a laser, can be located downstream of the junction **410** to selectively polymerize occupied droplets (e.g., polymerize the biological particles therein). In some instances, the light source **424** can be a lamp or light emitting diode (LED). The light source can be an ultraviolet (UV) radiation source. The light source **424** can generate optical pulses or an electromagnetic beam at a targeted direction. For example, the light source **424** can be configured to only emit electromagnetic waves when an occupied droplet is passing by. The light source **424** can be operatively coupled to a controller **426**. The light source **424** can receive instructions from the controller **426** on whether or not a droplet passing by the light source **424**, or a droplet expected to pass by the light source at a certain time, is occupied. While **FIG. 4** depicts one light source **424**, it may be appreciated that there may be a plurality of light sources, each in communication with the controller **426** and/or with each other. For example, a plurality of light sources may each be located at different locations, including different upstream/downstream locations in the fluidic channels. Alternatively, a different polymerization application unit can be used to subject the droplets to a stimulus, such as to trigger polymerization via heating, cooling, electromagnetic radiation, and/or light. The stimulus can be a chemical stimulus. In some instances, a plurality of the same or different types of polymerization application units can be used at different locations.

[00288] A sensor **422** can be configured to sense the presence of a biological particle (or cell) **414** in the fluid flow. For example, the sensor **422** can be configured to sense the presence of a biological particle (or cell) **414** in the channel segment **401** upstream of the junction **409**. The sensor **422** may be located upstream of the junction **409**. In some instances, the sensor **422** can be an impedance sensor configured to measure bulk impedance when cells **414** pass by the sensor **422**. In some instances, a higher impedance can be measured when a cell **414** passes by

than when only the first aqueous fluid **412** passes by. In some instances, the sensor **422** can be an optical sensor configured to measure optical properties of a cell **414**. The optical sensor and/or a supporting device may be configured to emit a detection signal configured to probe one or more droplets, including for example an electromagnetic signal (e.g., in any wavelength) and/or an acoustic signal. In some instances, the optical sensor and/or a supporting device may comprise an illumination source configured to illuminate the cell with one or more types of electromagnetic radiation. In some instances, the electromagnetic radiation can include illumination in one or more of the visible spectrum, infrared spectrum, the ultraviolet spectrum, and ionizing radiation spectrum. In some instances, the ionizing radiation can include x-rays. The illumination can be transillumination or epi-illumination. Alternatively, the sensor **422** may be one or more devices that are configured to provide one or more of optical sensing, thermal sensing, laser imaging, infrared imaging, capacitance sensing, mass sensing, vibration sensing across at least a portion of the electromagnetic spectrum, and magnetic induction sensing. The sensor **422** may collect sensor data on one or more properties (e.g., optical properties, impedance properties, etc.) or characteristics of a cell **414**.

[00289] The sensor **422** can be operatively coupled to the controller **426**. For example, the sensor **426** may transmit sensor data (e.g., on presence of one or more cells **414**) to the controller **426**. The controller **426** may determine when a cell has passed by the sensor location from the sensor data. The controller **426** may then use such sensor data, the location of the sensor and/or the location in the fluidic channel at which the presence of a cell **414** was detected, the time the sensor detected a presence of the cell **414** in the flow, fluid flow rate of the first aqueous fluid **412** in the channel segment **402**, fluid flow rate of emulsion in the channel segment **408**, location of the light source **424**, time it takes for the sensor **426** to detect and/or transmit data to the controller **426**, and/or time it takes for the controller **426** to send instructions to the light source **424**, to send instructions to the light source **424** on whether or not to emit an electromagnetic wave to polymerize a droplet. For example, assuming that the fluid flow rates in the channel segments **402** and/or **408** are substantially constant, the controller **426** may determine whether a droplet created (e.g., at junction **410**) at a certain time contains a cell or does not contain a cell. Based on the fluid flow rates in the channel segments **402** and/or **408**, the controller **426** may determine whether a droplet passing by the light source **424** at a certain time (e.g., time it takes for droplet to travel from junction **410** to the location of the light source **424** site is the same every time) is occupied or unoccupied.

[00290] While **FIG. 4** depicts one sensor **422**, it may be appreciated that there may be a plurality of sensors, each in communication with the controller **426** and/or with each other. For

example, there can be a plurality of sensors upstream of the junction **409** and/or upstream of the junction **410** at different locations, for example, detecting the presence of a cell **414**.

[00291] While **FIG. 4** depicts one controller **426** operatively coupled to both the sensor **422** and the light source **424**, a separate controller can be coupled to the sensor **422** and a separate controller can be coupled to the light source **424**. The separate controllers may or may not be in communication with each other. In some instances, there may be a plurality of controllers (e.g., two controllers to sensor **422**), wherein each controller may or may not be in communication with each other. The controller **426** may send instructions to sensor **422** and/or the light source **424** via wired connection and/or wireless connection (e.g., Wi-Fi, Bluetooth, NFC, etc.). The controller **422** may receive data from the sensor **422** and/or the light source **424** via wired connection and/or wireless connection (e.g., Wi-Fi, Bluetooth, NFC, etc.). In some instances, the components can be directly or indirectly be in communication with each other, with or without going through the controller **426**. For example, the sensor **422** may be directly coupled to the light source **426**.

[00292] **FIG. 5** shows another example of a microfluidic channel structure for selective polymerization of partitions (e.g., biological particles therein) based on occupancy.

[00293] The emulsion mechanism of **FIG. 5** can largely parallel that of **FIGS. 1** and **4**. As shown in **FIG. 5**, the channel structure can include channel segments **501**, **502**, **504**, **506** and **508**. Channel segments **501** and **502** can communicate at a channel junction **509**. Channel segments **502**, **504**, **506**, and **508** can communicate at a channel junction **510**. In operation, a first aqueous fluid **512** can be delivered to junction **509** from each of channel segments **502** and **501**. Cells **514** can be introduced into the junction **509** via the channel segment **501** as suspensions in the first aqueous fluid **512** flowing along the channel segment **501**. The first aqueous fluid **512** may or may not contain suspended field-attractable particles **515**. As described elsewhere herein, occupied droplets and unoccupied droplets may be subsequently sorted via the field-attractable particles **515**. A second fluid **516** that is immiscible with the aqueous fluid **512** is delivered to the junction **510** from each of channel segments **504** and **506** to create discrete droplets **518**, **520** of the first aqueous fluid **512** flowing into channel segment **508**, and flowing away from junction **510**. A discrete droplet generated may or may not include biological particles **514**. Each cell **514** introduced into the droplet can comprise fluorescent labels (such as in accordance with the widely used Fluorescence-Activated Cell Sorting (FACS) mechanism) or other optical labels that allow for detection by an optical sensor.

[00294] The second fluid **516** can comprise an oil, such as a fluorinated oil, that includes a fluorosurfactant for stabilizing the resulting droplets, e.g., inhibiting subsequent coalescence of the resulting droplets. Examples of particularly useful partitioning fluids and fluorosurfactants

are described for example, in U.S. Patent Application Publication No. 2010/0105112, which is entirely incorporated herein by reference for all purposes.

[00295] The generated droplets may comprise two subsets of droplets: (1) occupied droplets **518**, containing one or more biological particles **514**, and (2) unoccupied droplets **520**, not containing any biological particles **514**.

[00296] A photo polymerization light source **524**, such as a laser, can be located downstream of the junction **510** to selectively polymerize occupied droplets. In some instances, the light source **524** can be a lamp or light emitting diode (LED). The light source **524** can generate optical pulses or an electromagnetic beam at a targeted direction. For example, the light source **524** can be configured to only emit electromagnetic waves when an occupied droplet is passing by. The light source **524** can be operatively coupled to a controller **526**. The light source **524** can receive instructions from the controller **526** on whether or not a droplet passing by the light source **524**, or a droplet expected to pass by the light source at a certain time, is occupied. While **FIG. 5** depicts one light source **524**, it may be appreciated that there may be a plurality of light sources, each in communication with the controller **526** and/or with each other. For example, a plurality of light sources may each be located at different locations, including different upstream/downstream locations in the fluidic channels. Alternatively, a different polymerization application unit can be used to subject the droplets to a stimulus, such as to trigger polymerization of one or more biological particles therein via heating, cooling, electromagnetic radiation, and/or light. The stimulus can be a chemical stimulus. In some instances, a plurality of the same or different types of polymerization application units can be used at different locations.

[00297] A sensor **522** can be configured to sense one or more characteristics of a droplet indicative of whether the droplet is occupied or unoccupied. The sensor **522** may be located downstream of the junction **510**. In some instances, the sensor **522** can be an impedance sensor configured to measure bulk impedance when droplets pass by the sensor **522**. In some instances, a higher impedance can be measured when an occupied droplet **518** passes by than when an unoccupied droplet **520** passes by. In some instances, the sensor **522** can be an optical sensor configured to measure optical properties of a droplet. The optical sensor and/or a supporting device may be configured to emit a detection signal configured to probe one or more droplets, including for example an electromagnetic signal (e.g., in any wavelength) and/or an acoustic signal. In some instances, the optical sensor and/or a supporting device may comprise an illumination source configured to illuminate the droplet or droplets with one or more types of electromagnetic radiation. In some instances, the electromagnetic radiation can include illumination in one or more of the visible spectrum, infrared spectrum, the ultraviolet spectrum,

and ionizing radiation spectrum. In some instances, the ionizing radiation can include x-rays. The illumination can be transillumination or epi-illumination. Alternatively the sensor **522** may be one or more devices that are configured to provide one or more of optical sensing, thermal sensing, laser imaging, infrared imaging, capacitance sensing, mass sensing, vibration sensing across at least a portion of the electromagnetic spectrum, and magnetic induction sensing. The sensor **522** may collect sensor data on one or more properties (e.g., optical properties, impedance properties, etc.) or characteristics of a droplet **414**. For example, the one or more properties or characteristics determined by the sensor **522** can be indicative of a certain type of droplets, such as occupied droplets, unoccupied droplets, singularly occupied droplets, multiply occupied droplets, droplets of a certain size or size range, etc.

[00298] The sensor **522** can be operatively coupled to the controller **526**. For example, the sensor **526** may transmit sensor data (e.g., one or more characteristics indicative of an occupancy of a droplet) to the controller **526**. The controller **526** may then use such data, the location of the sensor and/or the location in the fluidic channel at which the occupied droplet **518** was detected, the time the sensor **522** detected an occupied droplet **518**, fluid flow in the channel segment **508**, location of the light source **524**, time it takes for the sensor **526** to detect and/or transmit data to the controller **526**, and/or time it takes for the controller **526** to send instructions to the light source **524**, to send instructions to the light source **524** on whether or not to emit an electromagnetic wave to polymerize a droplet. For example, using such data, the controller **526** may determine whether a droplet passing by the sensor **522** location at a certain time is occupied or unoccupied. Based on the fluid flow rate in channel segment **508**, the controller **526** may determine whether a droplet passing by the light source **524** at a certain time (e.g., assuming time it takes for droplet to travel from the sensor **522** location to the location of the light source **524** site is the same every time) is occupied or unoccupied.

[00299] While **FIG. 5** depicts one sensor **522**, it may be appreciated that there may be a plurality of sensors, each in communication with the controller **526** and/or with each other. For example, there can be a plurality of sensors upstream or downstream of the junction **510** at different locations, for example, detecting the occupancy of a droplet.

[00300] While **FIG. 5** depicts one controller **526** operatively coupled to both the sensor **522** and the light source **524**, a separate controller can be coupled to the sensor **522** and a separate controller can be coupled to the light source **524**. The separate controllers may or may not be in communication with each other. In some instances, there may be a plurality of controllers (e.g., two controllers to sensor **522**), wherein each controller may or may not be in communication with each other. The controller **526** may send instructions to sensor **522** and/or the light source **524** via wired connection and/or wireless connection (e.g., Wi-Fi, Bluetooth, NFC, etc.). The

controller **522** may receive data from the sensor **522** and/or the light source **524** via wired connection and/or wireless connection (e.g., Wi-Fi, Bluetooth, NFC, etc.). In some instances, the components can be directly or indirectly be in communication with each other, with or without going through the controller **526**. For example, the sensor **522** may be directly coupled to the light source **526**.

[00301] FIG. 6 shows an example of a microfluidic channel structure for selective polymerization of partitions based on droplet size.

[00302] The emulsion mechanism of FIG. 6 can largely parallel that of FIGS. 1, 4, and 5. As shown in FIG. 6, the channel structure can include channel segments **601**, **602**, **604**, **606** and **608**. Channel segments **601** and **602** can communicate at a channel junction **609**. Channel segments **602**, **604**, **606**, and **608** can communicate at a channel junction **610**. In operation, a first aqueous fluid **612** can be delivered to junction **609** from each of channel segments **602** and **601**. Cells **614** can be introduced into the junction **609** via the channel segment **601** as suspensions in the first aqueous fluid **612** flowing along the channel segment **601**. The first aqueous fluid **612** may or may not contain suspended field-attractable particles **615**. As described elsewhere herein, occupied droplets and unoccupied droplets may be subsequently sorted via the field-attractable particles **615**. A second fluid **616** that is immiscible with the aqueous fluid **612** is delivered to the junction **610** from each of channel segments **604** and **606** to create discrete droplets **618**, **620** of the first aqueous fluid **612** flowing into channel segment **608**, and flowing away from junction **610**. A discrete droplet generated may or may not include biological particles **614**. Each cell **614** introduced into the droplet can comprise fluorescent labels (such as in accordance with the widely used Fluorescence-Activated Cell Sorting (FACS) mechanism).

[00303] In some instances, each droplet generated by the above emulsion may be of substantially uniform size that is appropriate (and/or acceptable) for feeding to subsequent single cell applications. In some instances, some droplets may be of substantially uniform size, and some droplets may have different sizes. For example, the droplets generated can have a size distribution where at least about 10%, 20%, 30%, 40%, 50%, 55%, 60%, 65%, 70%, 75%, 80%, 85%, 90%, 95%, 96%, 97%, 98%, 99% or a higher percentage of droplets generated can have a substantially uniform size. Alternatively, less than 10% of the droplets generated can have a size distribution where less than 10% of the droplets generated have a substantially uniform size. The system and methods described herein may selectively polymerize only droplets (e.g., polymerize biological particles contained therein the droplets) that have the appropriate (and/or acceptable) size and/or droplets that are occupied.

[00304] The second fluid **616** can comprise an oil, such as a fluorinated oil, that includes a fluorosurfactant for stabilizing the resulting droplets, e.g., inhibiting subsequent coalescence of the resulting droplets. Examples of particularly useful partitioning fluids and fluorosurfactants are described for example, in U.S. Patent Application Publication No. 2010/0105112, which is entirely incorporated herein by reference for all purposes.

[00305] The generated droplets may comprise two subsets of droplets: (1) occupied droplets **618A**, **618B**, containing one or more biological particles **614**, and (2) unoccupied droplets **620**, not containing any biological particles **614**. As described above, within the subset of occupied droplets **618A**, **618B**, some droplets may have the appropriate size (e.g., droplet **618A**) and some droplets may have an inappropriate size (e.g., droplet **618B**).

[00306] A photo polymerization light source **624**, such as a laser, can be located downstream of the junction **610** to selectively polymerize occupied droplets. In some instances, the light source **624** can be a lamp or light emitting diode (LED). The light source **624** can generate optical pulses or an electromagnetic beam at a targeted direction. For example, the light source **624** can be configured to only emit electromagnetic waves when an occupied droplet is passing by. The light source **624** can be operatively coupled to a controller **626**. The light source **624** can receive instructions from the controller **626** on whether or not a droplet passing by the light source **624**, or a droplet expected to pass by the light source at a certain time, is occupied. While **FIG. 6** depicts one light source **624**, it may be appreciated that there may be a plurality of light sources, each in communication with the controller **626** and/or with each other. For example, a plurality of light sources may each be located at different locations, including different upstream/downstream locations in the fluidic channels. Alternatively, a different polymerization application unit can be used to subject the droplets to a stimulus, such as to trigger polymerization via heating, cooling, electromagnetic radiation, and/or light. The stimulus can be a chemical stimulus. In some instances, a plurality of the same or different types of polymerization application units can be used at different locations.

[00307] A sensor **622** can be configured to sense one or more characteristics of a droplet indicative of whether the droplet is occupied or unoccupied. The sensor **622** may be located downstream of the junction **610**. In some instances, the sensor **622** can be an impedance sensor configured to measure bulk impedance when droplets pass by the sensor **622**. In some instances, a higher impedance can be measured when a larger droplet (e.g., droplet **618B**) passes by than when a smaller droplet (e.g., droplet **618A** or droplet **620**) passes by. In some instances, a higher impedance can be measured when an occupied droplet (e.g., droplets **618A**, **618B**) passes by than when an unoccupied droplet (e.g., droplet **620**) passes by. In some instances, the sensor **622** can be an optical sensor configured to measure optical properties of a droplet. The optical sensor

and/or a supporting device may be configured to emit a detection signal configured to probe one or more droplets, including for example an electromagnetic signal (e.g., in any wavelength) and/or an acoustic signal. In some instances, the optical sensor and/or a supporting device may comprise an illumination source configured to illuminate the droplet or droplets with one or more types of electromagnetic radiation. In some instances, the electromagnetic radiation can include illumination in one or more of the visible spectrum, infrared spectrum, the ultraviolet spectrum, and ionizing radiation spectrum. In some instances, the ionizing radiation can include x-rays. The illumination can be transillumination or epi-illumination. Alternatively the sensor **622** may be one or more devices that are configured to provide one or more of optical sensing, thermal sensing, laser imaging, infrared imaging, capacitance sensing, mass sensing, vibration sensing across at least a portion of the electromagnetic spectrum, and magnetic induction sensing. The sensor **622** may collect sensor data on one or more properties (e.g., optical properties, impedance properties, etc.) or characteristics of a droplet. For examples, the one or more properties and/or other characteristics of a droplet measured by the sensor **622** can be indicative of a size and/or an occupancy of the droplet.

[00308] The sensor **622** can be operatively coupled to the controller **626**. For example, the sensor **626** may transmit sensor data (e.g., size and/or occupancy of a droplet) to the controller **626**. The controller **626** may then use such data, the location of the sensor and/or the location in the fluidic channel at which the occupancy and/or size of a droplet was detected, the time the sensor **622** detected, fluid flow in the channel segment **608**, location of the light source **624**, time it takes for the sensor **626** to detect and/or transmit data to the controller **626**, and/or time it takes for the controller **626** to send instructions to the light source **624**, to send instructions to the light source **624** on whether or not to emit an electromagnetic wave to polymerize a droplet. For example, assuming that the fluid flow rates in the channel segment **608** are substantially constant, the controller **626** may determine whether a droplet passing by a sensor **622** location at a certain time is occupied or unoccupied. Based on the fluid flow rate in channel segment **608**, the controller **626** may determine whether a droplet passing by the light source **624** at a certain time (e.g., assuming time it takes for droplet to travel from the sensor **622** location to the location of the light source **624** site is the same every time) is occupied or unoccupied.

[00309] While **FIG. 6** depicts one sensor **622**, it may be appreciated that there may be a plurality of sensors, each in communication with the controller **626** and/or with each other. For example, there can be a plurality of sensors upstream or downstream of the junction **610** at different locations, for example, detecting the occupancy of a droplet. In some instances, a separate sensor can detect occupancy of a droplet and a separate sensor can detect size of the

droplet. The separate sensors may or may not detect such characteristics at the same upstream/downstream location of the fluid channel.

[00310] While **FIG. 6** depicts one controller **626** operatively coupled to both the sensor **622** and the light source **624**, a separate controller can be coupled to the sensor **622** and a separate controller can be coupled to the light source **624**. The separate controllers may or may not be in communication with each other. In some instances, there may be a plurality of controllers (e.g., two controllers to sensor **622**), wherein each controller may or may not be in communication with each other. The controller **626** may send instructions to sensor **622** and/or the light source **624** via wired connection and/or wireless connection (e.g., Wi-Fi, Bluetooth, NFC, etc.). The controller **622** may receive data from the sensor **622** and/or the light source **624** via wired connection and/or wireless connection (e.g., Wi-Fi, Bluetooth, NFC, etc.). In some instances, the components can be directly or indirectly be in communication with each other, with or without going through the controller **626**. For example, the sensor **622** may be directly coupled to the light source **626**.

[00311] In some instances, a plurality of droplets, wherein a first subset comprises polymerized droplets and a second subset comprises pre-polymerized droplets can be further sorted based on polymerization status, such as via solvent exchange. For example, the pre-polymerized droplets can be washed away during solvent exchange to isolate the polymerized droplets.

[00312] The separation systems and methods for sorting and/or selective polymerization described above and further below may achieve super Poissonian loading. For example, the droplets can be separated into two subsets such that at least about 5%, 10%, 15%, 20%, 25%, 30%, 40%, 50%, 60%, 70%, 80%, 90%, 95%, 96%, 97%, 98%, 99%, or greater of a first subset of droplets that is isolated are occupied droplets (e.g., containing at least one biological particle). Such occupancy may be greater than or equal to 1%, 2%, 3%, 4%, 5%, 10%, 20%, 30%, 40%, 50%, 60%, 70%, 80%, 90%, 95%, or higher. Alternatively, less than about 97% of the first subset of droplets can be occupied droplets. In some instances, at least about 97%, 98%, 99%, or a higher percentage of a second subset of droplets that is isolated are unoccupied droplets (e.g., not containing any biological particle and not containing any barcode carrying beads). Alternatively, less than about 97% of the second subset of droplets can be unoccupied droplets. The separation systems and methods described above and below may achieve super Poissonian monodispersity. For example, the droplets can be separated into two subsets such that at least about 5%, 10%, 15%, 20%, 25%, 30%, 40%, 50%, 60%, 70%, 80%, 90%, 95%, 96%, 97%, 98%, 99%, or greater of a first subset of droplets that is isolated are within a given droplet size range. Such monodispersity may be greater than or equal to 1%, 2%, 3%, 4%, 5%, 10%, 20%,

30%, 40%, 50%, 60%, 70%, 80%, 90%, 95%, or higher. Alternatively, less than about 97% of the first subset of droplets can be within a given droplet size range.

[00313] As described elsewhere herein, a cell bead can be formed after the polymerization process, such as via the selective polymerization systems and methods described herein. Alternatively, a different polymerization procedure can be used. For example, cell beads can be formed by selectively polymerizing one or more biological particles within droplets, such as via methods described in relation to **FIG. 4-6**. In another example, a cell bead can be formed by polymerizing one or more biological particles that are suspended in a first solvent, such as oil. In some cases, a plurality of biological particles (e.g., cells) may be hardened and/or polymerized in bulk by applying a stimulus (e.g., light, chemical, temperature, etc.) to the first solvent carrying the plurality of biological particles (e.g., as suspensions). Upon formation, a plurality of cell beads may be surrounded by the first solvent, such as an oil. In order to promote integration of a cell bead into a droplet with a gel bead, the cell bead may be placed into an aqueous environment by a solvent exchange process. The solvent exchange process may comprise the operations of collecting a plurality of cell beads surrounded by oil (for instance, in an Eppendorf tube or other collection vessel), removing excess oil (for instance, by pipetting), adding a ligation buffer (such as a 3x ligation buffer), vortexing, adding a buffer (such as a 1x 1H,1H,2H,2H-perfluoro-1-octanol (PFO) buffer), vortexing, centrifugation, and separation. The separation operation may comprise magnetic separation.

[00314] Each of the cell beads may comprise field-attractable particles (e.g., paramagnetic particles). For example, cell beads comprising field-attractable particles can be formed using the systems and methods described elsewhere herein (e.g., field-attractable particles **115** in **FIG. 1** are suspended in fluids that form emulsion droplets which can be polymerized to form cell beads). The magnetic separation may be accomplished by using a magnetic separating apparatus to pull cell beads containing paramagnetic particles away from unwanted remaining oil and solvents. In some instances, the magnetic separating apparatus can be a field application unit as described elsewhere herein (e.g., the same type of field application unit **216** in **FIG. 2A**, field application unit **316** in **FIG. 3**). For instance, the magnetic separation apparatus may be used to pull cell beads containing paramagnetic particles away from the ligation buffer and PFO to allow removal of the ligation buffer and PFO (for instance by pipetting). The cell beads containing paramagnetic particles may then be suspended in a ligation buffer and vortexed. The cell beads containing paramagnetic particles may again be separated magnetically and the ligation buffer may be removed. This cycle of re-suspension, vortexing, and magnetic separation may be repeated until the cell beads are clean. For instance, the cycle may be repeated 1, 2, 3, 4, 5, 6, 7, 8, 9, 10, or more than 10 times. The cell beads may then be placed into an aqueous medium.

[00315] Once the cell beads are in an aqueous medium, the cell beads may be further treated. For instance, the cell beads in aqueous solution may be filtered (for instance, using a 70 μm filter) to remove clumps and/or large cell beads from the solution. In some cases, additional reagents may be added to and/or removed from the aqueous medium to further process the cell beads. The cell beads may then be combined into droplets with gel beads, as described herein.

[00316] Also provided herein are the microfluidic devices used for partitioning the cells as described above. Such microfluidic devices can comprise channel networks for carrying out the partitioning process like those set forth in **FIGS. 1, 4, 5, and 6**. These microfluidic devices can comprise channel networks, such as those described herein, for partitioning cells into separate partitions, and co-partitioning such cells with oligonucleotide barcode library members, e.g., disposed on beads. These channel networks can be disposed within a solid body, e.g., a glass, semiconductor or polymer body structure in which the channels are defined, where those channels communicate at their termini with reservoirs for receiving the various input fluids, and for the ultimate deposition of the partitioned cells, etc., from the output of the channel networks. By way of example, and with reference to **FIG. 1**, a reservoir fluidly coupled to channel **102** may be provided with an aqueous suspension of cells **114**, while a reservoir coupled to another channel (not shown) may be provided with an aqueous suspension of beads carrying the oligonucleotides. Channel segments **106** and **108** may be provided with a non-aqueous solution, e.g., an oil, into which the aqueous fluids are partitioned as droplets at the channel junction **110**. Finally, an outlet reservoir may be fluidly coupled to channel **108** into which the partitioned cells and beads can be delivered and from which they may be harvested. As will be appreciated, while described as reservoirs, it will be appreciated that the channel segments may be coupled to any of a variety of different fluid sources or receiving components, including tubing, manifolds, or fluidic components of other systems.

[00317] Also provided are systems that control flow of these fluids through the channel networks e.g., through applied pressure differentials, centrifugal force, electrokinetic pumping, compressors, capillary or gravity flow, or the like.

[00318] The systems and methods described herein may allow for the production of one or more droplets containing a single biological particle and/or a single bead. The systems and methods may also allow for the production of one or more droplets containing a single biological particle and more than one bead, one or more droplets containing more than one biological particle and a single bead, or one or more droplets containing more than one biological particle and more than one bead. The systems and methods described herein may allow for the production of one or more cell beads containing a single biological particle and/or a single bead. The systems and methods may also allow for selective polymerization of occupied droplets

and/or appropriately sized droplets, which mixture of polymerized and pre-polymerized droplets may or may not be subjected to subsequent sorting.

[00319] FIG. 7 shows a flowchart for a method of sorting occupied droplets and unoccupied droplets, wherein an occupied droplet contains at least a biological particle (cell) and/or a barcode carrying bead (particle).

[00320] In an operation 701, a plurality of droplets are generated upon bringing a first phase in contact with a second phase, wherein the first phase and the second phase are immiscible. Each of the plurality of droplets comprises some number and/or concentration of field-attractable particles. A first subset of the plurality of droplets contains therein cells and/or barcode carrying particles, and a second subset of the plurality of droplets does not contain therein cells and/or barcode carrying particles. A given droplet in the first subset of the plurality of droplets may contain a single cell or a plurality of cells. A given droplet in the first subset of the plurality of droplets may contain a single barcode carrying particle or a plurality of barcode carrying particles. A given droplet of the first subset of the plurality of droplets may contain a fewer number and/or lower concentration of field-attractable particles than a given droplet of the second subset of the plurality of droplets, on account of the volume occupied by the cell and/or barcode carrying particles contained in the occupied droplet.

[00321] In an operation 702, the plurality of droplets is directed along the first channel towards an intersection of the first channel. The intersection can be between the first channel, a second channel, and a third channel. The plurality of droplets may be directed along one or more channels in a flow of fluid (e.g., either the first phase or the second phase used to generate the droplets), such as via a fluid flow unit.

[00322] In an operation 703, the plurality of droplets is subject to a force field, such as via a field application unit, at or near the intersection. The force field can be a magnetic field and/or an electric field. The plurality of droplets can be subjected to the force field under conditions sufficient to separate the first subset of droplets from the second subset of the droplets, wherein upon separation, the first subset of droplets flows along the second channel, and the second subset of droplets flows along the third channel. For example, the field-attractable particles can be paramagnetic particles when a magnetic field is applied. The field-attractable particles can be conductive particles when an electric field is applied. Because a given droplet in the second subset of the plurality of droplets has a greater number and/or concentration of field-attractable particles than a given droplet in the first subset of the plurality of droplets, for the same field applied, a stronger force can act on a given droplet in the second subset of droplets than on a given droplet in the first subset of droplets. The force differential may separate the two subsets,

such as by influencing a greater deviation in fluid flow path direction for a given droplet in the second subset of droplets than for a given droplet in the first subset of droplets.

[00323] The method of **FIG. 7** may isolate occupied droplets (e.g., first subset of droplets) with super-Poissonian loading. For example, a plurality of droplets can be separated into two subsets such that at least about 5%, 10%, 15%, 20%, 25%, 30%, 40%, 50%, 60%, 70%, 80%, 90%, 95%, 96%, 97%, 98%, 99%, or greater of a first subset of droplets that is isolated are occupied droplets (e.g., containing at least one biological particle). Such occupancy may be greater than or equal to 1%, 2%, 3%, 4%, 5%, 10%, 20%, 30%, 40%, 50%, 60%, 70%, 80%, 90%, 95%, or higher. Alternatively, less than about 97% of droplets of a separated subset of the plurality of droplets may be occupied droplets.

[00324] The method of **FIG. 7** may be similarly used to isolate occupied particles from a plurality of particles containing occupied and unoccupied particles. For example, a plurality of particles may be generated to comprise a first subset of occupied particles (containing a biological particle and/or a barcode carrying particle therein) and a second subset of unoccupied particles, wherein particles of both the first subset and the second subset comprise field-attractable particles. A given particle of the first subset may contain a fewer number and/or lower concentration of field-attractable particles than a given particle of the second subset, on account of the volume occupied by the cell and/or barcode carrying particles contained in the occupied particle. The plurality of particles may be directed along a first channel towards an intersection of the first channel. The intersection can be between the first channel, a second channel, and a third channel.

[00325] The plurality of particles can be subject to a force field, such as via a field application unit, at or near the intersection. The force field can be a magnetic field and/or an electric field. The plurality of particles can be subjected to the force field under conditions sufficient to separate the first subset from the second subset, wherein upon separation, the first subset of particles flows along the second channel, and the second subset of particles flows along the third channel. For example, the field-attractable particles can be paramagnetic particles when a magnetic field is applied. The field-attractable particles can be conductive particles when an electric field is applied. Because a given particle in the second subset has a greater number and/or concentration of field-attractable particles than a given particle in the first subset, for the same field applied, a stronger force can act on a given particle in the second subset than on a given particle in the first subset. The force differential may separate the two subsets, such as by influencing a greater deviation in fluid flow path direction for a given particle in the second subset than for a given particle in the first subset.

[00326] The method of **FIG. 7** may isolate occupied particles (e.g., first subset of particles) with super-Poissonian loading. For example, a plurality of particles can be separated into two subsets such that at least about 5%, 10%, 15%, 20%, 25%, 30%, 40%, 50%, 60%, 70%, 80%, 90%, 95%, 96%, 97%, 98%, 99%, or greater of a first subset of particles that is isolated are occupied particles (e.g., containing at least one biological particle). Such occupancy may be greater than or equal to 1%, 2%, 3%, 4%, 5%, 10%, 20%, 30%, 40%, 50%, 60%, 70%, 80%, 90%, 95%, or higher. Alternatively, less than about 97% of particles of a separated subset of the plurality of particles may be occupied particles.

[00327] **FIG. 8** shows a flowchart for a method of sorting occupied droplets and unoccupied droplets, wherein an occupied droplet contains at least a biological particle (cell) and/or a barcode carrying bead (particle).

[00328] In an operation **801**, a plurality of droplets are generated upon bringing a first phase in contact with a second phase, wherein the first phase and the second phase are immiscible. Each of the plurality of droplets comprises may or may not comprise some number and/or concentration of field-attractable particles. The presence of field-attractable particles is not required. A first subset of the plurality of droplets contains therein cells and/or barcode carrying particles, and a second subset of the plurality of droplets does not contain therein cells and/or barcode carrying particles. A given droplet in the first subset of the plurality of droplets may contain a single cell or a plurality of cells. A given droplet in the first subset of the plurality of droplets may contain a single barcode carrying particle or a plurality of barcode carrying particles.

[00329] In an operation **802**, the plurality of droplets is directed along the first channel towards an intersection of the first channel. The intersection can be between the first channel, a second channel, and a third channel. The plurality of droplets may be directed along one or more channels in a flow of fluid (e.g., either the first phase or the second phase used to generate the droplets), such as via a fluid flow unit.

[00330] In an operation **803**, the plurality of droplets is subject to a pressure pulse, such as via a pressure application unit, at or near the intersection. The pressure pulse can be provided as a positive pressure pulse or a negative pressure pulse. The plurality of droplets can be subjected to the pressure pulse under conditions sufficient to separate the first subset of droplets from the second subset of the droplets, wherein upon separation, the first subset of droplets flows along the second channel, and the second subset of droplets flows along the third channel. Because a given droplet in the second subset of the plurality of droplets has different particle and/or suspension characteristics in the fluid than a given droplet in the first subset of the plurality of droplets, for the same pressure pulse applied, a different hydrodynamic force can act on a given

droplet in the second subset of droplets than on a given droplet in the first subset of droplets. The pressure pulse may separate the two subsets, such as by influencing a greater deviation in fluid flow path direction for a given droplet in the second subset of droplets than for a given droplet in the first subset of droplets.

[00331] In some instances, a sensor, such as an impedance sensor or an optical sensor, may measure one or more characteristics of a droplet at an upstream location of the intersection. The sensing data may be indicative of the occupancy of the droplet. The sensing data may be transmitted to a controller. The controller may use the sensing data to determine the occupancy of the droplet and instruct the pressure application unit to generate or not generate pressure pulses to separate the first subset from the second subset.

[00332] The method of **FIG. 8** may isolate occupied droplets (e.g., first subset of droplets) with super-Poissonian loading. For example, a plurality of droplets can be separated into two subsets such that at least about 5%, 10%, 15%, 20%, 25%, 30%, 40%, 50%, 60%, 70%, 80%, 90%, 95%, 96%, 97%, 98%, 99%, or greater of a first subset of droplets that is isolated are occupied droplets (e.g., containing at least one biological particle). Such occupancy may be greater than or equal to 1%, 2%, 3%, 4%, 5%, 10%, 20%, 30%, 40%, 50%, 60%, 70%, 80%, 90%, 95%, or higher. Alternatively, less than about 97% of droplets of a separated subset of the plurality of droplets may be occupied droplets.

[00333] The method of **FIG. 8** may be similarly used to isolate cell beads from a plurality of particles containing both cell beads and unoccupied particles. For example, a plurality of particles may be generated to comprise a first subset of occupied particles (containing a biological particle and/or a barcode carrying particle therein) and a second subset of unoccupied particles. The presence of field-attractable particles is not required. The plurality of particles may be directed along a first channel towards an intersection of the first channel. The intersection can be between the first channel, a second channel, and a third channel. The plurality of particles may be subject to a pressure pulse, such as via a pressure application unit, at or near the intersection. The pressure pulse can be provided as a positive pressure pulse or a negative pressure pulse.

[00334] The plurality of particles can be subjected to the pressure pulse under conditions sufficient to separate the first subset of particles (e.g., cell beads) from the second subset of the particles (e.g., unoccupied particles), wherein upon separation, the first subset of particles flows along the second channel, and the second subset of particles flows along the third channel. Because a given particle in the second subset of the plurality of particles has different particle and/or suspension characteristics in the fluid than a given particle in the first subset of the plurality of particles, for the same pressure pulse applied, a different hydrodynamic force can act

on a given particle in the second subset of particles than on a given particle in the first subset of particles. The pressure pulse may separate the two subsets, such as by influencing a greater deviation in fluid flow path direction for a given particle in the second subset of particles than for a given particle in the first subset of particles.

[00335] In some instances, a sensor, such as an impedance sensor or an optical sensor, may measure one or more characteristics of a particle at an upstream location of the intersection. The sensing data may be indicative of the occupancy of the particle. The sensing data may be transmitted to a controller. The controller may use the sensing data to determine the occupancy of the particle and instruct the pressure application unit to generate or not generate pressure pulses to separate the first subset from the second subset.

[00336] The method of **FIG. 8** may isolate cell beads (e.g., first subset of particles) with super-Poissonian loading. For example, a plurality of particles can be separated into two subsets such that at least about 5%, 10%, 15%, 20%, 25%, 30%, 40%, 50%, 60%, 70%, 80%, 90%, 95%, 96%, 97%, 98%, 99%, or greater of a first subset of particles that is isolated are cell beads (e.g., containing at least one biological particle). Such occupancy may be greater than or equal to 1%, 2%, 3%, 4%, 5%, 10%, 20%, 30%, 40%, 50%, 60%, 70%, 80%, 90%, 95%, or higher. Alternatively, less than about 97% of particles of a separated subset of the plurality of particles may be cell beads.

[00337] **FIG. 9** shows a flowchart for a method of selectively polymerizing occupied droplets, wherein an occupied droplet contains at least a biological particle (cell) and/or a barcode carrying bead (particle).

[00338] In an operation **901**, a plurality of droplets are generated upon bringing a first phase in contact with a second phase, wherein the first phase and the second phase are immiscible. Each of the plurality of droplets comprises may or may not comprise some number and/or concentration of field-attractable particles. The presence of field-attractable particles is not required. A first subset of the plurality of droplets contains therein cells and/or barcode carrying particles, and a second subset of the plurality of droplets does not contain therein cells and/or barcode carrying particles. A given droplet in the first subset of the plurality of droplets may contain a single cell or a plurality of cells. A given droplet in the first subset of the plurality of droplets may contain a single barcode carrying particle or a plurality of barcode carrying particles.

[00339] In an operation **902**, at an upstream location, a sensor detects and/or measures one or more characteristics of a droplet passing through the upstream location. The one or more characteristics can be indicative of the occupancy of the droplet. In some instances, the sensor can be an impedance sensor configured to detect bulk impedance as a droplet or a plurality of

droplets passes through the upstream location. A higher impedance can be measured for occupied droplets than for unoccupied droplets. In some instances, the sensor can be an optical sensor configured to detect one or more optical characteristics of the droplet as the droplet passes through the upstream location. Alternatively, a plurality of the same or different types of sensors can be used to detect and/or measure one or more characteristics of the droplet passing through the upstream location.

[00340] In an operation **903**, the sensing data may be transmitted to a controller. For example, the sensor can be operatively coupled to the controller. The controller can determine, based at least in part on the sensor data, whether a droplet passing through a downstream location is occupied or unoccupied. For example, the controller may use such sensor data, the location of the sensor and/or the location in the fluidic channel at which the occupancy of a droplet was detected, the time the sensor detected the occupancy of a droplet, fluid flow rate of one or more channels, location of the light source, time it takes for the sensor to detect and/or transmit data to the controller, and/or time it takes for the controller to send instructions to the light source, to send instructions to the light source on whether or not to emit an electromagnetic wave to polymerize a droplet.

[00341] Alternatively, in some instances, the sensor may detect the presence of a cell suspended in a fluid flow before the droplets are generated (e.g., at the intersection), and use such sensor data of the presence of the cell, and other information (e.g., location, times, fluid flow rates) to determine whether a droplet at a downstream location is occupied.

[00342] In an operation **904**, the controller may transmit instruction to a light source at a downstream location to emit electromagnetic waves to polymerize a droplet if the droplet is occupied, and not to emit electromagnetic waves if the droplet is unoccupied, thus letting the unoccupied droplet pass through unpolymerized. Alternatively, other polymerization application units can be used in place of, or in conjunction with the light source.

[00343] The method of **FIG. 9** may polymerize occupied droplets (e.g., first subset of droplets) with super-Poissonian distribution. The separation systems and methods disclosed herein may achieve super Poisson loading. For example, at least about 5%, 10%, 15%, 20%, 25%, 30%, 40%, 50%, 60%, 70%, 80%, 90%, 95%, 96%, 97%, 98%, 99%, or greater of a plurality of droplets that are polymerized can be occupied droplets. Such occupancy may be greater than or equal to 1%, 2%, 3%, 4%, 5%, 10%, 20%, 30%, 40%, 50%, 60%, 70%, 80%, 90%, 95%, or higher. Alternatively, less than about 97% of polymerized droplets may be occupied droplets.

[00344] **FIG. 10** shows a flowchart for a method of selectively polymerizing appropriately sized droplets.

[00345] In an operation **1001**, a plurality of droplets are generated upon bringing a first phase in contact with a second phase, wherein the first phase and the second phase are immiscible. Each of the plurality of droplets comprises may or may not comprise some number and/or concentration of field-attractable particles. The presence of field-attractable particles is not required. A first subset of the plurality of droplets contains therein cells and/or barcode carrying particles, and a second subset of the plurality of droplets does not contain therein cells and/or barcode carrying particles. A given droplet in the first subset of the plurality of droplets may contain a single cell or a plurality of cells. A given droplet in the first subset of the plurality of droplets may contain a single barcode carrying particle or a plurality of barcode carrying particles.

[00346] In an operation **1002**, at an upstream location, a sensor detects and/or measures one or more characteristics of a droplet passing through the upstream location. The one or more characteristics can be indicative of a size of the droplet. In some instances, the sensor can be an impedance sensor configured to detect bulk impedance as a droplet or a plurality of droplets passes through the upstream location. A higher impedance can be measured for larger droplets than for smaller droplets. In some instances, the sensor can be an optical sensor configured to detect one or more optical characteristics of the droplet as the droplet passes through the upstream location. Alternatively, a plurality of the same or different types of sensors can be used to detect and/or measure one or more characteristics of the droplet passing through the upstream location.

[00347] In an operation **1003**, the sensing data may be transmitted to a controller. For example, the sensor can be operatively coupled to the controller. The controller can determine, based at least in part on the sensor data, whether a droplet passing through a downstream location is appropriately sized or inappropriately sized. For example, the controller may use such sensor data, the location of the sensor and/or the location in the fluidic channel at which the size of a droplet was detected, the time the sensor detected the size of a droplet, fluid flow rate of one or more channels, location of the light source, time it takes for the sensor to detect and/or transmit data to the controller, and/or time it takes for the controller to send instructions to the light source, to send instructions to the light source on whether or not to emit an electromagnetic wave to polymerize a droplet.

[00348] In an operation **1004**, the controller may transmit instruction to a light source at a downstream location to emit electromagnetic waves to polymerize a droplet if the droplet is appropriately sized, and not to emit electromagnetic waves if the droplet is inappropriately sized, thus letting the inappropriately sized droplet pass through unpolymerized. Alternatively, other polymerization application units can be used in place of, or in conjunction with the light source.

[00349] The method of **FIG. 10** may polymerize appropriately sized droplets (e.g., first subset of droplets) with super-Poissonian distribution. For example, at least about 5%, 10%, 15%, 20%, 25%, 30%, 40%, 50%, 60%, 70%, 80%, 90%, 95%, 96%, 97%, 98%, 99%, or greater of a plurality of droplets that is polymerized can be appropriately sized droplets. Alternatively, less than about 97% of polymerized droplets may be appropriately sized droplets.

[00350] In some instances, the methods of **FIG. 9** and **FIG. 10** can be combined such that one or more sensors detect one or more characteristics of a droplet at an upstream location (or upstream locations), wherein the one or more characteristics of the droplet are indicative of both a size and an occupancy of the droplet, and transmits the sensor data to a controller. The controller transmits instructions to a light source at a downstream location to polymerize the droplet only if the droplet is both appropriately sized and occupied.

[00351] In another aspect, provided is a passive mechanism for sorting occupied droplets from unoccupied droplets. The passive mechanism may not require application of external forces (e.g., magnetic field, electric field, pressure pulse, etc.) on the droplets to achieve sorting. The passive mechanism may sort droplets based at least in part on mechanical properties of the droplets. For example, the passive mechanism may sort droplets based at least in part on properties such as deformability and surface tension (e.g., surface interface energy) of the droplets. In some instances, due to the presence of one or more biological particles in an occupied droplet, the occupied droplet may demonstrate lower deformability and/or higher surface tension properties than unoccupied droplets, making occupied droplets ‘harder’ or ‘stiffer’ than unoccupied droplets. Thus, when a plurality of droplets comprising both a first subset of occupied droplets and a second subset of unoccupied droplets is directed to pass through an aperture which is smaller in size than a diameter of a given droplet in the plurality of droplets, only those droplets capable of deforming (e.g., unoccupied droplets having higher deformability properties) may pass through the aperture, trapping the occupied droplets, thereby sorting the occupied droplets from the unoccupied droplets.

[00352] **FIG. 11** shows a schematic example of a microfluidic channel structure for separating occupied droplets from unoccupied droplets. As described elsewhere herein, when droplets are generated, there may be at least a first subset population of occupied droplets containing one or more biological particles and at least a second subset population of unoccupied droplets not containing any biological particles. In some cases, the droplets may additionally contain one or more barcode carrying beads. For example, a droplet may have only a biological particle, a droplet may have only a barcode carrying bead, a droplet may have both a biological particle and a barcode carrying bead, or a droplet may have neither biological particles nor barcode carrying beads. In some cases, the majority of occupied partitions (e.g., droplets) can

include no more than one biological particle per occupied partition and, in some cases, some of the generated partitions can be unoccupied (e.g., by any biological particle). In some cases, though, some of the occupied partitions may include more than one biological particle. In some cases, the partitioning process may be controlled such that fewer than 25% of the occupied partitions contain more than one biological particle, fewer than 20% of the occupied partitions have more than one biological particle, or fewer than 10% or even fewer than 5% of the occupied partitions include more than one biological particle per partition.

[00353] As shown in **FIG. 11**, the channel structure can include a channel segment **1100** with an entrance **1102** and exit **1104**. In some instances, the outflow channel **108** of the emulsion carrying the generated droplets in **FIG. 1** can be upstream of the channel segment **1100**. A fluid flow unit (not shown) can be configured to facilitate flow of fluid in the channel structure.

[00354] In operation, a plurality of discrete droplets, each comprising a first aqueous fluid **1100** can flow as emulsions in a second fluid **1112**, wherein the second fluid **1112** is immiscible to the first aqueous fluid **1110**. The droplets being transported along channel segment **1100** can comprise a first subset of droplets **1108** that are each occupied with at least a biological particle and/or a barcode carrying bead and a second subset of droplets **1110** that are each unoccupied. As described above, a given unoccupied droplet can have a higher deformability and/or lower surface tension property than a given occupied droplet, due to the presence of one or more biological particles in the occupied droplet.

[00355] The channel segment **1100** can comprise a plurality of entrapment structures **1114**. An entrapment structure can define an aperture. A size of the aperture may be less than a diameter (or other size dimension) of a droplet. A size of the aperture may be less than a minimum dimension of a droplet. In some instances, the size of the aperture can be at most about 90%, 80%, 70%, 60%, 50%, 45%, 40%, 35%, 30%, 25%, 20%, 15%, 10%, or 5% of the diameter of a droplet (in a pre-deformed state). The size of the aperture can be less than about 5% of the diameter of a droplet. Alternatively, the size of the aperture can be greater than 50%, 60%, 70%, 80%, 90%, 100%, 150%, or 200% of the diameter of a droplet. The size of the aperture can be greater than the diameter of the droplet. When a plurality of droplets comprising both a first subset of occupied droplets **1108** and a second subset of unoccupied droplets **1110** is directed to pass through entrapment structures **1114** defining apertures which is smaller in size than a diameter of a given droplet in the plurality of droplets, only those droplets deforming **1118** (e.g., unoccupied droplets **1110** having higher deformability properties) such that at least one dimension of the droplet is less than a size of the aperture may pass through one or more apertures defined by the entrapment structures **1114**. Because occupied droplets **1108** may be 'harder' or 'stiffer,' due to a presence of one or more biological particles in the droplets, the

occupied droplets may resist deformation, at least from deforming to a size smaller than a size of the aperture, and remain trapped by the entrapment structures **1114**.

[00356] In some embodiments, there may exist more entrapment structures **1114** (and thus more apertures) in the channel structure than there are droplets **1106**, **1108** passing through the channel structure. Beneficially, when the occupied droplets **1108** are prevented from flowing through the entrapment structures **1114**, and the occupied droplets **1108** clog (or block) some apertures of the entrapment structures **1114**, the unoccupied droplets **1110** may still deform and flow through other apertures. After sorting, the entrapment structures **1114** may retain from the plurality of droplets only the first subset of occupied droplets **1108**. The unoccupied droplets **1104** may flow through all entrapment structures **1114** and exit the channel segment **1100** to a separate compartment, such as for recycling or discarding. While **FIG. 11** shows exemplary configurations and a layout of entrapment structures in the channel structure, the configurations and layout of entrapment structures are not limited as such. For example, an entrapment structure can be a single plate with a plurality of apertures (e.g., holes) defined in the plate. The plate can be planar, curved, and/or a combination thereof. The channel structure and the entrapment structures **1114** can be configured such that a droplet from the plurality of droplets passes through at least one entrapment structure (and aperture defined therein). After entrapment and/or sorting of the occupied droplets, the fluid flow unit (not shown) can be configured to reverse a fluid flow direction to collect the occupied droplets from the entrapment structures.

[00357] In some instances, the fluid flow unit may comprise a compressor to provide positive pressure at an upstream location to direct the fluid from the upstream location to flow to a downstream location. In some instances, the fluid flow unit may comprise a pump to provide negative pressure at a downstream location to direct the fluid from an upstream location to flow to the downstream location. In some instances, the fluid flow unit may comprise both a compressor and a pump, each at different locations. In some instances, the fluid flow unit may comprise different devices at different locations. The fluid flow unit may comprise an actuator.

[00358] The systems and methods described with respect to **FIG. 11** may be used to separate occupied particles (e.g., cell beads) from unoccupied particles. As described elsewhere herein, a plurality of particles may comprise a first subset of particles occupied by biological particles (e.g., cells) and a second subset of particles unoccupied by biological particles. As described above, a given unoccupied particle can have a higher deformability and/or lower surface tension property than a given occupied particle (e.g., cell bead) due to the presence of one or more biological particles in the occupied particle. In a channel structure including channel segment **1100** with an entrance **1102** and exit **1104**, and comprising the plurality of entrapment structures **1114**, the plurality of particles may be directed to flow (e.g., as suspensions in a fluid, e.g.,

aqueous fluid) along the channel segment **1100** from entrance **1102** to exit **1104** across the plurality of entrapment structures **1114**.

[00359] An entrapment structure can define an aperture. A size of the aperture may be less than a diameter (or other size dimension) of a particle. A size of the aperture may be less than a minimum dimension of a particle. In some instances, the size of the aperture can be at most about 90%, 80%, 70%, 60%, 50%, 45%, 40%, 35%, 30%, 25%, 20%, 15%, 10%, or 5% of the diameter of a particle (in a pre-deformed state). The size of the aperture can be less than about 5% of the diameter of a particle. Alternatively, the size of the aperture can be greater than 50%, 60%, 70%, 80%, 90%, 100%, 150%, or 200% of the diameter of a particle. The size of the aperture can be greater than the diameter of the particle. When a plurality of particles comprising both a first subset of occupied particles **1108** and a second subset of unoccupied particles **1110** is directed to pass through entrapment structures **1114** defining apertures which is smaller in size than a diameter of a given particle in the plurality of particles, only those particles deforming **1118** (e.g., unoccupied particles **1110** having higher deformability properties) such that at least one dimension of the particle is less than a size of the aperture may pass through one or more apertures defined by the entrapment structures **1114**. Because occupied particles **1108** (e.g., cell beads) may be harder or stiffer, due to a presence of one or more biological particles in the particles, the occupied particles may resist deformation, at least from deforming to a size smaller than a size of the aperture, and remain trapped by the entrapment structures **1114**.

[00360] In some embodiments, there may exist more entrapment structures **1114** (and thus more apertures) in the channel structure than there are particles **1106**, **1108** passing through the channel structure. Beneficially, when the occupied particles **1108** are prevented from flowing through the entrapment structures **1114**, and the occupied particles **1108** clog (or block) some apertures of the entrapment structures **1114**, the unoccupied particles **1110** may still deform and flow through other apertures. After sorting, the entrapment structures **1114** may retain from the plurality of particles only the first subset of occupied particles **1108**. The unoccupied particles **1104** may flow through all entrapment structures **1114** and exit the channel segment **1100** to a separate compartment, such as for recycling or discarding.

[00361] The separation systems and methods disclosed herein (such as with reference to **FIG. 11**) may achieve super Poisson loading. For example, the droplets can be separated into two subsets such that at least about 5%, 10%, 15%, 20%, 25%, 30%, 40%, 50%, 60%, 70%, 80%, 90%, 95%, 96%, 97%, 98%, 99%, or greater of a first subset of droplets that is isolated are occupied droplets (e.g., containing at least one biological particle). Such occupancy may be greater than or equal to 1%, 2%, 3%, 4%, 5%, 10%, 20%, 30%, 40%, 50%, 60%, 70%, 80%, 90%, 95%, or higher. Alternatively, less than about 97% of the first subset of droplets can be

occupied droplets. In some instances, at least about 97%, 98%, 99%, or a higher percentage of a second subset of droplets that is isolated can be unoccupied droplets (e.g., not containing any biological particle and not containing any barcode carrying beads). Alternatively, less than about 97% of the second subset of droplets can be unoccupied droplets. For example, the plurality of particles can be separated into two subsets such that at least about 5%, 10%, 15%, 20%, 25%, 30%, 40%, 50%, 60%, 70%, 80%, 90%, 95%, 96%, 97%, 98%, 99%, or greater of a first subset of particles that is isolated are cell beads (e.g., containing at least one biological particle). Such occupancy may be greater than or equal to 1%, 2%, 3%, 4%, 5%, 10%, 20%, 30%, 40%, 50%, 60%, 70%, 80%, 90%, 95%, or higher. Alternatively, less than about 97% of the first subset of particles can be cell beads. In some instances, at least about 97%, 98%, 99%, or a higher percentage of a second subset of particles that is isolated can be unoccupied particles (e.g., not containing any biological particle and not containing any barcode carrying beads). Alternatively, less than about 97% of the second subset of particles can be unoccupied particles.

Microfluidic architectures

[00362] In an aspect, provided herein are various microfluidic architectures that can be used in conjunction with the systems and methods described herein.

[00363] In accordance with certain aspects, beads may be delivered to droplets. **FIG. 12** shows an example of a microfluidic channel structure **1200** for delivering barcode carrying beads to droplets. An example of a barcode carrying bead is described with respect to **FIG. 19**. The channel structure **1200** can include channel segments **1201**, **1202**, **1204**, **1206** and **1208** communicating at a channel junction **1210**. In operation, the channel segment **1201** may transport an aqueous fluid **1212** that includes a plurality of beads **1214** (e.g., with nucleic acid molecules, oligonucleotides, molecular tags) along the channel segment **1201** into junction **1210**. The plurality of beads **1214** may be sourced from a suspension of beads. For example, the channel segment **1201** may be connected to a reservoir comprising an aqueous suspension of beads **1214**. The channel segment **1202** may transport the aqueous fluid **1212** that includes a plurality of biological particles **1216** along the channel segment **1202** into junction **1210**. The plurality of biological particles **1216** may be sourced from a suspension of biological particles. For example, the channel segment **1202** may be connected to a reservoir comprising an aqueous suspension of biological particles **1216**. In some instances, the aqueous fluid **1212** in either the first channel segment **1201** or the second channel segment **1202**, or in both segments, can include one or more reagents, as further described below. A second fluid **1218** that is immiscible with the aqueous fluid **1212** (e.g., oil) can be delivered to the junction **1210** from each of channel segments **1204** and **1206**. Upon meeting of the aqueous fluid **1212** from each of channel segments **1201** and **1202** and the second fluid **1218** from each of channel segments **1204** and

1206 at the channel junction **1210**, the aqueous fluid **1212** can be partitioned as discrete droplets **1220** in the second fluid **1218** and flow away from the junction **1210** along channel segment **1208**. The channel segment **1208** may deliver the discrete droplets to an outlet reservoir fluidly coupled to the channel segment **1208**, where they may be harvested.

[00364] As an alternative, the channel segments **1201** and **1202** may meet at another junction upstream of the junction **1210**. At such junction, beads and biological particles may form a mixture that is directed along another channel to the junction **1210** to yield droplets **1220**. The mixture may provide the beads and biological particles in an alternating fashion, such that, for example, a droplet comprises a single bead and a single biological particle.

[00365] Beads, biological particles and droplets may flow along channels at substantially regular flow profiles (e.g., at regular flow rates). Such regular flow profiles may permit a droplet to include a single bead and a single biological particle. Such regular flow profiles may permit the droplets to have an occupancy (e.g., droplets having beads and biological particles) greater than 5%, 10%, 20%, 30%, 40%, 50%, 60%, 70%, 80%, 90%, or 95%. Such regular flow profiles and devices that may be used to provide such regular flow profiles are provided in, for example, U.S. Patent Publication No. 12015/0292988, which is entirely incorporated herein by reference.

[00366] The second fluid **1218** can comprise an oil, such as a fluorinated oil, that includes a fluorosurfactant for stabilizing the resulting droplets, for example, inhibiting subsequent coalescence of the resulting droplets **1220**.

[00367] A discrete droplet that is generated may include an individual biological particle **1216**. A discrete droplet that is generated may include a barcode or other reagent carrying bead **1214**. A discrete droplet generated may include both an individual biological particle and a barcode carrying bead, such as droplets **1220**. In some instances, a discrete droplet may include more than one individual biological particle or no biological particle. In some instances, a discrete droplet may include more than one bead or no bead. A discrete droplet may be unoccupied (e.g., no beads, no biological particles).

[00368] Beneficially, a discrete droplet partitioning a biological particle and a barcode carrying bead may effectively allow the attribution of the barcode to macromolecular constituents of the biological particle within the partition. The contents of a partition may remain discrete from the contents of other partitions.

[00369] As will be appreciated, the channel segments described herein may be coupled to any of a variety of different fluid sources or receiving components, including reservoirs, tubing, manifolds, or fluidic components of other systems. As will be appreciated, the microfluidic channel structure **1200** may have other geometries. For example, a microfluidic channel structure can have more than one channel junctions. For example, a microfluidic channel

structure can have 2, 3, 4, or 5 channel segments each carrying beads that meet at a channel junction. Fluid may be directed flow along one or more channels or reservoirs via one or more fluid flow units. A fluid flow unit can comprise compressors (e.g., providing positive pressure), pumps (e.g., providing negative pressure), actuators, and the like to control flow of the fluid. Fluid may also or otherwise be controlled via applied pressure differentials, centrifugal force, electrokinetic pumping, vacuum, capillary or gravity flow, or the like.

[00370] In accordance with certain aspects, biological particles may be partitioned along with lysis reagents in order to release the contents of the biological particles within the partition. In such cases, the lysis agents can be contacted with the biological particle suspension concurrently with, or immediately prior to, the introduction of the biological particles into the partitioning junction/droplet generation zone, such as through an additional channel or channels upstream of the channel junction. In accordance with other aspects, additionally or alternatively, biological particles may be partitioned along with other reagents, as will be described further below.

[00371] **FIG. 13** shows an example of a microfluidic channel structure **1300** for co-partitioning biological particles and reagents. The channel structure **1300** can include channel segments **1301**, **1302**, **1304**, **1306** and **1308**. Channel segments **1301** and **1302** communicate at a first channel junction **1309**. Channel segments **1302**, **1304**, **1306**, and **1308** communicate at a second channel junction **1310**.

[00372] In an example operation, the channel segment **1301** may transport an aqueous fluid **1312** that includes a plurality of biological particles **1314** along the channel segment **1301** into the second junction **1310**. As an alternative or in addition to, channel segment **1301** may transport beads (e.g., gel beads). The beads may comprise barcode molecules.

[00373] For example, the channel segment **1301** may be connected to a reservoir comprising an aqueous suspension of biological particles **1314**. Upstream of, and immediately prior to reaching, the second junction **1310**, the channel segment **1301** may meet the channel segment **1302** at the first junction **1309**. The channel segment **1302** may transport a plurality of reagents **1315** (e.g., lysis agents) suspended in the aqueous fluid **1312** along the channel segment **1302** into the first junction **1309**. For example, the channel segment **1302** may be connected to a reservoir comprising the reagents **1315**. After the first junction **1309**, the aqueous fluid **1312** in the channel segment **1301** can carry both the biological particles **1314** and the reagents **1315** towards the second junction **1310**. In some instances, the aqueous fluid **1312** in the channel segment **1301** can include one or more reagents, which can be the same or different reagents as the reagents **1315**. A second fluid **1316** that is immiscible with the aqueous fluid **1312** (e.g., oil) can be delivered to the second junction **1310** from each of channel segments **1304** and **1306**. Upon meeting of the aqueous fluid **1312** from the channel segment **1301** and the second fluid

1316 from each of channel segments **1304** and **1306** at the second channel junction **1310**, the aqueous fluid **1312** can be partitioned as discrete droplets **1318** in the second fluid **1316** and flow away from the second junction **1310** along channel segment **1308**. The channel segment **1308** may deliver the discrete droplets **1318** to an outlet reservoir fluidly coupled to the channel segment **1308**, where they may be harvested.

[00374] The second fluid **1316** can comprise an oil, such as a fluorinated oil, that includes a fluorosurfactant for stabilizing the resulting droplets, for example, inhibiting subsequent coalescence of the resulting droplets **1318**.

[00375] A discrete droplet generated may include an individual biological particle **1314** and/or one or more reagents **1315**. In some instances, a discrete droplet generated may include a barcode carrying bead (not shown), such as via other microfluidics structures described elsewhere herein. In some instances, a discrete droplet may be unoccupied (e.g., no reagents, no biological particles).

[00376] Beneficially, when lysis reagents and biological particles are co-partitioned, the lysis reagents can facilitate the release of the contents of the biological particles within the partition. The contents released in a partition may remain discrete from the contents of other partitions.

[00377] As will be appreciated, the channel segments described herein may be coupled to any of a variety of different fluid sources or receiving components, including reservoirs, tubing, manifolds, or fluidic components of other systems. As will be appreciated, the microfluidic channel structure **1300** may have other geometries. For example, a microfluidic channel structure can have more than two channel junctions. For example, a microfluidic channel structure can have 2, 3, 4, 5 channel segments or more each carrying the same or different types of beads, reagents, and/or biological particles that meet at a channel junction. Fluid flow in each channel segment may be controlled to control the partitioning of the different elements into droplets. Fluid may be directed flow along one or more channels or reservoirs via one or more fluid flow units. A fluid flow unit can comprise compressors (e.g., providing positive pressure), pumps (e.g., providing negative pressure), actuators, and the like to control flow of the fluid. Fluid may also or otherwise be controlled via applied pressure differentials, centrifugal force, electrokinetic pumping, vacuum, capillary or gravity flow, or the like.

[00378] In some aspects, provided are systems and methods for controlled partitioning. Droplet size may be controlled by adjusting certain geometric features in channel architecture (e.g., microfluidics channel architecture). For example, an expansion angle, width, and/or length of a channel may be adjusted to control droplet size.

[00379] **FIG. 14** shows an example of a microfluidic channel structure for the controlled partitioning of beads into discrete droplets. A channel structure **1400** can include a channel

segment **1402** communicating at a channel junction **1406** (or intersection) with a reservoir **1404**. The reservoir **1404** can be a chamber. Any reference to “reservoir,” as used herein, can also refer to a “chamber.” In operation, an aqueous fluid **1408** that includes suspended beads **1412** may be transported along the channel segment **1402** into the junction **1406** to meet a second fluid **1410** that is immiscible with the aqueous fluid **1408** in the reservoir **1404** to create droplets **1416**, **1418** of the aqueous fluid **1408** flowing into the reservoir **1404**. At the junction **1406** where the aqueous fluid **1408** and the second fluid **1410** meet, droplets can form based on factors such as the hydrodynamic forces at the junction **1406**, flow rates of the two fluids **1408**, **1410**, fluid properties, and certain geometric parameters (e.g., w , h_0 , α , etc.) of the channel structure **1400**. A plurality of droplets can be collected in the reservoir **1404** by continuously injecting the aqueous fluid **1408** from the channel segment **1402** through the junction **1406**.

[00380] A discrete droplet generated may include a bead (e.g., as in occupied droplets **1416**). Alternatively, a discrete droplet generated may include more than one bead. Alternatively, a discrete droplet generated may not include any beads (e.g., as in unoccupied droplet **1418**). In some instances, a discrete droplet generated may contain one or more biological particles, as described elsewhere herein. In some instances, a discrete droplet generated may comprise one or more reagents, as described elsewhere herein.

[00381] In some instances, the aqueous fluid **1408** can have a substantially uniform concentration or frequency of beads **1412**. The beads **1412** can be introduced into the channel segment **1402** from a separate channel (not shown in **FIG. 14**). The frequency of beads **1412** in the channel segment **1402** may be controlled by controlling the frequency in which the beads **1412** are introduced into the channel segment **1402** and/or the relative flow rates of the fluids in the channel segment **1402** and the separate channel. In some instances, the beads can be introduced into the channel segment **1402** from a plurality of different channels, and the frequency controlled accordingly.

[00382] In some instances, the aqueous fluid **1408** in the channel segment **1402** can comprise biological particles. In some instances, the aqueous fluid **1408** can have a substantially uniform concentration or frequency of biological particles. As with the beads, the biological particles can be introduced into the channel segment **1402** from a separate channel. The frequency or concentration of the biological particles in the aqueous fluid **1408** in the channel segment **1402** may be controlled by controlling the frequency in which the biological particles are introduced into the channel segment **1402** and/or the relative flow rates of the fluids in the channel segment **1402** and the separate channel. In some instances, the biological particles can be introduced into the channel segment **1402** from a plurality of different channels, and the frequency controlled accordingly. In some instances, a first separate channel can introduce beads and a second

separate channel can introduce biological particles into the channel segment **1402**. The first separate channel introducing the beads may be upstream or downstream of the second separate channel introducing the biological particles.

[00383] The second fluid **1410** can comprise an oil, such as a fluorinated oil, that includes a fluorosurfactant for stabilizing the resulting droplets, for example, inhibiting subsequent coalescence of the resulting droplets.

[00384] In some instances, the second fluid **1410** may not be subjected to and/or directed to any flow in or out of the reservoir **1404**. For example, the second fluid **1410** may be substantially stationary in the reservoir **1404**. In some instances, the second fluid **1410** may be subjected to flow within the reservoir **1404**, but not in or out of the reservoir **1404**, such as via application of pressure to the reservoir **1404** and/or as affected by the incoming flow of the aqueous fluid **1408** at the junction **1406**. Alternatively, the second fluid **1410** may be subjected and/or directed to flow in or out of the reservoir **1404**. For example, the reservoir **1404** can be a channel directing the second fluid **1410** from upstream to downstream, transporting the generated droplets.

[00385] The channel structure **1400** at or near the junction **1406** may have certain geometric features that at least partly determine the sizes of the droplets formed by the channel structure **1400**. The channel segment **1402** can have a height, h_0 and width, w , at or near the junction **1406**. By way of example, the channel segment **1402** can comprise a rectangular cross-section that leads to a reservoir **1404** having a wider cross-section (such as in width or diameter). Alternatively, the cross-section of the channel segment **1402** can be other shapes, such as a circular shape, trapezoidal shape, polygonal shape, or any other shapes. The top and bottom walls of the reservoir **1404** at or near the junction **1406** can be inclined at an expansion angle, α . The expansion angle, α , allows the tongue (portion of the aqueous fluid **1408** leaving channel segment **1402** at junction **1406** and entering the reservoir **1404** before droplet formation) to increase in depth and facilitate decrease in curvature of the intermediately formed droplet. Droplet size may decrease with increasing expansion angle. The resulting droplet radius, R_d , may be predicted by the following equation for the aforementioned geometric parameters of h_0 , w , and α :

$$R_d \approx 0.44 \left(1 + 2.2 \sqrt{\tan \alpha} \frac{w}{h_0} \right) \frac{h_0}{\sqrt{\tan \alpha}}$$

[00386] By way of example, for a channel structure with $w = 21 \mu\text{m}$, $h = 21 \mu\text{m}$, and $\alpha = 3^\circ$, the predicted droplet size is $121 \mu\text{m}$. In another example, for a channel structure with $w = 25 \mu\text{m}$, $h = 25 \mu\text{m}$, and $\alpha = 5^\circ$, the predicted droplet size is $123 \mu\text{m}$. In another example, for a channel structure with $w = 28 \mu\text{m}$, $h = 28 \mu\text{m}$, and $\alpha = 7^\circ$, the predicted droplet size is $124 \mu\text{m}$.

[00387] In some instances, the expansion angle, α , may be between a range of from about 0.5° to about 4°, from about 0.1° to about 10°, or from about 0° to about 90°. For example, the expansion angle can be at least about 0.01°, 0.1°, 0.2°, 0.3°, 0.4°, 0.5°, 0.6°, 0.7°, 0.8°, 0.9°, 1°, 2°, 3°, 4°, 5°, 6°, 7°, 8°, 9°, 10°, 15°, 20°, 25°, 30°, 35°, 40°, 45°, 50°, 55°, 60°, 65°, 70°, 75°, 80°, 85°, or higher. In some instances, the expansion angle can be at most about 89°, 88°, 87°, 86°, 85°, 84°, 83°, 82°, 81°, 80°, 75°, 70°, 65°, 60°, 55°, 50°, 45°, 40°, 35°, 30°, 25°, 20°, 15°, 10°, 9°, 8°, 7°, 6°, 5°, 4°, 3°, 2°, 1°, 0.1°, 0.01°, or less. In some instances, the width, w , can be between a range of from about 100 micrometers (μm) to about 500 μm . In some instances, the width, w , can be between a range of from about 10 μm to about 200 μm . Alternatively, the width can be less than about 10 μm . Alternatively, the width can be greater than about 500 μm . In some instances, the flow rate of the aqueous fluid **1408** entering the junction **1406** can be between about 0.04 microliters (μL)/minute (min) and about 40 $\mu\text{L}/\text{min}$. In some instances, the flow rate of the aqueous fluid **1408** entering the junction **1406** can be between about 0.01 microliters (μL)/minute (min) and about 100 $\mu\text{L}/\text{min}$. Alternatively, the flow rate of the aqueous fluid **1408** entering the junction **1406** can be less than about 0.01 $\mu\text{L}/\text{min}$. Alternatively, the flow rate of the aqueous fluid **1408** entering the junction **1406** can be greater than about 40 $\mu\text{L}/\text{min}$, such as 45 $\mu\text{L}/\text{min}$, 50 $\mu\text{L}/\text{min}$, 55 $\mu\text{L}/\text{min}$, 60 $\mu\text{L}/\text{min}$, 65 $\mu\text{L}/\text{min}$, 70 $\mu\text{L}/\text{min}$, 75 $\mu\text{L}/\text{min}$, 80 $\mu\text{L}/\text{min}$, 85 $\mu\text{L}/\text{min}$, 90 $\mu\text{L}/\text{min}$, 95 $\mu\text{L}/\text{min}$, 100 $\mu\text{L}/\text{min}$, 110 $\mu\text{L}/\text{min}$, 120 $\mu\text{L}/\text{min}$, 130 $\mu\text{L}/\text{min}$, 140 $\mu\text{L}/\text{min}$, 150 $\mu\text{L}/\text{min}$, or greater. At lower flow rates, such as flow rates of about less than or equal to 10 microliters/minute, the droplet radius may not be dependent on the flow rate of the aqueous fluid **1408** entering the junction **1406**.

[00388] In some instances, at least about 50% of the droplets generated can have uniform size. In some instances, at least about 55%, 60%, 65%, 70%, 75%, 80%, 85%, 90%, 95%, 96%, 97%, 98%, 99%, or greater of the droplets generated can have uniform size. Alternatively, less than about 50% of the droplets generated can have uniform size.

[00389] The throughput of droplet generation can be increased by increasing the points of generation, such as increasing the number of junctions (e.g., junction **1406**) between aqueous fluid **1408** channel segments (e.g., channel segment **1402**) and the reservoir **1404**. Alternatively or in addition, the throughput of droplet generation can be increased by increasing the flow rate of the aqueous fluid **1408** in the channel segment **1402**.

[00390] **FIG. 15** shows an example of a microfluidic channel structure for increased droplet generation throughput. A microfluidic channel structure **1500** can comprise a plurality of channel segments **1502** and a reservoir **1504**. Each of the plurality of channel segments **1502** may be in fluid communication with the reservoir **1504**. The channel structure **1500** can comprise a plurality of channel junctions **1506** between the plurality of channel segments **1502**

and the reservoir **1504**. Each channel junction can be a point of droplet generation. The channel segment **1402** from the channel structure **1400** in **FIG. 14** and any description to the components thereof may correspond to a given channel segment of the plurality of channel segments **1502** in channel structure **1500** and any description to the corresponding components thereof. The reservoir **1404** from the channel structure **1400** and any description to the components thereof may correspond to the reservoir **1504** from the channel structure **1500** and any description to the corresponding components thereof.

[00391] Each channel segment of the plurality of channel segments **1502** may comprise an aqueous fluid **1508** that includes suspended beads **1512**. The reservoir **1504** may comprise a second fluid **1510** that is immiscible with the aqueous fluid **1508**. In some instances, the second fluid **1510** may not be subjected to and/or directed to any flow in or out of the reservoir **1504**. For example, the second fluid **1510** may be substantially stationary in the reservoir **1504**. In some instances, the second fluid **1510** may be subjected to flow within the reservoir **1504**, but not in or out of the reservoir **1504**, such as via application of pressure to the reservoir **1504** and/or as affected by the incoming flow of the aqueous fluid **1508** at the junctions. Alternatively, the second fluid **1510** may be subjected and/or directed to flow in or out of the reservoir **1504**. For example, the reservoir **1504** can be a channel directing the second fluid **1510** from upstream to downstream, transporting the generated droplets.

[00392] In operation, the aqueous fluid **1508** that includes suspended beads **1512** may be transported along the plurality of channel segments **1502** into the plurality of junctions **1506** to meet the second fluid **1510** in the reservoir **1504** to create droplets **1516**, **1518**. A droplet may form from each channel segment at each corresponding junction with the reservoir **1504**. At the junction where the aqueous fluid **1508** and the second fluid **1510** meet, droplets can form based on factors such as the hydrodynamic forces at the junction, flow rates of the two fluids **1508**, **1510**, fluid properties, and certain geometric parameters (e.g., w , h_0 , α , etc.) of the channel structure **1500**, as described elsewhere herein. A plurality of droplets can be collected in the reservoir **1504** by continuously injecting the aqueous fluid **1508** from the plurality of channel segments **1502** through the plurality of junctions **1506**. Throughput may significantly increase with the parallel channel configuration of channel structure **1500**. For example, a channel structure having five inlet channel segments comprising the aqueous fluid **1508** may generate droplets five times as frequently than a channel structure having one inlet channel segment, provided that the fluid flow rate in the channel segments are substantially the same. The fluid flow rate in the different inlet channel segments may or may not be substantially the same. A channel structure may have as many parallel channel segments as is practical and allowed for the size of the reservoir. For example, the channel structure may have at least about 2, 3, 4, 5, 6, 7,

8, 9, 10, 20, 30, 40, 50, 60, 70, 80, 90, 100, 150, 200, 250, 300, 350, 400, 450, 500, 600, 700, 800, 900, 1000, 1500, 5000 or more parallel or substantially parallel channel segments.

[00393] The geometric parameters, w , h_0 , and α , may or may not be uniform for each of the channel segments in the plurality of channel segments **1502**. For example, each channel segment may have the same or different widths at or near its respective channel junction with the reservoir **1504**. For example, each channel segment may have the same or different height at or near its respective channel junction with the reservoir **1504**. In another example, the reservoir **1504** may have the same or different expansion angle at the different channel junctions with the plurality of channel segments **1502**. When the geometric parameters are uniform, beneficially, droplet size may also be controlled to be uniform even with the increased throughput. In some instances, when it is desirable to have a different distribution of droplet sizes, the geometric parameters for the plurality of channel segments **1502** may be varied accordingly.

[00394] In some instances, at least about 50% of the droplets generated can have uniform size. In some instances, at least about 55%, 60%, 65%, 70%, 75%, 80%, 85%, 90%, 95%, 96%, 97%, 98%, 99%, or greater of the droplets generated can have uniform size. Alternatively, less than about 50% of the droplets generated can have uniform size.

[00395] **FIG. 16** shows another example of a microfluidic channel structure for increased droplet generation throughput. A microfluidic channel structure **1600** can comprise a plurality of channel segments **1602** arranged generally circularly around the perimeter of a reservoir **1604**. Each of the plurality of channel segments **1602** may be in fluid communication with the reservoir **1604**. The channel structure **1600** can comprise a plurality of channel junctions **1606** between the plurality of channel segments **1602** and the reservoir **1604**. Each channel junction can be a point of droplet generation. The channel segment **1402** from the channel structure **1400** in **FIG. 14** and any description to the components thereof may correspond to a given channel segment of the plurality of channel segments **1602** in channel structure **1600** and any description to the corresponding components thereof. The reservoir **1404** from the channel structure **1400** and any description to the components thereof may correspond to the reservoir **1604** from the channel structure **1600** and any description to the corresponding components thereof.

[00396] Each channel segment of the plurality of channel segments **1602** may comprise an aqueous fluid **1608** that includes suspended beads **1612**. The reservoir **1604** may comprise a second fluid **1610** that is immiscible with the aqueous fluid **1608**. In some instances, the second fluid **1610** may not be subjected to and/or directed to any flow in or out of the reservoir **1604**. For example, the second fluid **1610** may be substantially stationary in the reservoir **1604**. In some instances, the second fluid **1610** may be subjected to flow within the reservoir **1604**, but not in or out of the reservoir **1604**, such as via application of pressure to the reservoir **1604**.

and/or as affected by the incoming flow of the aqueous fluid **1608** at the junctions.

Alternatively, the second fluid **1610** may be subjected and/or directed to flow in or out of the reservoir **1604**. For example, the reservoir **1604** can be a channel directing the second fluid **1610** from upstream to downstream, transporting the generated droplets.

[00397] In operation, the aqueous fluid **1608** that includes suspended beads **1612** may be transported along the plurality of channel segments **1602** into the plurality of junctions **1606** to meet the second fluid **1610** in the reservoir **1604** to create a plurality of droplets **1616**. A droplet may form from each channel segment at each corresponding junction with the reservoir **1604**. At the junction where the aqueous fluid **1608** and the second fluid **1610** meet, droplets can form based on factors such as the hydrodynamic forces at the junction, flow rates of the two fluids **1608**, **1610**, fluid properties, and certain geometric parameters (e.g., widths and heights of the channel segments **1602**, expansion angle of the reservoir **1604**, etc.) of the channel structure **1600**, as described elsewhere herein. A plurality of droplets can be collected in the reservoir **1604** by continuously injecting the aqueous fluid **1608** from the plurality of channel segments **1602** through the plurality of junctions **1606**. Throughput may significantly increase with the substantially parallel channel configuration of the channel structure **1600**. A channel structure may have as many substantially parallel channel segments as is practical and allowed for by the size of the reservoir. For example, the channel structure may have at least about 2, 3, 4, 5, 6, 7, 8, 9, 10, 20, 30, 40, 50, 60, 70, 80, 90, 100, 150, 200, 250, 300, 350, 400, 450, 500, 600, 700, 800, 900, 1000, 1500, 5000 or more parallel or substantially parallel channel segments. The plurality of channel segments may be substantially evenly spaced apart, for example, around an edge or perimeter of the reservoir. Alternatively, the spacing of the plurality of channel segments may be uneven.

[00398] The reservoir **1604** may have an expansion angle, α (not shown in **FIG. 16**) at or near each channel junction. Each channel segment of the plurality of channel segments **1602** may have a width, w , and a height, h_0 , at or near the channel junction. The geometric parameters, w , h_0 , and α , may or may not be uniform for each of the channel segments in the plurality of channel segments **1602**. For example, each channel segment may have the same or different widths at or near its respective channel junction with the reservoir **1604**. For example, each channel segment may have the same or different height at or near its respective channel junction with the reservoir **1604**.

[00399] The reservoir **1604** may have the same or different expansion angle at the different channel junctions with the plurality of channel segments **1602**. For example, a circular reservoir (as shown in **FIG. 16**) may have a conical, dome-like, or hemispherical ceiling (e.g., top wall) to provide the same or substantially same expansion angle for each channel segments **1602** at or

near the plurality of channel junctions **1606**. When the geometric parameters are uniform, beneficially, resulting droplet size may be controlled to be uniform even with the increased throughput. In some instances, when it is desirable to have a different distribution of droplet sizes, the geometric parameters for the plurality of channel segments **1602** may be varied accordingly.

[00400] In some instances, at least about 50% of the droplets generated can have uniform size. In some instances, at least about 55%, 60%, 65%, 70%, 75%, 80%, 85%, 90%, 95%, 96%, 97%, 98%, 99%, or greater of the droplets generated can have uniform size. Alternatively, less than about 50% of the droplets generated can have uniform size. The beads and/or biological particle injected into the droplets may or may not have uniform size.

[00401] **FIG. 17A** shows a cross-section view of another example of a microfluidic channel structure with a geometric feature for controlled partitioning. A channel structure **1700** can include a channel segment **1702** communicating at a channel junction **1706** (or intersection) with a reservoir **1704**. In some instances, the channel structure **1700** and one or more of its components can correspond to any other channel structure described herein and one or more of its components. **FIG. 17B** shows a perspective view of the channel structure **1700** of **FIG. 17A**.

[00402] An aqueous fluid **1712** comprising a plurality of particles **1716** may be transported along the channel segment **1702** into the junction **1706** to meet a second fluid **1714** (e.g., oil, etc.) that is immiscible with the aqueous fluid **1712** in the reservoir **1704** to create droplets **720** of the aqueous fluid **1712** flowing into the reservoir **1704**. At the junction **1706** where the aqueous fluid **1712** and the second fluid **1714** meet, droplets can form based on factors such as the hydrodynamic forces at the junction **1706**, relative flow rates of the two fluids **1712**, **1714**, fluid properties, and certain geometric parameters (e.g., Δh , etc.) of the channel structure **1700**. A plurality of droplets can be collected in the reservoir **1704** by continuously injecting the aqueous fluid **1712** from the channel segment **1702** at the junction **1706**.

[00403] A discrete droplet generated may comprise one or more particles of the plurality of particles **1716**. As described elsewhere herein, a particle may be any particle, such as a bead, cell bead, gel bead, biological particle, macromolecular constituents of biological particle, or other particles. Alternatively, a discrete droplet generated may not include any particles.

[00404] In some instances, the aqueous fluid **1712** can have a substantially uniform concentration or frequency of particles **1716**. As described elsewhere herein (e.g., with reference to **FIG. 14**), the particles **1716** (e.g., beads) can be introduced into the channel segment **1702** from a separate channel (not shown in **FIG. 17**). The frequency of particles **1716** in the channel segment **1702** may be controlled by controlling the frequency in which the particles **1716** are introduced into the channel segment **1702** and/or the relative flow rates of the fluids in the

channel segment **1702** and the separate channel. In some instances, the particles **1716** can be introduced into the channel segment **1702** from a plurality of different channels, and the frequency controlled accordingly. In some instances, different particles may be introduced via separate channels. For example, a first separate channel can introduce beads and a second separate channel can introduce biological particles into the channel segment **1702**. The first separate channel introducing the beads may be upstream or downstream of the second separate channel introducing the biological particles.

[00405] In some instances, the second fluid **1714** may not be subjected to and/or directed to any flow in or out of the reservoir **1704**. For example, the second fluid **1714** may be substantially stationary in the reservoir **1704**. In some instances, the second fluid **1714** may be subjected to flow within the reservoir **1704**, but not in or out of the reservoir **1704**, such as via application of pressure to the reservoir **1704** and/or as affected by the incoming flow of the aqueous fluid **1712** at the junction **1706**. Alternatively, the second fluid **1714** may be subjected and/or directed to flow in or out of the reservoir **1704**. For example, the reservoir **1704** can be a channel directing the second fluid **1714** from upstream to downstream, transporting the generated droplets.

[00406] The channel structure **1700** at or near the junction **1706** may have certain geometric features that at least partly determine the sizes and/or shapes of the droplets formed by the channel structure **1700**. The channel segment **1702** can have a first cross-section height, h_1 , and the reservoir **1704** can have a second cross-section height, h_2 . The first cross-section height, h_1 , and the second cross-section height, h_2 , may be different, such that at the junction **1706**, there is a height difference of Δh . The second cross-section height, h_2 , may be greater than the first cross-section height, h_1 . In some instances, the reservoir may thereafter gradually increase in cross-section height, for example, the more distant it is from the junction **1706**. In some instances, the cross-section height of the reservoir may increase in accordance with expansion angle, β , at or near the junction **1706**. The height difference, Δh , and/or expansion angle, β , can allow the tongue (portion of the aqueous fluid **1712** leaving channel segment **1702** at junction **1706** and entering the reservoir **1704** before droplet formation) to increase in depth and facilitate decrease in curvature of the intermediately formed droplet. For example, droplet size may decrease with increasing height difference and/or increasing expansion angle.

[00407] The height difference, Δh , can be at least about 1 μm . Alternatively, the height difference can be at least about 1, 2, 3, 4, 5, 6, 7, 8, 9, 10, 11, 12, 13, 14, 15, 16, 17, 18, 19, 20, 25, 30, 35, 40, 45, 50, 60, 70, 80, 90, 100, 200, 300, 400, 500 μm or more. Alternatively, the height difference can be at most about 500, 400, 300, 200, 100, 90, 80, 70, 60, 50, 45, 40, 35, 30, 25, 20, 19, 18, 17, 16, 15, 14, 13, 12, 11, 10, 9, 8, 7, 6, 5, 4, 3, 2, 1 μm or less. In some

instances, the expansion angle, β , may be between a range of from about 0.5° to about 4° , from about 0.1° to about 10° , or from about 0° to about 90° . For example, the expansion angle can be at least about 0.01° , 0.1° , 0.2° , 0.3° , 0.4° , 0.5° , 0.6° , 0.7° , 0.8° , 0.9° , 1° , 2° , 3° , 4° , 5° , 6° , 7° , 8° , 9° , 10° , 15° , 20° , 25° , 30° , 35° , 40° , 45° , 50° , 55° , 60° , 65° , 70° , 75° , 80° , 85° , or higher. In some instances, the expansion angle can be at most about 89° , 88° , 87° , 86° , 85° , 84° , 83° , 82° , 81° , 80° , 75° , 70° , 65° , 60° , 55° , 50° , 45° , 40° , 35° , 30° , 25° , 20° , 15° , 10° , 9° , 8° , 7° , 6° , 5° , 4° , 3° , 2° , 1° , 0.1° , 0.01° , or less.

[00408] In some instances, the flow rate of the aqueous fluid **1712** entering the junction **1706** can be between about 0.04 microliters (μL)/minute (min) and about 40 $\mu\text{L}/\text{min}$. In some instances, the flow rate of the aqueous fluid **1712** entering the junction **1706** can be between about 0.01 microliters (μL)/minute (min) and about 100 $\mu\text{L}/\text{min}$. Alternatively, the flow rate of the aqueous fluid **1712** entering the junction **1706** can be less than about 0.01 $\mu\text{L}/\text{min}$. Alternatively, the flow rate of the aqueous fluid **1712** entering the junction **1706** can be greater than about 40 $\mu\text{L}/\text{min}$, such as 45 $\mu\text{L}/\text{min}$, 50 $\mu\text{L}/\text{min}$, 55 $\mu\text{L}/\text{min}$, 60 $\mu\text{L}/\text{min}$, 65 $\mu\text{L}/\text{min}$, 70 $\mu\text{L}/\text{min}$, 75 $\mu\text{L}/\text{min}$, 80 $\mu\text{L}/\text{min}$, 85 $\mu\text{L}/\text{min}$, 90 $\mu\text{L}/\text{min}$, 95 $\mu\text{L}/\text{min}$, 100 $\mu\text{L}/\text{min}$, 110 $\mu\text{L}/\text{min}$, 120 $\mu\text{L}/\text{min}$, 130 $\mu\text{L}/\text{min}$, 140 $\mu\text{L}/\text{min}$, 150 $\mu\text{L}/\text{min}$, or greater. At lower flow rates, such as flow rates of about less than or equal to 10 microliters/minute, the droplet radius may not be dependent on the flow rate of the aqueous fluid **1712** entering the junction **1706**. The second fluid **1714** may be stationary, or substantially stationary, in the reservoir **1704**. Alternatively, the second fluid **1714** may be flowing, such as at the above flow rates described for the aqueous fluid **1712**.

[00409] In some instances, at least about 50% of the droplets generated can have uniform size. In some instances, at least about 55%, 60%, 65%, 70%, 75%, 80%, 85%, 90%, 95%, 96%, 97%, 98%, 99%, or greater of the droplets generated can have uniform size. Alternatively, less than about 50% of the droplets generated can have uniform size.

[00410] While **FIGs. 7A** and **7B** illustrate the height difference, Δh , being abrupt at the junction **1706** (e.g., a step increase), the height difference may increase gradually (e.g., from about 0 μm to a maximum height difference). Alternatively, the height difference may decrease gradually (e.g., taper) from a maximum height difference. A gradual increase or decrease in height difference, as used herein, may refer to a continuous incremental increase or decrease in height difference, wherein an angle between any one differential segment of a height profile and an immediately adjacent differential segment of the height profile is greater than 90° . For example, at the junction **1706**, a bottom wall of the channel and a bottom wall of the reservoir can meet at an angle greater than 90° . Alternatively or in addition, a top wall (e.g., ceiling) of the channel and a top wall (e.g., ceiling) of the reservoir can meet an angle greater than 90° . A

gradual increase or decrease may be linear or non-linear (e.g., exponential, sinusoidal, etc.). Alternatively or in addition, the height difference may variably increase and/or decrease linearly or non-linearly. While **FIGs. 7A** and **7B** illustrate the expanding reservoir cross-section height as linear (e.g., constant expansion angle, β), the cross-section height may expand non-linearly. For example, the reservoir may be defined at least partially by a dome-like (e.g., hemispherical) shape having variable expansion angles. The cross-section height may expand in any shape.

[00411] The channel networks, e.g., as described above or elsewhere herein, can be fluidly coupled to appropriate fluidic components. For example, the inlet channel segments are fluidly coupled to appropriate sources of the materials they are to deliver to a channel junction. These sources may include any of a variety of different fluidic components, from simple reservoirs defined in or connected to a body structure of a microfluidic device, to fluid conduits that deliver fluids from off-device sources, manifolds, fluid flow units (e.g., actuators, pumps, compressors) or the like. Likewise, the outlet channel segment (e.g., channel segment **1208**, reservoir **1604**, etc.) may be fluidly coupled to a receiving vessel or conduit for the partitioned cells for subsequent processing. Again, this may be a reservoir defined in the body of a microfluidic device, or it may be a fluidic conduit for delivering the partitioned cells to a subsequent process operation, instrument or component.

[00412] The methods and systems described herein may be used to greatly increase the efficiency of single cell applications and/or other applications receiving droplet-based input. For example, following the sorting of occupied cells and/or appropriately-sized cells, subsequent operations that can be performed can include generation of amplification products, purification (e.g., via solid phase reversible immobilization (SPRI)), further processing (e.g., shearing, ligation of functional sequences, and subsequent amplification (e.g., via PCR)). These operations may occur in bulk (e.g., outside the partition). In the case where a partition is a droplet in an emulsion, the emulsion can be broken and the contents of the droplet pooled for additional operations. Additional reagents that may be co-partitioned along with the barcode bearing bead may include oligonucleotides to block ribosomal RNA (rRNA) and nucleases to digest genomic DNA from cells. Alternatively, rRNA removal agents may be applied during additional processing operations. The configuration of the constructs generated by such a method can help minimize (or avoid) sequencing of the poly-T sequence during sequencing and/or sequence the 5' end of a polynucleotide sequence. The amplification products, for example, first amplification products and/or second amplification products, may be subject to sequencing for sequence analysis. In some cases, amplification may be performed using the Partial Hairpin Amplification for Sequencing (PHASE) method.

[00413] A variety of applications require the evaluation of the presence and quantification of different biological particle or organism types within a population of biological particles, including, for example, microbiome analysis and characterization, environmental testing, food safety testing, epidemiological analysis, e.g., in tracing contamination or the like.

Computer control systems

[00414] The present disclosure provides computer control systems that are programmed to implement methods of the disclosure. **FIG. 18** shows a computer system **1801** that is programmed or otherwise configured to (i) sort occupied droplets from unoccupied droplets by including field-attractable particles in each droplet and applying a force field, (ii) sort occupied droplets from unoccupied droplets by applying a pressure pulse, (iii) sort occupied particles (e.g., cell beads) from unoccupied particles using field-attractable particles by applying a force field, (iv) sort occupied particles (e.g., cell beads) from unoccupied particles by applying a pressure pulse, (v) selectively polymerize occupied droplets, and/or (vi) selectively polymerize appropriately sized droplets. The computer system **1801** can regulate various aspects of the present disclosure, such as, for example, the timed exposure of the single biological particle to a variety of chemical or biological operations, regulating fluid flow rate in one or more channels in a microfluidic structure, regulating field strength applied by one or more field application units, regulating pressure pulses applied by one or more pressure application units, and/or regulating timing of polymerization application units. The computer system **1801** can be an electronic device of a user or a computer system that is remotely located with respect to the electronic device. The electronic device can be a mobile electronic device.

[00415] The computer system **1801** includes a central processing unit (CPU, also “processor” and “computer processor” herein) **1805**, which can be a single core or multi core processor, or a plurality of processors for parallel processing. The computer system **1801** also includes memory or memory location **1810** (e.g., random-access memory, read-only memory, flash memory), electronic storage unit **1815** (e.g., hard disk), communication interface **1820** (e.g., network adapter) for communicating with one or more other systems, and peripheral devices **1825**, such as cache, other memory, data storage and/or electronic display adapters. The memory **1810**, storage unit **1815**, interface **1820** and peripheral devices **1825** are in communication with the CPU **1805** through a communication bus (solid lines), such as a motherboard. The storage unit **1815** can be a data storage unit (or data repository) for storing data. The computer system **1801** can be operatively coupled to a computer network (“network”) **1830** with the aid of the communication interface **1820**. The network **1830** can be the Internet, an internet and/or extranet, or an intranet and/or extranet that is in communication with the Internet. The network **1830** in some cases is a telecommunication and/or data network. The network **1830** can include

one or more computer servers, which can enable distributed computing, such as cloud computing. The network **1830**, in some cases with the aid of the computer system **1801**, can implement a peer-to-peer network, which may enable devices coupled to the computer system **1801** to behave as a client or a server.

[00416] The CPU **1805** can execute a sequence of machine-readable instructions, which can be embodied in a program or software. The instructions may be stored in a memory location, such as the memory **1810**. The instructions can be directed to the CPU **1805**, which can subsequently program or otherwise configure the CPU **1805** to implement methods of the present disclosure. Examples of operations performed by the CPU **1805** can include fetch, decode, execute, and writeback.

[00417] The CPU **1805** can be part of a circuit, such as an integrated circuit. One or more other components of the system **1801** can be included in the circuit. In some cases, the circuit is an application specific integrated circuit (ASIC).

[00418] The storage unit **1815** can store files, such as drivers, libraries and saved programs. The storage unit **1815** can store user data, e.g., user preferences and user programs. The computer system **1801** in some cases can include one or more additional data storage units that are external to the computer system **1801**, such as located on a remote server that is in communication with the computer system **1801** through an intranet or the Internet.

[00419] The computer system **1801** can communicate with one or more remote computer systems through the network **1830**. For instance, the computer system **1801** can communicate with a remote computer system of a user (e.g., operator). Examples of remote computer systems include personal computers (e.g., portable PC), slate or tablet PC's (e.g., Apple® iPad, Samsung® Galaxy Tab), telephones, Smart phones (e.g., Apple® iPhone, Android-enabled device, Blackberry®), or personal digital assistants. The user can access the computer system **1801** via the network **1830**.

[00420] Methods as described herein can be implemented by way of machine (e.g., computer processor) executable code stored on an electronic storage location of the computer system **1801**, such as, for example, on the memory **1810** or electronic storage unit **1815**. The machine executable or machine readable code can be provided in the form of software. During use, the code can be executed by the processor **1805**. In some cases, the code can be retrieved from the storage unit **1815** and stored on the memory **1810** for ready access by the processor **1805**. In some situations, the electronic storage unit **1815** can be precluded, and machine-executable instructions are stored on memory **1810**.

[00421] The code can be pre-compiled and configured for use with a machine having a processor adapted to execute the code, or can be compiled during runtime. The code can be

supplied in a programming language that can be selected to enable the code to execute in a pre-compiled or as-compiled fashion.

[00422] Aspects of the systems and methods provided herein, such as the computer system **1801**, can be embodied in programming. Various aspects of the technology may be thought of as “products” or “articles of manufacture” typically in the form of machine (or processor) executable code and/or associated data that is carried on or embodied in a type of machine readable medium. Machine-executable code can be stored on an electronic storage unit, such as memory (e.g., read-only memory, random-access memory, flash memory) or a hard disk. “Storage” type media can include any or all of the tangible memory of the computers, processors or the like, or associated modules thereof, such as various semiconductor memories, tape drives, disk drives and the like, which may provide non-transitory storage at any time for the software programming. All or portions of the software may at times be communicated through the Internet or various other telecommunication networks. Such communications, for example, may enable loading of the software from one computer or processor into another, for example, from a management server or host computer into the computer platform of an application server. Thus, another type of media that may bear the software elements includes optical, electrical and electromagnetic waves, such as used across physical interfaces between local devices, through wired and optical landline networks and over various air-links. The physical elements that carry such waves, such as wired or wireless links, optical links or the like, also may be considered as media bearing the software. As used herein, unless restricted to non-transitory, tangible “storage” media, terms such as computer or machine “readable medium” refer to any medium that participates in providing instructions to a processor for execution.

[00423] Hence, a machine readable medium, such as computer-executable code, may take many forms, including but not limited to, a tangible storage medium, a carrier wave medium or physical transmission medium. Non-volatile storage media include, for example, optical or magnetic disks, such as any of the storage devices in any computer(s) or the like, such as may be used to implement the databases, etc. shown in the drawings. Volatile storage media include dynamic memory, such as main memory of such a computer platform. Tangible transmission media include coaxial cables; copper wire and fiber optics, including the wires that comprise a bus within a computer system. Carrier-wave transmission media may take the form of electric or electromagnetic signals, or acoustic or light waves such as those generated during radio frequency (RF) and infrared (IR) data communications. Common forms of computer-readable media therefore include for example: a floppy disk, a flexible disk, hard disk, magnetic tape, any other magnetic medium, a CD-ROM, DVD or DVD-ROM, any other optical medium, punch cards paper tape, any other physical storage medium with patterns of holes, a RAM, a ROM, a

PROM and EPROM, a FLASH-EPROM, any other memory chip or cartridge, a carrier wave transporting data or instructions, cables or links transporting such a carrier wave, or any other medium from which a computer may read programming code and/or data. Many of these forms of computer readable media may be involved in carrying one or more sequences of one or more instructions to a processor for execution.

[00424] The computer system **1801** can include or be in communication with an electronic display **1835** that comprises a user interface (UI) **1840** for providing, for example, fluid control options (e.g., fluid flow rate, timing of applying polymerization source (e.g., light), strength of magnetic or electric force field, strength and/or frequency of pressure pulses, etc.). Examples of UI's include, without limitation, a graphical user interface (GUI) and web-based user interface.

[00425] Methods and systems of the present disclosure can be implemented by way of one or more algorithms. An algorithm can be implemented by way of software upon execution by the central processing unit **1805**. The algorithm can, for example, (i) sort occupied droplets from unoccupied droplets by including field-attractable particles in each droplet and applying a force field, (ii) sort occupied droplets from unoccupied droplets by applying a pressure pulse, (iii) sort occupied particles (e.g., cell beads) from unoccupied particles using field-attractable particles by applying a force field, (iv) sort occupied particles (e.g., cell beads) from unoccupied particles by applying a pressure pulse, (v) selectively polymerize occupied droplets, and/or (vi) selectively polymerize appropriately sized droplets. The algorithm can also, for example, generate a plurality of droplets that may or may not contain biological particles (cells) and/or barcode carrying beads (particles).

[00426] While preferred embodiments of the present invention have been shown and described herein, it will be obvious to those skilled in the art that such embodiments are provided by way of example only. It is not intended that the invention be limited by the specific examples provided within the specification. While the invention has been described with reference to the aforementioned specification, the descriptions and illustrations of the embodiments herein are not meant to be construed in a limiting sense. Numerous variations, changes, and substitutions will now occur to those skilled in the art without departing from the invention. Furthermore, it shall be understood that all aspects of the invention are not limited to the specific depictions, configurations or relative proportions set forth herein which depend upon a variety of conditions and variables. It should be understood that various alternatives to the embodiments of the invention described herein may be employed in practicing the invention. It is therefore contemplated that the invention shall also cover any such alternatives, modifications, variations or equivalents. It is intended that the following claims define the scope of the invention and that methods and structures within the scope of these claims and their equivalents be covered thereby.

CLAIMS

WHAT IS CLAIMED IS:

1. A method for sorting droplets, comprising:
 - (a) bringing a first phase in contact with a second phase immiscible with said first phase, to generate a plurality of droplets, wherein said plurality of droplets comprises field attractable particles, and wherein said plurality of droplets comprises (i) a first subset of droplets each including, and not more than, one biological particle, and (ii) a second subset of droplets each having more than one biological particle, wherein said biological particle is a cell, a derivative of a cell, or a constituent of a cell, wherein each droplet of said first subset comprises more field attractable particles than each droplet of said second subset having more than one biological particle;
 - (b) directing said plurality of droplets along a first channel towards an intersection of said first channel with at least a second channel and a third channel; and
 - (c) subjecting said plurality of droplets to an electric or magnetic field under conditions sufficient to separate at least a portion of said first subset of said plurality of droplets from at least a portion of said second subset of said plurality of droplets, wherein upon separation, said at least said portion of said first subset of said plurality of droplets flows along said second channel and said at least said portion of said second subset of said plurality of droplets flows along said third channel.
2. The method of claim 1, wherein said first subset of said plurality of droplets includes particles having coupled thereto molecules comprising barcode sequences.
3. The method of claim 2, wherein said particles are gel beads.
4. The method of any one of claims 1-3, further comprising detecting individual droplets of said first subset of said plurality of droplets, and subjecting said individual droplets to a stimulus to facilitate polymerization in said biological particles upon detecting said individual droplets.
5. The method of claim 4 wherein:
 - (a) said stimulus is applied prior to said intersection;
 - (b) said stimulus is applied subsequent to said intersection; or
 - (c) said stimulus is an optical stimulus or chemical stimulus.
6. The method of any one of claims 1-5, wherein said biological particles are cells enclosed within or comprising a gel or polymer matrix.
7. The method of claim 6, wherein a concentration of said field-attractable particles in droplets of said second subset not having any biological particle is substantially uniform.

8. The method of any one of claims 1-7, wherein forces induced on said first subset are greater than forces induced on droplets of said second subset having more than one biological particle.
9. The method of any one of claims 1-8, wherein:
- (a) said field-attractable particles are magnetic-field attractable particles; and/or
 - (b) said conditions of said electric or magnetic field sufficient to separate said at least said portion of said first subset and said at least said portion of said second subset are determined based at least in part on a ratio between sizes of said plurality of droplets and sizes of said biological particles in said first subset of said plurality of droplets.
10. The method of any one of claims 1-9, further comprising, subsequent to (c), subjecting nucleic acid molecules derived from said biological particles in said first subset to nucleic acid sequencing.
11. The method of claim 10, further comprising, subsequent to (c), subjecting said first subset of said plurality of droplets to conditions sufficient to yield extension products of said nucleic acid molecules from said biological particles in said first subset, and subjecting said extension products or derivatives thereof to nucleic acid sequencing.