

CORRECTED VERSION

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
22 April 2004 (22.04.2004)

PCT

(10) International Publication Number
WO 2004/033103 A2

(51) International Patent Classification⁷: **B03C**

Charles, W. [US/US]; 408 East Minnehaha Parkway, Minneapolis, MN 55419 (US). **BUCHA, Robert** [US/US]; 6372 Smithtown Road, Excelsior, MN 55331 (US).

(21) International Application Number:
PCT/US2003/032197

(74) Agents: **CHRISTENSEN, Douglas, J.** et al.; Patterson, Thunte, Skaar & Christensen, P.A., 4800 IDS Center, 80 South Eighth Street, Minneapolis, MN 55402-2100 (US).

(22) International Filing Date: 9 October 2003 (09.10.2003)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
60/417,150 9 October 2002 (09.10.2002) US

(81) Designated States (*national*): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.


(71) Applicant (*for all designated States except US*): **ENTEGRIS, INC.** [US/US]; 3500 Lyman Boulevard, Chaska, MN 55318 (US).

(84) Designated States (*regional*): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE,

(72) Inventors; and
(75) Inventors/Applicants (*for US only*): **EXTRAND,**

[Continued on next page]

(54) Title: HIGH TEMPERATURE, HIGH STRENGTH, COLORABLE MATERIALS FOR DEVICE PROCESSING SYSTEMS



(57) Abstract: Electrostatic-discharge safe devices for processing electronic components, e.g., matrix trays, chip trays, and wafer carriers are disclosed that are made from a mixture of a high temperature, high strength polymer and at least one metal oxide, and optionally with at least one pigment. The use of the metal oxides as conductive materials advantageously allows for light-colored electrostatic-discharge safe materials to be made. Such materials may be colored with pigments without compromise of material performance specifications.

WO 2004/033103 A2



ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO,
SE, SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM,
GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

(15) Information about Correction:

see PCT Gazette No. 48/2004 of 25 November 2004, Sec-
tion II

Published:

— *without international search report and to be republished
upon receipt of that report*

(48) Date of publication of this corrected version:

25 November 2004

*For two-letter codes and other abbreviations, refer to the "Guid-
ance Notes on Codes and Abbreviations" appearing at the begin-
ning of each regular issue of the PCT Gazette.*