

23 SEP 2002

WO 99/49224

PCT/IB99/00459

Description

Axial flow fan



166166



G00002

Technical Field

The present invention relates to an axial flow fan equipped with blades inclined in the plane of rotation of the fan.

5 The fan disclosed by the present invention has diverse applications, for example, to move air through a heat exchanger or radiator in the cooling system of a motor vehicle or similar engine, or to move air through a heat exchanger in the heating system of the interior compartment of a vehicle. In addition, the fan disclosed by the present invention can be used to move air in
10 the fixed air conditioning or heating installations of buildings.

 Fans of this kind have to satisfy various different requirements, including low noise, high efficiency, dimensional compactness and good values of head (pressure) and delivery.

15

Background Art

 Patent EP - 0 553 598 B, in the name of the same Applicant
20 as the present, discloses a fan whose blades have a constant chord length along their entire length. In addition, the leading and trailing edges of the blades form two curves which, if projected onto the plane of rotation of the fan, are two circular arcs. Fans made in accordance with this patent achieve good results in terms
25 of efficiency and low noise but their ability to achieve high head or pressure values is limited mainly because of their small axial dimensions.

 The need to achieve high head values has become an increasingly important requirement on account of the thermal units
30 in modern automobiles which include two or more exchangers arranged in series - for example, the condenser of the air conditioning system, the radiator of the cooling system and the heat exchanger for the air supply of turbo engines - or on account

of radiators that have become thicker to compensate for the smaller frontal dimensions.

Disclosure of the Invention

The aim of the present invention is to solve the problem of head or pressure of the above mentioned fans and to further improve them in terms of efficiency and low noise.

The problem is solved by the characteristics described in the independent claim. The dependent claims refer to preferred, advantageous embodiments of the invention.

The invention will now be described with reference to the accompanying drawings which illustrate preferred embodiments of the invention and in which:

- Figure 1 is a front view of a fan made in accordance with the present invention;
- Figure 2 illustrates in a front view the geometrical features of a blade of the fan disclosed by the present invention;
- Figure 3 shows sections of a blade of the fan disclosed by the present invention taken at regular intervals starting from the hub to the end of the blade;
- Figure 4 illustrates in a perspective view other geometrical features of a blade of the fan disclosed by the present invention;
- Figure 5 shows a scaled up detail of the fan illustrated in Figure 1 and the related duct;
- Figure 6 is a front view of another embodiment of the fan disclosed by the present invention;
- Figure 7 shows a diagram representing, in Cartesian coordinates, the convex edge of a blade of the fan disclosed by the present invention; and
- Figure 8 is a diagram showing the changes in the blade angle in different sections of a blade as a function of the radius of the fan disclosed by the present invention.

The terms used to describe the fan are defined as follows:

- the chord (L) is the length of the straight-line segment subtended by the arc extending from the leading edge to the trailing edge over an aerodynamic profile of the section of the blade obtained by intersecting the blade with a cylinder whose axis coincides with the axis of rotation of the fan and whose radius r coincides at a point Q;
- the centre line or midchord line (MC) of the blade is the line joining the midpoints of the chords L to the different rays;
- the sweep angle (δ) measured at a given point Q of a characteristic curve of the blade, for example, the curve representing the trailing edge of the fan blade, is the angle made by a ray emanating from the centre of the fan to the point Q concerned and the tangent to the curve at the same point Q;
- the skew angle or net angular displacement (α) of a characteristic curve of the blade is the angle between the ray passing through the characteristic curve, for example, the curve representing the midchord line of the blade, to the fan hub, and the ray passing through the characteristic curve at the end of the blade;
- the blade angle (β) is the angle between the plane of rotation of the fan and the straight line joining the leading edge to the trailing edge of the aerodynamic profile of the blade section;
- the pitch ratio (P/D) is the ratio between the pitch of the helix, that is to say, the amount by which the point Q concerned is axially displaced, that is, $P = 2 \cdot \pi \cdot r \cdot \tan(\beta)$, where r is the length of the ray to the point Q and β is the blade angle at the point Q, and the maximum diameter of the fan;
- the profile camber (f) is the longest straight-line segment perpendicular to the chord L, measured from the chord L to the blade camber line; the position of the profile camber f relative to the chord L may be expressed as a percentage of the length of the chord itself;
- the rake (V) is the axial displacement of the blade from the plane of rotation of the fan, including not only the displacement of the entire profile from the plane of rotation but also the axial component due to the blade curvature, if any - also in axial direction.

With reference to the accompanying drawings, the fan 1 rotates about an axis 2 and comprises a central hub 3 mounting a plurality of blades 4 curved in the plane of rotation XY of the fan 1. The blades 4 have a root 5 and an end 6 and are delimited by a convex edge 7 and a concave edge 8.

Since satisfactory results in terms of efficiency, noise level and head have been obtained by rotating the fan made according to the present invention either in one direction or the other, the convex edge 7 and the concave edge 8 may each be either the leading edge or the trailing edge of the blade.

In other words, the fan 1 may rotate in such a way that the air to be moved meets first with the convex edge 7 and then the concave edge 8 or, vice versa, first with the concave edge 8 and then the convex edge 7.

Obviously, the aerodynamic profile of the blade section must be oriented according to the mode of operation of the fan 1, that is to say, according to whether the air to be moved meets the convex edge 7 or the concave edge 8 first.

At the end 6 of the blades 4, a reinforcement ring 9 may be fitted. The ring 9 strengthens the set of the blades 4 for example by preventing the angle β of the blade 4 from varying in the area at the end of the blade on account of aerodynamic loads. Moreover, the ring 9, in combination with a duct 10, limits the whirling of the air around the fan and reduces the vortices at the end 6 of the blades 4, these vortices being created, as is known, by the different pressure on the two faces of the blade 4.

For this purpose, the ring 9 has a thick lip portion 11, that fits into a matching seat 12 made in the duct 10. The distance (a), very small in the axial direction, between the lip 11 and the seat 12 together with the labyrinth shape of the part between the two elements, reduces air whirl at the end of the fan blades.

Moreover, the special fit between the outer ring 9 and the duct 10 allows the two parts to come into contact with each other while at the same time reducing the axial movements of the fan.

As a whole, the ring 9 has the shape of a nozzle, that is to say, its inlet section is larger than the section through which

the air passes at the end of the blades 4. The larger suction surface keeps air flowing at a constant rate by compensating for flow resistance.

5 However, as shown in Figure 6, the fan made according to the present invention need not be equipped with the outer reinforcement ring and the related duct.

The blade 4, projected onto the plane of rotation XY of the fan 1, has the geometrical characteristics described below.

10 The angle at the centre (B), assuming as the centre the geometrical centre of the fan coinciding with the axis of rotation 2 of the fan, corresponding to the width of the blade 4 at the root 5, is calculated using a relation that takes into account the gap that must exist between two adjacent blades 4. In fact, since fans of this kind are made preferably of plastic using injection
15 moulding, the blades in the die should not overlap, otherwise the die used to make the fan has to be very complex and production costs inevitably go up as a result.

Moreover, it should be remembered that, especially in the case of motor vehicle applications, the fans do not work
20 continuously because a lot of the time that the engine is running, the heat exchangers to which the fans are connected are cooled by the air flow created by the movement of the vehicle itself. Therefore, air must be allowed to flow through easily even when the fan is not turning. This is achieved by leaving a relatively
25 wide gap between the fan blades. In other words, the fan blades must not form a screen that prevents the cooling effect of the air flow created by vehicle motion. The relation used to calculate the angle (B) in degrees is:

30
$$B = (360^\circ / \text{No. of blades}) - K; K_{\min} = f(\text{hub diameter; height of blade profile at the hub}).$$

The angle (K) is a factor that takes into account the minimum distance that must exist between two adjacent blades to prevent them from overlapping during moulding and is a function of the hub diameter: the larger the hub diameter is, the smaller the
35 angle (K) can be. The value of the angle (K) may also be influenced by the height of the blade profile at the hub.

The description below, given by way of example only and without restricting the scope of the inventive concept, refers to a practical application of the fan made in accordance with the present invention. As shown in the accompanying drawings, the fan has seven blades, a hub with a diameter of 140 mm and an outside diameter, corresponding to the diameter of the outer ring 9, of 385 mm.

The angle (B), corresponding to the width of a blade at the hub, calculated using these values, is 44° .

The geometry of a blade 4 of the fan 1 will now be described: the blade 4 is first defined as a projection onto the plane of rotation XY of the fan 1 and the projection of the blade 4 onto the plane XY is then transferred into space.

With reference to the detail shown in Figure 2, the geometrical construction of the blade 4 consists in drawing the bisector 13 of the angle (B) which is in turn delimited by the ray 17 on the left and the ray 16 on the right. A ray 14, rotated in anticlockwise direction by an angle $A = 3/11 B$ relative to the bisector 13, and a ray 15, also rotated in anticlockwise direction by an angle (A) but relative to the ray 16, are then drawn. The two rays 14, 15 are thus both rotated by an angle $A = 3/11 B$, that is, $A = 12^\circ$. The intersections of the rays 17 and 16 with the hub 3 and the intersections of the rays 14 and 15 with the outer ring 9 of the fan (or with a circle equal in diameter to the outer ring 9), determine four points (M, N, S, T) lying in the plane XY, which define the projection of the blade 4 of the fan 1. The projection of the convex edge 7 is also defined, at the hub, by a first tangent 21 inclined by an angle $C = 3/4 A$, that is, $C = 9^\circ$, relative to the ray 17 passing through the point (M) at the hub 3.

As can be seen in Figure 2, the angle (C) is measured in a clockwise direction relative to the ray 17 and therefore the first tangent 21 is ahead of the ray 17 when the convex edge 7 is the first to meet the air flow, or behind the ray 17 when the convex edge 7 is the last to meet the air flow, that is, when the edge 8 is the first to meet the air flow.

At the outer ring 9, the convex edge 7 is also defined by a second tangent 22 which is inclined by an angle (W) equal to 6

times the angle (A), that is, 72°, relative to the ray 14 passing through the point (N) at the outer ring 9. As shown in Fig. 2, the angle (W) is measured in an anticlockwise direction relative to the ray 14 and therefore the second tangent 22 is ahead when the convex edge 7 is the first to meet the air flow, or behind the ray 14 when the convex edge 7 is the last to meet the air flow, that is, when the edge 8 is the first to meet the air flow.

In practice, the projection of the convex edge 7 is tangent to the first tangent 21 and to the second tangent 22 and is characterized by a curve with a single convex portion, without flexions. The curve which defines the projection of the convex edge 7 is a parabola of the type:

$$y = a x^2 + b x + c.$$

In the embodiment illustrated, the parabola is defined by the following equation:

$$y = 0.013 x^2 - 2.7 x + 95.7.$$

This equation determines the curve illustrated in the Cartesian diagram, shown in Figure 7, as a function of the related x and y variables of the plane XY.

Looking at Figure 2 again, the endpoints of the parabola are defined by the tangents 21 and 22 at the points (M) and (N) and the zone of maximum convexity is that nearest the hub 3.

Experiments have shown that the convex edge 7, with its parabolic projection onto the plane of rotation XY of the fan, provides excellent efficiency and noise characteristics.

As regards the projection of the concave edge 8 of the blade 4 onto the plane XY, any second degree curve arranged in such a way as to define a concavity can be used. For example, the projection of the concave edge 8 may be defined by a parabola similar to that of the convex edge 7 and arranged in substantially the same way.

In a preferred embodiment, the curve defining the projection of the concave edge 8 onto the plane XY is a circular arc whose radius (R_{cu}) is equal to the radius (R) of the hub and, in the practical application described here, the value of this radius is 70 mm.

As shown in Figure 2, the projection of the concave edge 8 is delimited by the points (S) and (T) and is a circular arc whose radius is equal to the radius of the hub. The projection of the concave edge 8 is thus completely defined in geometrical terms.

5 Figure 3 shows eleven profiles 18 representing eleven sections of the blade 4 made at regular intervals from left to right, that is, from the hub 3 to the outer edge 6 of the blade 4. The profiles 18 have some characteristics in common but are all geometrically different in order to be able to adapt to the
10 aerodynamic conditions which are substantially a function of the position of the profiles in the radial direction. The characteristics common to all the blade profiles are particularly suitable for achieving high efficiency and head and low noise.

15 The first profiles on the left are more arched and have a larger blade angle (β) because, being closer to the hub, their linear velocity is less than that of the outer profiles.

20 The profiles 18 have a face 18a comprising an initial straight-line segment. This straight-line segment is designed to allow the air flow to enter smoothly, preventing the blade from "beating" the air which would interrupt smooth air flow and thus increase noise and reduce efficiency. In Figure 3, this straight-line segment is labelled (t) and its length is from 14% to 17% of the length of the chord (L).

25 The remainder of the face 18a is substantially made up of circular arcs. Passing from the profiles close to the hub towards those at the end of the blade, the circular arcs making up the face 18a become larger and larger in radius, that is to say, the profile camber (f) of the blade 4 decreases.

30 With respect to the chord (L), the profile camber (f) is located at a point, labelled (lf) in Figure 3, between 35% and 47% of the total length of the chord (L). This length must be measured from the edge of the profile that meets the air first.

35 The back 18b of the blade is defined by a curve such that the maximum thickness (G_{max}) of the profile is located in a zone between 15% and 25% of the total length of the blade chord and preferably at 20% of the length of the chord (L). In this case

too, this length must be measured from the edge of the profile that meets the air first.

Moving from the profiles closer to the hub where the maximum thickness (G_{max}) has its highest value, the thickness of the profile 18 decreases at a constant rate towards the profiles at the end of the blade where it is reduced by about a quarter of its value. The maximum thickness (G_{max}) decreases according to substantially linear variation as a function of the fan radius. The profiles 18 of the sections of the blade 4 at the outermost portion of the fan 1 have the lowest (G_{max}) thickness value because their aerodynamic characteristics must make them suitable for higher speeds. In this way, the profile is optimized for the linear velocity of the blade section, this velocity obviously increasing with the increase in the fan radius.

The length of the chord (L) of the profiles (18) also varies as a function of the radius.

The chord length (L) reaches its highest value in the middle of the blade 4 and decreases towards the end 6 of the blade so as to reduce the aerodynamic load on the outermost portion of the fan blade and also to facilitate the passage of the air when the fan is not operating, as stated above.

The blade angle (β) also varies as a function of the fan radius. In particular, the blade angle (β) decreases according to a quasi-linear law.

The law of variation of the blade angle (β) can be chosen according to the aerodynamic load required on the outermost portion of the fan blade.

In a preferred embodiment, the variation of the blade angle (β) as a function of the fan radius (r) follows a cubic law defined by the equation

$$(\beta) = -7 \cdot 10^{-6} \cdot r^3 + 0.0037 \cdot r^2 - 0.7602 r + 67.64$$

The law of variation of (β) as a function of the fan radius (r) is represented in the diagram shown in Figure 8.

Figure 4 shows how the projection of the blade 4 in the plane XY is transferred into space. The blade 4 has a rake V relative to the plane of rotation of the fan 1.

Figure 4 shows the segments joining the points (M', N') and (S', T') of a blade (4).

These points (M', N', S', T') are obtained by starting from the points (M, N, S, T) which lie in the plane XY and drawing
 5 perpendicular segments (M, M'), (N, N'), (S, S'), (T, T') which thus determine a rake (V) or, in other words, a displacement of the blade 4 in axial direction.

Moreover, in the preferred embodiment, each blade 4 has a shape defined by the arcs 19 and 20 in Figure 4. These arcs 19 and
 10 20 are circular arcs whose curvature is calculated as a function of the length of the straight-line segments (M', N') and (S', T'). As shown in Figure 4, the arcs 19 and 20 are offset from the corresponding straight-line segments (M', N') and (S', T') by lengths (h1) and (h2) respectively. These lengths (h1) and (h2)
 15 are measured on the perpendicular to the plane of rotation XY of the fan 1 and are calculated as a percentage of the length of the segments (M', N') and (S', T') themselves.

The dashed lines in Figure 4 are the curves - parabolic segment and circular arc - related to the convex edge 7 and to the
 20 concave edge 8

The rake V of the blade 4, both as regards its axial displacement component and as regards curvature makes it possible to correct blade flexions due to aerodynamic load and to balance
 25 the aerodynamic moments on the blade in such a way as to obtain uniform axial air flow distributed over the entire front surface of the fan.

All the characteristic values of the fan blade, according to the embodiment described, are summarized in the table below where r is the generic fan radius and the following geometrical
 30 variables refer to the corresponding radius value:

L indicates the chord length;
 f indicates the profile camber
 t indicates the initial straight-line segment of the blade section;
 35 lf indicates the position of the profile camber relative to the chord L;

β indicates the angle of the blade section profile in sexagesimal degrees;

x and y indicate the Cartesian coordinates in the plane XY of the parabolic edge of the blade.

5

r	70	100.6	131.2	161.9	179
L	59.8	68.7	78.2	73	71.2
f	8.2	7.5	7.8	6.7	5
t	10	10.5	11	10.5	10
lf	21	25.5	31.2	32.8	33
β	30.1	21.9	15.7	13.3	11.1
x	65.3	93.2	126.1	161.9	176.4
y	-25.2	-43.0	-38.1	-0.7	23.9

Experiments have shown that the fans made in accordance with the present invention have a noise level 25-30%, measured in dB(A), lower than conventional fans of this kind, with a considerable improvement in acoustic comfort, meaning by this that the noise generated was much more "pleasant" than that of conventional fans.

Moreover, under the same conditions of air delivery, the fans made according to the present invention develop head values up to 50% greater than conventional fans of this kind.

In fans made according to the present invention, passing from a blades back to a blades forward configuration does not result in any appreciable change in noise level. Moreover, under certain working conditions, in particular in the high head range, the blades forward configuration delivers 20-25% more than the blades back configuration.

Claims

1. An axial flow fan rotating in a plane and comprising a central hub, a plurality of blades, each having a root and an end, the blades being also delimited by a convex edge and a concave edge and consisting of sections with aerodynamic profiles with a blade angle which decreases gradually and constantly from the root towards the end of the blade, the blade angle being defined as the current angle between the plane of rotation and a straight line joining the leading edge to the trailing edge of the aerodynamic profile of each blade section, the fan being characterized in that the projection of the convex edge onto the plane is defined by a parabolic segment.
2. The fan according to claim 1 characterized in that the projection of the concave edge onto the plane is defined by a second degree curve segment.
3. The fan according to claim 1 or 2 characterized in that the projection of the concave edge onto the plane is defined by a parabolic segment.
4. The fan according to claim 2 characterized in that the projection of the concave edge onto the plane is defined by a circular arc.
5. The fan according to any of the foregoing claims characterized in that the aerodynamic profiles have a face comprising at least one initial straight-line segment.
6. The fan according to claim 5 characterized in that the aerodynamic profiles have a face comprising a segment, following the initial segment, that is substantially made up of circular arcs.
7. The fan according to claim 5 or 6 characterized in that the aerodynamic profiles have a chord length and a back defined by a convex curve which, in combination with the face, determines a maximum thickness value of the profile in a zone between 15% and 25% of the total length of the chord measured from the edge that meets the air first.

8. The fan according to any of the foregoing claims characterized in that each blade projected onto the plane is delimited by four points lying in the plane and defined as a function of an angle (B) relative to the width of a single blade subtended at the centre of the fan; and being characterized also in that the four points are determined by the following geometric characteristics:

the first and the third points are located at the hub or at the root of the blade and are defined by the rays emanating from the centre of the fan and forming the angle (B);

the second point is located at the end of the blade and is displaced in anticlockwise direction by an angle $(A) = 3/11 (B)$ relative to the bisector of the angle (B);

the fourth point is located at the end of the blade and is displaced in anticlockwise direction by an angle $(A) = 3/11 (B)$ relative to the ray emanating from the centre of the fan and passing through the third point.

9. The fan according to claim 8 characterized in that the projection of the convex edge onto the plane at the first point has a first tangent inclined by an angle (C) equal to three quarters of (A) relative to a ray passing through the first point; and characterized also in that the projection of the convex edge onto the plane at the second point has a second tangent inclined by an angle (W) equal to six times (A) relative to a ray passing through the second point; the first and second tangents being ahead of the corresponding rays when the direction of rotation of the fan is such that the convex edge is the first to meet the air flow and the first and second tangents are arranged in such a way as to define a curve in the plane that has a single convex portion without flexions.

10. The fan according to one of the foregoing claims from 4 to 9 characterized in that the circular arc formed by the projection of the concave edge onto the plane has a radius equal to the radius of the hub.

11. The fan according to any of the foregoing claims characterized in that the blades are formed of sections whose aerodynamic profiles have a blade angle that decreases gradually and constantly from the root towards the end of the blade according to a cubic law of variation as a function of the radius.