

Hardened wave-guide antenna

FIELD OF THE INVENTION

This invention relates to radio-frequency antenna structures and, more particularly, to low-profile hardened wave-guide antennas.

BACKGROUND OF THE INVENTION

5 Mobile radio communications presently mainly rely on conventional whip-type antennas mounted to the roof, hood, or trunk of a motor vehicle. Although whip antennas generally provide acceptable mobile communications performance, they have a number of disadvantages. For example, a whip antenna must be mounted on an exterior surface of the vehicle, so that the antenna is unprotected from the weather, and
10 may for example, be damaged by vehicle washes, unless temporarily removed.

The user of mobile radio equipment is often plagued today by the problem of vandalism of car radio antennas and burglary of the equipment. Indeed, the presence of a whip antenna on the exterior of a car is a good clue to thieves that a radio, telephone transceiver or other equipment is installed within the vehicle.

15 Varieties of covert antennas are known in the art. Such antennas are usually substantially flush-mounted to a vehicle, covered with fiberglass and refinished to blend with the rest of the car body. In particular, annular slot-type stripline antennas can be useful, as where such an antenna is to be substantially flush-mounted to a vehicle. One such annular slot-type stripline antenna element is described in U.S. Pat. No. 3,665,480.
20 As discussed therein, the antenna element includes a pair of parallel conductive plates formed on opposite faces of a dielectric support structure, one of which has formed therein a generally annular radiating slot of substantially uniform width, and a feed element disposed between the parallel plates and extending radially into the central region of the annular slot for feeding electromagnetic energy into such a slot.

- 2 -

U.S. Pat. No. 4,821,040 describes a compact quarter-wavelength microstrip element especially suited for use as a mobile radio antenna. The antenna is not visible to a passerby observer when installed, since it is literally part of the vehicle. The microstrip radiating element is conformal to a passenger vehicle, and may, for example,
5 be mounted under a plastic roof between the roof and the headliner.

U.S. Pat. No. 4,821,042 describes a vehicle antenna system including high frequency pickup type antennas concealed within the vehicle body for receiving broadcast waves. The high frequency pickups are arranged on the vehicle body at locations spaced apart from one another, that is, at least one adjacent to the vehicle roof
10 and the other on a trunk hinge.

U.S. Pat. No. 5,402,134 describes a flat plate antenna module for use in a non-conductive cab of a motor vehicle and includes a dielectric substrate and one or more antenna loops arranged on the substrate. The substrate is adapted to be installed between the headliner of a cab and the dielectric roof. The module may include a CB antenna
15 loop, an AM/FM antenna loop, a cellular mobile telephone antenna loop, and a global positioning system antenna, without the need for any antenna structure external to the cab. The antennae are arranged on the module in a nested configuration.

U.S. Pat. No. 6,023,243 describes a flat panel antenna for microwave transmission. The antenna comprises at least one printed circuit board, and has active
20 elements including radiating elements and transmission lines. There is at least one ground plane for the radiating elements and at least one surface serving as a ground plane for the transmission lines. The panel is arranged such that the spacing between the radiating elements and their respective groundplane is independent of the spacing between the transmission lines and their respective groundplane. A radome may
25 additionally be provided which comprises laminations of polyolefin and an outer skin of polypropylene.

SUMMARY OF THE INVENTION

Despite the prior art in the area of covert antennas, there is still a need in the art
30 for further improvement in order to provide an antenna that might be substantially flush-mounted to a vehicle, has broad band performance and a reduced aperture. It would also be advantageous to have an antenna that would be sufficiently hardened in order to

- 3 -

withstand vandalism, and harsh weather conditions. There is also a need and it would be advantageous to have an antenna that can survive the impact of road pebbles, gravel and other objects that can impact the antenna during exploitation.

The present invention partially eliminates disadvantages of cited reference
5 techniques and provides a novel antenna element that is substantially covert and difficult to detect and vandalize.

According to one embodiment, the antenna element includes a waveguide configured for operating in a below-cutoff mode, an exciter configured for exciting the waveguide, and a shield configured for protecting the exciter. The waveguide has a
10 cavity. The shield includes a holder arranged within the cavity, and a front plate mounted on the holder and disposed over at least a part of the exciter. A gap between the inner walls of the waveguide and the front plate defines an aperture of the waveguide. Preferably, the front plate is substantially flush with the aperture.

According to one embodiment, the exciter includes a printed-circuit antenna
15 arranged within the cavity and configured for feeding the waveguide, and a feed arrangement coupled to the printed-circuit antenna at a feed point for providing radio frequency energy to the printed-circuit antenna. The printed-circuit antenna has a layered structure and includes a thin layer of a dielectric material, a patch printed on an under-side of the thin layer, and a substrate arranged between the patch and a bottom of
20 the cavity. The patch includes an orifice that defines the location of the feed point.

According to one embodiment, the orifice is arranged at a verge of the patch, which is the distant edge from the center of the patch. According to one embodiment, the orifice is arranged within the solid portion of the patch.

According to one embodiment, the printed-circuit antenna also includes a pad
25 and a stub coupled to the pad. The pad and stub are both printed on the upper side of the thin layer and arranged under the orifice of the patch.

According to an embodiment, the waveguide is a circular waveguide. In this case, the patch, the thin layer and the substrate all have ring shapes hollowed out in the ring center to define a lumen.

30 According to an embodiment, the holder of the shield is inserted through the lumen in the center of the layered structure formed by the patch, the thin layer and the substrate.

- 4 -

According to an embodiment, the holder has a tubular shape and includes a tapered portion and a uniform portion. The tapered portion is tapered with contraction from the front plate towards a uniform portion located at the bottom of the cavity. The contraction of the holder extends from the front plate until the location of the printed-circuit antenna. The uniform portion can have a base threaded into the bottom of the cavity.

According to an embodiment, the feed arrangement includes a pin and a sleeve arranged within the substrate between the patch and the bottom of the cavity. The pin passes through a common hole arranged within the waveguide at the bottom of the cavity, the sleeve and the thin layer. The pin is connected to the pad at the feed point of the printed-circuit antenna.

According to an embodiment, the pin is surrounded with an isolator layer. The isolator layer can, for example, be made of teflon.

According to a further embodiment, the antenna element further comprises a radome mounted on the top of the antenna element over the aperture.

According to another aspect of the present invention, there is provided a phased array antenna that comprises a plurality of the antenna elements described above, and a beam steering system coupled to the antenna elements and configured for steering an energy beam produced by said phased array antenna.

According to one embodiment, the waveguides of the antenna elements are arranged in a common conductive ground plane and spaced apart at a predetermined distance from each other.

According to another embodiment, the antenna elements have individual waveguides. Each waveguide is arranged in an individual conductive ground plane and spaced apart at a predetermined distance from each other.

The antenna element of the present invention has many of the advantages of the prior art techniques, while simultaneously overcoming some of the disadvantages normally associated therewith.

The antenna element of the present invention can generally be configured to operate in a broad band within the frequency range of about 20 MHz to 80 GHz.

The antenna element according to the present invention may be efficiently manufactured. The printed circuit part of the antenna (e.g., exciter) can, for example, be manufactured by using printed circuit techniques.

- 5 -

The installation of the antenna element and antenna array of the present invention is relatively quick and easy and can be accomplished without substantially altering a vehicle in which it is to be installed.

The antenna element according to the present invention is of durable and reliable
5 construction.

The antenna element according to the present invention may be readily conformed to complexly shaped surfaces and contours of a mounting platform. In particular, it can be readily conformable to a car or other structures.

There has thus been outlined, rather broadly, the more important features of the
10 invention in order that the detailed description thereof that follows hereinafter may be better understood. Additional details and advantages of the invention will be set forth in the detailed description, and in part will be appreciated from the description, or may be learned by practice of the invention.

BRIEF DESCRIPTION OF THE DRAWINGS

15 In order to understand the invention and to see how it may be carried out in practice, embodiments will now be described, by way of non-limiting example only, with reference to the accompanying drawings, in which:

Fig. 1 is a schematic side cross-sectional fragmentary view of a single antenna element, according to one embodiment of the present invention;

20 **Fig. 2A** is a perspective front view of an array antenna structure assembled from the single element antennas shown in **Fig. 1**, according to one embodiment of the present invention;

Fig. 2B is a perspective view of an interface for coupling the array antenna structure shown in **Fig. 2A** to other modules, according to one embodiment of the
25 present invention;

Fig. 3 illustrates exemplary graphs depicting the frequency dependence of the input reflection (return loss) coefficient for antenna element shown in **Fig. 1** for various values of the radius of the cavity;

Fig. 4 illustrates exemplary graphs depicting the frequency dependence of the
30 input reflection (return loss) coefficient for antenna element shown in **Fig. 1** for various values of the cavity length;

Fig. 5 is a perspective view of the shield of the single element antennas shown in **Fig. 1**, according to one embodiment of the present invention;

Fig. 6 illustrates exemplary graphs depicting the frequency dependence of the input reflection coefficient for antenna element shown in **Fig. 1** for various values of the thickness of the front plate;

Fig. 7 illustrates exemplary graphs depicting the frequency dependence of the input reflection coefficient for antenna element shown in **Fig. 1** for various values of the radius of the holder;

Fig. 8 illustrates exemplary graphs depicting the frequency dependence of the input reflection coefficient for antenna element shown in **Fig. 1** for various values of the tapering angle of the holder;

Fig. 9 illustrates exemplary graphs depicting the frequency dependence of the input reflection coefficient for antenna element shown in **Fig. 1** for various dimensions of the gap between the front disk of the holder and the inner walls of the waveguide cavity;

Fig. 10 shows an exploded perspective view of the single antenna element shown in **Fig. 1**, according to one embodiment of the present invention;

Fig. 11 shows a schematic underside view of the supporting layer of the printed-circuit antenna shown in **Fig. 10**, according to one embodiment of the present invention;

Fig. 12 shows a schematic view of the printed-circuit antenna, according to one embodiment of the present invention;

Fig. 13A illustrates exemplary graphs depicting the frequency dependence of the input reflection coefficient for antenna element shown in **Fig. 1** for various values of the outer radius of the printed circuit patch of the exciter;

Fig. 13B illustrates exemplary graphs depicting the frequency dependence of the input reflection coefficient for antenna element shown in **Fig. 1** for various values of the inner radius of the printed circuit patch of the exciter;

Fig. 14 illustrates exemplary graphs depicting the frequency dependence of the input reflection coefficient for antenna element shown in **Fig. 1** for various values of the thickness of the substrate;

Fig. 15 illustrates exemplary graphs depicting the frequency dependence of the input reflection coefficient for antenna element shown in **Fig. 1** for various values of the radius of orifice in the patch;

- 7 -

Fig. 16 illustrates exemplary graphs depicting the frequency dependence of the input reflection coefficient for antenna element shown in **Fig. 1** for various values of the radius of the pad;

Fig. 17A illustrates exemplary graphs depicting the frequency dependence of the input reflection coefficient for antenna element shown in **Fig. 1** for various values of the length of the microstrip stub;

Fig. 17B illustrates exemplary graphs depicting the frequency dependence of the input reflection coefficient for antenna element shown in **Fig. 1** for various values of the width of the microstrip stub;

Fig. 18 illustrates exemplary graphs depicting the frequency dependence of the input reflection coefficient for antenna element shown in **Fig. 1** for various values of the distance of the pin from the center of the patch;

Fig. 19A illustrates exemplary graphs depicting the frequency dependence of the input reflection coefficient for antenna element shown in **Fig. 1** for various values of the height of the sleeve;

Fig. 19B illustrates exemplary graphs depicting the frequency dependence of the input reflection coefficient for antenna element shown in **Fig. 1** for various values of the radius of the sleeve; and

Fig. 20 illustrates exemplary graphs depicting the frequency dependence of the input reflection coefficient for antenna element shown in **Fig. 1** for various values of the thickness of the radome.

DETAILED DESCRIPTION OF EMBODIMENTS

The principles of the antenna according to the present invention may be better understood with reference to the drawings and the accompanying description, wherein like reference numerals have been used throughout to designate identical elements. It being understood that these drawings which are not necessarily to scale, are given for illustrative purposes only and are not intended to limit the scope of the invention. Examples of constructions, materials, dimensions, and manufacturing processes are provided for selected elements. Those versed in the art should appreciate that many of the examples provided have suitable alternatives which may be utilized.

- 8 -

Referring now to the drawings, **Fig. 1** illustrates a schematic side cross-sectional fragmentary view of an antenna element **10**, according to one embodiment of the present invention. The antenna element **10** includes a waveguide **11** having a cavity **13** and configured for operating in a below-cutoff mode. The antenna element **10** also includes an exciter (shown schematically by a reference numeral **12**) configured for exciting the waveguide **11**. The exciter **12** includes a printed-circuit antenna (shown schematically by a reference numeral **15**) arranged within the cavity **13**, and a feed arrangement (shown schematically by a reference numeral **16**) configured for feeding the printed-circuit antenna **15**. The feed arrangement **16** is coupled to the printed-circuit antenna **15** at a feed point **161** for providing radio frequency energy thereto. In turn, the printed-circuit antenna **15** is configured for feeding the waveguide **11**.

Preferably, but not mandatory, the waveguide **11** is a circular waveguide. It should be noted that using a circular waveguide has a number of distinct advantages. One advantage is that a circular waveguide, owing to its symmetry, can operate in any polarization. From a mechanical point of view the circular waveguide is appropriate because of its mechanical simplicity and hardness.

The antenna element **10** also includes a shield (shown schematically by a reference numeral **17**) configured to protect the printed-circuit antenna **15**, for example, from vandalism, impact of road pebbles and gravel, and/or from other damaging actions. The shield **17** includes a holder **171** arranged within the cavity **13**, and a front plate **172** mounted on the holder **171**. A gap between the inner walls of the waveguide **11** and the front plate **172** defines an aperture **14** of the waveguide **11**.

When the waveguide **11** is a circular waveguide, the front plate **172** preferably has a shape of a disk. It should be noted that the shield **17** has a twofold purpose. Electrically, the shield causes the antenna to operate the antenna above the cutoff frequency. This function of the shield is in addition to protecting the antenna from foreign elements.

According to one embodiment, the holder **171** has a tubular shape and includes a tapered portion **173** having a varied diameter, and a uniform portion **174** having a uniform diameter. The tapered portion **173** is tapered with contraction from the front plate (disk) **172** towards a uniform portion **174** that is located at a bottom **131** of the cavity **13**.

- 9 -

When the waveguide **11** is a circular waveguide, the printed-circuit antenna **15** has a ring shape with a circular lumen **150** arranged in the center of the ring. As shown in **Fig. 1**, the contraction of the holder **171** can extend from the front plate **172** up to the location of the printed-circuit antenna **15**. The uniform portion **174** of the holder **171** passes through the lumen **150**.

According to an embodiment, the uniform portion **174** of the holder **171** is attached to the bottom **131** of the cavity **13**. The connection of the holder **171** to the bottom **131** can, for example, be made with a laser weld, plasma weld pulse, electromagnetic weld or other welding process. Moreover, such fixing may be done by soldering, brazing, crimping, application of glues or by any other known technique depending on the material selected for each component. When desired, the holder **171** can include a base **175** of the uniform portion **174** that can be threaded into the waveguide **13** at the bottom **131** of the cavity **13**. When desired, the base **175** of the holder **171** can have a screw thread for screwing the shield **17** to the waveguide **13** at the bottom **131**.

The front plate **172** is disposed over the printed-circuit antenna **15** of the exciter **12**, and is substantially flush with the aperture **14** and does not protrude. This provision can prevent the onset of surface waves.

There is a wide choice of materials available suitable for the antenna element **10**. The waveguide **11** can, for example, be formed from aluminum to provide a lightweight structure, although other metallic materials, e.g., zinc plated steel, etc. can also be employed.

The shield **17** can, for example, be formed from a hard and strong material to provide good protection from vandalism. Examples of the material suitable for the shield **17** include, but are not limited to, metallic materials.

According to a further embodiment, the antenna element **10** can include a radome **19** mounted on the top of the antenna element over the aperture **14**. Placement of a relatively thin radome ensures, *inter alia*, that the antenna can be waterproof. As will be shown hereinbelow, the thickness of radome affects to a very large extent the resonant frequency of the antenna.

When desired, the space in the cavity **13** between the printed-circuit antenna **15** and the aperture **14** can be filled with a dielectric material.

Exemplary values of design parameters are shown in Table 1.

Table 1
Exemplary values of design parameters of the antenna element **10**

Parameter	Value
Cavity Radius	$0.212\lambda_0$
Cavity Length	$0.27\lambda_0$
Thickness of Front Plate	8mm
Radius of Holder	$0.075\lambda_0$
Taper Angle of Holder	55.2°
Gap between the Front Disk of the Holder and Inner Walls of the Waveguide	$0.0475\lambda_0$
Outer Radius of Printed Circuit	$0.167\lambda_0$
Inner Radius of Printed Circuit	$0.090\lambda_0$
Thickness of Substrate	$0.065\lambda_0$
Radius of Orifice of Patch	$0.023\lambda_0$
Radius of Pad	$0.022\lambda_0$
Length of Microstrip Stub	$0.043\lambda_0$
Width of Microstrip Stub	$0.0225\lambda_0$
Distance of Pin from center	$0.11\lambda_0$
Height of Sleeve	$0.0154\lambda_0$
Radius of Sleeve	$0.0125\lambda_0$
Thickness of Radome	$0.0054\lambda_0$

5 It should be noted that the geometric parameters of the antenna element are represented within the present description in the dimensions normalized to the value of the wavelength in free space λ_0 . In particular, λ_0 is defined by c/f , where c is the speed of light and f is the frequency of operation of the antenna element.

Referring to **Fig. 2A**, the single element antenna described above with
 10 references to **Fig. 1**, can be implemented in a phase array antenna structure **20**, taking the characteristics of the corresponding array factor. It should be noted that the phase array antenna structure **20** can be implemented in various ways.

- 11 -

For example, as shown in **Fig. 2A**, all the waveguides of the antenna elements **10** can be arranged within a common conductive ground plane **21**. Alternatively, the plurality of the antenna elements **10** can have individual waveguides. In this case, each waveguide can, for example, be arranged in an individual conductive ground plane (not shown).

In the example shown in **Fig. 2A**, the antenna elements **10** are arranged in columns and rows, however other arrangements are also contemplated. It should also be noted that although the array antenna shown in **Fig. 2A** has an oval shape, it may alternatively take other shapes, including, but not limited to, a circular, polygonal (e.g., triangular, square, rectangular, quadrilateral, pentagon, hexagonal, etc) and other shapes. Accordingly, the number of the rows in which the antenna elements **10** are arranged can be equal to the number of the columns. Alternatively, the numbers of the rows and the columns in the antenna array can be different. Moreover, the number of the antenna elements **10** in neighboring rows can be either equal or different. Moreover, the arrangement of the antenna elements **10** in the array can be either regular or staggered, thereby forming a rectangular or triangular lattice.

It should still further be noted that the phase array antenna **20** may be used as a single radiator in conjunction with a transceiver device, or it may be combined together with additional antenna arrays to form a larger array antenna. And it should still further be noted that although the front side **22** of the array antenna shown in **Fig. 2** has a planar shape, when desired, the array antenna may alternatively have a curved or undulated face.

Furthermore, this array antenna can include a beam steering system (not shown) coupled to the plurality of the antenna elements **10** and configured for steering an energy beam produced by the phased array antenna. The beam steering system is a known system that can, *inter alia*, include such components as T/R modules, DSP-driven switches, and other components required to control steerable multi-beams.

Fig. 2B illustrates a perspective view of an interface **23** for coupling the array antenna shown in **Fig. 2A** to other modules, according to one embodiment of the present invention. For example, the interface **23** can couple the array antenna structure to T/R modules (not shown). In particular, each antenna element can be fed with a T/R module which is connected via a corresponding connector **24**.

It was found that the configuration and parameters of the antenna element **10** and the array antenna structure **20** significantly affect their performance. Several examples of such dependencies will be illustrated herein below.

One of the important parameters of a phased array antenna is spacing S between
 5 antenna elements. The spacing S determines the required scan angle of the antenna. Specifically, the farther out the antenna needs to be scanned, the closer the element should be arranged in order to eliminate the onset of grating lobes into real space.

In operation, the spacing S has a major effect on the antenna element (**10** in **Fig. 1**), since there is very strong electromagnetic coupling between the elements, which has
 10 a rather significant effect on the electrical characteristics of the antenna. This coupling has a strong effect on the return loss and element pattern of the antenna.

It should be understood that the spacing S between the elements **10** limits the diameter D of the cavity (**13** in **Fig. 1**) of the element **10**. On the other hand, it was found by the inventors that diameter of the cavity can affect the resonant frequency of
 15 the antenna.

Fig. 3 illustrates exemplary graphs obtained by computer simulations depicting the frequency dependence of the input reflection (return loss) coefficient for antenna element shown in **Fig. 1** for various values of the radius R of the cavity (**13** in **Fig. 1**), while the other design parameters are held constant, as represented in Table 1.

20 The computer simulations were carried out when the radius R of the cavity was set to $0.200\lambda_0$ (curve **31**), $0.212\lambda_0$ (curve **32**), and $0.217\lambda_0$ (curve **33**), correspondingly. As was noted above, the radius R of the cavity as well as all other geometric parameters of the antenna element are represented herein in the dimensions normalized to the value of the wavelength in free space λ_0 .

25 As can be seen, the resonant frequency decreases when the radius R of the cavity increases. In practice, the radius of the cavity should be chosen such that the antenna radiates at the desired frequency and bandwidth.

Another parameter of the cavity (**13** in **Fig. 1**) which has an effect on the resonant frequency of the antenna is length L of the cavity. As mentioned above, the
 30 cavity operates below the cutoff frequency; therefore the length of the cavity is very critical.

Fig. 4 shows an example of computer simulation carried out to check how the change in cavity length L can affect the resonant frequency and bandwidth of the

- 13 -

antenna element. The computer simulations were carried out when the cavity length L was set to $0.26\lambda_0$ (curve 41), $0.27\lambda_0$ (curve 42), $0.28\lambda_0$ (curve 43), and $0.29\lambda_0$ (curve 44) correspondingly, where λ_0 is the characteristic wavelength. As can be seen, the resonant frequency decreases when the cavity length increases. In practice, the diameter of the cavity should be chosen such that the antenna radiates at the desired frequency and bandwidth.

Referring to **Fig. 1 and Fig. 5**, the length L of the cavity is also determined by the length of the holder 171 of the shield 17 and the thickness of the front plate 172 mounted on top of the holder 171. As mentioned above, the front plate 172, *inter alia*, serves to protect the antenna from vandalism or from other damaging actions. Moreover, it is also configured to allow the cavity 13 to operate above the cutoff frequency. There are several parameters of the shield which needed to be designed in order for the antenna to operate properly.

The first parameter for which the effect of its magnitude on the frequency response was checked was the thickness l of the front plate 172. Referring to **Fig. 6**, a computer simulation analysis was done to see the effect of the thickness of the front plate on the resonant frequency of the antenna element. The computer simulations were carried out in which the front plate was selected in the shape of a disk and the thickness l of the front disk was set to 6mm (curve 61), 7mm (curve 62), 8mm (curve 63), and 9mm (curve 64), correspondingly. As can be seen in **Fig. 6**, the variations in the thickness l of the front disk did not modify the resonant frequency and bandwidth of the antenna element very much. In addition, thickness l seems to have only a minor effect of the Return Loss of the antenna.

In practice, the thickness l of the front plate 172 should, *inter alia*, be chosen to withstand vandalism and other aggressive actions against the antenna. Preferably, the thickness of the front plate is equal to or greater than about 8 mm, in order to properly mechanically protect the antenna element. Accordingly, further computer simulations were carried out in which the front plate was selected in the shape of a disk and the thickness of the front disk was set to 8 mm. For this case, the following parameters were optimized: the radius δ of the holder 171 at the bottom portion 174, the tapering angle α of the holder, the radius r of the front disk and the length s of the cavity (14 in **Fig. 1**), i.e. a gap between the walls of the waveguide and the front disk 172.

Referring to **Fig. 7**, another parameter for which the effect of its magnitude on the frequency response was checked was the radius r of the holder **171**. The computer simulations were carried out when the radius r of the holder at the bottom portion was set to $0.065\lambda_0$ (curve **71**), $0.075\lambda_0$ (curve **72**), and $0.085\lambda_0$ (curve **73**), correspondingly.

5 **Fig. 7** shows the effect the radius of the holder on the resonance frequency and bandwidth of the antenna element. As can be seen, there are particular radii of the holder, such as $0.065\lambda_0$ and $0.075\lambda_0$, at which the antenna is resonant, whereas at the radius of $0.085\lambda_0$ the antenna element is not resonant.

Referring to **Fig. 8**, the further parameter that was analyzed is the effect of the
 10 tapering angle α of the holder on the frequency response of the antenna. The computer simulations were carried out when the tapering angle α of the holder was set to 52.3 degrees (curve **81**), 55.2 degrees (curve **82**), 57.7 degrees (curve **83**), 58.9 degrees (curve **84**), and 61.8 degrees (curve **85**). As one can see, the tapering angle of the holder influences the resonant frequency and bandwidth of the antenna element. Modifying the
 15 angle of the holder has a profound effect on the resonant frequency of the antenna element. In addition, there are angles at which the antenna element almost does not resonate.

Referring to **Fig. 9**, the next parameter that was analyzed is the effect of the gap between the front disk and the inner walls of the waveguide cavity (**13** in **Fig. 1**), i.e.,
 20 how the dimension of the waveguide's cavity (**14** in **Fig. 1**) affects the performance of the antenna element. The computer simulations were carried out when the gap dimension was set to $0.0375\lambda_0$ (curve **91**), $0.040\lambda_0$ (curve **92**), $0.0425\lambda_0$ (curve **93**), $0.045\lambda_0$ (curve **94**), and $0.0475\lambda_0$ (curve **95**). As can be seen on **Fig. 9**, small changes in the gap dimension have a profound effect on the resonant frequency and bandwidth
 25 of the antenna element, therefore care must be taken to choose the correct gap.

In practice, the gap should preferably be chosen to be as small as possible. This should be done to make the face of the aperture as smooth as possible, thereby to prevent the antenna from penetrating any foreign objects into the cavity. On the other hand, the gap is the area from which the antenna radiates. Thus, when designing the
 30 antenna, one inherently chooses the largest possible gap that is acceptable. The designer then chooses the gap dimension from which the other antenna parameters can be optimized. The inventor believes that in practice, a gap that is suitable can, for example be the gap having dimensions in the range of about $0.0375\lambda_0$ to $0.0475\lambda_0$.

- 15 -

Referring to **Fig. 1** and **Fig. 10** together, the further part of the antenna element which is described hereinbelow in detail is the exciter **12**. As described above, the exciter **12** includes the printed-circuit antenna **15** arranged within the cavity **13**, and the feed arrangement **16** coupled to the printed-circuit antenna **15** at a feed point **161**, for providing radio frequency energy thereto. A detailed description of embodiments of the printed-circuit antenna **15** and the feed arrangement **16** are described hereinbelow.

The printed-circuit antenna **15** has a layered structure and includes a supporting layer **152** having an underside **153** and an upper side **154**. The supporting layer **152** is a thin layer of a dielectric material. As used throughout this description, the terms 'underside' and 'upper side' are referred to surfaces of the plates and layers in relation to the cavity of the waveguide (**10** in **Fig. 1**). Specifically the surface that faces the bottom of the cavity is referred to as 'underside', whereas the surface that can be exposed in the aperture is referred to as 'upper side'.

The printed-circuit antenna **15** also includes a patch **151**. **Fig. 11** shows a schematic perspective view of the supporting layer **152** turned upper side down, according to one embodiment of the present invention. As can be seen, the patch **151** is printed on the under-side **153** of the supporting layer **152**.

Referring back to **Fig. 1** and **Fig. 10**, the printed-circuit antenna **15** further includes a substrate **155** arranged between the patch **151** and the bottom **131** of the cavity **13**. In accordance with one embodiment, the underside of the patch **151** is adhesively bonded onto an upper side of the substrate **155**. The substrate **155** can fill a portion or entire volume of the cavity between the patch **151** and the bottom **131** of the cavity **13**.

According to an embodiment, the patch **151**, the supporting layer **152** and the substrate **155** are all have ring shapes hollowed out in the ring center. As shown in **Fig. 1**, this provision enables the holder **171** of the shield **17** to be inserted through the lumen **150** in the center of the layered structure formed by the patch **151**, the supporting layer **152** and the substrate **155**. Moreover, when desired, the metallic base **175** of the holder **171** can be threaded into the bottom of the cavity **13**.

It should be appreciated that from an electromagnetic standpoint it is permitted to place the holder **171** within the center of the patch **151** since the voltage is zero at the center and as the current travels along one direction the voltage is positive, and while the current travels in the opposite direction the voltage is negative. As a result, placing a

- 16 -

metallic object in the center of patch symmetric about its center does not disable the patch and does not prevent it from operating properly. The only effect of placing a metallic object is that the resonant frequency is altered.

It was found that the dielectric constant of the substrate can affect the bandwidth and resonant frequency of the antenna element. Accordingly, the dielectric constant of the substrate **155** arranged beneath the patch **151** must be chosen to optimize the performance of the antenna. One must be judicious in choosing the dielectric constant. Choosing a very high dielectric constant might reduce the bandwidth, however choosing a very low dielectric constant might make the exciter too large and unable to fit into the cavity.

An example of the dielectric material suitable for the substrate **155** includes, but is not limited to, ROHACELL[®] foam which can, for example, be produced by thermal expansion of a co-polymer sheet of methacrylic acid and methacrylonitrile. It should be noted that ROHACELL[®] foam is formed of a dielectric material having a dielectric constant nearly equivalent to the dielectric constant of air.

Referring to **Fig. 11**, the patch **151** includes an orifice **156** defining the location of the feed point (**161 in fig 1**). The orifice **156** can, for example, have a circular shape, however other shapes of the orifice are also contemplated. According to the embodiment shown in **Figs. 10 and 11**, the orifice **156** is arranged at a verge **157** of the patch which is the distant edge from the center of the patch **151**. In this case, the shape of the cut out portion of the orifice **156** has a shape of a partial circle. Alternatively, when desired, the orifice **156** can be arranged completely within the solid portion of the patch **151**. In this case, the shape of the cut out portion can have a shape of a full circle.

Referring to **Fig. 12**, the printed-circuit antenna **15** further includes a pad **158** and a stub **159** coupled to the pad **158**. The pad **158** and the stub **159** are printed on the upper side **154** of the supporting layer **152** and mounted under the orifice (**156 in Fig. 11**) arranged in the patch (**151 in Fig. 11**). As shown in **Fig. 12**, the pad **158** has a circular shape, whereas the stub **159** has a rectangular shape; however other shapes for the pad and stub are contemplated.

The thickness of the supporting layer **152** should be as thin as possible. The reason for this is in order for the pad **158** and the stub **159** to be as close to the printed circuit patch **151** as possible, since the patch acts as a ground plane for the stub and the pad.

- 17 -

An example of the dielectric material suitable for the supporting layer **152** includes, but is not limited to epoxy glass, however other dielectric materials can also be suitable. The substrate **155** can, for example, be made of a dielectric material, however other materials, e.g., semiconducting ceramics, could also be used for substrate. It was found that the dielectric constant of the PC Board is of minor significance. Since the antenna is very thin, the dielectric constant of the PC Board is not a significant parameter. More important, are the mechanical characteristics of the material. Moreover, one needs a material which can be bonded onto the substrate **155**.

Turning back to **Figs. 1 and 10**, the feed arrangement **16** is formed as a direct current coaxial feed and includes an electrically conductive pin **163** and an electrically conductive sleeve **162** surrounding the pin **163**. The electrically conductive sleeve **162** is arranged within the substrate **155** of the printed-circuit antenna **15** between the patch **151** and the bottom **131** of the cavity **13**. The sleeve **162** can, for example, be made of metal or any other conductive material. According to one embodiment, the electrically conductive sleeve **162** is attached to the bottom **131** of the cavity. According to another embodiment, the sleeve **162** is formed in the cavity **13** and it is integrated with the waveguide **11**.

The electrically conductive pin **163** passes through a common hole **164** arranged within the waveguide **11** at the bottom of the cavity **13**, the sleeve **162** and the supporting layer **152**. The pin **163** is connected to the pad **158** at the feed point **161** of the printed-circuit antenna **15**. The connection of the pin **163** to the pad **158** can, for example, be carried out by soldering, welding, or by any other suitable technique. According to one embodiment, the pin **163** is surrounded with an isolator layer **165** made, for example, from teflon.

The pin **163** is coupled electromagnetically to the printed circuit patch **151**. The pad **158** acts a capacitor in series with the pin **163**. The pad **158** and the stub **159** together act as a reactive transmission line in which the patch **151** acts as its ground plane. The purpose of the stub **159** is to tune the patch **151** to 50 ohms or to any other impedance desired. The stub **159** can also increase the bandwidth of the antenna element.

It should be appreciated that the antenna element described above has the ability to operate in any polarization chosen. This implies that the antenna element can provide vertical, horizontal or circular polarized radiation. When desired, the radiation can be

- 18 -

polarized to 45 degrees or any other polarization desired. The reason is that the polarization is determined by the position of the feed point **161** with respect to the printed circuit patch **151**. Since the patch **151** is symmetric the feed point **161** can be located in any position desired. If circular polarization is desired, two feed points and, correspondingly, two coaxial feed arrangements can be used placed orthogonally to each other and phased 90° apart to achieve circular polarization.

As discussed above, the configuration and parameters of the antenna element and the array antenna structure significantly affect their performance. Several examples of the dependencies of the geometric dimensions of the waveguide (**11** in **Fig. 1**) and the shield (**17** in **Fig. 1**) have been shown above. As will be illustrated hereinbelow, the configuration and parameters of the exciter (**12** in **Fig. 1**) also significantly affect the antenna performance. Simulations were done to check the effect of the various parameters of the printed-circuit antenna (**15** in **Fig. 1**) and the feed arrangement (**16** in **Fig. 1**) on the performance of the antenna element (**10** in **Fig. 1**).

Fig. 13A shows an example obtained by computer simulations of the effect of variation of the outer radius r_{outer} of the printed circuit patch (**151** in **Fig. 11**) on the resonant frequency and bandwidth of the antenna element (**10** in **Fig. 1**), while the other design parameters are held constant. The computer simulations were carried out when the outer radius r_{outer} of the printed circuit patch was set to $0.157\lambda_0$ (curve **1301**), $0.160\lambda_0$ (curve **1302**), $0.162\lambda_0$ (curve **1303**), $0.165\lambda_0$ (curve **1304**) and $0.167\lambda_0$ (curve **1305**), correspondingly.

As one can see, the resonant frequency varies with outer radius of the patch **151**. As one can see, the resonant frequency decreases with decrease in the patch radius. It was found by the applicant that the behavior of the resonant frequency of the antenna element, in which the patch is enclosed within a cavity, differs from the behavior of a conventional patch, in which the resonant frequency usually increases with decrease in the patch radius.

The next parameter analyzed was the inner radius r_{inner} of the printed circuit patch (**151** in **Fig. 11A**). The simulation shown below illustrates the return loss of the antenna for three inner radii. **Fig. 13B** shows an example obtained by computer simulations of the effect of variation of the inner radius r_{inner} of the printed circuit patch (**151** in **Fig. 11A**) on the resonant frequency and bandwidth of the antenna element (**10** in **Fig. 1**), while the other design parameters are held constant. The

computer simulations were carried out when the inner radius r_{inner} of the printed circuit patch was set to $0.085\lambda_0$ (curve **1306**), $0.09\lambda_0$ (curve **1307**) and $0.095\lambda_0$ (curve **1308**), correspondingly. As one can see, the inner radius affects the return loss of the antenna. In order for the antenna return loss to be optimal, the inner radius must be chosen
 5 carefully. In this example, the optimum inner radius equals $0.085\lambda_0$, which is large by $0.01\lambda_0$ than the radius of the uniform portion **174** of the holder **171**.

The next parameter analyzed was the thickness s of the substrate (**155** in **Fig. 1**) arranged underneath the patch (**151** in **Fig. 1**). **Fig. 14** shows an example obtained by computer simulations of the effect of variation of the thickness s of the substrate on the
 10 resonant frequency of the antenna element (**10** in **Fig. 1**), while the other design parameters are held constant. The computer simulations were carried out when the thickness s was set to $0.045\lambda_0$ (curve **1401**), $0.055\lambda_0$ (curve **1402**), $0.065\lambda_0$ (curve **1403**), $0.075\lambda_0$ (curve **1404**).

As one can see, the thickness of the substrate has a direct effect on the
 15 bandwidth and resonant frequency of the antenna. For example, in order that an antenna properly operate between $0.975f_0$ and $1.02f_0$ (where $f_0 = c/\lambda_0$, and c is the light velocity), one can choose a thickness of $0.065\lambda_0$.

As described above with reference to **Fig. 11**, the patch **151** has the orifice **156** that defines the location of the feed point **161**. The pin **163** is coupled
 20 electromagnetically to the patch. The diameter of orifice **156** has a profound effect on strength of the coupling of the pin to the patch.

Fig. 15 shows an example obtained by computer simulations of the effect of variation of the radius of orifice **156** in the patch **151** on the resonant frequency and bandwidth of the antenna element (**10** in **Fig. 1**), while the other design parameters are
 25 held constant. The computer simulations were carried out when the radius of orifice **156** was set to $0.019\lambda_0$ (curve **1501**), $0.021\lambda_0$ (curve **1502**), $0.023\lambda_0$ (curve **1503**), and $0.025\lambda_0$ (curve **1504**), correspondingly.

As one can see from **Fig. 15**, the variation of the radius of orifice **156** in a relatively broad range between $0.019\lambda_0$ and $0.021\lambda_0$ does not change the frequency
 30 behavior of the return losses (see curves **1501** and **1502**). However, the small variation of the orifice between $0.023\lambda_0$ and $0.025\lambda_0$ (see curve **1503** and **1504**) brings the coupling to optimum. At the radius of $0.023\lambda_0$ the antenna is resonant at desired frequency.

The next parameter analyzed was the radius R_{pad} of the pad **158**. Simulations were done to determine the effect of modifying the radius of the pad. **Fig. 16** shows an example obtained by computer simulations of the effect of variation of the radius R_{pad} of the pad on the resonant frequency of the antenna element (**10** in **Fig. 1**), while the other design parameters are held constant. The computer simulations were carried out when the radius R_{pad} was set to $0.017\lambda_0$ (curve **1601**), $0.018\lambda_0$ (curve **1602**), $0.020\lambda_0$ (curve **1603**), and $0.022\lambda_0$ (curve **1604**). As one can see, there is an optimal pad radius equal to $0.022\lambda_0$ which gives the maximum bandwidth and best possible return loss.

The further analyzed parameters are the length L_{stub} and the width W_{stub} of the stub **159** when the stub has a rectangular shape (as shown in **Fig. 12**). As described above, the stub **159** can be a microstrip line connected to the microstrip pad **158** and configured to tune the patch **151**. **Figs. 17A and 17B** show, correspondingly, examples obtained by computer simulations of the effect of variation of the length and width of the stub **159** on the resonant frequency and bandwidth of the antenna element (**10** in **Fig. 1**), while the other design parameters are held constant. The computer simulations were carried out when the length L_{stub} was set to $0.031\lambda_0$ (curve **1701**), $0.0425\lambda_0$ (curve **1702**), $0.054\lambda_0$ (curve **1703**), $0.060\lambda_0$ (curve **1704**), correspondingly, and when the width W_{stub} was set to $0.01\lambda_0$ (curve **1705**), $0.0163\lambda_0$ (curve **1706**), $0.0225\lambda_0$ (curve **1707**), $0.0288\lambda_0$ (curve **1708**).

As can be seen from **Fig. 17A**, the length L_{stub} of the microstrip stub affects the bandwidth and resonant frequency of the antenna element. Accordingly, there is an optimal stub length which gives the maximum bandwidth and optimal return loss. On the other hand, as can be seen from **Fig. 17B**, the width W_{stub} of the stub has a minor influence on the antenna in this configuration.

It was also found that the distance of the feed point **161** from the center **O** of the patch **151** has a very noticeable effect on the impedance of the patch **151**. **Fig. 18** shows an example obtained by computer simulations of the effect of variation of the distance of the feed point from the center of the patch **151** on the resonant frequency and bandwidth of the antenna element (**10** in **Fig. 1**), while the other design parameters are held constant. The computer simulations were carried out when the distance of the feed point **161** from the center **O** was set to $0.08\lambda_0$ (curve **1801**), $0.0875\lambda_0$ (curve **1802**), $0.095\lambda_0$ (curve **1803**), $0.1025\lambda_0$ (curve **1804**), and $0.11\lambda_0$ (curve **1805**).

- 21 -

As can be seen from **Fig. 18**, the distance of the feed point **161** from the center **O** affects the bandwidth and resonant frequency of the antenna element. Accordingly, there is an optimal stub length which gives the maximum bandwidth and optimal return loss. Thus, a major part of the design effort is the proper placement of the (pin **163** in **Fig. 10**) from the center of the patch **151**.

Turning back to **Figs. 1, 10** and **12** together, another important parameter in the construction of the antenna element is the electrically conductive sleeve **162** which surrounds the pin **163** and the isolator layer **165**. It should be understood that the height of the sleeve **162** behaves as an inductance, whereas the diameter behaves like a capacitor in series with the pin **163**.

Figs. 19A and **19B** show, correspondingly, examples obtained by computer simulations of the effect of variation of the height and radius of the sleeve **162** on the resonant frequency and bandwidth of the antenna element (**10** in **Fig. 1**), while the other design parameters are held constant. The computer simulations were carried out when the height of the sleeve was set to $0.0064\lambda_0$ (curve **1901**), $0.0128\lambda_0$ (curve **1902**), $0.0154\lambda_0$ (curve **1903**), $0.0184\lambda_0$ (curve **1904**), $0.0240\lambda_0$ (curve **1905**), correspondingly, and when the radius of the sleeve was set to $0.008\lambda_0$ (curve **1906**), $0.0010\lambda_0$ (curve **1907**), $0.0125\lambda_0$ (curve **1908**), $0.0148\lambda_0$ (curve **1909**), and $0.017\lambda_0$ (curve **1910**).

As one can see from **Fig. 19A**, varying the height of the sleeve has a significant effect on the impedance and bandwidth of the element. Accordingly, there is an optimal sleeve height which gives the maximum bandwidth and optimal return loss. On the other hand, as can be seen from **Fig. 19B**, the radius of the sleeve has a minor influence on the antenna in this configuration.

Turning back to **Fig. 1**, a further parameter which is important for the construction of the antenna element is the thickness of the radome **19** placed on top of antenna element to prevent dust and dirt from entering the slots of the antenna. The radome affects to a very large extent the resonant frequency of the antenna. The extent of the radome's influence depends on the thickness and dielectric constant of the radome **19**.

Fig. 20 shows an example obtained by computer simulations of the effect of variation of the thickness of the radome on the resonant frequency and bandwidth of the antenna element (**10** in **Fig. 1**), while the other design parameters are held constant. The

- 22 -

computer simulations were carried out when the thickness of the radome **19** was set to $0.002\lambda_0$ (curve **201**), $0.0037\lambda_0$ (curve **202**), $0.0054\lambda_0$ (curve **203**), $0.0071\lambda_0$ (curve **204**), $0.008\lambda_0$ (curve **205**), correspondingly. As can be seen from **Fig. 20**, even a small change in the radome thickness has a very strong influence on the resonant frequency and bandwidth of the antenna. The thicker the radome, the greater the impact on the antenna resonant frequency. Moreover, the higher the dielectric constant, the greater the effect the radome has on the resonant frequency of the antenna.

As such, those skilled in the art to which the present invention pertains, can appreciate that while the present invention has been described in terms of preferred embodiments, the conception, upon which this disclosure is based, may readily be utilized as a basis for the designing of other structures systems and processes for carrying out the several purposes of the present invention.

The antenna of the present invention may be utilized in various intersystems, e.g., in communication within the computer wireless LAN (Local Area Network), PCN (Personal Communication Network) and ISM (Industrial, Scientific, Medical Network) systems.

The antenna may also be utilized in communications between a LAN and cellular phone network, GPS (Global Positioning System) or GSM (Global System for Mobile communication).

It is to be understood that the phraseology and terminology employed herein are for the purpose of description and should not be regarded as limiting.

It is important, therefore, that the scope of the invention is not construed as being limited by the illustrative embodiments set forth herein. Other variations are possible within the scope of the present invention as defined in the appended claims. Other combinations and sub-combinations of features, functions, elements and/or properties may be claimed through amendment of the present claims or presentation of new claims in this or a related application. Such amended or new claims, whether they are directed to different combinations or directed to the same combinations, whether different, broader, narrower or equal in scope to the original claims, are also regarded as included within the subject matter of the present description.

CLAIMS:

1. An antenna element (10) comprising:
 - a waveguide (11) configured for operating in a below-cutoff mode and having a cavity (13);
 - 5 an exciter (12) configured for exciting the waveguide (11); and
 - a shield (17) including:
 - a holder (171) arranged within the cavity (13); and
 - a front plate (172) mounted on the holder and disposed over at least a part of the exciter (12).
- 10 2. The antenna element of claim 1, wherein the exciter (12) includes:
 - a printed-circuit antenna (15) arranged within the cavity (13) and configured for feeding the waveguide (11); and
 - a feed arrangement (16) coupled to the printed-circuit antenna (15) at a feed point (161) for providing radio frequency energy thereto.
- 15 3. The antenna element of claim 2, wherein said printed-circuit antenna (15) has a layered structure and includes:
 - a thin layer (152) of a dielectric material having an underside (153) and an upper side (154);
 - a patch (151) printed on the underside (153) of the thin layer (152), and
 - 20 a substrate (155) arranged between the patch (151) and a bottom of the cavity (13).
4. The antenna element of claim 3, wherein the patch (151) includes an orifice (156) defining the location of the feed point (161).
5. The antenna element of claim 4, wherein the orifice (156) is arranged at a verge
- 25 (157) of the patch, which is the distant edge from the center of the patch (151).
6. The antenna element of claim 4, wherein the orifice (156) is arranged within the solid portion of the patch (151).
7. The antenna element of claim 4, wherein said printed-circuit antenna (15) includes a pad (158) and a stub (159) coupled to the pad (158), the pad (158) and the stub
- 30 (159) are printed on the upper side (154) of the thin layer (152) and arranged under the orifice (156) of the patch (151).

- 24 -

8. The antenna element of claim 3, wherein the waveguide (11) is a circular waveguide, and wherein the patch (151), the thin layer (152) and the substrate (155) all have ring shapes hollowed out in the ring center to define a lumen.
9. The antenna element of claim 8, wherein the holder (171) of the shield (17) is
5 inserted through the lumen in the center of the layered structure formed by the patch (151), the thin layer (152) and the substrate (155).
10. The antenna element of claim 2, wherein the holder (171) has a tubular shape and includes a tapered portion (173) and a uniform portion (174), said tapered portion (173) is tapered with contraction from the front plate (172) towards a uniform portion (174) located
10 at a bottom (131) of the cavity (13).
11. The antenna element of claim 10, wherein the contraction of the holder (171) extends from the front plate (172) until the location of the printed-circuit antenna (15).
12. The antenna element of claim 10, wherein the uniform portion (174) has a base (175) threaded into the bottom of the cavity (13).
- 15 13. The antenna element of claim 7, wherein the feed arrangement (16) includes an electrically conductive pin (163), and an electrically conductive sleeve (162) arranged within the substrate (155) between the patch (151) and the bottom (131) of the cavity (13) and surrounding the pin (163).
14. The antenna element of claim 13, wherein the pin (163) passes through a
20 common hole (164) arranged within the waveguide (11) at the bottom of the cavity (13), the electrically conductive sleeve (162) and the thin layer (152).
15. The antenna element of claim 14, wherein the pin (163) is connected to the pad (158) at the feed point (161) of the printed-circuit antenna (15).
16. The antenna element of claim 13, wherein the pin (163) is surrounded with an
25 isolator layer (165).
17. The antenna element of claim 1 further comprising a radome mounted on the top of the antenna element over the aperture (14).
18. A phased array antenna (20) comprising:
a plurality of the antenna elements (10) of any one of the preceding claims having
30 waveguides (11) arranged in a common conductive ground plane (21) and spaced apart at a predetermined distance from each other; and
a beam steering system coupled to said a plurality of the antenna elements (10) and configured for steering an energy beam produced by said phased array antenna.

- 25 -

19. The phased array antenna of claim 18, wherein the waveguides (11) of said plurality of the antenna elements are arranged in a common conductive ground plane (21).

20. The phased array antenna of claim 18, wherein at least one waveguide (11) of said plurality of the antenna elements is arranged in an individual conductive ground plane.

5

10

15

20

25

30