

Description

The present invention relates to a continuous process for producing dimethyl carbonate with high productivity values.

Dimethyl carbonate is an extremely versatile product which finds use as an organic solvent and additive for fuels, or a reactant, as a substitute for phosgene, in the synthesis of other alkyl or aryl carbonates useful as synthetic lubricants, solvents, plasticizers and monomers for organic glasses and in reactions of methylation and carbonylation for preparing isocyanates, urethanes and polycarbonates.

The usual route to prepare dimethyl carbonate consists in the reaction of methanol with phosgene, as described, e.g., in Kirk-Othmer, *Encyclopedia of Chemical Technology*, 3rd Edition, Volume 4, page 758. Such a process shows several disadvantages deriving from the use of phosgene and the co-production of hydrogen chloride, with consequent safety and corrosion problems, and the need for using a hydrogen chloride acceptor.

Therefore, alternative processes were developed in the past to replace the phosgene-based process; among these, the process based on the oxidative carbonylation of methanol in the presence of catalyst was particularly successful during the past years. The catalysts used for such a process of oxidative carbonylation are generally constituted by copper compounds, as disclosed, e.g., in US-A-3,846,488; US-A-4,218,391; US-A-4,318,862; US-A-4,360,477; US-A-4,625,044; EP-A-71,286, EP-A-134,668; EP-A-217,651; DE-A-3,016,187 and DE-A-3,016,187.

EP-A-134,668 discloses a continuous catalytic process for producing dialkyl carbonates, in which an aliphatic alcohol, carbon monoxide and oxygen are fed to a liquid reaction mixture from which a stream containing the reaction products, dimethyl carbonate and water, is continuously evaporated. A critical aspect of the process of EP-A-134,668 consists in that at each time in the liquid reaction mixture a low level of alcohol (preferably less than 5% by weight) and a low water level (preferably less than 1% by weight) has to be maintained.

The low water content prevents that catalyst deactivation phenomena may occur, and the low alcohol level makes it possible co-produced water -- which is removed as an azeotropic mixture with dimethyl carbonate -- to be easily removed.

Unfortunately, it was observed that, by operating under the conditions of EP-A-134,668, the drawback occurs that the productivity to dialkyl carbonate is low, with the term "productivity" the amount of dialkyl carbonate being understood, which is produced per unit useful reactor volume, and per time unit. This matter of fact renders the same process not very attractive for an application on the commercial scale.

Therefore, the purpose of the present invention is

a catalytic process for the continuous, high-productivity production of dimethyl carbonate, which overcomes the drawbacks of the prior art, as reported hereinabove.

In particular, the present Applicant found, according to the present invention, that a high rate of conversion of the reactants, and a high selectivity to dimethyl carbonate can be attained if methanol, carbon monoxide and oxygen are fed to a liquid reaction mixture which contains a copper catalyst, in which liquid reaction mixture the concentration of methanol is maintained, at any time, at a level of at least 30% by weight. The present Applicant found also that if one operates under these conditions, the concentration of water in the reaction mixture is not particularly critical, as regards the phenomena of catalyst deactivation, and that caring that water level is always equal to, or less than, 10% by weight, is enough.

In accordance therewith, the present invention relates to a process for the continuous preparation of dimethyl carbonate, which process comprises:

- (a) feeding methanol, carbon monoxide and oxygen to a reaction chamber maintained under reaction conditions and containing a liquid reaction mixture consisting of methanol, dimethyl carbonate, water, and a copper catalyst;
- (b) vapourising from the reaction mixture a stream of methanol, water and dimethyl carbonate, which is developed together with the carbon-monoxide-containing gas stream; and
- (c) recovering from said vapourised mixture water and dimethyl carbonate in amounts substantially equal to the respective amounts thereof formed in the reaction chamber; and recycling the other components to the reaction chamber; said process being characterized in that the composition and the volume of the liquid reaction mixture are kept substantially constant over time, with methanol concentration and water concentration being respectively kept equal to, or higher than, 30% by weight, and equal to, or lower than, 10% by weight, relatively to the weight of the same mixture.

More particularly, according to the present invention:

- (a) a stream of both fresh and recycled methanol, carbon monoxide and oxygen and recycled dimethyl carbonate is fed, in a reaction chamber, to a liquid mixture with substantially constant composition and volume, containing methanol, dimethyl carbonate, water, and a copper catalyst, with methanol concentration and water concentration being constantly kept respectively equal to, or higher than, 30% by weight, and equal to, or lower than, 10% by weight;
- (b) from the reaction methanol, a water amount substantially equal to the amount of water formed in the reaction chamber of (a) and an amount of dimethyl carbonate larger than the amount of di-

methyl carbonate formed in the reaction chamber in (a) are vapourised (together with the carbon-monoxide-containing gas stream); and

(c) from the so vapourised stream:

(i) a carbon-monoxide-containing gas stream,
(ii) a first liquid stream consisting of water and dimethyl carbonate, in amounts substantially equal to the respective amounts thereof which are formed in the reaction chamber in (a);

(iii) a second liquid stream consisting of methanol and of the excess of dimethyl carbonate over the amount of dimethyl carbonate formed in the reaction chamber in (a)

are separated;



with the gas stream (i) and the liquid stream (iii) being recycled to the reaction chamber of (a) and the liquid stream (ii) being recovered.

The reaction of formation of dimethyl carbonate from methanol, carbon monoxide and oxygen takes place in the presence of a catalyst, in particular a copper catalyst. The catalyst is generally supplied as cuprous chloride which, in the reaction chamber and under the reaction conditions, can originate such species as copper methoxychloride and copper chlorohydroxides. Of course, the catalyst can also be directly fed to the reaction as copper methoxychloride and/or copper chlorohydroxides. Finally, active catalytic mixtures can be preformed by bringing into contact, outside of the reaction chamber, copper chlorides, oxides, hydroxides or carbonates.


According to the description published in I.E.C. Product and Research Development, Volume 19, pages 396-403, 1980, the catalytically active species can be represented by copper methoxychloride



formed *in situ* from oxygen, cuprous chloride (CuCl) and methanol, and that constitutes the basis for the establishment of a catalytic cycle in that the reaction of formation of dimethyl carbonate involves the reduction of $\text{Cu}(\text{II})$ to $\text{Cu}(\text{I})$, according to the following reaction scheme:



Therefore, the global reaction leading to the formation of dimethyl carbonate from methanol, carbon monoxide and oxygen can be represented as follows:



The critic aspect of the process of the present invention consists in limiting the conversion of methanol per each pass through (a), in such a way that the reaction is carried out in a liquid reaction mixture in which, at any time, the concentration of methanol and the concentration of water are respectively kept constantly equal to, or higher than, 30% by weight, and equal to, or lower than, 10% by weight. In particular, the concentration of methanol and of water in the reaction mixture can be respectively comprised within

the range of from 30 to 80% by weight, and within the range of from 1 to 10% by weight.

In the preferred form of practical embodiment, the process is carried out with a liquid reaction mixture having a composition comprised within the following ranges of values:

* methanol from 35% to 70% by weight, and

* water from 2 to 7% by weight,

* with the balance to 100% being essentially constituted by dimethyl carbonate and unavoidable impurities.

Furthermore, the liquid reaction mixture will contain the copper catalyst in an amount comprised within the range of from 5 to 30 parts by weight, expressed as cuprous chloride, per each 100 parts by weight of the same mixture.

To the above disclosed reaction mixture both fresh and recycled methanol, carbon monoxide and oxygen are fed together With recycled dimethyl carbonate, with the amounts of the fresh reactants being equivalent to the amounts converted in the reaction chamber.

The reaction temperature in (a) can be generally comprised within the range of from 70 to 150°C. Temperatures higher than as indicated are not desirable, because they cause a decrease in reaction selectivity, with byproducts being formed at expense of methanol, with the formation of carbon dioxide being increased and the catalyst being deactivated. Lower temperatures than as indicated are undesirable on considering the low reaction kinetics. However, it is preferable to operate at temperatures close to the high limit of this range in order to have high reaction rates, as well as high values of vapour tension of water and of the organic constituents, with their removal from the reaction chamber being thus favoured. In practice, the preferred reaction temperatures are comprised within the range of from 120 to 140°C.

The pressures at which the reaction is carried out in (a) may vary within wide limits and will anyway be such as to maintain the reaction mixture in the liquid phase at the operating temperature. The preferred pressure values are comprised within the range of from 15 to 40 kg/cm², on considering that lower pressures than as indicated undesirably slow down the reaction kinetics, whilst higher values do not enable adequate concentrations of the organic components and water removed by the gas stream developing from the reaction mixture, to be obtained.

To the liquid reaction mixture in (a) a gas stream containing carbon monoxide, oxygen and, optionally, inert gases, is fed, with the latter being contained at levels of up to 50% by volume in the gas mixture. By "inert gases", such gases as nitrogen, hydrogen or methane, which can be intentionally fed to the reaction chamber, and carbon dioxide, formed as a reaction byproduct, are understood. In the gas stream fed to (a), the molar ratio of carbon monoxide plus any

possible inert gases, to oxygen, is kept comprised within the range of from 100 : 1 to 20 : 1.

By operating under the above conditions, from the liquid reaction mixture a stream of dimethyl carbonate, water and methanol, which is developed together with the excess of carbon monoxide, any possible unreacted oxygen, carbon dioxide and other possibly present inert gases, is removed in (b). Under these conditions, the catalyst, mostly present as a suspended solid, is not removed, and therefore the process can be carried out with high catalyst concentrations, with evident advantages from the viewpoint of the reaction rate.

By carrying out the removal of the reaction products by vapourization, owing to the liquid-vapour equilibria of methanol/dimethyl carbonate/water system, the amount of water removed, within the range of useful compositions, results to be lower -- as expressed as mols -- to the removed amount, as mols, of dimethyl carbonate. Inasmuch as during the course of the reaction one mol of water is formed per each mol of dimethyl carbonate, the removal of produced water is the limiting factor which controls the reaching of the steady-state operating conditions required to carry out the process in continuous fashion. Keeping this into due account, the process according to the present invention is carried out with a large excess of carbon monoxide, relatively to the required amount for the reaction and possibly also in the presence of inert gases, so as to maintain a relatively high flowrate of the gas stream fed to (a). In particular, on considering that at the temperatures at which the reaction is carried out in (a), the vapour pressure of the organic components is of the order of from 5 to 10 kg/cm² and the concentration of water, in the condensate separated from the gas stream leaving the reaction chamber, is of the order of 2-3% by weight, the flowrate of the gas stream fed in (a) is advantageously maintained at a value of from 200 to 1000 litres, referred to standard temperature and pressure conditions (STP), per each litre of useful volume of the reactor, and per each hour. By "useful reactor volume", the volume of the liquid reaction mixture is meant.

The gas stream exiting the reaction chamber is suitably treated in (c) by cooling to temperatures equal or close to room temperature values, in order to separate the condensable organic products and water, from a gas stream [stream (ii)], containing the excess of carbon monoxide, any possibly unreacted oxygen, besides carbon dioxide byproduct, and possible inert substances. This stream is recycled, after a preliminary partial vent or treatment having the purpose of maintaining the concentration of carbon dioxide in the system at a substantially constant level.

The liquid phase condensed in (c) typically contains 45-70% by weight of methanol, 2-3% by weight of water and 25-50% by weight of dimethyl carbonate. This liquid phase can be typically treated by means

of the normal distillation and de-mixing techniques to separate a stream of water and dimethyl carbonate [stream (ii)], in an amount substantially equal to the amount formed in the reaction in, (a), which is recovered, and a stream consisting of the unreacted methanol and dimethyl carbonate in excess over to the amount formed during the reaction [stream (iii)], which is recycled to the reaction in (a). The stream (ii) is treated in order to separate dimethyl carbonate from water.

By operating according to the process of the present invention, dimethyl carbonate can be prepared with a high selectivity and a productivity generally higher than 40 and which, depending on the adopted conditions, may be as high as about 150 grams of dimethyl carbonate per litre of useful reactor volume and per hour.

Figure 1 of the accompanying drawing table schematically shows a suitable apparatus for practicing the process according to the present invention. More particularly, in said figure by the reference numeral (1) the reactor, equipped with stirring means and heat-exchange jacket, is indicated, to which the stream of fresh methanol, and a stream of recycled methanol and dimethyl carbonate are respectively sent via the lines (2) and (3), the streams (2) and (3) being combined and fed to the reactor (1) via the line (4). The stream of fresh carbon monoxide is fed by means of the line (5), the stream of fresh oxygen is fed by means of the line (6) and a recycle stream containing carbon monoxide is fed by means of the line (7). The streams (5), (6) and (7) are combined with one another and are fed to the reactor (1) via the line (8). The stream exiting the reactor via the line (9) is cooled in the heat exchanger (10), the condensed organic products and water are collected in the collector (11) and the residual gases are recycled to the reactor (1) through the line (7), after a preliminary vent inside the line (13).

From the collector (11), the organic condensate is sent, through the line (14), to the separation section (15) in which a stream of dimethyl carbonate and water [line (16)], which is recovered, is separated from a stream of methanol and dimethyl carbonate in excess, which is recycled [line (3)].

Example 1

The apparatus schematically shown in Figure (1) is used, in which the reactor (1) is a reactor with an inner enamel coating, provided with stirring means and a temperature-control jacket inside which a diathermic oil is circulated, which reactor contains 3 litres of reaction liquid phase and 480 g of cuprous chloride (CuCl) catalyst, equivalent to a concentration of 160 g/litre. The reactor is pressurized at a relative pressure of 24 kg/cm², and is heated at 125°C.

Under steady-state conditions, the following

streams are fed to the reactor:

- * 97 g/hour of methanol [line (2)];
- * 1,013 g/hour of a recycle stream [line (3)] containing 78.0% by weight of methanol and 22% by weight of dimethyl carbonate; the streams (2) and (3), combined with each other, are fed to the reactor (1) through the line (4);
- * 310 STP litres/hour of a stream of carbon monoxide and nitrogen, containing 64.5% by volume of carbon monoxide [line (5)];
- * 25 STP litres/hour of 98% pure oxygen, with the balance to 100% being mainly constituted by argon [line (6)];
- * 1,500 STP litres/hour of a recycle stream [line (7)] containing carbon monoxide, carbon dioxide and nitrogen, with 55% by volume of carbon monoxide and 0.5% by volume of oxygen, the balance to 100% being constituted by nitrogen, carbon dioxide and argon; the streams (5), (6) and (7), combined with one another, are fed to the reactor (1) through the line (8).

Under steady-state conditions, the average composition of the liquid mixture inside the reactor (1) is as follows:

- methanol 61.5% by weight,
- dimethyl carbonate 33.0% by weight and
- water 5.5% by weight.

The gas stream leaving the reactor (1) through the line (9) is cooled down to approximately 20°C in the heat exchanger (10) and in the collector (11) a mixture is separated at an average rate of 1,170 g/hour, which has the following composition:

- methanol 67.5% by weight,
- dimethyl carbonate 30.1% by weight,
- water 2.2% by weight and
- volatile byproducts 0.2% by weight.

The gases, after separation of the organic condensate in the collector (11), are recycled [line (7)], after a preliminary vent of 280 STP litres/hour [line (13)]. The condensate is transferred from the collector (11) to the separation unit (15) through the line (14).

In the separation unit (15), an average amount of 130 g/hour of dimethyl carbonate and of 26 g/hour of water is separated [line (16)], by fractional distillation and de-mixing, from a stream of unreacted methanol and excess dimethyl carbonate, which is recycled to the reactor (1) through the line (3).

From the above data, a conversion of methanol of 11.0% is determined, with a molar selectivity to dimethyl carbonate of 95%, based on methanol. The productivity is of 43 g of dimethyl carbonate per litre of useful volume and per hour.

Example 2

The process is carried out as in Example 1, with the following streams being fed to the reactor:

- * line (2): 150 g/hour of methanol;
- * line (3): 1,155 g/hour of a mixture containing: 77.5% by weight of methanol and 22.5% by weight of dimethyl carbonate;
- * line (5): 200 STP litre/hour of carbon monoxide at 100%;
- * line (6): 40 STP litres/hour of oxygen at 98%;
- * line (7): 1,500 STP litres/hour of a mixture containing: 85% by volume of carbon monoxide and 0.5% by volume of oxygen, the balance to 100% being constituted by carbon dioxide and small amounts of argon.

Furthermore, in the reactor (1) the process is carried out at a temperature of 135°C, with the liquid reaction mixture having the following average composition:

- methanol 55.6% by weight,
- dimethyl carbonate 38.0% by weight, and
- water 6.4% by weight.

Through the line (13) 150 STP litres/hour of gas are vented.

Under these conditions, from the line (14) an average amount of 1,400 g/hour is recovered of a mixture containing

- methanol 63.9% by weight,
- dimethyl carbonate 32.9% by weight,
- water 2.8% by weight and
- byproducts 0.4% by weight.

Furthermore, from the line (16) an average amount of 200 g/hour of dimethyl carbonate and 40 g/hour of water is recovered.

The conversion of methanol is consequently of 14.3%, with a molar selectivity to dimethyl carbonate of 95%. The productivity is of 67 g of dimethyl carbonate per litre of useful reactor volume and per hour.

Example 3

The apparatus schematically shown in Figure (1) is used, in which the reactor (1) is a reactor with an inner enamel coating, provided with stirring means and temperature-control jacket inside which a diathermic oil is circulated, which reactor contains 10 litres of reaction liquid and 2,600 g of cuprous chloride (CuCl) catalyst, equivalent to a concentration of g/litre. The reactor is pressurized at a relative pressure of 24 kg/cm², and is heated at 130°C.

Under steady-state conditions, the following streams are fed to the reactor:

- * 990 g/hour of methanol [line(2)];
- * 6,820 g/hour of a recycle stream [line (3)] containing 77% by weight of methanol and 23% by weight of dimethyl carbonate; the streams (2) and (3), combined with each other, are fed to the reactor (1) through the line (4);
- * 800 STP litres/hour of a stream of pure carbon

monoxide [line (5)];

- * 240 STP litres/hour of 98% pure oxygen, with the balance to 100% being mainly constituted by argon and nitrogen [line (6)];

- * 10,000 STP litres/hour of a recycle stream [line (7)] containing carbon monoxide, carbon dioxide and small concentrations of oxygen and inert gases (argon, nitrogen), with 82% by volume of carbon monoxide and 1.0% by volume of oxygen, the balance to 100% being constituted by nitrogen, carbon dioxide and argon; the streams (5), (6) and (7), combined with one another, are fed to the reactor (1) through the line (8).

Under steady-state conditions, the average composition of the liquid mixture inside the reactor (1) is as follows:

- methanol 57.0% by weight,
- dimethyl carbonate 36.0% by weight and
- water 6.9% by weight.

The gas stream leaving the reactor (1) through the line (9) is cooled down to approximately 20°C in the heat exchanger (10) and in the collector (11) a mixture is separated at an average rate of 7,930 g/hour, having the following composition:

- methanol 61.0% by weight,
- dimethyl carbonate 35.3% by weight,
- water 3.4% by weight and
- volatile byproducts 0.3% by weight.

The gases, after separation of the organic condensate in the drum (11), are recycled [line (7)], after preliminarily venting 400 STP litres/hour [line (13)]. The condensate is transferred from the collector (11) to the separation unit (15) through the line (14).

In the separation unit (15), by fractional distillation and de-mixing, an average amount of 1,350 g/hour of dimethyl carbonate and of 270 g/hour of water is separated [line (16)] from a stream of unreacted methanol and excess dimethyl carbonate, which is recycled to the reactor (1) through the line (3).

From the above data, a conversion of methanol of 17.0% is determined, with a molar selectivity to dimethyl carbonate of 97%, based on methanol. The productivity is of 135 g of dimethyl carbonate per litre of useful volume and per hour.

Claims

1. Process for the continuous preparation of dimethyl carbonate, which process comprises:

- (a) feeding methanol, carbon monoxide and oxygen to a reaction chamber maintained under reaction conditions and containing a liquid reaction mixture consisting of methanol, dimethyl carbonate, water, and a copper catalyst;

- (b) vapourising from the reaction mixture a

stream of methanol, water and dimethyl carbonate, which is developed together with the carbon-monoxide-containing gas stream; and (c) recovering from said vapourised mixture water and dimethyl carbonate, in amounts substantially equal to the respective amounts thereof formed in the reaction chamber; and recycling the other components to the reaction chamber;

said process being characterized in that the composition and the volume of the liquid reaction mixture are kept substantially constant over time, with methanol concentration and water concentration being respectively kept equal to, or higher than, 30% by weight, and equal to, or lower than, 10% by weight, relatively to the weight of the same mixture.

2. Process according to claim 1, characterized in that:

- (a) a stream of both fresh and recycled methanol, carbon monoxide and oxygen and recycled dimethyl carbonate is fed, in a reaction chamber, to a liquid reaction mixture with substantially constant composition and volume, containing methanol, dimethyl carbonate, water, and a copper catalyst, with methanol concentration and water concentration being constantly kept respectively equal to, or higher than, 30% by weight, and equal to, or lower than, 10% by weight;

- (b) from the reaction methanol, a water amount substantially equal to the amount of water formed in the reaction chamber of (a) and an amount of dimethyl carbonate larger than the amount of dimethyl carbonate formed in the reaction chamber in (a) are vapourised (together with the carbon-monoxide-containing gas stream); and

- (c) from the so vapourised stream:

- (i) a carbon-monoxide-containing gas stream,

- (ii) a first liquid stream consisting of water and dimethyl carbonate, in amounts substantially equal to the respective amounts thereof which are formed in the reaction chamber in (a);

- (iii) a second liquid stream consisting of methanol and of the excess of dimethyl carbonate over the amount of dimethyl carbonate formed in the reaction chamber in (a)

are separated;

with the gas stream (i) and the liquid stream (iii) being recycled to the reaction chamber of (a) and the liquid stream (ii) being recovered.

3. Process according to claim 1 or 2, characterized

monoxide [line (5)];

- * 240 STP litres/hour of 98% pure oxygen, with the balance to 100% being mainly constituted by argon and nitrogen [line (6)];
- * 10,000 STP litres/hour of a recycle stream [line (7)] containing carbon monoxide, carbon dioxide and small concentrations of oxygen and inert gases (argon, nitrogen), with 82% by volume of carbon monoxide and 1.0% by volume of oxygen, the balance to 100% being constituted by nitrogen, carbon dioxide and argon; the streams (5), (6) and (7), combined with one another, are fed to the reactor (1) through the line (8).

Under steady-state conditions, the average composition of the liquid mixture inside the reactor (1) is as follows:

- methanol 57.0% by weight,
- dimethyl carbonate 36.0% by weight and
- water 6.9% by weight.

The gas stream leaving the reactor (1) through the line (9) is cooled down to approximately 20°C in the heat exchanger (10) and in the collector (11) a mixture is separated at an average rate of 7,930 g/hour, having the following composition:

- methanol 61.0% by weight,
- dimethyl carbonate 35.3% by weight,
- water 3.4% by weight and
- volatile byproducts 0.3% by weight.

The gases, after separation of the organic condensate in the drum (11), are recycled [line (7)], after preliminarily venting 400 STP litres/hour [line (13)]. The condensate is transferred from the collector (11) to the separation unit (15) through the line (14).

In the separation unit (15), by fractional distillation and de-mixing, an average amount of 1,350 g/hour of dimethyl carbonate and of 270 g/hour of water is separated [line (16)] from a stream of unreacted methanol and excess dimethyl carbonate, which is recycled to the reactor (1) through the line (3).

From the above data, a conversion of methanol of 17.0% is determined, with a molar selectivity to dimethyl carbonate of 97%, based on methanol. The productivity is of 135 g of dimethyl carbonate per litre of useful volume and per hour.

Claims

1. Process for the continuous preparation of dimethyl carbonate, which process comprises:
 - (a) feeding methanol, carbon monoxide and oxygen to a reaction chamber maintained under reaction conditions and containing a liquid reaction mixture consisting of methanol, dimethyl carbonate, water, and a copper catalyst;
 - (b) vapourising from the reaction mixture a

stream of methanol, water and dimethyl carbonate, which is developed together with the carbon-monoxide-containing gas stream; and (c) recovering from said vapourised mixture water and dimethyl carbonate, in amounts substantially equal to the respective amounts thereof formed in the reaction chamber; and recycling the other components to the reaction chamber;

said process being characterized in that the composition and the volume of the liquid reaction mixture are kept substantially constant over time, with methanol concentration and water concentration being respectively kept equal to, or higher than, 30% by weight, and equal to, or lower than, 10% by weight, relatively to the weight of the same mixture.

2. Process according to claim 1, characterized in that

(a) a stream of both fresh and recycled methanol, carbon monoxide and oxygen and recycled dimethyl carbonate is fed, in a reaction chamber, to a liquid reaction mixture with substantially constant composition and volume, containing methanol, dimethyl carbonate, water, and a copper catalyst, with methanol concentration and water concentration being constantly kept respectively equal to, or higher than, 30% by weight, and equal to, or lower than, 10% by weight;

(b) from the reaction methanol, a water amount substantially equal to the amount of water formed in the reaction chamber of (a) and an amount of dimethyl carbonate larger than the amount of dimethyl carbonate formed in the reaction chamber in (a) are vapourised (together with the carbon-monoxide-containing gas stream); and

(c) from the so vapourised stream:

(i) a carbon-monoxide-containing gas stream,

(ii) a first liquid stream consisting of water and dimethyl carbonate, in amounts substantially equal to the respective amounts thereof which are formed in the reaction chamber in (a);

(iii) a second liquid stream consisting of methanol and of the excess of dimethyl carbonate over the amount of dimethyl carbonate formed in the reaction chamber in (a)

are separated;

with the gas stream (i) and the liquid stream (iii) being recycled to the reaction chamber of (a) and the liquid stream (ii) being recovered.

3. Process according to claim 1 or 2, characterized



* C L M S *

- in that during the reaction in (a) the process is carried out with a catalyst fed as cuprous chloride, copper methoxychloride, copper chlorohydroxide or as a mixture obtained by bringing into contact copper chlorides, oxides, hydroxides or carbonates, said catalyst being present in an amount of from 5 to 30 parts by weight, expressed as cuprous chloride, per each 100 parts by weight of liquid reaction mixture.
4. Process according to claim 1 or 2, characterized in that in the liquid reaction mixture in (a) the concentration of methanol is comprised within the range of from 30 to 80% by weight and the concentration of water is comprised within the range of from 1 to 10% by weight.
5. Process according to claim 4, characterized in that the process is carried out with a liquid reaction mixture in (a), having a composition comprised within the following ranges of values:
- * methanol from 35% to 70% by weight, and
 - * water from 2 to 7% by weight,
 - * with the balance to 100% being essentially constituted by dimethyl carbonate.
6. Process according to claim 1 or 2, characterized in that the reaction temperature in (a) is comprised within the range of from 70 to 150°C and preferably of from 120 to 140°C.
7. Process according to claim 1 or 2, characterized in that the reaction in (a) is carried out at a pressure comprised within the range of from 15 to 40 kg/cm².
8. Process according to claim 1 or 2, characterized in that to the reaction in (a) a gas stream containing carbon monoxide, oxygen and, optionally, inert gases, is fed, with the latter being contained at a level of up to 50% by volume in the gas mixture; with a molar ratio of carbon monoxide plus any possible inert gases, to oxygen, comprised within the range of from 100 : 1 to 20 : 1.
9. Process according to claim 1 or 2, characterized in that the flowrate of the gas stream fed in (a) is comprised within the range of from 200 to 1000 litres, referred to standard temperature and pressure conditions, per each litre of useful volume of the reactor, and per each hour.

Patentansprüche

1. Verfahren zur kontinuierlichen Herstellung von Dimethylcarbonat, welches Verfahren umfaßt:
- (a) Zuführen von Methanol, Kohlenmonoxid

und Sauerstoff zu einer Reaktionskammer, die unter Reaktionsbedingungen gehalten wird und ein flüssiges Reaktionsgemisch enthält, bestehend aus Methanol, Dimethylcarbonat, Wasser und einem Kupferkatalysator;

(b) Verdampfen eines Stroms aus Methanol, Wasser und Dimethylcarbonat aus dem Reaktionsgemisch, der zusammen mit dem kohlenmonoxidhaltigen Gasstrom entwickelt wird, und

(c) Gewinnen von Wasser und Dimethylcarbonat aus diesem verdampften Gemisch in Mengen, die im wesentlichen den entsprechenden, in der Reaktionskammer gebildeten Mengen gleich sind; und Recyclieren der anderen Komponenten zur Reaktionskammer; welches Verfahren dadurch gekennzeichnet ist, daß die Zusammensetzung und das Volumen des flüssigen Reaktionsgemisches im wesentlichen gegenüber der Zeit konstant gehalten werden, wobei die Methanolkonzentration gleich oder über 30 Gew.-% und die Wasserkonzentration gleich oder unter 10 Gew.-%, bezogen auf das Gewicht dieses Gemisches, gehalten werden.

2. Verfahren nach Anspruch 1, dadurch gekennzeichnet, daß

(a) ein Strom aus sowohl frischem als auch recykliertem Methanol, Kohlenmonoxid und Sauerstoff und recykliertem Dimethylcarbonat in einer Reaktionskammer einem flüssigen Reaktionsgemisch zugeführt wird, welches Gemisch eine im wesentlichen konstante Zusammensetzung und ein im wesentlichen konstantes Volumen aufweist, und Methanol, Dimethylcarbonat, Wasser und einen Kupferkatalysator enthält, wobei die Methanolkonzentration konstant auf gleich oder höher als 30 Gew.-% und die Wasserkonzentration konstant auf gleich oder niedriger als 10 Gew.-% gehalten werden;

(b) aus der Reaktion Methanol, eine Wassermenge, die im wesentlichen der in der Reaktionskammer von (a) gebildeten Wassermenge gleich ist, und eine Dimethylcarbonatmenge, die größer als die in der Reaktionskammer in (a) gebildete Dimethylcarbonatmenge ist, verdampft werden (zusammen mit dem kohlenmonoxidhaltigen Gasstrom); und

(c) aus dem so verdampften Strom:

- (i) ein kohlenmonoxidhaltiger Gasstrom,
- (ii) ein erster flüssiger Strom, bestehend aus Wasser und Dimethylcarbonat in Mengen, die im wesentlichen den entsprechenden Mengen hievon gleich sind, die in der Reaktionskammer in (a) gebildet werden;



(iii) ein zweiter flüssiger Strom, bestehend aus Methanol und dem Überschuß an Dimethylcarbonat über die in der Reaktionskammer in (a) gebildete Dimethylcarbonatmenge, abgetrennt werden;
wobei der Gasstrom (i) und der Flüssigkeitsstrom (iii) zur Reaktionskammer von (a) recycelt werden und der flüssige Strom (ii) gewonnen wird.

3. Verfahren nach Anspruch 1 oder 2, dadurch gekennzeichnet, daß während der Reaktion in (a) das Verfahren mit einem Katalysator ausgeführt wird, der als Kupfer-(I)-chlorid, Kupfermethoxychlorid, Kupferchlorhydroxid oder als ein durch Inkontaktbringen von Kupferchloriden, -oxiden, -hydroxiden oder -carbonaten gebildetes Gemisch zugeführt wird, welcher Katalysator in einer Menge von 5 bis 30 Gew.-Teilen, ausgedrückt als Kupfer-(I)-chlorid, je 100 Gew.-Teile des flüssigen Reaktionsgemisches zugegen ist.
4. Verfahren nach Anspruch 1 oder 2, dadurch gekennzeichnet, daß in dem flüssigen Reaktionsgemisch in (a) die Methanolkonzentration im Bereich von 30 bis 80 Gew.-% liegt und die Wasserkonzentration im Bereich von 1 bis 10 Gew.-% liegt.
5. Verfahren nach Anspruch 4, dadurch gekennzeichnet, daß das Verfahren mit einem flüssigen Reaktionsgemisch in (a) ausgeführt wird, das eine Zusammensetzung innerhalb der folgenden Bereichsgrenzen aufweist:
 - * Methanol 35 bis 70 Gew.-% und
 - * Wasser 2 bis 7 Gew.-%,
 - * wobei der Rest auf 100 % im wesentlichen aus Dimethylcarbonat besteht.
6. Verfahren nach Anspruch 1 oder 2, dadurch gekennzeichnet, daß die Reaktionstemperatur in (a) im Bereich von 70 bis 150°C und vorzugsweise von 120 bis 140°C liegt.
7. Verfahren nach Anspruch 1 oder 2, dadurch gekennzeichnet, daß die Umsetzung in (a) bei einem Druck im Bereich von 15 bis 40 kg/cm² ausgeführt wird.
8. Verfahren nach Anspruch 1 oder 2, dadurch gekennzeichnet, daß zu der Umsetzung in (a) ein Kohlenmonoxid, Sauerstoff und gegebenenfalls Inertgase enthaltender Gasstrom zugeführt wird, wobei die letztgenannten im Gasgemisch in einem Ausmaß von bis zu 50 Vol.-% enthalten sind, wobei ein Molverhältnis von Kohlenmonoxid samt etwaigen möglichen Inertgasen zu Sauerstoff im Bereich von 100:1 bis 20:1 eingehalten wird.

9. Verfahren nach Anspruch 1 oder 2, dadurch gekennzeichnet, daß die Strömungsgeschwindigkeit des in (a) eingespeisten Gasstromes im Bereich von 200 bis 1000 l, bezogen auf Standardtemperatur- und -druckbedingungen, je Liter Nutzvolumen des Reaktors und je Stunde liegt.

10 Revendications

1. Procédé pour la préparation en continu de carbonate de diméthyle, ce procédé comprenant :
 - (a) l'alimentation en méthanol, monoxyde de carbone et oxygène d'une chambre de réaction maintenue dans des conditions de réaction et contenant un mélange réactionnel liquide se composant de méthanol, carbonate de diméthyle, eau, et d'un catalyseur de cuivre ;
 - (b) la vaporisation du mélange réactionnel d'un courant de méthanol, eau et carbonate de diméthyle, qui se développe en même temps que le courant gazeux contenant du monoxyde de carbone ; et
 - (c) la récupération à partir du mélange vaporisé de l'eau et du carbonate de diméthyle en quantités effectivement égales à leurs quantités respectives formées dans la chambre de réaction ; et le recyclage des autres composants vers la chambre de réaction ;
 le procédé étant caractérisé en ce qu'on maintient effectivement constants dans le temps, la composition et le volume du mélange réactionnel liquide, la concentration en méthanol et la concentration en eau étant respectivement maintenues égales à, ou supérieures à, 30 % en poids et égales à ou inférieures à, 10 % en poids, par rapport au poids du même mélange.
2. Procédé selon la revendication 1, caractérisé en ce que :
 - (a) on alimente avec un courant de méthanol, de monoxyde de carbone et d'oxygène à la fois frais et recyclés et de carbonate de diméthyle recyclé, dans une chambre de réaction, un mélange réactionnel liquide ayant une composition et un volume effectivement constants, contenant du méthanol, du carbonate de diméthyle, de l'eau et un catalyseur de cuivre, la concentration en méthanol et la concentration en eau étant maintenues respectivement constantes pour être égales à, ou supérieures à, 30 % en poids, et égales à, ou inférieures à 10 % en poids ;
 - (b) on vaporise (en même temps que le courant gazeux contenant du monoxyde de carbone) le méthanol réactionnel, une quantité d'eau effectivement égale à la quantité d'eau



formée dans la chambre de réaction à l'étape (a) et une quantité de carbonate de diméthyle supérieure à la quantité de carbonate de diméthyle formée dans la chambre de réaction à l'étape (a) ; et

(c) on sépare du courant ainsi vaporisé :

(i) un courant gazeux contenant du monoxyde de carbone,

(ii) un premier courant liquide se composant d'eau et de carbonate de diméthyl, en quantités effectivement égales à leurs quantités respectives formées dans la chambre de réaction lors de l'étape (a) ;

(iii) un second courant liquide se composant de méthanol et de l'excès de carbonate de diméthyle par rapport à la quantité de carbonate de diméthyle formée dans la chambre de réaction à l'étape (a) ;

le courant gazeux (i) et le courant liquide (iii) étant recyclés vers la chambre de réaction de l'étape (a) et le courant liquide (ii) étant récupéré.

3. Procédé selon la revendication 1 ou 2, caractérisé en ce que pendant la réaction à l'étape (a) le procédé est mis en oeuvre avec une alimentation en catalyseur tel que du chlorure cuivreux, du méthoxy chlorure de cuivre, de l'hydroxychlorure de cuivre ou sous forme d'un mélange obtenu en amenant en contact des chlorures, oxydes, hydroxydes ou carbonate de cuivre, ledit catalyseur étant présent en une quantité de 5 à 30 parties en poids, exprimées en chlorure cuivreux, pour 100 parties en poids de mélange réactionnel liquide.

4. Procédé selon la revendication 1 ou 2, caractérisé en ce que, dans le mélange réactionnel liquide de l'étape (a), la concentration en méthanol est comprise entre 30 et 80 % en poids et la concentration en eau est comprise entre 1 et 10 % en poids.

5. Procédé selon la revendication 4, caractérisé en ce qu'on met en oeuvre le procédé avec un mélange réactionnel liquide à l'étape (a) ayant une composition comprise dans les domaines de valeurs suivants :

- méthanol de 35 % à 70 % en poids, et
- eau de 2 à 7 % en poids,
- le complément jusqu'à 100 % en poids étant essentiellement constitué par du carbonate de diméthyle.

6. Procédé selon la revendication 1 ou 2, caractérisé en ce que la température de réaction à l'étape (a) est comprise dans la gamme de 70 et 150°C et de préférence entre 120 et 140°C.

7. Procédé selon la revendication 1 ou 2, caractérisé en ce que la réaction à l'étape (a) s'effectue à une pression comprise entre 15 et 40 kg/cm².

8. Procédé selon la revendication 1 ou 2, caractérisé en ce qu'on ajoute au mélange réactionnel de l'étape (a) un courant gazeux contenant du monoxyde de carbone, de l'oxygène et, facultativement, des gaz inertes, ces derniers étant contenus à un niveau allant jusqu'à 50 % en volume du mélange gazeux, le rapport molaire du monoxyde de carbone plus tous gaz inertes possibles à l'oxygène, étant compris entre 100:1 et 20:1.

9. Procédé selon la revendication 1 ou 2, caractérisé en ce que le débit du courant gazeux ajouté à l'étape (a) est compris entre 200 et 1 000 litres, dans les conditions normales de température et de pression, pour chaque litre de volume utile du réacteur et par heure.

