

DATA MANAGING SYSTEM FOR WORK PRODUCTION LINE

The present invention relates to a data managing system for a work production line for supplying and receiving processing data between a memory disposed on a conveying pallet and a processing station disposed on a conveying passage of the
5 palette.

Conventionally, during manufacturing mechanical apparatus constituted by assembling a plurality of parts, as disclosed in Unexamined Japanese Patent Application (OPI) No.
10 Sho. 60-16348, in case of conveying a work mounted onto a palette through a production line and each of parts is assembled onto the work at each process station, a memory member such as an IC card or the like is disposed on the palette, which memory stores therein processing conditions or
15 inspection data, thereby to obtain data corresponding to the specific work.

However, in case where a plurality of separate lines are required such as, for example, if the production line cannot be constructed continuously in a single line due to a
20 small space, if a cycle time is different between a plurality of assembly lines or if a work is conveyed from an assembly line for each unit to a main assembly line for the products, the palette must be conveyed to the next line while mounting thereon the work. For this reason, it would be intricate to

This Sheet Has Been ReplacedTHIS SHEET HAS BEEN
REPLACED

convey such a palette particularly when the production line is for producing a small scale product such as a recording head of a printing apparatus.

The above problem may be solved to connect between the assembly lines by a transmission line to transmit data for each work. However, this will cause another difficulty that the work must be identified with a specific data.

The present invention was made in view of the foregoing difficulties and problems accompanying the conventional data managing system for production lines.

Accordingly, an object of the present invention is to provide a data managing system for a production line in which a plurality of separated assembly lines are connected together by a conveying pallet. Each of the assembly lines includes a parts supplying station, a process station, an inspection station and a work removing station which are provided along a passage for conveying assembly pallets. A first and second data storage members are disposed on each of the assembly pallets and the conveying pallets, and inspection result is stored in the first data storage member at each of the inspection stations, whereas the data stored in the first data storage member is transferred to the second data storage member at the work removing station, and the data stored in the second data storage member is transferred at the next parts supplying

This Sheet Has Been Replaced



THIS SHEET HAS BEEN
REPLACED

station to a first data storage member of the assembly palette, to correspond to each of the works.

According to the present invention, a plurality of the inspection data obtained in one assembly line are transferred to the second data storage member, and then the data is transferred to the first data storage member of the assembly palette in the next assembly line, corresponding to the specific work. Therefore, according to the present invention, even if the plurality of assembly lines are separated from one another or located far from one another, the inspection data of each work by each assembly line can accurately be maintained. The reliability of managing the quality of works can effectively be maintained.

Embodiments of the invention will now be described by way of example only and with reference to the accompanying drawings, in which:-

Fig. 1 is a block diagram showing one embodiment of assembly line to which the present invention is applied;

Fig. 2 is a perspective view showing the process station and inspection station which constitute the assembly line according to one embodiment of the present invention;

Figs. 3A and 3B show an embodiment of the assembly pallet;

Fig. 4 is a schematic diagram showing an embodiment of an IC card applicable for the present invention;

Fig. 5 is a flowchart showing an operation of the system according to an embodiment of the present invention;

This Sheet Has Been Replaced



THIS SHEET HAS BEEN
REPLACED

Fig. 6 show a condition of storage in an IC card.

The preferred embodiment of the present invention will now be described in detail with reference to accompanying drawings.

Fig. 1 is a block diagram showing one embodiment of assembly line to which the present invention is applied. A parts supplying station 1 where a work conveyed from outside is mounted on an assembly palette 40 described later is disposed at an initial stage of a first assembly line I. The assembly line I includes, along the conveying passage of the assembly palette 40, process stations 2, 2 where the works mounted on the assembly palette 40 are processed and inspection stations 3, 3 where processed dimensions and processed accuracy are measured is disposed immediately after the process station 2. Each of the inspection stations 3, 3 is provided with an IC card reading and writing member 4, so that inspection results of every processed parts are recorded in an IC card mounted on the assembly palette 40.

A work removing station 5 is located at an end of the assembly line I where, after the work is subjected with required processes, the work is removed from the assembly pallet 40 and mounted on a conveying pallet 6 for mounting thereon a plurality of works. The conveying pallet 6 is provided with a storage member such as an IC card 7, for

This Sheet Has Been Replaced



THIS SHEET HAS BEEN
REPLACED

example, having a capacity for storing the inspection data of a plurality of works. IC card reading and writing members 8 and 9 are disposed at the work removing station 5 and a position of waiting for the conveying pallet, respectively, so that the inspection data is read out by the IC card reading and writing member 8 from the IC card mounted on the assembly pallet 40 harmonized with the removal of the work which is provisionally assembled from the assembly pallet 40 at the work removing station 5. At the same time, the data is recorded on the IC card 7 mounted on the conveying pallet 6 by the IC card reading and writing member 9.

A second assembly line II is separately constructed from the first assembly line I, which includes at an initial stage thereof a head parts supplying station 10 where the work which is provisionally assembled by the first assembly line I and conveyed therefrom through the conveying pallet 6 is mounted on an assembly pallet 40 which is the same as that used in the first assembly line I.

IC card reading and writing members 11 and 12 are disposed at a position of waiting for the conveying pallet 6 and the head parts supplying station 10, respectively, so that the data of each work recorded on the IC card in the assembly line I is read out by the IC card reading and writing member 11 and transferred to the IC card reading and writing member 12 and then recorded on the IC card 7 of the assembly pallet 40

This Sheet Has Been Replaced



THIS SHEET HAS BEEN
REPLACED

every time the provisionally assembled work is taken out of the conveying pallet 6.

Similar to the first assembly line I, the second assembly line II includes, along the conveying passage of the assembly pallet 40, process stations 13, 13 where the works mounted on the assembly pallet 40 are processed and an inspection stations 14, 14 where processed dimensions and processed accuracy are measured is disposed immediately after the process station 2. Each of the inspection stations 14 and 14 is provided with an IC card reading and writing member 15 and 16, respectively, so that inspection results of every processed parts are recorded in an IC card mounted on the assembly pallet 40. A head removing station 17 is located at an end of the assembly line II where the work is removed from the assembly pallet 40. The head parts removing station 17 is provided with an IC card reading and writing member 18 for reading out process data of the recording head (work) recorded on the IC card 43 of the assembly pallet 40 and then transferred to a recording device 19.

Fig. 2 is a perspective view showing the process station and inspection station which constitute the assembly line according to one embodiment of the present invention.

The assembly pallets 40 moves on a pair of conveying rails 31, 31 fixedly secured on an upper surface of a base frame 30. Process stations 34 and an inspection station 35 are provided at desired locations as a unit. Combination of such

This Sheet Has Been Replaced



THIS SHEET HAS BEEN
REPLACED

a unit in plural enhances a flexibility of the production line architecture.

Figs. 3A and 3B show an embodiment of the assembly pallet. The assembly pallet is provided with a pallet body 40, a pair of guide grooves 41 at a lower surface of the side wall thereof which are parallel with the assembly line for engaging with the pair of conveying rails 31, and a socket 42 at a bottom of the body 40 for inserting therein the IC card 43. Reference numeral 45 denotes a head for connecting the pallet to an IC card reading and writing member.

Fig. 4 is a schematic diagram showing an embodiment of an IC card applicable for the present invention. A plate like IC card 50 has a semiconductor storage circuit and reading and writing control circuit which are molded by a high-molecular material. The IC card is further provided at a surface thereof a pair of coils 57 and 58 for a transmission of power and signal by non-contact. The coils 57 and 58 are supplied with operational power due to an alternate magnetic field from a recording head 55 when the coils are located at a position facing the recording head. Further, data is transferred between the coils and recording head by a high frequency signal acting as a carrier signal, so that the data from the inspection station is stored in and read from the semiconductor storage circuit.

The operation of the system thus constructed will be described with reference to a flowchart shown in Fig. 5.

This Sheet Has Been Replaced



THIS SHEET HAS BEEN
REPLACED

When a preassembled work is conveyed by a parts conveying pallet (not shown) to a starting point of the production line (Step A), the work is mounted on the assembly pallet 40 by the head supply station 1 (Step B). The assembly
5 pallet 40 is conveyed by a belt-conveyer or the like up to the process stations 2 (Step E), necessary parts are assembled onto the work (Steps F, G) and, after the assembling process (Step H), the pallet 40 is conveyed to the next process station 2 (Step E).

10 The assembly is thus taken place with required process steps. The pallet 40 is then moved to the inspection station 3 (Step I) where the size or relative position of the parts assembled on the work during the assembling processes are measured (Step J). After finishing the measurement (Step K),
15 the data representing the result of the measurement is output by the IC card reading and writing member 4 to the recording head and written in the IC card 43 attached on the assembly pallet 40 with an ID data (Fig. 6, I,II and Step L).

20 After the inspection, the work assembled therewith required parts is transferred to the work removing station 5 which is an end station of the production, where the work mounted on the assembly pallet 40 is removed therefrom by an arm of machine robot or the like and then accommodated in the conveying pallet 6 (Step M). At the same time, the measurement
25 data stored in the IC card 43 attached on the assembly pallet 41 from which the work is removed is read by the IC card

This Sheet Has Been Replaced



THIS SHEET HAS BEEN
REPLACED

reading and writing member 8 provided at the work removing station 5, and the data is transferred to the IC card reading and writing member 9 provided at the conveying pallet 6 through a transmission line and then written in the IC card 7 attached
5 on the conveying pallet 6 (Fig. 6, III and Step N).

The work preassembled as described above is accommodated in the conveying pallet 6 which conveys the work to a start point of the second assembly line II (Step A). At the start point of the second assembly line II each
10 preassembled work is taken out from the conveying pallet 6 with the predetermined sequence by the head parts supplying station 10 and then mounted on the assembly pallet 40 similar to that employed in the first assembly line (Step B). In this case, since the second line is the next to the first assembly line
15 (Step C), the measurement data stored during the former inspection in the storage member (IC card) 7 is read out by the IC card reading and writing member 11 and transferred through the transmission line to an IC card reading and writing member 12. The measurement data thus transferred is then written in
20 the IC card 43 of the assembly pallet 40 mounting thereon the preassembled work (Fig. 6, V and Step D).

After carrying out a predetermined provisional process, the assembly pallet 40 is conveyed to the process station 13 where necessary parts are assembled on the preassembled work
25 (Steps F, G and H) similar to the first assembly line I. Afterwards, the second inspection is taken place at necessary

This Sheet Has Been Replaced



THIS SHEET HAS BEEN
REPLACED

steps by inspection stations 14 (Steps I, J and K). The result of the inspection (measurement) is written in the IC card 43 attached on the assembly pallet 40 by the IC card reading and writing member 15 (Fig. 6, V and Step L).

5 When the assembly pallet 40 is conveyed up to the end of the assembly line after completing the predetermined process steps, the completely assembled work is removed from the assembly pallet 40 at the removing station 17. At the same time, all inspection data is read out by the IC card reading and writing member 43 provided at the assembly pallet 40 and
10 stored in the recording device 19.

 Although the above embodiment is described in case of employing separate two assembly lines, the invention is not limited thereto or thereby. For example, it is apparent that
15 the concept of the present invention may be applied to a product line having three separate assembly lines.

 As described above, according to the present invention, both the assembly pallet and conveying pallet are provided with a data storage member, the inspection result at each inspection
20 station is stored in the data storage member attached on the assembly pallet, and the data stored in the data storage member attached on the assembly pallet is transferred into the storage member provided at the conveying pallet at the work removing station. Therefore, the inspection data for a specific work
25 which must be assembled through a plurality of separated assembly lines can be managed corresponding to the work. Owing

This Sheet Has Been Replaced



THIS SHEET HAS BEEN
REPLACED

to this data managing system, even if one product line is divided into a plurality of assembly lines which are located far from one other, the reliability of managing the quality of works can effectively be maintained.

This Sheet Has Been Replaced



THIS SHEET HAS BEEN
REPLACED

CLAIMS



1 1. A data managing system for a work production line
2 comprising a plurality of assembly lines connecting
3 sequentially to the next line, each assembly line comprising:
4 an assembly pallet for mounting thereon a work, said
5 assembly pallet comprising a data storage means;
6 a parts supplying station where the work conveyed from
7 outside is mounted on said assembly palette;
8 at least one process station where the work mounted on
9 said assembly palette is processed;
10 at least one inspection station where processed work is
11 measured, said inspection station comprises means for reading
12 and writing data of the measurement in said data storage means
13 of said assembly pallet;
14 a work removing station where the work is removed from
15 said assembly pallet and mounted on a conveying pallet for
16 conveying the work to the next assembly line, said conveying
17 pallet comprising a data storage means, said work removing
18 station comprises means for transferring said measurement data
19 stored in said data storage means of said assembly pallet to
20 said data storage means of said conveying pallet.

This Sheet Has Been Replaced



THIS SHEET HAS BEEN
REPLACED



1 2. The data managing system of Claim 1, further
2 comprising a data recording device at an end of the last
3 assembly line for recording therein all data of the work.

1 3. The data managing system of Claim 1, wherein said
2 data storage means of said assembly pallet is an IC card.

1 4. The data managing system of Claim 1, wherein said
2 data storage means of said conveying pallet is an IC card.

1 5. The data managing system of Claim 3, wherein said
2 assembly pallet comprises:

3 a pallet body;

4 a pair of guide grooves disposed at a lower surface of
5 a side wall thereof which are parallel with the assembly line
6 for engaging with a pair of conveying rails; and

7 a socket disposed at a bottom of said body for
8 inserting therein said IC card.

1 6. The data managing system of Claim 3 or 4, wherein
2 said IC card is a plate like card, said IC card comprising:

3 a semiconductor storage circuit and reading and writing
4 control circuit which are molded by a high-molecular material;

5 a pair of coils for a transmission of power and signal
6 by non-contact, said coils are supplied with operational power
7 due to an alternate magnetic field from a recording head of

This Sheet Has Been Replaced



THIS SHEET HAS BEEN
REPLACED



8 said data reading and writing means when said coils are located
9 at a position facing said recording head whereby transferring
10 said data between said coils and said recording head by a high
11 frequency signal acting as a carrier signal.

1 7. A method for managing data for a work production
2 line comprising a plurality of assembly lines connecting
3 sequentially to the next line, comprising steps of:

4 mounting at least one work on an assembly pallet having
5 a data storage member;

6 processing the work mounted on said assembly pallet;
7 inspecting the processed work;

8 writing data of the result of said inspection in said
9 data storage member of said assembly pallet;

10 removing the work from said assembly pallet and
11 mounting the same work on a conveying pallet having a data
12 storage member for conveying the work to the next second
13 assembly line while transferring the data stored in said data
14 storage member of said assembly pallet to said data storage
15 member of said conveying pallet;

16 transferring data stored in said data storage member of
17 said conveying pallet to a storage member of a new assembly
18 pallet in the second assembly line.

This Sheet Has Been Replaced



THIS SHEET HAS BEEN
REPLACED



1 8. The data managing method of Claim 7, further
2 comprising a step of recording all data of the work in a data
3 recording device at an end of the last assembly line.

1 9. The data managing method of Claim 7, wherein said
2 data storage member of said assembly pallet and said conveying
3 pallet is an IC card.

1 10. The data managing method of Claim 7, wherein said
2 IC card is a plate like card, said IC card comprising:

3 a semiconductor storage circuit and reading and writing
4 control circuit which are molded by a high-molecular material;

5 a pair of coils for a transmission of power and signal
6 by non-contact, said coils are supplied with operational power
7 due to an alternate magnetic field from a recording head of
8 said data reading and writing means when said coils are located
9 at a position facing said recording head whereby transferring
10 said data between said coils and said recording head by a high
11 frequency signal acting as a carrier signal.

This Sheet Has Been Replaced



THIS SHEET HAS BEEN
REPLACED