

(12) 特許協力条約に基づいて公開された国際出願

(19) 世界知的所有権機関  
国際事務局



(43) 国際公開日  
2011 年 2 月 17 日(17.02.2011)

PCT

(10) 国際公開番号  
WO 2011/019000 A1


- (51) 国際特許分類:  
*F16K 43/00* (2006.01) *F16K 3/02* (2006.01)  
*E03B 7/07* (2006.01) *F16K 27/00* (2006.01)
- (21) 国際出願番号: PCT/JP2010/063398
- (22) 国際出願日: 2010 年 8 月 6 日(06.08.2010)
- (25) 国際出願の言語: 日本語
- (26) 国際公開の言語: 日本語
- (30) 優先権データ:  
特願 2009-185965 2009 年 8 月 10 日(10.08.2009) JP
- (71) 出願人 (米国を除く全ての指定国について): 株式会社水道技術開発機構 (WATERWORKS TECHNOLOGY DEVELOPMENT ORGANIZATION CO., LTD.) [JP/JP]; 〒5300001 大阪府大阪市北区梅田一丁目 1 番 3 - 2 7 0 0 号 Osaka (JP).
- (72) 発明者; および
- (75) 発明者/出願人 (米国についてのみ): 浅井久和 (ASAI Hisakazu) [JP/JP]; 〒5300001 大阪府大阪市北区梅田一丁目 1 番 3 - 2 7 0 0 号 株式会社水道技術開発機構内 Osaka (JP).
- (74) 代理人: 北村修一郎 (KITAMURA Shuichiro); 〒5300005 大阪府大阪市北区中之島三丁目 3 番 3 号 Osaka (JP).
- (81) 指定国 (表示のない限り、全ての種類の国内保護が可能): AE, AG, AL, AM, AO, AT, AU, AZ, BA, BB, BG, BH, BR, BW, BY, BZ, CA, CH, CL, CN, CO, CR, CU, CZ, DE, DK, DM, DO, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, GT, HN, HR, HU, ID, IL, IN, IS, KE, KG, KM, KN, KP, KR, KZ, LA, LC, LK, LR, LS, LT, LU, LY, MA, MD, ME, MG, MK, MN, MW, MX, MY, MZ, NA, NG, NI, NO, NZ, OM, PE, PG, PH, PL, PT, RO, RS, RU, SC, SD, SE, SG, SK, SL, SM, ST, SV, SY, TH, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, ZA, ZM, ZW.
- (84) 指定国 (表示のない限り、全ての種類の広域保護が可能): ARIPO (BW, GH, GM, KE, LR, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), ユーラシア (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), ヨーロッパ (AL, AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HR, HU, IE, IS, IT, LT, LU, LV, MC, MK, MT, NL, NO, PL, PT, RO, SE, SI, SK, SM, TR), OAPI (BF,

[続葉有]

(54) Title: SLUICE VALVE FOR OPERATIONS

(54) 発明の名称: 作業用仕切弁

[図13]



(57) Abstract: A fluid device installed through the inside of the valve case of a sluice valve for operations is efficiently and easily fixed and coupled to a coupling flange from the outside, in such a way that a sufficient depth is secured for externally installing a coupling cylinder unit on the coupling flange, while seeing to it that a pulling and fixing means is easily installed and that the installation strength is secured. A valve case (32) that is provided with a coupling cylinder unit (32C) which can be installed externally on the coupling flange of a connection pipe from the direction of the pipe axis center is equipped with a valve element (31) which can move freely in a direction perpendicular to the pipe axis center and with a valve operation means (30) for subjecting the valve element (31) to moving operations. In the coupling cylinder unit (32C) in the valve case (32), there is provided a pulling and fixing means for pulling the valve case (32) to the coupling flange, thereby fixing the valve case (32) to the coupling flange. In the coupling cylinder unit (32C) in the valve case (32), there is formed an operation recessed part (32J) for operating a fastener from the backside of the coupling flange, the purpose of the aforementioned fastener being so that the fluid device joined through a flow path in the valve case (32) is fixed and coupled to the coupling flange.

(57) 要約:

[続葉有]



WO 2011/019000 A1