



- (51) **International Patent Classification:**
C08K 5/41 (2006.01) *C09D 183/02* (2006.01)
- (21) **International Application Number:**
PCT/EP2011/073938
- (22) **International Filing Date:**
23 December 2011 (23.12.2011)
- (25) **Filing Language:** English
- (26) **Publication Language:** English
- (30) **Priority Data:**
61/428,346 30 December 2010 (30.12.2010) US
- (71) **Applicant (for all designated States except US):** **AKZO NOBEL COATINGS INTERNATIONAL B.V.** [NL/NL]; Velperweg 76, NL-6824 BM Arnhem (NL).
- (72) **Inventor; and**
- (75) **Inventor/Applicant (for US only):** **CROWLEY, Stephen John** [US/US]; 16022 Lakegrove Forest, Tomball, Texas 77377 (US).
- (74) **Agent:** **DE VRIES, Adriaan Jacobus c.s.**; Akzo Nobel N.V., Legal, IP & Compliance, P.O. Box 9300, NL-6800 SB Arnhem (NL).
- (81) **Designated States (unless otherwise indicated, for every kind of national protection available):** AE, AG, AL, AM, AO, AT, AU, AZ, BA, BB, BG, BH, BR, BW, BY, BZ, CA, CH, CL, CN, CO, CR, CU, CZ, DE, DK, DM, DO, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, GT, HN, HR, HU, ID, IL, IN, IS, JP, KE, KG, KM, KN, KP, KR, KZ, LA, LC, LK, LR, LS, LT, LU, LY, MA, MD, ME, MG, MK, MN, MW, MX, MY, MZ, NA, NG, NI, NO, NZ, OM, PE, PG, PH, PL, PT, QA, RO, RS, RU, RW, SC, SD, SE, SG, SK, SL, SM, ST, SV, SY, TH, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, ZA, ZM, ZW.
- (84) **Designated States (unless otherwise indicated, for every kind of regional protection available):** ARIPO (BW, GH, GM, KE, LR, LS, MW, MZ, NA, RW, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AL, AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HR, HU, IE, IS, IT, LT, LU, LV, MC, MK, MT, NL, NO, PL, PT, RO, RS, SE, SI, SK, SM, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).
- Published:**
— with international search report (Art. 21(3))

(54) **Title:** LOW HUMIDITY CURE FOR MOISTURE CURABLE COATINGS

(57) **Abstract:** The invention is directed to a low humidity cure moisture curable coating composition which includes a moisture cure binder component that includes: a moisture curable binder material and at least one organic solvent; and a humectant component that includes a slow evaporating volatile humectant; wherein the humectant is present in an amount sufficient to increase the cure rate of the coating and to provide a cured coating having acceptable mechanical and cosmetic properties at a relative humidity of 50% or lower; and the invention is also directed to a method for curing moisture curable coating compositions under low humidity conditions.



WO 2012/089659 A1