

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
9 September 2005 (09.09.2005)

PCT

(10) International Publication Number
WO 2005/084092 A2

(51) International Patent Classification⁷: **H05K 3/00**,
G12B 21/02, G02F 7/00, 1/1362, C09D 11/00

(21) International Application Number:
PCT/US2005/006009

(22) International Filing Date: 25 February 2005 (25.02.2005)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
60/547,091 25 February 2004 (25.02.2004) US

(71) Applicant (for all designated States except US):
NANOINK, INC. [US/US]; 1335 W. Randolph Street,
Chicago, IL 60607 (US).

(72) Inventors; and

(75) Inventors/Applicants (for US only): **AMRO, Nabil**
[LB/US]; 10113 Old Orchard Court, Apt. 3D, Skokie,
IL 60076 (US). **DEMERS, Linette** [CA/US]; 1735
Washington Street, Evanston, IL 60202 (US). **DISAWAL,**
Sandeep [US/US]; c/o NanoInk, Inc., 1335 Randolph
Street, Chicago, IL 60607 (US). **ZHANG, Hua** [CN/US];
1228 Oak Avenue, Apt.5, Evanston, IL 60202 (US).
ELGHANIAN, Robert [US/US]; 541 Laverne Avenue,
Wilmette, IL 60091 (US). **CRUCHON-DUPEYRAT,**

Sylvain [FR/US]; 605 West Madison #2913, Chicago, IL
60661 (US). **BUSSAN, John** [US/US]; 1353 Middleburg
Road, Naperville, IL 60540 (US).


(74) Agents: **MAEBIUS, Stephen, B.** et al.; Foley & Lard-
ner LLP, 3000 K Street, NW, Suite 500, Washington, D.C.
20007-5143 (US).

(81) Designated States (unless otherwise indicated, for every
kind of national protection available): AE, AG, AL, AM,
AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN,
CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI,
GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE,
KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD,
MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG,
PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SM, SY, TJ,
TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA,
ZM, ZW.

(84) Designated States (unless otherwise indicated, for every
kind of regional protection available): ARIPO (BW, GH,
GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM,
ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM),
European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI,
FR, GB, GR, HU, IE, IS, IT, LT, LU, MC, NL, PL, PT, RO,
SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN,
GQ, GW, ML, MR, NE, SN, TD, TG).

[Continued on next page]

(54) Title: MICROMETRIC DIRECT-WRITE METHODS FOR PATTERNING CONDUCTIVE MATERIAL AND APPLICATIONS TO FLAT PANEL DISPLAY REPAIR



(57) Abstract: A new, low temperature method for directly writing conductive metal traces with micron and sub-micron sized features. In this method, a flat beam is used, such as an AFM cantilever, with or without a tip, to draw traces of metal precursor ink onto a substrate. The dimensions of the metal traces can be directly controlled by the geometry of the cantilever, so that one can controllably deposit traces from 1 micron to over 100 microns wide with microfabricated cantilevers. Cantilevers with sharp tips can be used to further shrink the minimum features sizes to sub-micron scale. The height of the features can be increased by building layers of similar or different material. To obtain highly conductive and robust patterns with this deposition method, two general ink formulation strategies were designed. The key component of both ink systems is nanoparticles with diameters less than 100 nm. Because nanoparticles typically have significantly lower melting points than the bulk material, one can fuse, sinter, or coalesce collections of discrete particles into continuous (poly)crystalline films at very low temperatures (less than about 300 °C, and as low as about 120 °C). In the first strategy, one can disperse hydrocarbon-capped nanoparticles in a suitable solvent, deposit them on a surface in the form of a pattern, and then anneal the film by heating to form continuous metallic patterns. In the second strategy, one can deliver metal compounds to the surface in the presence of a reducing matrix and then form nanoparticles in situ by heating that subsequently coalesce to form continuous metallic patterns. In studies with platinum and gold inks, both nanoparticle-based methods yield micron sized traces on glass and oxidized silicon that have low resistivity (4 microhm.cm), and excellent adhesion properties.



WO 2005/084092 A2



Published:

— without international search report and to be republished
upon receipt of that report

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.