

PCT

WORLD INTELLECTUAL PROPERTY ORGANIZATION
International Bureau



pos's copy!
990297-3

INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification ⁶ : B65D 83/54		A1	(11) International Publication Number: WO 98/29321
			(43) International Publication Date: 9 July 1998 (09.07.98)
(21) International Application Number: PCT/EP97/07224		(81) Designated States: AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, CA, CH, CN, CU, CZ, DE, DK, EE, ES, FI, GB, GE, GH, HU, ID, IL, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, UA, UG, US, UZ, VN, YU, ZW, ARIPO patent (GH, GM, KE, LS, MW, SD, SZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, ML, MR, NE, SN, TD, TG).	
(22) International Filing Date: 23 December 1997 (23.12.97)			
(30) Priority Data: 9626960.0 27 December 1996 (27.12.96) GB			
(71) Applicant (for all designated States except US): GLAXO GROUP LIMITED [GB/GB]; Glaxo Wellcome House, Berkeley Avenue, Greenford, Middlesex UB6 0NN (GB).			
(72) Inventors; and (75) Inventors/Applicants (for US only): DI GIOVANNI, Patrick [FR/FR]; Valois Pharm, Route des Falaises, F-27100 Le Vaudrueil (FR); ROGERSON, Cheryl, Vanessa [GB/GB]; Cotherstone House, 5 Marshalls Piece, Stepping, Great Dunmow, Essex CM6 3R2 (GB).			
(74) Agent: QUILLIN, Helen, Kaye; Glaxo Wellcome plc, Glaxo Wellcome House, Berkeley Avenue, Greenford, Middlesex UB6 0NN (GB).		Published With international search report. Before the expiration of the time limit for amending the claims and to be republished in the event of the receipt of amendments.	

(54) Title: VALVE FOR AEROSOL CONTAINER

(57) Abstract

Valve for an aerosol container for dispensing a suspension of a substance in a liquid propellant contained therein. The valve comprises a valve body (1) having at least one orifice (16) to allow a quantity of the suspension to pass from the container into the valve. The valve further comprises a ring (18) disposed around the valve body (1), the ring being positioned below the at least one orifice to reduce the volume of suspension that can be accommodated within the container below the at least one orifice when the container is orientated with the valve at the bottom, the ring having at least one portion of reduced axial thickness to provide a trough (19) around the valve body below the at least one orifice.

