

THIS SHEET HAS BEEN
REPLACED

DESCRIPTION

COMPONENT FEEDING METHOD AND APPARATUS THEREFOR

TECHNICAL FIELD

5 The present invention relates to a component feeding method, as well as an apparatus therefor, for feeding components, which are to be mounted on boards, at their mounting positions in an electronic component mounting machine.

BACKGROUND ART

10 Component feeding apparatus in electronic component mounting machines are provided in several types, such as taping-compatible, tray-compatible or stick-compatible types depending on the style of packing of electronic components. Among others, the taping-
15 ~~compatible~~ type component feeding apparatuses are capable of feeding electronic components with high speed and in a wide variety of component types, so that they are widely used particularly in high-speed, high-production type mounting machines out of electronic component mounting
20 machines.

 Some of the component feeding apparatuses used in high-speed, high-production type mounting machines are



equipped with a plurality of component feeding tables. An example of the arrangement of such a component feeding apparatus is shown in Fig. 7.

Referring to the individual functional parts in the example of Fig. 7, a plurality of component feeding tables 701 to 704 each have a driving motor incorporated therein one by one, so that the component feeding tables are enabled to operate independently of one another. Each of components placed on each component feeding table is positioned to a component suckup position 709, and fed from the component feeding table to the mounting machine.

As for the component replacement position where electronic components are replenished upon exhaustion of the electronic components on the component feeding table, there are arranged a component replacement position 705 for the component feeding table 701, a component replacement position 706 for the component feeding table 702, a component replacement position 707 for the component feeding table 703, and a component replacement position 708 for the component feeding table 704. When any of the component feeding tables have exhausted components, the component feeding table has to move to its specified component replacement position. Whereas the example of Fig. 7 is shown in a case where the number of motors is the same as that of the component feeding

THIS SHEET HAS BEEN
REPLACED

This Sheet Has Been Replaced



tables in one-to-one correspondence, there are some cases where the number of motors is smaller than that of the component feeding tables.

5 The purpose of preparing a plurality of component feeding tables is to keep productional operation of the electronic component mounting machine continued without being interrupted and thereby to prevent the machine from lowering in availability even during the periods during which an exhausted component feeding table is moved to the component replacement position and the electronic components are replenished. This is accomplished by, during such periods, feeding the same type of components which have previously been prepared on a component feeding table other than the exhausted component feeding table, not from the exhausted component feeding table but from the other component feeding table to the component suckup position.

10

15

For example, the component feeding tables 701 and 702 are used as one set of component feeding tables, and the same components as those placed on the component feeding tables 701 and 702 are placed on the component feeding tables 703 and 704, respectively. Then, the production is started with the set of component feeding tables 701 and 702. Those component feeding tables, upon an occurrence of exhaustion of components, are changed

20

25

over to the set of the component feeding tables 703 and 704, and the component feeding tables 701 and 702 are moved to the component replacement positions 705 and 706, respectively. Then, replenishing components onto the component feeding tables 701 and 702, if done completely while the production is continued with the component feeding tables 703 and 704, allows the productional operation of the mounting machine to be continued even when the component feeding tables 703 and 704 in turn come to exhaustion of components.

As for the factors in lowering the availability of the equipment, the interruption of productional operation due to exhaustion of the components that are being fed is one of the greatest factors. Therefore, electronic-component mounting equipment has been demanded that the production can be continued as much as possible even upon exhaustion of components, while component replenishment can be carried out. The tooling change at a change of the production model is also a factor that lowers the availability of the electronic-component mounting equipment. As a result, the equipment has also been demanded to carry out the tooling change at the same time as the productional operation or to reduce the working time.

However, with the component feeding method and apparatus therefor of the prior art as described above, there is a need of previously selecting such an operational mode that the combination of component feeding tables is free from any difficulty in continued production upon exhaustion of components, so that the combination of component feeding tables is greatly limited, as an issue.

As an example of those combinations, one combination is shown in Fig. 8, which shows an operational mode in which production can be continued even when exhaustion of components has occurred to component feeding tables. Referring to Fig. 8, operational states 800 and 810 show operational modes in which component feeding tables 801 and 802 and component feeding tables 803 and 804 are operated in combination as one set of component feeding tables, respectively. In this operational mode, upon an occurrence of exhaustion of components during the production with the component feeding tables 801 and 802 (shown by the operational state 800), the component feeding tables 801 and 802 are moved to their component replacement positions, while the component feeding tables 803 and 804 are moved to a predetermined specified component suckup position (shown by the operational state 810), and the productional

operation of the electronic-component mounting equipment is continued with the components on the component feeding tables 803 and 804.

Also referring to Fig. 8, operational states
5 820 and 830 show an operational mode in which component feeding tables 821 and 824 are not used for production. In this operational mode, upon an occurrence of exhaustion of components during the production with a component feeding table 822 (shown by the operational
10 state 820), the component feeding table 822 is moved to its component replacement position, while a component feeding table 823 is moved to the component suckup position (shown by the operational state 830), and the productional operation of the electronic-component
15 mounting equipment is continued with the components on the component feeding table 823.

Given an operational mode in such a combination of component feeding tables as described above, even if exhaustion of components has occurred to the component
20 feeding tables, the productional operation of the electronic-component mounting equipment can be carried out without interruptions. However, with the combination of component feeding tables other than that shown in Fig. 8, the production would inevitably be interrupted upon

occurrences of exhaustion of components, such that the productivity of equipment would be lowered.

For example as shown in Fig. 9, in an operational mode that production is started initially with a component feeding table 901 without using component feeding tables 903 and 904 for production and with the same type of components as on the component feeding table 901 placed on a component feeding table 902, even when components have been exhausted during the production with the component feeding table 901 (shown by an operational state 900), the same type components are fed with the component feeding table 902 (shown by an operational state 910) so that the production can be continued without interruption. However, upon exhaustion of components of the component feeding table 902 in this state, if the component replenishment to the component feeding table 901 has been completed, the apparatus can move to the operational state 900 so that the production can be continued, but if the component replenishment to the component feeding table 901 has not been completed yet, the apparatus comes to an operational state 920 such that the productional operation of the equipment would inevitably be interrupted.

Besides, even if the apparatus can move to the operational state 900, components could not be

replenished to the component feeding table 902 because the exhausted component feeding table 902 is not in the component replacement position. In this case, to execute the component replenishment on the exhausted component feeding table 902, the apparatus would necessarily come to the operational state 920, such that the production operation would have to be interrupted in the end.

As shown above, an attempt to eliminate the interruption of production upon an occurrence of exhaustion of components in component feeding tables would involve limitations in the combination of component feeding tables as an operational mode for the apparatus, as an issue.

DISCLOSURE OF INVENTION

Accordingly, an object of the present invention is to provide a component feeding method, as well as an apparatus therefor, which are capable of minimizing interruption of production upon an occurrence of component exhaustion and thereby improving the productivity of equipment without limiting the combination of component feeding tables which are provided to a plural number of quantity.

In accomplishing these and other aspects, according to a first aspect of the present invention,

THIS SHEET HAS BEEN REPLACED

there is provided a component feeding apparatus comprising three or more component feeding tables arrayed on a straight line on a base which are replenished with components at component replacement positions, the component replacement positions being disposed, relative to a component suckup position provided at one place on the base, to a number of a number determined based on a total number of the using tables of the component feeding tables, the number of component replacement positions being expressed as (the total number of the using component feeding tables - 1) $\times$ 2.

According to a second aspect of the present invention, there is provided a component feeding apparatus as defined in the first aspect, wherein the component replacement positions of a number of (the total number of the using component feeding tables - 1) are disposed at each of both sides of the composition suckup position.

According to a third aspect of the present invention, there is provided a component feeding apparatus as defined in the first aspect, further comprising a control unit comprises parts for:

setting sequence numbers of the component replacement positions based on their distances from the component suckup position;

This Sheet Has Been Replaced



setting sequence numbers and component-replacement directions of the using component feeding tables based on the set sequence numbers of the component replacement positions;

5 determining, upon occurrence of component exhaustion of the component feeding table, a component replacement position for the component-exhausted component feeding table based on the set sequence numbers and component-replacement directions of the component feeding tables; and

10

controlling to move the component-exhausted component feeding table to the determined component replacement position in the component-replacement direction thereof.

15 According to a fourth aspect of the present invention, there is provided a component feeding apparatus as defined in the third aspect, wherein in the part for setting the sequence numbers and component-replacement directions of the using component feeding

20 tables based on the set sequence numbers of the component replacement positions, the sequence numbers of the component feeding tables are determined in ascending order from 0 in the same direction as that in which the sequence numbers of the component replacement positions

25 have been set and the component replacement direction of

THIS SHEET HAS BEEN
REPLACED

This Sheet Has Been Replaced



THIS SHEET HAS BEEN
REPLACED

the component feeding table is determined in a direction opposite to the ascending-order direction in which the sequence numbers of the component replacement positions have been set, and

5 in the part for setting the sequence numbers and component-replacement directions of the using component feeding tables, the component replacement position for the component-exhausted component feeding table is assigned a component replacement position having the same
10 sequence number as the sequence number of the component feeding table searched out in the same direction as the component-replacement direction of the component feeding table.

 According to a fifth aspect of the present
15 invention, there is provided a component feeding method using a component feeding apparatus comprising three or more component feeding tables arrayed on a straight line on a base which are replenished with components at component replacement positions, the component
20 replacement positions being disposed, relative to a component suckup position provided at one place on the base, to a number of a number determined based on a total number of the using tables of the component feeding tables, the number of component replacement positions

This Sheet Has Been Replaced



12

being expressed as (the total number of the using component feeding tables - 1) $\times$ 2,

the method comprising:

5 setting sequence numbers of the component replacement positions based on their distances from the component suckup position;

10 setting sequence numbers and component-replacement directions of the using component feeding tables based on the set sequence numbers of the component replacement positions;

 setting sequence numbers and component-replacement directions of the using component feeding tables based on the set sequence numbers of the component replacement positions; and

15 moving the component-exhausted component feeding table to the determined component replacement position in the component-replacement direction thereof.

 According to a sixth aspect of the present invention, there is provided a component feeding method as defined in the fifth aspect, wherein in setting the
20 sequence numbers and component-replacement directions of the using component feeding tables based on the set sequence numbers of the component replacement positions, the sequence numbers of the component feeding tables are
25 determined in ascending order from 0 in the same

This Sheet Has Been Replaced



THIS SHEET HAS BEEN
REPLACED

THIS SHEET HAS BEEN
REPLACED

direction as that in which the sequence numbers of the component replacement positions have been set and the component replacement direction of the component feeding table is determined in a direction opposite to the ascending-order direction in which the sequence numbers of the component replacement positions have been set, and in setting the sequence numbers and component-replacement directions of the using component feeding tables, the component replacement position for the component-exhausted component feeding table is assigned a component replacement position having the same sequence number as the sequence number of the component feeding table searched out in the same direction as the component-replacement direction of the component feeding table.

With this arrangement, components can be replenished without interrupting the production upon component exhaustion, by moving a component feeding table that is not in the component suckup position necessarily to any one of the component replacement positions regardless of the combination of component feeding tables.

With this method, when a component feeding table has exhausted components, components can be replenished without interrupting the production upon

This Sheet Has Been Replaced



component exhaustion, by promptly determining the component replacement position for the exhausted component feeding table and moving to the component replacing work.

5 In addition, the sequence numbers of component replacement positions are set, for example, by a function as shown as one example in Fig. 3. In addition, the sequence numbers and component-replacement directions of the plurality of component feeding tables are set, for
10 example, by a function as shown as one example in Fig. 4, while the component replacement position for an exhausted component feeding table is determined, for example, by a function as shown as one example in Fig. 5.

BRIEF DESCRIPTION OF DRAWINGS

15 These and other aspects and features of the present invention will become clear from the following description taken in conjunction with the preferred embodiments thereof with reference to the accompanying drawings, in which:

20 Fig. 1 is a schematic view showing the arrangement of the component feeding apparatus according to an embodiment of the present invention;

 Fig. 2 is a flow chart showing the component feeding method of the embodiment;

Fig. 3 is an explanatory view of setting the sequence numbers of the component replacement positions in the embodiment;

5 Fig. 4 is an explanatory view of setting the sequence numbers and component-replacement direction on the component feeding tables in the embodiment;

Fig. 5 is an explanatory view of the component-replacement-position decision function in the embodiment;

10 Fig. 6 is an explanatory view of the component feeding method according to an another embodiment of the present invention;

Fig. 7 is a schematic view showing the arrangement of a component feeding apparatus according to the prior art;

15 Fig. 8 is an explanatory view of a component feeding method according to the prior art; and

Fig. 9 is an explanatory view of another component feeding method according to the prior art.

BEST MODE FOR CARRYING OUT THE INVENTION

20 Before the description of the present invention proceeds, it is to be noted that like parts are designated by like reference numerals throughout the accompanying drawings.

Hereinbelow, a component feeding method and a component feeding apparatus, which show an embodiment of the present invention, are explained in detail with reference to the accompanying drawings.

5 Fig. 1 schematically shows production equipment in which the component feeding apparatus of the present embodiment is incorporated. The component feeding apparatus has four component feeding tables 101, 102, 103, 104, and has component replacement positions 105, 106, 107, 108, 109, 110 for occurrences of component exhaustion. Like this, in the case of the production equipment with this arrangement, the number of component replacement positions is six according to Equation 1: (total number of component feeding tables - 1) $\times$ 2 (which is referred to as Equation 1), based on that the total number of component feeding tables is four. This arrangement enables any component feeding table out of a component suckup position 111 to be necessarily located at any one of the component replacement positions 105 to 110. In Fig. 1, reference numeral 45 denotes a rotary head having a plurality of suction heads each for sucking a component at the component suckup position 111, 46 denotes a board to which the suckup component is mounted, denotes a component mounting apparatus, 48 denotes a guide rail for guiding the component feeding tables each

10
15
20
25

having a drive device for reciprocally moving on the guide rail, 41 denotes a control unit of the component mounting apparatus 47 connected to and driving the rotary head 45, all of the component feeding tables and etc.,
5 and 42 denotes an input device.

Fig. 2 is a flow chart showing the component feeding method of this embodiment.

Referring to Fig. 2, first, the number of component replacement positions relative to the number of component feeding tables to be used for production is
10 previously calculated. This is intended to allow all the component feeding tables to effectively function at all times in the component feeding apparatus and component feeding method of this embodiment even when out of use in
15 the production. It is essential that the total number of component feeding tables to be used in the production as well as the number of component replacement positions satisfy the function shown in Equation 1. Hereinbelow, in this embodiment, a case is explained in which all the
20 component feeding tables are used for the production as shown in Fig. 1. Further, the setting of sequence numbers of the component replacement positions, the setting of sequence numbers and component-replacement direction on the component feeding tables are determined

by functions shown in Figs. 3 and 4, respectively (step #201).

Fig. 3 gives a simplified explanation of the function for implementing the setting of sequence numbers on the component replacement positions, where examples of the setting of sequence numbers are shown. The setting of sequence numbers on the component replacement positions is accomplished by numbering the component replacement positions in ascending order from 0 in sequence with the component suckup position taken as the start point, and by numbering the rest of the component replacement positions in ascending order from 0 in the opposite direction to the component suckup position. As examples of the setting of sequence numbers on the component replacement positions, there are shown cases where the number of component replacement positions is four, where the number is six, and where the number is eight. In Fig. 3, reference character T denotes a component feeding table.

Fig. 4 gives a simplified explanation of the function for setting the sequence numbers and component-replacement direction on the component feeding tables, where examples thereof are shown. The setting of sequence numbers on the component feeding tables has been accomplished by arraying the component feeding tables in

a row and by numbering them in ascending order from 0, with their physical direction identical to that of the component replacement positions assigned in Fig. 3. Meanwhile, the component-replacement direction of the component feeding tables has been set by taking, as initial data, an order opposite to the ascending order in which the sequence numbers of component feeding tables are set. As examples of setting the sequence numbers and component-replacement direction on the component feeding tables, there are shown cases where the total number of component feeding tables is three, four and five. In Fig. 4, reference character T denotes a component feeding table.

With these initial settings prepared prior to the start of production by the equipment, the production is started. After waiting for an occurrence of component exhaustion (step #202), when component exhaustion has occurred, the component-feeding-table sequence number and component-replacement direction assigned to the exhausted component feeding table are given to a component-replacement-position decision function fp, so that the component replacement position to which the component feeding table should be moved is determined (step #203). The contents of this component-replacement-position decision function fp are shown in Fig. 5, where an

example of decision contents is shown as well. In Fig. 5, for example, upon an occurrence of component exhaustion, if the sequence number of the exhausted component feeding table is 0, i.e., if the 0-placed component feeding table that has currently been in the suckup position has exhausted as shown in a decision state 500, a component replacement position 510 is given as the component replacement position for the relevant component feeding table.

Now that the component replacement position to which the 0-placed component feeding table should be moved has been determined as 5110, the exhausted 0-placed component feeding table is moved to the position 510 for replenishing components thereon and a next 1-placed component feeding table is moved to the component suckup position in the determined direction for sequential component mounting operation under a predetermined component mounting program as shown in the state 501 (step #204). Then, the component-replacement direction data of the 0-placed component feeding table moved to the component replacement position 510 is reversed (step #205, decision state 501). This reversal is to move the 0-placed table to a component replacement position reverse to that of the last time upon another occurrence of component exhaustion after the components have been

replenished and fed to the component suckup position once again. Then, when 1-placed component feeding table has exhausted, the 1-placed component feeding table is moved to the 1-placed component replacement position adjacent to the position 510 for replenishing components thereon while the 2-placed component feeding table is moved to the component suckup position for sequential component mounting operation under the component mounting program as shown in the state 502.

10 In the similar manner, the 2-placed component feeding table is located at the component suckup position and then moved to the component replacement position when has exhausted while the 3-placed component feeding table is moved to the component suckup position and the component-replacement direction data of the 3-placed component feeding table moved to the component suckup position is reversed as shown in the states 503 and 504. Then, the 3-placed component feeding table has exhausted, the 3-placed table is moved to the 3-placed component replacement position for replenishing components thereon while the 2-placed and component-replenished component feeding table is moved to the component suckup position. In such a manner, the 2-placed and 1-placed and component-replenished component feeding tables are sequentially moved to the component suckup position and

then the 2-placed and 1-placed component replenishment positions in a manner opposite to the above manner. Then, the 0-placed and component-replenished component feeding table is moved to the component suckup position and the component-replacement direction data of the 3-placed component feeding table moved to the component suckup position is reversed as shown in the state 500. Then, when the 0-placed component feeding table has exhausted, the 0-placed table is moved to the component replacement position 510 as described above. Then, the above manner is repeated under the program.

In order to perform the operations, the component feeding apparatus comprises the control unit 41. The control unit 41 comprises a first part for setting sequence numbers of the component replacement positions 105-110; a second part for setting sequence numbers and component-replacement directions of the using component feeding tables 101-104; a third part for determining a component replacement position for the component-exhausted component feeding table; and a fourth part for controlling to move the component-exhausted component feeding table to the determined component replacement position.

The first part is performed to set sequence numbers of the component replacement positions 105-110

based on their distances from the component suckup position 111 by utilizing information inputted by an operator with an input device 42 such as a keyboard or a mouse or information read from a memory or a recording medium such as a CD-ROM. The second part is performed to set sequence numbers and component-replacement directions of the using component feeding tables 101-104 based on the set sequence numbers of the component replacement positions 105-110 by utilizing information inputted by the operator with the input device 42 or information read from the memory or the recording medium. The fourth part is performed to determine, upon occurrence of component exhaustion of the component feeding table, a component replacement position for the component-exhausted component feeding table based on the set sequence numbers and component-replacement directions of the component feeding tables. The fourth part is performed to control to move the component-exhausted component feeding table to the determined component replacement position in the component-replacement direction thereof. In the second part for setting the sequence numbers and component-replacement directions of the using component feeding tables based on the set sequence numbers of the component replacement positions, the sequence numbers of the component feeding tables are determined in ascending

order from 0 in the same direction as that in which the sequence numbers of the component replacement positions have been set and the component replacement direction of the component feeding table is determined in a direction
5 opposite to the ascending-order direction in which the sequence numbers of the component replacement positions have been set, and in the second part for setting the sequence numbers and component-replacement directions of the using component feeding tables, the component
10 replacement position for the component-exhausted component feeding table is assigned a component replacement position having the same sequence number as the sequence number of the component feeding table searched out in the same direction as the component-replacement direction of the component feeding table.
15

The above operation will be effected each time component exhaustion occurs. Thus, by replenishing components to the component feeding table that is in the component replacement position upon component exhaustion
20 in turns at the component replacement position, the equipment is enabled to run for long time without lowering the equipment productivity.

Although the above embodiment has been described by way of example on a case where four
25 component feeding tables are involved, the component

feeding apparatus can produce similar effects with a similar concept only if the component feeding apparatus has three or more component feeding tables.

5 A component feeding method, as well as an apparatus therefor, which show another embodiment different from the foregoing embodiment, are explained below with reference to the accompanying drawings.

Fig. 6 shows the using component feeding apparatus of a modification example of the present invention, where the component feeding method of the present embodiment is applied to operation in which part of the component feeding tables are used. This is a case where only component feeding tables 601 and 602 are used for production by the equipment, and component feeding tables 603 and 604 are not used for production by the equipment. Since the number of component feeding tables is two, it can be seen from Equation 1 that the necessary number of component replacement positions is two. Therefore, only two out of the component replacement positions shown in an operational state 600 of Fig. 6 are used. In terms of the arrangement of the component feeding apparatus in this embodiment, the component feeding tables and the component replacement positions in the component feed section are discussed on line as shown in Figs. 3 and 4, and their positional relationship is

10
15
20
25

set with a component suckup position Q1 interposed therebetween. This gives rise to a need of neglecting component replacement positions 606 and 607 as excess component replacement positions. The result is that the component feeding apparatus of this embodiment is applied with the component replacement positions provided as two, 605 and 608.

In an application of the component feeding apparatus of this embodiment to the operational mode of Fig. 6 with the assumptions as shown above, upon an occurrence of component exhaustion in the operational state 600, the component feeding table 601 moves to the component replacement position 605 (shown by operational state 610). Then, the production is continued with the component feeding table 602. When the component feeding table 602 comes to component exhaustion, the apparatus comes to an operational state 620. At this time point, if the component feeding table 601 has completed the component replenishment, the production can be continued without interruption.

As shown above, it can be understood that, whereas the production would be interrupted upon component exhaustion of the component feeding table 601 with the conventional component feeding apparatus (see Fig. 9), the production can be continued without

interruption according to the component feeding method of this embodiment.

As described hereinabove, according to the present invention, components can be replenished without interrupting the production upon component exhaustion, by moving a component feeding table that is not in the component suckup position necessarily to any one of the component replacement positions regardless of the combination of component feeding tables.

Also, when a component feeding table has exhausted components, components can be replenished without interrupting the production upon component exhaustion, by promptly determining the component replacement position for the exhausted component feeding table and moving to the component replacing work.

Therefore, interruption of production upon component exhaustion can be eliminated as much as possible without limiting the combination of component feeding tables provided to a plural number of quantity, so that the equipment productivity can be improved.

In the embodiments, the component feeding tables of the same number, for example, a number of (the total number of the using component feeding tables - 1) are preferably disposed at each of both sides of the composition suckup position.

The entire disclosure of Internal Application No. PCT/JP97/00139 (Japanese Patent Applications No. 8-11555 filed on January 26, 1996, and No. 8-11641 filed on January 26, 1996) and Japanese Patent Application No. 8-95771 filed on April 18, 1996, including specifications, claims, drawings, and summaries are incorporated herein by reference in its entirety. An example of the component mounting apparatus to which the present invention can be applied is disclosed in the International application and the Japanese Patent Applications No. 8-11555 filed on January 26, 1996, and No. 8-11641 filed on January 26, 1996 incorporated herein by reference in its entirety.

Although the present invention has been fully described in connection with the preferred embodiments thereof with reference to the accompanying drawings, it is to be noted that various changes and modifications are apparent to those skilled in the art. Such changes and modifications are to be understood as included within the scope of the present invention as defined by the appended claims unless they depart therefrom.

THIS SHEET HAS BEEN
REPLACED

This Sheet Has Been Replaced



29

THIS SHEET HAS BEEN
REPLACED

CLAIMS

1. A component feeding apparatus comprising three or more component feeding tables arrayed on a straight line on a base which are replenished with components at component replacement positions, the component replacement positions being disposed, relative to a component suckup position provided at one place on the base, to a number of a number determined based on a total number of the using tables of the component feeding tables, the number of component replacement positions being expressed as (the total number of the using component feeding tables - 1) $\times$ 2.

2. A component feeding apparatus as defined in Claim 1, wherein the component replacement positions of a number of (the total number of the using component feeding tables - 1) are disposed at each of both sides of the composition suckup position.

3. A component feeding apparatus as defined in Claim 1, further comprising a control unit comprises parts for:

setting sequence numbers of the component replacement positions based on their distances from the component suckup position;



* C L M S *



setting sequence numbers and component-replacement directions of the using component feeding tables based on the set sequence numbers of the component replacement positions;

5 determining, upon occurrence of component exhaustion of the component feeding table, a component replacement position for the component-exhausted component feeding table based on the set sequence numbers and component-replacement directions of the component
10 feeding tables; and

controlling to move the component-exhausted component feeding table to the determined component replacement position in the component-replacement direction thereof.

15 4. A component feeding apparatus as defined in Claim 3, wherein in the part for setting the sequence numbers and component-replacement directions of the using component feeding tables based on the set sequence numbers of the component replacement positions, the
20 sequence numbers of the component feeding tables are determined in ascending order from 0 in the same direction as that in which the sequence numbers of the component replacement positions have been set and the component replacement direction of the component feeding
25 table is determined in a direction opposite to the

THIS SHEET HAS BEEN
REPLACED





THIS SHEET HAS BEEN
REPLACED

ascending-order direction in which the sequence numbers of the component replacement positions have been set, and

in the part for setting the sequence numbers and component-replacement directions of the using component feeding tables, the component replacement position for the component-exhausted component feeding table is assigned a component replacement position having the same sequence number as the sequence number of the component feeding table searched out in the same direction as the component-replacement direction of the component feeding table.

5. A component feeding method using a component feeding apparatus comprising three or more component feeding tables arrayed on a straight line on a base which are replenished with components at component replacement positions, the component replacement positions being disposed, relative to a component suckup position provided at one place on the base, to a number of a number determined based on a total number of the using tables of the component feeding tables, the number of component replacement positions being expressed as (the total number of the using component feeding tables - 1) $\times$ 2,

the method comprising:





setting sequence numbers of the component replacement positions based on their distances from the component suckup position;

5 setting sequence numbers and component-replacement directions of the using component feeding tables based on the set sequence numbers of the component replacement positions;

10 setting sequence numbers and component-replacement directions of the using component feeding tables based on the set sequence numbers of the component replacement positions; and

moving the component-exhausted component feeding table to the determined component replacement position in the component-replacement direction thereof.

15 6. A component feeding method as defined in Claim 5, wherein in setting the sequence numbers and component-replacement directions of the using component feeding tables based on the set sequence numbers of the component replacement positions, the sequence numbers of
20 the component feeding tables are determined in ascending order from 0 in the same direction as that in which the sequence numbers of the component replacement positions have been set and the component replacement direction of the component feeding table is determined in a direction
25 opposite to the ascending-order direction in which the





sequence numbers of the component replacement positions have been set, and

5 in setting the sequence numbers and component-replacement directions of the using component feeding tables, the component replacement position for the component-exhausted component feeding table is assigned a component replacement position having the same sequence number as the sequence number of the component feeding table searched out in the same direction as the
10 component-replacement direction of the component feeding table.

BEEN

THIS SHEET HAS BEEN
REPLACED



* C L M S *