SYSTEM AND METHOD OF PRODUCTION OF LIQUEFIED NATURAL GAS

The invention relates to a process to obtain Liquefied Natural Gas (LNG) using air as refrigerant. This process can be performed by using an open or close air refrigerant cycle.

BACKGROUND ART

Natural gas is often available in areas remote from where it will be ultimately used. When carrying it, natural gas is cooled to a temperature of approximately −260 °F (−160 °C) at atmospheric pressure so that it condenses to a liquid called liquefied natural gas (LNG). This LNG is normally transported overseas in appropriate carrier vessels.

Numerous process cycles have been developed for LNG production to provide the large refrigeration requirements. Such cycles typically use a mixed refrigerant comprising light hydrocarbons and optionally nitrogen. e.g., US 4,274,849 patent discloses a mixture of hydrocarbons, at least two, as a refrigerating fluid in a process to liquefy a natural gas.

SUMMARY OF THE INVENTION

The present invention refers to a novel process, system or plant capable of liquefying natural gas from any kind of natural gas fields, and particularly from “offshore” fields, and more particularly from stranded natural gas fields, wherein this process comprises air used as refrigerant.

The system of the present invention comprises a simple and easily reproducible process in all possible locations, preferably “offshore” natural gas fields. This system is particularly advantageous when located in barges for liquefying gas from small natural gas fields located in distant areas, far away from the coast.

Thus, a first aspect of this invention refers to a process to obtain liquefied natural gas which comprises the air used as refrigerant. This process can be developed as an air refrigeration cycle independent from the natural gas stream.

According to the process of the present invention, it is provided an air refrigeration cycle comprising the following steps:

a. compressing the air
b. cooling said compressed air of step (a)
c. expanding said compressed air once cooled at step (b); and
d. using said expanded air (step (c)) for cooling natural gas

In an embodiment of the present invention, the process can also comprise the further step:

e. adding an air make-up in order to compensate the probable air losses.

The air make-up may be treated to remove the CO_2 and water that can be carried using treating facilities known in the art.

In a more preferred embodiment, step (a) of the process is carried out in at least one stage, preferably more than one.

The air refrigerant cycle of the invention can be open or closed. When the air refrigeration cycle is open, the air is continuously taken from the environment, at atmospheric conditions, treated to remove CO_2 and water, used to cool natural gas according to the above steps, and given back to the atmosphere.

When the air refrigeration cycle is closed, the air used to cool natural gas goes back to the beginning of the process (step (a)).

According to the process of the present invention, the natural gas stream passes through the following steps:

a. cooling the natural gas.

b. expanding said natural gas once cooled at step (a), obtaining LNG or LNG and a vapour phase (endflash gas).

Thus, the natural gas can be liquefied completely (LNG), without letting any vapor phase, or not obtaining two phases, liquid and vapor.

In another embodiment of the present invention, if two phases are obtained in step (b), the natural gas stream comprises the further step:

c. separating said phases: liquid (LNG) and vapor (endflash gas).

Optionally, the natural gas stream may further comprise the stage of separating their natural gas liquids (NGL), before liquefaction.

The term "Natural gas liquids (NGL)" as used herein refers to less volatile components of the natural gas, from ethane to higher hydrocarbons (ethane, propane, butane, isobutane and natural gasoline, the latter sometimes called condensate), with minor content of methane.

In another embodiment of the present invention, the natural gas stream can be pre-treated, if required, before cooling it. Various pretreatment arrangements are known in the art. The appropriate pretreatment depends on the location, the type, the precise composition and the level and nature of undesirable contaminants or impurities present in the natural gas feed. It usually could comprise the removal, but are not limited to, Hg, H_2O, CO_2 or H_2S.

This natural gas stream is often passed to the process with a pressure of at least 1 bar, and preferably above 10 bar; it also depends on the location, and the type of the natural gas in the gas-field.

The feed of natural gas can be poor in heavier hydrocarbons and it needs no separation of the natural gas liquids; alternately, should the natural gas is partially rich in heavier hydrocarbons, the natural gas liquids can be kept in the final LNG and separated by fractionation after its transportation to

the final destination. In both cases the natural gas is liquefied as such and this is realized using a single heat exchanger.

In a more preferred embodiment, a natural gas stream particularly rich in heavier hydrocarbons is cooled in two stages:

First, the natural gas is cooled with air, until a suitable temperature that allows condensing as a liquid the required quantity of natural gas liquids (NGL). This stage is carried out through a first heat exchanger. This temperature could depend on the natural gas feed composition, LNG specifications, or on particular requirements in heavier components recoveries and/or purities. This temperature will not be lower than -100ºC.

The result of the previous stage is a light hydrocarbon gaseous stream called lean natural gas. The term “lean natural gas” refers to a stream which contains almost all the methane and the nitrogen of the initial feed, the desired quantity of ethane and small residual quantities of the less volatile components (propane and higher).

Secondly, the lean natural gas goes through a second heat exchanger where it is cooled with the air, until the gas is almost totally or fully liquefied. The temperature at which the NG exits this heat exchanger will not be lower than -163ºC.

As an alternate embodiment, the cooling and liquefaction of a natural gas stream particularly rich in heavier hydrocarbons can be carried out in only one heat exchanger. In this case, the NGL extraction is done after the gas pretreatment and before the cooling and liquefaction.

In another embodiment of the invention, the endflash gas stream, obtained as subproduct in the liquefying of natural gas, is used to cool natural gas and air streams in the process in order to recover its cryogenic energy, and as fuel gas. This fuel could feed gas turbines and it will typically need to be pressurized by a compressor before being introduced to them. The amount of endflash gas obtained can match the quantity of required fuel

gas or it can be part of it or it can be in excess and be used partly for other purposes.

A second aspect of the present invention refers to a system to carry out the previously described process which comprises a continuous stream of natural gas, gas treatment facilities and an air refrigerant cycle.

Air is used as refrigerant in the refrigerant cycle of this system in order to obtain liquefied natural gas. This cycle can preferably be closed loop or open cycle.

In other embodiment, the system comprises the following pieces of equipment:

- Heat exchangers. Any type of heat exchangers may be used in the present invention, although plate-fin heat exchangers are preferred. The minimum number of heat exchangers in the natural gas side is one, although any number of heat exchangers is possible.

  In an embodiment of the present invention, the system can have the exchange of heat between the compressed air stream and the exhaust air after cooling and liquefaction in a separate heat exchanger.

- Expanders. Examples of suitable expanders are a JT-valve (Joule Thompson valve) and a turbine expander, although any type of expander may be employed.

  In the air side, at least one expander is necessary for air expansion. Due to power limitations, the air expanders can be more than one in parallel. The air expanders can be coupled to one or more air compressors in order to recovery their power. Alternately, their power can be utilized for other process purposes, such as power generation.

  In the natural gas side, at least one expander is necessary for expanding the liquid obtained from the heat exchange section.

- Compressors. At least one is required for compressing the air. The number of compression stages in the air cycle depends on the process optimization; it is not a fixed number.

The compression zone preferably comprises one or more heat exchangers (intercoolers) between compressors, in case more than one compressor is used, and one or more heat exchangers (aftercoolers) after the last compressor. The intercoolers and the aftercoolers preferably use water as coolant medium, although air can also be used. Shell -and-tube heat exchangers are preferred.

Another compressor, together with its cooling system, may be required to feed the gas turbines with the endflash gas.

- Compressor drivers. They drive all of the compression stages, except for one if it is coupled to the air expander. Gas turbines or electric motors can be used.

In a more preferred embodiment, the system comprises further equipment:

- Column for NGL extraction. If an NGL fractionation is required, more than one column could be necessary. The column for NGL extraction can be bypassed if no natural gas liquids need to be extracted, so in this case, the natural gas stream can be directed to a further heat exchanger for the liquefaction of natural gas.

In a still preferred embodiment, the system comprises further equipment:

- Endflash vessel.

On a second embodiment of the present invention, this system may be located on a fixed structure such as a platform or a movable structure such as a barge or a ship. Both structures may be used in all types of natural gas fields, including onshore and offshore gas fields. This allows the

exploitation in any kind of deposit, even for exploitation of stranded gas (small volume and remote area fields).

The term “onshore” as used herein refers to something that is on land.

The term “offshore” as used herein refers to something that is in the sea away from the shore; not on the shoreline but out to the sea.

As an alternate embodiment, the system can be located on two separate areas (two different fixed structures, two different movable structures or one fixed structure and one movable structure). One area may be dedicated to the gas pretreatment unit and the NGL extraction facilities, while the other area may be dedicated to the liquefaction unit.

Thus, a third aspect of this invention refers to the use of the system previously described for natural gas fields, and preferably for stranded natural gas fields.

The term “stranded natural gas field” as used herein refers to a natural gas field that has been discovered, but remains unusable for either physical or economic reasons. Economically, because the reserve is too remote from a market for natural gas; or physically, if the gas field is too deep to drill for, or is beneath an obstruction.

Another aspect of this invention relates to the use of the previously described system for producing at least 0.1 MTA (million tonnes per year) of LNG, and preferably, the production of LNG is within the range of 0.5 to 3 MTA.

Unless otherwise defined, all technical and scientific terms used herein have the same meaning as commonly understood by one of ordinary skilled in the art to which this invention belongs. Methods and materials similar or equivalent to those described herein can be used in the practice of the present invention. Throughout the description and claims the word "comprise" and its variations are not intended to exclude other technical

features, additives, components, or steps. Additional objects, advantages and features of the invention will become apparent to those skilled in the art upon examination of the description or may be learned by practice of the invention. The following examples and drawings are provided by way of illustration and are not intended to be limiting of the present invention. Various required subsystems such as valves, control systems, sensors, clamps, and riser support structures have been deleted from the Figures for the purposes of simplicity and clarity of presentation.

BRIEF DESCRIPTION OF THE DRAWINGS

Fig. 1 and **Fig. 3**.- are schematic diagrams of a closed refrigerant cycle according to the invention.

Fig. 2.- is a schematic diagram of an open refrigerant loop according to the invention.

EXAMPLES

The following examples give a description of some of the possible process schemes and operating conditions which do not cover all the possible schemes and conditions which are detailed in the claim list given below.

EXAMPLE 1

Fig.1 shows one example of the present invention as applied to liquefaction of a natural gas feed stream using air as refrigerant. The natural gas feed stream **1** is treated in a conventional pretreatment plant **A** to remove CO_2, H_2S, water and mercury contaminants.

The treated gas, stream **2**, corresponds to a sweet, dry natural gas stream at 15ºC, 30 bar. Stream **2** has a molar composition as given in Table 1 below.

Treated gas composition example	
Component	Mole Fraction
Nitrogen	0.0020
Methane	0.8387
Ethane	0.1204
Propane	0.0274
n-Butane	0.0081
n-Pentane	0.0034

Table 1

Stream **2** enters the liquefaction plant, passing through two heat exchangers **100**, **101** in order to obtain a subcooled high pressure liquid, stream **6**. In the first heat exchanger **100**, the natural gas is precooled to an intermediate temperature of about -69ºC (stream **3**), in order to condense the natural gas liquids. Stream **3** enters a column **B** where the natural gas liquids are extracted as stream **4** at the bottom, while the lean gas, stream **5**, exits the column at the top. Stream **4** will be directed to a fractionation zone, if specific products like propane and butane are required.

The lean natural gas (stream **5**) enters the second heat exchanger **101**, and it is cooled to a temperature of about -130ºC, obtaining a subcooled high pressure liquid stream (stream **6**), which is directed to a JT-valve **102**, through which the stream **6** is expanded adiabatically to 1.1 bar and finally directed to an endflash vessel **103**, which separates liquid and vapor, producing LNG to storage (stream **8**) and endflash gas (stream **9**), both at about –160ºC and 1.1 bar.

Stream **9** is passed back to both heat exchangers **101** and **100**, respectively, where the cryogenic energy of this stream is recovered. Thus, stream **9** exits the heat exchanger **101** at -91ºC, obtaining stream **10**, which is further heated by heat exchanger **100** to the temperature of 15ºC (stream **11**). This vapor stream **11** can be used as fuel within the

plant. In case this fuel feeds gas turbines, stream **11** will typically need to be pressurized by a compressor before being introduced to them.

In this example, the heat exchangers in the natural gas side are plate-fin heat exchangers.

The air refrigeration cycle which transforms gas stream **2** to liquid stream **6** will now be described, starting with air stream **12** which has been exhausted of all or most of its cooling properties by absorbing heat from the feed gas. Stream **12**, at about 34ºC, is at the lowest pressure of the cycle (about 2 bar) and is fed to and recompressed in a multistage compressor unit **104** provided with intercooling and aftercooling stages to produce compressed stream **18**. The compressor zone comprises three compressors **105**, **107** and **109**, with one heat exchanger **106** between compressors **105** and **107**, one heat exchanger **108** between compressors **107** and **109** and one heat exchanger **110** after the last compressor **109**. The intercoolers **106** and **108**, and the aftercooler **110** use water as coolant medium. Compressed stream **18** exits the compressor unit **104** at 40ºC, 30 bar and is directed to heat exchanger **100**, where is precooled to -24ºC by the countercurrent passage of air refrigerant stream **21** and of endflash gas **10**. Stream **18** emerges as stream **19** from heat exchanger **100** and is passed to an expander zone **111** to reduce the pressure and temperature of the air stream **19**, resulting in the stream **24**. The expander zone comprises two turboexpanders **112** and **113** in parallel and is used to provide part of the power for the compressors of the compressor unit **104**. The air stream **24** (which has been expanded in the expander zone **111**) is at 2.1 bar and at a temperature of about -135ºC. It passes through both heat exchangers **101** and **100**, respectively. In the heat exchanger **101**, the stream **24** provides enough cooling to liquefy the natural gas stream **5** to form liquid natural gas (stream **6**). Stream **24** emerges as stream **25** from heat exchanger **101** at a temperature of -73ºC and it enters heat exchanger **100**, where it precools both the natural gas (stream **2**) and the compressed air (stream **18**). Stream **25** leaves the heat exchanger **100** as stream **12** and it starts the cycle again.

The air cycle will have a point for make up in order to compensate for air losses in the air cycle. The air make-up will have to be treated in treating facilities to eliminate the CO_2 and water that it can carry.

Table 2 shows the operating conditions of the main streams of **FIG. 1**.

Stream	P (bar)	T (ºC)
2	30	15
3	29.8	-68.6
5	29.8	-68.6
6	29.6	-130.4
7	1.1	-159.4
8	1.1	-159.4
9	1.1	-159.4
10	1.05	-90.8
11	1	15
12	1.95	34.5
18	30	40
19	29.9	-24.1
24	2.15	-134.6
25	2.05	-73.4

Table 2

EXAMPLE 2

FIG. 2 shows another example of the present invention. The example shown in **FIG. 2** has, as modification in relation to **FIG. 1**, that the air used as refrigerant flows in an open loop.

As in the previous example, the natural gas **1** is treated in the pretreatment plant **A** to remove CO_2, H_2S, water and mercury contaminants (the treated gas, stream **2**, has the composition shown in Table 1) and then liquefied by exchange with cold air in two steps. First, it is precooled in the heat exchanger **100** to a temperature of about -69ºC (stream **3**). It passes through a column **B** where the liquids are extracted as the bottom stream **4**; the lean natural gas exits the column **B** at the top (stream **5**) and enters the second heat exchanger **101**. The liquid stream emerging from heat

exchanger **101** at about -130ºC (stream **6**) is directed to an expansion zone, where is expanded adiabatically in a JT-valve **102** to 1.1 bar (stream **7**). Finally, stream **7** is directed to an endflash vessel **103**, which separates liquid and vapor, producing LNG to storage (stream **8**) and endflash gas (stream **9**), both at about -160ºC and 1.1 bar.

Stream **9** is passed back to both heat exchangers **101** and **100**, respectively, where the cryogenic energy of this stream is recovered, in an identical way as in Example 1. In the end, endflash gas exits heat exchanger **100** as stream **11** at 15ºC, 1 bar. This vapor stream **11** can be used as fuel within the plant.

The air refrigeration cycle, in **FIG. 2**, is an open loop. In this cycle, the air is continuously taken from the atmosphere at ambient conditions (stream **12'**). Stream **12'** enters the treating plant **C**, which is in charge of removing the CO_2 and water that can carry the air and leaves the plant as stream **12** (15ºC, 1 bar). Stream **12** is compressed in a multistage compressor unit **104** provided with intercooling and aftercooling stages to produce compressed stream **18**, which exits the compressor unit **104** at 40ºC and 16 bar. It is directed to heat exchanger **100**, where is precooled to about -27ºC by the countercurrent passage of air refrigerant stream **21** and of endflash gas **10**. Stream **18** emerges as stream **19** from heat exchanger **100** and is passed to an expander zone **111**, where the pressure and the temperature is reduced to about 1.2 bar and -133ºC, respectively (stream **24**). Stream **24** passes through both heat exchangers **101** and **100**, respectively. In the heat exchanger **101**, the stream **24** provides enough cooling to liquefy the natural gas stream **5** to form liquid natural gas (stream **6**). Stream **24** emerges as stream **25** from heat exchanger **101** at a temperature of about -74ºC and it enters heat exchanger **100**, where it precools both the natural gas (stream **2**) and the compressed air (stream **18**). Stream **25** leaves the heat exchanger **100** at about 33ºC and 1 bar, and it is released directly to the atmosphere **26**.

Table 3 shows the operating conditions of the main streams of **FIG. 2**.

Stream	P (bar)	T (ºC)
2	30	15
3	29.8	-68.6
5	29.8	-68.6
6	29.6	-130.4
7	1.1	-159.4
8	1.1	-159.4
9	1.1	-159.4
10	1.05	-90.8
11	1	15
12	1	15
18	16	40
19	15.9	-26.7
24	1.2	-133.1
25	1.1	-74.1
26	1	33.3

Table 3

EXAMPLE 3

FIG. 3 shows another example of the present invention.

As in the previous examples, the natural gas **1** is treated in the pretreatment plant **A** (the treated gas, stream **2**, has the composition shown in Table 1) and then liquefied by exchanging heat with cold air in two steps. First, it is precooled in the heat exchanger **120** to a temperature of about -69ºC (stream **3**). It passes through a column **B** where the liquids are extracted as the bottom stream **4**; the lean natural gas exits the column **B** at the top (stream **5**) and enters the second heat exchanger **101**. The liquid stream emerging from heat exchanger **101** at about -131ºC (stream **6**) is directed to an expansion zone, where is expanded adiabatically in a JT-valve **102** to 1.1 bar (stream **7**). Finally, stream **7** is directed to an endflash vessel **103**, which separates liquid and vapor, producing LNG to storage (stream **8**) and endflash gas (stream **9**), both at about -160ºC and 1.1 bar.

Stream **9** is passed back to both heat exchangers **101** and **120**, respectively, where the cryogenic energy of this stream is recovered, in an identical way as in Examples 1 and 2. In the end, endflash gas exits heat exchanger **120** as stream **11** at 15ºC, 1 bar. This vapor stream **11** can be used as fuel within the plant.

The air refrigeration cycle which transforms gas stream **2** to liquid stream **6** will now be described, starting with air stream **12**. Stream **12**, which is at about 36ºC and 3.6 bar is compressed in a multistage compressor unit **104** provided with intercooling and aftercooling stages to produce compressed stream **18**, which exits the compressor unit **104** at 40ºC and 43 bar. It is directed to an additional heat exchanger **114**, where is precooled to about -33ºC by the countercurrent passage of air refrigerant stream**121**. Stream **18** emerges as stream **19** from heat exchanger **114** and is passed to an expander zone **111**, where the pressure and the temperature is reduced to about 4 bar and -135ºC, respectively (stream **24**). Stream **24** passes through both heat exchangers **101** and**120**, respectively. In the heat exchanger **101**, the stream **24** provides enough cooling to liquefy the natural gas stream **5** to form liquid natural gas (stream **6**). Stream **24** emerges as stream **25** from heat exchanger **101** at a temperature of about -81ºC and it enters heat exchanger **120**, where it precools the natural gas (stream **2**). Stream **25** leaves the heat exchanger **120** as stream **121** at about -43ºC and 3.7 bar, and is directed to the heat exchanger **114**, where this stream precools the countercurrent air stream **18**. Stream **121** leaves the heat exchanger **114** and it starts the cycle again.

The air cycle will have a point for make up in order to compensate for air losses in the air cycle. The air make up will have to be treated in treating facilities to eliminate the CO_2 and water that it can carry.

Table 4 shows the operating conditions of the main streams of **FIG. 3**.

Stream	P (bar)	T (ºC)
2	30	15
3	29.9	-69.1
5	29.8	-68.9
6	29.6	-130.6
7	1.1	-159.5
8	1.1	-159.5
9	1.1	-159.5
10	1.05	-80
11	1	15
12	3.6	36.4
18	43	40
19	42.9	-33.1
24	3.9	-135.4
25	3.8	-80.7
121	3.7	-43.3

Table 4

CLAIMS

1.- A system of production of Liquefied Natural Gas (LNG) comprising:

- a mobile structure, and
- a natural gas liquefaction plant installed on the mobile structure which comprises:

at least one compressor (105, 107, 109) where air (12) is compressed to obtain compressed air (18),

at least one expander (112, 113) where a cooled compressed air (19) is expanded to obtain expanded air (24, 25),

at least one heat exchanger (100, 120, 101) where the natural gas (2, 5) is cooled with the expanded air (24, 25) and with an end-flash gas (9, 10) to obtain a cooled natural gas (3, 6),

an expansion device (102) where the cooled natural gas (6) is expanded to obtain an expanded cooled natural gas (7), and

an end-flash vessel (103) where the expanded cooled natural gas (7) is separated in liquefied natural gas LNG (8) and in the end-flash gas (9).

2.- A system of production of Liquefied Natural Gas (LNG) according to claim 1 wherein the heat exchanger (100) further comprises:

an inlet for the compressed air (18),

an outlet for the cooled compressed air (19), and

an outlet for the air (12) which is further connected to the compressor (105, 107, 109) in a closed refrigeration cycle or with the atmosphere (26) in an open refrigeration cycle.

3.- A system of production of Liquefied Natural Gas (LNG) according to claim 1 wherein it comprises an additional heat exchanger (114) where the compressed air (18) is cooled with the air (121) coming from the heat exchanger (120) to obtain the cooled compressed air (19).

4.- A system of production of Liquefied Natural Gas (LNG) according to claim 1 wherein it further comprises a fractionation unit B, located after the heat exchanger (100, 120), where the cooled natural gas (3) enters, a natural gas liquids enriched stream (4) is extracted, and a lean natural gas (5) is extracted.

5.- A system of production of Liquefied Natural Gas (LNG) according to claim 4 wherein a heat exchanger (101) is located after the fractionation unit B where the lean natural gas (5) is cooled with the expanded air (24) and with the end-flash gas (9) to obtain the cooled natural gas (6).

6.- A system of production of Liquefied Natural Gas (LNG) according to claim 1 wherein it further comprises a pretreatment plant A located prior to the heat exchanger (100, 120) where the undesired contaminants or impurities present in the natural gas feed (1) are removed.

7.- A system of production of Liquefied Natural Gas (LNG) according to claim 1 wherein it further comprises a treating plant C where CO2 and water are removed from air (12') taken from the atmosphere, obtaining the air (12) which is directed to the compressor (105, 107, 109).

8.- A system of production of Liquefied Natural Gas (LNG) according to claim 1 wherein the mobile structure consists on a barge.

9.- A system of production of Liquefied Natural Gas (LNG) according to claim 1 wherein the mobile structure consists on a ship.

10.- A method of production of Liquefied Natural Gas (LNG), which comprises the following steps:

a. compressing air (12) to obtain a compressed air (18),
b. cooling the compressed air (18) to obtain a cooled compressed air (19),
c. expanding said cooled compressed air (19) to obtain an expanded air (24, 25),

d. using the expanded air (24, 25) for cooling the natural gas stream (2, 5) to obtain a cooled natural gas (6),
e. expanding the cooled natural gas (6) to obtain an expanded natural gas (7) and separating said expanded natural gas in liquid (LNG) (8) and a an end-flash gas (9),

wherein the end-flash gas (9) is used to cool the natural gas stream (2, 5).

11.- The method according to claim 10, which further comprises the step of:

f. incorporating air make-up to the air circuit in order to compensate the air losses.

12.- The method according claim 10, wherein the step of compressing air (12) is carried out in more than one stage.

13.- The method according to claim 10, wherein the expanded air (25) once used to cool the natural gas goes back to the beginning of the process as air (12) which is further compressed.

14.- The method according to claim 10, wherein the expanded air (25) once used to cool the natural gas is given back to the atmosphere (26).

15.- The method according to claim 10, which comprises the additional step of:

g. separating the natural gas in natural gas liquids enriched stream (NGL) (4) and a lean gas (5) before the liquefaction of natural gas.

16.- The method according to claim 10, wherein the natural gas stream passes to the process with a pressure of at least 1 bar.

17.- The method according to claim 10, wherein the natural gas is cooled to liquefaction in two stages.

18.- The method according to claim 17, wherein the natural gas stream is cooled down, in the first stage of cooling, to a temperature that allows the

extraction of natural gas liquids enriched stream (NGL) (4).

19.- The method according to claim 17, wherein the natural gas stream is cooled down, in the second stage of cooling, to a temperature that allows the liquefaction of it.

20.- The method according to claim 10 wherein natural gas is pre-treated before cooling it.

21.- The method according to claim 20, wherein the pre-treatment of natural gas comprises the removal of CO_2, H_2S, H_2O or Hg.