

SLIDE FASTENER CHAIN

The present invention relates to the production of slide fasteners, and more particularly to a slide fastener chain including a pair of fastener stringers of a continuous length.

In the manufacture of slide fasteners, it has been the common practice to cut or sever a slide fastener chain to slide fastener lengths by a special cutting device such as scissors or punch. The present invention is an improved slide fastener chain which is capable of being separated or torn to slide fastener lengths only by hand, requiring no cutting device.

According to the invention, there is provided a slide fastener chain comprising a pair of fastener stringers of a continuous length including a pair of continuous stringer tapes and a pair of rows of coupling elements mounted on said stringer tapes along their respective inner longitudinal edges; wherein said pair of fastener stringers has a plurality of separating regions along which the slide fastener chain is to be torn to predetermined slide fastener lengths, said separating regions being spaced at predetermined distances along said pair of fastener stringers, each separating region extending transversely across said pair of fastener stringers and being at least partially thinner than the remaining portions of said tapes; and wherein each tape is a woven or knit fabric made of synthetic fibre yarns, or made of blended yarns comprising natural and synthetic fibres, each separating region having been made at least partially thinner by the formation of recesses by heat or fusion.

It is believed possible by means of the invention to provide

(14) a slide fastener chain which can be separated or torn to predetermined slide fastener lengths one after another only by hand without difficulty, thus requiring no cutting device.

It is also believed possible by means of the invention to provide a slide fastener chain having a plurality of spaced separating regions which is thin enough to be torn by hand and which is thick enough to prevent the fastener chain from being inadvertently torn at the separating regions during transportation.

The invention will be described by way of example with reference to the accompanying drawings, wherein:-

Figure 1 is a fragmentary plan view of a slide fastener chain embodying the present invention, showing only one of a plurality of spaced separating regions;

Figure 2 is an enlarged cross-sectional view taken along line II-II of Figure 1;

Figure 3 is a cross-sectional view similar to Figure 2, but showing a modified separating region;

Figure 4 is a fragmentary plan view of a slide fastener chain according to a second embodiment;

Figure 5 is a fragmentary plan view similar to Figure 1,

(18)

but showing a third embodiment;

Figures 6 and 7 are enlarged cross-sectional views taken along line VI-VI and line VII-VII, respectively, of Figure 5;

5 Figure 8 is a fragmentary plan view of a slide fastener chain according to a fourth embodiment;

Figure 9 is a detail view showing a portion A of Figure 8;

Figure 10 is an enlarged cross-sectional view taken
10 along line X-X of Figure 9;

Figure 11 is a cross-sectional view similar to Figure 10, but showing a modified separating region;

Figure 12 is a fragmentary plan view similar to Figure 8, but showing a fifth embodiment;

15 Figures 13 and 14 are enlarged cross-sectional views taken along line XIII-XIII and line XIV-XIV, respectively, of Figure 12;

Figure 15 is a fragmentary plan view of a slide fastener chain according to a sixth embodiment;

20 Figures 16 and 17 are enlarged cross-sectional views taken along line XVI-XVI and line XVII-XVII, respectively, of Figure 15;

Figure 18 is a fragmentary plan view of a slide fastener chain according to a seventh embodiment;

25 Figure 19 is an enlarged cross-sectional view taken along line XIX-XIX of Figure 18;

Figure 20 is a fragmentary cross-sectional view showing a modification of the separating region of Figure 1; and

Figures 21 and 22 are fragmentary cross-sectional views respectively showing modifications of the separating region of Figure 8.

As shown in Figure 1, a slide fastener-chain 1 (hereinafter referred to as "fastener chain") comprises a pair of fastener stringers 2,2 of a continuous length including a pair of interengaged rows of coupling elements 3,3 mounted on a pair of stringer tapes 4,4 along their respective inner longitudinal edges. Each tape 4 is a woven or knit fabric made of synthetic fiber yarns, or made of blended yarns comprising natural and synthetic fibers. Each row of coupling elements 3 is in the form of a coiled or zigzag-shaped filament made of thermoplastic synthetic resin and is attached to the tape 4 by means of a line of stitching 5. The fastener chain 1 has a plurality of element-free portions 6 (only one element-free portion is illustrated for clarity) spaced at predetermined distances along the inner longitudinal tape edges.

The fastener chain 1 also has a plurality of separating regions 7 (only one separating region is illustrated for clarity) along which the fastener chain 1 is to be separated or torn to individual slide fastener lengths. The separating regions 7 are spaced at predetermined distances along the fastener chain 1, each separating region 7 extending transversely across the fastener chain 1 at a respective element-free portion 6. Each separating region 7 comprises a pair of longitudinally aligned straight recesses 8,8, each disposed in one surface of a respective one fastener stringer 2 and extending transversely across

the fastener stringer 2. The recesses 8,8 have a trapezoidal cross section (Figure 2), and each of such thinned or recessed portions has a uniform thickness through its whole length.

5 The recesses 8,8 may be formed by simply pressing the fastener chain 1 at the prospective separating regions 7 by a heated edge or roller (not shown), or by an ultrahigh-frequency fusing device (not shown) of a known construction; the thermoplastic synthetic fibers (which are
10 contained in the tapes 4,4) at the prospective separating regions 7 are thereby fused to constitute the walls 8a,8b of the recesses 8,8. As the result of this fusing, the stitching threads 5,5 are broken at the recesses 8,8. The bottom wall 8a of each recess 8 is considerably thinner
15 than the general thickness of the tape 4, but it is thick enough to prevent the fastener chain 1 from being inadvertently torn or broken at such recessed portions during transportation.

With the thus provided separating regions 7, the
20 fastener chain 1 is capable of being torn to slide fastener lengths one after another only by hand without difficulty, requiring no cutting device.

The bottom wall 8a of each recess 8 may have a pair of notches 9,9 (Figure 3) extending along the corners of
25 the recess 8 to assist separation.

Figure 4 shows a modified slide fastener chain 10 according to a second embodiment, which is similar to the fastener chain 1 of Figure 1 and is different therefrom only in that the recesses 8,8 of each separating region 7

21

extend in a zigzag course.

Figure 5 shows a modified slide fastener chain 20 according to a third embodiment, which is similar to the fastener chain 1 of Figure 1 and is different therefrom only in that each recessed portion 8 comprises a plurality of long and short sections 8a', 8a'' of different thicknesses disposed alternately along the recess 8. The long sections 8a' has a thickness smaller than the thickness of the short sections 8a'', as shown in Figures 6 and 7.

Figure 8 shows a modified slide fastener chain 30 according to a fourth embodiment, which is different from the embodiments of Figures 1, 4 and 5 only in that each separating region 7 comprises three series of discrete recesses 11, 11, 11 disposed in one surface of the fastener chain 30 and extending transversely across the fastener chain 30. The recesses 11 of each series are virtually aligned laterally with the inter-recess portions of an adjacent series and extend each beyond opposite ends of a respective inter-recess portion of the adjacent series. Thus every warp yarn 4a of the tape 4 is interrupted by at least one of the recesses 11 so that the fastener chain 30 can be separated or torn along the separating region 7 without difficulty.

The inter-recess portions between adjacent series 11, 11 have a thickness equal to the general thickness of the tape 4 (Figure 10). Alternatively, such inter-recess-series portions may have a thickness smaller than the general thickness of the tape 4 and greater than the thickness of the recessed portion 11a (Figure 11),

assisting separation of the fastener chain 30 at the separating regions 7.

Figure 12 shows a slide fastener chain 40 according to a fifth embodiment, which is different from the fastener chain 30 of Figure 8 only in that each separating region 7 comprises a pair of series of discrete recesses 13, 13 disposed in one surface of the fastener chain 40 and extending transversely across the fastener chain 40. Each series of the recesses 13 comprises a plurality of alternating long and short recesses 13', 13" of different thicknesses, the long recesses 13' of one series being virtually aligned laterally with the inter-long-recess portions of the other series and extending each beyond opposite ends of a respective inter-long-recess portion of the other series. The bottom wall 13"_a of each short recess 13" is thicker than the bottom wall 13'_a of each long recess 13', as shown in Figures 13 and 14.

Figure 15 shows a slide fastener chain 50 according to a sixth embodiment, which is different from the fastener chain 1 of Figure 1 in that in the absence of element-free portions, each straight recess 14 extends transversely across both the tape 4 and the coupling element row 3. The recess 14 may be formed by simply pressing the fastener chain 50 at the prospective separating region 7 by a heated edge or roller (not shown), or by an ultra-high-frequency fusing device (not shown); both the thermoplastic synthetic fibers (contained in the tapes 4, 4) and the thermoplastic synthetic resin of the coupling elements 3 at the prospective separating region 7 are thereby fused to constitute

23

the walls 14a,14b of the recess 14, as shown in Figures 16 and 17.

Figure 18 shows a slide fastener chain 60 according to a seventh embodiment, which is different from the fastener chain 30 of Figure 8 in that a plurality of thermoplastic synthetic resin strips 15 (only one strip is illustrated for clarity) is attached to the respective element-free portions 6 (Figure 8). The strips 15 serve to prevent the stitching threads 5,5 from fraying at the element-free portions 6. The three series of discrete recesses 11,11,11 are interrupted by the strip 15; a series of continuous recesses 16 in the strip 15 is longitudinally aligned with one of the three series of discrete recesses 11. Thus the recesses 11 are defined by fused thermoplastic synthetic fibers of the tapes 4,4, while the recesses 16 are defined by fused thermoplastic synthetic resin of the strip 15.

Figure 20 shows a modification of the separating region 7 of Figure 1, in which an additional pair of longitudinally aligned recesses 18,18 is disposed in the other surface of the respective stringers 2,2 and is aligned with the recesses 8,8, respectively, in one surface of the stringers 2,2.

Figures 21 and 22 respectively show modifications of the separating region 7 of Figure 8, in which two additional series of discrete recesses 21,21 are disposed in the other surface of the stringers 2,2 and are staggered with respect to the three series of the recesses 11,11,11 in one surface of the stringers 2,2.

(24)

In any of the embodiments described above, every warp yarn of the tape is interrupted by at least one of the recesses so that the fastener chain can be separated or torn along the separating region 7 only by hand without 5 difficulty. If there are some warp yarns remaining un-interrupted or totally unfused, easy and proper separation cannot be achieved. Further, because of such totally unfused warp yarns the separated or torn ends of the tape would be unsightly.



CLAIMS:-

1. A slide fastener chain comprising a pair of fastener stringers of a continuous length including a pair of continuous stringer tapes and a pair of rows of coupling elements mounted on said stringer tapes along their respective inner longitudinal edges; wherein said pair of fastener stringers has a plurality of separating regions along which the slide fastener chain is to be torn to predetermined slide fastener lengths, said separating regions being spaced at predetermined distances along said pair of fastener stringers, each separating region extending transversely across said pair of fastener stringers and being at least partially thinner than the remaining portions of said tapes; and wherein each tape is a woven or knit fabric made of synthetic fibre yarns, or made of blended yarns comprising natural and synthetic fibres, each separating region having been made at least partially thinner by the formation of recesses by heat or fusion.

2. A slide fastener chain according to claim 1, each said separating region including a pair of longitudinally aligned recesses, each disposed in one surface of a respective one of said fastener stringers and extending transversely across said respective one fastener stringers, walls of said recesses including fused thermoplastic synthetic materials.

3. A slide fastener chain according to claim 2, each of such recessed portions having a uniform thickness through its whole length.

4. A slide fastener chain according to claim 2, each of such recessed portions comprising a plurality of long and short sections



26

of different thicknesses disposed alternately along each said recessed portion, said long sections having a thickness smaller than that of said short sections.

5. A slide fastener chain according to claim 2, each of said recesses extending in a straight course.

6. A slide fastener chain according to claim 2, each of said recesses extending in a zigzag course.

7. A slide fastener chain according to claim 3, each said recessed portion having a pair of notches extending along a pair of corners, respectively, of the recess.

8. A slide fastener chain according to claim 1, each said separating region including at least two series of discrete recesses disposed in one surface of said pair of fastener stringers and extending transversely across said pair of fastener stringers, walls of said recesses including fused thermoplastic synthetic materials.

9. A slide fastener chain according to claim 8, said recesses of one series being substantially aligned laterally with inter-recess portions of the other series and extending each beyond opposite ends of a respective one of the inter-recess portions of said other series.

10. A slide fastener chain according to claim 8, each series of said recesses comprising a plurality of alternating long and short recesses of different thicknesses, said long recesses of one series being substantially aligned laterally with inter-long-recess portions of the other series and extending each beyond opposite ends of a respective one of the inter-long-recess portions of said other series.

27



11. A slide fastener chain according to claim 8, portions of said fastener stringers between said two series of recesses having a thickness greater than the thickness of said recessed portions and smaller than the general thickness of said tapes.
12. A slide fastener chain according to claim 2, each said separating region including an additional pair of longitudinally aligned recesses each disposed in the other surface of said respective one fastener stringer and aligned with each said recess in said one surface of the same fastener stringer.
13. A slide fastener chain according to claim 8, each said separating region including at least one additional series of discrete recesses disposed in the other surface of said pair of fastener stringers and staggered with respect to said series of recesses in said one surface of said pair of fastener stringers.
14. A slide fastener chain according to claim 1, each said fastener stringer having a plurality of element-free portions spaced at predetermined distances along the inner longitudinal tape edge, each said recesses extending transversely across a respective one of said element-free portion.
15. A slide fastener chain according to claim 8, including a plurality of spaced thermoplastic synthetic resin strips attached to one surface of said pair of fastener stringers, one of said two series of discrete recesses of each said separating region extending transversely across a respective one of said film strips.
16. A slide fastener chain substantially as described with reference to and as illustrated in Figures 1 and 2 of the accompanying drawings.



17. A slide fastener chain substantially as described with reference to and as illustrated in Figures 1 and 2 modified as in Figure 3 of the accompanying drawings.

18. A slide fastener chain substantially as described with reference to and as illustrated in Figure 4 of the accompanying drawings.

19. A slide fastener chain substantially as described with reference to and as illustrated in Figures 5 to 7 of the accompanying drawings.

20. A slide fastener chain substantially as described with reference to and as illustrated in Figures 8 to 10 of the accompanying drawings.

21. A slide fastener chain substantially as described with reference to and as illustrated in Figures 8 to 10 modified as in Figure 11 of the accompanying drawings.

22. A slide fastener chain substantially as described with reference to and as illustrated in Figures 12 to 14 of the accompanying drawings.

23. A slide fastener chain substantially as described with reference to and as illustrated in Figures 15 to 17 modified as in Figures of the accompanying drawings.

24. A slide fastener chain substantially as described with reference to and as illustrated in Figures 18 to 20 of the accompanying drawings.

25. A slide fastener chain substantially as described with reference to and as illustrated in Figures 8 to 10 modified as in Figure 22 of the accompanying drawings.



26. A slide fastener chain substantially as described with reference to and as illustrated in Figures 8 to 10 modified as in Figure 22 of the accompanying drawings.
