

DESCRIPTION

FRESH-WATER GENERATING APPARATUS

TECHNICAL FIELD

[0001]

The present invention relates to a fresh-water generating apparatus for purifying, *inter alia*, seawater, sludge water, oily water, and industrial waste water.

BACKGROUND ART

[0002]

In the past, systems of heating and evaporating seawater and then cooling the water to obtain fresh water have been common as methods for purifying, *inter alia*, seawater, and multi-stage flushing systems have been used in which the water is distilled under reduced pressure in order to improve heating efficiency, and a large number of depressurizing chambers are combined in a practical plant (Patent Document 1). The salt concentration of the generated fresh water is low at approximately less than 5 ppm, and fresh water can be generated in large quantities.

[0003]

In recent years, a system has been employed in which seawater is passed under pressure through a type of filtering membrane known as a reverse-osmosis membrane (a so-called RO membrane), and the salt in the seawater is condensed and removed to strain out freshwater, for which a large plant is

constructed that exceeds 10,000 tons per day. An RO membrane requires higher pressure for filtration with higher salt concentrations in the seawater or with lower desired salt concentrations in the freshwater, and various membranes of complicated structures, known as hollow fiber membranes and spiral membranes, have been proposed to withstand this pressure (Patent Document 2). A turbine pump, a plunger pump, or another high-pressure pump is used to increase pressure.

[Prior Art Documents]

[Patent Documents]

[0004]

[Patent Document 1] Japanese Laid-open Patent Publication No.
10-71320

[Patent Document 2] Japanese Patent No. 4113568

DISCLOSURE OF THE INVENTION

[Problems the Invention Is Intended to Solve]

[0005]

However, with the multi-stage flushing system described above, although large quantities of fresh water can be generated, the quality of the seawater is not inspected, and a problem with this system has been that heating efficiency is very poor and large amounts of energy are required. A problem with a system that uses an RO membrane has been that because a pump is used to increase pressure, the amount of fresh water generated is only about 5% from seawater and only about 10% from sludge water or oily water. Moreover, because the RO

membrane can become clogged, either periodic maintenance must be performed to undo the clogging by reverse pressurization, or the RO membrane itself must be replaced as appropriate. Another problem with these prior-art systems has been that including maintenance costs, it is costly to construct and operate a fresh water-generating plant, and high costs are inevitable even considering cost against fresh water-generating efficiency.

[0006]

In view of this, the applicant's purpose is to provide a fresh-water generating apparatus that does not require large amounts of heating energy as in the past, that can generate fresh water at room temperature, and that, which a simpler configuration, does not incur high installation costs including maintenance expenses.

[Means for Solving the Aforementioned Problems]

[0007]

To solve the problems described above, the present invention is configured as follows. Specifically, a fresh-water generating apparatus according to a first aspect of the present invention is characterized by comprising: a first storage tank in which seawater, sludge water, oily water, industrial waste water, or another stored liquid is accommodated; a first water-absorbing base material of which a lower end is impregnated with the stored liquid of the first storage tank; a blowing means for blowing air at an upper-end

side of the first water-absorbing base material; a second water-absorbing base material for causing water vapor vaporized and blown out from the upper-end side of the first water-absorbing base material by the air blown by the blowing means to adsorb and condense on the upper-end side, the second water-absorbing base material being designed so that the condensed water droplets drip down from a lower-end side; a second storage tank in which the condensed water dripping down from the second water-absorbing base material is stored; a lid for closing an upper space of the first and second storage tanks; and a guide pipe of which one end communicates with the upper space of the second storage tank of the lid to exhaust the air blown from the blowing means, and the other end communicates with the upper space of the first storage tank and with an intake side of the blowing means to form a circulation path for the blown air.

[0008]

In a fresh-water generating apparatus according to a second aspect, the first and second water-absorbing base materials are configured from synthetic zeolite of which each hole diameter of a porous structure is formed to the size of a water molecule.

[0009]

In a fresh-water generating apparatus according to a third aspect, the first and second water-absorbing base materials are configured from nanocarbon of which each hole

diameter of a porous structure is formed to the size of a water molecule.

[0010]

In a fresh-water generating apparatus according to a fourth aspect, the first and second water-absorbing base materials are configured from a fabric having excellent water absorbency.

[0011]

In a fresh-water generating apparatus according to a fifth aspect, the first and second water-absorbing base materials are connected at an upper adjacent surface on which the base materials are disposed, and are formed integrally in the shape of an upside-down letter U.

[0012]

A fresh-water generating apparatus according to a sixth aspect is configured such that an air cooler is installed, compressed air being supplied to the air cooler, and cold air jetted from the air cooler is supplied to the second storage tank while hot air exhausted from the air cooler is supplied to the intake side of the blowing means.

[0013]

A fresh-water generating apparatus according to a seventh aspect is configured such that the stored liquid is stored in the first storage tank with the level of the liquid lowered as much as possible.

[0014]

A fresh-water generating apparatus according to an eighth aspect is configured such that suspended inside the second storage tank are a plurality of metal fin-like members for causing water vapor accumulating in the second storage tank to condense.

[Effect of the Invention]

[0015]

With the fresh-water generating apparatus according to the present invention, the lower end of the first water-absorbing base material is immersed in, *inter alia*, seawater stored in the first storage tank, and the interior of this water-absorbing base material is impregnated only with moisture from the, *inter alia*, seawater stored in the first storage tank. The moisture impregnating the first water-absorbing base material is sequentially vaporized and blown out as water vapor by the air blown by the blowing means.

[0016]

When the vaporized water vapor is blown out along with the blown air from the first water-absorbing base material, this water vapor reaches the second water-absorbing base material where it is adsorbed within the second water-absorbing base material, the water vapor then sequentially releases heat and condenses while continuing to impregnate the base material, and the vapor becomes fresh water droplets which drip down from the lower-end side of the base material

into the second storage tank. When the blown air itself continues to pass through the second water-absorbing base material, the temperature rises due to the water vapor condensation, the air is dried and exhausted through the guide pipe, and the air is refluxed to the intake side of the blowing means.

[0017]

The air refluxed to the intake side of the blowing means is blown to the first water-absorbing base material as dry air higher in temperature than before going through this circulation cycle; therefore, the water impregnating the substrate is caused to vaporize more than the previous time, and the condensed fresh water is caused to be stored in the second storage tank.

[0018]

Thus, only moisture is vaporized from, *inter alia*, the seawater stored in the first storage tank between the first and second water-absorbing base materials, the vaporized water vapor condenses, and fresh water is continually stored in the second storage tank, whereby fresh water generation can be carried out at room temperature.

[0019]

The apparatus configuration can be easily achieved by using, as the water-absorbing base materials, synthetic zeolite or nanocarbon developed by the applicant and having each hole diameter of a porous structure formed to the size of

a water molecule, and a fabric having excellent water absorbency can be substituted in order to achieve an even simpler configuration. A yet even simpler configuration can be achieved if the first and second water-absorbing base materials are connected at an upper adjacent surface on which the base materials are disposed, and are formed integrally in the shape of an upside-down letter U.

[0020]

If the configuration is such that a so-called ultra-low temperature air generator, which is an air cooler, is installed, compressed air being supplied to the air cooler, and cold air jetted from the air cooler is supplied to the second storage tank while hot air exhausted from the air cooler is supplied to the intake side of the blowing means, then air refluxing to the intake side of the blowing means is blown as warm air of an even higher temperature to the first porous water-absorbing base material, vaporization is further facilitated, ultra-low temperature air is supplied into the second storage tank, the temperature of the second water-absorbing base material decreases, further facilitating water vapor condensation, and the efficiency of fresh water generation can be increased.

[0021]

Additionally, the efficiency of heat transfer to the stored liquid itself is ensured to not decrease by appropriately replenishing the stored liquid so that the

stored liquid is stored in the first storage tank with the level of the liquid lowered as much as possible, and if a plurality of metal fin-like members are suspended within the second storage tank, the water vapor is condensed on the fin-like members as well when the water vapor accumulating within the second storage tank is cooled by the cold air; therefore, the efficiency of fresh water generation can be further increased.

BRIEF DESCRIPTION OF THE DRAWINGS

[0022]

FIG. 1 is a schematic configuration diagram showing the overall configuration of a fresh-water generating apparatus.

FIG. 2 is a schematic configuration diagram showing an example in which first and second water-absorbing base materials are formed as being integrated together.

BEST MODE FOR CARRYING OUT THE INVENTION

[0023]

An embodiment of the present invention is described below with reference to the drawings.

[0024]

FIG. 1 is a schematic configuration diagram showing the overall configuration of a fresh-water generating apparatus. In this diagram, a first storage tank 1, in which seawater, sludge water, oily water, or another stored liquid 4 is stored, and a second storage tank 2, adjacent to the storage tank 1, are set up next to each other. In the bordering side

of the storage tank 1 that is adjacent to the storage tank 2, a first porous water-absorbing substrate 3, which serves as a water-absorbing base material of which each hole diameter of the porous structure is formed to the size of a water molecule, is suspended from a lid 5 provided so as to close off an upper space of the storage tank 1 and the storage tank 2, and the lower end portion thereof is immersed in the stored liquid 4 stored in the storage tank 1. A blower 6 for blowing air at the upper side of the first porous water-absorbing substrate 3 not immersed in the stored liquid 4 is installed on the inner front wall surface of the lid 5.

[0025]

In the bordering side of the storage tank 2 that is adjacent to the storage tank 1, a second porous water-absorbing substrate 7, which serves as a water-absorbing base material of which each hole diameter of the porous structure is formed to the size of a water molecule, is suspended from the lid 5 in a position of facing the first porous water-absorbing substrate 3, so that the lower end of the second porous water-absorbing substrate 7 leads into the storage tank 2. An exhaust port 8 is formed in the inner rear wall surface of the lid 5 closing the second storage tank 2 side, and a guide pipe 10 is provided to the exhaust port 8, the guide pipe 10 passing above the lid 5 and communicating with an intake port 9 provided to the aforementioned blower 6 side.

[0026]

The aforementioned first and second porous water-absorbing substrates 3, 7 are made from synthetic zeolite of which each hole diameter of the porous structure is formed to the same diameter as a water molecule, by baking for a long period of time under strict temperature control using a specially constructed baking furnace, developed by the applicant and capable of heating to single-degree accuracy in a high-temperature range of 800 to 2000°C. When immersed in the stored liquid, the substrates function so as to be able to instantly adsorb only water molecules in the porous portions, and when the substrates have adsorbed water vapor, the substrates can exhibit the function of condensing the water vapor and extracting the vapor as distilled water. A nanocarbon material or a fabric or the like woven to water molecule diameters can also be used as water-absorbing base materials exhibiting the same functions.

[0027]

The fresh water-generating function of the fresh-water generating apparatus configured as above shall be described. Because the lower end of the first porous water-absorbing substrate 3 is immersed in the stored liquid 4 stored in the storage tank 1, only the moisture in the stored liquid 4 instantly impregnates entirely through the porous water-absorbing substrate 3. The blower 6 continues to blow air (shown by the arrows in the diagram) at the front-surface side

of the first porous water-absorbing substrate 3, and the moisture continually impregnating the substrate 3 is therefore sequentially vaporized and blown out as water vapor (shown by the dashed-line arrows in the diagram) from the reverse-surface side of the substrate 3.

[0028]

The water vapor thus blown out reaches the front surface of the second porous water-absorbing substrate 7 suspended on the second storage tank 2 side, impregnates the second porous water-absorbing substrate 7, sequentially releases heat and condenses while impregnating the substrate, and becomes fresh water droplets (shown by the white empty arrows in the diagram) which drip down from the lower-end-side of the substrate 7; thus, fresh water is stored in the storage tank 2.

[0029]

The blown air itself, exhausted from the exhaust port 8 provided to the rear inner wall surface of the lid 5 closing the storage tank 2, is blown through the guide pipe 10 out to the intake port 9 provided to the aforementioned blower 6, and the air thus refluxes. The blown air itself at this time rises in temperature due to the heat released by the condensation of the water vapor, and becomes drier air.

[0030]

Air that has refluxed to the intake port 9 side of the blower 6 is blown to the first porous water-absorbing

substrate 3 as dry air higher in temperature than before going through this circulation cycle; therefore, the water impregnating the substrate 3 is caused to vaporize more than the previous time, only moisture continues to be efficiently absorbed from the stored liquid 4 in the storage tank 1, the vaporized water vapor is adsorbed on the second porous water-absorbing substrate 7, and the water condenses and continues to drop in greater amounts into the storage tank 2. If the amount of the stored liquid 4 decreases, the liquid is replenished into the storage tank 1 from a supply channel (not shown), and the liquid is taken out through an inlet channel (not shown) when the fresh water stored in the storage tank 2 increases.

[0031]

When only moisture is extracted from the stored liquid 4 in the storage tank 1 due to this fresh water-generating process, salt or the like remains as residue in the storage tank 1 in the case of seawater, of sludge in the case of sludge water and various oils in the case of oily water, and these residues are recovered and disposed by post-treatment so as not to incur a load on the environment.

[0032]

The fresh-water generating apparatus according to the present invention, as described above, has a very simple apparatus configuration which draws up only moisture from a stored liquid 4 in a storage tank 1 between first and second

porous water-absorbing substrates, vaporizes the moisture by blowing air, causes the vaporized water vapor to adsorb and condense, and stores the vapor in a storage tank 2, by using porous water-absorbing substrates capable of instantly adsorbing moisture, the substrates being made of synthetic zeolite baked from a special component blend developed by the applicant and having each hole diameter of a porous structure formed to the same diameter as a water molecule. The fresh-water generating apparatus according to the present invention can thereby efficiently generate fresh water at room temperature without requiring large amounts of heating energy and with no need to replace the substrates themselves. The amount of fresh water generated can be controlled merely by adjusting the amount of air blown in a blowing means, and a basic apparatus configuration for an ordinary storage tank can therefore be actualized in a very simple manner and at low cost.

[0033]

In the above example, the apparatus can have a simpler configuration if the first and second porous water-absorbing substrates 3, 7 are connected at an upper adjacent surface and formed integrally in the shape of an upside-down letter U, as shown in FIG. 2. In this case, the lower end of the first porous water-absorbing substrate 3 should be formed shorter than the lower end of the second porous water-absorbing substrate 7, in consideration for tube capillarity.

[0034]

Though not illustrated, if the configuration is such that a so-called ultra-low temperature air generator, which is an air cooler, is installed, compressed air being supplied to the air cooler, and cold air jetted from the air cooler is supplied to the storage tank 2 while hot air exhausted from the air cooler is supplied to the intake side of the blower 6, then air refluxing to the intake side of the blower 6 is blown as warm air of an even higher temperature to the first porous water-absorbing substrate 3, vaporization is further facilitated, ultra-low temperature air is supplied into the storage tank 2, the temperature of the second porous water-absorbing substrate 7 decreases, further facilitating water vapor condensation, and the efficiency of fresh water generation can be increased.

[0035]

Furthermore, the efficiency of heat transfer to the stored liquid 4 itself is ensured to not decrease by appropriately replenishing the stored liquid so that the stored liquid 4 is stored in the storage tank 1 with the level of the liquid lowered as much as possible, and if a plurality of metal fin-like members (not shown) are suspended within the second storage tank 2, the water vapor accumulating in the storage tank 2 is also condensed on the fin-like members when the interior of the storage tank 2 is cooled by the cold air; therefore, the efficiency of fresh water generation can be

further increased.

INDUSTRIAL APPLICABILITY

[0036]

As described above, drinkable water can be obtained if heating and ozone treatment are carried out on, and minerals added to, fresh water generated from seawater. Even with contaminated water contaminated with arsenic or the like, the contaminant can be removed to obtain drinkable water. Furthermore, with industrial waste water as well, with which biochemical oxygen demand and chemical oxygen demand are problems, if waste water treatment is performed using the present apparatus, problem-free waste water can be achieved, and waste water treatment can be performed on dyes and other dye water made similarly transparent.

REFERENCE SIGNS LIST

[0037]

- 1 First storage tank
- 2 Second storage tank
- 3 First porous water-absorbing substrate
- 4 Stored liquid
- 5 Lid
- 6 Blower
- 7 Second porous water-absorbing substrate
- 8 Exhaust port
- 9 Intake port
- 10 Guide pipe

CLAIMS

[Claim 1]

A fresh-water generating apparatus, characterized by comprising:

a first storage tank in which stored liquid is accommodated;

a first water-absorbing base material of which a lower end is impregnated with the stored liquid of the first storage tank;

a blowing means for blowing air at an upper-end side of the first water-absorbing base material;

a second water-absorbing base material for causing water vapor vaporized and blown out from the upper-end side of the first water-absorbing base material by the air blown by the blowing means to adsorb and condense on the upper-end side, the second water-absorbing base material being designed so that the condensed water droplets drip down from a lower-end side;

a second storage tank in which the condensed water dripping down from the lower-end side of the second water-absorbing base material is stored;

a lid for closing an upper space of the first and second storage tanks; and

a guide pipe of which one end communicates with the upper space of the second storage tank of the lid to exhaust the air blown from the blowing means, and the other end communicates

with the upper space of the first storage tank and with an intake side of the blowing means to form a circulation path for the blown air.

[Claim 2]

The fresh-water generating apparatus according to claim 1, wherein the first and second water-absorbing base materials comprise synthetic zeolite of which each hole diameter of a porous structure is formed to the size of a water molecule.

[Claim 3]

The fresh-water generating apparatus according to claim 1, wherein the first and second water-absorbing base materials comprise nanocarbon of which each hole diameter of a porous structure is formed to the size of a water molecule.

[Claim 4]

The fresh-water generating apparatus according to any of claims 1 to 3, wherein the first and second water-absorbing base materials are connected at an upper adjacent surface on which the base materials are disposed, and are formed integrally in the shape of an upside-down letter U.

[Claim 5]

The fresh-water generating apparatus according to any of claims 1 to 4, wherein an air cooler is installed, compressed air being supplied to the air cooler, and

cold air jetted from the air cooler is supplied to the second storage tank while hot air exhausted from the air cooler is supplied to the intake side of the blowing means.