



(51) International Patent Classification:

B01D 29/11 (2006.01) **B01D 29/90** (2006.01)
B01D 29/52 (2006.01)

(21) International Application Number:

PCT/NL2014/050695

(22) International Filing Date:

7 October 2014 (07.10.2014)

(25) Filing Language:

English

(26) Publication Language:

English

(30) Priority Data:

2011597 11 October 2013 (11.10.2013) NL

(71) Applicant: **PWN TECHNOLOGIES B.V.** [NL/NL];
Rijksweg 501, NL-1991 AS Velsbroek (NL).

(72) Inventor: **KAMP, Petrus Cornelis**; Herenweg 288, NL-
1934 PW Egmond aan de Hoef (NL).

(74) Agent: **NEDERLANDSCH OCTROOIBUREAU**; J.W.
Frisolaan 13, NL-2517 JS The Hague (NL).

(81) Designated States (unless otherwise indicated, for every
kind of national protection available): AE, AG, AL, AM,
AO, AT, AU, AZ, BA, BB, BG, BH, BN, BR, BW, BY,
BZ, CA, CH, CL, CN, CO, CR, CU, CZ, DE, DK, DM,

DO, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, GT,
HN, HR, HU, ID, IL, IN, IR, IS, JP, KE, KG, KN, KP, KR,
KZ, LA, LC, LK, LR, LS, LU, LY, MA, MD, ME, MG,
MK, MN, MW, MX, MY, MZ, NA, NG, NI, NO, NZ, OM,
PA, PE, PG, PH, PL, PT, QA, RO, RS, RU, RW, SA, SC,
SD, SE, SG, SK, SL, SM, ST, SV, SY, TH, TJ, TM, TN,
TR, TT, TZ, UA, UG, US, UZ, VC, VN, ZA, ZM, ZW.

(84) Designated States (unless otherwise indicated, for every
kind of regional protection available): ARIPO (BW, GH,
GM, KE, LR, LS, MW, MZ, NA, RW, SD, SL, ST, SZ,
TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, RU,
TJ, TM), European (AL, AT, BE, BG, CH, CY, CZ, DE,
DK, EE, ES, FI, FR, GB, GR, HR, HU, IE, IS, IT, LT, LU,
LV, MC, MK, MT, NL, NO, PL, PT, RO, RS, SE, SI, SK,
SM, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ,
GW, KM, ML, MR, NE, SN, TD, TG).


Published:

- with international search report (Art. 21(3))
- before the expiration of the time limit for amending the
claims and to be republished in the event of receipt of
amendments (Rule 48.2(h))

(88) Date of publication of the international search report:
4 June 2015

(54) Title: FILTER DEVICE HAVING A DIVERGING CLEANING DUCT WITH INTERNAL PARTITIONS

Fig. 4



(57) Abstract: The invention relates to a filter device comprising a housing with an end part and a side wall and containing an axi-
ally arranged array of filter elements, such as ceramic elements. An inlet in the end part supplies fluid to the filter elements and an
outlet in the side wall is provided for transporting filtered fluid from the housing, the side wall of the filter device being provided
with a cleaning duct for supplying cleaning fluid to the filter elements via the side wall. The cleaning duct 6 comprises a distal chan-
nel portion 15 having a relatively small diameter D1 and a proximal portion 16 adjacent the side wall having a relatively large dia-
meter D2. A number of partitions 36,37 extend in the proximal portion from a position at or near the sidewall towards the distal
channel portion 15 at an angle (β) to a centre line 20 of the cleaning duct 6.

