



SHARED DATA PURIFYING APPARATUS AND
SHARED DATA PURIFYING METHOD

Field of the Invention

5 The present invention relates to a shared data purifying apparatus for and shared data purifying method of purifying shared data containing errors so as to produce errorless shared data for communication using quantum cryptography or the like.

10 Background of the Invention

 For example, a prior art error correction method for use with quantum cryptography is disclosed in "INTRODUCTION TO QUANTUM COMPUTATION AND INFORMATION" (EDITOR: Hoi-Kwong Lo, et al.). Some protocols defining procedures are proposed to
15 implement the quantum cryptography, and among them BB84 protocol is currently assumed to be a standard protocol for the quantum cryptography. After that, this protocol has been improved and is provided as a protocol effective even in noisy realistic communication paths. The improved BB84 protocol
20 described in "Experimental Quantum Cryptography" (C.H.Bennett, F.Bessette, G.Brassard, L.Salvail and J.Smolín, J.Cryptology Vol.5, pp.3-28) roughly consists of two parts: a first procedure for sharing physically-safe initial data using a quantum communication path and a second procedure for correcting errors
25 included in the initial data by using an error correction method on a public line (i.e., a classical path), and for reducing a volume of information leaking to third parties in terms of information theory. The first procedure of roughly sharing data by using a quantum communication path is unrelated directly
30 to the present invention. The BB84 protocol is referred to as



this improved BB84 protocol from here on. The present invention relates to "the second procedure for correcting errors included in the initial data, and for reducing a volume of information leaking to third parties in terms of information theory". The
5 prior art method can be explained as follows.

With the current state of the art, the shared data that appear in the first half of the BB84 protocol include errors that occur at a rate of about 1%. These errors result from the accuracy or the like of the apparatus that is affected by
10 fluctuations, such as thermal noise, and reflected light, which appear in the communication path. Third party involvement can also cause an error. Although the biggest feature of the quantum cryptography is that it is possible to detect third party involvement as an error, that may be true under ideal
15 circumstances. As previously mentioned, it is impossible at this stage to judge whether the occurrence of an error is caused by a leakage that blends into the level of a rate of errors caused spontaneously or by third party involvement. Furthermore, although according to the BB84 protocol the transmitter roughly
20 shares data with the receiver, the system does not properly function in most cases if the shared data include errors that occur at a rate as much as 1%. When the shared data is used as key data in common key cryptographic scheme, for example, it is to be understood at once that even a single-bit error is
25 not included in the shared data. To solve this problem, there has been provided a method of removing errors while preventing information from leaking to wiretappers as much as possible, simultaneously throwing away information leaked during quantum communications, and sharing only safe data between the
30 transmitter and the receiver. This method is called error

correction and privacy amplification.

The principle of the error correction method is simple. In accordance with the method, it is assumed that there is shared data containing some errors between the transmitter and the receiver. The shared data is divided into some blocks, and single-bit parities are compared with each other for each block. At this time, because a public line is used, it can be generally assumed that the parity information can be also leaked to wiretappers. Therefore, in this case the volume of leaked information is 1 bit in terms of information theory, and 1 bit of the roughly-shared data being held now is thrown away to make them balance each other out. The processing on blocks whose parities agree with those of corresponding blocks is then terminated for the time being. Each block whose parity does not agree with that of the corresponding block is further divided into equal halves, and a similar parity check is then performed on each of them. Two-branch searching is repeatedly carried out until an erroneous bit is detected, and this erroneous bit is finally corrected. Thus, (the number of parity bits used for the two-branch searching + 1) bits are thrown away, and remaining bits are defined as a candidate of the shared information. This is because when an even number of errors are included in each block of the shared data the parities agree with each other between the shared data being held by the transmitter and that being held by the receiver and no error cannot be detected, and therefore in accordance with the prior art method bits of the shared data are appropriately inverted and erroneous bits are surely removed by repeating the same processing from the beginning several times. In accordance with the privacy amplification method, even if the

above-mentioned error correction is carried out, there is a possibility that there exist bits that have not been detected as erroneous bits even when a wiretapper taps the shared data, though the bits are few in number. To prevent the possibility of part of the information being tapped, each of the transmitter and the receiver carries out a process of further improving the safety by implementing a hash operation on the shared information and assuming the hash value as final shared data. This method is the so-called privacy amplification method.

10 A t -resilient function for use in the prior art method will be explained hereafter.

f is a Boolean function: $Z_2^n \rightarrow Z_2^m$ ($n > m$), where Z_2 is Z_2 and 2^n is the n -th power of 2.

By definition, the fact that f is balanced (or equitable) means that a reverse image $f^{-1}(y)$ of f has 2^{n-m} elements for all m -bit strings y .

This definition is equivalent to the fact that when y is an output and an input x is chosen at random, $P(y)$ becomes 2^{-m} for all m -bit strings y , assuming that the probability of $f(x) = y$ is $P(y)$. Then, assume that t bits of the input x input to f are fixed. In other words, assume that

$$x_{\{i_1\}} = c_1, \dots, x_{\{i_t\}} = c_t$$

where $x_{\{i_1\}}$ is x_{i_1} and c_1 is c_{i_1} , and $x_{\{i_t\}}$ is x_{i_t} and c_t is c_{i_t} .

25 Assume that $P(y \mid x_{\{i_1\}} = c_1, \dots, x_{\{i_t\}} = c_t)$ is the probability of $f(x) = y$ on condition that $x_{\{i_1\}} = c_1, \dots, x_{\{i_t\}} = c_t$.

By definition, the fact that f is correlation-immune of order t means that $P(y \mid x_{\{i_1\}} = c_1, \dots, x_{\{i_t\}} = c_t) = P(y)$ is established for all $x, y, c_1, c_2, \dots$, and c_t .

In the above description, 2^{-m} means 2^{-m} .

It is to be understood through intuition that even though t bits of the n -bit string x has come to light to a wiretapper, the probability that the wiretapper can estimate $f(x) = y$ is made to become $P(y) = 2^{-m}$ after making f act on the n -bit string x . This probability is the same as that in the case where nothing has to come to light to the wiretapper. In other words, the probability is 2^{-m} . Regardless of whether or not t bits of the n -bit string x has come to light to the wiretapper, an m -bit shared key has an m -bit entropy (the estimated probability is 2^{-m}) by making f act on the n -bit string x when viewed from the wiretapper.

By definition, the fact that f is a t -resilient function means that f is balanced and is correlation-immune of order t .

This definition is equivalent to the fact that $P(y | x_{\{i_1\}} = c_1, \dots, x_{\{i_t\}} = c_t) = 2^{-m}$ is established for all possible variables.

It is to be understood through intuition that f is made to act on the n -bit string x even if some bits (t bits or less) of them have come to light to the wiretapper, so that the bit length of the shared key is shortened from n bits to m bits.

At this time, because some bits of x (i.e., the n -bit string) have come to light to the wiretapper, the probability of estimating the n -bit string x becomes smaller than 2^{-n} when viewed from the wiretapper. In other words, the complete safety is not achieved (the complete safety of the n -bit string x means that the probability of estimating the n -bit string x must be just 2^{-n}).

On the other hand, for $y = f(x)$ (i.e., the m -bit string), the probability of the wiretapper estimating y is just 2^{-m} .

In other words, there is entropy of m bits.

Therefore, t is assumed to be a maximum of the number of bits that can be tapped by Eve in the quantum communication while being buried in errors. Accordingly, the value of t must be
5 determined according to the error rate.

Therefore, if n is determined, t is determined according to the error rate, the t -resilient function is constructed, and the communication protocol is designed so that m is sufficiently large, even if some bits are leaked to a wiretapper during
10 initial key exchanging, the complete safety (the complete safety intuitively means that the probability that the wiretapper estimates a key of m bits must be just 2^{-m} if it is assumed that m to be a security parameter) can be achieved by using the t -resilient function.

15 By the way, a method of constructing the t -resilient function may be known to the wiretapper. In other words, the t -resilient function is public information.

A problem encountered with the prior art method is that while a t -resilient function is made to act on data to be
20 transmitted to improve the safety of transmission, there doesn't exist a proper method of constructing the t -resilient function in all cases, depending on the bit length of the input data, the output bit length, and security parameters.

The present invention is proposed to solve the
25 above-mentioned problem, and it is therefore an object of the present invention to provide a method that can deal with all the above-mentioned cases by using a general function, such as SHA-1, other than t -resilient functions.

It is another object of the present invention to provide
30 a method that can make the safety when sending and receiving

data result in the safety of the Vernam cipher encryption, and that provides higher safety in terms of information theory.

Disclosure of the Invention

5 In a shared data purifying apparatus in accordance with the present invention, after mixing each purification block by using a Hamming distance amplification effect, a transmitter Vernam-encrypts each purification block with disposable data and transmits it to a receiver.

10 As a result, the shared data purifying apparatus offers an advantage of reducing the risk of data being tapped.

 In a shared data purifying apparatus in accordance with the present invention, each of a transmitter and a receiver (i.e., a shared data purifying apparatus) divides
15 temporarily-shared data into one or more purification blocks and one or more disposable blocks, so that a Hamming distance between corresponding purification blocks being held by the transmitter and the receiver is enlarged by using a Hamming distance amplification effect.

20 As a result, the shared data purifying apparatus offers an advantage of easily determining whether temporarily-shared data being held by the transmitter is identical with or different from that being held by the receiver.

25 Brief Description of the Figures

 Fig. 1 is a diagram showing a shared data purifying system in accordance with embodiment 1 of the present invention;

 Fig. 2 is a block diagram showing a data processing means Y of the shared data purifying system in accordance with
30 embodiment 1 of the present invention;

Fig. 3 is a flow chart showing an operation of the shared data purifying system in accordance with embodiment 1 of the present invention;

Fig. 4A is a diagram showing division of temporarily-shared data X into purification data and disposable data in accordance with embodiment 1 of the present invention;

Fig. 4B is a diagram showing division of temporarily-shared data Y into purification data and disposable data in accordance with embodiment 1 of the present invention;

Fig. 5 is a diagram showing experimental results of the mixing performance of a hash function SHA-1;

Fig. 6 is a flow chart showing an operation of a shared data purifying system in accordance with embodiment 2 of the present invention;

Fig. 7 is a flow chart showing an operation of a shared data purifying system in accordance with embodiment 3 of the present invention;

Fig. 8A is a diagram for explaining a procedure for generating a Vernam-encrypted block X from a purification block in accordance with embodiment 3 of the present invention;

Fig. 8B is a diagram for explaining a procedure for generating a Vernam-encrypted block Y from a purification block in accordance with embodiment 3 of the present invention;

Fig. 9 is a diagram for explaining an estimation of erroneous positions in accordance with embodiment 3 of the present invention;

Fig. 10 is a flow chart showing an operation of a shared data purifying system in accordance with embodiment 4 of the present invention;

Fig. 11 is a flow chart showing an operation of a shared

data purifying system in accordance with embodiment 5 of the present invention;

Fig. 12A is a diagram showing division of temporarily-shared data X into purification data and disposable data in accordance with embodiment 5 of the present invention;

Fig. 12B is a diagram showing division of temporarily-shared data Y into purification data and disposable data in accordance with embodiment 5 of the present invention;

Fig. 13 is a diagram showing a shared data purifying system in accordance with embodiment 6 of the present invention; and

Fig. 14 is a flow chart showing an operation of the shared data purifying system in accordance with embodiment 6 of the present invention.

15 Preferred Embodiments of the Invention

In order to explain the present invention in greater detail, the preferred embodiments will be described below with reference to the accompanying figures.

Embodiment 1.

Fig. 1 is a diagram showing a shared data purifying system according to this embodiment, Fig. 2 is a block diagram of a data processing means of this shared data purifying system, Fig. 3 is a flow chart showing an operation of this shared data purifying system, and Figs. 4A and 4B are diagrams showing division of temporarily-shared data X and Y into purification data and disposable data.

In Fig. 1, reference numeral 1 denotes a transmitter, reference numeral 2 denotes a receiver, reference numeral 3 denotes a quantum communication line that connects the transmitter 1 with the receiver 2, and reference numeral 4

denotes a public network that connects the transmitter 1 with the receiver 2.

In addition, reference numeral 11 denotes a communication means X included in the transmitter 1, which is connected with
5 a communication means Y 21 included in the receiver 2. Each of the communication means X 11 and the communication means Y 21 can contain both a quantum communication means and a public communication means.

The quantum communication line 3 has a high possibility
10 that errors of about 1 percent occur during transmission of data. In the public network 4, an error correction code, such as a Reed-Solomon code, is added to data by either of the communication means X 11 and the communication means Y 21, and data can be corrected even if the data includes errors.

15 Reference numerals 12 and 22 denote a data processing means X and a data processing means Y that are included in the transmitter 1 and the receiver 2, respectively, each of them consisting of a CPU, a RAM, and so on. Reference numerals 13 and 23 denote a data storage means X and a data storage means
20 Y that are included in the transmitter 1 and the receiver 2, respectively, each of them consisting of either a volatile memory such as a RAM or a nonvolatile memory such as a flash memory or a hard disk drive.

In Fig. 2, reference numeral 221 denotes a block
25 generating means, reference numeral 222 denotes a data mixing means, reference numeral 223 denote a decrypted block generating means, reference numeral 224 denotes an identity judgment means, reference numeral 225 denotes an error correcting means, and these components are included in the data
30 processing means Y 22.

The receiver 2 is a shared data purifying apparatus.

Next, an operation of the shared data purifying system will be explained with reference to the flow chart of Fig. 3.

First of all, in step 101, the communication means X 11
5 transmits data for transmission stored in the data storage means
X 13 of the transmitter 1 to the receiver 2 by using quantum
cryptography communications through the quantum communication
line 3. The receiver 2 receives this data by way of the
communication means Y 21 and then stores the data in the data
10 storage means Y 23. As a result, although the transmitter 1
and the receiver 2 share the data for transmission with each
other, there is a possibility that this shared data in the
transmitter 1 is not completely identical to the shared data
in the receiver 2 due to errors that occur while the shared data
15 is transmitted from the transmitter 1 to the receiver 2 or
trapping by a third party. This is expressed by "temporary
sharing" in Fig. 3. Hereafter, the data for transmission stored
in the data storage means X 13 is referred to as
temporarily-shared data X and the data for transmission stored
20 in the data storage means Y 23 is referred to as
temporarily-shared data Y.

The transmitter 1, in step 102, divides the temporarily
shared data X, which are temporarily shared in step 101, into
purification data Ax and disposable data Bx used to generate
25 Vernam-encrypted data, as shown in Fig. 4A, and the receiver
2, in step 110, divides the temporarily shared data Y, which
are temporarily shared in step 101, into purification data Ay
and disposable data By used to generate Vernam-encrypted data,
as shown in Fig. 4B. Fig. 4A is a diagram showing the division
30 of the temporarily shared data X. In the figure, reference

numeral 301 denotes the temporarily shared data X, reference numeral 302 denotes the purification data Ax, reference numeral 303 denotes the disposable data Bx, and reference numeral 304 denotes a remainder. Furthermore, Fig. 4B is a diagram showing the division of the temporarily shared data Y. In the figure, reference numeral 305 denotes the temporarily shared data Y, reference numeral 306 denotes the purification data Ay, reference numeral 307 denotes the disposable data By, and reference numeral 308 denotes a remainder. The data processing means X 12 carries out the division of the temporarily-shared data X, and the data processing means Y 22 (i.e., a block generating means) carries out the division of the temporarily-shared data Y.

In addition, the purification data Ax of the temporarily shared data X is divided into n purification blocks Axr ($r = 1$ to n) each having an equal bit number P, and the disposable data Bx is divided into n disposable blocks Bxr ($r = 1$ to n) each having an equal bit number Q. Similarly, the purification data Ay of the temporarily shared data Y is divided into n purification blocks Ayr each having an equal bit number P, and the disposable data By is divided into n disposable blocks Byr each having an equal bit number Q. The plurality of purification blocks Axr and the plurality of disposable blocks Bxr are stored in a RAM within the data processing means X 12, and the plurality of purification blocks Ayr and the plurality of disposable blocks Byr are stored in a RAM within the data processing means Y 22. As an alternative, the plurality of purification blocks Axr and the plurality of disposable blocks Bxr can be stored in the data storage means X 13, and the plurality of purification blocks Ayr and the plurality of

disposable blocks By_r can be stored in the data storage means
Y 23.

Because the number of bits of the temporarily shared data
X is equal to that of the temporarily shared data Y, each of
5 them can be L bits, as can be seen from Figs. 4A and 4B, the
number of blocks n into which each of Ax , Bx , Ay , and By is divided
can be obtained from the following equation.

$$L = (P + Q) \cdot n + \alpha \quad (\alpha < P+Q)$$

10

In this case, the remainder of α bits is not used. The division
is thus carried out according to such a predetermined division
rule.

The rate of errors that occur between the purification
15 blocks Ax_r and Ay_r at the same suffix r and between the disposable
blocks Bx_r and By_r at the same suffix r depends on the quality
of the quantum communication line 3 and can be assumed to be
about 1 percent.

Steps 103 and later of the transmitter 1 are carried out
20 in parallel with one another for each suffix r ($r = 1$ to n),
and steps 111 and later of the receiver 2 are also carried out
in parallel with one another for each suffix r ($r = 1$ to n).
In other words, the n identical processes progress in parallel
in each of the transmitter and the receiver. The case of $r =$
25 r will be explained hereafter.

The transmitter 1 and the receiver 2 mix the purification
blocks Ax_r and Ay_r , respectively, by using a Hamming distance
amplification effect, such as a hash function, (i.e., according
to a data mixing rule), and, after mixing them, convert them
30 into mixed blocks Cx_r and Cy_r in steps 103 and 111, respectively.

Each of the mixed blocks C_{xr} and C_{yr} has Q bits. The data processing means X_{12} and the data processing means Y_{22} (i.e., a data mixing means) carry out these conversion processes, respectively.

5 The Hamming distance between two digital data is the number of bit positions in which the two digital data disagree. The Hamming distance amplification effect is to use either a Hamming distance increase function F , as defined in (a), or an exclusive-OR entropy enhancement function, as defined in (b).

10 (a) Hamming distance increase function F : that provides a Hamming distance between $F(s)$ and $F(r)$, which is equal to or longer than d , $F(s)$ and $F(r)$ being respectively mappings of an arbitrary bit string s and each of all bit strings r having a Hamming distance equal to or shorter than a small number ε that
15 exists for the arbitrary bit string s , where $d \gg 1$.

(b) Exclusive-OR entropy enhancement function: that increases the entropy of the logical exclusive-OR of two bit strings.

The reason why this processing is carried out will be
20 explained hereafter. In other words, while the Hamming distance amplification effect on two identical data results in their mappings having the same value, the Hamming distance amplification effect on two data, which are different from each other at least one bit position thereof, results in their
25 mappings having quite different values. That is, it can be thought that the Hamming distance of 1 bit or more between two different data is enlarged to the one that is about one-half of their data size. This is a feature of the present invention.

In this specification, the purification block A_{xr} is a
30 second purification block, the purification block A_{yr} is a first

purification block, the disposable block Bxr is a second disposable block, the disposable block Byr is a first disposable block, the mixed block Cxr is a second mixed block, and the mixed block Cyr is a first mixed block.

5 Because the size of each of the mixed blocks Cxr and Cyr becomes 160 bits if "SHA-1" that is a well-known hash function is used as the Hamming distance amplification effect (i.e., the data mixing rule), $Q = 160$. Therefore, each of the disposable blocks Bxr and Byr has to have 160 bits.

10 Next, as shown in Fig. 3, the transmitter 1 calculates a random number sequence as the disposable block Bxr having the same size as this mixed block Cxr, which has been mapped (or mixed), and implements an exclusive-OR (XOR) operation on the mixed block Cxr and the disposable block Bxr by using the data
15 processing means X 12. The transmitter 1 then sends the calculation result, as the transmission block Dr, to the receiver 2 by way of the public network 4 by using the communication means X 11. In other words, the transmitter 1 sends the calculation result as Vernam-encrypted data. The
20 transmission block Dr has a size of Q bits.

 Vernam-encrypted data is encrypted data in which safety has been proven in terms of information theory when a bit string to be transmitted has the same length as a random number sequence that is the other one on which an XOR operation is implemented.
25 At this time, the random number sequence can be used only once.

 The transmission block Dr is an encrypted block.

 When the receiver 2 receives the transmission block Dr by way of the communication means Y 21, the receiver 2 implements an XOR operation on the transmission block Dr and the disposable
30 block Byr by using the data processing means Y 22 (i.e., a

decrypted block generating means and an identity judgment means) first in step 112. The receiver then sets the calculation result to a made-for-verification block E_r , and compares this made-for-verification block E_r with the mixed
 5 block C_{yr} .

In other words,

$$E_r = D_r \text{ XOR } B_{yr}$$

(where XOR shows the exclusive-OR operation)

10

Because $D_r = C_{xr} \text{ XOR } B_{xr}$,

$$E_r = D_r \text{ XOR } B_{yr}$$

$$= (C_{xr} \text{ XOR } B_{xr}) \text{ XOR } B_{yr}$$

15 Because $E_r = C_{xr}$ if B_{xr} and B_{yr} are identical with each other, the comparison between the made-for-verification block E_r and the mixed block C_{yr} is equivalent to the comparison between the mixed blocks C_{xr} and C_{yr} .

Actually, there is a possibility that the disposable
 20 blocks B_{xr} and B_{yr} are not identical with each other in a strict sense, but have an error rate of about 1 percent, as previously mentioned.

The made-for-verification block E_r is a decrypted block, and it is a decrypting rule to implement an XOR operation on
 25 the transmission block D_r and the disposable block B_{yr} .

Because the size of each of the mixed blocks C_{xr} and C_{yr} becomes 160 bits if "SHA-1" that is a well-known hash function is used as the Hamming distance amplification effect, $Q = 160$. Therefore, each of the disposable blocks B_{xr} and B_{yr} has to have
 30 160 bits.

Furthermore, if the purification blocks A_{xr} and A_{yr} are quite the same data as each other, the mixed blocks C_{xr} and C_{yr} become quite the same data. If the purification blocks A_{xr} and A_{yr} have even a single bit error, the mixed blocks C_{xr} and C_{yr} become quite different data under the influence of the Hamming distance amplification effect in steps 103 and 111.

Fig. 5 shows experimental results showing the performance of mixing data by the hash function "SHA-1".

The bit length of the input is fixed to 512 bits in this experiment. The figure shows what the Hamming distance between the outputs of two 512-bit data that are different from each other at only 1 bit position thereof is with a histogram of 10 million samples. The vertical axis shows frequencies normalized with the entire number of samples. Therefore, the probability of occurrence of the Hamming distance of 80 is 6% or more.

In this experiment, the mean value (m) is 79.999550 and the standard deviation (σ) is 6.327267. We further carried out experiments so as to also determine what the Hamming distance between the outputs of two 512-bit data that are different from each other at only two bit positions thereof is, and what the Hamming distance between the outputs of two 256-bit data that are different from each other at only one bit position thereof is. In those cases, the experiment results show a normal distribution having a means value of about 80 and a standard deviation of about 6.3. In other words, it has been proven that almost every pair of bit strings is converted into a pair of bit strings having no correlation to each other and a Hamming distance of about 80. Furthermore, as can be seen from the graph, the amount of variance is small and there is a peak at the Hamming

distance of about 80 while the total number of bits is 160 bits. In general, users can set a security margin as a confidence interval. The width of the confidence interval can be set to $6 \cdot \sigma = 38$ that will be generally accepted by users. Actually,
 5 a minimum Hamming distance that appears in the case of the above-mentioned experiment using SHA-1 is 44, and the frequency of occurrence of the minimum Hamming distance is as very low as 1 or 2. Therefore, in the case of using SHA-1, $80 - 38 = 42$ bits can be set to be a threshold used for judging whether
 10 or not two arbitrary bit strings are identical with each other.

In other words, when SHA-1 is chosen as a function having the Hamming distance amplification effect, it can be assumed that $x_1 = x_2$ with a very high possibility if the Hamming distance between $f(x_1)$ and $f(x_2)$ is 42 or less for the two
 15 bit strings x_1 and x_2 .

As can be seen from the above description, when the Hamming distance between the purification blocks A_{xr} and A_{yr} is 1 or more and is sufficiently smaller than one-half of the number of bits included in each of the purification blocks A_{xr} and A_{yr}
 20 (e.g., 1/100 or less), the hash function SHA-1 mixes the purification blocks A_{xr} and A_{yr} so that the Hamming distance between the mixed blocks C_{xr} and C_{yr} becomes longer than that between the purification blocks A_{xr} and A_{yr} .

Furthermore, assuming that the bit number of each of the
 25 purification blocks A_{xr} and A_{yr} is LA , the Hamming distance between them is HA , the bit number of each of the mixed blocks C_{xr} and C_{yr} is LC , the Hamming distance between them is HC , a before-mixing Hamming distance ratio is HA/LA , and an after-mixing Hamming distance ratio is HC/LC , when the
 30 before-mixing Hamming distance ratio exceeds 0 and is

sufficiently smaller than 0.5 (e.g., 0.01 or less), the after-mixing Hamming distance ratio becomes larger than the before-mixing Hamming distance ratio, and becomes 0.5 ± 0.25 when the confidence interval is assumed to be ± 0.25 , for example.

5 In this case, $38/160$ is approximated at 0.25.

In addition, in this embodiment, in consideration of a rate (about 1%) of errors that occur between the disposable blocks Bxr and Byr, because $42-160 \cdot 0.01 = 40.4$ the mixed blocks Cxr and Cyr are the same as each other and therefore the purification blocks Axr and Ayr are identical with each other if the Hamming distance between the made-for-verification block Er and the mixed block Cyr is 40 or less in step 112, and the data processing means Y 22 then judges that "they are identical with each other". In other words, the data processing means Y 22 judges that "they are identical with each other" if the physical error rate is equal to or smaller than 25 percents.

Furthermore, because when the Hamming distance between the made-for-verification block Er and the mixed block Cyr exceeds 40 the mixed blocks Cxr and Cyr are different from each other and therefore the purification blocks Axr and Ayr are not identical with each other, the data processing means Y 22 judges that "they are different with each other".

Therefore, in this embodiment the "predetermined value" of the Hamming distance in step 112 of Fig. 3 is 40.

25 When the data processing means Y 22 judges that "they are identical with each other" in step 112, the receiver 2 notifies the transmitter 1 that they are identical with each other by way of the public network 4 by using the communication means Y 21 (in step 113). The receiver 2 further stores the purification block Ayr at a position of a purified-data storing

area (not shown in the figure), which is specified by the value of the suffix r , within the data storage means $Y\ 23$ (in step 114), and finishes the process about this block (in step 115).

The transmitter 1 receives the judgment result sent thereto from the receiver 2 by way of the communication means $X\ 11$, and then checks the judgment result by using the data processing means $X\ 12$ (in step 105). When the judgment result indicates "They are identical with each other", the transmitter 1 finishes the process about that block (in step 106). As a result, the purification blocks A_{xr} and A_{yr} that are identical with each other are stored in the data storage means $X\ 13$ and the storage means $Y\ 23$, respectively, and are completely shared between the transmitter 1 and the receiver 2.

"Completely shared" means that the transmitter 1 and the receiver 2 hold the same data.

The data processing means $X\ 12$ and the data processing means $Y\ 22$ store information indicating which purification blocks can be completely shared between the transmitter and the receiver, i.e., the value of the suffix r of the purification blocks A_{xr} and A_{yr} that can be completely shared between the transmitter and the receiver in their respective "complete block number registers" (not shown in the figure) in the order that the complete sharing of the purification blocks A_{xr} and A_{yr} are complete. Furthermore, each of the data processing means $X\ 12$ and the data processing means $Y\ 22$ counts the number of purification blocks that have been completely shared between the transmitter and the receiver, and, when the number of completely-shared purification blocks becomes n , determines that all the purification blocks are completely shared between the transmitter and the receiver and therefore the purification

data Ax and Ay can be completely shared between the transmitter and the receiver.

When the data processing means Y 22 judges that "they are different from each other" in step 112, the receiver 2 notifies
 5 the transmitter 1 that they are different from each other by way of the communication means Y 21 and waits for an error correction code for the purification block Axr to be sent from the transmitter 1 (in step 116).

The transmitter 1 receives the judgment result sent
 10 thereto from the receiver 2 by way of the communication means X 11, and checks the judgment result by using the data processing means 12 (in step 105) and then, in step 107, generates an error correction code Arc for the purification block Axr (correction information) when the judgment result indicates that they are
 15 different from each other.

This error correction code Arc is information used to make the purification block Ayx agree with the purification block Axr.

A rough estimation of the length of a redundant code which
 20 makes it possible to carry out error correction using a Reed-Solomon code will be made hereafter. First, assume that a Reed-Solomon code on $GF(2^8)$ is used. In addition, assume that errors are not burst errors but random errors, and the average bit error rate is 1%. A coded word has 255 ($= 2^8 - 1$) bytes ·
 25 $8 = 2040$ bits on this descriptor, and $2040 \times 0.01 \approx 21$ error bits exist therein on average. Assuming that a single-bit error occurs per 1 symbol ($= 1$ byte in this case), it is understood that there is an error in each of 21 bytes of 255 bytes. At this time, the number of check symbols that are defined for the
 30 Reed-Solomon code, i.e., the length of the redundant code

becomes 42 bytes that is twice as large as 21 bytes. Therefore, in the case that the code length is 255 bytes, the information length is 213 bytes and the redundant length is 42 bytes, and therefore the ratio between them is about 1 : 0.2. When applying
 5 the error correction using a Reed-Solomon code to this embodiment, in accordance with the above-mentioned setting of the ratio, it is necessary to generate a redundant code having a length of about 20 percent of the target code to be corrected, and to send it as a Vernam-encrypted code after implementing
 10 an XOR operation on the redundant code and a random number sequence, depending on the size and bit error rate of the descriptor, of course.

While the transmitter 1 implements an exclusive-OR operation on the error correction code Arc and data (i.e., data
 15 for encryption) having the same length as the error correction code Arc, and transmits the exclusive-OR result, as Vernam-encrypted data, to the receiver 2, in step 107, the receiver 2 has to have the same data for encryption. Then, the data processing means X 12 reads the smallest one s of the numbers
 20 (i.e., the values of suffixes r) of other blocks that have already been completely shared from the above-mentioned "Completely-shared block number register", and reads the purification block Axs having the block number s from the data storage means X 13. The data processing means X 12 then
 25 implements an exclusive-OR operation on data including a number of leading bits of the purification block Axs, the number of leading bits being the same as the number of bits included in the error correction code Arc, and the error correction code Arc so as to generate Vernam-encrypted data, and transmits it,
 30 as an encryption error correction code, to the receiver 2

through the public network 4 by using the communication means X 11.

In addition, the data processing means X 12 stores the block number s in the "Completely-shared block number register" and increments the number of purification blocks that have been completely shared between the transmitter and the receiver.

The receiver 2, in step 117, receives this encryption error correction code by way of the communication means Y 21, and the data processing means Y 22 (error correcting means) reads the smallest one s of the numbers (i.e., the values of suffixes r) of other blocks that have already been completely shared from the above-mentioned "Completely-shared block number register", and reads the purification block Ays having the block number s from the data storage means Y 23. The data processing means Y 23 then implements an exclusive-OR operation on data (i.e., data for decryption) including a number of leading bits of the purification block Ays , the number of leading bits being the same as the number of bits included in the received encryption error correction code, and the received encryption error correction code so as to decrypt the Vernam-encrypted data, makes an error correction to the purification block Ayr using the decrypted error correction code Arc , and stores the error-corrected purification block Ayr in the data storage means Y 23.

In addition, the data processing means Y 23 stores the value of the suffix r (i.e., the block number s) in the "Completely-shared block number register" and increments the number of purification blocks that have been completely shared.

The above-mentioned data for encryption and the above-mentioned data for decryption are identical with each

other.

As previously explained, in steps 107 and 117, the data processing means reads the smallest one s of the numbers of other blocks that have already been completely shared from the above-mentioned "Completely-shared block number register". At that time, when there is no purification block that has already been completely shared and therefore the "Completely-shared block number register" is empty, the data processing means interrupts the processing of step 107 until it completes the completely sharing of either of remaining purification blocks and stores the corresponding block number in the "Completely-shared block number register".

In the flow chart of Fig. 3, step 101 is a temporarily-shared data transmission step, step 102 is a second block generation step, step 103 is a second mixed block generation step, step 104 is an encrypted block generation step, step 105 is a second identity judgment step, step 106 is an ending step, step 107 is a correction information transmission step, step 110 is a first block generation step, step 111 is a first mixed block generation step, step 112 is an identity judgment step, steps 113 and 114 are a first purification block storage step, step 116 is a judgment result transmission step, and step 117 is an error correction step.

As mentioned above, in accordance with this embodiment, because the shared data purifying apparatus performs an error correction, it makes it possible for the transmitter and the receiver to completely share the same data without throwing away a lot of data compared with the prior art shared data purifying method. When the hash function SHA-1 is used as the Hamming distance amplification effect, for example, it is estimated

that the hash function SHA-1 can generate a 160-bit hash value from data of $2^{64}-1$ bits or less. More concretely, it is assumed that the hash function SHA-1 generates a 160-bit hash value from data of 10,000 bits. Furthermore, assume that the error rate is as extremely small as about 0.01% (although this error rate cannot be provided in present quantum cryptography experiments, a following explanation will be made based on this assumption). Data of 10,000 bits can have about one error. Because the hash value has 160 bits, disposable data that is used as Vernam-encrypted data will have 160 bits. Therefore, if no error is included in the data of 10,000 bits, because 160 bits are thrown away and 9,840 bits are shared between the transmitter and the receiver, data having about 98% or more of the length of the original data can be picked up as shared data. In contrast, when the data includes errors, an error correction code is generated for the data of 10,000 bits. Assuming that these errors can be corrected with a redundant code having about 30% of the length of the original data, it is necessary to send data of 3,000 bits as Vernam-encrypted data to the receiver. Therefore, the disposable data finally has $160 + 3,000 = 3,160$ bits in all, and, as a result, about 70% of the original data can be saved because 6,840 bits of the original data can be shared between the transmitter and the receiver.

Furthermore, in accordance with this embodiment, each of the transmitter and the receiver (i.e., the shared data purifying apparatus) divides temporarily-shared data into a plurality of purification blocks and a plurality of disposable blocks, and enlarges the Hamming distance between corresponding purification blocks being held by the transmitter and the receiver by using a Hamming distance amplification effect. As

a result, the present embodiment offers an advantage of easily judging whether the temporarily-shared data stored in the transmitter is identical with or different from that stored in the receiver.

5 Particularly, when each block that is temporarily shared between the transmitter and the receiver has a Hamming distance sufficiently smaller than 50% of its data size, because the Hamming distance is enlarged after the block is mixed, the shared data purifying apparatus judges whether the
10 temporarily-shared data stored in the transmitter is identical with or different from that stored in the receiver more effectively.

 Furthermore, in accordance with this embodiment, the transmitter and the receiver carry out error corrections when
15 the temporarily-shared data stored in the transmitter is identical with or different from that stored in the receiver. As a result, the present embodiment offers an advantage of making it possible for the transmitter and the receiver to share many pieces of identical data with each other.

20 In addition, in accordance with this embodiment, the transmitter Vernam-encrypts each purification block with disposable data and transmits it to the receiver after mixing each purification block by using the Hamming distance amplification effect. As a result, the present embodiment
25 offers another advantage of reducing the risk of data being tapped.

 Furthermore, in accordance with this embodiment, each of the transmitter and the receiver divides the temporarily-shared data into a plurality of blocks (a pair of a plurality of
30 purification blocks and a plurality of disposable blocks). As

a result, the present embodiment offers another advantage of making it possible for the transmitter to transmit an error correction code (i.e., correction information) to the receiver by using data on other blocks that have been completely shared successfully, thereby improving the safety of hiding of data.

In addition, in accordance with this embodiment, in each of the transmitter and the receiver there is provided a completely-shared block number register in which the numbers of blocks that have been completely shared successfully are stored. As a result, the present embodiment offers another advantage of speeding up the process of Vernam-encrypting and transmitting error correction codes.

Furthermore, in accordance with this embodiment, the shared data purifying apparatus determines whether the first purification block and the second purification block are identical with or different from each other by using the Hamming distance between the decrypted block and the first mixed block. As a result, the present embodiment offers another advantage of being able to flexibly change the judgment reliability by changing a reference value (i.e., a predetermined value) for use in the judgment of whether or not the Hamming distance exceeds the predetermined value.

In accordance with this embodiment, instead of the above-mentioned hash function SHA-1, another hash function can be used as the Hamming distance amplification effect.

Although it is assumed that the "predetermined value" in step 112 of Fig. 3 to be 40, the predetermined value can be 42 because the sufficient reliability can be provided even though the predetermined value is 42 (i.e., the confidence interval of 6σ) as previously explained as to the experimental results.

In addition, in the case of using another hash function other than the hash function SHA-1, the predetermined threshold can be another value according to the number of output bits and data mixing characteristics.

5 Furthermore, the Hamming distance amplification effect only has to be a means of mixing data and is not limited to a hash function. For example, an encryption function for use with common key encryptions, such as DES and MISTY, and public key encryptions, such as RSA, can be used as the Hamming distance
10 amplification effect.

 In addition, in accordance with this embodiment, the shared data purifying apparatus carries out quantum cryptography communications so that the transmitter 1 and the receiver 2 can share data with each other, as previously
15 mentioned. The shared data purifying apparatus can carry out communications via a public line instead of quantum cryptography communications, and can alternatively use communications other than cryptography communications. In other words, the transmitter 1 only has to transmit data to the
20 receiver 2 in order to share the data with the receiver 2 in step 101. Neither the format of data to be transmitted nor the transmission method of transmitting the data to the receiver are limited to the ones mentioned above.

 Furthermore, in accordance with this embodiment, P and
25 Q can be so determined that $n = 1$.

 In this case, the first purification data and the first purification block are identical with each other, the first disposable data and the first disposable block are identical with each other, the second purification data and the second
30 purification block are identical with each other, and the second

disposable data and the second disposable block are identical with each other.

In addition, in accordance with this embodiment, in steps 107 and 117 of the flow chart of Fig. 3, the transmitter and the receiver use parts of the purification blocks as data for encryption and data for decryption, respectively, as previously explained. As an alternative, in step 112, the shared data purifying apparatus can assume that the disposable blocks Bxr and Byr are completely shared between the transmitter and the receiver when the Hamming distance between the corresponding purification blocks is 0, and can use parts of the disposable blocks Bxr and Byr as data for encryption and data for decryption, respectively.

Furthermore, in accordance with this embodiment, in steps 103 and later of the transmitter 1 processes are carried out in parallel with one another for all suffixes r ($r = 1$ to n), and in steps 111 and later of the receiver 2 processes are also carried out in parallel with one another for all suffixes r ($r = 1$ to n), as previously mentioned. As an alternative, those processes can be carried out sequentially in the order of the block numbers r , starting from $r = 1$, in each of the transmitter 1 and the receiver 2. In this case, when it is determined that in step 112 "they are different from each other" for a certain block number u , and there is no other purification block that has been completely shared and the "Completely-shared block number register" is empty, the process about the block number u is interrupted and the process about the next block number will be started. Then, when the completely sharing of another purification block specified by another block number v is completed and the number v of the other purification block is

stored in "Completely-shared block number register", the process about the block number u is restarted and the error correction code is Vernam-encrypted by using the purification block specified by the block number v and is then decrypted.

5

Embodiment 2.

As previously mentioned, in the shared data purifying system in accordance with embodiment 1, the transmitter 1 generates and transmits an error correction code for each purification block to the receiver 2 only when the receiver 2 compares a made-for-verification block E_r with a mixed block C_{yr} and then judges that "they are different from each other".

In contrast, in a shared data purifying system in accordance with embodiment 2, a transmitter 1 generates and transmits an error correction code for every purification block to a receiver 2.

The shared data purifying system in accordance with this embodiment has the same structure as that of Fig. 1 as explained in Embodiment 1. Furthermore, each of the transmitter and receiver of the shared data purifying system divides temporarily-shared data into purification data and disposable data, as shown in Figs. 4A and 4B, like that of embodiment 1.

Fig. 6 is a flow chart showing an operation of the shared data purifying system in accordance with this embodiment.

In the flow chart of Fig. 6, in steps designated by the same reference numerals as shown in Fig. 3 the shared data purifying system carries out the same processes as those done by that of embodiment 1, and therefore the explanation of those processes will be omitted hereafter.

Even in this embodiment, in steps 103 and later of the

transmitter 1 of Fig. 6 processes are carried out in parallel with one another for all suffixes r ($r = 1$ to n), and in steps 111 and later of the receiver 2 processes are also carried out in parallel with one another for all suffixes r ($r = 1$ to n).

5 In other words, the n identical processes progress in parallel in each of the transmitter 1 and the receiver 2. The case of $r = r$ will be explained hereafter.

A data processing means X 12 of the transmitter 1 generates an error correction code $Axrc$ for the purification block Axr
10 in step 201.

The data processing means X 12 then, in step 202, reads the smallest one t of the numbers (i.e., the values of suffixes r) of other blocks that have already been completely shared from a "Completely-shared block number register", and reads the
15 purification block Axt having the block number t from a data storage means X 13. Then, in step 203 of generating an error correction code $Axtc$ for the purification block Axt , the data processing means X 12 implements an exclusive-OR (XOR) operation on a mixed block Cxr and a disposable block Bxr , and
20 defines the XOR operation result as a transmission block Dr , like that of embodiment 1. In addition, the data processing means X 12 implements an exclusive-OR operation on the above-mentioned error correction codes $Axrc$ and $Axtc$, defines the operation result as a correction code Gr for transmission,
25 and transmits it to the receiver 2 through a public network by using a transmission means X 11.

The data processing means X 12 further stores the block number specifying the purification block Axt in the "Completely-shared block number register", and increments the
30 number of purification blocks that have already been completely

shared.

When the receiver 2 receives the above-mentioned transmission block D_r and the above-mentioned correction code G_r for transmission by way of a communication means Y_{21} , the receiver 2 implements an XOR operation on the transmission block D_r and a disposable block B_{yr} by using a data processing means Y_{22} (i.e., a decrypted block generating means and an identity judgment means) in step 112, defines the XOR operation result as a made-for-verification block E_r , and compares this made-for-verification block E_r with a mixed block C_{yr} .

Like that of embodiment 1, when the Hamming distance between the made-for-verification block E_r and the mixed block C_{yr} is equal to or less than a predetermined value (e.g., 40), the data processing means Y_{22} , in step 112, judges that "they are identical with each other" because the mixed blocks C_{xr} and C_{yr} are identical with each other and therefore the purification blocks A_{xr} and A_{yr} are identical with each other.

In contrast, when the Hamming distance between the made-for-verification block E_r and the mixed block C_{yr} is greater than the predetermined value (e.g., 40), the data processing means Y_{22} judges that "they are different from each other" because the mixed blocks C_{xr} and C_{yr} are different from each other and therefore the purification blocks A_{xr} and A_{yr} are not identical with each other.

When the data processing means Y_{22} , in step 112, judges that "they are identical with each other", the receiver 2 stores the purification block A_{yr} at a position of a purified-data storing area (not shown in the figure), which is specified by the value of the suffix r , within a data storage means Y_{23} (in step 114), and finishes the process about this block (in step

115). As a result, the purification blocks A_{xr} and A_{yr} that are identical with each other are stored in the data storage means X_{13} and the storage means Y_{23} , respectively, and are completely shared between the transmitter 1 and the receiver 2.

The data processing means Y_{22} stores the block number in a "Completely-shared block number register" and increments the number of purification blocks that have been completely shared.

10 The data processing means Y_{22} (i.e., an error correcting means) of the receiver 2 reads the smallest one t of the numbers (i.e., the values of suffixes r) of other blocks that have already been completely shared from the "Completely-shared block number register", and reads the purification block A_{yt} 15 having the block number t from the data storage means Y_{23} . The data processing means Y_{22} then generates an error correction code A_{ytc} for this purification block A_{yt} (in step 211).

The data processing means Y_{22} (i.e., the error correcting means) further implements an exclusive-OR H_r operation on the 20 above-mentioned correction code G_r for transmission and the above-mentioned error correction code A_{ytc} (in step 212) as follows.

$H_r = G_r \text{ XOR } A_{ytc}$ (where XOR represents an exclusive-OR 25 operation)

Because $G_r = A_{xrc} \text{ XOR } A_{xtc}$,

$H_r = G_r \text{ XOR } A_{ytc}$

$= (A_{xrc} \text{ XOR } A_{xtc}) \text{ XOR } A_{ytc}$.

A_{xtc} and A_{ytc} are identical with each other because they 30 are generated from the purification blocks A_{xt} and A_{yt} specified

by the block number t , which have already been completely shared, in steps 202 and 211, respectively.

Therefore, $H_r = A_{xrc}$, where H_r is the error correction code for the purification block A_{xrc} .

5 The data processing means Y 22 makes a correction to the purification data A_{yr} having errors by using H_r , and stores the corrected purification data A_{yr} in the data storage means Y 23 (in step 213). The data processing means Y 22 stores the block number in the "Completely-shared block number register" and
10 increments the number of purification blocks that have been completely shared, and, after that, finishes the process about this block number (in step 214).

 In the flow chart of Fig. 6, step 201 is a second correction information generation step, step 202 is a second shared
15 correction information generation step, step 203 is a correction information encryption step and a correction information transmission step, step 211 is a first shared correction information generation step, step 212 is a correction information decrypting step, and step 213 is an error
20 correction step.

 As mentioned above, in accordance with this embodiment, the transmitter 1 transmits a correction code G_r for transmission as well as a transmission block D_r to the receiver
2. As a result, the present embodiment offers an advantage of
25 eliminating the necessity for the receiver 2 to respond to any data transmission from the transmitter 1, and therefore reducing the volume of traffic between them because transmission of data between them is carried out with one-way traffic from the transmitter to the receiver.

Embodiment 3.

As previously mentioned, in the shared data purifying system in accordance with embodiment 1, the transmitter 1 generates and transmits an error correction code for each purification block to the receiver 2 when the receiver 2 compares a made-for-verification block E_r with a mixed block C_{yr} and then judges that "they are different from each other".

In a shared data purifying system in accordance with this embodiment 3, when a receiver 2 judges that "they are different from each other", a transmitter 1 converts each purification block A_{xr} into Vernam-encrypted data and transmits it to the receiver 2, and the receiver also converts each purification block A_{yr} into Vernam-encrypted data so as to estimate bit positions where errors occur.

The shared data purifying system in accordance with this embodiment has the same structure as that of Fig. 1 as explained in Embodiment 1. Furthermore, each of the transmitter and receiver of the shared data purifying system divides temporarily-shared data into purification data and disposable data, as shown in Figs. 4A and 4B, like that of embodiment 1.

Fig. 7 is a flow chart showing an operation of the shared data purifying system in accordance with this embodiment. In the flow chart of Fig. 7, in steps designated by the same reference numerals as shown in Fig. 3 the shared data purifying system carries out the same processes as those done by that of embodiment 1, and therefore the explanation of those processes will be omitted hereafter.

Even in this embodiment, in steps 103 and later of the transmitter 1 of Fig. 7 processes are carried out in parallel with one another for all suffixes r ($r = 1$ to n), and in steps

111 and later of the receiver 2 processes are also carried out in parallel with one another for all suffixes r ($r = 1$ to n). In other words, the n identical processes progress in parallel in each of the transmitter 1 and the receiver 2. The case of
 5 $r = r$ will be explained hereafter.

The transmitter 1 receives a judgment result sent thereto from the receiver 2 by way of a communication means X 11, and then checks the judgment result by using a data processing means X 12 (in step 105). When the judgment result indicates "they
 10 are different from each other", the data processing means X 12, in step 607 as shown in Fig. 8A, divides the purification block A_{xr} into first and second equal halves, and implements an exclusive-OR operation on all bits of the first half of A_{xr} and corresponding bits of the second half so as to generate
 15 Vernam-encrypted data X. The transmitter 1 then transmits this Vernam-encrypted data X to the receiver 2 by way of the communication means X 11.

The receiver 2 receives this Vernam-encrypted data X by way of a communication means Y 21, and a data processing means
 20 Y 22, divides the purification block A_{yr} into first and second equal halves, as shown in Fig. 8B, and implements an exclusive-OR operation on all bits of the first half of A_{yr} and corresponding bits of the second half so as to generate Vernam-encrypted data Y. Although this Vernam-encrypted data
 25 Y is not transmitted to outside the receiver 2, the data is called "encrypted data" for convenience' sake.

Although the Vernam-encrypted data X and the Vernam-encrypted Y must be identical with each other if the purification blocks A_{xr} and A_{yr} are identical with each other,
 30 in this case the Vernam-encrypted data X and the

Vernam-encrypted Y are not identical with each other because the judgment results of steps 105 and 112 indicate that "they are different from each other". The data processing means of the receiver can estimate which bit positions of the purification block Ayr differ from the corresponding bits of the purification block Axr from the bit positions which the digits differ between the Vernam-encrypted X and the Vernam-encrypted Y.

To this end, the data processing means implements an exclusive-OR operation on the Vernam-encrypted X and the Vernam-encrypted Y, as shown in Fig. 9, so as to generate verification data. For example, when "1" appears at the b1-th bit of this verification data, the data processing means can estimate that either the b1-th bit of the first half of the purification block Ayr or the b1-th bit of the second half of the purification block Ayr is erroneously an inversion of the same bit of the purification block Axr. When "1" also appears at the b2-th bit of the verification data, the data processing means can similarly estimate that either the b2-th bit of the first half of the purification block Ayr or the b2-th bit of the second half of the purification block Ayr is erroneously an inversion of the same bit of the purification block Axr. The receiver 2 carries out the above-mentioned process of generating the Vernam-encrypted Y and the above-mentioned process of estimating erroneous bit positions of the purification block Ayr in step 617.

The receiver 2 then inverts either one of the bit positions of the purification block Ayr which have been estimated to have errors by using the data processing means Y 22 (i.e., an error correcting means) so as to generate a temporary purification

block Ayr2, and then mixes this temporary purification block Ayr2 through the same Hamming distance amplification effect as that used in step 111 so as to generate a temporary mixed block Cyr2 (in step 618).

5 The data processing means Y 22 compares this temporary mixed block Cyr2 with a made-for-verification block Er determined in step 112, and checks to see whether the Hamming distance between them is equal to or less than a predetermined value (e.g., 40 in this embodiment). Because the data
10 processing means Y 22 can assume that the temporary purification block Ayr2 is identical with the purification data Ayr when the Hamming distance is equal to or less than the predetermined value, the data processing means Y 22 stores this temporary purification block Ayr2 in a position of a purified data storing
15 area of a data storage means Y 23, which is specified by the value of the suffix r.

 When the Hamming distance between the temporary mixed block Cyr2 and the made-for-verification block Er is greater than the predetermined value, the data processing means Y 22
20 inverts all bits included in one of varying combinations of all bits of the purification block Ayr that have been estimated to have errors, e.g., inverts some other bits of the purification block Ayr that have been estimated to have errors so as to generate a temporary purification block Ayr2, or simultaneously
25 inverts all bits of the purification block Ayr that have been estimated to have errors, and repeats the inversion process until the Hamming distance between the temporary mixed block Cyr and the made-for-verification block Er becomes equal to or shorter than the predetermined value. When the Hamming
30 distance between the temporary mixed block Cyr and the

made-for-verification block E_r becomes equal to or shorter than the predetermined value, the data processing means Y 22 stores the temporary purification block A_{yr2} in a position of the purified data storing area of the data storage means Y 23, which
5 is specified by the value of the suffix r (in step 619), and then finishes the processing about this block number (in step 118).

In the flow chart of Fig. 7, step 607 is a correction information transmission step, and steps 617 to 619 are an error
10 correction step.

As mentioned above, in accordance with this embodiment, even if errors occur, the receiver can estimate and correct positions where the errors occur only from purification blocks that have already been transmitted thereto. As a result, the
15 present embodiment offers an advantage of being able to effectively use transmitted data.

The transmitter and the receiver need not calculate error correction codes, and, therefore, need not send and receive these error correction codes. As a result, the present
20 embodiment offers another advantage of simplifying processing for error corrections.

Embodiment 4.

As previously mentioned, in the shared data purifying
25 system in accordance with embodiment 3, the transmitter 1 converts each purification block A_{xr} into a Vernam-encrypted block and transmits it to the receiver 2 when the receiver 2 compares a made-for-verification block E_r with a mixed block C_{yr} and then judges that "they are different from each other".

30 In a shared data purifying system in accordance with this

embodiment 4, a transmitter 1 converts each of all purification blocks into a Vernam-encrypted block and transmits it to a receiver 2.

The shared data purifying system in accordance with this embodiment has the same structure as that of Fig. 1 as explained in Embodiment 1. Furthermore, each of the transmitter and receiver of the shared data purifying system divides temporarily-shared data into purification data and disposable data, as shown in Figs. 4A and 4B, like that of embodiment 1.

Fig. 10 is a flow chart showing an operation of the shared data purifying system in accordance with this embodiment.

In the flow chart of Fig. 10, in steps designated by the same reference numerals as shown in Figs. 3 and 7 the shared data purifying system carries out the same processes as those done by those of embodiments 1 and 3, and therefore the explanation of those processes will be omitted hereafter.

Even in this embodiment, in steps 103 and later of the transmitter 1 of Fig. 10 processes are carried out in parallel with one another for all suffixes r ($r = 1$ to n), and in steps 111 and later of the receiver 2 processes are also carried out in parallel with one another for all suffixes r ($r = 1$ to n). In other words, the n identical processes progress in parallel in each of the transmitter 1 and the receiver 2. The case of $r = r$ will be explained hereafter.

The transmitter 1, in step 901, divides each purification block A_{xr} into first and second equal halves, as shown in Fig. 8A, and implements an exclusive-OR operation on all bits of the first half of A_{xr} and corresponding bits of the second half of A_{xr} so as to generate Vernam-encrypted data X .

Next, as in the case of step 104 of Fig. 3 explained in

Embodiment 1, the transmitter 1, in step 902, calculates a random number sequence as a disposable block Bxr having the same size as a mixed block Cxr, and implements an exclusive-OR (XOR) operation on the mixed block Cxr and the disposable block Bxr by using a data processing means. The transmitter 1 then sends the calculation result, as a transmission block Dr, to the receiver 2 by way of a public network 4 by using a communication means X 11.

As mentioned above, in accordance with this embodiment, the transmitter 1 can transmit the Vernam-encrypted X as well as the transmission block Dr to the receiver. As a result, the present embodiment offers an advantage of eliminating the necessity for the receiver 2 to respond to any data transmission from the transmitter 1, and therefore reducing the volume of traffic between them because transmission of data between them is carried out with one-way traffic from the transmitter to the receiver.

As mentioned above, in accordance with this embodiment, even if errors occur, the receiver can estimate and correct positions where the errors occur only from purification blocks that have already been transmitted thereto. As a result, the present embodiment offers an advantage of being able to effectively use transmitted data.

The transmitter and the receiver need not calculate error correction codes, and, therefore, need not send and receive these error correction codes. As a result, the present embodiment offers another advantage of simplifying processing for error corrections.

Embodiment 5.

As previously mentioned, in the shared data purifying system in accordance with embodiment 1, the transmitter 1 converts the mixed block C_{xr} into a transmission block D_r and then transmits it to the receiver 2. In contrast, in a shared data purifying system in accordance with this embodiment, a transmitter 1 transmits a mixed block C_{xr} to a receiver 2.

The shared data purifying system in accordance with this embodiment has the same structure as that of Fig. 1 as explained in Embodiment 1.

Fig. 11 is a flow chart showing an operation of the shared data purifying system in accordance with this embodiment.

Figs. 12A and 12B are diagrams showing divisions of temporarily-shared data X and Y into purification data in accordance with this embodiment. In the figure, reference numerals 310 and 311 denote remainders each having a size of β bits. Furthermore, the same elements as shown in Figs. 4A and 4B are designated by the same reference numerals, and therefore the explanation of those elements will be omitted hereafter.

In the flow chart of Fig. 11, in steps designated by the same reference numerals as shown in Fig. 3 the shared data purifying system carries out the same processes as those done by those of embodiment 1, and therefore the explanation of those processes will be omitted hereafter.

Even in this embodiment, in steps 103 and later of the transmitter 1 of Fig. 11 processes are carried out in parallel with one another for all suffixes r ($r = 1$ to n), and in steps 111 and later of the receiver 2 processes are also carried out in parallel with one another for all suffixes r ($r = 1$ to n). In other words, the n identical processes progress in parallel

in each of the transmitter 1 and the receiver 2. The case of $r = r$ will be explained hereafter.

The transmitter 1 and the receiver 2, in steps 901 and 911, divide temporarily-shared data X and temporarily-shared data Y, which are temporarily shared in step 101, into n purification blocks A_{xr} ($r = 1$ to n) and n purification blocks A_{yr} ($r = 1$ to n), these purification blocks A_{xr} and A_{yr} having equal numbers P of bits, as shown in Figs. 12A and 12B, respectively.

The plurality of purification blocks A_{xr} are stored in a RAM within a data processing means X 12, and the plurality of purification blocks A_{yr} are stored in a RAM within a data processing means Y 22. As an alternative, the plurality of purification blocks A_{xr} can be stored in a data storage means X 13, and the plurality of purification blocks A_{yr} can be stored in a data storage means Y 23.

Assuming that the temporarily-shared data X has the same bit number, i.e. L bits, as the temporarily-shared data Y, as can be seen from Figs. 12A and 12B, n is obtained from the following equation.

$$L = P \cdot n + \beta \quad (\beta < P)$$

In this case, the remainder of β bits is not used.

The rate of errors that occur between the purification blocks A_{xr} and A_{yr} at the same suffix r depends on the quality of a quantum communication line 3 and can be assumed to be about 1 percent.

Steps 103 and later of the transmitter 1 are carried out in parallel with one another for each suffix r ($r = 1$ to n),

and steps 911 and later of the receiver 2 are also carried out in parallel with one another for each suffix r ($r = 1$ to n). In other words, the n identical processes progress in parallel.

The transmitter 1, in step 902, transmits the
5 above-mentioned mixed block C_{xr} to the receiver 2 through a public network 4 by using a communication means X_{11} .

When the receiver 2 receives the above-mentioned mixed block C_{xr} by way of a communication means Y_{21} , the receiver 2 compares this mixed block C_{xr} with a mixed block C_{yr} by using
10 the data processing means Y_{22} , in step 912.

The processing is thus carried out hereafter, as in the case of embodiment 1, and the purification blocks A_{xr} and A_{yr} are completely shared between the transmitter 1 and the receiver 2.

15 In accordance with this embodiment, the transmitter 1 transmits the mixed data C_{xr} to the receiver 2 without Vernam-encrypting it and the receiver 2 compares it with mixed data C_{yr} without carrying out any process on the received mixed data C_{xr} . As a result, the present embodiment offers an
20 advantage of simplifying the processing.

Embodiment 6.

As previously mentioned, in the shared data purifying system in accordance with embodiment 1, the transmitter 1
25 transmits temporarily-shared data to the receiver 2. In contrast, in a shared data purifying system in accordance with embodiment 6, a transmitter 1 and a receiver 2 independently acquire temporarily-shared data, and the receiver 2 checks to see whether it is holding the same shared data as that being
30 held by the transmitter 1.

Fig. 13 is a diagram showing the shared data purifying system in accordance with this embodiment, and Fig. 14 is a flow chart showing an operation of the shared data purifying system. In Figs. 13 and 14, because the components and steps designated
5 by the same reference numerals as shown in Figs. 1 and 3 and as explained in Embodiment 1 are the same as those of embodiment 1, the detailed explanation of those components and steps will be omitted hereafter.

The shared data purifying system shown in Fig. 13 is the
10 same as that of embodiment 1 as shown in Fig. 1, with the exception that the shared data purifying system of this embodiment does not include a quantum communication line 3.

In Fig. 14, the transmitter 1 and the receiver 2, in steps
1001 and 1002, acquire temporarily-shared data X and
15 temporarily-shared data Y, respectively. Hereafter, assume that there exists a data supply apparatus not shown in the figure, for example, identical data are supplied to both the transmitter 1 and to the receiver 2 as the temporarily-shared data X and the temporarily-shared data Y from this data supply apparatus
20 and are stored in a data storage means X 13 and in a data storage means Y 23, respectively.

Because there is a possibility that these temporarily shared-data X and temporarily-shared data Y are not completely identical with each other because of errors or the like that
25 occurs on a transmission path from the data supply apparatus, they are called, "temporarily-shared data".

In accordance with the present invention, the temporarily-shared data X is second temporarily-shared data and the temporarily-shared data Y is first temporarily-shared data,
30 and the receiver 2 is a shared data purifying apparatus.

After that, the transmitter carries out processes of steps 102, 103 and 104, like that of embodiment 1, and transmits a transmission block Dr generated in step 104 to the receiver 2.

5 The receiver 2 carries out processes of steps 110, 111 and 112, like that of embodiment 1, and, in step 112, generates a made-for-verification block Er and compares it with a mixed block Cyr generated in step 111.

10 When the Hamming distance between the mixed block Cyr and the made-for-verification block Er exceeds a predetermined value, in step 112, the receiver 2, in step 116, transmits information indicating "they are different from each other" to the transmitter 1 as a judgment result through a public network.

15 When the judgment result indicates "they are different from each other", each of the transmitter 1 and the receiver 2 receives a supply of data from the data supply apparatus again and repeats the above-mentioned processing until the judgment result indicates "they are identical with each other".

20 When the Hamming distance between the mixed block Cyr and the made-for-verification block Er is equal to or less than the predetermined value, in step 112, the receiver 2, in step 113, transmits information indicating "they are identical with each other" to the transmitter 1 as the judgment result through the public network.

25 Because the transmitter 1 and the receiver 2 share the same data with each other when the judgment result indicates "they are identical with each other", the transmitter can carry out cryptography communications by using this shared data as a key for common key encryption systems, for example.

30 As mentioned above, because the receiver according to

this embodiment checks to see whether the temporarily-shared data that is temporarily shared with the transmitter is identical with the temporarily-shared data being held by the transmitter, the receiver can be called either a shared data
5 verification apparatus or a shared data authentication apparatus.

Furthermore, in accordance with this embodiment, each of the transmitter and the receiver (i.e., the shared data purifying apparatus) divides the temporarily-shared data into
10 a plurality of purification blocks and a plurality of disposable blocks, and enlarges the Hamming distance between corresponding purification blocks being held by the transmitter and the receiver by using a Hamming distance amplification effect, like that of embodiment 1. As a result, the present embodiment
15 offers an advantage of easily judging whether the temporarily-shared data stored in the transmitter is identical with or different from that stored in the receiver.

In accordance with this embodiment, data other than the temporarily-shared data are sent and received by way of the
20 public network. In accordance with the present invention, the line via which data other than the temporarily-shared data are sent and received is not limited to the public network. As an alternative, data other than the temporarily-shared data can be sent and received by way of a privately used line or by radio.

25 Furthermore, in accordance with this embodiment, when generating and Vernam-encrypting an error correction code, the transmitter selects the smallest one of the numbers of blocks which have already been completely shared between the transmitter and the receiver as data for encryption. However,
30 in accordance with the present invention, the selected number

is not limited to the smallest one of the numbers of blocks which have already been completely shared between the transmitter and the receiver as data for encryption. As an alternative, the transmitter can select either one of the numbers of blocks which
5 have already been completely shared between the transmitter and the receiver. In this case, both the transmitter and the receiver use blocks of the same number (these blocks having the same bit number as that of the error correction code).

10 Industrial Applicability

As mentioned above, the shared data purifying apparatus and shared data purifying method in accordance with the present invention are suitable for reducing the risk of temporarily-shared data being tapped and enlarging the ratio
15 of effective data when removing errors from the data temporarily shared between the transmitter and the receiver.

Claims

1. A shared data purifying apparatus comprising:

5 a block generating means for dividing temporarily-shared data transmitted from a transmitter according to a predetermined division rule so as to generate a first purification block and a first disposable block;

a data mixing means for mixing said first purification block according to a predetermined data mixing rule so as to
10 generate a first mixed block, said data mixing means mixing each of two arbitrary digital data that are at a Hamming distance of 0 from each other so that two generated mixed data are at a Hamming distance of 0 from each other, and mixing each of two arbitrary digital data that are at a Hamming distance of 1 or
15 more from each other so that two generated mixed data are at a have a Hamming distance of 1 or more from each other;

a means of acquiring an encrypted block generated according a predetermined encryption rule based on a second mixed block, which is generated by mixing a second purification
20 block, which said transmitter generates together with a second disposable block by dividing temporarily-shared data that said transmitter has transmitted according to the predetermined division rule, according to the predetermined data mixing rule, and based on the second disposable block;

25 a decrypted block generating means for decrypting the encrypted block with the first disposable block according to a predetermined decrypting rule corresponding to said predetermined encryption rule so as to generate a decrypted block; and

30 an identity judgment means for comparing said decrypted

block with said first mixed block so as to judge whether said first purification block and said second purification block are identical with or different from each other according to a comparison result.

5

2. The shared data purifying apparatus according to Claim 1, characterized in that said apparatus further comprises a data storage means, and said identity judgment means compares the decrypted block with the first mixed block, and judges that said first purification block is identical with said second purification block and stores said first purification block in said data storage means when a Hamming distance between said decrypted block and said first mixed block is equal to or less than a predetermined value.

15

3. The shared data purifying apparatus according to Claim 1, characterized in that said transmitter transmits the temporarily-shared data through quantum cryptography communications.

20

4. The shared data purifying apparatus according to Claim 1, characterized in that said apparatus further comprises an error correcting means, and characterized in that said identity judgment means compares the decrypted block with the first mixed block and judges that the first purification block is different from the second purification block when the comparison result indicates that a Hamming distance between the decrypted block and the first mixed block exceeds a predetermined value, and, when a judgment result from said identity judgment means indicates that the first purification block is "different" from

25
30

the second purification block, said error correcting means acquires correction information used to make said first purification block agree with said second purification block, and corrects said first purification block based on the
5 correction information so that said first purification block agrees with said second purification block.

5. The shared data purifying apparatus according to Claim 2, characterized in that said apparatus further comprises an
10 error correcting means, and said decrypted block generating means acquires correction information used to make the first purification block, which said transmitter generates as well as the encrypted block, agree with the second purification block, and said identity judgment means compares the decrypted block
15 with the first mixed block and judges that the first purification block is different from the second purification block when the comparison result indicates that a Hamming distance between the decrypted block and the first mixed block exceeds a predetermined value, and, when a judgment result from
20 said identity judgment means indicates that the first purification block is "different" from the second purification block, said error correcting means corrects said first purification block based on the correction information so that said first purification block agrees with said second
25 purification block.

6. The shared data purifying apparatus according to Claim 4, characterized in that the correction information is an error correction code for the second purification block, and said
30 error correcting means corrects said first purification block

with the error correction code.

7. The shared data purifying apparatus according to Claim 4, characterized in that said apparatus encrypts the correction information by implementing an exclusive-OR operation on the correction information and data being held by both said transmitter and a data storage means, and said error correcting means acquires and decrypts the encrypted correction information by implementing an exclusive-OR operation on this encrypted correction information and the data acquired from said data storage means, and corrects said first purification block based on the decrypted correction information so that said first purification block agrees with said second purification block.

15

8. The shared data purifying apparatus according to Claim 4, characterized in that said apparatus obtains the correction information by implementing an exclusive-OR operation on equal halves into which said second purification block is divided, and said error correcting means generates comparison information that is a result of an exclusive-OR operation implemented on equal halves into which said first purification block is divided, estimates bit positions in where said first and second purification blocks disagree from said correction information and said comparison information, and corrects said first purification block so that said first purification block agrees with said second purification block by inverting bits of said first purification block at the estimated bit positions.

25
30

9. A shared data purifying apparatus that receives

temporarily-shared data transmitted from a transmitter, divides the temporarily-shared data according to a predetermined division rule so as to generate a first purification block and a first disposable block, mixes said first purification block according to a predetermined data mixing rule so as to generate a first mixed block, acquires an encrypted block generated according a predetermined encryption rule based on a second mixed block, which is generated by mixing a second purification block, which is generated together with a second disposable block by dividing the temporarily-shared data that said transmitter has transmitted according to the predetermined division rule, according to the predetermined data mixing rule, and based on the second disposable block, decrypts said encrypted block with said first disposable block according to a predetermined decrypting rule corresponding to said predetermined encryption rule so as to generate a decrypted block, and compares said decrypted block with said first mixed block so as to judge whether said first purification block and said purification block are identical with each other or different from each other according to a comparison result, wherein

according to said data mixing rule, said apparatus mixes each of two arbitrary digital data that are at a Hamming distance of 0 from each other so that two generated mixed data are at a Hamming distance of 0 from each other, and mixes each of two arbitrary digital data that are at a Hamming distance of 1 or more from each other so that two generated mixed data are at a have a Hamming distance of 1 or more from each other.

10. A shared data purifying apparatus comprising:

a block generating means for dividing first temporarily-shared data being held by a shared data purifying apparatus among temporarily-shared data temporarily shared by a transmitter and said shared data purifying apparatus
5 according to a predetermined division rule so as to generate a first purification block and a first disposable block;

a data mixing means for mixing said first purification block according to a predetermined data mixing rule so as to generate a first mixed block, said data mixing means mixing each
10 of two arbitrary digital data that are at a Hamming distance of 0 from each other so that two generated mixed data are at a Hamming distance of 0 from each other, and mixing each of two arbitrary digital data that are at a Hamming distance of 1 or more from each other so that two generated mixed data are at
15 a have a Hamming distance of 1 or more from each other;

a means of acquiring an encrypted block generated according a predetermined encryption rule based on a second mixed block, which is generated by mixing a second purification block, which said transmitter generates together with a second
20 disposable block by dividing second temporarily-shared data being held by said transmitted among the temporarily-shared data temporarily shared by said transmitter and said shared data purifying apparatus according to the predetermined division rule, according to the predetermined data mixing rule, and based
25 on the second disposable block;

a decrypted block generating means for decrypting said encrypted block with said first disposable block according to a predetermined decrypting rule corresponding to said predetermined encryption rule so as to generate a decrypted
30 block; and

an identity judgment means for comparing said decrypted block with said first mixed block so as to judge whether said first purification block and said purification block are identical with or different from each other according to a comparison result.

11. The shared data purifying apparatus according to Claim 1, characterized in that the first disposable block, the second mixed block, and the second disposable block are equal in bit number, and the predetermined encryption rule is a rule according to which said apparatus implements an exclusive-OR operation on the second mixed block and the second disposable block and the predetermined decrypting rule is a rule according to which said decrypted block generating means implements an exclusive-OR operation on the encrypted block and the first disposable block.

12. The shared data purifying apparatus according to Claim 9, characterized in that the first disposable block, the second mixed block, and the second disposable block are equal in bit number, and the predetermined encryption rule is a rule according to which said apparatus implements an exclusive-OR operation on the second mixed block and the second disposable block and the predetermined decrypting rule is a rule according to which said decrypted block generating means implements an exclusive-OR operation on the encrypted block and the first disposable block.

13. The shared data purifying apparatus according to Claim 10, characterized in that the first disposable block, the

second mixed block, and the second disposable block are equal in bit number, and the predetermined encryption rule is a rule according to which said apparatus implements an exclusive-OR operation on the second mixed block and the second disposable
5 block and the predetermined decrypting rule is a rule according to which said decrypted block generating means implements an exclusive-OR operation on the encrypted block and the first disposable block.

10 14. The shared data purifying apparatus according to Claim 1, characterized in that the predetermined data mixing rule is a rule according to which said data mixing means mixes the first purification block so that a Hamming distance between the first and second mixed blocks is larger than that between
15 said first and second purification blocks when the Hamming distance between the first and second purification blocks is 1 or more and is sufficiently less than one half of a bit number of each of the first and second purification blocks.

20 15. The shared data purifying apparatus according to Claim 9, characterized in that the predetermined data mixing rule is a rule according to which said data mixing means mixes the first purification block so that a Hamming distance between the first and second mixed blocks is larger than that between
25 said first and second purification blocks when the Hamming distance between the first and second purification blocks is 1 or more and is sufficiently less than one half of a bit number of each of the first and second purification blocks.

30 16. The shared data purifying apparatus according to

Claim 10, characterized in that the predetermined data mixing rule is a rule according to which said data mixing means mixes the first purification block so that a Hamming distance between the first and second mixed blocks is larger than that between
5 said first and second purification blocks when the Hamming distance between the first and second purification blocks is 1 or more and is sufficiently less than one half of a bit number of each of the first and second purification blocks.

10 17. The shared data purifying apparatus according to Claim 1, characterized in that the predetermined data mixing rule is a hash function.

 18. The shared data purifying apparatus according to
15 Claim 9, characterized in that the predetermined data mixing rule is a hash function.

 19. The shared data purifying apparatus according to Claim 10, characterized in that the predetermined data mixing
20 rule is a hash function.

 20. A shared data purifying method for use in a shared data purifying system including a transmitter and a receiver, comprising the steps of:

25 each of said transmitter and said receiver using a predetermined data mixing rule;

 said transmitter transmitting temporarily-shared data to said receiver;

 said receiver dividing the temporarily-shared data
30 received thereby according to a predetermined division rule so

as to generate a first purification block and a first disposable block;

said receiver mixing said first purification block according to the predetermined data mixing rule so as to
5 generate a first mixed block;

said transmitter dividing the temporarily-shared data transmitted thereby according to the predetermined division rule so as to generate a second purification block and a second disposable block;

10 said transmitter mixing said second purification block according to the predetermined data mixing rule so as to generate a second mixed block;

said transmitter generating an encrypted block from the second mixed block and the second disposable block according
15 to a predetermined encryption rule and then transmitting the encrypted block to said receiver;

said receiver receiving the encrypted block, decrypting the encrypted block with the first disposable block according to a predetermined decrypting rule corresponding to said
20 predetermined encryption rule so as to generate a decrypted block, comparing the decrypted block with the first mixed block so as to determine whether the first and second purification blocks are identical with or different from each other according to a comparison result, and advancing to either of following
25 steps (a) and (b) according to a judgment result;

(a) when the judgment result indicates that "the first and second purification blocks are identical to each other", transmitting the judgment result indicating the fact to said transmitter and storing the first purification block in a data
30 storage means;

(b) when the judgment result indicates that "the first and second purification blocks are different from each other", transmitting the judgment result indicating the fact to said transmitter;

5 said transmitter advancing to either of following steps (c) and (d) according to the received judgment result;

(c) when the received judgment result indicates that "the first and second purification blocks are identical to each other", finishing processing;

10 (d) when the received judgment result indicates that "the first and second purification blocks are different from each other", generating and transmitting correction information used to make the second purification block agree with the first purification block to said receiver;

15 said receiver correcting the first purification block by using the correction information received from said transmitter so that the first purification block agrees with the second purification block; and

20 according to the predetermined data mixing rule, mixing each of two arbitrary digital data that are at a Hamming distance of 0 from each other so that two generated mixed data are at a Hamming distance of 0 from each other, and mixing each of two arbitrary digital data that are at a Hamming distance of 1 or more from each other so that two generated mixed data are at
25 a have a Hamming distance of 1 or more from each other.

21. A shared data purifying method for use in a shared data purifying system including a transmitter and a receiver, comprising the steps of:

30 each of said transmitter and said receiver using a

predetermined data mixing rule;

said transmitter transmitting temporarily-shared data to
said receiver;

said receiver dividing the temporarily-shared data
5 received thereby according to a predetermined division rule so
as to generate a first purification block and a first disposable
block;

said receiver mixing the first purification block
according to the predetermined data mixing rule so as to
10 generate a first mixed block;

said transmitter dividing the temporarily-shared data,
which said transmitter has transmitted, according to the
predetermined division rule so as to generate a second
purification block and a second disposable block;

15 said transmitter mixing said second purification block
according to the predetermined data mixing rule so as to
generate a second mixed block;

said transmitter generating correction information used
to make the second purification block agree with the first
20 purification block from the second purification block according
to a predetermined correction information generation rule;

said transmitter generating an encrypted block from the
second mixed block and the second disposable block according
to a predetermined encryption rule and then transmitting the
25 encrypted block and the correction information to said
receiver;

said receiver receiving the encrypted block, decrypting
the encrypted block with the first disposable block according
to a predetermined decrypting rule corresponding to said
30 predetermined encryption rule so as to generate a decrypted

block, comparing the decrypted block with the first mixed block so as to judge whether the first and second purification blocks are identical with or different from each other according to a comparison result, and advancing to either of following steps

5 (e) and (f) according to a judgment result;

(e) when the judgment result indicates that "the first and second purification blocks are identical with each other", storing the first purification block in a data storage means;

(f) when the judgment result indicates that "the first
10 and second purification blocks are different from each other", correcting the first purification block by using the correction information received from said transmitter so that the first purification block agrees with the second purification block; and

15 according to the predetermined data mixing rule, mixing each of two arbitrary digital data that are at a Hamming distance of 0 from each other so that two generated mixed data are at a Hamming distance of 0 from each other, and mixing each of two arbitrary digital data that are at a Hamming distance of 1 or
20 more from each other so that two generated mixed data are at a have a Hamming distance of 1 or more from each other.

22. The shared data purifying method according to Claim
20, characterized in that the correction information is
25 obtained by implementing an exclusive-OR operation on equal halves into which said second purification block is divided, and in said correcting step said receiver generates comparison information that is a result of an exclusive-OR operation implemented on equal halves into which said first purification
30 block is divided, estimates bit positions in where said first

and second purification blocks disagree from said correction information and said comparison information, and corrects said first purification block so that said first purification block agrees with said second purification block by inverting bits
5 of said first purification block at the estimated bit positions.

23. The shared data purifying method according to Claim 21, characterized in that said receiver has a data storage means, in said correction information generating step, said
10 transmitter encrypts the generated correction information by implementing an exclusive-OR operation on the correction information and data being held by both said transmitter and said data storage means and then transmits the encrypted correction information to said receiver, and in said error
15 correcting step said receiver acquires and decrypts the encrypted correction information by implementing an exclusive-OR operation on this encrypted correction information and the data acquired from said data storage means, and corrects the first purification block based on the decrypted
20 correction information so that the first purification block agrees with the second purification block.