

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property Organization
International Bureau



G00002

(43) International Publication Date
14 February 2002 (14.02.2002)


PCT

(10) International Publication Number
WO 02/13190 A1


- (51) International Patent Classification⁷: **G11B 5/66**
- (21) International Application Number: PCT/GB01/03302
- (22) International Filing Date: 23 July 2001 (23.07.2001)
- (25) Filing Language: English
- (26) Publication Language: English
- (30) Priority Data:
09/631,908 4 August 2000 (04.08.2000) US
- (71) Applicant: **INTERNATIONAL BUSINESS MACHINES CORPORATION** [US/US]; New Orchard Road, Armonk, NY 10504 (US).
- (71) Applicant (for MG only): **IBM UNITED KINGDOM LIMITED** [GB/GB]; P.O. Box 41, North Harbour, Portsmouth, Hampshire PO6 3AU (GB).
- (72) Inventors: **DOERNER, Mary, Frances**; 148 Forest Avenue, Santa Cruz, CA 95062 (US). **FULLERTON, Eric**,
- Edward; 17212 Quail Court, Morgan Hill, CA 95037 (US). **MARGULIES, David, Thomas**; 10610C New Avenue, Gilroy, CA 95020 (US).
- (74) Agent: **BURT, Roger, James**; IBM United Kingdom Limited, Intellectual Property Law, Hursley Park, Winchester, Hampshire SO21 2JN (GB).
- (81) Designated States (national): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, TZ, UA, UG, UZ, VN, YU, ZA, ZW.
- (84) Designated States (regional): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

[Continued on next page]

(54) Title: ANTIFERROMAGNETICALLY COUPLED MAGNETIC RECORDING MEDIA



(57) Abstract: A magnetic recording medium for data storage uses a magnetic recording layer having at least two ferromagnetic films exchange coupled together antiferromagnetically across a nonferromagnetic spacer film. In this antiferromagnetically-coupled (AFC) recording layer the magnetic moments of the two ferromagnetic films are oriented antiparallel, and thus the net remanent magnetization-thickness product (Mrt) of the AFC recording layer is the difference in the Mrt values of the two ferromagnetic films. This reduction in Mrt is accomplished without a reduction in thermal stability of the recording medium. The lower ferromagnetic film in the AFC recording layer is a boron-free ferromagnetic CoCr alloy that does not require a nucleation layer between it and the Cr alloy underlayer. The ferromagnetic CoCr alloy has sufficient saturation magnetization (M_s) to produce excellent magnetic recording performance for the AFC recording layer, while also serving as a template or nucleation layer to induce the growth of the spacer layer and top ferromagnetic boron-containing ferromagnetic film.

**Published:**

- with international search report
- before the expiration of the time limit for amending the claims and to be republished in the event of receipt of amendments
- entirely in electronic form (except for this front page) and available upon request from the International Bureau

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.