

(19) World Intellectual Property Organization
International Bureau



(43) International Publication Date
10 April 2003 (10.04.2003)

PCT

(10) International Publication Number
WO 03/029089 A1

(51) International Patent Classification⁷: **B65D 1/12**,
25/14, 85/72, 79/00, B65B 31/02, B32B 15/08, B21D
51/26, B67C 3/02

(74) Agent: **FREEHILLS CARTER SMITH BEADLE**; 101
Collins Street, Melbourne, Victoria 3000 (AU).

(21) International Application Number: PCT/AU02/00725

(22) International Filing Date: 5 June 2002 (05.06.2002)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
PR 8001 28 September 2001 (28.09.2001) AU

(71) Applicant (*for all designated States except US*):
BAROKES PTY LTD. [AU/AU]; 95 Puckle Street,
Moonee Ponds, VIC 3039 (AU).

(72) Inventors; and

(75) Inventors/Applicants (*for US only*): **STOKES, Gregory,**
John Charles [AU/AU]; 2 Horseshoe Bend Road, Keilor,
Victoria 3036 (AU). **BARICS, Steven, John Anthony**
[AU/AU]; 51 Waratah Avenue, Tullamarine, Victoria 3043
(AU).

(81) Designated States (*national*): AE, AG, AL, AM, AT, AU,
AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU,
CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH,
GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC,
LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW,
MX, MZ, NO, NZ, OM, PH, PL, PT, RO, RU, SD, SE, SG,
SI, SK, SL, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ,
VN, YU, ZA, ZM, ZW.

(84) Designated States (*regional*): ARIPO patent (GH, GM,
KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW),
Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM),
European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR,
GB, GR, IE, IT, LU, MC, NL, PT, SE, TR), OAPI patent
(BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR,
NE, SN, TD, TG).

Published:

— with international search report

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

(54) Title: PROCESS FOR PACKAGING WINE IN ALUMINIUM CANS

(57) Abstract: Process for packaging red or white, still or carbonated wine in two piece aluminium cans. The wine has less than 35 ppm of free sulphur dioxide, total sulfur dioxide levels less than 250 ppm, less than 330 ppm of chloride and less than 800 ppm of sulfates. Each can has an aluminium body filled with wine and sealed with an aluminium closure such that the pressure within the can is at least 25 psi and the inner surface of the aluminium is coated with a thermoset corrosion resistant coating. The coating or lining may be an epoxy resin combined with a formaldehyde based crosslinking agent and baked at temperatures in the range 165-185 °C for twenty minutes. The wines exhibit excellent performance after storage or the quality of the wine does not deteriorate significantly on storage.



WO 03/029089 A1