

INFLATABLE BED HAVING A BUILT-IN ELECTRIC AIR
PUMP UNIT FOR INFLATING A MATTRESS ASSEMBLY

This invention relates to an inflatable bed, and more particularly to an inflatable bed having a built-in electric air pump unit for inflating a mattress assembly. 1. Description of the Related Art

A conventional inflatable bed includes a built-in electric air pump for inflating a mattress of the inflatable bed. When the electric air pump is a centrifugal pump, although it can inflate the mattress at a higher speed, the air pressure in the mattress cannot be increased precisely to a desired pressure value. Conversely, when the electric air pump is a diaphragm pump, although it can inflate the mattress to increase precisely the air pressure in the mattress to the desired pressure value, the inflating speed thereof is slow.

Embodiments of the present invention provide an inflatable bed that includes an improved air pump unit, which can inflate a mattress at a high speed and which can increase precisely the air pressure in the mattress to a desired pressure value.

One aspect of the present invention provides an inflatable bed comprising: a bedstead assembly; a mattress assembly having at least one air chamber; and an electric air pump unit in connection with said mattress assembly and including a centrifugal pump device in fluid communication with said air chamber

in said mattress assembly for inflating said air chamber, a first control valve operable to allow for and interrupt fluid communication between said centrifugal pump device and said air chamber, and a diaphragm pump device in communication with said air chamber for inflating said air chamber; whereby, said first control valve is controllable to allow for fluid communication between said centrifugal pump device and said air chamber so that said centrifugal pump device is operable to perform inflation of said air chamber to a first pressure value; and said first control valve is controllable to interrupt fluid communication between said centrifugal pump device and said air chamber so that said diaphragm pump device is operable to perform inflation of the air chamber to a second pressure value.

To inflate the air chamber to a desired volume, the centrifugal pump device may be first operated until the air chamber is expanded to about 90% of the desired volume at a higher speed. Subsequently, the diaphragm pump device is operated to inflate precisely the air chamber to the desired volume at a slower speed.

These and other features and advantages of this invention will become apparent in the following detailed description of the preferred embodiments of this invention, with reference to the accompanying drawings, in which:

Fig. 1 is a fragmentary exploded perspective view of the first preferred embodiment of an inflatable bed according to this invention, wherein an electric air pump unit is removed;

Fig. 2 is a perspective view of a corner positioning member of the first preferred embodiment;

Fig. 3 is an assembled perspective view of a mattress assembly and the electric air pump unit of the first preferred embodiment;

Fig. 4 is a partly exploded perspective view of a bedstead assembly of the first preferred embodiment;

Fig. 5 is a perspective view of a support frame of the bedstead assembly of the first preferred embodiment in an unfolded state;

Fig. 6 is a fragmentary perspective view of a foldable plate of a foldable frame member of the support frame of the first preferred embodiment in an unfolded state;

Fig. 7 is a perspective view of the foldable frame member of the first preferred embodiment in a semi-folded state;

Fig. 8 is a fragmentary perspective view of the foldable plate of the first preferred embodiment in a semi-folded state;

Fig. 9 is a partly exploded perspective view of the support frame of the first preferred embodiment in a fully folded state;

Fig. 10 is a fragmentary perspective view of the foldable plate of the first preferred embodiment in a fully folded state;

Fig. 11 is an assembled perspective view of a mattress assembly of the second preferred embodiment of an inflatable bed according to this invention;

Fig. 12 is an assembled perspective view of an electric air pump unit of the first preferred embodiment;

Fig. 13 is a partly sectional side view of a solenoid-operated diaphragm device of the electric air pump unit of the second preferred embodiment, illustrating a diaphragm valve in an opened state;

Fig. 14 is a view similar to Fig. 5 but illustrating the diaphragm valve in a closed state;

Fig. 15 is a schematic view of a controller of the second preferred embodiment;

Fig. 16 is a flowchart illustrating operations of the second preferred embodiment in response to pressing of a head key, a body key, a confirmation key, a micro-adjustment inflation key, and a micro-adjustment deflation key, respectively;

Fig. 17 is a flowchart illustrating operation of the second preferred embodiment in response to pressing of a main inflation key;

Fig. 18 is a flowchart illustrating operation of the second preferred embodiment in response to pressing of a deflation key;

Fig. 19 is a flowchart illustrating operation of the second preferred embodiment in response to pressing of a memory key;

Fig. 20 is a flowchart illustrating operation of the second preferred embodiment in response to pressing of a lock key;

Fig. 21 is a schematic view illustrating a modified electric air pump unit;

Fig. 22 is an assembled perspective view of a mattress assembly and an electric air pump unit of the third preferred embodiment of an inflatable bed according to this invention;

Fig. 23 is a schematic view illustrating a connection between the mattress assembly and an electric air pump unit of the third preferred embodiment;

Fig. 24 is an exploded perspective view of a mattress

assembly of the fourth preferred embodiment of an inflatable bed according to this invention; and

Fig. 25 is an assembled perspective view of the mattress assembly and an air pump unit of the fourth preferred embodiment.

Before the present invention is described in greater detail in connection with the preferred embodiments, it should be noted that similar elements and structures are designated by like reference numerals throughout the entire disclosure.

Referring to Figs. 1 and 2, the first preferred embodiment of an inflatable bed according to this invention includes a mattress assembly 1, a covering unit, an electric air pump unit 2, a bedstead assembly 3, and a cushion unit consisting of two cushion members 6.

The mattress assembly 1 includes a rectangular top sheet 11, a rectangular bottom sheet 12, two juxtaposed surrounding sheets 13 interconnecting the top and bottom sheets 11, 12 to define two air chambers (E) that are not in fluid communication with each other, and two reinforcing units 14 disposed respectively within the air chambers (E). When inflated fully, the air chambers (E) have the same shape and volume. As such, the mattress assembly 1 has two mattresses 10 each including a respective one of the surrounding sheets 13 and defining a respective one of the air chambers (E). Each of the mattresses 10 may be used to support one person. Each of the air chambers (E) is

defined among the top and bottom sheets 11, 12 and the corresponding surrounding sheet 13. Each of the reinforcing units 14 includes a row of pull belts 141 and a surrounding belt 142 disposed around the row of pull belts 141 and formed with a plurality of vent holes 143 therethrough. Each of the pull belts 141 and the surrounding belts 142 is connected fixedly to the top and bottom sheets 11, 12. The top and bottom sheets 11, 12, the surrounding sheets 13, and the reinforcing units 14 are received within the covering unit. The covering unit includes an upper covering member 15, a lower covering member 16, and a surrounding member 17. The upper and lower covering members 15, 16 are interconnected by a zipper unit. The zipper unit consists of upper and lower zipper halves 18, 18' attached respectively to the upper and lower covering members 15, 16 and interconnected removably. The cushion members 6 are disposed between the upper covering member 15 and the top sheet 11. The bedstead assembly 3 includes a rectangular bedstead body 31 and a cover 32 for covering the bedstead body 31. The surrounding member 17 includes four sponge bars 171 arranged to form a rectangular frame disposed in the covering between the upper and lower covering members 15, 16, and four corner positioning members 172 (only three are shown in Fig. 1) for supporting four corners of the rectangular frame, respectively. Each of the corner positioning members 172 is disposed between the upper and lower coverings 15, 16, and is formed with

an integral positioning post 173 inserted into a hole (not shown) in the corresponding sponge bar 171. With further reference to Fig. 1A, in this embodiment, each of the corner positioning members 172 has a horizontal rectangular bottom plate portion 174 and an L-shaped plate portion 175 extending upwardly from two adjacent sides of the bottom plate portion 174. Each of the positioning posts 173 extends upwardly from the bottom plate portion 174 of the corresponding corner positioning member 172. The lower covering member 16, the bedstead body 31, and the cover 32 have respectively aligned holes 161, 311, 323 formed therethrough. The electric air pump unit 2 is received within the holes 161, 311, 323 in the lower covering member 16, the bedstead body 31 and the cover 32, is disposed under and in fluid communication with one of the air chambers (E), and is in fluid communication with the other air chamber (E) via an air tube 4 (see Fig. 2).

Referring to Fig. 4, the bedstead assembly 3 includes a bedstead body 31 and a cover 32 made of a fabric for covering the bedstead body 31. The cover 32 has a rectangular top sheet 321 disposed on and above the bedstead body 31, and a surrounding sheet 322 extending downwardly from a periphery of the top sheet 321 and disposed around the bedstead body 31.

With further reference to Fig. 5, the bedstead body 31 includes a rigid support frame 33 and a top plate unit disposed on and above the support frame 33 and consisting

of six coplanar top plates 34 made of a plastic material. One of the top plates 34 is formed with the hole 311 therethrough. Any adjacent two ones of the top plates 34 are interconnected removably by two tongue and groove engagement units 35.

With additional reference to Fig. 9, the support frame 33 includes a pair of rectangular first and second foldable frame members 330 each convertible between an unfolded state shown in Fig. 5 and a folded state shown in Fig. 9. Each of the first and second foldable frame members 330 includes four parallel non-foldable plates 331 and three pairs of the foldable plates 332. Any two adjacent ones of the non-foldable plates 332 interconnect pivotally one corresponding pair of foldable plates 332 to define a void space 333 when a corresponding one of the first and second foldable frame members 330 is in the unfolded state. As such, the void spaces 333 in each of the first and second foldable frame members 330 are arranged in a row along a direction perpendicular to the non-foldable plates 331. The top plates 34 cover the void spaces 333, respectively. Each of the foldable plates 332 includes two pivotable plate portions 334 having outer ends connected respectively and pivotally to the corresponding non-foldable plates 331, and inner ends interconnected pivotally. In the unfolded state, the pivotable plate portions 334 of the foldable plates 332 are perpendicular to the non-foldable plates 331. In the folded state, the pivotable plate portions 334

of the foldable plates 332 are parallel to the non-foldable plates 331.

With particular reference to Figs. 6 and 8, each of the foldable plates 332 has a positioning unit including a positioning hole 335 formed in one of the pivotable plate portions 334 of the corresponding foldable plate 332, and a positioning projection 336 extending from the other of the pivotable plate portions 334 of the corresponding foldable plate 332 and engaging the positioning hole 335 when a corresponding one of the first and second foldable frame members 330 is in the unfolded state. Each of the pivotable plate portions 334 is connected pivotally to one end of the corresponding non-foldable plate 331, and the pivotable plate portions 334 of each of the foldable plates 332 are interconnected in such a manner that, when the corresponding one of the first and second foldable frame members 330 is in the unfolded state, each of the pivotable plate portions 334 is pivotable in only a direction toward the other end of the corresponding non-foldable plate 331, as shown in Figs. 7 and 8. When the first and second foldable frame members 330 are fully folded, the pivotable plate portions 334 of each of the foldable plates 332 abut against each other, and are sandwiched between the corresponding non-foldable plates 331. In this state, the positioning projections 336 are spaced apart from the positioning holes 335, respectively, as shown in Fig. 10.

With particular reference to Fig. 9, the first foldable

frame member 330 has an end connected pivotally to an end of the second foldable frame member 330 by four pivot units. The pivot units are disposed at adjacent ends of the first and second foldable frame members 330, and are adjacent to aligned top surfaces of the first and second foldable frame members 330. Each of pivot units includes two side sleeves 337 disposed on one of the first and second foldable frame members 330, a middle sleeve 338 disposed on the other of the first and second foldable frame members 330 and between the side sleeves 337, and a pivot pin 339 extending through the side sleeves 337 and the middle sleeve 338. As such, one of the folded frame members 330 can be pivoted about the pivot pins 339 to abut against the top surface of the other of the first and second foldable frame members 330, thereby resulting in convenience during transport and storage thereof.

Alternatively, the bedstead body 31 may include only one foldable frame member 330, and the foldable frame member 330 may include only two non-foldable plates 331 and two foldable plates 332 interconnecting the non-foldable plates 331 to define only one void space.

Referring to Fig. 11, the second preferred embodiment of this invention is similar in construction to the first preferred embodiment. In this embodiment, a first modified mattress assembly 1' also includes a top sheet 11, a bottom sheet 12, two surrounding sheets (not shown), and two reinforcing units (not shown). The top and bottom

5 sheets 11, 12 cooperate with the surrounding sheets to define a large air chamber (E') and a small air chamber (E'') that are not in fluid communication with each other. When inflated fully, the volume of the large air chamber (E') is greater than that of the small air chamber (E''). The reinforcing units are disposed respectively within the large and small air chambers (E', E''). The surrounding sheets are disposed respectively around the reinforcing units. As such, the mattress assembly 1' has a large
10 mattress 10 and a small mattress 10'. Each of the large and small mattresses 10, 10' includes a respective one of the surrounding sheets, and defines a respective one of the large and small air chambers (E', E''). The large and small mattresses 10, 10' are used to support the body and
15 head of one person, respectively.

With particular reference to Fig. 12, in this embodiment, the electric air pump unit 2 includes a housing 20, a centrifugal pump device 21 disposed in the housing 20, a solenoid-operated diaphragm pump device 22 disposed in the
20 housing 20, a first transfer chamber 23 formed in the housing 20 and in fluid communication with the centrifugal pump device 21, a second transfer chamber 24 formed in the housing 20 and in fluid communication with the first transfer chamber 23, a first control valve 25 biased to
25 a close position and operable to move to an open position so as to allow for fluid communication between the first and second transfer chambers 23, 24, two second control

valves 26 each biased to a close position and operable to move to an open position so as to allow for fluid communication between the second transfer chamber 24 and a respective one of the large and small air chambers (E', E'') in the mattress assembly 1', and a pressure sensor 27 in fluid communication with the second transfer chamber 24 via a sensor-connecting conduit 28.

It is noted that the centrifugal pump device 21 provides a smaller thrust for forcing air to flow at a higher flow rate, while the diaphragm pump device 22 provides a greater thrust for forcing air to flow at a slower flow rate. To promote the efficiency of the electric air pump unit 2 to inflate fully a selected one of the large and small air chambers (E', E''), the centrifugal pump device 21 is first operated until the selected one of the large and small air chambers (E', E'') is expanded to about 90% of its full-inflated volume. Subsequently, the diaphragm pump device 22 is operated to inflate the selected one of the large and small air chambers (E', E'') fully. That is, the centrifugal pump device 21 and the diaphragm pump device 22 perform respectively initial and subsequent inflation of the mattress assembly 1'. As a consequence, the air pump unit 2 can inflate the selected one of the large and small air chambers (E', E'') at a high speed to increase precisely the air pressure in the same to a desired pressure value. Thus, the object of this invention can be achieved.

To inflate the selected one of the large and small air

chambers (E' , E"), the centrifugal pump device 21 is activated, and the first control valve 25 and the corresponding second control valve 26 are opened. Hence, air is drawn into the centrifugal pump device 21, and is then forced into the selected one of the large and small air chambers (E' , E") via the first and second transfer chambers 23, 24. When the pressure sensor 27 detects that the air pressure in the second transfer chamber 24 reaches a first preset pressure value, e.g., 420 mmHG, it emits a signal to a controller 5 (see Fig. 15) via an electrical wire 6. When the controller 5 receives the signal, it deactivates the centrifugal pump device 21, closes the first control valve 25, and activates the diaphragm pump device 22 to force air into the second transfer chamber 24 via a pump-connecting conduit 29 until the pressure sensor 27 detects that the air pressure in the second transfer chamber 24 reaches a second preset pressure value to complete a full inflation of the selected one of the large and small air chambers (E' , E").

With further reference to Figs. 13 and 14, the diaphragm pump device 22 includes a valve seat 220 formed with a valve hole 221, a diaphragm valve 222, a valve rod 223 connected fixedly to the diaphragm valve 222, a coiled compression spring 223' for biasing the diaphragm valve 222 to close the valve hole 221 in the valve seat 220, and a driving unit for moving the valve rod 223. The driving unit includes a cam member 224 pivotable relative to the valve

seat 220 and having a cam surface 225 and a sector gear
 portion 226, a driving rod 227 rotatable about the central
 axis thereof and having a threaded portion 227' engaging
 the sector gear portion 226, a motor 228 having a motor
 5 shaft 228', and a transmission unit 229 interconnecting
 the motor shaft 228' and the driving rod 227 for
 transferring rotation of the motor shaft 228' to the driving
 rod 227. An end of the valve rod 223 is biased by the
 compression spring 223' to contact the cam surface 225 of
 10 the cam member 224. The driving rod 227 and the motor shaft
 228' are journaled on a mounting wall 20' of the housing
 20. The transmission unit includes a driving pulley 229
 sleeved fixedly on the motor shaft 228', a driven pulley
 229' sleeved fixedly on the driving rod 227, and a
 15 transmission belt 229" trained on the driving pulley 229
 and the driven pulley 229'.

With further reference to Fig. 15, the controller 5
 includes a display 51, a head key 52, a body key 53, a
 confirmation key 54, a micro-adjustment inflation key 55,
 20 a micro-adjustment deflation key 55', a main inflation key
 56, a main deflation key 57, a memory key 58, and a lock
 key 59. The operations of the keys 52, 53, 54, 55, 55',
 56, 57, 58, 59 are outlined in Figs. 16, 17, 18, 19, and
 20. The controller 5 is used to control the operation of
 25 the centrifugal pump device 21, the diaphragm pump device
 22, and the first and second control valves 25, 26.

When it desired to inflate the mattress 1, the main

inflation key 56 is first pressed to inflate the large and small air chambers (E', E'') to the first preset pressure value through operation of the centrifugal pump device 21. Next, a selected one of the head key 52 and the body key 53 is pressed, and subsequently, the confirmation key 54 is operated to select the softness of the selected one of the large and small mattresses 10, 10'. During operation of the confirmation key 54, the word "FIRM" is shown in the display 51 when the confirmation key 54 is pressed for the first time, the word "MEDIUM" is shown in the display 51 when the confirmation key 54 is pressed for the second time, and the word "PLUSH" is shown in the display 51 when the confirmation key 54 is pressed for the third time. Thereafter, if necessary, the micro-adjustment inflation key 55 or the micro-adjustment deflation key 55' can be pressed to micro-adjust the air pressure in the selected one of the large and small mattresses 10, 10' through operation of the diaphragm pump device 22. When "FIRM" is selected during operation of the confirmation key 54, the selected one of the large and small air chambers (E', E'') can be inflated fully.

When it is desired to deflate a selected one of the large and small mattresses 10, 10', a corresponding one of the head key 52 and the body key 53 is pressed to open the first control valve 25 and the corresponding second control valve 26 to thereby allow air to flow from the selected one of the large and small mattresses 10, 10' out of the housing

20 via the first control valve 25 and the centrifugal pump device 21.

When it is desired to increase the softness of a selected one of the large and small mattresses 10, 10', the corresponding one of the head key 52 and the body key 53 is pressed, and the micro-adjustment deflation key 55' is operated. When the micro-adjustment deflation key 55' is pressed, the first control valve 25 and the corresponding second control valve 26 are opened to allow for outflow of air from the selected one of the large and small mattresses 10, 10'. When the micro-adjustment deflation key 55' is released, the first control valve 25 and the corresponding second control valve 26 are closed.

When it is desired to change the first preset pressure value, the memory key 58 is operated.

The control panel 5 can be converted between locked and unlocked states through pressing of the lock key 59. In the locked state, when any of the remaining keys 52, 53, 54, 55, 55', 56, 57, 58 is pressed (e.g., unintentionally), no operation is executed and the mattress assembly 1 remains in its present state.

Fig. 21 shows a modified air pump unit 2', which is similar in construction to the electric air pump unit 2 (see Fig. 12) except that the pressure sensor 27 is in fluid communication with the large and small mattresses 10, 10' through two mattress-connecting conduits 28' (only one is shown), respectively. As such, the air pressures in the

large and small mattresses 10, 10' can be measured accurately.

Referring to Fig. 22, the third preferred embodiment of this invention is similar in construction to the second preferred embodiment. In this embodiment, a second modified mattress assembly 1" includes four surrounding sheets (not shown) and four reinforcing units (not shown), and the control panel includes a pair of left and right head keys (not shown) for replacing the head key 52 (see Fig. 15), and a pair of left and right body keys (not shown) for replacing the body key 53 (see Fig. 15). The top and bottom sheets 11, 12 cooperate with the surrounding sheets to define two juxtaposed large air chambers (E') and two juxtaposed small air chambers (E''). The large and small air chambers (E', E'') are arranged in a matrix. The reinforcing units are disposed respectively within the large and small air chambers (E', E''). The surrounding sheets are disposed respectively around the reinforcing units. As such, the mattress assembly 1" has two large mattresses 10 and two small mattresses 10'. Each of the large and small mattresses 10, 10' includes a respective one of the surrounding sheets, and defines a respective one of the large and small air chambers (E', E''). Each aligned pair of the large and small mattresses 10, 10' may be used to support the body and head of one person, respectively. Stated differently, the mattress assembly 1" can support two people.

In this embodiment, with additional reference to Fig. 23, the mattress assembly 1" includes four air conduits (A) (only three are shown) in fluid communication with the large and small air chambers (E', E'') (only three are shown), respectively. Each of the air conduits (A) has an internally threaded connecting end (A'). The electric air pump unit 2 includes four externally threaded connecting members (B) engaging respectively and threadably the connecting ends (A') of the air conduits (A) of the mattress assembly 1". An electrical socket unit (C) is disposed on a sidewall 30 of the bedstead assembly 3. An electrical wire unit (W) interconnects electrically the electrical socket unit (C) and the electric air pump unit 2.

Referring to Figs. 24 and 25, the fourth preferred embodiment of this invention is similar in construction to the first preferred embodiment. In this embodiment, a third modified mattress assembly 1A includes a top sheet 11, a bottom sheet 12, a surrounding sheet 13 interconnecting the top and bottom sheets 11, 12 to define an air chamber (E), and a reinforcing unit 14 consisting of a plurality of pull belts 141 and a surrounding belt 142. In this embodiment, since the mattress assembly 1A is formed with a single air chamber (E), the second transfer chamber 24 (see Fig. 12) is in direct fluid communication with the air chamber (E), and the second control valves 26 are omitted from the configuration of the electric air pump unit 2.

To inflate the air chamber (E) to a desired volume, the centrifugal pump device 21 (see Fig. 12) may be first operated until the air chamber (E) is expanded to about 90% of the desired volume at a higher speed. Subsequently, the diaphragm pump device 22 (see Fig. 12) is operated to inflate precisely the air chamber (E) to the desired volume at a slower speed.

CLAIMS:

1. An inflatable bed comprising:

a bedstead assembly;

a mattress assembly having at least one air chamber;

5 and

an electric air pump unit in connection with said mattress assembly and including

a centrifugal pump device in fluid communication with said air chamber in said mattress assembly for inflating said air chamber,

10

a first control valve operable to allow for and interrupt fluid communication between said centrifugal pump device and said air chamber, and

15

a diaphragm pump device in communication with said air chamber for inflating said air chamber;

20

whereby, said first control valve is controllable to allow for fluid communication between said centrifugal pump device and said air chamber so that said centrifugal pump device is operable to perform inflation of said air chamber to a first pressure value; and said first control valve is controllable to interrupt fluid communication between said centrifugal pump device and said air chamber so that said diaphragm pump device is operable to perform inflation of the air chamber to a second pressure value.

25

2. The inflatable bed as claimed in Claim 1, wherein said air pump unit further includes a housing for receiving

said centrifugal pump device and said diaphragm pump device therein.

3. The inflatable bed as claimed in Claim 2, wherein

5 said mattress assembly is formed with two said air chambers that are not in fluid communication with each other; and

 said air pump unit further includes:

10 a first transfer chamber formed in said housing and in fluid communication with said centrifugal pump device;

 a second transfer chamber formed in said housing and in fluid communication with said first transfer chamber and said air chamber, said first control valve being operable to allow for and interrupt fluid communication between said first and second transfer chambers; and

15 two second control valves each controllable to allow for and interrupt fluid communication between said second transfer chamber and a respective one of said air chambers.

20 4. The inflatable bed as claimed in Claim 3, wherein said air pump unit further includes a controller operable to control operation of said centrifugal pump device, said diaphragm pump device, and said first and second control valves.

25 5. The inflatable bed as claimed in Claim 3, wherein said air pump unit further includes a pressure sensor and a sensor-connecting conduit, said pressure sensor being

in fluid communication with said second transfer chamber via said sensor-connecting conduit for detecting an air pressure in said second transfer chamber.

5 6. The inflatable bed as claimed in Claim 1, wherein said air pump unit further includes a pressure sensor and a sensor-connecting conduit, said pressure sensor being in fluid communication with said air chamber via said sensor-connecting conduit.

10 7. The inflatable bed as claimed in Claim 1, wherein said diaphragm pump device includes:

a valve seat formed with a valve hole;

a diaphragm valve;

a valve rod connected fixedly to said diaphragm valve;

15 a coiled compression spring for biasing said diaphragm valve to close said valve hole in said valve seat; and

a driving unit for moving said valve rod.

20 8. The inflatable bed as claimed in Claim 7, wherein said driving unit includes:

a cam member pivotable relative to said valve seat and having a cam surface and a sector gear portion, an end of said valve rod being biased by said compression spring to contact said cam surface of said cam member;

25 a driving rod rotatable about a central axis thereof and having a threaded portion engaging said sector gear portion;

a motor having a motor shaft; and
a transmission unit interconnecting said motor shaft
and said driving rod for transferring rotation of said
motor shaft to said driving rod.

- 5 9. The inflatable bed as claimed in Claim 8, wherein said
transmission unit includes:

a driving pulley sleeved fixedly on said motor
shaft;

- 10 a driven pulley sleeved fixedly on said driving rod;
and

a transmission belt trained on said driving pulley
and said driven pulley.

10. The inflatable bed as claimed in Claim 1, wherein:

- 15 said mattress assembly includes a plurality of said
air chambers, and a plurality of air conduits in fluid
communication with said air chambers, respectively,
each of said air conduits having a connecting end; and

- 20 said electric air pump unit includes a plurality of
connecting members engaging respectively and threadably
said connecting ends of said air conduits of said
mattress assembly.

- 25 11. The inflatable bed as claimed in Claim 10, wherein said
bedstead assembly includes a sidewall, said inflatable
bed further comprising an electrical socket unit
disposed on said sidewall, and an electrical wire unit
interconnecting electrically said electrical socket
unit and said electric air pump unit.

12. The inflatable bed as claimed in Claim 1, wherein said mattress assembly is disposed on and above said bedstead assembly.

5 13. The inflatable bed as claimed in Claim 1, wherein said electric air pump unit is disposed on said bedstead assembly.