

Description

This invention relates to a hook and loop fastener otherwise known as a velvet clasp fastener comprising two layers of fabric which are releasably engageable with each other. One of the fabric layers carries hook-shaped or male elements engageable with loop or female elements on the other fabric layer. The present invention is more specifically concerned with such hook and loop fasteners which comprise a warp-knit support tape carrying thereon a multiplicity of pile-loop elements and engageable with its mating hook-carrying tape.

A typical hook and loop fastener having a warp-knit support tape structure is known, as for example disclosed in Japanese Patent Publication No. 57-381, in which threads are formed into pile-loops by lateral lapping over every other wale on the tape, the pile-loops being anchored in place with their leg portions knitted into chain stitches of a foundation web. (See fig. 6 enclosed).

Such prior art fastener has a drawback in that due to pile-loops being formed by lapping over every other wale, the interstices of the web in between the pile and the foundation become coarse and weak so that the pile is prone to shift out of position and to get sometimes pulled off.

The European patent application EP-A 91 273 describes a warp pile fabric support tape carrying the loops for a hook-and-loop fastener with laid-in weft threads, the pile loops extending longitudinally of the tape.

The present invention seeks to provide a hook and loop fastener which will eliminate the foregoing drawbacks of the prior art and which has a warp-knit support tape carrying thereon pile-loops or female elements better securely held in place against displacement or dislocation.

The present invention further seeks to provide a hook and loop fastener in which the pile-loops are arranged to provide increased opportunity of engagement with hook elements on the mating support tape.

The warp-knit support tape of the present invention as claimed comprises the loop or female part of a hook and loop fastener, and has a pile portion with laid-in weft threads and pile loops extending longitudinally of the tape. According to the invention, the pile portion further comprises two needle stitches laced together with the laid-in weft threads to make a foundation of the tape. Chain stitches are formed by sinker looping into a multiplicity of pile-loops, in such a way that the pile-loops extend alternatively along the right and left sides of the wales.

The invention will be better understood from the following detailed description of an example taken with reference to the accompanying drawings.

Figure 1 schematically illustrates the construction of a warp-knit support tape embodying the invention for use as a loop part of a hook and loop fastener;

Figures 2a - 2d, inclusive, each are schematic diagrams of stitches constituting the warp-knit tape of Figure 1;

Figure 3 is a schematic representation on enlarged scale of a portion of the tape of Figure 1;

Figure 4 is a schematic side elevation showing the pile-loops of the tape of Figure 1;

Figures 5a - 5d, inclusive, each are schematic diagrams of stitches constituting another form of warp-knit tape embodying the invention; and

Figure 6 schematically shows the construction of a prior art warp-knit tape for a hook and loop fastener.

Referring now to the drawings and Figure 1 in particular, there is shown a preferred form of a warp-knit support tape 10 to be used as a loop or female part of a hook and loop fastener. The support tape 10 consists of a pile portion 11 and selvage portions 12 and 13 extending warwise on opposite sides of the pile portion 11. The pile portion 11 of the tape 10 is constructed with two needle stitches 14, laid-in weft threads 15, both of which are laced together to make up a foundation of the tape 10, and chain stitches 16 which form a multiplicity of pile-loops 17. As shown in Figure 2a, the chain stitch 16 is of an open lap having a Link No. 1-0/0-0/0-1/1-1, and threads therefor are positively overfed about 1.5 times the normal rate of feed of threads for the remaining stitches and formed by sinker looping into pile-loops 17 extending over every other course in overlapping relation to the knitting needles. The pile-loops 17 are arranged to extend longitudinally of the tape 10 alternately along the right and left sides of wales 18 as shown in Figure 3, and also to tilt sidewise alternately in opposite direction as shown in Figure 4, the arrangement being that the pile-loops 17 give themselves more opportunity to engage the hooks on the mating tape, not shown, than would be otherwise possible.

In the embodiment shown in Figure 1 and as better shown in Figure 2a, the pile-loops 17 extend over every other course. They may of course be modified to extend over every two or three, or even at each course as shown in Figure 5, depending upon the size of starting threads, the density of knit fabric, or the combination with companion hooks.

The foundation of the support tape 10 is formed by two needle stitches 14 of Link No. 0-2/2-0/0-2/2-0 as shown in Figure 2c and laid-in weft threads 15 of Link No. 0-0/4-4/0-0/4-4. As shown in Figure 3, the sinker loops 14a, 14b of two needle stitches 14 are arranged to urge and hold the leg portions 17a of pile-loops 17 criss-cross against the foundation web of the tape 10, while the laid-in weft threads 15 fill up in between the sinker loops 14a, 14b and the pile-loops 17, thus anchoring the pile-loops 17 stably in place against displacement or dislocation.

As better shown in Figure 3, the sinker loops 14a, 14b of two needle stitches 14 are laced in a manner to bear against the foundation loops 19 that form the wales 18, and the weft threads 15 that are laid in densely between the foundation loops 19 and the sinker loops 14a, 14b are held in place by the latter loops, whereby the tape system as a whole is rendered highly resistant to stretch in either direction. This will in turn reduce the amount of resinous coatings required to make the knit tape firm and prevent

the pile-loops from falling off and further serve to provide a tape product which is physically soft.

The selvages 12 and 13 extend over three wales on opposite sides of the tape 10 as shown in Figure 1 and are constructed with the two needle stitches 14, laid-in weft threads 15 and chain stitches 20 of an open lap having Link No. 1-0/0-1/1-0/0-1. The tape 10 is sewn or otherwise attached along the selvages 12 and 13 onto a garment article.

Claims

1. Warp-knit support tape (10) comprising the loop or female part of a hook and loop fastener, with a file portion having laid-in weft threads (15) and pile-loops (17) extending longitudinally of the tape (10), characterized in that said pile portion further comprises two needle stitches (14) laced together with said laid-in-weft threads to make up a foundation of the tape, and chain stitches (16) formed by sinker looping into a multiplicity of pile-loops (17) in such a way that the pile loops extend alternately along the right and left sides of the wales (18).

2. A warp-knit support tape (10) according to claim 1 wherein said pile-loops (17) are tilted sidewise alternately in opposite directions.

3. A warp-knit support tape (10) according to claim 1 wherein said pile-loops (17) extend over every other course.

4. A warp-knit support tape (10) according to claim 1 wherein said pile-loops (17) extend along each course.

5. A warp-knit support tape (10) according to claim 1 wherein said two needle stitches (14) have their sinker loops (14a), (14b) arranged to hold said pile-loops (17) criss-cross against the foundation of the tape (10).

Patentansprüche

1. Kettengewirktes Tragband (10), umfassend den Schlingenteil oder den weiblichen Teil eines Haftverschlusses, mit einem Florbereich, der eingelegte Schußfäden (15) und Florschlingen (17) aufweist, die sich in Längsrichtung des Tragbandes (10) erstrecken, dadurch gekennzeichnet, daß der Florbereich ferner zwei Nadelfäden (14) umfaßt, die mit den eingelegten Schußfäden abgebunden sind, um ein Grundgewirk des Tragbandes zu bilden, und Fransenfäden (16) aufweist, deren Platinenmaschen eine Vielzahl von Florschlingen (17) derart bilden, daß sich die Florschlingen abwechselnd auf der rechten und linken Seite der Maschenstäbchen (18) erstrecken.

2. Kettengewirktes Tragband (10) nach Anspruch 1, wobei die Florschlingen (17) abwechselnd in entgegengesetzten Richtungen geneigt sind.

3. Kettengewirktes Tragband (10) nach Anspruch 1, wobei sich die Florschlingen (17) über eine Maschenreihe nach der anderen erstrecken.

4. Kettengewirktes Tragband (10) nach Anspruch 1, wobei sich die Florschlingen (17) entlang jeder Maschenreihe erstrecken.

5. Kettengewirktes Tragband (10) nach Anspruch 1, wobei die Platinenmaschen (14a, 14b) der Nadelfä-

den (14) so angeordnet sind, um die Florschlingen (17) kreuz und quer gegen das Grundgewirk des Tragbandes (10) zu halten.

5 Revendications

1. Ruban de support (10) tricoté-chaîne comprenant la partie munie de boucles, ou partie femelle, d'une fermeture à crochets et boucles, comportant une partie munie de poils présentant des fils de trame (15) incorporés et des boucles-poils (17) s'étendant dans le sens longitudinal du ruban (10) caractérisé en ce que ladite partie munie de poils comprend en outre des mailles (14) sur deux aiguilles, entrelacées avec les fils de trame incorporés pour constituer le fond du ruban, et des mailles (16) de chaînette créées par la platine pour former une multiplicité de boucles-poils (17) d'une façon telle que les boucles-poils s'étendent alternativement sur les côtés gauche et droit des colonnes (18).

2. Ruban de support (10) selon la revendication 1, dans lequel lesdites boucles-poils (17) sont inclinées latéralement alternativement dans des sens opposés.

3. Ruban de support (10) selon la revendication 1, dans lequel lesdites boucles-poils (17) s'étendent sur une rangée sur deux.

4. Ruban de support (10) selon la revendication 1, dans lequel lesdites boucles-poils (17) s'étendent le long de chaque rangée.

5. Ruban de support (10) selon la revendication 1, dans lequel lesdites mailles (14) à deux aiguilles comportent des boucles d'abattage (14a), (14b) disposées de façon à retenir lesdites boucles-poils (17) dans les deux sens contre la base du ruban (10).

40

45

50

55

60

65

the pile-loops from falling off and further serve to provide a tape product which is physically soft.

The selvages 12 and 13 extend over three wales on opposite sides of the tape 10 as shown in Figure 1 and are constructed with the two needle stitches 14, laid-in weft threads 15 and chain stitches 20 of an open lap having Link No. 1-0/0-1/1-0/0-1. The tape 10 is sewn or otherwise attached along the selvages 12 and 13 onto a garment article.

Claims

1. Warp-knit support tape (10) comprising the loop or female part of a hook and loop fastener, with a file portion having laid-in weft threads (15) and pile-loops (17) extending longitudinally of the tape (10), characterized in that said pile portion further comprises two needle stitches (14) laced together with said laid-in-weft threads to make up a foundation of the tape, and chain stitches (16) formed by sinker looping into a multiplicity of pile-loops (17) in such a way that the pile loops extend alternately along the right and left sides of the wales (18).
2. A warp-knit support tape (10) according to claim 1 wherein said pile-loops (17) are tilted sidewise alternately in opposite directions.
3. A warp-knit support tape (10) according to claim 1 wherein said pile-loops (17) extend over every other course.
4. A warp-knit support tape (10) according to claim 1 wherein said pile-loops (17) extend along each course.
5. A warp-knit support tape (10) according to claim 1 wherein said two needle stitches (14) have their sinker loops (14a), (14b) arranged to hold said pile-loops (17) criss-cross against the foundation of the tape (10).

Patentansprüche

1. Kettengewirktes Tragband (10), umfassend den Schlingenteil oder den weiblichen Teil eines Haftverschlusses, mit einem Florbereich, der eingelegte Schußfäden (15) und Florschlingen (17) aufweist, die sich in Längsrichtung des Tragbandes (10) erstrecken, dadurch gekennzeichnet, daß der Florbereich ferner zwei Nadelfäden (14) umfaßt, die mit den eingelegten Schußfäden abgebunden sind, um ein Grundgewirk des Tragbandes zu bilden, und Fransenfäden (16) aufweist, deren Platinenmaschen eine Vielzahl von Florschlingen (17) derart bilden, daß sich die Florschlingen abwechselnd auf der rechten und linken Seite der Maschenstäbchen (18) erstrecken.
2. Kettengewirktes Tragband (10) nach Anspruch 1, wobei die Florschlingen (17) abwechselnd in entgegengesetzten Richtungen geneigt sind.
3. Kettengewirktes Tragband (10) nach Anspruch 1, wobei sich die Florschlingen (17) über eine Maschenreihe nach der anderen erstrecken.
4. Kettengewirktes Tragband (10) nach Anspruch 1, wobei sich die Florschlingen (17) entlang jeder Maschenreihe erstrecken.
5. Kettengewirktes Tragband (10) nach Anspruch 1, wobei die Platinenmaschen (14a, 14b) der Nadelfä-

den (14) so angeordnet sind, um die Florschlingen (17) kreuz und quer gegen das Grundgewirk des Tragbandes (10) zu halten.

Revendications

1. Ruban de support (10) tricoté-chaine comprenant la partie munie de boucles, ou partie femelle, d'une fermeture à crochets et boucles, comportant une partie munie de poils présentant des fils de trame (15) incorporés et des boucles-poils (17) s'étendant dans le sens longitudinal du ruban (10) caractérisé en ce que ladite partie munie de poils comprend en outre des mailles (14) sur deux aiguilles, entrelacées avec les fils de trame incorporés pour constituer le fond du ruban, et des mailles (16) de chaîne créées par la platine pour former une multiplicité de boucles-poils (17) d'une façon telle que les boucles-poils s'étendent alternativement sur les côtés gauche et droit des colonnes (18).
2. Ruban de support (10) selon la revendication 1, dans lequel lesdites boucles-poils (17) sont inclinées latéralement alternativement dans des sens opposés.
3. Ruban de support (10) selon la revendication 1, dans lequel lesdites boucles-poils (17) s'étendent sur une rangée sur deux.
4. Ruban de support (10) selon la revendication 1, dans lequel lesdites boucles-poils (17) s'étendent le long de chaque rangée.
5. Ruban de support (10) selon la revendication 1, dans lequel lesdites mailles (14) à deux aiguilles comportent des boucles d'abattage (14a), (14b) disposées de façon à retenir lesdites boucles-poils (17) dans les deux sens contre la base du ruban (10).

