

Description**TECHNICAL FIELD**

5 The present invention relates to a bleaching detergent composition containing crystalline alkali metal aluminosilicate (zeolite) as a detergency builder, and also including a bleach system comprising a peroxy bleach compound and a bleach precursor.

BACKGROUND AND PRIOR ART

10 The ability of crystalline alkali metal aluminosilicate (zeolite) to sequester calcium ions from aqueous solution has led to its becoming a well-known replacement for phosphates as a detergency builder. Particulate detergent compositions containing zeolite are widely disclosed in the art, for example, in GB 1 473 201 (Henkel), and are sold commercially in many parts of Europe, Japan and the United States of America.

15 Although many crystal forms of zeolite are known, the preferred zeolite for detergents use has always been zeolite A: other zeolites such as X or P(B) have not found favour because their calcium ion uptake is either inadequate or too slow. Zeolite A has the advantage of being a "maximum aluminium" structure containing the maximum possible proportion of aluminium to silicon - or the theoretical minimum Si:Al ratio of 1.0 - so that its capacity for taking up calcium ions from aqueous solution is intrinsically greater than those of zeolite X and P which generally contain a lower proportion of aluminium (or a higher Si:Al ratio).

20 EP 384 070A (Unilever) describes and claims a novel zeolite P (maximum aluminium zeolite P, or zeolite MAP) having an especially low silicon to aluminium ratio, not greater than 1.33 and preferably not greater than 1.15. This material is demonstrated to be a more efficient detergency builder than conventional zeolite 4A.

25 EP 448 297A and EP 502 675A (Unilever) disclose detergent formulations containing zeolite MAP with a cobuilder (citrate or polymer), and also containing sodium perborate monohydrate bleach and TAED bleach precursor. Compositions containing zeolite MAP exhibit better detergency than corresponding compositions containing zeolite 4A.

30 It has now been discovered that replacement of zeolite A by zeolite MAP gives an additional benefit in detergent powders of high bulk density (700 g/l and above) containing bleach precursors: the stability of the bleach precursor on storage is significantly increased. This is surprising because the water content of zeolite MAP is not significantly lower than that of zeolite A.

DEFINITION OF THE INVENTION

35 The present invention provides the use of zeolite P having a silicon to aluminium ratio not greater than 1.33 (zeolite MAP) to improve the stability of a bleach precursor in a particulate bleaching detergent composition having a bulk density of at least 700 g/l and comprising:

- 40 (a) one or more detergent-active compounds,
 (b) one or more detergency builders including alkali metal aluminosilicate comprising zeolite MAP, and
 (c) a bleach system comprising a peroxy bleach compound and a bleach precursor.

A further subject of the invention is a particulate bleaching detergent composition comprising

- 45 (a) one or more detergent-active compounds,
 (b) one or more detergency builders including alkali metal aluminosilicate comprising zeolite P having a silicon to aluminium ratio not greater than 1.33 (zeolite MAP), and
 (c) a bleach system comprising a peroxy bleach compound other than sodium perborate monohydrate and a bleach precursor.

50 Particulate bleaching detergent compositions as defined above but containing sodium perborate monohydrate as peroxy bleach compound are the subject of EP 552 053A (Unilever).

DETAILED DESCRIPTION OF THE INVENTION

55 The subject of the invention is the use of zeolite MAP to stabilise a bleach precursor in a particulate bleaching detergent composition of high bulk density containing detergent-active compounds, a builder system based on zeolite MAP, and a bleaching system containing a peroxy bleach compound and a bleach precursor. These are the essential elements of the invention; other optional detergent ingredients may also be present in the composition as desired or required.

A preferred detergent composition in accordance with the invention comprises:

- (a) from 5 to 60 wt% of one or more detergent-active compounds,
 - (b) from 10 to 80 wt% of one or more detergency builders, including zeolite MAP;
 - (c) a bleach system comprising from 5 to 35 wt% of a peroxy bleach compound and from 1 to 8 wt% of a bleach precursor,
 - (d) optionally other detergent ingredients to 100 wt%,
- all percentages being based on the detergent composition.

The detergent-active compound

The detergent compositions of the invention will contain, as essential ingredients, one or more detergent-active compounds (surfactants) which may be chosen from soap and non-soap anionic, cationic, nonionic, amphoteric and zwitterionic detergent-active compounds, and mixtures thereof. Many suitable detergent-active compounds are available and are fully described in the literature, for example, in "Surface-Active Agents and Detergents", Volumes I and II, by Schwartz, Perry and Berch.

The preferred detergent-active compounds that can be used are soaps and synthetic non-soap anionic and nonionic compounds.

Anionic surfactants are well-known to those skilled in the art. Examples include alkylbenzene sulphonates, particularly linear alkylbenzene sulphonates having an alkyl chain length of C_8 - C_{15} ; primary and secondary alkyl sulphates, particularly C_{12} - C_{15} primary alkyl sulphates; alkyl ether sulphates; olefin sulphonates; alkyl xylene sulphonates; dialkyl sulphosuccinates; and fatty acid ester sulphonates. Sodium salts are generally preferred.

Nonionic surfactants that may be used include the primary and secondary alcohol ethoxylates, especially the C_{10} - C_{20} aliphatic alcohols ethoxylated with an average of from 1 to 20 moles of ethylene oxide per mole of alcohol, and more especially the C_{12} - C_{15} primary and secondary aliphatic alcohols ethoxylated with an average of from 1 to 10 moles of ethylene oxide per mole of alcohol.

Also of interest are non-ethoxylated nonionic surfactants, for example, alkylpolyglycosides; and O-alkanoyl glucosides as described in EP 423 968A (Unilever).

The choice of detergent-active compound (surfactant), and the amount present, will depend on the intended use of the detergent composition: different surfactant systems may be chosen, as is well known to the skilled formulator, for handwashing products and for products intended for use in different types of washing machine.

The total amount of surfactant present will also depend on the intended end use, but will generally range from 5 to 60 wt%, preferably from 5 to 40 wt%.

Detergent compositions suitable for use in most automatic fabric washing machines generally contain anionic non-soap surfactant, or nonionic surfactant, or combinations of the two in any ratio, optionally together with soap.

The detergency builder system

The detergent compositions of the invention also contains one or more detergency builders. The total amount of detergency builder in the compositions will suitably range from 10 to 80 wt%.

The detergency builder system of the compositions of the invention is based on zeolite MAP, optionally in conjunction with one or more supplementary builders. The amount of zeolite MAP present may suitably range from 5 to 60 wt%, more preferably from 15 to 40 wt%.

Preferably, the alkali metal aluminosilicate present in the compositions of the invention consists substantially wholly of zeolite MAP.

Zeolite MAP

Zeolite MAP (maximum aluminium zeolite P) and its use in detergent compositions are described and claimed in EP 384 070A (Unilever). It is defined as an alkali metal aluminosilicate of the zeolite P type having a silicon to aluminium ratio not greater than 1.33, preferably within the range of from 0.9 to 1.33, and more preferably within the range of from 0.9 to 1.2.

Of especial interest is zeolite MAP having a silicon to aluminium ratio not greater than 1.15; and zeolite MAP having a silicon to aluminium ratio not greater than 1.07 is especially preferred.

Zeolite MAP generally has a calcium binding capacity of at least 150 mg CaO per g of anhydrous aluminosilicate, as measured by the standard method described in GB 1 473 201 (Henkel) and also

described, as "Method I", in EP 384 070A (Unilever). The calcium binding capacity is normally at least 160 mg CaO/g and may be as high as 170 mg CaO/g. Zeolite MAP also generally has an "effective calcium binding capacity", measured as described under "Method II" in EP 384 070A (Unilever), of at least 145 mg CaO/g, preferably at least 150 mg CaO/g.

Although zeolite MAP like other zeolites contains water of hydration, for the purposes of the present invention amounts and percentages of zeolite are generally expressed in terms of the notional anhydrous material. The amount of water present in hydrated zeolite MAP at ambient temperature and humidity is normally about 20 wt%.

10 Particle size of the zeolite MAP

Preferred zeolite MAP for use in the present invention is especially finely divided and has a d_{50} (as defined below) within the range of from 0.1 to 5.0 micrometres, more preferably from 0.4 to 2.0 micrometres and most preferably from 0.4 to 1.0 micrometres.

15 The quantity " d_{50} " indicates that 50 wt% of the particles have a diameter smaller than that figure, and there are corresponding quantities " d_{80} ", " d_{90} " etc. Especially preferred materials have a d_{90} below 3 micrometres as well as a d_{50} below 1 micrometre.

Various methods of measuring particle size are known, and all give slightly different results. In the present specification, the particle size distributions and average values (by weight) quoted were measured 20 by means of a Malvern Mastersizer (Trade Mark) with a 45 mm lens, after dispersion in demineralised water and ultrasonification for 10 minutes.

Advantageously, but not essentially, the zeolite MAP may have not only a small average particle size, but may also contain a low proportion, or even be substantially free, of large particles. Thus the particle size distribution may advantageously be such that at least 90 wt% and preferably at least 95 wt% are smaller 25 than 10 micrometres; at least 85 wt% and preferably at least 90 wt% are smaller than 6 micrometres; and at least 80 wt% and preferably at least 85 wt% are smaller than 5 micrometres.

Other builders

30 The zeolite MAP may, if desired, be used in conjunction with other inorganic or organic builders. However, the presence of significant amounts of zeolite A is not preferred.

Inorganic builders that may be present include sodium carbonate, if desired in combination with a crystallisation seed for calcium carbonate, as disclosed in GB 1 437 950 (Unilever). Organic builders that may be present include polycarboxylate polymers such as polyacrylates, acrylic/maleic copolymers, and 35 acrylic phosphinates; monomeric polycarboxylates such as citrates, gluconates, oxydisuccinates, glycerol mono-, di- and trisuccinates, carboxymethyloxysuccinates, carboxymethyloxymalonates, dipicolinates, hydroxyethyliminodiacetates, alkyl- and alkenylmalonates and succinates; and sulphonated fatty acid salts. This list is not intended to be exhaustive.

Builders, both inorganic and organic, are preferably present in alkali metal salt, especially sodium salt, 40 form.

Preferred supplementary builders for use in conjunction with zeolite MAP include citric acid salts, more especially sodium citrate, suitably used in amounts of from 3 to 20 wt%, more preferably from 5 to 15 wt%. This builder combination is described and claimed in EP 448 297A (Unilever).

Also preferred are polycarboxylate polymers, more especially acrylic/maleic copolymers, suitably used 45 in amounts of from 0.5 to 15 wt%, especially from 1 to 10 wt%, of the detergent composition; this builder combination is described and claimed in EP 502 675A (Unilever).

The bleach system

50 Detergent compositions according to the invention contain a bleach system, which comprises a peroxy bleach compound in combination with a bleach precursor.

The peroxy bleach compound is suitably present in an amount of from 5 to 35 wt%, preferably from 10 to 25 wt%.

The bleach precursor is suitably present in an amount of from 1 to 8 wt%, preferably from 2 to 5 wt%.

The peroxy bleach compound

The compositions of the invention contain an inorganic or organic peroxy bleach compound capable of yielding hydrogen peroxide in aqueous solution.

5 Peroxy bleach compounds suitable for use in the compositions of the invention include organic peroxides such as urea peroxide, and inorganic persalts, such as the alkali metal perborates, percarbonates, perphosphates, persilicates and persulphates. Mixtures of two or more such compounds may also be suitable.

10 Particularly preferred are sodium perborate tetrahydrate and, especially, sodium perborate monohydrate. Sodium perborate monohydrate is preferred because of its high active oxygen content.

Particulate detergent compositions having a bulk density of at least 700 g/l and containing a builder system comprising zeolite MAP and a bleach system sodium perborate monohydrate are the subject of EP 552 053A (Unilever).

15 Sodium percarbonate may also be preferred for environmental reasons. Especially preferred is sodium percarbonate having a protective coating to improve its storage stability: coated sodium percarbonate is available commercially from FMC Corporation (USA) and from Kao Corporation (Japan), and is disclosed in GB 2 123 044B (Kao).

Particulate detergent compositions containing a builder system comprising zeolite MAP and a bleach system comprising sodium percarbonate are the subject of EP 522 726A (Unilever).

The bleach precursor

20 Peroxyacid bleach precursors are known and amply described in the literature, for example, GB 836 988, GB 864 798, GB 907 356, GB 1 003 310, GB 1 519 351, DE 3 337 921A, EP 185 522A, EP 174 132A, EP 120 591A, US 1 246 339, US 3 332 882, US 4 128 494, US 4 412 934 and US 4 675 393.

Preferred bleach precursors are peroxycarboxylic acid precursors, more especially peracetic acid precursors and peroxybenzoic acid precursors; and peroxycarbonic acid precursors.

An especially preferred peracetic acid precursor is N,N,N',N'-tetraacetylenediamine (TAED).

30 One class of especial interest is formed by the quaternary ammonium- and phosphonium-substituted bleach precursors, for example, as disclosed in US 4 751 015 and US 4 397 757 (Lever Brothers Company), and EP 284 292A and EP 331 229A (Unilever). Examples of peroxyacid bleach precursors of this class are:

2-(N,N,N-trimethylammonium) ethyl sodium-4-sulphophenyl carbonate chloride (SPCC), also known as choly-p-sulphophenyl carbonate (CSPC);

35 N-octyl-N,N-dimethyl-N₁₀-carbophenoxydecyl ammonium chloride (NDC);

3-(N,N,N-trimethylammonium)propyl sodium-4-sulphophenyl carboxylate; and
N,N,N-trimethylammonium toluoyloxy benzene sulphonate.

A further special class of cationic peroxyacid bleach precursors is formed by the cationic nitriles as disclosed in EP 284 292A, EP 303 520A, EP 458 396A and EP 464 880A (Kao).

40 Any one of these peroxyacid bleach precursors may be used in the compositions of the present invention, although some may be more preferred than others.

Of the above classes of bleach precursors, the preferred classes are the esters, including acyl phenol sulphonates and acyl alkyl phenol sulphonates;

the acyl-amides; and the quaternary ammonium substituted peroxyacid precursors including the cationic

45 nitriles.

Examples of preferred peroxyacid bleach precursors for use in the present invention include:

sodium 4-benzoyloxybenzene sulphonate (SBOBS);

N,N,N',N'-tetracetyl ethylenediamine (TAED);

sodium 1-methyl-2-benzoyloxybenzene-4-sulphonate;

50 sodium 4-methyl-3-benzoyloxy benzoate;

2-(N,N,N-trimethylammonium) ethyl sodium-4-sulphophenyl carbonate chloride (SPCC), also known as choly-p-sulphophenyl carbonate (CSPC);

trimethylammonium toluoyloxybenzene sulphate;

sodium nonanoyloxybenzene sulphonate (SNOBS);

55 sodium 3,5,5-trimethylhexanoyloxybenzene sulphonate (STHOBS);

and the substituted cationic nitriles.

Other ingredients

Other materials that may be present in detergent compositions of the invention include sodium silicate; antiredeposition agents such as cellulosic polymers; fluorescers; inorganic salts such as sodium sulphate; lather control agents or lather boosters as appropriate; pigments; and perfumes. This list is not intended to be exhaustive.

Bulk density

The particulate detergent compositions of the invention have a bulk density of at least 700 g/l, and preferably at least 800 g/l.

Preparation of the detergent compositions

The particulate detergent compositions of the invention may be prepared by any method suitable for the production of high bulk density powders.

One suitable method comprises spray-drying a slurry of compatible heat-insensitive ingredients, including the zeolite MAP, any other builders, and at least part of the detergent-active compounds: densifying the resulting base powder in a batch or continuous high-speed mixer/granulator; and then spraying on or postdosing those ingredients unsuitable for processing via the slurry, including the peroxy bleach compound and bleach precursor.

In another method, especially preferred, the spray-drying step can be omitted altogether, the high bulk density base powder being prepared directly from its constituent raw materials, by mixing and granulating in a high-speed mixer/granulator, and then postdosing bleach and other ingredients as in the spray-drying/post-tower densification route.

Processes using high-speed mixer/granulators are disclosed, for example, in EP 340 013A, EP 367 339A, EP 390 251A and EP 420 317A (Unilever).

EXAMPLES

The invention is further illustrated by the following Examples, in which parts and percentages are by weight unless otherwise indicated. Examples identified by numbers are in accordance with the invention, while those identified by letters are comparative.

The zeolite MAP used in the Examples was prepared by a method similar to that described in Examples 1 to 3 of EP 384 070A (Unilever). Its silicon to aluminium ratio was 1.07. Its particle size (d_{50}) as measured by the Malvern Mastersizer was 0.8 micrometres.

The zeolite A used was Wessalith (Trade Mark) P powder ex Degussa.

The anionic surfactant used was coconut alcohol sulphate (cocoPAS) ex Philippine Refining Co..

The nonionic surfactants used were Synperonic (Trade Mark) A7 and A3 ex ICI, which are C_{12} - C_{15} alcohols ethoxylated, respectively with an average of 7 and 3 moles of ethylene oxide.

Example 1, Comparative Example A

Detergent base powders were prepared to the formulations given below (in parts by weight), by mixing and granulating in a Fukae (Trade Mark) FS-30 batch high-speed mixer/granulator.

	1	A
CocoPAS	5.10	5.10
Nonionic surfactant 7EO	4.80	4.80
Nonionic surfactant 3EO	7.10	7.10
Zeolite 4A (as anhydrous*)	-	27.00
Zeolite MAP (as anhydrous*)	25.00	-
Sodium carbonate	-	15.00
SCMC	0.50	0.50
Fluorescer	0.21	0.21
Moisture (nominal)	6.25	6.75
	48.96	66.46
Bulk density (g/l)	808	816

*The zeolites were used in hydrated form, but the amounts are quoted in terms of anhydrous material, the water of hydration being included in the amount shown for total moisture.

The actual moisture contents of the base powders were determined by measuring weight loss after heating to 135 °C for 1 hour, and were found to be as follows:

Moisture (wt% _{1h})	8.6	6.5
-------------------------------	-----	-----

Thus the base powder containing zeolite MAP had a slightly higher moisture content. Powder samples were prepared by mixing 0.5 g of cholyl-4-sulphophenyl carbonate (CSPC) granules, with 9.5 g of each base powder.

The composition of the CSPC granules (in weight percent) was as follows:

CSPC (95 wt% active) material	61.03
succinic acid	6.34
fatty acid (Prifac 7901)	3.9
polyethylene glycol (molecular weight 1500)	26.23
silica coating	2.5

Each powder therefore contained 5 wt% of CSPC granules, equivalent to 2.90 wt% of CSPC itself.

The products were stored in open bottles at 28 °C and 70% relative humidity. Storage stabilities were assessed by removing samples at different time intervals and determining residual peracid by titrating with sodium thiosulphate on ice. Sodium perborate was added in the analysis to ensure complete generation of peracid from the CSPC.

The results, expressed as percentages of the initial value, were as follows:

Storage time (days)	1 (MAP)	A (4A)
0	100	100
7	100	87.9
14	100	41.6
28	100	41.7
56	99.3	26.3

Example 2, Comparative Example B

The procedure of Examples 1 and A was repeated using different storage conditions: sealed bottles at 37 °C. The powder of Example 2 had the same composition as the powder of Example 1, and the powder of Comparative Example B had the same composition as the powder of Comparative Example A.

The results were as follows:

Storage time (days)	2 (MAP)	B (4A)
0	100	100
7	100	100
14	97.4	45.8
28	100	30.0
56	66.2	18.4

Example 3, Comparative Example C

The procedure of Example 1 was repeated using powder samples containing an inorganic persalt, sodium perborate monohydrate, in addition to the CSPC granules.

Each sample contained 9.5 g (86.36 wt%) base powder, 0.5 g (4.55 wt%) CSPC granules, equivalent to 0.29 g (2.64 wt%) CSPC, and 1.0 g (9.09 wt%) sodium perborate monohydrate. The powder of Example 3 contained the base powder of Example 1, while the powder of Comparative Example C contained the base powder of Comparative Example A.

As in Example 1, storage was in open bottles at 28 °C and 70% relative humidity.

The results were as follows:

Storage time (days)	3 (MAP)	C (4A)
0	100	100
7	100	78.9
14	53.6	23.2
28	41.7	27.4

Example 4, Comparative Example D

The procedure of Examples 3 and C was repeated using different storage conditions: sealed bottles at 37 °C. The powder of Example 4 had the same composition as the powder of Example 3, and the powder of Comparative Example D had the same composition as the powder of Comparative Example C. The results were as follows:

Storage time (days)	4 (MAP)	D (4A)
0	100	100
7	69.7	47.3
14	69.7	26.0
28	35.2	3.0

In all these Examples better CSPC stability was exhibited in the zeolite-MAP-containing powder, despite its higher moisture content.

Example 5, Comparative Example E

Detergent powders were prepared to the formulations given below (in weight percent), by a non-tower process comprising mixing and granulating the surfactants and builders in a Lödige (Trade Mark) continuous high-speed mixer/granulator, and postdosing the remaining ingredients:

	5	E
CocoPAS	5.0	5.0
Nonionic surfactant 7EO	5.0	5.0
Nonionic surfactant 3EO	7.0	6.0
Soap	2.0	2.0
Zeolite 4A (as anhydrous)	-	27.6
Zeolite MAP (as anhydrous)	29.6	-
Sodium carbonate	8.0	11.0
Sodium disilicate	4.0	4.0
Sodium percarbonate	20.0	20.0
TAED granules	8.0	8.0
EDTMP (Dequest)	0.4	0.4
Antifoam granules	2.0	2.0
Enzyme granules	1.0	1.0
Moisture	8.0	8.0
	100.0	100.0
Bulk density (g/l)	870	870

The TAED granules had a TAED content of 83 wt%, the remaining ingredients being sodium sulphate (9.5 wt%), acrylic/maleic copolymer (2.3 wt%), clay (2.1 wt%) and water (2.5 wt%).

The sodium percarbonate was a coated material supplied by Kao Corporation (Japan), having a coating based on sodium metaborate and sodium metasilicate as described in GB 2 123 044B (Kao).

The products were stored in laminated packs at 37 °C and 70% relative humidity. Residual TAED was measured by titration (of peracetic acid) against sodium thiosulphate. The results were as follows:

Storage time (days)	5 (MAP)	E (4A)
0	100	100
28	79	70
42	70	56
56	60	44

Claims

- Use of zeolite P having a silicon to aluminium ratio not greater than 1.33 (zeolite MAP) to improve the stability of a bleach precursor in a particulate bleaching detergent composition having a bulk density of at least 700 g/l and comprising:
 - one or more detergent-active compounds,
 - one or more detergency builders including alkali metal aluminosilicate comprising zeolite MAP, and
 - a bleach system comprising a peroxy bleach compound and a bleach precursor.
- Use as claimed in claim 1, characterised in that the zeolite MAP has a silicon to aluminium ratio not greater than 1.07.
- Use as claimed in claim 1 or claim 2, characterised in that the bleach precursor is N,N,N',N'-tetraacetyl ethylenediamine.
- Use as claimed in claim 1 or claim 2, characterised in that the bleach precursor is a quaternary ammonium or phosphonium-substituted bleach precursor.
- Use as claimed in claim 4, characterised in that the bleach precursor is choly-4-sulphophenyl carbonate.



	5	E
CocoPAS	5.0	5.0
Nonionic surfactant 7EO	5.0	5.0
Nonionic surfactant 3EO	7.0	6.0
Soap	2.0	2.0
Zeolite 4A (as anhydrous)	-	27.6
Zeolite MAP (as anhydrous)	29.6	-
Sodium carbonate	8.0	11.0
Sodium disilicate	4.0	4.0
Sodium percarbonate	20.0	20.0
TAED granules	8.0	8.0
EDTMP (Dequest)	0.4	0.4
Antifoam granules	2.0	2.0
Enzyme granules	1.0	1.0
Moisture	8.0	8.0
	100.0	100.0
Bulk density (g/l)	870	870

The TAED granules had a TAED content of 83 wt%, the remaining ingredients being sodium sulphate (9.5 wt%), acrylic/maleic copolymer (2.3 wt%), clay (2.1 wt%) and water (2.5 wt%).

The sodium percarbonate was a coated material supplied by Kao Corporation (Japan), having a coating based on sodium metaborate and sodium metasilicate as described in GB 2 123 044B (Kao).

The products were stored in laminated packs at 37 °C and 70% relative humidity. Residual TAED was measured by titration (of peracetic acid) against sodium thiosulphate. The results were as follows:

Storage time (days)	5 (MAP)	E (4A)
0	100	100
28	79	70
42	70	56
56	60	44

Claims

- Use of zeolite P having a silicon to aluminium ratio not greater than 1.33 (zeolite MAP) to improve the stability of a bleach precursor in a particulate bleaching detergent composition having a bulk density of at least 700 g/l and comprising:
 - one or more detergent-active compounds,
 - one or more detergency builders including alkali metal aluminosilicate comprising zeolite MAP, and
 - a bleach system comprising a peroxy bleach compound and a bleach precursor.
- Use as claimed in claim 1, characterised in that the zeolite MAP has a silicon to aluminium ratio not greater than 1.07.
- Use as claimed in claim 1 or claim 2, characterised in that the bleach precursor is N,N,N',N'-tetraacetyl ethylenediamine.
- Use as claimed in claim 1 or claim 2, characterised in that the bleach precursor is a quaternary ammonium or phosphonium-substituted bleach precursor.
- Use as claimed in claim 4, characterised in that the bleach precursor is cholyl-4-sulphophenyl carbonate.



6. Use as claimed in any preceding claim, characterised in that the peroxy bleach compound is sodium perborate monohydrate or sodium percarbonate.
7. Use as claimed in any preceding claim, characterised in that the zeolite MAP has a particle size distribution such that 50 wt% of its particles have a diameter smaller than a figure d_{50} which lies within the range of from 0.1 to 5.0 micrometres.
8. Use as claimed in any preceding claim, characterised in that the detergent composition is substantially free of zeolite A.
9. Use as claimed in any preceding claim, characterised in that the composition comprises:
 - (a) from 5 to 60 wt% of one or more detergent-active compounds,
 - (b) from 10 to 80 wt% of one or more detergency builders comprising zeolite MAP,
 - (c) a bleach system comprising from 5 to 35 wt% of a peroxy bleach compound and from 1 to 8 wt% of a bleach precursor,
 - (d) optionally other detergent ingredients to 100 wt%, all percentages being based on the detergent composition.
10. Use as claimed in any preceding claim, characterised in that the detergent composition has a bulk density of at least 800 g/l.
11. A particulate bleaching detergent composition comprising:
 - (a) one or more detergent-active compounds,
 - (b) one or more detergency builders including alkali metal aluminosilicate comprising zeolite P having a silicon to aluminium ratio not greater than 1.33 (zeolite MAP), and
 - (c) a bleach system comprising a peroxy bleach compound other than sodium perborate monohydrate and a bleach precursor, characterised in that the composition has a bulk density of at least 700 g/l.
12. A detergent composition as claimed in claim 11, wherein the peroxy bleach compound is sodium percarbonate.

Patentansprüche

1. Verwendung von Zeolith P mit einem Silicium-zu-Aluminium-Verhältnis von nicht mehr als 1,33 (Zeolith MAP) zur Verbesserung der Stabilität einer Bleichmittelvorstufe in einem teilchenförmigen bleichenden Waschmittel mit einer Schüttdichte von mindestens 700 g/l und umfassend:
 - (a) einen oder mehrere Waschmittelaktivstoffe,
 - (b) einen oder mehrere Waschmittelbuilder, einschließlich Alkalimetallaluminosilicat, umfassend Zeolith MAP, und
 - (c) ein Bleichmittelsystem, umfassend eine Peroxybleichmittelverbindung und eine Bleichmittelvorstufe.
2. Verwendung nach Anspruch 1, dadurch gekennzeichnet, daß der Zeolith MAP ein Silicium-zu-Aluminium-Verhältnis von nicht mehr als 1,07 aufweist.
3. Verwendung nach Anspruch 1 oder Anspruch 2, dadurch gekennzeichnet, daß die Bleichmittelvorstufe N,N,N',N'-Tetraacetylenylendiamin ist.
4. Verwendung nach Anspruch 1 oder Anspruch 2, dadurch gekennzeichnet, daß die Bleichmittelvorstufe eine quaternäre Ammonium- oder Phosphonium- substituierte Bleichmittelvorstufe ist.
5. Verwendung nach Anspruch 4, dadurch gekennzeichnet, daß die Bleichmittelvorstufe Cholyl-4-sulfophenylcarbonat ist.
6. Verwendung nach einem vorangehenden Anspruch, dadurch gekennzeichnet, daß die Bleichmittelvorstufe Natriumperboratmonohydrat oder Natriumpercarbonat ist.



7. Verwendung nach einem vorangehenden Anspruch, dadurch gekennzeichnet, daß der Zeolith MAP eine solche Teilchengrößenverteilung aufweist, daß 50 Gew.-% seiner Teilchen einen Durchmesser kleiner als einen d_{50} -Wert aufweisen, der in einem Bereich von 0,1 bis 5,0 μm liegt.
- 5 8. Verwendung nach einem vorangehenden Anspruch, dadurch gekennzeichnet, daß das Waschmittel im wesentlichen frei von Zeolith A ist.
9. Verwendung nach einem vorangehenden Anspruch, dadurch gekennzeichnet, daß das Mittel umfaßt:
 - (a) 5 bis 60 Gew.-% von einem oder mehreren Waschmittelaktivstoffen,
 - 10 (b) 10 bis 80 Gew.-% von einem oder mehreren Waschmittelbuildern, umfassend Zeolith MAP,
 - (c) ein Bleichmittelsystem, umfassend 5 bis 35 Gew.-% einer Peroxybleichmittelverbindung und 1 bis 8 Gew.-% einer Bleichmittelvorstufe,
 - (d) gegebenenfalls andere Waschmittelbestandteile bis 100 Gew.-%,
 - alle Prozentangaben sind auf das Gewicht des Waschmittels bezogen.
- 15 10. Verwendung nach einem vorangehenden Anspruch, dadurch gekennzeichnet, daß das Waschmittel eine Schüttdichte von mindestens 800 g/l aufweist.
11. Teilchenförmiges bleichendes Waschmittel, umfassend:
 - 20 (a) einen oder mehrere Waschmittelaktivstoffe,
 - (b) einen oder mehrere Waschmittelbuilder, einschließlich Alkalimetallaluminosilicat, umfassend Zeolith P mit einem Silicium-zu-Aluminium-Verhältnis von nicht mehr als 1,33 (Zeolith MAP), und
 - (c) ein Bleichmittelsystem, umfassend eine Peroxybleichmittelverbindung, die von Natriumperboratmonohydrat verschieden ist, und eine Bleichmittelvorstufe,
 - 25 dadurch gekennzeichnet, daß das Mittel eine Schüttdichte von mindestens 700 g/l aufweist.
12. Waschmittel nach Anspruch 11, wobei die Peroxybleichmittelverbindung Natriumpercarbonat ist.

Revendications

- 30 1. Utilisation de zéolite P ayant un rapport silicium:aluminium ne dépassant pas 1,33 (zéolite MAP) pour améliorer la stabilité d'un précurseur de blanchiment dans une composition détergente de blanchiment particulière ayant une densité apparente d'au moins 700 g/l et comprenant :
 - (a) un (ou plusieurs) composant actif détergent,
 - 35 (b) un (ou plusieurs) adjuvant de détergence dont un aluminosilicate de métal alcalin comprenant la zéolite MAP, et
 - (c) un système de blanchiment comprenant un composé de blanchiment peroxy et un précurseur de blanchiment.
- 40 2. Utilisation selon la revendication 1, caractérisée en ce que la zéolite MAP présente un rapport silicium:aluminium qui ne dépasse pas 1,07.
3. Utilisation selon la revendication 1 ou 2, caractérisée en ce que le précurseur de blanchiment est la N,N,N',N'-tetraacétyl-éthylènediamine.
- 45 4. Utilisation selon la revendication 1 ou 2, caractérisée en ce que le précurseur de blanchiment est un précurseur de blanchiment à substitution ammonium quaternaire ou phosphonium.
5. Utilisation selon la revendication 4, caractérisée en ce que le précurseur de blanchiment est le carbonate de cholesteryl-4-sulfophényle.
- 50 6. Utilisation selon l'une quelconque des revendications précédentes, caractérisée en ce que le composé de blanchiment peroxy est le perborate de sodium monohydraté ou le percarbonate de sodium.
- 55 7. Utilisation selon l'une quelconque des revendications précédentes, caractérisée en ce que la zéolite MAP présente une distribution granulométrique telle que 50% en poids de ses particules ont un diamètre plus petit qu'une valeur d_{50} qui se situe dans la gamme allant de 0,1 à 5,0 μm .



8. Utilisation selon l'une quelconque des revendications précédentes, caractérisée en ce que la composition détergente est sensiblement exempte de zéolite A.
9. Utilisation selon l'une quelconque des revendications précédentes, caractérisée en ce que la composition comprend :
- (a) de 5 à 60% en poids d'un (ou plusieurs) composé détergent actif,
 - (b) de 10 à 80% en poids d'un (ou plusieurs) adjuvant de détergence comprenant une zéolite MAP,
 - (c) un système de blanchiment comprenant de 5 à 35% en poids d'un composé de blanchiment peroxy et de 1 à 8% en poids d'un précurseur de blanchiment,
 - (d) facultativement, d'autres ingrédients détergents q.s.p 100%,
- tous les pourcentages étant par rapport à la composition détergente.
10. Utilisation selon l'une quelconque des revendications précédentes, caractérisée en ce que la composition détergente présente une densité apparente d'au moins 800 g/l.
11. Composition détergente de blanchiment particulière comprenant :
- (a) un (ou plusieurs) composé détergent actif,
 - (b) un (ou plusieurs) adjuvant de détergence dont un aluminosilicate de métal alcalin comprenant la zéolite P ayant un rapport silicium:aluminium qui ne dépasse pas 1,33 (zéolite MAP), et
 - (c) un système de blanchiment comprenant un composé de blanchiment peroxy autre que le perborate de sodium monohydraté et un précurseur de blanchiment,
- caractérisée en ce que la composition présente une densité apparente d'au moins 700 g/l.
12. Composition détergente selon la revendication 11, dans laquelle le composé de blanchiment peroxy est un percarbonate de sodium.