

GAS GENERATOR

BACKGROUND OF THE INVENTION

1. Field of the invention

5 The present invention relates to a gas generator, and more particularly, to a gas generator which can provide the function of filtering and humidification, and reduces the consumption of the electrolyte.

2. Description of the prior art

10 As people have always been paying much attention on health developments, many developments in medical technology are often targeted on treating diseases and prolonging human life. Also, most of the treatments in the past are passive, which means that the disease is treated only when it occurs, and the treatments may include an operation, a medication treatment, a radiation therapy, or a medical treatment for cancer. However, in recent years, most of the medical experts' researches are gradually moving towards preventive medical methods, such as research on healthy
15 food, screening and the prevention of inherited diseases, which actively prevents diseases from occurring in the future. Due to the focus of the prolongation of human life, many anti-aging and anti-oxidation technologies including skin care products and anti-oxidation food/medicine are gradually being developed and are becoming increasingly popular to the general public.

20 Studies have found that there are instable oxygen species (O^+), also known as free radicals, in the human body. The free radicals are usually generated due to diseases, diet, and environment. And, one's lifestyle can be excreted in the form of water by reacting with the inhaled hydrogen. With this method, the amount of free radicals in the human body can be reduced, thereby restoring the body condition
25 from an acidic state to an alkaline state, to achieve an anti-oxidation, anti-aging and

beauty health effect, and even to eliminate chronic diseases. Furthermore, there are also clinical experiments showing that patients who need to inhale a high concentration of oxygen for an extended period of time would experience lung damage. However, it could be ameliorated by inhaling hydrogen.

5 General electrolysis device generates high temperature in the electrolyzing process, which will decrease the efficiency of electrolyzing and cause energy consumption problems; furthermore, the hydrogen-oxygen mixed gas becomes unsuitable for the user to inhale. Although the problems mentioned above can be solved through replenishing supplementary water or the electrolyte continuously, it
10 also makes the operation of the electrolysis device inconvenient.

SUMMARY OF THE INVENTION

Therefore, the present inventor with many years engaged in the manufacture and development of related products and design experience went through the detailed design and careful assessment to finally confirm that the present invention is
15 practically usable.

The present invention provides a gas generator for electrolyzing water and generating the hydrogen-oxygen mixed gas, meanwhile the electrolyte in the hydrogen-oxygen mixed gas is condensed and filtered. The gas is humidified to reduce the amount of the electrolyte in the hydrogen-oxygen mixed gas to make it be
20 able to be inhaled by the user. Moreover, by replenishing the supplementary water and flushing the electrolyte back into the electrolysis device to restore the filtering function of the circulating passageway. It can not only avoid the block and corrosion in the circulating passageway but also reduce the consumption of the electrolyte.

The present invention provides a gas generator comprising the water tank, the
25 electrolysis device, the condensate filter, the humidification device and the pump device. The water tank accommodates electrolyzed water, wherein the electrolyzed water comprises electrolyte. The electrolysis device is coupled to the water tank for

electrolyzing the electrolyzed water to generate a hydrogen-oxygen mixed gas. The condensate filter is connected to the electrolysis device for condensing the hydrogen-oxygen mixed gas generated at the electrolysis device and filtering the electrolyte in the hydrogen-oxygen mixed gas for generating the filtered hydrogen-oxygen mixed gas. The humidification device connected to the condensate filter accommodates the supplementary water for humidifying the filtered hydrogen-oxygen mixed gas. The pump device is connected to the water tank for generating negative pressure in the water tank in order to pump back the supplementary water from the humidification device through the condensate filter into the water tank, and the electrolyte adsorbed in the condensate filter is back flushed to the water tank. When the flow rate of generating the hydrogen-oxygen mixed gas by the gas generator is 600L/hr after operating 40 to 60 hours, the loss of the electrolyte is equal to or less than 5g.

Furthermore, the present invention provides a gas generator which selectively comprises an atomized gas mixing tank. The atomized gas mixing tank comprises a gas outlet. The water tank and the atomized gas mixing tank are connected to the by the pump device. When the pump device is in operation, the gas in the water tank is pumped out through the gas outlet of the atomized gas mixing tank to generate a negative pressure in the water tank.

The atomized gas mixing tank is selectively connected to the humidification device for receiving a humidified hydrogen-oxygen mixed gas. The atomized gas mixing tank generates an atomized gas mixed with the humidified hydrogen-oxygen mixed gas to generate a healthy gas for a user to inhale. The atomized gas comprises at least one of water vapor, atomized liquid, volatile purified oils or combinations thereof.

The humidification device selectively comprises at least an output tube. The output tube comprises a plurality of holes. The hydrogen-oxygen mixed gas is pumped out from the plurality of holes of the output tube to humidify the filtered hydrogen-oxygen mixed gas °

The condensate filter selectively comprises a plurality of the condensate plates.

Every condensate plate comprises a passageway. The passageway of the condensate plate is connected to the passageway of the adjacent condensate plate to form a circulating passageway for circulating the hydrogen-oxygen mixed gas.

Furthermore, the present invention further provides a gas generator which
5 comprises a water tank, an electrolysis device, a condensate filter, a humidification filter, a humidification device and a pump device. The water tank accommodates electrolyzed water. The electrolyzed water comprises an electrolyte. The electrolysis device is coupled to the water tank for electrolyzing electrolyzed water to generate a hydrogen-oxygen mixed gas. The humidification filter connected to the condensate
10 filter accommodates water and filter the filtered hydrogen-oxygen mixed gas which is filtered by the condensate filter. The humidification device is connected to the humidification filter accommodates a supplementary water for humidifying the hydrogen-oxygen mixed gas filtered by the humidification filter. The pump device is connected to the water tank for generating a negative pressure in the water tank to
15 pump back the supplementary water from the humidification device through the humidification filter and the condensate filter into the water tank and back flush the electrolyte adsorbed in the condensate filter. When the flow rate of generating the hydrogen-oxygen mixed gas by the gas generator is 600L/hr after operating 40 to 60 hours, the loss of the electrolyte is equal to or less than 5g.

20 In conclusion, the present invention is to provide a gas generator. The hydrogen-oxygen mixed gas is generated by the electrolysis device of the gas generator of the present invention. The hydrogen-oxygen mixed gas is condensed and filtered out the electrolyte through the condensate filter. The gas is humidified to reduce the amount of the electrolyte in the hydrogen-oxygen mixed gas to be inhaled
25 by the user. In another embodiment, the gas generator can further comprise the humidification filter which is configured between the condensate filter and the humidification device for filtering out the impurities in the hydrogen-oxygen mixed gas to provide a better hydrogen-oxygen mixed gas for the user to inhale. Moreover, by replenishing the supplementary water and back flushing the electrolyte into the

electrolysis device to restore the filtering function of the circulating passageway, it can not only avoid the block and corrosion in the passageway but also reduce the consumption of the electrolyte.

5 The advantages and spirits of the invention may be understood by the following recitations together with the appended drawings.

BRIEF DESCRIPTION OF THE APPENDED DRAWINGS

Some of the embodiments will be described in detail, with reference to the following figures, wherein like designations denote like members, wherein:

10 FIG. 1A and FIG. 1B are the diagrams which show a gas generator of the present invention in different angels.

FIG. 2A, FIG. 2B and FIG. 2C are the diagrams which show the gas generator of the present invention in an embodiment in different angels.

15 FIG. 3A, FIG. 3B and FIG. 3C are the diagrams which show the embodiment of FIG. 2A without the external shell of the water tank, the top cover of the water tank, the structure of the humidification device and the external tube of the humidification device in different angels.

FIG. 4A and FIG. 4B are the diagrams which show the embodiment of FIG. 3A without the water tank in the different angels.

20 FIG. 5A and FIG. 5B are the plan view and the sectional view through the A-A line which show the embodiment of FIG. 2A only with the condensate filter and the cover of the water tank.

FIG. 6A and FIG. 6B are the diagrams which show the gas generator of the present invention in another embodiment only with the combination of the condensate filter and the cover of the water tank in different angels.

25 FIG. 7 is a diagram shows the combination of the condensate filter and the cover of the water tank shown in FIG. 6 without the cover of the water tank.

FIG. 8 is a diagram shows the combination of the condensate filter and the cover of the water tank shown in FIG. 6 without the cover of the water tank in FIG. 7 without the filter net.

FIG. 9 is a diagram shows the combination of the condensate filter and the cover of the water tank shown in FIG. 6 without the cover of the water tank in FIG. 7 without the filter net in FIG. 8 without the filter net cover.

FIG. 10A and FIG. 10B are the plan view and the sectional view through the B-B line which show the condensate filter of the gas generator of FIG. 6A.

FIG. 11 is the diagram which shows the humidification device of the gas generator of the present invention in another embodiment.

FIG. 12 is the diagram which shows the gas generator of the present invention in another embodiment.

The advantages, sprits, and features of the present invention will be explained and discussed with embodiments and figures as following.

DETAILED DESCRIPTION OF THE INVENTION

A detailed description of the hereinafter described embodiments of the disclosed apparatus and method are presented herein by way of exemplification and not limitation with reference to the Figures. Although certain embodiments are shown and described in detail, it should be understood that various changes and modifications may be made without departing from the scope of the appended claims. The scope of the present invention will in no way be limited to the number of constituting components, the materials thereof, the shapes thereof, the relative arrangement thereof, etc., and are disclosed simply as an example of embodiments of the present invention.

Please refer to FIG.1A to FIG. 3C. FIG. 1A and FIG. 1B are the diagrams which show a gas generator of the present invention in different angels. FIG. 2A,

FIG. 2B and FIG. 2C are the diagrams which show the gas generator of the present invention in an embodiment in different angels. FIG. 3A, FIG. 3B and FIG. 3C are the diagrams which show the embodiment of FIG. 2A without the external shell of the water tank, the top cover of the water tank, the structure of the humidification device and the external tube of the humidification device in different angels. The gas generator **1** of the present invention comprises the water tank **2**, the electrolysis device **3** which is not shown in FIG. 1A and FIG. 1B but in the FIG. 4A and FIG. 4B, the atomized gas mixing tank **4**, the pump device **5** which is not shown in FIG. 1A and FIG. 1B but in FIG. 2B and FIG. 4B, the condensate filter **6**, the cooling device **7** and the humidification device **9**.

The water tank **2** accommodates electrolyzed water, wherein the electrolyzed water comprises an electrolyte. The electrolysis device **3** is coupled to the water tank **2** for electrolyzing the electrolyzed water to generate a hydrogen-oxygen mixed gas. The condensate filter **6** is connected to the electrolysis device **3** for receiving and condensing the hydrogen-oxygen mixed gas generated by the electrolysis device **3**. Then, the condensate filter filters the electrolyte in the hydrogen-oxygen mixed gas to generate the filtered hydrogen-oxygen mixed gas. The humidification device **9** receives and humidifies the filtered hydrogen-oxygen mixed gas. The humidification device **9** accommodates the supplementary water and is connected to the first hollow portion **20** of the water tank **2**. The pump device **5** is connected to the first hollow portion **20** of the water tank **2**. When the pump device is in operation, the gas in the first hollow portion **20** of the water tank **2** is pumped out by the pump device **5** for generating a negative pressure in the water tank **2**. The humidification device **9** back flush the supplementary water into the condensate filter **6** and fills the supplementary water into the water tank **2** by the negative pressure to reduces the loss of the electrolyte. Wherein the flow rate of the hydrogen-oxygen mixed gas is 120L/hr and the loss of the electrolyte is less than 50g for 2000 to 3000 hours in operation. That is to say, it is expected that the flow rate of hydrogen-oxygen mixed gas generated by the gas generator is 600L/hr and the loss of the electrolyte is equal to or less than 5g for 40 to 60 hours in operation. The cooling device **7** is set on the cover of the water

tank **2** and connected to the water tank for cooling the electrolyzed water which generates the hydrogen-oxygen mixed gas. The sentences below illustrate every design of every element of the present invention.

Please refer to FIG. 5A and FIG. 5B; FIG. 5A and FIG. 5B are the plan view
5 and the sectional view through the A-A line which show the embodiment of FIG. 2A only with the condensate filter and the cover of the water tank. FIG. 6A and FIG. 6B are the diagrams which show the gas generator of the present invention in another embodiment only with the combination of the condensate filter and the cover of the water tank in different angels. The water tank **2** comprises a first hollow portion **20**.
10 The first hollow portion **20** of the water tank **2** accommodates electrolyzed water. The electrolyzed water comprises an electrolyte. The electrolyte in this embodiment is NaOH, but in practice the electrolyte is not limited to it. In practice, the electrolyte can be CaCO₃, NaCl or edible NaOH. The water tank **2** further comprises a tube **22**, a water tank **24** and a cover of the water tank **26**. The inner space of the water tank
15 **24** is the first hollow portion **20**. The tube **22** can be set on the cover of the water tank **26** for being connected to the condensate filter **6** and the water tank **2** for outputting the hydrogen-oxygen mixed gas generated by the electrolysis device **3** and pumping the electrolyzed water into water tank **2**. The cover of the water tank **26** comprises a plurality of the cover holes which are connected to the first hollow
20 portion **20** of the water tank **2** for the electrode columns **33** of the electrolysis device **3** (shown in FIG. 4A) to be configured in by penetrating through the cover holes. Besides, the plurality of the cover holes are also available for detecting devices, such as flow rate detector, water level gauge and security valve to be configured in by penetrating through the cover holes.

25 Please refer to FIG. 4A and FIG. 4B; FIG. 4A and FIG. 4B are the diagrams which show the embodiment of FIG. 3A without the water tank in the different angels. The electrolysis device **3** comprises an electrolyze tank **32**, a plurality of electrodes which are not shown in the figures, the backing board **36**, the upper cover **37** and the lower cover **38**. Wherein the plurality of electrodes is able to be set

separately in the electrolyze tank **32** to form a passageway with the plurality of electrodes. The bottom of the electrolyze tank has a plurality of lower holes. The backing board **36** is set on the upper surface of the every electrode. The backing board has a plurality of upper holes. The upper cover **37** is set on the backing board
5 **36** corresponding to another side of the electrolyze tank **32**. The upper cover **37** is able to comprise at least a first passageway **370**. The pluralities of upper holes of backing board **36** are connected to the first hollow portion **20** by at least a first passageway **370** of the upper cover **37**. The lower cover **38** is set on the lower surface of the electrolyze tank **32** corresponding to another side of the upper cover **37**.
10 The lower cover **38** comprises at least a second passageway **380**. The plurality of lower holes set on the bottom of the electrolyze tank **32** are connected to the first hollow portion **20** by at least a second passageway **380** of the lower cover **38**.

Please refer to FIG. 5A to FIG. 10B; FIG. 7 is a diagram shows the combination of the condensate filter and the cover of the water tank shown in FIG. 6
15 without the cover of the water tank. FIG. 8 is a diagram shows the combination of the condensate filter and the cover of the water tank shown in FIG. 6 without the cover of the water tank in FIG. 7 without the filter net. FIG. 9 is a diagram shows the combination of the condensate filter and the cover of the water tank shown in FIG. 6 without the cover of the water tank in FIG. 7 without the filter net in FIG. 8 without
20 the filter net cover. FIG. 10A and FIG. 10B are the plan view and the sectional view through the B-B line which show the condensate filter of the gas generator of FIG. 6A. The condensate filter **6** comprises a gas inlet hole **60** and a gas outlet hole **62**. The gas inlet hole **60** can be connected to the electrolysis device **3** for receiving the hydrogen-oxygen mixed gas. The gas outlet hole **62** can output the filtered hydrogen-
25 oxygen mixed gas. Moreover, the condensate filter **6** comprises a plurality of condensate plate **64**. Every condensate plate **64** comprises a passageway **640a**. The passageway **640a** of the condensate plate **64** is connected to the passageway **640a** of the adjacent condensate plate **64** to form a circulating passageway **640** for circulating the hydrogen-oxygen mixed gas and condensing the hydrogen-oxygen mixed gas.
30 The gas inlet hole **60** is connected to the gas outlet hole **62** by the circulating

passageway **640**.

In one embodiment, the passageway **640a** of the condensate plate **64** is a combination of a diverging passageway **642** and a connecting passageway **644**. Please refer to FIG. 5B and FIG. 10B. The diverging passageway **642** is a
5 passageway has the diverging cross section which is not limited to the diverging passageway **642** shown in FIG. 5B and FIG. 10B. In practice, the shape of the cross section of the diverging passageway can be the half-circle, the triangle or the ladder shape. The diverging passageway **642** has a relatively broad terminal and a relatively narrow terminal. The relatively broad terminal and the relatively narrow terminal of
10 the diverging passageway **642** have an opening. The connecting passageway **644** comprises a passageway and two corresponding openings. The two corresponding openings of the connecting passageway **644** can be connected to each other by the passageway. In one embodiment, when the diverging passageway **642** is connected to the connecting passageway **644**, the diverging passageway **642** is connected to the
15 connecting passageway **644** by the relatively broad opening connected to the opening of the connecting passageway **644**. The design of the structure of the passageway **640a** of the condensate plate **64** makes the horizon passageway (which is the diverging passageway **642**) be connected to the vertical passageway (which is the connecting passageway **644**). The horizon passageway is not limited to the
20 passageway with diverging cross section. In practice, the horizon passageway can be the same cross section of the passageway. Moreover, when the passageway **640a** of the condensate plat **64** is connected to the passageway **640a** of the adjacent condensate plate **64**, the two passageways **640a** are connected by the relatively narrow opening of the diverging passageway **642** with the opening of the connecting
25 passageway **644** of the adjacent condensate plate **64**. Therefore, the design of the structure of the passageway **640a** of the condensate plate **64** makes the passageway **640a** of the condensate plate **64** be connected to the passageway **640a** of the adjacent condensate plate **64** to form a circulating passageway **640** for circulating the hydrogen-oxygen mixed gas. That is to say, in the embodiment, the connecting
30 method of the condensate plate and the adjacent condensate plate enables the

hydrogen-oxygen mixed gas pass through a longer condensation-filtering route to get a better efficient of condensing and filtering. Moreover, in one embodiment, an activated carbon fiber is coupled to the passageway **640a** for filtering the electrolyte in the hydrogen-oxygen mixed gas. The filter material comprising the ceramics, the quartz, the diatomaceous earth, the meerschaum or any combinations thereof is coupled to the passageway **640a**. The filter material further filters the electrolyte in the hydrogen-oxygen mixed gas. Besides, in one embodiment, the gas inlet hole **60** of the present invention comprises a filter net **600** and a filter net cover **602**. The filter net **600** is connected to the filter net cover **602** at the electrolysis device **3** for receiving and filtering the hydrogen-oxygen mixed gas.

In one embodiment, the circulating passageway **640** can achieve the condensing effect by the two sets of passageways **640a**, which simplifies the design of the condensate filter **6** and reduces the cost. However, the invention is not limited thereto and the amount of the passageways can be adjusted according to the design requirement.

Please refer to FIG. 2C and FIG. 11. FIG.11 shows the humidification device of the gas generator of the present invention in another embodiment. The humidification device **9** comprises a hollow main body **90**, a first tube **92**, at least an output tube **94**, a third tube **96**, and a fourth tube **98**. The hollow main body **90** can accommodate supplementary water. The second tube **92** is set on the hollow main body **90** for connecting the electrolysis device **3**. At least an output tube **94** is coupled to the hollow main body **90** and connected to the second tube **92**. The second tube **92** is connected to two output tubes **94** to form a T-shape. In practice, the present invention is not limited thereto, and the connection of the second tube to at least one output tube **94** can be adjusted according to the design requirement.

Moreover, the surface of two output tubes **94** comprises a plurality of holes. In one embodiment, the diameter of the holes ranges from 2nm to 3nm for refining the gas to form easily-dissolved fine bubbles. In practice, the invention is not limited thereto, and the diameter of the holes is adjustable according to the requirement of

the user. Two rubber plugs are respectively set on the terminal of two output tubes **94** connected to the second tube **92** for outputting the hydrogen-oxygen mixed gas in the second tube **92** by the pluralities of nano-holes on the output tube **94** into the hollow main body **90**. In practice, the present invention is not limited thereto, and the terminal of two output tubes **94** connected to the second tube **92** can be designed as closed face.

The third tube **96** can be set on the hollow main body **90** for replenishing the supplementary water W2. In practice, the third tube can be connected to a pilot hole. The hydrogen water is output through the pilot hole by the third tube or input into the supplementary water. The fourth tube **98** can be set on the hollow main body **90** for outputting the humidified hydrogen-oxygen mixed gas.

Please refer to FIG. 3B and FIG. 4A. The pump device **5** can be set on the water tank cover **26** and be connected to the first hollow portion **20** of the water tank **2** for taking out the gas in the water tank **2** to generate a negative pressure to input the supplementary water from the humidification device **9** to the water tank and back flush the electrolyte in the condensate filter **6** into the first hollow portion **20** of the water tank **2**.

Please refer to FIG. 3B and FIG. 4. The atomized gas mixing tank **4** can be connected to the humidification device **9** for receiving the humidified hydrogen-oxygen mixed gas. The atomized gas mixing tank can generate the atomized gas, wherein the atomized gas comprises at least one of the water vapor, the atomized liquid, the volatile purified oils and combinations thereof. The atomized gas mixing tank can mix the atomized gas and the humidified hydrogen-oxygen mixed gas to form the healthy gas for user to inhale. Furthermore, the atomized gas mixing tank **4** can comprise a gas outlet **40**. The design of the gas outlet is not limited to the diagram shown in FIG.4A in practice. The gas outlet can be the gas outlet tube, and the gas outlet is according to the requirement of the user. The gas outlet **40** of the atomized gas mixing tank **4** and the pump device **5** is connected to each other. In one embodiment, when the electrolysis device **3** stops electrolyzing electrolyzed water

for generating the hydrogen-oxygen mixed gas, the pump device starts to operate. The pump device **5** pumps out the gas in the water tank and output the gas from the gas outlet **40** of the atomized gas mixing tank **4** to generate a negative pressure in the water tank to input the supplementary water from the humidification device into the water tank and back flush the electrolyte absorbed in the condensate filter into the water tank.

The sentences mentioned above elaborate every design of every element; hereafter, the sentences mentioned below elaborate every method of combination and every application.

In the electrolysis device **3**, there are a plurality of electrodes set on the electrolyze tank **32**, the backing board **36** is set on the surface of every electrode, the upper cover **37** is covered on another terminal of backing board **36** corresponding to the electrolyze tank **32**, and the lower cover **38** is covered on the lower surface of the electrolyze tank **32** corresponding to another terminal of the upper cover **37**.

In the water tank **2** and the electrolysis device **3**, the anode plate and the cathode plate of the electrolysis device **3** are respectively fixed on the water tank cover **26** by two electrode columns **33**. When the water tank **24** combined with the water tank cover **26**, the electrolysis device **3** can be fixed and hung in the water tank **2**. Wherein, the water tank **2** and the electrolysis device **3** are connected to each other. The detecting device, such as the flow rate detector **F**, is penetrated through the plurality of cover holes **261** and configured on the water tank cover **26**.

In the water tank **2**, the electrolysis device **3** and the condensate filter **6**, the water tank **2** which has electrolysis device **3** is connected to the condensate filter **6** by the tube **22** of the water tank **2** and the gas inlet hole **60** of the condensate filter **6**. Then, the condensate filter **6** which is connected to the water tank is connected to the humidification device **9** by the connection between the gas outlet hole **60** of the condensate filter **6** and the second tube **92** of the humidification device **9**. Moreover, the atomized gas mixing tank **4** can be connected to the fourth tube **98** of the humidification device **9**.

In practice, the water tank **2** accommodates an electrolyzed water **W**, the electrolysis device **3** is coupled to the water tank **2** for electrolyzing the electrolyzed water **W** to generate a hydrogen-oxygen mixed gas. The hydrogen-oxygen mixed gas generated at the passageway of the electrode is input into the first hollow portion **20** by the upper hole on the backing board **36** and the first passageway **370** of the upper cover **37**. The hydrogen-oxygen mixed gas which is input into the first hollow portion **20** is output through the tube **22** of the water tank **2**. The hydrogen-oxygen mixed gas output from the tube **22** of the water tank **2** is input into the condensate filter **6** through the gas inlet hole **60** of the condensate filter **6** to condense and filter. The hydrogen-oxygen mixed gas which is went through the gas inlet hole **60** of the condensate filter **6** is wen t through the filter net **600** and the filter net cover **602** first to initially filter. Then the initially filtered hydrogen-oxygen mixed gas is input into the circulating passageway **640** to do the condensation. At the same time, the hydrogen-oxygen mixed gas is filtered by the activated carbon fiber coupled to the passageway **640a**, and the hydrogen-oxygen mixed gas makes the electrolyte be adsorbed in the circulating passageway **640a**. Then the filtered hydrogen-oxygen mixed gas is output by the gas outlet hole **62** of the condensate filter **6**.

Moreover, the filtered hydrogen-oxygen mixed gas is passed into the humidification device **9** by the second tube **92** which is connected to the gas outlet hole **62**. The filtered hydrogen-oxygen mixed gas received by the second tube **92** is input into the hollow main body **90** by the pluralities of nano-holes of two output tubes **94**. In practice, because there are pluralities of nano-holes on the surface of the output tube **94**, the hydrogen-oxygen mixed gas in the humidification device is able to be small to form the dissolvable small gas bubbles. After the filtered hydrogen-oxygen mixed gas is humidified by the humidification device, the electrolyte in the hydrogen-oxygen mixed gas become lower for users to use safely when the electrolyte is dissolved in the water. The humidified hydrogen-oxygen mixed gas which is output by the humidification device **9** is provided for the user to inhale. In real practice, the present invention is not limited thereto, and the humidified hydrogen-oxygen mixed gas which is output by the humidification device **9** can be

mixed with the atomized gas generated by the atomized gas mixing tank **4** to form a healthy gas for the user to inhale.

Moreover, when the electrolysis device **3** stops electrolyzing the electrolyzed water for generating the hydrogen-oxygen mixed gas, the pump device can pump out
5 the gas in the water tank **2** to generate a negative pressure. The supplementary water recharged by the third tube **96** can be input from the humidification device **9** into the water tank **2** which has electrolysis device **3** by the negative pressure mentioned above. More particularly, the supplementary water is input from the humidification
10 device **9** into the condensate filter **6** by the connection between the second tube **92** of the humidification device **9** and the gas outlet hole **62** of the condensate filter **6**. Moreover, the electrolyte adsorbed in the circulating passageway **640** of the condensate filter **6** can be flushed back into the water tank **2** of the electrolysis device **3** with the supplementary water through the gas inlet hole **60** and the tube **22** for restoring the filtering function of the circulating passageway. It can not only avoid
15 the block and corrosion in the circulating passageway **640** but also reduce the consumption of the electrolyte. In one embodiment, after the hydrogen-oxygen mixed gas generated by the gas generator generated under 120L/hr for 2000 hours to 3000 hours, the loss of the electrolyte is equal to or less than 50g and the present invention is not limited thereto. In practice, after the hydrogen-oxygen mixed gas
20 generated by the gas generator has generated under 600L/hr for 40 hours to 60 hours, the loss of the electrolyte is equal to or less than 5g.

In practice, the present invention uses the supplementary water to back flush the electrolyte into the water tank **2** of the electrolysis device **3** for providing the electrolysis device **3** with the electrolyzed water which is used for electrolyzing.
25 Moreover, the replenished electrolyzed water of the first hollow portion **20** needs to go through the second passageway **380** of the lower cover **38** and the pluralities of lower holes corresponding to the electrode passageway of the electrolyze tank **32** for providing electrolysis device **3** with the electrolyzed water **W** when the electrolysis device **3** is in operation. In one embodiment, the gas generator of the present

invention can detect the water level in the first hollow portion accommodated in the water tank and/or the electrolysis device by the water level gauge to control the replenishment of the electrolyzed water.

Please refer to FIG.4. The flow rate detector F is coupled to the electrolysis device **3** for detecting the flow rate of the hydrogen-oxygen mixed gas. In one embodiment, the flow rate of the hydrogen-oxygen mixed gas of the gas generator **1** ranges from the 0.01 L/min to the 12 L/min. After the gas generator generates the hydrogen-oxygen mixed gas generated under 120L/hr for 2000 hours to 3000 hours, the loss of the electrolyte is equal to or lower than 50g; and it is predictable that the loss of the electrolyte is equal to or lower than 5g after the gas generator generates the hydrogen-oxygen mixed gas generated under 600L/hr for 40 hours to 60 hours; or it is predictable that the loss of the electrolyte is equal to or lower than 0.25g after the gas generator generates the hydrogen-oxygen mixed gas generated under 30L/hr for 40 hours to 60 hours; it is also predictable that the loss of the electrolyte is equal to or lower than 2g after the gas generator generates the hydrogen-oxygen mixed gas generated under 240L/hr for 40 hours to 60 hours; it is also predictable that the loss of the electrolyte is equal to or lower than 3g after the gas generator generates the hydrogen-oxygen mixed gas generated under 360L/hr for 40 hours to 60 hours; and it is also predictable that the loss of the electrolyte is equal to or lower than 2g after the gas generator generates the hydrogen-oxygen mixed gas generated under 30L/hr for 40 hours to 600 hours. In practice, the present invention is not limited to it; the user can adjust the flow rate and the operation time according to the usage requirement.

Please refer to FIG. 12, FIG. 12 shows the gas generator of the present invention in another embodiment. In one embodiment, the gas generator **1** comprises the water tank **2**, the electrolysis device **3**, the condensate filter **6**, the humidification filter **8**, the humidification device **9** and the pump device **5**. The electrolysis device **3** is coupled to the water tank **2**. The condensate filter **6** is connected between the electrolysis device **3** and the humidification filter **8**. The humidification filter **8** accommodates water. The humidification filter **8** is connected to the condensate filter

6. The humidification device **9** is connected to the humidification filter **8**. The condensate filter condenses the hydrogen-oxygen mixed gas generated by the electrolysis device and filters the electrolyte of the hydrogen-oxygen mixed gas. The humidification filter **8** is used for filtering the filtered hydrogen-oxygen mixed gas which is filtered by the condensate filter. The humidification device **9** can humidify the hydrogen-oxygen mixed gas which is filtered by the humidification filter **8**.

In one embodiment, the humidification filter **8** comprises a tank, a first tube, a first filter, and a first tube. The tank has a space for accommodating water but not limited to it. The tank is able to accommodate the liquid according the usage requirement. The first tube is connected to the external side and the inner side of the tank. The first tube has the first terminal and the second terminal corresponding to the first terminal. The first terminal and the second terminal are able to connect the external side and the inner side of the tank. The first filter is set at the second terminal of the first tube for connecting the external side and the inner side of the tank.

In one embodiment, the humidification filter **8** further comprise a second filter **23** coupled to the entrance and the exit of the first tube. In practice, the second filter can be coupled under the first tube to directly output the filtered hydrogen-oxygen mixed gas. The first filter and the second filter may be made of porous plastics. In another embodiment, the porous plastics may be a polyethylene but not limited to it.

The hydrogen-oxygen mixed gas is pumped from the outside through the first terminal of the first tube, and the hydrogen-oxygen mixed gas is pumped into the tank through the second terminal of the first tube. Because the first filter is set on the second terminal, the hydrogen-oxygen mixed gas is pumped through the first filter when the gas mixture is output from the second terminal, and the impurities is filtered out by the first filter, wherein the impurities can be electrolytes. After the hydrogen-oxygen mixed gas is pumped into the water in the tank, the hydrogen-oxygen mixed gas is filtered by the water. The filtered gas comprising hydrogen and oxygen which can pass through the second filter element to filter the vapor in the

hydrogen-oxygen mixed gas and be pumped out from the tank through the first tube.

In one embodiment, the humidification filter **8** comprises a tube. One terminal of the tube is connected between the first terminal and the second terminal of the first tube. One of the terminals of branch connects the first tube and the second tube and
5 another terminal of branch comprises a one-way valve. The one-way valve can be used to keep the hydrogen-oxygen mixed gas being output from the branch. Therefore, when the first tube receives the hydrogen-oxygen mixed gas from the outside, the hydrogen-oxygen mixed gas is blocked by the one-way valve and pumped through the first terminal of the first tube to the second terminal and into the
10 tank. In one embodiment, the one-way valve of the humidification filter **8** can control the water level of the tank (not shown in the figures). When the water level is higher than a predetermined value, the humidification filter **8** will pump out the water in the tank by the one-way valve through the first tube and the branch until the water level is lower than the predetermined value in order to maintain the water level of the tank.

15 The pump device is connected to the water tank for generating negative pressure in the water tank in order to pump back the supplementary water from the humidification device through the condensate filter into the water tank, and the electrolyte adsorbed in the condensate filter is back flushed to the water tank. When the flow rate of generating the hydrogen-oxygen mixed gas by the gas generator is
20 600L/hr after operating 40 to 60 hours, the loss of the electrolyte is less than 5g.

In one embodiment, the electrolysis device is connected to the external power source. The output voltage of the power source ranges from 17V to 27V. The output electric current of the power source ranges from 30A to 40A. That is to say, the amount of the output gas of the electrolysis device ranges from 1.5L/min to 4.0L/min.
25 The voltage of every pair of electrodes ranges from 1.5V to 3V. If there are eight pairs of electrodes, the voltage ranges from 12V to 24V but the voltage is not limited to it. In practice, when the electrolysis device is connected to the external power source, the output voltage of the power source ranges from 5V to 24V, the output electric current ranges from 2A to 150A, and the power of the electrolysis device

ranges from 10W to 3600W, the output gas generated by the electrolysis device ranges from 0.01L/min to 12L/min.

In conclusion, the hydrogen-oxygen mixed gas is generated by the electrolysis device of the gas generator of the present invention. The electrolyte in the hydrogen-oxygen mixed gas is able to be condensed and filtered out by the condensate filter. The amount of the electrolyte in the hydrogen-oxygen mixed gas is reduced after being humidified by the humidification device for the user to inhale. In another embodiment, the gas generator further comprises a humidification filter configured between the condensate filter and the humidification device which is able to filter out the impurities in the hydrogen-oxygen mixed gas for providing a better hydrogen-oxygen mixed gas for the user to inhale. Besides, the supplementary water is pumped back into the water tank through the humidification device by the pump device which is connected to the water tank. Furthermore, the gas generator pumps the supplementary water and back flushes the electrolyte into the electrolysis device to restore the filtering function of the circulating passageway. Therefore, the present invention not only avoid the blocking, etching, and corrosion in the circulating passageway but also reduce the consumption of the electrolyte.

With the examples and explanations mentioned above, the features and spirits of the invention are hopefully well described. More importantly, the present invention is not limited to the embodiment described herein. Those skilled in the art will readily observe that numerous modifications and alterations of the device may be made while retaining the teachings of the invention. Accordingly, the above disclosure should be construed as limited only by the metes and bounds of the appended claims.

25

What is claimed is:

1. A gas generator comprising:

a water tank accommodating electrolyzed water, wherein the electrolyzed water comprises an electrolyte;

5 an electrolysis device disposed within the water tank for electrolyzing the electrolyzed water to generate a hydrogen-oxygen mixed gas;

a condensate filter connected to the electrolysis device for condensing the hydrogen-oxygen mixed gas and filtering the electrolyte in the hydrogen-oxygen mixed gas to generate a filtered hydrogen-oxygen mixed gas and a filtered electrolyte;

10 a humidification device accommodating a supplementary water and coupled to the condensate filter for humidifying the filtered hydrogen-oxygen mixed gas to generate a humidified hydrogen-oxygen mixed gas; and

a pump device coupled to the water tank for generating a negative pressure in the water tank such that the supplementary water is pumped from the humidification device through the condensate filter to the water tank, and the filtered electrolyte in the condensate filter is flushed back to the water tank;

15 wherein the flow rate of the hydrogen-oxygen mixed gas generated by the gas generator is between 360 to 600 liter per hour, and the loss of the electrolyte is less than 3g to 5g after the gas generator is operated between 40 to 60 hours.

2. The gas generator of claim 1, wherein the electrolyte is an edible sodium hydroxide.

25 3. The gas generator of claim 1, further comprising an atomized gas mixing tank, wherein the atomized gas mixing tank comprises a gas outlet, the water tank is connected to the atomized gas mixing tank by the pump device, and a gas in the water tank is pumped out through the gas outlet of the atomized gas mixing tank to generate the negative pressure in the water tank when the pump

device is in operation.

4. The gas generator of claim 3, wherein the atomized gas mixing tank is coupled to the humidification device to receive the humidified hydrogen-oxygen mixed gas, the atomized gas mixing tank generates an atomized gas and mixes
5 the atomized gas with the humidified hydrogen-oxygen mixed gas to form a healthy gas for user to inhale, and the atomized gas is selected from the group consisting of water vapor, atomized liquid, volatile purified oil and combinations thereof.

5. The gas generator of claim 1, wherein the humidification device further
10 comprises at least an output tube having a plurality of holes, and the hydrogen-oxygen mixed gas is outputted through the plurality of holes of the output tube to humidify the filtered hydrogen-oxygen mixed gas.

6. The gas generator of claim 1, wherein the condensate filter comprises a plurality of condensate plates, and each condensate plate has a passageway,
15 each passageway of the condensate plate is connected to the passageway of the adjacent condensate plate to form a circulating passageway for circulating the hydrogen-oxygen mixed gas.

7. The gas generator of claim 6, wherein the passageway is a combination of a diverging passageway and a connecting passageway, and the diverging
20 passageway of the condensate plate is connected to the diverging passageway of the adjacent condensate plate by the connecting passageway.

8. The gas generator of claim 6, wherein each passageway of the condensate plate is disposed with an activated carbon fiber for filtering out impurities in the hydrogen-oxygen mixed gas, and the impurities is the electrolyte of the
25 electrolyzed water.

9. The gas generator of claim 6, wherein each passageway of the condensate plate is disposed with a filter material, and the filter material comprises

ceramics, quartz, diatomaceous earth, meerscham or combinations thereof.

10. The gas generator of claim 7, wherein the diverging passageway is a sectional diverging passageway, the diverging passageway comprises an opening, the connecting passageway comprises a passageway and two corresponding openings, the two openings of the connecting passageway are connected to each other by the passageway, and the opening of the diverging passageway of the condensate plate is connected to the opening of the diverging passageway of the adjacent condensate plate by the two corresponding openings of the connecting passageway.

11. A gas generator, comprising:

a water tank accommodating electrolyzed water, wherein the electrolyzed water comprises an electrolyte;

an electrolysis device coupled to the water tank and configured for electrolyzing the electrolyzed water to generate a hydrogen-oxygen mixed gas;

a condensate filter connected to the electrolysis device for condensing the hydrogen-oxygen mixed gas and filtering the electrolyte in the hydrogen-oxygen mixed gas to generate a filtered hydrogen-oxygen mixed gas and a filtered electrolyte;

a humidification filter accommodating the water and coupled to the condensate filter for filtering the filtered hydrogen-oxygen mixed gas filtered by the condensate filter;

a humidification device accommodating a supplementary water and connected to the condensate filter for humidifying the filtered hydrogen-oxygen mixed gas filtered by the humidification filter; and

a pump device connected to the water tank for generating a negative pressure in the water tank such that the supplementary water is pumped from the humidification device through the humidification filter and the condensate filter to the water tank, such that the filtered electrolyte in the condensate filter is

flushed back to the water tank;

wherein the flow rate of the hydrogen-oxygen mixed gas generated by the gas generator is between 360 to 600 liter per hour, and the loss of the electrolyte is less than 3g to 5g after the gas generator is operated between 40 to 60 hours.

5