CLAIMS

What is claimed is:

1. An audio processing device for processing an event by using a spatial audio position transfer function dataset, the device comprising:

an audio rendering module configured to position 1st and 2nd audio signals respectively comprising at least a voice communication stream and a media stream in selected ones of at least a first spatial audio position and a second spatial audio position, each of the first and second spatial audio positions rendered by using respective first and second transfer functions from the spatial audio position transfer function dataset;

a monitoring module to monitor initiation of a voice communication event, the event comprising receipt of a phone call, and upon initiation of the phone call, processing the first and second audio signals by positioning the voice communication to the first spatial audio position and transitioning the media stream from an initial spatial audio position to the second spatial audio position;

an output module configured for rendering the resultant audio over two output channels to a coupled pair of headphones; and

wherein the audio rendering module is configured to receive from a selection processor a spatial audio position transfer function personalized for the individual from a memory having a candidate pool of a plurality of spatial audio position transfer function datasets that have been provided for a population of individuals, the spatial audio position transfer function datasets each indexed by their corresponding image based audio related physical properties.

2. The audio processing device as recited in claim 1 wherein the spatial audio position transfer function dataset is one of an HRIR dataset or a BRIR dataset customized for an individual and wherein the initial spatial audio position is the first spatial audio position.

3. The audio processing device as recited in claim 1 wherein the selection processor determines the individualized BRIR dataset by accessing the candidate pool by comparing the extracted image based audio related physical properties for the individual against the extracted image based properties for the candidate pool, to identify one or more BRIR datasets based on a closeness metric.

4. The audio processing device as recited in claim 2 wherein the first and second spatial audio positions from the determined individualized BRIR dataset are derived by interpolation or other computation methods from a captured dataset in the memory and wherein the first and second spatial audio positions comprise respectively foreground and background positions.

5. The audio processing device as recited in claim 4 wherein upon determination by the individual listener that the voice call is of a lower priority and generation of a corresponding control signal, the voice call is directed to the background position and the music to the foreground position.

6. The audio processing device as recited in claim 2 wherein upon determination by the individual listener that the voice call is of a lower priority and generation of a corresponding control signal, the apparent distance of the voice call is increased and the apparent distance of the music is decreased using individualized BRIRs corresponding to different distances for the same directions.

7. The audio processing device as recited in claim 2 wherein the positioning of the voice communication to the first spatial audio position and the transitioning of the media stream to the second spatial audio position is performed in an abrupt manner.

8. The audio processing device as recited in claim 2 further including a portable image capturing device configured for acquiring the input image and wherein the audio processing device is one of a mobile phone, communication device, or tablet that captures the image and extracts the image-based properties.

9. The audio processing device as recited in claim 1 wherein the audio processing device is configured to reposition the media stream to the first spatial audio position upon termination of the voice communication stream.

10. The audio processing device as recited in claim 1 wherein the media stream comprises music.

11. The audio processing device as recited in claim 1 wherein the apparent distance of the voice call is increased and the apparent distance of the music is decreased using respective first and second spatial audio position sound transfer functions from the individualized BRIRs corresponding to different distances for the same directions.

12. The audio processing device as recited in claim 1 wherein the output module is coupled to the headphone via one of a wireless connection and a wired connection.

13. The audio processing device as recited in claim 1 wherein the output module includes a digital to analog converter and the coupling to the headphones is through an analog port.

14. The audio processing device as recited in claim 1 wherein the output module is configured to pass a digital signal to the headphones and the headphones include a digital to analog converter.

15. The audio processing device as recited in claim 1 further comprising a user interface configured for choosing a location for at least one of the first spatial audio position and the second spatial audio position.

16. A method for processing audio streams to a set of headphones comprising:

positioning 1st and 2nd audio signals respectively comprising at least a voice communication stream and a media stream in selected ones of at least a first spatial audio position and a second spatial audio position, each of the first and second spatial audio positions rendered by using respective first and second transfer functions from a spatial audio position transfer function dataset;

monitoring initiation of a voice communication event, the event comprising receipt of a phone call, and upon initiation of the phone call processing the first and second audio signals by positioning the voice communication to the first spatial audio position and transitioning the media stream from an initial spatial audio position to the second spatial audio position wherein at least an associated room impulse response is present in the second transfer function for the second spatial audio position; and

rendering the resultant audio over two output channels to a coupled pair of headphones, wherein the spatial audio position transfer function dataset is one of an HRIR or a BRIR dataset customized for an individual and wherein the initial spatial audio position is the first spatial audio position, and wherein the customization includes extracting image-based audio related physical properties for the individual from an input image and transmitting the image based properties to a selection processor configured to determine an individualized BRIR dataset from a memory having a candidate pool of a plurality of BRIR datasets that have been provided for a

population of individuals, the BRIR datasets each associated with their corresponding image based properties.

17. The method as recited in claim 16 wherein determining the individualized BRIR dataset comprises interpolation between existing BRIR datasets in the candidate pool.

18. A method for rendering audio streams comprising:

acquiring a first and second spatial audio transfer function customized for an individual from a database comprising a candidate pool of spatial audio transfer functions for a population of individuals, each spatial audio transfer function indexed according to extracted image based biometric properties;

positioning 1st and 2nd audio signals respectively comprising at least a voice communication stream and a media stream in selected ones of at least a first virtual audio position and a second virtual audio position, each of the first and second virtual audio positions rendered by using respect spatial audio transfer functions customized for an individual; and

transitioning the media stream and the voice communication stream between the first and second virtual audio positions based upon a triggering event.

19. The method as recited in claim 18 wherein the triggering event is one of a receipt of a phone call and the termination of a phone call.