

CORRECTED VERSION

(19) World Intellectual Property Organization
International Bureau(43) International Publication Date
4 October 2007 (04.10.2007)

PCT

(10) International Publication Number
WO 2007/111845 A3

(51) International Patent Classification:

H04N 3/15 (2006.01) *H04N 5/335* (2006.01)

(21) International Application Number:

PCT/US2007/006597

(22) International Filing Date: 16 March 2007 (16.03.2007)

(25) Filing Language:

English

(26) Publication Language:

English

(30) Priority Data:

11/386,678 23 March 2006 (23.03.2006) US

(71) Applicant (for all designated States except US): **MICRON TECHNOLOGY, INC.** [US/US]; 8000 S. Federal Way, Boise, ID 83707-006 (US).

(72) Inventors; and

(75) Inventors/Applicants (for US only): **XU, Chen** [CN/US]; 1464 S. Loggers Pond Place, #22, Boise, ID 83706 (US). **ALTICE, Parker** [US/US]; 4941 Fairborough Drive, Meridian, ID 83642 (US).(74) Agent: **D'AMICO, Thomas, J.**; Dickstein Shapiro LLP, 1825 Eye Street, NW, Washington, DC 20006-5403 (US).

(81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN,

CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, GT, HN, HR, HU, ID, IL, IN, IS, JP, KE, KG, KM, KN, KP, KR, KZ, LA, LC, LK, LR, LS, LT, LU, LY, MA, MD, MG, MK, MN, MW, MX, MY, MZ, NA, NG, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RS, RU, SC, SD, SE, SG, SK, SL, SM, SV, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, ZA, ZM, ZW.

(84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IS, IT, LT, LU, LV, MC, MT, NL, PL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Published:

— with international search report

(88) Date of publication of the international search report:

1 November 2007

(48) Date of publication of this corrected version:


27 December 2007

(15) Information about Correction:

see PCT Gazette No. 52/2007 of 27 December 2007

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

(54) Title: METHOD AND APPARATUS FOR PROVIDING A ROLLING DOUBLE RESET TIMING FOR GLOBAL STORAGE IN IMAGE SENSORS



(57) Abstract: An apparatus for and a method of operating an array of pixels of an image sensor, where each pixel includes at least a photosensor, an associated storage device and a floating diffusion region and the array of pixels is configured in a plurality of rows and columns. The photosensors associated with the pixels are reset and charges are accumulated in the photosensor. The accumulated charges are then globally transferred to storage devices associated with the pixels. A rolling double reset is used to reduce the deleterious effects on the accumulated charges stored in the storage devices. The accumulated charges stored in the storage devices are transferred to floating diffusion regions associated with the pixels and the charges residing in the floating diffusion region are read out. In a second embodiment the storage device is eliminated and the rolling double reset is used to reduce the deleterious effects on the accumulated charges stored in the floating diffusion region.

WO 2007/111845 A3