

HEADGEAR FOR RESPIRATORY INTERFACES

BACKGROUND

Field of the Invention

[0001] The present disclosure generally relates to headgear for respiratory
5 interfaces. More particularly, the present disclosure relates to straps and hook assemblies
for such headgear.

Description of the Related Art

[0002] Headgear is used to secure user interfaces during breathing treatments.
10 Improvements to the headgear are desired to provide easier to use headgear as well as
more comfortable headgear.

SUMMARY

[0003] Accordingly, a variety of configurations are shown and described
15 herein that will provide improved fit, form and/or function to headgear and/or that will
provide the public with a useful option.

[0004] In some configurations, headgear for a breathing interface is provided.
The headgear comprises at least the one strap with the at least one strap having a
customizable stretch characteristic.

20 [0005] In some configurations, the at least one strap includes at least one
receiving region that is configured to receive an insert, the insert being rigid or semi-rigid.

[0006] In some configurations, the insert is removable from the receiving
region.

[0007] In some configurations, the insert is movable among two or more of the
25 at least one receiving regions. In some such configurations, wherein the insert can be
replaced by a second insert that is receivable within the receiving region.

[0008] In some configurations, the at least one strap includes multiple
separable segments. In some such configurations, the multiple separable segments are
positioned internally within the at least one strap. In some such configurations, two
30 adjacent segments of the multiple separable segments are configured to be dislocated from
each other to provide a custom stretch characteristic in one or more locations.

[0009] In some configurations, the at least one strap incorporates a stretch component, a relatively non-stretch member and two or more buckles that interconnect the at least one strap and the relatively non-stretch member. In some such configurations, the stretch component has a greater length than the relatively non-stretch member. In some such configurations, the two or more buckles are adjustable along a length of the relatively non-stretch member. In some such configurations, the two or more buckles are adjustable such that an intermediate length of the stretch component disposed between the two buckles can be varied. In some such configurations, adjusting the spacing between the two or more buckles adjusts the amount of the stretch component that is secured to the relatively non-stretch member and, therefore, unable to stretch. In some such configurations, the relatively non-stretch component comprises a hollow portion through which the stretch component passes. In some such configurations, the two or more buckles attach to the non-stretch component with the stretch component being secured within the non-stretch component.

[0010] In some configurations, the at least one strap incorporates a stretch component, a relatively non-stretch member and two or more limiters that interconnect the at least one strap and the relatively non-stretch member. In some such configurations, the stretch component has a greater length than the relatively non-stretch member. In some such configurations, the nonstretch member comprises two or more apertures that receive the two or more limiters and the stretch member comprises two or more apertures. In some such configurations, the nonstretch member comprises at least three openings and the stretch component comprises at least three openings. In some such configurations, the two or more apertures of the non-stretch member have a first spacing and the two or more apertures of the stretch member have a second spacing. In some such configurations, the second spacing is the same as the first spacing. In some such configurations, the second spacing is different from the first spacing. In some such configurations, the second spacing is less than the first spacing. In some such configurations, the two or more limiters are connected for movement. In some such configurations, a hinge connects two adjacent limiters such that depressing one causes a lifting of the other.

[0011] In some configurations, a connector is configured to be attached to the at least one strap and the connector comprises a passage through which the at least one strap passes. In some such configurations, the connector comprises a clamping configuration that secures the connector in position along the at least one strap. In some

such configurations, the clamping configuration comprises a living hinge between a first portion and a second portion of the connector and the first portion can be brought into engagement with the second portion with the connector positioned in a desired location along the at least one strap. In some such configurations, the clamping configuration
5 comprises a locking mechanism that can be provided as part of the connector. In some such configurations, the locking mechanism includes a push-button that can lock the connector in position along the at least one strap. In some such configurations, the locking mechanism includes a hinge system that locks onto the at least one strap.

[0012] In some configurations, at least a portion of the at least one strap
10 comprises a thermoplastic element. In some such configurations, the at least one strap comprises a woven or braided construction that integrates the thermoplastic element. In some such configurations, the at least one strap can be provided with regions of different stretch characteristics through the use of ultrasonic welding. In some such configurations, one or more connectors can be attached to the at least one strap in a region that has
15 undergone forming.

[0013] In some configurations, the headgear features upper straps, lower straps and a top strap. In some such configurations, the headgear comprises a three dimensional shape when not being worn such that the headgear does not lie flat when not being worn.

[0014] In some configurations, the headgear can be used with a patient
20 interface.

[0015] In some such configurations, the patient interface is selected from the group consisting of full face mask, nasal mask, nasal pillows, non-invasive or a cannula. In some such configurations, the headgear and the patient interface are connected by connectors. In some such configurations, the connectors comprise clips. In some
25 configurations, the interface comprises a delivery conduit. In some such configurations, the delivery conduit is connected to the interface with a ball joint, which may be removable. In some such configurations, the delivery conduit comprises a swivel connector. In some such configurations, the interface comprises a frame and a cushion that is removable from the frame. In some such configurations, the interface further
30 comprises an anti-asphyxiation valve. In some such configurations, the interface further comprises bias flow holes. In some such configurations, the interface further comprises a forehead support. In some such configurations, the patient interface does not comprise a forehead support.

[0016] In some configuration, a headgear assembly is provided for use with a patient interface. The headgear assembly comprises at least one strap. The at least one strap comprises an end with a hook component. The hook component is securable to a loop component. The hook component comprises at least two fingers that are spaced
5 apart from each other by a gap such that lifting one of the at least two fingers will not result in lifting of the other of the at least two fingers.

[0017] In some configurations, the two or more fingers are symmetrical with each other.

[0018] In some configurations, the two or more fingers are asymmetrical with
10 each other.

[0019] In some configurations, the gap results in the at least two fingers defining a forked configuration.

[0020] In some configurations, the gap is centrally positioned along the hook component.

[0021] In some configurations, one of the at least two fingers at least partially
15 surrounds another of the at least two fingers. In some such configurations, one of the at least two fingers completely surrounds another of the at least two fingers. In some such configurations, one of the at least two fingers defines a central tab and another of the at least two finger defines an outer tab that circumscribes the central tab.

[0022] In some configurations, one of the at least two fingers only partially
20 surrounds another of the at least two fingers.

[0023] In some configurations, the gap extends inwardly from a lateral edge of the hook component. In some such configurations, a second gap extends inwardly from a second lateral edge of the hook component and two fingers are defined with a narrow
25 section connecting to a wide end.

[0024] In some such configurations, the at least one strap comprises a single strap.

[0025] In some such configurations, the at least one strap comprises an upper strap and a lower strap.

[0026] In some such configurations, the at least one strap comprises an upper
30 strap, a lower strap and a crown strap.

[0027] In some configurations, a strap is provided for a breathing assistance apparatus interface. The strap comprises a first portion and a second portion that combine

to form a hollow tubular configuration. The first portion has different properties from the second portion at the same axial location along the strap.

[0028] In some such configurations, the first portion is an outer portion and the second portion is an inner portion and the outer portion has greater rigidity than the inner portion.

[0029] In some configurations, a strap is provided for a breathing assistance apparatus interface. The strap comprises a continuous braid section wherein the continuous braid section comprises a first portion and a second portion that are at differing axial positions along the continuous braid section. The first portion being relatively more stretchable than the second portion.

[0030] In some such configurations, the continuous braid section comprises a third portion with the first portion being positioned between the second portion and the third portion and the first portion being relatively more stretchable than the third portion. In some such configurations, the first portion, the second portion and the third portion define zones to secure a beaded member.

[0031] In some configurations, a strap is provided for a breathing assistance apparatus interface. The strap is formed by at least one of weaving and braiding. The strap incorporates at least one of a thermoplastic string, a rubberized string, a silicone string and a closure structure formed during the at least one of weaving and braiding. The closure structure comprises at least one of a looped surface, a well-defined loop and a button hole.

[0032] In some configurations, a strap is provided for a breathing assistance apparatus interface. The strap is formed by at least one of weaving and braiding. The strap has a varied cross section.

[0033] In some such configurations, the varied cross section comprises a window formed during the at least one of weaving and braiding.

[0034] In some such configurations, the window can be severed to form portions of two different headgear.

[0035] In some such configurations, the strap is severed between two different windows to form two different headgear.

[0036] In some such configurations, the window is filled with a mesh material.

[0037] In some such configurations, the strap forms an entire seamless headgear unit.

[0038] In some configurations, a strap is provided for a breathing assistance apparatus interface. The strap comprises a tubular component formed by at least one of braiding and weaving with a rigid or semi-rigid component being positioned within a lumen defined by the tubular component.

5 **[0039]** In some such configurations, the rigid or semi-rigid component spans a connection between a first finger of the strap and a second finger of the strap such that the rigid or semi-rigid component spans a corner between the first finger and the second finger.

[0040] In some configurations, a strap is provided for a breathing assistance apparatus. The strap comprises a stretch increasing configuration. The stretch increasing component is configured to allow increased stretchability of the strap by severing a connection between two or more adjacent portions of the strap.

[0041] In some configurations, headgear is provided for a breathing assistance apparatus. The headgear comprises a strap and a strap adjustment mechanism.

15 **[0042]** In some such configurations, the strap adjustment mechanism comprises at least one of a tie down system and at least two structures that connect a relatively nonstretch component to a relatively stretchable component in at least two corresponding spaced apart locations, wherein at least one of the at least two corresponding spaced apart locations can be adjusted relative to the other of the two locations. In some such configurations, the strap adjustment mechanism comprises a passage through a hook, the hook being used to secure the strap to the interface. In some such configurations, the strap adjustment mechanism comprises a winding mechanism. In some such configurations, the headgear further comprises an adjustment mechanism that alters a position of a mask relative to the headgear. In some such configurations, the strap adjustment mechanism comprises at least one of a pinching lever, a loop and a post connection. In some such configurations, the strap adjustment mechanism comprises at least one scissor mechanism. In some such configurations, the strap adjustment mechanism comprises a hook member and a loop fastener member, the hook member comprising a plurality of fingers.

BRIEF DESCRIPTION OF THE DRAWINGS

[0043] Certain features, aspects and advantages of specific embodiments and modifications of the present disclosure will become apparent to those skilled in the art from the detailed description herein having reference to the sheets of figures that follow.

5 [0044] Figure 1 is a perspective view of a portion of a strap.

[0045] Figure 2 is a perspective view of a portion of another strap.

[0046] Figure 3 is a perspective view of the strap of Figure 2 undergoing rolling movement.

10 [0047] Figure 4 is a perspective view showing a portion of a strap disposed around a structural component.

[0048] Figure 5 is a perspective view of the strap of Figure 4 undergoing rolling movement.

[0049] Figure 6 is plan view of a strap having bands of different elasticity.

15 [0050] Figure 7 is a plan view of an end connector attached to a strap having regions of differing elasticity along a length of the strap.

[0051] Figure 8 is a plan view of another strap having bands of different elasticity.

[0052] Figure 9 is a plan view of a strap and adjustment mechanism shown in partial section.

20 [0053] Figure 10 is a plan view of another strap and adjustment mechanism shown in partial section.

[0054] Figure 11 is a view of a strap shown prior to connection of two ends.

[0055] Figure 12 is a plan view of a strap.

[0056] Figure 13 is a plan view of another strap.

25 [0057] Figure 14 is a plan view of a strap.

[0058] Figure 15a is a plan view of another strap.

[0059] Figure 15b is a view of the strap of Figure 15a and a connecting hook.

[0060] Figure 16 is plan view of another strap.

[0061] Figures 17-19 are views of straps having friction pads.

30 [0062] Figures 20 and 21 are views of a strap having a non-uniform width along the length.

- [0063] Figures 22 and 23 are views of a strap having a more complicated shape.
- [0064] Figures 24-26 illustrate headgear strap formed as a continuous member.
- 5 [0065] Figures 27-29 illustrate two headgear straps formed as a continuous member.
- [0066] Figures 30-32 illustrate a headgear strap formed from a continuous member.
- [0067] Figures 33-36 illustrate headgear formed as a single knit.
- 10 [0068] Figures 37-46 illustrate headgear with rigid or semi-rigid components.
- [0069] Figures 47-56 illustrate straps with length adjusting segments.
- [0070] Figures 57-62b illustrate headgear incorporating a tie-down and strap management system.
- [0071] Figures 63-69 illustrate headgear incorporating a stretch limiting system.
- 15 [0072] Figures 70-76 illustrate headgear incorporating a stretch limiting system using push-buttons or domes.
- [0073] Figures 77-81 illustrate headgear incorporating one-time setup features.
- [0074] Figures 82-87 illustrate an assembly incorporating a screw adjustment for headgear and/or a mask seal.
- 20 [0075] Figures 88-92 illustrate a rack and pinion adjustment for headgear and/or a mask seal.
- [0076] Figures 93-98 illustrate an Archimedes screw adjustment for headgear and/or a mask seal.
- 25 [0077] Figures 99-102 illustrate an adjustment for headgear and/or a mask seal.
- [0078] Figure 103 illustrates a hook adjustment for headgear and/or a mask seal.
- [0079] Figures 104-107c illustrate an over-center pinch adjustment for a strap.
- 30 [0080] Figures 108-110c illustrate scissor linkage adjustments for a strap.
- [0081] Figures 111-114 illustrate a fine-tuning adjustment for a scissor linkage for a strap.

[0082] Figures 115-116i illustrate hook and loop fastener adjustments for headgear.

DETAILED DESCRIPTION OF SPECIFIC EMBODIMENTS

5 [0083] In some of the following description, materials are formed using one or more of weaving, knitting and braiding. Weaving is interlacing, usually at right angles, of two sets of threads to form cloth, rug or other types of woven textiles. In automated processes, two distinct sets of yarns called the warp and the filling or weft are interlaced with each other to form a fabric. The lengthwise yarns that run front to back in the loom
10 are called the warp while the yarns that extend crosswise are called the weft. Typically, the warp threads are held stationary while the weft threads are woven through them.

[0084] The yarn in knitted fabrics follows a meandering path, forming symmetric loops or stitches. When the interlocking loops run lengthwise, each row is called a wale. A wale can be compared with the warp in weaving. When the loops run
15 across the fabric, each row is called a course. A course corresponds to the weft. There are two major varieties of knitting: weft knitting and warp knitting. In weft knitting, one continuous yarn forms courses across the fabric. In warp knitting, a series of yarns form wales in the lengthwise direction of the fabric. As used herein, knitting will typically refer to warp knitting but may refer to weft knitting in certain configurations.

20 [0085] In braiding, three or more strands can be interwoven to form a rope-like member. The interweaving is performed in a diagonally overlapping pattern. Braiding is done by intertwining yarns in whatever direction suited to the manufacturer's purpose. Braiding can be classified as two and three-dimensional braiding. Two-dimensional braid structure can be a circular or flat braid. They are formed by crossing a
25 number of yarns diagonally so that each yarn passes alternately over and under one or more of the others. Three dimensional braiding is a two dimensional array of interconnected 2-D circular braids. As used herein, braiding will typically refer to two-dimensional braiding but could refer to three-dimensional braiding in certain configurations.

30 [0086] Various head strap configurations and headgear configurations will be described. In some configurations, the headgear features upper straps, lower straps and a top strap. In some such configurations, the headgear comprises a three dimensional shape when not being worn such that the headgear does not lie flat when not being worn. In

some configurations, the headgear can be used with a patient interface. In some such configurations, the patient interface is selected from the group consisting of full face mask, nasal mask, nasal pillows, non-invasive or a cannula. In some such configurations, the headgear and the patient interface are connected by connectors. In some such configurations, the connectors comprise clips. In some configurations, the interface comprises a delivery conduit. In some such configurations, the delivery conduit is connected to the interface with a ball joint, which may be removable. In some such configurations, the delivery conduit comprises a swivel connector. In some such configurations, the interface comprises a frame and a cushion that is removable from the frame. In some such configurations, the interface further comprises an anti-asphyxiation valve. In some such configurations, the interface further comprises bias flow holes. In some such configurations, the interface further comprises a forehead support. In some such configurations, the patient interface does not comprise a forehead support.

Multi-Yarn Knits with Split Materials

15 **[0087]** With reference now to Figures 1-5, a head strap configuration 1000 is shown that can be formed by braiding multiple yarns together. In some embodiments, the head strap configuration 1000 can be formed of a braid of knit components. In other words, multiple yarns can be knit together to define a knit component and then the knit component can be used to form the braid. In some embodiments, the head strap configuration 1000 can feature a split material construction in which different yarns are used for a top portion 1002 of the head strap configuration 1000 and a bottom portion 1004 of the head strap configuration 1000. The top portion 1002 and the bottom portion 1004 of the head strap configuration 1000 can be joined in any suitable manner. For example, the two may be joined by thermal bonding, stitching, adhesive or the like.

25 **[0088]** In some configurations, the knit or braid, although mainly circular and continuous, can have very different properties for the top portion 1002 (i.e., a portion other than the portion that will sit closest to the face and/or the portion furthest from the portion that will sit closest to the face) and the bottom portion 1004 (i.e., the portion that will sit closest to the face). In such configurations, the yarns or materials chosen for the top and bottom surfaces or portions 1002, 1004 can be chosen for desired properties. For example, in some configurations, one portion (e.g., the top portion 1002) may comprise a rather rigid structural side while the other portion (e.g., the bottom portion 1004) may comprise a soft, cushioning side with the soft side being the side that will be in contact

with the skin. In some configurations, a strong, stiff yarn can be used to create structural rigidity for the head strap configuration 1000. In some configurations, a yarn can be used for the soft side that provides breathability and moisture absorption for the surface that will contact the skin of the user. In some configurations, such a material can include
5 merino wool.

[0089] As illustrated, the strong, stiff side (e.g., the top portion 1002) can provide some structural integrity to the head strap configuration 1000. For example, the strong, stiff side can provide structural rigidity, which can help reduce or eliminate the likelihood of twisting and tangles in headgear, which can be formed using the head strap
10 configuration 1000. Nevertheless, in the illustrated configuration, the braid resulting from the knit product would create a hollow tube that can allow some rolling of the strap relative to the user without undue slippage relative to the user, which slippage could cause chaffing over time. In other words, the head strap configuration 1000 comprises an inner lumen 1006. The inner lumen 1006 may allow relative movement between the upper
15 portion 1002 and the lower portion 1004 without necessarily creating significant movement between the lower portion 1004 and skin or hair of the user, as shown in Figure 3.

[0090] In some configurations, such as those shown in Figures 4 and 5, a structural headgear component 1010 can be enveloped or at least partially enveloped
20 within the lumen 1006 of the hollow braid. For example, in the illustrated configuration, the hollow braid of the head strap configuration 1000 would be able to roll around the structural headgear component 1010 and provide softness or a soft hand to the structural headgear component 1010. In some such configurations, the hollow braid would have the same properties around the circumference of the hollow braid, which is different from the
25 configuration discussed directly above in which an inner surface and an outer surface might have differing properties. In some configurations, however, the hollow braid also could have differing properties in different regions.

[0091] An advantage of these combined braid/knit configurations is the ability to produce the head strap during a single manufacturing process. For example, in some
30 configurations, the knit can be built with multiple yarns and possibly very different knitting patterns for the top and the bottom half. If one of the sides is intended to be in contact with the skin, properties like breathability might be considered. One particularly

interesting combination is a combination of a knit (e.g., such as the strap used with the PILAIRO interface) and a braid (e.g., a climbing rope's outer sleeve).

Multi-Yarn Knit in a Continuous Braid with Sections Having Different Properties

[0092] With reference now to Figures 6-8, a head strap configuration 1020 can include a strap 1022 that combines bands 1024 with different properties. For example, the strap 1022 can be knit from multiple yarns. In such configurations, bands 1024, 1026 can be formed by primarily knitting and/or braiding with one of the yarns (e.g., relatively non-stretch yarn) where the other(s) (e.g., relatively stretch yarn) is just carried across to the next section where the roles are reversed.

10 [0093] In the illustrated configuration, a relatively stretchy material can be used for the strap 1022 and the relatively stretchy material can be alternated with a relatively non-stretchy material for the ends 1026. In other words, a region 1024 can be formed predominantly using a relatively stretchy yarn (i.e., a region knitted from the relatively stretchy yarn) and that region can be bounded by two regions 1026 formed
15 predominantly using a relatively less stretchy or more rigid yarn. The number, size and configuration of the bands 1024, 1026 can be varied in any suitable or desired manner.

[0094] The relatively non-stretch regions 1026 can form ends 1026. The relatively non-stretch ends 1026 can improve the reliability of crimped connections 1030. For example, as shown in Figure 7, when clips 1030 are crimped onto the strap 1022 (e.g.,
20 hooks or the like), the clips 1030 are more securely attached in regions that are generally less stretchy or that are more stable and less elastic in an axial direction.

[0095] Configurations featuring different regions or bands can provide increased reliability and can provide ease of manufacture. Accordingly, such configurations may result in less rejects during manufacturing options and also may result
25 in less returns.

Multi-Yarn Knits with Sections having Different Stretch for Adjustment

[0096] With reference now to Figures 9-11, in some configurations, the knit of a head strap 1040 can be built using multiple yarns. In some configurations, the head strap 1040 can be formed with alternating bands 1042, 1044 of more and less elasticity.
30 As described above, the bands 1042, 1044 can be formed using yarns having differing elasticity values. For example, the bands 1042, 1044 can be formed by knitting primarily with one of the yarns where the other(s) are just carried across to the next section where the roles are reversed.

[0097] As shown, the head strap 1040 can be formed into a tubular shape that defines a lumen 1046. The tubular shape of the head strap 1040 can incorporate a series of the bands 1042, 1044. As described directly above, the bands 1042, 1044 can have differing elasticity. In some configurations, the bands 1042, 1044 can have alternating elasticity. Such a configuration can allow a series of beads 1050 or the like to be inserted into the lumen 1046 defined by the tubular shaped sleeve of the head strap 1040. In some configurations, the beads 1050 and the tubular shape of the head strap 1040 can be integrated into a single component (i.e., the two can form a single component as shown in Figure 11). In some configurations, the beads 1050 and the tubular shape of the head strap 1040 can be separate components. The beads 1050 can be advanced or retracted to alter a length or circumference of the strap or headgear component, for example, but without limitation. As such, the varied stretch properties in the bands 1042, 1044 can be used to adjust the length of the string of beads 1050 that can be pulled through the tubular sleeve of the head strap 1040, which can be formed by braiding, for example but without limitation. The relatively more stretchy bands 1042 can expand to accommodate the beads 1050 while the relatively less stretchy bands 1044 can resist circumferential expansion and can act to hold the beads 1050 in position.

[0098] The illustrated configurations can provide increased reliability and improved ease of manufacture. Accordingly, such configurations can result in less rejects and less returns.

Multi-Yarn Knit in a Continuous Braid Employing Thermoplastic Yarn

[0099] With reference now to Figures 12 and 13, a combination of technologies can be used to modify the braid or the weave. In some configurations, such as those shown in Figure 12, a thermoplastic material can be used in the braided or woven strap 1060. The thermoplastic material allows deformation under heat, which allows welding, such as ultrasonic welding, calendaring, fusing, and the like. For example, additional parts can be welded on to help create at least a portion of, if not a complete, headgear assembly. In the illustrated configurations, a clip, buckle, or other mechanical components 1062 can be secured to the strap 1060 using welding, such as ultrasonic welding, for example, but without limitation.

[0100] In some configurations, the thermoplastic nature can be used to change properties of the strap 1060 in specific regions (e.g., alter the elasticity). For example, in the illustrated configuration, a portion 1064 of the strap 1060 is shown crushed and fused,

which can alter characteristics in that region of the strap 1060. In some configurations, such as that shown in Figure 13, calendaring can be used, for example but without limitation, to add a pattern 1066. In some configurations, the strap 1060 can be branded by taking advantage of the thermoplastic characteristics.

5 **[0101]** Thus, in configurations employing thermoplastic yarn, the thermoplastic yarn can allow permanent thermoplastic, post-knitting, deformation, for example but without limitation. An advantage of such a construction is that the thermoplastic yarn can help incorporate features that would be otherwise impossible, difficult, and/or expensive to provide.

10 **Multi-Yarn Knit in a Continuous Braid Employing a Fancy Knitting Pattern**

[0102] With reference to Figure 14, 15a, 15b, and 16, configurations are illustrated in which a strap 1070 can feature a knit that is varied to create features and properties. In some configurations, tactile properties can be created or altered by adjusting or varying the knit. In some configurations, features can be created during the
15 knitting process simply by using different knitting patterns.

[0103] As illustrated, the knitting machine can be adjusted to create a braid or a knit that incorporates desired features. For example but without limitation, in some configurations, such as that shown in Figure 14, multiple loops can be created for tactile and/or functional reasons. In the illustrated configurations, the loops can be used in
20 conjunction with hook-style fasteners or the like. For example, in Figure 14, the loops can provide a differing tactile feel while also providing a loop segment 1072 that can improve connection with hooks of a hook-and-loop style fastener. In some configurations, such as those shown in Figures 15a and 15b, for example, well defined loops 1074 can be used as catches for hooks on a connector member 1076. In other
25 words, rather than having to attach separate catches for the hook of a clip, the well-defined loops 1074 can be used to secure the hook of the clip 1076. In some configurations, such as shown in Figure 16, for example, holes 1080 can be formed that can be used to receive buttons or posts, for example but without limitation.

[0104] An advantage of such a construction is that all of the different
30 properties are still part of the same knit with all of the advantages of knitting. In other words, there is only one manufacturing process to create the strap and no or minimal waste is created.

Multi-Yarn Knit in a Continuous Braid Incorporating Tactile Elements

[0105] With reference Figures 17-19, a strap or headgear component 1900 is illustrated that has incorporated a surface texture 1902. The surface texture can be used to increase grip, for example but without limitation.

5 [0106] As illustrated, in some configurations, such as that shown in Figure 17, the knit or braid can incorporate a string 1904, such as a rubber string, a silicone string, or the like. Such configurations can use exposed regions of the string 1904 to create the surface texture, which defines a high friction component, such as a pad, that can be integrated into the braid of the strap or headgear component 1900.

10 [0107] In addition to, or as an alternative to, using the multi yarn knit to create a textured surface 1902, other techniques also can be used. For example, in some configurations, such as those shown in Figures 18 and 19, screen printing can be used to create a textured surface 1902. Screen printing has the additional advantage of complete freedom in shape and size of the print. In the illustrated configurations, rubber dots can
15 be screen printed. In some configurations, other shapes can be defined. In some configurations, other shapes can be defined by screen printing or the like. For example but without limitation, the shapes can change as desired and, in some instances, depending upon fashion desires.

[0108] In some configurations, being able to provide surface texture can
20 facilitate better control over how certain portions of the headgear behaves or feels when disposed against the skin, for example.

Continuous Braids with Varied Shapes

[0109] With reference now to Figures 20-32, various configurations are shown in which headgear and head straps can be created having varied shapes, which can be
25 desired for multiple reasons.

[0110] With reference first to Figures 20 and 21, the illustrated configurations generally involve straps 2000 having varied cross sections. In the illustrated configurations, the headgear can be created as a continuous knitting process as described above. As illustrated, the knit can have wider regions 2002 and narrower regions 2004
30 and can be cut for finishing with appropriate or desired hooks, buckles, clips or the like. Such configurations can improve the fit, form and function of the headgear strap.

[0111] With reference to Figures 22-, these configurations generally involve straps 2010 that are a more complex knit with splits and joins. In some configurations,

the knit, much like that of Figure 20 and 21, can be formed as an endless strip that can be cut later into individual straps or headgear assemblies. In the illustrated configurations, the straps 2010 can define windows, openings or other large voids 2012 (see Figures 22-23, for example) _ that are included within the materials of the braid and/or knit. In some configurations, the straps can be configured such that two different varieties of headgear can be formed from the same braid and/or weave (see Figures 27-29, for example). For example, in some configurations, a window can be formed within the braid and/or weave that can be positioned on a back of a user's head (see Figure 29) while, if split, the portions of the strap 2010 that form the window 2012 can be used as a forked headgear with two strap ends that connect to an interface or the like (see Figure 28). The two strap ends can receive any suitable connector, buckle, hook, clip or the like.

[0112] With reference now to Figures 30-32, a further configuration is illustrated that is similar in some respects to the configuration of Figures 27-29. In the configurations of Figures 30-32, the windows 2012 discussed above can include a filling component 2014. In some configurations, the windows 2012 can include a mesh material 2014. In some configurations, the mesh material 2014 can be integrally formed with the straps 2010 that generally define the windows 2012. In some configurations, the mesh material 2014 can be formed separately and secured into the windows 2012 or onto the straps 2010 in any suitable manner. In some configurations, the headgear can be formed as a continuous strip that can be severed into multiple headgear during manufacturing.

Single Knit Headgear

[0113] With reference now to Figures 33-36, an entire, complex, headgear 2020 can be knit in one seamless knit. In some configurations, two or more of the straps 2022 used in the headgear 2020 can be integrated into a single knit. In some configurations, a majority of the straps 2022 used in the headgear 2020 can be integrated into a single knit. In some configurations, all of the straps 2022 used in the headgear 2020 can be integrated into a single knit.

[0114] In some configurations, each headgear 2020 can be knit individually. By forming the entire or the majority of the headgear 2020 in a single knit component, very complex shapes can be obtained without undertaking labor intensive stitching or welding steps. Generally, such a seamless knit configuration is less likely to be continuous (i.e., not an endless string of headgear assemblies). In some configurations, however, the seamless knitting process can be used to form headgear 2020 having a rather

complex configurations (e.g., three separate strap components 2022 on each side of the headgear) while still be formed in a continuous strip of headgear assemblies, as shown in Figure 34.

Headgear Incorporating Rigid or Semi-Rigid Inserts

5 **[0115]** With reference now to Figures 37-46, headgear 2030 can be created that includes one or more receiving regions, such as pockets, recesses or voids that receive and/or enclose rigid or semi-rigid inserts 2032 to help define a resting shape of the headgear 2030. One or more of the inserts 2032 can be removable from the pockets, recesses or voids. For example, the inserts 2032 can be removed for cleaning of the
10 headgear 2030. In some situations, the headgear 2030 can be used without the inserts 2032. In some situations, the inserts 2032 can have different characteristics and can be interchanged to vary one or more characteristic of the associated headgear 2030. Moreover, in some situations, the inserts 2032 can be moved to different regions of the headgear 2030. For example, the inserts 2032 can be moved among a set of receiving
15 regions to alter one or more characteristic of the headgear 2030.

[0116] One of the difficulties sometimes encountered with more complex headgear is getting the straps into the correct location when donning the headgear. In other words, many of the current headgear configurations on the market function well when in use. However, when not in use, the numerous straps can easily become tangled
20 and knotted, which frustrates users each time they have to put the mask back on. By utilizing straps having pre-defined resting shapes, headgear tangling can be reduced or eliminated while also creating a shape that will aid the user in understanding how best to approach wearing the headgear on their first trial.

[0117] As used herein, the rigid or semi-rigid structure 2032 can be positioned
25 internally or externally. In some configurations, the rigid or semi-rigid structures 2032 can be positioned within the hollow defined by the strap (e.g., defined by the braid). The rigid or semi-rigid structures 2032 can be secured in position using any suitable techniques. In some configurations, the rigid or semi-rigid structures 2032 can be secured with adhesive, with stitching or with any other technique. In some configurations, the
30 rigid or semi-rigid structures 2032 can maintain a specific shape of the head gear when in the resting position. In some configurations, the rigid or semi-rigid components 2032 can be applied to a single strap or multiple strap head gear arrangements.

[0118] As used herein, the resting shape is a shape that reduces or eliminates the likelihood of entanglement of the headgear when the headgear is not in use. The resting shape has an added benefit of also making it more obvious how the head gear should be put on by the user.

5 [0119] The rigid or semi-rigid member 2032 can be positioned in or on any one or more of the components of the headgear. In some configurations employing multiple rigid or semi-rigid members, the multiple members 2032 can be completely separate of each other. In some configurations employing multiple rigid or semi-rigid members 2032, the multiple members 2032 can be interconnected in any suitable manner.

10 [0120] In some configurations, as shown in Figures 39 and 40, for example, a crown strap 2034 of the headgear assembly can include two different rigid or semi-rigid members 2032 that are positioned within a stretchable strap 2036. The strap can be stretched during donning but returns to a contracted position following doffing. In some configurations, the stretching occurs in regions separating the two or more rigid or semi-rigid members 2032. An example of stretching of a strap 2036 in regions that do not including the rigid or semi-rigid member 2032 is shown in Figures 38a-38c. In some configurations, the stretching occurs in the regions generally enveloping the rigid or semi-rigid members 2032.

[0121] In some configurations, such as those shown in Figures 41-44, the rigid or semi-rigid member 2032 can have a more complex shape that connects the single rigid or semi-rigid member 2032 with two or more strap members 2036. In some such configurations, the rigid or semi-rigid member 2032 can help define a shape of the headgear 2030 by holding two or more straps 2036 in a desired position relative to each other. For example, in some configurations, the rigid or semi-rigid member 2032 can be a complex spreader that holds two or straps 2036 spread apart in a desired angular orientation. In some configurations, such as that shown in Figures 45 and 46, the rigid or semi-rigid member 2032 can provide support to a base and back portion of the headgear assembly 2030. The rigid or semi-rigid members 2032 can span the rear portion of the user's head and can wrap forward such that the straps 2036 are presented forward to simplify donning the headgear. Other configurations are possible.

Strap Incorporating Internal Stretch Increasing Elements

[0122] With reference now Figure 47-56, certain configurations of straps 2040 can include an internal structure 2042 that has multiple segments 2044. In some

configurations, such as shown in Figures 47 and 48, the internal structure 2042 can be wound or looped. In some configurations, the material for the internal structure 2042 can be non-stretch thread (e.g., natural fiber thread (e.g., cotton or wool) or synthetic thread), a low-stretch elastic member or the like. In some configurations, the internal structure
5 2042 can extend throughout the strap. In some configurations, the internal structure 2042 can be limited to specific regions in which adjustability might be desired.

[0123] In some configurations, the structure 2042 can be fully internal. In some configurations, such as shown in Figure 52, at least a portion of the structure 2042 can be raised to allow severing of the strap in locations underlying the raised structure
10 portions 2042. In some configurations, such as shown in Figures 53 and 54, the strap 2040 can include loops 2046 that restrain folded material until the loops 2046 are broken or cut, for example but without limitation. As shown in Figure 56, a folded region 2050 or the like can be provided with an extensible portion of the structure 2042 housed within the region 2050. When the region 2050 is separated from the portions of the strap 2040 to
15 either side, the structure 2042 connects the portions of the strap 2040 while facilitating expansion of the strap 2040. Separation can occur through cutting or axial forces applied along the length of the strap or within the segment of the strap where elongation is desired.

[0124] The segments 2044 can be connected or connectable together. The
20 segments 2044 resist stretching of the straps 2040. Accordingly, in some configurations, at least a portion of each of the multiple segments 2044 can be secured to at least a portion of the strap 2040 in some suitable manner. When two adjacent segments 2044 are separated, the strap 2040 can be stretched in locations between the segments 2044. In some configurations, when the two adjacent segments 2044 are separated, the strap 2040
25 can be stretched between the location points on the strap 2040 at which the strap 2040 is secured to the segments 2044.

[0125] In some configurations, such as shown in Figures 49-50, the internal structure 2042 can be snapped or broken into segments 2044 in order to increase the stretch of the strap 2040. In some configurations, the internal structure 2042 can be
30 stitched into the head strap 2040 and thereby limit the initial amount of stretch available. The internal structure 2042 can include a series of sections 2044 that, when pulled with a predetermined force or bent with a predetermined force or some combination of the two, will separate at a snap point 2048, for example but without limitation. In some

configurations, the snap points 2048 will snap and permanently add a small amount of stretch to the head strap 2040. By providing multiple snap points 2048 across several sections of the head strap 2040, the strap can dramatically increase elasticity. While the illustrated configurations illustrate single straps 2040, the same structure also can be used
5 in multiple strap headgear.

[0126] To assist with locating the snap points, visual snap point indicator can be used. The indicators can be graphical representations. The graphical representations can indicate to the user the areas of the head gear that are appropriate to snap

[0127] It is believed that users prefer the simplicity of not only having a single
10 strap head gear but also not having numerous tabs that need to be adjusted time and time again for a desired fit. This poses a challenge in how to create one single strap that fits the large variation between head circumferences of the smallest and biggest size of users. By incorporating an 'invisible' adjustment such as those described above, a greater number of users can be accommodated in a way that adds little or no additional structure, tabs or
15 buckles.

Headgear Incorporating a Tie Down and Strap Management System

[0128] With reference now to Figures 57-62b, a single strap head gear 2100 is shown with a tie down and strap management system 2102 that is arranged and configured in accordance with certain features, aspects and advantages of the present
20 invention.

[0129] As used herein, a tie down 2102 can be a strap management system that allows a single strap head gear 2100 to be folded back onto itself via a loop point, buckle or the like 2104. As illustrated, the strap 2100 can be folded back at a component that is integrated into the interface or mask assembly 2106 or the strap 2100 can be folded back
25 at a component that is separate from or separable from the interface or mask assembly 2106, such as a hook, clip, connector or the like (see Figure 58b, for example).

[0130] The strap 2100 can then be locked at a specific point providing less or more length via a buckle (e.g., Figure 58a, 58b or 59a) or spring loaded mechanism (e.g., Figure 59b, and Figures 60a-60d). In the illustrated configurations, the buckle 2110
30 and/or the spring loaded mechanism 2112 can be provided with serrations, teeth or the like 2114 (see Figure 59b) to provide added grip on the strap 2100. In some configurations, as shown in Figures 60a-60d, a lever 2116 can be used to secure the strap 2100 in position. In some configurations, the lever 2116 can be biased by a spring

member 2118. In some configurations, the lever 2116 can have a resilient configuration such that no spring member is required and the lever 2116 is simply a cantilevered member. In some configurations, the lever 2116 rotates about a shaft 2120. In some configurations, the mechanism resists movement of the strap 2100 in a first direction but
5 generally allows movement of the strap 2100 in a second opposite direction.

[0131] As used herein, a loop point is a point at which the head strap 2100 can be folded back on itself. This can be built into the mask, into the seal or and through an additional buckle or the like.

[0132] As used herein, a grip point 2122 is a rigid and/or semi-rigid material
10 that is placed on the strap 2100 to facilitate gripping during adjustment of the strap 2100.

[0133] As illustrated in Figures 61a-61c, the length of the strap 2100 that is positioned between a slider 2124 and the loop point can be adjustable. The slider 2124 can move along the strap 2100. In the illustrated configuration, the slider 2124 can be in contact with two overlapping segments of the strap 2100. The slider 2124 can have any
15 suitable configuration. As shown in Figures 62a-62c, the illustrated slider 2124 has a central member 2126 that depresses a portion of the strap 2100 and effectively locks the slider 2124 in position along the strap 2100.

[0134] By utilizing a tie down system, users are free to tweak their initial set up as and when desired at any future date. Accordingly, if the users face shape changes or
20 the elasticity of the strap weakens over years of use, there is still a suitable adjustment method to account for this.

Headgear Incorporating Stretch Limiting System

[0135] With reference now to Figures 63-69, a strap 2200 is illustrated that can incorporate an elastic head strap 2202 that uses buckles 2204. In the illustrated
25 configurations, two or more buckles 2204 and a relatively non-stretch component 2206 can be used to adjust the degree of stretch that can be provided along a length of a strap 2200.

[0136] In some configurations, such as illustrated in Figure 64, the non-stretch component 2206 can be a relatively (relative to the strap) non-stretch sleeve. The non-stretch sleeve has a length that is less than the stretch component (e.g., elastic strap). As
30 used herein, a non-stretch sleeve can be either an external sleeve (Figure 63) or an internal structure that has non-stretch properties (Figure 64) and that is used in conjunction with a stretchable head strap 2202.

[0137] In the illustrated configurations, one or more buckles, clips or the like 2204 can be used to increase or decrease the ability of the strap 2202 to stretch. In some configurations, two small buckles 2204 can be used to limit the amount of elastic deformation of the strap 2202 available to the user. Such configurations allow the users
5 to quickly and easily fine tune the forces that they experience when using the headgear 2200. In other words, the user is able to use the buckles, clips or the like 2204, to couple the relatively more stretchable portion to the relatively less stretchable portion in various locations. This allows the relatively less stretchable portion to resist stretching of the relatively more stretchable portion between the two buckles, clips or the like 2204. In
10 other words, as shown in Figures 67a-67c, moving together two clips 2204 that lock or otherwise secure together the relatively less stretchable component and the relatively more stretchable component will increase the length of relatively more stretchable strap 2202 available for stretching, which can increase the overall amount of stretch available to the user.

15 [0138] The buckles and clips can have any suitable configuration. In some configurations, the clips 2204 can be generally clam-shell in configuration. In some such configurations, such as shown in Figures 66a and 66b, the clips 2204 can fold closed and lock in a closed position. In some such configurations, the clips 2204 can include serrations or the like 2208 to define teeth or the like to help secure the clips 2204 in
20 position and to help hold the relatively non-stretch component to the relatively stretch component. In some configurations, the clip 2204 can include a member that slides along a slot defined within the relatively non-stretch component 2206. In some configurations, such as shown in Figures 65a and 65b, the clip 2204 can include a protruding component 2210 that extends inwardly through the slot and engages against the relatively stretchable
25 component 2202 to lock the relatively non-stretch component 2206 and the stretch component 2202 together. In some configurations, such as that shown in Figure 65a, the protruding component 2210 extends fully across an opening defined by the clip 2204. In some configurations, such as that shown in Figure 65b, the protruding component 2210 extends only partially across the opening such that the clip 2204 can be installed onto a
30 strap 2202 without having access to any end of the strap 2202. In some configurations and as shown in Figure 69, the illustrated configurations can be used in a tie-down arrangement or in conjunction with a tie-down arrangement such as those described above.

Headgear Incorporating Stretch Limiting System Using Push-Buttons/Domes

[0139] With reference now to Figures 70-76, a stretch limiting system 2300 is illustrated that incorporates an elastic head strap using limiters, such as push buttons, domes or the like, to limit stretch of the strap.

5 [0140] In the illustrated configurations, a generally non-stretch sleeve 2302 can be used to limit the stretch of the relatively more stretchable strap. The sleeve 2302 can be an external sleeve or an internal structure that can be used in conjunction with a relatively stretchable head strap. In some configurations, the sleeve 2302 can be an external sleeve that is formed in two or more separable pieces, such as that shown in
10 Figure 70. In some configurations, the sleeve 2302 can be formed of two or more separable pieces that can snapped or clipped together, such as that shown in Figure 70, for example.

[0141] In some configurations, push buttons, domes or the like 2304 can be positioned at predetermined spacing along the non-stretch sleeve 2302. An example of a
15 configuration of a push button 2304 is shown in Figure 71. As illustrated, there is a base portion 2306 and a head portion 2308. The base portion 2306 has a flange and the head portion 2308 has a flange. When engaged, the flanges interlock the base portion 2306 and the head portion 2308 together. Locking these buttons in specified patterns can increase or decrease the stretching capabilities of the strap and therefore create varying sizes for
20 each user.

[0142] In some configurations, such as that shown in Figures 73a, 73b, and 73c, the strap 2310 can include predetermined holes 2312 or hole spacing. In some configurations, the holes 2312 of the stretch limiting system 2312 are oversized such that material of the strap 2310 can be displaced into the holes of the stretch limiting system
25 2300 and secured therein by the button, dome or the like 2304. As described above, the further away from each other the outermost push buttons, domes or the like 2304 are that interlock the relatively non-stretch sleeve 2302 and the relatively stretchable strap 2310, the less of the relatively stretchable strap 2310 is available to stretch.

[0143] In some configurations, adjacent members, such as adjacent buttons, domes or the like 2304 can be connected by an internal lever release system, such as that
30 shown in Figure 72. In such configurations, pressing on a first member 2304 can cause movement of two adjacent members 2304. The interconnecting levers can pivot about a hinge point, a fulcrum or the like 2314.

[0144] In some configurations, the use of removable buckles, clips, or the like poses problems, such as being bulky, being additional components, and being components that can be broken or lost by the user. Accordingly, incorporating the dome, push buttons, and the like directly into the head gear can be used to remove one or more of these concerns. Built-in buttons also easily can be hidden and/or accounted for in the shaping of the head gear. In other words, the integrated buttons, domes or the like could be recessed in a way that would reduce or eliminate the likelihood of discomfort to the user during use (e.g., when laying on a pillow with the strap between the head and the pillow). In some configurations, the relatively non-stretch sleeve can be secured to the relatively stretchable strap in one or more locations. In some such configurations, the amount of control the relatively stretchable strap will be proportional to the distance from the connection point to the last available button, dome or the like.

Headgear Incorporating One-Time Setup Features

[0145] With reference now to Figures 77-81, a strap and clip configuration 2400 is illustrated that accommodates one-time set up of a strap 2402 for a headgear assembly.

[0146] As illustrated, a connector, such as a buckle or clip, 2404 can be configured to attach to a strap 2402. The clip or buckle 2404 can include a passage through which the strap 2402 can be threaded. With reference to Figures 78a-78c, the clip or buckle 2404 also can include a locking member 2406 that can allow the strap to be secured in position. For example, when positioned as shown in Figure 78b, the strap 2402 can be moved through the clip or buckle 2404. When the locking member 2406 is positioned as shown in Figure 78c, the strap 240 can be locked in position relative to the clip or buckle 2404. In some configurations, the strap 2402 can be locked at a specific position permanently.

[0147] In some configurations, the head strap 2402 comprises a single strap. In some configurations, the single strap 2402 initially can be provided with excess length to allow the user to feed it through the buckle or clip 2404 to a desired length. Once positioned as desired, the user can cut away the excess, such as with a pair of scissors for example but without limitation. Such a configuration has been illustrated in Figures 79a-79c.

[0148] In the some configurations, a living hinge 2408 (see Figure 77) can be provided between a first portion 2410 and a second portion 2412 of the clip or buckle

2404. The strap 2402 can be positioned between the two portions 2410, 2412 and the two portions can be secured together. With the strap 2402 positioned as desired and the two portions 2410, 2412 locked together, the excess strap can be removed.

[0149] In some configurations, the first portion 2410 and the second portion 2412 can be secured together but the strap 2402 can continue to be adjusted. In some configurations, a locking mechanism 2406, such as that described above, can be provided as a part of the buckle or clip 2404. In some configurations, the locking mechanism 2406 can include a push-button that can lock the buckle or clip 2404 in position along the strap 2402. In some configurations, the clip or buckle 2404 can include a hinge system 2414, such as that illustrated in Figures 80 and 81. In some configurations, the hinge system 2414 can lock onto the strap 2402 through a pivoting action. In some configurations, the hinge system 2414 allows that strap 2402 to be thread through the buckle or clip 2404 and exposed at a right angle such that the strap 2402 can be more easily trimmed.

[0150] By adding in a mechanism that initially allows for excess headgear to be provided and cut away by the user, the aesthetic or function of the single strap head gear can be better maintained while providing adjustability. Further, headgear incorporating one-time setup features may be useful in single-use applications, such as hospital patient treatment, where a single size of headgear may be stocked and fit to patients.

20 Screw Adjustment for Headgear and/or Mask Seal

[0151] With reference now to Figures 82-87, some screw adjustment mechanisms 2500 are illustrated that can be used to adjust one or both of the headgear 2502 and the mask seal 2504.

[0152] As used herein, a screw adjustment mechanism 2500 can be a mechanism that is positioned at a specific point either on the mask frame 2506 or on the seal component 2504 and that rotates around a central axis to result in adjustments to the fit of the headgear 2502 and/or seal 2504. In the illustrated configurations, the screw adjustment mechanism 2500 may be spring loaded to allow quick and easy retracting/extending of the head strap 2502. In some configurations, the screw adjustment mechanism 2500 could be positioned at one or more adjustment points.

[0153] As used herein, a head strap 2502 is a single or multiple strap head gear that is attached at specific points on the screw mechanism 2500. As the screw mechanism 2500 is turned by the user, the screw mechanism 2500 can wind or unwind the head strap

2502, thereby varying the size of the headgear assembly depending on the user's needs. As shown in Figure 85, in some configurations, the screw mechanism 2500 can be turned to expand the head strap length and the strap 2502 can be pulled to extract the additional length as desired. In some configurations, a single screw mechanism 2500 can be provided (see, e.g., Figure 86). In some configurations, multiple screw mechanisms 2500 can be provided (see, e.g., Figure 87). In some configurations, the screw mechanism 2500 can be provided on each side of the interface.

[0154] In some configurations, the screw mechanism 2500 provides a mechanical solution to the adjustability of the single strap head gear 2502. In some configurations, a large dial 2508 (see Figure 86, e.g.) can be provided directly in front or to the side of the face. The dial 2508 can allow users of all capability levels to easily be able to adjust the head strap to a desired size. For example, the dial 2508 can be twisted to expand or contract the length of the head strap 2502.

[0155] With reference to Figure 84, in some configurations, a spring-loaded mechanism 2510 can be provided. The spring-loaded mechanism 2510 can have any suitable configuration. In some configurations, the spring-loaded mechanism 2510 can allow the screw mechanism 2500 to self-adjust by simply being over-stretched and the spring 2512 allowed to then retract the strap 2502 into position around the users head. In some configurations, the strap 2502 can lock at certain points and can return to a retracted position upon over extension. Other configurations also can be provided.

Rack and Pinion Adjustment for Headgear and/or Mask Seal

[0156] With reference now to Figures 88-92, a rack and pinion system 2600 can be provided to adjust the fit of the strap 2602 and/or headgear. In some configurations, the ends of the strap 2602 can be provided with a rack configuration (e.g., teeth) 2604. In some configurations, at least one end of the strap 2602 can be secured to a member that includes teeth and that can serve the function of a rack. In some configurations, a knob 2606 or the like can be provided with teeth that can interlock with the teeth of the rack 2604. By rotating the knob 2606, the length of the strap 2602 can be adjusted.

[0157] In some configurations, rather than an actual rack and pinion system 2600 that incorporates meshing teeth, a similar function can be provided through a cord or wire winding mechanism 2608. Such a configuration is shown in Figure 90. A hook 2610 can be positioned on one or more end of the strap 2602. As the knob 2612 is turned,

the length of a cord, wire or the like 2614 can be adjusted and the hook 2610 causes the adjustment to be transferred, at least in part, to the headgear 2602. Other arrangements can be used to secure the headgear 2602 to the cord, wire or the like 2614.

[0158] Furthermore, in some configurations, assemblies 2616 can be provided that translate between vertical movement and horizontal movement or between pivotal movement and axial movement of the headgear 2602. In other words, in some configurations, a pivotal movement of a component to which the headgear is attachable can result in an adjustment of the length of the combined headgear and the component. Similarly, in some configurations, movement of one or more component toward each other can result in retraction and extension of the attached headgear. Two such configurations are illustrated in Figures 91 and 92. In Figure 91, one or more pivoting elements 2618 control relative movement between two elements that are connected to the headgear. In Figure 92, two elements 2620 that move toward and away from each other can cause relative movement between two elements that are connected to the headgear.

15 Archimedes Screw Adjustment for Headgear and/or Mask Seal

[0159] With reference now to Figures 93-98, an assembly 2700 is provided that can cause movement of a mask seal 2702 relative to a mask frame 2704, or relative to a headgear assembly 2706, for example but without limitation.

[0160] As used herein, a bridge or a bracket 2708 can be a component that creates a predetermined, consistent distance between the users face and the mask/seal 2704/2702. The Archimedes screw 2710 can be attached to the bracket 2708 to provide an adjustment point between the bracket 2708 and the mask seal 2702, as shown in Figure 94. Advancing and retracting the screw mechanism 2710 directly increases and decreases the force at which the mask seal 2702 is pressing against the users face. The adjustment point can be a ring 2712 that is attached to the Archimedes screw 2710. The ring 2712, when rotated, can advance and retract the screw mechanism or assembly 2700.

[0161] Accordingly, because interface designs are designed for the masses, the Archimedes screw mechanism or assembly 2700 can allow fine-tuning of the fit of the interface designs. Thus, more control can be provided for users to adjust the device to better suit their needs or desires.

30 Snap-On Adjustment for Headgear and/or Mask Seal

[0162] With reference now to Figures 99-102, a further strap adjustment assembly 2800 is shown. In the illustrated configuration, the strap length can be adjusted

by creating a loop with the headgear and then using a suitable assembly to adjust the length of the head strap.

[0163] In some configurations, a bracket 2802 can be formed that is attached to the interface or mask assembly while a locking member 2804 can be connected to at least one end of the strap 2806. The bracket 2802 can include a plurality of connecting points 2808 and the locking member 2804 can connect at each of the connecting points 2808; depending upon selected connecting point 2808, the length of the strap 2806 can be adjusted. In such a configuration, a 1:1 adjustment between the strap length and the positioning on the mask frame can result.

[0164] In some configurations, such as that shown in Figure 102, a multiplier 2810, such as a pulley, turnbuckle or the like, can be positioned along the strap 2806 between the ends. In some configurations, such as that shown in Figure 100, the end connectors for the strap 2806 can have a multiplier 2810 in the form of a hinged structure (e.g., a watch band) with the end being adjustable to adjust the length. As shown in Figure 101, the hinged structure 2810 can be folded into a receptacle formed in the bracket 2802. In such configurations, the hinged structure 2810 can be secured into one or more of the connecting points 2808 of the bracket 2802. Thus, in such configurations, a smaller adjustment at the frame region can result in a larger adjustment to the headgear strap (e.g., 2:1).

Hook Adjustment for Headgear and/or Mask Seal

[0165] With reference to Figure 103, a strap 2900 can include a small loop 2902 formed at the end. In some configurations, the loop 2902 can be secured to the strap end 2900 with a small fitting 2904. In some configurations, the loop 2902 and strap end fitting 2904 approximate a camera strap.

[0166] The mask frame or interface assembly 2906 can include a member with a plurality of hooks 2908. The loop 2902 can be passed over any of the hooks 2908 as desired to provide different levels of adjustment. In some configurations, the hooks 2908 are formed on an inside of the mask. In such configurations, the hooks 2908 and adjustment features are obscured from view, thereby creating a clean look while facilitating an adjustable configuration.

Over-Center Pinch Adjustment for Strap

[0167] With reference too Figures 104-107c, the strap length can be adjusted using an over-center pinch assembly 3000. The figures illustrate a series of mechanisms

based on changing the effective length of a strap 3002 by forming a sub-loop 3004 and fixing its position with a clamp 3006. Figure 104 illustrates a simple folded over strap with an over-center pinch clip used to secure the length of the strap 3002. The strap is secured to the clamp 3006 at a fixing location 3010. Figure 105 illustrates a construction that is similar to that shown in Figure 104 but the configuration of Figure 105 includes a multiplier such that a 2:1 adjustment ratio results. In Figure 105, the strap 3002 is secured to the mask frame 3012 or the like at a fixing location 3010. Other configurations also are possible.

[0168] Figures 106 and 107a-107c illustrate a continuous loop headgear 3014. To adjust the effective length of the headgear, a sub loop 3016 is formed and folds back on itself. The position can be fixed with any suitable clamp 3018, for example. In some configurations, the clamp 3018 can be an over center clamp. Figures 107a-107c illustrate the effect of using various sizes of sub loops 3016 on the overall headgear size.

Scissor Linkage Strap Adjustment

[0169] With reference now to Figures 108 through 110c, a scissor link system 3100 is illustrated. The scissor link system 3100 can comprising a plurality of matched sets of pivoting arms 3104. Both of the arms of each set can be linked together and each of the sets can be linked together. Other configurations are possible.

[0170] The scissor link system 3100 allows varying degrees of adjustability based on whether the links have been expanded or contracted, as illustrated in Figures 109a-109c. It is envisaged that this could be a large mechanical type mechanism, or could be scaled down much further to the point where the device functions the same but may not be apparent to the naked eye how this works.

[0171] In some configurations, the scissor link system 3100 includes an adjustment mechanism 3102, as shown in Figures 110b, 110c. The adjustment mechanism 3102 can include a button or a glider that, when adjusted, will directly affect the level of compression or extension in the scissor link system 3100. Because of the mechanical nature of the adjustment, there is much greater control over the amount of adjustment, the ease of adjustment and the strength of materials compared to the configurations discussed above.

[0172] In some configurations, the adjustment mechanism 3102 and the scissor link system 3100 is configured such that each of the scissor arms will experience a generally equal adjustment throughout the assembly 3100. In some configurations,

however, different sections of the assembly 3100 can be adjusted with different degrees of expansion or compression. For example, as shown in Figures 110a and 110b, one end may remain generally compressed while the other end may be more fully expanded.

[0173] In some configurations, such as that shown in Figure 110c, the scissor link system 3100 can include a member 3102 that allows for the adjustment to be locked. In some configurations, the adjustment member (or locking member) 3102 can be positioned at each end of the scissors mechanism (e.g., Figure 110b). In some configurations, the adjustment member (or locking member) 3102 can be positioned at only one end (e.g., Figure 110c). In some configurations, the adjustment member (or locking member) can be used to adjust one linkage, which can result in adjustment to the rest of the linkages. In some configurations, the adjustment member (or locking member) can be a push-button or the like. Other configurations are possible.

Fine Tuning Adjustment for Scissor Link

[0174] With reference now to Figures 111-114, several additional scissor link systems 3200 are shown. The illustrated configurations provide for more finely tuned adjustments.

[0175] As described above, a scissor link system 3200 allows varying degrees of adjustability based on whether the links 3202 have been expanded or contracted. In some configurations, one or more of the links 3202 can be biased using a spring 3204 or another suitable biasing member. In some such configurations, an extension spring 3204 can apply a force (e.g., a constant force) on the scissor links 3202 in order retract the links 3202 as and when required or desired by the user.

[0176] In some configurations, a threaded member 3206 can be used in order to expand or contract the links 3202 via the twist knob or push button 3208. In such configurations, for example, a bracket 3210 can be used to maintain a distance between the threaded member 3206, the associated link 3202 and one or more tracks 3212. As used herein, tracks 3212 can be slots, grooves, protrusions or that like that can be formed on or the scissor links 3202, which, in combination with the bracket 3210 and threaded member 3206, allow the links 3202 to smoothly retract and expand. In some configurations, movement of the threaded member 3206 can be directed using a twist knob 3208 or the like. For example, in some configurations, the knob 3208 or button can be used to twist, push or pull the threaded member 3206 forward and backward, which results in the scissor links 3202 expanding and retracting. Other suitable configurations

also can be used. For example, in some configurations, such as that illustrated in Figures 113 and 114, an external thread 3214 can generally enclose two of the links 3202 or the links 3202 can have a threaded surface 3214. In such configurations, turning the knob 3208 causes the knob 3208 to advance along the links 3202 and to compress the links 3202 toward each other (because the internally threaded portion of the knob 3208 does not change sizes).

[0177] The illustrated configurations provide greater control over the level of adjustment to the headgear via the scissor link system 3200. In some configurations, a visual indicator can be provided showing a specific setting (e.g., 1-10). The visual indicator would allow users to quickly and easily set up the head gear after cleaning and/or would allow users to match existing settings when they replace the head gear in the future.

Adjustment for Headgear and/or Mask Seal

[0178] With reference now to Figures 15-16h, an arrangement featuring a hook and loop fastener based limiting/locking system 3300 is illustrated. As used herein, a hook tab 3302 is a tab specifically designed to increase the difficulty of removing the strap 3304 in question. This system 3300 provides adjustment to users who are trained in its use and makes it more difficult for users who are not. As used herein, a loop head strap 3304 means a loop material for the hook 3302 to grab onto and lock in place.

[0179] In some headgear configurations, the headgear can require a one-time set up by a sleep tech or other experienced person. Following the one-time set up, it is intended that such headgear not be readjusted by the user. The one-time set up poses a problem in how to create a method of adjustment that can be adjusted by one person but not another. By utilizing a more complex adjustment method such as the hook tab 3302 proposed, trained/experienced users will easily be able to make the adjustment, while the difficulty in doing so for others not trained will deter them from using it and instead direct them to use other adjustment methods provided.

[0180] In some configurations, the hook tab 3302 comprises a forked configuration with at least one recessed region 3306. In some such configurations, the hook tab 3302 comprises a plurality of fingers 3308. The plurality of fingers 3308 need to be raised simultaneously in order to release the hook tab 3302 from the underlying loop material of the strap 3304, for example but without limitation. A variety of tab configurations are illustrated in Figures 115 and 116a-116i. In many of the

configurations, one or more of the fingers 3308 extends further along the strap 3304 than others of the fingers. In some of the configurations, one or more of the fingers 3308 is at least partially circumscribed by another of the fingers 3308. In some of the configurations, one or more of the fingers 3308 is fully circumscribed by another of the
5 fingers 3308. In some configurations, for example, Figure 116i, the fingers are not circumscribed but, rather, the hook tab 3303 comprises a wide free end 3310 connected to a second portion 3312 via a narrow section 3314 with the fingers 3308 being located on one or both sides of the narrow section 3314 having fingers 3308 on either or each side.

[0181] Unless the context clearly requires otherwise, throughout the
10 description and the claims, the words “comprise”, “comprising”, and the like, are to be construed in an inclusive sense as opposed to an exclusive or exhaustive sense, that is to say, in the sense of “including, but not limited to.”

[0182] Where, in the foregoing description reference has been made to
15 integers or components having known equivalents thereof, those integers are herein incorporated as if individually set forth.

[0183] The invention may also be said broadly to consist in the parts, elements and features referred to or indicated in the specification of the application, individually or collectively, in any or all combinations of two or more of said parts, elements or features.

[0184] Reference to any prior art in this specification is not, and should not be
20 taken as, an acknowledgement or any form of suggestion that that prior art forms part of the common general knowledge in the field of endeavour in any country in the world.

[0185] Certain features, aspects and advantages of some configurations of the present disclosure have been described with reference to use by a patient or user. However, certain features, aspects and advantages of the use of the headgear and/or straps
25 as described may be advantageously practiced by other people on behalf of the patient, including medical professionals, medical device dealers, or medical device providers. Certain features, aspects and advantages of the methods and apparatus of the present disclosure may be equally applied to usage by other people.

[0186] Although the present disclosure has been described in terms of certain
30 embodiments, other embodiments apparent to those of ordinary skill in the art also are within the scope of this disclosure. Thus, various changes and modifications may be made without departing from the spirit and scope of the disclosure. For instance, various components may be repositioned as desired. Moreover, not all of the features, aspects and

advantages are necessarily required to practice the present disclosure. Accordingly, the scope of the present disclosure is intended to be defined only by the claims that follow.

WHAT IS CLAIMED IS:

1. Headgear for a breathing interface, the headgear comprising at least the one strap, the at least one strap having a customizable stretch characteristic, wherein the at least one strap incorporates a stretch component, a relatively non-stretch member and two or more buckles that interconnect the at least one strap and the relatively non-stretch member, and wherein the two or more buckles are adjustable along a length of the relatively non-stretch member.
2. The headgear of Claim 1, wherein the stretch component has a greater length than the relatively non-stretch member.
3. The headgear of Claim 1 or Claim 2, wherein the two or more buckles are adjustable such that an intermediate length of the stretch component disposed between the two buckles can be varied.

4. The headgear of any of the preceding Claims, wherein adjusting the spacing between the two or more buckles adjusts the amount of the stretch component that is secured to the relatively non-stretch member and, therefore, unable to stretch.

5. The headgear of any of the preceding Claims, wherein the relatively non-stretch component comprises a hollow portion through which the stretch component passes.

6. The headgear of Claim 5, wherein the two or more buckles attach to the non-stretch component with the stretch component being secured within the non-stretch component.

7. Headgear for a breathing interface, the headgear comprising at least the one strap, the at least one strap having a customizable stretch characteristic, wherein the at least one strap incorporates a stretch component, a relatively non-stretch member and two or more limiters that interconnect the at least one strap and the relatively non-stretch member, and wherein the nonstretch member comprises two or more apertures that receive the two or more limiters and the stretch member comprises two or more apertures.

8. The headgear of Claim 7, wherein the stretch component has a greater length than the relatively non-stretch member.

9. The headgear of Claim 7 or Claim 8, wherein the nonstretch member comprises at least three openings and the stretch component comprises at least three openings.

10. The headgear of any of Claims 7-9, wherein the two or more apertures of the non-stretch member have a first spacing and the two or more apertures of the stretch member have a second spacing.

11. The headgear of Claim 10, wherein the second spacing is the same as the first spacing.

12. The headgear of Claim 10, wherein the second spacing is different from the first spacing.

13. The headgear of Claim 12, wherein the second spacing is less than the first spacing.

14. The headgear of any of Claims 7-13, wherein the two or more limiters are connected for movement.

15. The headgear of Claim 14, wherein a hinge connects two adjacent limiters such that depressing one causes a lifting of the other.