

9

Description

The invention relates to a pillow comprising a core formed of cushion material and being inserted into a hollow body and comprising a plurality of heat conducting means attached to the surface of the core.

From the US—A—4,330,892 a pillow of this type is known having a plurality of magnets fixedly arranged on the surface of the core.

From the US—A—3,885,259 a cushion is known which is provided at the top sheet of the cover with a large number of thermally conductive buttons made from a ceramic material.

Sleeping is indispensably important for overcoming fatigue or tiredness. For sound sleep, not only bedding but also the pillow has a great influence. "Keeping the head cool and the feet warm" has been said to be a first condition for obtaining comfortable sleep. This is correct from the scientific view, too. Thus medical data reports that the mind is relaxed and a person may go into a state of natural sleeping by lowering the temperature of the pillow by about 5 to 10°C lower than the temperature of the back of the head (around 35°C). Further the size and the height of the pillow is closely related to peaceful sleep. Thus, a difference of more than 20 minutes arises until deep sleep occurs between pillows suitable and not suitable for sound sleep. Differences also occur in awareness at the time of waking up. Although a pillow gives a great influence to one's sleep, an ideal pillow has not appeared so far.

It is the object of the invention to provide a pillow of the above mentioned type with which sleep is naturally obtained.

For this purpose, the pillow according to the present invention is characterized in that the heat conducting means are porcelain tiles, said hollow body having permeability and elasticity, said hollow body being formed of a flexible urethane foam, the outer surface of which is harder than the remainder of said flexible foam, said porcelain tiles being maintained in position on the surface of said core via at least one spacer consisting of a plate having a shape corresponding to at least one space between the porcelain tiles, said at least one spacer being located on said core between adjacent porcelain tiles.

The pillow according to the present invention absorbs heat and reduces the temperature at the back of the head so that the condition of keeping the head cool and feet warm is maintained during sleeping.

The pillow according to the present invention has a most suitable height and hardness to provide peaceful sleep, so that ideal sleeping posture may be obtained.

Specific embodiments of the pillow according to the present invention are constructed as it is claimed by the patent claims 2 to 7.

An embodiment of the pillow according to the present invention will be described in the following with reference to the drawing.

Fig. 1 is a perspective view, partially in section,

showing an embodiment of the pillow according to the present invention, taking out stuffed material, and

Fig. 2 is a vertical cross-sectional view showing the inner structure.

An embodiment of the pillow according to the invention is obtained by inserting cushion material 3 having porcelain tiles on its surface into a bag body 1 made of urethane foam. The bag body 1 is made of the cushion material, preferably urethane foam where wave-like projections 5 are formed regularly lengthwise and crosswise on the urethane foam 4 of about 150 mm in thickness, and resin liquid such as liquid of urethane foam is impregnated thereon to form said bag of a had outer cover 6.

For the cushion material, thick urethane foam is in general employed, on a surface of which six, e.g. flat porcelain tiles 2 are fixed with adhesives, and at least one spacer 7 is arranged to stop movement of the tiles.

For the spacer 7 at least one plastic plate is used which runs lengthwise and crosswise in the spaces between the porcelain tiles 2, otherwise urethane foam pieces may be used which are hardened by impregnating same with resin liquid. Such one or more spacers 7 are fixedly positioned on determined parts of the cushion material 3, and subsequently the porcelain tiles 2 are attached to the cushion material 3, or after having attached the porcelain tiles 2, the one or more spacers 7 are positioned in place at the spaces between the tiles 2. The cushion material 3 having the tiles 2 is inserted into the bag body 1, and the bag body 1 is closed at its mouth. In use, the bag body 1 is protected with a suitable cloth cover.

The pillow according to the invention has the above structure and many advantages as follows:

1) It provides a natural sleeping posture thereby inducing peaceful sleep.

The combination of the concaves and convexes (wave-like projection) and the porcelain tiles keeps the shape of the pillow stable. Therefore the pillow moves little as do conventional pillows so that comfortable sleep may be obtained all night long.

2) It provides a good height for natural sleeping posture. Conventional pillows are often too high thereby causing muscles at the neck or the shoulders to become stretched with the result of stiffness occurring there. If a pillow is too low, conversely the neck is tense and sleep is insufficient to eliminate fatigue. The pillow of the invention makes the mind relaxed and is about 8 cm in height.

3) It keeps the head cool with the porcelain tiles while the feet are kept warm.

4) It is hygienic by air permeability and evaporation.

The permeable material such as the urethane foam is used and formed with concaves and convexes due to the wave like projections. The shape is held and the permeability is maintained.

Claims

1. A pillow comprising a core (3) formed of cushion material and being inserted into a hollow body (1) and comprising a plurality of heat conducting means (2) attached to the surface of the core (3) characterized in that the heat conducting means are porcelain tiles (2) said hollow body (1) having permeability and elasticity, said hollow body (1) being formed of a flexible urethane foam, the outer surface of which is harder than the remainder of said flexible foam, said porcelain tiles (2) being maintained in position on the surface of said core via at least one spacer (7) consisting of a plate having a shape corresponding to at least one space between the porcelain tiles, said at least one spacer (7) being located on said core (3) between adjacent porcelain tiles (2).

2. A pillow according to claim 1 characterized in that said urethane foam hollow body (1) has wave-like projections (5) formed regularly lengthwise and crosswise thereon.

3. A pillow according to claim 2 characterized in that said hollow body (1) is provided with its harder outer surface by impregnating said urethane foam with a resin liquid.

4. A pillow according to claim 1 characterized in that the core (3) comprises thick urethane foam.

5. A pillow according to claim 1 characterized in that said at least one spacer plate (7) is formed of plastic.

6. A pillow according to claim 5 characterized in that said at least one plastic spacer plate (7) is of urethane foam hardened by impregnation with resin liquid.

Patentansprüche

1. Matratze mit einem Kern (3) aus einem Polstermaterial, der in einen Hohlkörper (1) eingelegt ist, und mit einer Vielzahl von wärmeleitenden Einrichtungen (2), die an der Oberfläche des Kerns (3) angebracht sind, dadurch gekennzeichnet, daß die wärmeleitenden Einrichtungen Porzellanfliesen (2) sind, der Hohlkörper (1) eine Permeabilität und Elastizität hat, der Hohlkörper (1) aus einem flexiblen Urethanschaum gebildet ist, dessen Außenfläche härter als der Rest des flexiblen Schaumes ist, die Porzellanfliesen (2) in ihrer Lage auf der Oberfläche des Kernes über wenigstens einen Abstandhalter (7) gehalten sind, der aus einer Platte mit einer Form besteht, die wenigstens einem Zwischenraum zwischen den Porzellanfliesen entspricht, und der wenigstens eine Abstandhalter (7) auf der Kern (3) zwischen benachbarten Porzellanfliesen (2) angeordnet ist.

2. Matratze nach Anspruch 1, dadurch gekennzeichnet, daß der Hohlkörper (1) aus Urethanschaum wellenartige Vorsprünge (5) aufweist,

die regelmäßig darauf in Längsrichtung und in Querrichtung ausgebildet sind.

3. Matratze nach Anspruch 2, dadurch gekennzeichnet, daß der Hohlkörper (1) mit einer härteren Außenfläche dadurch versehen ist, daß der Urethanschaum mit einer Harzflüssigkeit imprägniert ist.

4. Matratze nach Anspruch 1, dadurch gekennzeichnet, daß der Kern (3) einen dicken Urethanschaumstoff umfaßt.

5. Matratze nach Anspruch 1, dadurch gekennzeichnet, daß die wenigstens eine Abstandshalterplatte (7) aus einem Kunststoffmaterial gebildet ist.

6. Matratze nach Anspruch 5, dadurch gekennzeichnet, daß die wenigstens eine Kunststoffabstandshalterplatte (7) aus Urethanschaum besteht, der dadurch gehärtet ist, daß er mit einer Harzflüssigkeit imprägniert ist.

Revendications

1. Oreiller comprenant un noyau (3) constitué par un matériau de rembourrage et inséré dans un corps creux (1), ainsi qu'une pluralité de moyens thermoconducteurs (2) fixés à la surface du noyau (3), caractérisé par le fait que les moyens thermoconducteurs sont des carreaux de porcelaine (2), ledit corps creux (1) étant doué de perméabilité et d'élasticité, ce corps creux (1) étant formé d'une mousse d'uréthane flexible dont la surface externe est plus dure que le reste de cette mousse flexible, lesdits carreaux de porcelaine (2) étant maintenus en place sur la surface dudit noyau par l'intermédiaire d'au moins une pièce d'espacement (7) constituée d'une plaque ayant une forme correspondant à au moins un espace entre les carreaux de porcelaine, ladite pièce d'espacement (7) prévue au minimum étant disposée, sur ledit noyau (3), entre des carreaux de porcelaine adjacents (2).

2. Oreiller selon la revendication 1, caractérisé par le fait que ledit corps creux (1) en mousse d'uréthane présente des protubérances ondulées (5), qui y sont formées régulièrement dans les sens longitudinal et transversal.

3. Oreiller selon la revendication 2, caractérisé par le fait que ledit corps creux (1) est muni d'une surface externe plus dure en imprégnant ladite mousse d'uréthane d'une résine liquide.

4. Oreiller selon la revendication 1, caractérisé par le fait que le noyau (3) consiste en de la mousse d'uréthane épaisse.

5. Oreiller selon la revendication 1, caractérisé par le fait que ladite plaque d'espacement (7) prévue au minimum est constituée d'une matière plastique.

6. Oreiller selon la revendication 5, caractérisé par le fait que ladite plaque d'espacement (7) en matière plastique prévue au minimum consiste en de la mousse d'uréthane durcie par imprégnation avec une résine liquide.

