

Description

BACKGROUND OF THE INVENTION

In general, the present invention relates to the field of ordinance and, more specifically, to non-lethal ammunition used in training and war games.

FIELD OF THE INVENTION

Normal automatic and semi-automatic weapons are actuated conventionally either by the expansion of propellant gas against a piston connected to the recoiling bolt mass or by direct blowback of the cartridge case against the bolt upon expansion of the propellant gas during the ballistic cycle of the ammunition. In these systems, the energy provided to the recoil mechanism is somewhat dependant on that imparted to the projectile. That is, a reduced pressure in the chamber or variations in weight of the projectile will result in variation in the total energy given to the weapon-operating mechanism which, in turn, will affect its cyclic rate or the reliability of its operation. With low-mass projectiles or the type used in training and non-lethal ammunition, the problem is especially severe. Frangible projectiles may not be capable of withstanding high accelerations. The low energy required for launch of these lightweight projectiles may not produce a sufficient reaction or necessitate a high enough chamber pressure to cycle conventional weapon mechanisms. Blank ammunition, that is, a cartridge without a projectile, will not normally be able to cycle a weapon without a muzzle adapter to increase the pressure in the system sufficiently to make the mechanism function.

The problem may also be observed in larger caliber guns, such as 40 mm grenade launchers, where a relatively low-velocity projectile with limited capacity to withstand high accelerations, is launched from an automatic gas-operated weapon. Prior attempts to achieve reliable weapon function, along with low-peak projectile acceleration have included "high-low" ballistic systems wherein propellant is initially burned in a high-pressure section of a partitioned cartridge case and released through orifices into the side containing the projectile at a rate sufficient to limit the peak pressure or acceleration on the projectile. Such a system is described in U.S. Patent No. 4,686,905 (Szabo). While such systems can provide reduced peak forces available for weapon function, necessitating design compromises in the weapon.

A similar device is disclosed in AT-B-357 445, upon which the pre-characterising portion of claim 1 is based.

SUMMARY OF THE INVENTION

The primary object of this invention is to provide

an ammunition configuration which will provide a more constant impulse to a weapon-cycling mechanism to assure its reliable function independent of the energy imparted to the projectile or even whether a projectile is present. This will permit the launching of low mass or acceleration-sensitive projectiles without exceeding their limitations or the firing of a blank cartridge while still providing reliable cycling of the weapon.

It is a further object of this invention to provide these functions in a conventional blowback-type of weapon with a minimum of changes to the weapon itself, permitting it to fire at reduced velocity, frangible or non-lethal or blank ammunition while still functioning in a normal manner.

It is a still further object of this invention to provide a means for cycling a weapon which uses an ammunition design compatible with existing manufacturing processes to minimize cost and make maximum use of existing production facilities.

These and other objects of the invention are achieved by the provision of a cartridge for low-mass, frangible projectiles which comprises a cartridge case having a primer at its base and a sabot or piston at its mouth. The sabot acts as a "shoe" or holder for the projectile. It is also present in the case of a blank variant of the invention wherein, as in the projectile version, it serves as a plug and piston in the end of the cartridge casing. While the description that follows refers to this component as a "sabot" in order to demonstrate the invention, in its broader characterization, this component of the cartridge of the invention may be called a plug - and will be claimed as such.

The sabot terminates with an outer annular shoulder that can thrust against a complementary, inwardly-formed step or inclined shoulder formed at the end of the chamber of a fire arm around the entrance to the barrel. The sabot is slideably contained within the cartridge case with a sealed engagement which permits little gas flow therebetween. The sabot can be provided with the longitudinal orifices, diagonal orifices, flutes, or any combination of orifices and flutes to provide a path for propellant gas from the volume of the case behind the sabot to flow to the rear of the projectile, and thence to the barrel of the gun. The projectile is inserted into a cylindrical recess in the front portion of the sabot. The orifices are in communication with this recess to permit propellant gas to bleed through and accelerate the projectile upon ignition. The amount of energy imparted to the projectile can be adjusted by varying the size of the orifices.

Upon ignition of the primer the cartridge casing, and/or the amount of propellant associated with the primer which is free to be displaced rearwardly, is so displaced under pressure from the exploding propellant. By reason of such rearward displacement, momentum is imparted to the breech block sufficient to

cycle the weapon. The case and the sabot can be provided respectively with a crimp and a stepped portion in order to limit travel of the cartridge case with respect to the sabot.

The invention is claimed in claim 1 and in sub-claims 2-11.

A better understanding of the disclosed embodiments of the invention will be achieved when the accompanying Detailed Description is considered in conjunction with the appended drawings, in which like reference numerals are used for the same parts as illustrated in the different figures.

BRIEF DESCRIPTION OF THE DRAWINGS

Figure 1 is a side elevational view of a cartridge in accordance with a first embodiment of the invention;

Figure 2 is a cross-sectional view of the cartridge of Figure 1, taken along line 2-2 of Figure 1;

Figure 3 is a cross-sectional view of the cartridge of Figure 1, taken along line 3-3 of Figure 2;

Figure 4 is a side elevational view of a cartridge in accordance with a second embodiment of the invention;

Figure 5 is a cross-sectional view of the cartridge of Figure 4, taken along line 5-5 of Figure 4;

Figure 6 is a cross-sectional view of the cartridge of Figure 4, taken along line 6-6 of Figure 5;

Figure 7 is a side elevational view of a cartridge in accordance with a third embodiment of the invention.

Figure 8 is a cross-sectional view of the cartridge of Figure 7, taken along line 8-8 of Figure 7.

Figure 9 is a cross-sectional view of the cartridge of Figure 7, taken along line 9-9 of Figure 8.

Figure 10 is a cross-sectional view of the cartridge of Figure 7, taken along line 10-10 of Figure 8.

Figure 11 is a cross-sectional view of a cartridge in accordance with a fourth embodiment of the invention.

Figure 12 is a cross-sectional view of the cartridge of Figure 11, taken along line 12-12 of Figure 11.

Figure 13 is a cross-sectional view of a cartridge in accordance with a fifth embodiment of the invention.

Figure 14 is a cross-sectional view of the cartridge of Figure 13, in the fired position.

Figure 15 is a side elevational view of a cartridge in accordance with a sixth embodiment of the invention.

Figure 16 is a cross-sectional view of the cartridge of Figure 15, taken along line 16-16 of Figure 15.

Figure 17 is a cross-sectional view of the cartridge of Figure 15, taken along line 17-17 of Figure 15.

ure 16.

DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENTS

In describing the preferred embodiments of the subject invention illustrated in the drawings, specific terminology will be resorted to for the sake of clarity. However, the invention is not intended to be limited to the specific terms so selected, and it is to be understood that each specific terms includes all technical equivalents which operate in a similar manner to accomplish a similar purpose.

A first embodiment of a cartridge in accordance with the present invention is depicted generally in Figure 1 through 3. The cartridge 10 comprises a cartridge case 12 containing a primer 14 in the base or head 16 of the case 12 to provide ignition and/or propulsion energy. A conventional propellant 20 may optionally be located within the case cavity 22 to provide the required propulsion energy if the energy of the primer 14 is insufficient to sufficiently excite the weapon and propel the projectile (if included). A flange 24 or crimp 24 can be provided at the mouth or forward end 26 of the case for a purpose to be described hereinafter. An extraction groove 28 is conventionally provided adjacent base 16 for use in the ejection process. Alternatively, a conventional flange (not shown) can be provided.

A one-piece piston or sabot 30 having forward 80 and rearward 72 ends, is inserted in the mouth 26 of cartridge case 12. The outer diameter of at least a portion of the rear portion 32 of sabot 30 is substantially equal to the inner diameter of wall 34 of case 12 to fit snugly and sealingly against the inner surface of wall 34 of case 12, restraining the escape of the propellant gas. The rear portion 32 can be formed with one or more additional portions having sidewalls 81 of decreased diameter, i.e., a diameter less than the inner diameter of wall 34, for the purpose to be described hereinafter. The forward portion 40 of the sabot 30 is larger in diameter than the rear portion 32, being substantially equal to the outer diameter of wall 34, to fit snugly in the chamber 102 of the gun (see Figure 14).

Longitudinal orifices 44 extend through the rear portion 32 of the sabot 30, opening into and terminating at a cylindrical axial recess 46 formed in the sabot 30 at the forward end 80 of the rear portion 32, to provide a path or gas passage means 44 for propellant gas from the larger area of cavity 22 within the case 12 to the forward end 80 of the sabot 30, rearwardly of the projectile 60, and thence to the barrel of the gun. As shown in Figures 2 and 3, there are two orifices 44 equidistant from the longitudinal axis of sabot 30 and parallel with the longitudinal axis and each other. However, the precise positioning and number of orifices 44 is not considered to be critical.

For example, although two orifices may be provided for balance, it is possible to use a single orifice, located axially or elsewhere.

An inward step 48 defined by the transition between the portions of differing diameter can be formed in the sidewall 81 of the rear portion 32 of sabot 30 rearwardly of and spaced-apart from the front portion 40, for a purpose to be described hereinafter. The projectile 60 is contained in recess 46 in the front portion of sabot 30. In the case of a blank, as will be described in greater detail hereinafter with respect to Figure 13 and 14, the projectile is omitted, permitting the gas to escape directly down the barrel.

Upon initiation of the primer 14 by the weapon firing pin (not shown), gas is generated by the primer 14 and/or the propellant 20 it ignites. The front portion 40 of the sabot 30 is restrained from moving forward by the step 100 in the chamber 102 of the weapon (see Figure 14) that is complementary to and engages with the outer annular shoulder 76 formed around the forward end 40 of the sabot 30. Though shown as being perpendicular to the direction of the barrel, the step 100 and shoulder 76 may be obliquely oriented so long as the shoulder 76 may thrust against the step 100. The expanding gas therefore propels the case 12 rearward, imparting momentum to the bolt of the weapon. Concurrently, the gas can flow through the orifices 44 to the projectile 60, beginning its acceleration. The amount of energy imparted to the projectile 60 can be adjusted by varying the size of the orifices 44. In the case of a blank, at this time, the gas is permitted to escape down the barrel causing the flash and noise that simulates the firing of an actual bullet.

The travel of the sabot 30 can be limited by an inwardly displaced flange 24, which may be in the form of a crimp, at the case mouth 26 which interferes with the side of the inwardly formed step 48 in the sidewall 81 of sabot 30 when it reaches the end of its travel. It can also be limited by the sidewall friction combined with decreasing internal pressure, eliminating the need for the step 48 in the sabot 30.

As the projectile 60 accelerates down the barrel, the case 12 and sabot 30 continue to be extracted by the bolt, rearward as a unit, to be ejected in the same manner as a conventional cartridge case is ejected from a recoiling bolt weapon. Because the case 12 is set in motion by the firing, there is reduced chance that it will seize within the chamber 102. This, in turn, allows a lighter gauge of material to be used for the wall 34 of the casing 12.

A second embodiment of the invention is shown in Figures 4 through 6. In this configuration, the sabot 30 is reduced in diameter at the rear portion 32 by providing an inwardly stepped surface 71 to fit snugly into a case 12 having a thinner, stepped portion 62 defined by a thicker sidewall 34a set inwardly from the mouth 26. Also, diagonal orifices 44a, which serve as gas passage means 44a, are provided in the rear por-

tion 32 of sabot 30. Orifices 44a angle outwardly and rearwardly from the forward end 80 of the sabot 30 (being in the case where a projectile is present, the bottom of the recess 46) towards the rear portion 32 of sabot 30, terminating at the inwardly stepped surface 71 where the sabot 30 is of reduced diameter at a location short of the rearward end 83 of the sabot 30. Upon initialization of the primer 14 and/or propellant 20, the gas is completely trapped until the end of the thinner stepped portion 62 in the case wall 34a clears the rear end 72 of the sabot 30, permitting the gas to flow through the orifices 44a to the projectile 60 and assuring that the weapon receives sufficient operating impulse prior to projectile acceleration.

A third embodiment of the invention is shown in Figures 7 through 10. The rear portion 32 of the sabot is fluted by grooves 64 (four being shown but one being sufficient) to permit the escape of gas when the case has moved rearward sufficiently to uncover the terminal end 84 of one of the grooves 64. At that time, gas flows through the grooves 64 along the case wall 34 and through the angled sabot orifices 44a to the base of the projectile 60 causing its acceleration as described above. This design also prevents the propellant gas from reaching the orifices 44a and thence the projectile 60 until the movement of the sabot 30 has almost reached its limit, assuring that sufficient energy has been supplied to the bolt to cycle the weapon regardless of the energy supplied to the projectile 60. Further, it eliminates the need for the step 62 in the cartridge case 12 as shown in Figure 5.

A fourth embodiment of the invention is shown in Figures 11 and 12. It is similar to the third embodiment shown in Figures 7 through 10, except that it also contains longitudinal orifices 44 extending through the sabot 30, as in the first embodiment as shown in Figure 2, to permit propellant gas to bleed through and accelerate the projectile 60 immediately upon ignition. Orifices 44 are designed to provide sufficient but limited pressure in the barrel before the case 12 and the bolt have moved rearward sufficiently to uncover the grooves 64 in the sabot 30. During this period the projectile 60 is accelerated to the end of the gun barrel. When the grooves 64 are uncovered, a much greater volume of gas is released, causing more noise and flash than can be obtained with either of the embodiments shown in Figure 1 or Figure 3. By proper design of the longitudinal orifices 44, the diagonal orifices 44a, bolt mass and propellant parameters, it is possible to obtain equivalent noise and recoil to a conventional weapon firing ball ammunition, while firing a reduced-energy projectile.

The same concept, that is, the use of an orifice tailored to open at some point in the travel of the projectile in the barrel, in combination with an orifice to provide initial projectile acceleration, can also be used to provide a boost in acceleration to larger mass projectiles in conventional weapons, increasing their

velocities without exceeding the maximum pressure limitations of the weapon and barrel.

Figures 13 and 14 show a fifth embodiment of the invention, a blank cartridge operating on the same principle as the first embodiment shown in Figures 1 through 3. The propellant energy is used to accelerate the weapon mechanism and the residual gas energy is released down the barrel when the grooves 64 in the rear portion 32 of sabot 30 are uncovered by the movement of the case 12 with respect to the sabot 30. This provides a means for cycling some weapons without the need of a blank firing adapter.

Another variation of the embodiment shown in Figures 1 through 3 is shown in Figures 15 through 17. In this sixth embodiment, the case 12 is reduced in size in proportion to the sabot 30 are reversed. In some weapons this configuration provides more support to the stationary component, permitting the gas to expand the case 12 against the wall of a tapered chamber of the weapon to provide additional bearing surface during the ballistic cycle. This can permit the use of a thinner wall case but carries with it the risk that the cartridge 10 may be more resistant to ejection. Nevertheless, so long as a significant proportion of the case wall 12 blows-back against the bolt on firing, then the benefits of the invention will be present. In this embodiment, the primer 14 and the propellant 20 are both positioned in a piston 74, and are in communication through a flash hole 70. Likewise, a single longitudinal orifice 44 and the recess 46 are formed in case 12.

All of the above embodiments can be used in conventional blowback weapons, such as small pistols and submachine guns, with little or no modification of the weapons. Their use in larger pistols which use a form of delayed blowback cycling mechanism and their use in semiautomatic gas-operated weapons, such as most rifles and automatic cannon, require changes to the weapon to convert them to a blow-back-operated mechanism.

From the above, it is apparent that any modifications and variations of the present invention are possible in light of the above teachings. It is therefore to be understood that, within the scope of the appended claims, the invention may be practiced otherwise than as specifically described.

Claims

1. A cartridge 10 for use in a recoil operated firearm having a firearm chamber 102 with an inwardly formed step 100 or inclined shoulder at the end thereof comprising:
 - (1) a cartridge case 12 having a base end 16 at the rearward portion;
 - (2) a primer 14;
 - (3) a plug 30 closing the forward portion of the

cartridge case 12, sealingly positioned at the forward end of the cartridge case 12 for sliding displacement therein and defining a closed cavity 22 within the cartridge case 12 containing the primer 14; and

(4) gas passage means 44, extending from said closed cavity 22 through the plug 30 to permit gas generated within the cavity 22 subsequent to ignition of the primer 14 to pass outwardly and forwardly from the forward end of the plug 30,

characterized by the plug 30 having a forward end bounded by an outer, annular shoulder 76 that is directed forwardly for engagement with and thrusting against the end of the firearm chamber, whereby said cartridge casing 12 will effect a sliding displacement in the rearward direction with respect to said plug 30 upon ignition of the primer 14.

2. A cartridge 10 as in claim 1 characterized in that:
 - (1) the plug 30 is provided within its sidewall 81 with an inwardly formed step 48 within the rear portion 32 of the plug 30, such step not extending to the rearward end 72 of the plug 30; and
 - (2) the case 12 has a wall 34 which is provided with an inwardly displaced flange 24 to sealingly engage with the inwardly formed step 48, whereby the casing 12 may be slidably displaced on the plug 30, but will not disengage therefrom.
3. A cartridge as in claims 1 or 2 characterized in that said gas passage means 44 is initially occluded, becoming opened upon displacement of the cartridge casing 12 rearwardly.
4. A cartridge as in claim 1 characterized in that:
 - (a) the plug 30 is provided within its sidewall 81 with an inwardly formed step 48 within the rear portion 32 of the plug 30;
 - (b) the sidewall 81 of the plug 30 is provided with at least one groove 64 in its rear portion 32 that extends from the rearward end 72 of the plug 30 to a terminal end 84 for the groove 64 at a position intermediate the ends of the inwardly formed step 48; and
 - (c) gas passage means 44a extending from the forward end of the plug 30 to provide a passageway to the inwardly formed step 48, whereby upon rearward displacement of the cartridge case 12 with respect to the plug 30, propellant gas may flow from the closed cavity 22 out through the forward end 80 of the plug 30.
5. A cartridge as in claims 1 or 2 characterized in that

velocities without exceeding the maximum pressure limitations of the weapon and barrel.

Figures 13 and 14 show a fifth embodiment of the invention, a blank cartridge operating on the same principle as the first embodiment shown in Figures 1 through 3. The propellant energy is used to accelerate the weapon mechanism and the residual gas energy is released down the barrel when the grooves 64 in the rear portion 32 of sabot 30 are uncovered by the movement of the case 12 with respect to the sabot 30. This provides a means for cycling some weapons without the need of a blank firing adapter.

Another variation of the embodiment shown in Figures 1 through 3 is shown in Figures 15 through 17. In this sixth embodiment, the case 12 is reduced in size in proportion to the sabot 30 are reversed. In some weapons this configuration provides more support to the stationary component, permitting the gas to expand the case 12 against the wall of a tapered chamber of the weapon to provide additional bearing surface during the ballistic cycle. This can permit the use of a thinner wall case but carries with it the risk that the cartridge 10 may be more resistant to ejection. Nevertheless, so long as a significant proportion of the case wall 12 blows-back against the bolt on firing, then the benefits of the invention will be present. In this embodiment, the primer 14 and the propellant 20 are both positioned in a piston 74, and are in communication through a flash hole 70. Likewise, a single longitudinal orifice 44 and the recess 46 are formed in case 12.

All of the above embodiments can be used in conventional blowback weapons, such as small pistols and submachine guns, with little or no modification of the weapons. Their use in larger pistols which use a form of delayed blowback cycling mechanism and their use in semiautomatic gas-operated weapons, such as most rifles and automatic cannon, require changes to the weapon to convert them to a blowback-operated mechanism.

From the above, it is apparent that any modifications and variations of the present invention are possible in light of the above teachings. It is therefore to be understood that, within the scope of the appended claims, the invention may be practiced otherwise than as specifically described.

Claims

1. A cartridge 10 for use in a recoil operated firearm having a firearm chamber 102 with an inwardly formed step 100 or inclined shoulder at the end thereof comprising:
 - (1) a cartridge case 12 having a base end 16 at the rearward portion;
 - (2) a primer 14;
 - (3) a plug 30 closing the forward portion of the

cartridge case 12, sealingly positioned at the forward end of the cartridge case 12 for sliding displacement therein and defining a closed cavity 22 within the cartridge case 12 containing the primer 14; and

(4) gas passage means 44, extending from said closed cavity 22 through the plug 30 to permit gas generated within the cavity 22 subsequent to ignition of the primer 14 to pass outwardly and forwardly from the forward end of the plug 30,

characterized by the plug 30 having a forward end bounded by an outer, annular shoulder 76 that is directed forwardly for engagement with and thrusting against the end of the firearm chamber, whereby said cartridge casing 12 will effect a sliding displacement in the rearward direction with respect to said plug 30 upon ignition of the primer 14.

2. A cartridge 10 as in claim 1 characterized in that:
 - (1) the plug 30 is provided within its sidewall 81 with an inwardly formed step 48 within the rear portion 32 of the plug 30, such step not extending to the rearward end 72 of the plug 30; and
 - (2) the case 12 has a wall 34 which is provided with an inwardly displaced flange 24 to sealingly engage with the inwardly formed step 48, whereby the casing 12 may be slidingly displaced on the plug 30, but will not disengage therefrom.
3. A cartridge as in claims 1 or 2 characterized in that said gas passage means 44 is initially occluded, becoming opened upon displacement of the cartridge casing 12 rearwardly.
4. A cartridge as in claim 1 characterized in that:
 - (a) the plug 30 is provided within its sidewall 81 with an inwardly formed step 48 within the rear portion 32 of the plug 30;
 - (b) the sidewall 81 of the plug 30 is provided with at least one groove 64 in its rear portion 32 that extends from the rearward end 72 of the plug 30 to a terminal end 84 for the groove 64 at a position intermediate the ends of the inwardly formed step 48; and
 - (c) gas passage means 44a extending from the forward end of the plug 30 to provide a passageway to the inwardly formed step 48, whereby upon rearward displacement of the cartridge case 12 with respect to the plug 30, propellant gas may flow from the closed cavity 22 out through the forward end 80 of the plug 30.
5. A cartridge as in claims 1 or 2 characterized in that:



- (1) the plug 30 is provided within its sidewall 81 with an inwardly formed stepped surface 71 within the rear portion 32 of the plug 30, such stepped surface 71 extending to the rearward end 72 of the plug 30;
- (2) the wall 34 of the case 12 is provided with a thicker sidewall 34a overlying and sealingly engaging with a sliding fit with the stepped surface 71;
- (3) the wall 34 of the case 12 is provided with thinner portion 62 to engage with the sidewall of the plug 30 forward of the stepped surface 71; and
- (4) gas passage means 44a extends from the forward end of the plug 30 to provide a passageway to the inwardly formed stepped surface 71 short of the rearward end 72 of the plug 30, whereby upon rearward displacement of the cartridge case 12 with respect to the plug 30, propellant gas may flow from the closed cavity 22 out through the forward end 80 of the plug 30.
6. A cartridge as in claim 1, 2, 3, 4 or 5 characterized in that said gas passage means 44 comprises both indirect gas passage means 44a which are initially occluded and a supplementary direct gas passage 44 extending through the plug 30 from the cavity 12 to the forward end of the plug 80 whereby propellant gas will pass directly through said direct passage 44 during the period that indirect gas passage means 44a are occluded.
7. A cartridge as in claim 6 in combination with a projectile 60 characterized in that the direct gas passage 44 is dimensioned to allow the propellant gas to carry the projectile 60 beyond the muzzle of the barrel in the time taken for the indirect gas passage means 44a to become opened.
8. A cartridge as in claim 6 in combination with a projectile 60 characterized in that the direct passage 44 is dimensioned to allow the propellant gas to carry the projectile 60 part way along the barrel towards the muzzle of the barrel in the time taken for the indirect gas passage means 44a to become opened.
9. A cartridge as in claims 1, 2, 3, 4, 5, 6, 7 or 8 characterized in that said primer 11 forms the supply of propellant gas.
10. A cartridge as in claims 1, 2, 3, 4, 5, 6, 7 or 8 characterized in that additional propellant gas material 20 in said cavity 22 forms the supply of propellant gas.

11. A cartridge as in claims 1, 2, 3, 4, 5, 6, 7 or 8 including a projectile 60 in the forward end of said plug 30.

Patentansprüche

1. Patrone (10) für die Verwendung in einer Rückstoß-Schusswaffe mit einer Schusswaffen-Kammer (102) mit nach innen gerichteter Abstufung oder geneigter Schulter an ihrem Ende mit
- (1) einer Patronenhülse (12) mit einer Sockelfläche (16) am hinteren Endbereich;
 - (2) einem Zünder (14);
 - (3) einem Verschlussstopfen (30), der den vorderen Bereich der Patronenhülse (12) abschließt, abdichtend am vorderen Ende der Patronenhülse (12) für eine gleitende Verschiebung in ihr angeordnet ist und einen geschlossenen Hohlraum (22) in der den Zünder (14) enthaltenden Patronenhülse begrenzt; und
 - (4) einer Gaskanalanordnung (44), die sich von dem geschlossenen Hohlraum (22) durch den Verschlussstopfen (30) erstreckt, um einen Durchgang für in dem Hohlraum (22) als Folge der Zündung des Zünders (14) erzeugtes Gas nach außen und vor das vordere Ende des Verschlussstopfens (30) zu ermöglichen,
- dadurch gekennzeichnet, daß der Verschlussstopfen (30) ein durch eine äußere ringförmige Schulter (76) begrenztes vorderes Ende aufweist, wobei die Schulter für einen Kontakt mit dem und einen Stoß gegen das Ende der Schusswaffen-Kammer nach vorn gerichtet ist, wodurch die Patronenhülse (12) eine gleitende Verschiebung in die Rückwärtsrichtung in bezug auf den Verschlussstopfen (30) beim Zünden des Zünders (14) bewirkt.
2. Patrone nach Anspruch 1, dadurch gekennzeichnet, daß
- (1) der Verschlussstopfen (30) in seiner Seitenwand (81) mit einer nach innen ausgebildeten Stufe (48) in dem hinteren Bereich des Verschlussstopfens (30) ausgebildet ist, wobei diese Stufe sich nicht bis zum hinteren Ende (72) des Verschlussstopfens (30) erstreckt; und
 - (2) die Hülse (12) eine Wand (34) aufweist, die mit einem nach innen versetzten Flansch (24) ausgebildet ist, um abdichtend mit der nach innen ausgebildeten Stufe (48) in Eingriff zu treten,
- wodurch die Hülse (12) gleitend auf dem Verschlussstopfen (30) verschiebbar ist, aber nicht von ihr außer Eingriff kommt.



3. Patrone nach Anspruch 1 oder 2, dadurch gekennzeichnet, daß die Gaskanalanordnung (44) anfänglich verschlossen ist und geöffnet wird, wenn die Patronenhülse (12) sich nach hinten verschiebt.

4. Patrone nach Anspruch 1, dadurch gekennzeichnet, daß

(a) der Verschlußstopfen (30) in seiner Seitenwand (81) mit einer nach innen gerichteten Stufe (48) in dem hinteren Bereich (32) des Verschlußstopfens (30) versehen ist,

(b) die Seitenwand (81) des Verschlußstopfens (30) mit mindestens einer Aussparung (64) in ihrem hinteren Bereich (32) versehen ist, die sich von dem hinteren Ende (72) des Verschlußstopfens (30) bis zu einem Anschlagende (84) für die Aussparung (64) an einer Stelle zwischen den Enden der nach innen ausgeformten Stufe (48) erstreckt; und

(c) ein Gaskanalanordnung (44a) sich von dem vorderen Ende des Verschlußstopfens (30) erstreckt, um einen Durchgang zu der nach innen ausgeformten Stufe (48) vorzusehen,

wodurch bei einer Rückwärtsverschiebung der Patronenhülse (12) in bezug auf den Verschlußstopfen (30) Treibgas von dem geschlossenen Hohlraum (22) durch das vordere Ende (80) des Verschlußstopfens (30) strömen kann.

5. Patrone nach Anspruch 1 oder 2, dadurch gekennzeichnet, daß

(1) der Verschlußstopfen in seiner Seitenwand (81) mit einer nach innen ausgeformten, abgestuften Fläche (71) im hinteren Bereich (32) des Verschlußstopfens (30) versehen ist, die sich zu dem hinteren Ende (72) des Verschlußstopfens (30) erstreckt;

(2) die Wand (34) der Hülse (12) mit einer dickeren Seitenwand (34a) versehen ist, die über der abgestuften Fläche (71) in einer abdichtenden Gleitpassung mit ihr liegt;

(3) die Wand (34) der Hülse (12) mit einem dünneren Bereich (62) in Kontakt mit der Seitenwand des Verschlußstopfens vor der abgestuften Fläche (71) versehen ist; und

(4) die Gaskanalanordnung (44a) sich von dem vorderen Ende des Verschlußstopfens (30) erstreckt, um einen Durchgang zu der nach innen ausgeformten, abgestuften Fläche (71) kurz vor dem hinteren Ende (72) des Verschlußstopfens (30) vorzusehen;

wodurch bei Rückwärtsverschiebung der Patronenhülse (12) in bezug auf den Verschlußstopfen (30) Treibgas von der geschlossenen Kammer (22) durch das vordere Ende (80) des Verschlußstopfens (30) nach außen strömen kann.

6. Patrone nach Anspruch 1, 2, 3, 4 oder 5, dadurch gekennzeichnet, daß die Gaskanalanordnung (44) sowohl einen indirekten Gaskanal (44a), der ursprünglich verschlossen ist, als auch einen zusätzlichen direkten Gaskanal (44), der sich durch den Verschlußstopfen (30) von dem Hohlraum (12) zu dem vorderen Ende des Verschlußstopfens (30) erstreckt, aufweist, wodurch Treibgas direkt durch den direkten Kanal (44) während des Zeitraums, in dem der indirekte Gaskanal (44a) geschlossen ist, hindurchgehen kann.

7. Patrone nach Anspruch 6 in Verbindung mit einem Projektil (60), dadurch gekennzeichnet, daß der direkte Gaskanal (44) so dimensioniert ist, daß das Treibgas das Projektil aus der Mündung des Laufs in der Zeit, die für die Öffnung des indirekten Gaskanals nötig ist, hinausträgt.

8. Patrone nach Anspruch 6 in Verbindung mit einem Projektil (60), dadurch gekennzeichnet, daß der direkte Kanal (44) so dimensioniert ist, daß das Treibgas das Projektil einen Teilweg längs des Laufs zu der Mündung des Laufs in der Zeit, die für die Öffnung des indirekten Gaskanals (44a) benötigt wird, trägt.

9. Patrone nach Anspruch 1, 2, 3, 4, 5, 6, 7 oder 8, dadurch gekennzeichnet, daß der Zünder (11) den Vorrat des Treibgases bildet.

10. Patrone nach Anspruch 1, 2, 3, 4, 5, 6, 7 oder 8, dadurch gekennzeichnet, daß zusätzliches Treibgasmaterial (20) in dem Hohlraum (22) den Vorrat des Treibgases bildet.

11. Patrone nach Anspruch 1, 2, 3, 4, 5, 6, 7 oder 8, die ein Projektil (60) in dem vorderen Ende des Verschlußstopfens (30) einschließt.

Revendications

1. Cartouche 10 devant être utilisée dans une arme à feu actionnée par une détente, comprenant une chambre 102 pourvue d'une butée 100 tournée vers l'intérieur ou un épaulement incliné à son extrémité, comprenant :

(1) une douille de cartouche 12 ayant une base 16 sur sa partie arrière;

(2) une amorce 14;

(3) un bouchon 30 fermant la partie avant de la douille 12, placée de manière étanche à l'extrémité avant de la douille 12 pour glisser dans celle-ci et définissant une cavité fermée 22 à l'intérieur de la douille 12 contenant l'amorce 14; et

(4) des moyens 44 de passage des gaz



s'étendant depuis ladite cavité fermée 22 à travers le bouchon 30 pour permettre aux gaz générés à l'intérieur de la cavité 22 par suite de la mise à feu de l'amorce 14 de passer vers l'extérieur et vers l'avant depuis l'extrémité avant du bouchon 30,

caractérisée en ce que le bouchon 30 a une extrémité avant maintenue par une collerette annulaire extérieure 76 dirigée vers l'avant pour s'appliquer contre l'extrémité de la chambre d'arme à feu et exercer une poussée sur cette extrémité, ladite douille 12 se déplaçant en glissant en direction de l'arrière par rapport au dit bouchon 30 lors de la mise à feu de l'amorce 14.

2. Cartouche selon la revendication 1 caractérisée en ce que :

(1) le bouchon 30 est muni sur sa paroi latérale 81 d'un degré 48 tourné vers l'intérieur dans la partie arrière 32 du bouchon 30, un tel degré ne s'étendant pas vers l'extrémité arrière 72 du bouchon 30; et

(2) la douille 12 a une paroi 34 munie d'une collerette 24 déformée vers l'intérieur pour s'engager de manière étanche sur le degré 48 tourné vers l'intérieur,

de manière que la douille 12 puisse être déplacée par glissement sur le bouchon 30 sans se désengager de celui-ci.

3. Cartouche selon les revendications 1 ou 2, caractérisée en ce que les dits moyens 44 de passage des gaz sont initialement obturés et s'ouvrent lors du déplacement de la douille 12 vers l'arrière.

4. Cartouche selon la revendication 1, caractérisée en ce que :

(a) le bouchon 30 est muni sur sa paroi latérale 81 d'un degré 48 tourné vers l'intérieur dans la partie arrière 32 du bouchon 30;

(b) la paroi 81 du bouchon 30 est munie d'au moins une rainure 64 dans sa partie arrière 32, qui s'étend depuis l'extrémité arrière 72 du bouchon 30 jusqu'à l'extrémité terminale 84 de la rainure 64 en une position intermédiaire entre les extrémités du degré 48 tourné vers l'intérieur; et

(c) des moyens 44a de passage des gaz s'étendant depuis l'extrémité avant du bouchon 30 pour former une voie de passage vers le degré 48,

de manière que le gaz propulseur, lors du déplacement arrière de la douille 12 par rapport au bouchon 30, puisse s'échapper depuis la cavité fermée 22 en traversant l'extrémité avant 80 du bouchon 30.

5. Cartouche selon la revendication 1 ou 2, caracté-

térisée en ce que :

(1) la paroi latérale 81 du bouchon 30 comprend une surface 71 épaulée vers l'intérieur et ménagée dans la partie arrière 32 du bouchon 30, cette surface épaulée 71 s'étendant vers l'extrémité arrière 72 du bouchon 30;

(2) la paroi 34 de la douille 12 est munie d'une paroi 34a plus épaisse recouvrant la surface épaulée 71 et s'engageant hermétiquement en contact glissant avec celle-ci;

(3) la paroi 34 de la douille 12 est munie d'une partie plus mince 62 en contact avec la paroi latérale du bouchon 30 à l'avant de la surface 71; et

(4) des moyens 44a de passage des gaz s'étendant depuis l'extrémité avant du bouchon 30 pour former une voie de passage vers la surface 71 près de l'extrémité arrière 72 du bouchon 30,

de manière que le gaz propulseur, lors du déplacement arrière de la douille 12 par rapport au bouchon 30, puisse s'échapper depuis la cavité fermée 22 en traversant l'extrémité avant 80 du bouchon 30.

6. Cartouche selon l'une quelconque des revendications 1, 2, 3, 4 ou 5, caractérisée en ce que lesdits moyens 44 de passage de gaz comprennent à la fois des moyens 44a de passage indirect des gaz, initialement fermés, et un passage direct supplémentaire 44 pour les gaz traversant le bouchon 30 depuis la cavité 22 vers l'extrémité arrière du bouchon 80, afin que les gaz propulseurs passent directement à travers ledit passage direct 44 pendant la période au cours de laquelle les moyens 44a de passage indirects des gaz sont fermés.

7. Cartouche selon la revendication 6 en combinaison avec un projectile 60, caractérisée en ce que le passage 44 direct est dimensionné de façon à permettre au gaz propulseur de déplacer le projectile 60 au-delà de la bouche du canon pendant le temps nécessaire pour que s'ouvrent les moyens 44a de passage direct des gaz.

8. Cartouche selon la revendication 6 en combinaison avec un projectile 60, caractérisée en ce que le passage 44 direct est dimensionné de façon à permettre au gaz propulseur de déplacer le projectile 60 le long du canon en direction de sa bouche pendant le temps nécessaire pour que s'ouvrent les moyens 44a de passage indirect des gaz.

9. Cartouche selon l'une quelconque des revendications 1, 2, 3, 4, 5, 6, 7 ou 8, caractérisée en ce



que ladite amorce 14 constitue la source de gaz propulseur.

10. Cartouche selon l'une quelconque des revendications 1, 2, 3, 4, 5, 6, 7 ou 8, caractérisée en ce qu'une matière supplémentaire 20 à gaz propulseur placé dans ladite cavité 22 constitue la source de gaz propulseur. 5
11. Cartouche selon l'une quelconque des revendications 1, 2, 3, 4, 5, 6, 7 ou 8, incluant un projectile 60 à l'extrémité avant dudit bouchon 30. 10

15

20

25

30

35

40

45

50

55

9

