

CROSS REFERENCE TO RELATED APPLICATION

5 **[0001]** This claims priority to U.S. Provisional Patent Application No. 61/564,206 filed on November 28, 2011, entitled “Medical Devices and Techniques for Antiseptic, Immunomodulatory and Antineoplastic Therapies,” which is hereby incorporated by reference in its entirety.

[0002] Infection remains a real problem in the medical industry today. Infections are often caused by contamination of intravascular (IV) lines (e.g., intravenous, intra-arterial, etc.), contamination of an injection site or blood draw site (e.g., from a vein, artery, or capillary), urinary catheters, wound sites, incision sites, and numerous other sources of infection in healthcare facilities. For example, in United States hospitals alone, central venous catheters cause an estimated 250,000 blood stream infections per year, which result substantial costs, both in terms of financial resources consumed and in patient morbidity. O'Grady, MD, et al., *Guidelines for the Prevention of Intravascular Catheter-Related Infections, 2011*, Center for Disease Control, Department of Health and Human Services. These numbers do not include infections caused contamination of injection sites, blood draw sites, non-venous catheters, or any of the other numerous sources of contamination in healthcare facilities. Infection is even more of a problem in

developing nations, where syringes, IV lines, and other equipment routinely are used and re-used for multiple different patients.

BRIEF DESCRIPTION OF THE DRAWINGS

5 **[0003]** The detailed description is set forth with reference to the accompanying figures. In the figures, the left-most digit(s) of a reference number identifies the figure in which the reference number first appears. The use of the same reference numbers in different figures indicates similar or identical items or features.

[0004] FIGS. 1A and 1B illustrate an example port protective cap.

10 **[0005]** FIGS. 2A-2C illustrates various example port protective caps which may include various mechanisms for attachment.

[0006] FIG.3 illustrates an example port cleansing cap.

[0007] FIGS. 4A-4C illustrate an example port cleansing system.

[0008] FIGS. 5A-5C illustrate example steps for attachment of an example port
15 protective cap.

[0009] FIGS. 6A and 6B illustrate an example site cleaning and disinfecting device.

[0010] FIGS. 7A and 7B illustrate two example packing implementations of the port protective cap, port cleansing cap and/or the site cleaning and disinfecting device.

20 **[0011]** FIGS. 8A and 8B illustrate example strips or kits of the port protective caps, port cleansing caps and/or the site cleaning and disinfecting devices.

DETAILED DESCRIPTION

OVERVIEW

[0012] This application describes approaches to reducing and/or preventing infections. In one aspect, the application describes example antimicrobial compositions that may be used alone or in combination with one or more medical devices to clean and/or disinfect intravascular (IV) line ports, other IV components (e.g., syringes, lumens, valves, etc.), injection sites, blood draw sites (e.g., from a vein, artery, or capillary), wound sites, incision sites, peritoneal dialysis sites, bladder or nephrostomy sites, other drainage sites, or any other site that is susceptible to infection.

10

EXAMPLE PORT PROTECTION AND CLEANING DEVICES

[0013] FIGS. 1A-5C illustrate details of several example port cleaning and protecting caps. Each of the caps may be made of materials such as, but not limited to, polyethylene, polypropylene, copolymer materials and/or mixtures thereof. The caps may also comprise a material or agent that is UV protective to preserve the integrity of hydrogen peroxide during storage, shipping, etc. The caps themselves may additionally or alternatively be housed in a packaging that contains UV protective materials to inhibit breakdown of the hydrogen peroxide.

15

[0014] FIGS. 1A and 1B illustrate an example of an IV port protective cap 100 designed to thread onto a threaded port, such as a female Leur® connector, to provide a physical barrier against recontamination. As shown in FIG. 1A, the protective cap 100 is hermetically sealed by a protective cover 102. The protective cap 100 may be removably

20

fused or bonded to the protective cap 100 by sonic welding, microwave welding, thermal fusion, or other bonding techniques. The protective cover 102 may be made of a same or different material than the protective cap 100. To facilitate the sealing of the protective cover 102 to the protective cap 100, as shown in FIG. 1B, the protective cap includes an energy director 104 disposed on a top surface of a rim 106 or flange surrounding an opening of the protective cap 100. The energy director 104 comprises a raised ridge or rib of material having a small cross section relative to the rim 106 of the protective cap 100. The small cross section of the energy director 104 allows the energy director to melt more quickly and to fuse with the protective cover 102 with less energy than that required to melt the entire rim 106 of the protective cap 100. The energy director 104 also allows the protective cover 102 to fuse to the protective cap 100 over a relatively thin region, thereby making the protective cover 102 easier to remove from the protective cap 100 than if it were fused over the entire area of the rim 106 of the protective cap 100.

[0015] The rim 106 is designed as a “no touch rim,” which extends radially from the perimeter of the main body of the protective cap 100, thereby minimizing a likelihood that a user’s fingers will come in contact with the internal surfaces of the protective cap during use. In the illustrated embodiment, the energy director 104 is disposed radially outward of an opening of the protective cap, but inward of an outer edge of the rim 106. This ensures that the portion of the rim 106 inside the energy director 104 remains sterile prior to use. The no touch rim 106 increases the likelihood that the portion of the rim 106 inside the energy director 104 remains sterile even during use. In other embodiments, the

energy director may be disposed anywhere on the rim 106 (e.g., centrally as shown, at an inner perimeter of the rim proximate the opening, or at an outer perimeter of the rim).

[0016] As shown in FIG. 1B, the protective cap 100 also includes an applicator material 108 (shown in exploded view in this figure for clarity). In the illustrated example, the applicator material comprises a cylindrical foam material having an open cell region 110 around the circumference of the sides of the cylinder and a closed cell region 112 on one or both axial ends of the cylinder. The open cell region 110 allows the applicator material 108 to absorb and carry an antimicrobial composition, such as those described below. The closed cell region 112 serves to at least partially cover and seal an end of an IV port to prevent the IV port from leaking and to prevent substantial amounts of an antimicrobial composition from entering the IV port. Both the open cell region 110 and the closed cell region 112 may have a certain amount of texture or roughness to scrub the IV port. In some embodiments, the applicator material may comprise polyurethane, silicon, silicon rubber, polyethylene, polypropylene, thermoplastic elastomer, or the like and mixtures thereof

[0017] Also, while applicator material 108 is illustrated as being a generally cylindrical body, in other embodiments, the applicator material may take on other shapes and/or sizes. Further, the applicator material 108 may include different surface treatments (e.g., siping, slitting, etc.), surface finishes (e.g., macro-, micro-, or nano-structures, etc.), and/or contours (e.g., rounded, ribbed, protrusions, fingers, etc.).

[0018] FIGS. 2A-2C illustrate several variations of IV port protective caps 200A, 200B, and 200C, respectively (collectively referred to as protective caps 200), for use

with IV port connectors of varying outer diameter (OD), such as male Leur® connectors. The protective caps 200 of these embodiment are slip fit caps, in that they are designed to slip over and fit securely on IV port connectors of varying OD, since not all port connectors have standardize OD.

5 **[0019]** FIG. 2A illustrates a protective cap 200A having a stepped inner surface, including a first inner surface 202 and a second inner surface 204, the second inner surface 204 having a smaller average diameter than the first inner surface. The first and second inner surfaces 202 and 204 may have diameters chosen to match ODs of common ports on the market, of maximum and minimum ODs of ports on the market, or based on
10 other criteria. Further both of the first and second inner surfaces 202 and 204 may be tapered (i.e., have a draft angle Θ), such that a diameter of the first and second inner surfaces is largest closest to an opening of the protective cap 200A and decreases toward the bottom, closed end of the protective cap. A draft angle of the first inner surface 202 may be the same as, greater than, or less than a draft angle of the second inner surface
15 204. When the protective cap 200A is placed on an IV port, the protective cap 200A will slide over the IV port until an OD of the IV port contacts and seals against the interior surface of the protective cap 200A at either the first inner diameter 202 (in the case of an IV port with a relatively large OD) or the second inner diameter 204 (in the case of an IV port with a relatively small OD).

20 **[0020]** FIGS. 2B and 2C illustrate alternative embodiments of slip fit protective caps 200B and 200C, respectively, which have continuous, smooth inner surfaces. Rather than being stepped as in the embodiment of FIG. 2A, the protective caps 200B

and 200C have continuous, smooth inner surfaces. Like the inner surfaces of the stepped protective cap 200, the inner surfaces of the protective caps 200B and 200C are tapered to accommodate IV ports of varying OD. However, in order to accommodate IV ports having a wide range of ODs, the draft angle Θ of the protective caps needs to be larger (i.e., a more pronounced taper) as in the case of protective cap 200B, and/or the protective cap needs to be made deeper, as in the case of protective cap 200C.

[0021] FIG. 3 illustrates an example IV port cleaning system 300 including a cleaning cap 302 having an applicator material 304 carrying an antimicrobial composition. The cleaning cap 302 may be used to clean an IV port 306. In the illustrated example, the IV port comprises a female Leur® connector. However, in other embodiments, such IV port cleaning systems may be used or adapted for use in cleaning male Leur® connectors, as well as other types of IV and non-IV ports and/or lumens. The cleaning cap 302 may be used to disinfect the IV port 306, for example, prior to connecting the port to a complimentary port, injecting a medication, drawing blood, or otherwise using the IV port 306. After being disinfected, volatile constituents of the antimicrobial composition may evaporate over time, leaving a film or barrier layer 308 of ethylenediaminetetraacetic acid (EDTA) or other chelating agent that may provide a lasting defense to contamination.

[0022] Once disinfected, a protective cap, such as one described above, may be applied to the IV port 306 to provide a physical barrier against recontamination. The protective cap may contain a same or different antimicrobial composition or other composition. In some implementations, the protective cap may securely couple to the IV

port 306 and may seal the IV port. In the event that the antimicrobial composition in the protective cap dries out over time, the protective cap may still include a residual barrier layer of EDTA or other chelating agent that will provide further defense to contamination. In other embodiments, the protective cap may simply be coated with a film or barrier layer of EDTA or other chelating agent over all or part of the interior
5 and/or exterior surfaces of the protective cap.

[0023] FIGS. 4A-4C illustrate the IV port cleaning and disinfection system 300 of FIG. 3 in more detail. Specifically, FIG. 4A illustrates the cleaning cap 302 prior to use. As shown in FIG. 4A, the cleaning cap 302 may come with a protective cover 400 that
10 maintains the interior of the cleaning cap 302 in a sterile condition. Additionally or alternatively, the cleaning cap 302 may come packaged within another sterile package (not shown in this figure) to maintain the entire cleaning cap 302 in a sterile condition prior to use. In order to use the cleaning cap 302 to clean the IV port 306, the protective seal may be removed, exposing the interior of the cap 302, as shown in FIG. 4B. The
15 cleaning cap 302 may then be placed onto the IV port 306 and twisted or otherwise used to scrub and clean the IV port 306. Specifically, the applicator material 304 carrying the antimicrobial composition may be used to scrub the exterior surfaces of the IV port 306 by twisting and pressing the cleaning cap 302 against the IV port 306.

[0024] If the IV port 306 is contaminated with bacteria, spores, parasites, viruses,
20 bodily fluids, or other contaminants, the antimicrobial composition will begin to bubble or foam 402, providing a visual indicator of the contamination. The bubbling or foaming action is caused by reaction of the hydrogen peroxide with the bacteria, spores, parasites,

and viruses. The hydrogen peroxide will also produce bubbles or foam in response to a Fenton reaction with the hemoglobin or platelets in the bodily fluids. The size and rate of bubble formation may be indicative of the level of contamination, giving the medical personnel a visual indication that the equipment is contaminated and may need further
5 cleaning and/or replacement to avoid infection.

[0025] FIGS. 5A-5C illustrate an example protective cap 500 that may in some embodiments be used in combination with the cleaning cap 302 of FIG. 3 and FIGS. 4A-4C. After the IV port 306 has been cleaned, a protective cover 502 may be removed from the protective cap 500 to expose the interior of the protective cap, as shown collectively
10 in FIG. 5A and 5B. As with the cleaning cap 302, the protective cap 500 may come packaged within another sterile package (not shown in this figure) to maintain the entire protective cap 500 in a sterile condition prior to use.

[0026] The protective cap 500 may then be applied to the IV port 306 to provide a physical barrier against recontamination, as shown in FIG. 5C. The protective cap 500
15 may contain a same or different antimicrobial composition or other composition than the cleaning cap 302. If, when the protective cap 500 is coupled to the IV port 306, bubbling or foaming 504 occurs, this bubbling or foaming will provide a visual indicator to medical personnel that the IV port 306 is still contaminated and needs further cleaning and/or replacement.

20 **[0027]** In some embodiments, the antimicrobial composition in the cleaning cap 302 the protective cap 500, or both may include a dye or colorant that serves to further enhance the visual indication of contamination. When provided, the dye or colorant in

the cleaning cap 302 may be the same or different color than that in the protective cap 500. For example, the dye or colorant may be of a color to match the color of the respective cap. In another example, the dye or colorant may be of a color to contrast with the color of the respective cap.

5 **[0028]** Additional details of example IV port cleaning and protective devices may be found in U.S. Patent Application No. 11/745,843, filed May 8, 2007, to Tennican, which is incorporated herein by reference.

EXAMPLE SITE PREPARATION DEVICES

10 **[0029]** FIGS. 6A and 6B illustrate an example of a site cleaning and disinfecting device 600, which may be used to clean and/or disinfect intravascular (IV) line ports, other IV components (e.g., syringes, lumens, valves, etc.), injection sites, blood draw sites (e.g., from a vein, artery, or capillary), catheters and/or catheter insertion sites, wound sites, incision sites, peritoneal dialysis sites, a drainage sites, or any other site that
15 is susceptible to infection.

[0030] The device 600 includes a housing or cap 602 sealed by a protective cover 604 (shown in broken lines in this figure to illustrate interior features of the device 600). Cap 602 may comprise and be constructed in similar form to protective caps 100 of FIGS. 1A and 1B. For example, cap 602 may be configured to include a “no-touch rim.”
20 Additionally, the protective cover 604 may be sealed to the cap 602 using the same techniques described above with respect to the protective cap 100 of FIGS. 1A and 1B. For example, and as described above, protective cover 604 may be fused with an energy

director to aid in removal of protective cover. Housed within the cap 602 is an applicator material 608, such as a foam or sponge material, that holds an antimicrobial composition such as those described above. When the protective cover 604 is in place (as shown in FIG. 6A), the applicator material 606 is in a state of compression, such when the
5 protective cover 604 is removed the applicator material 606 expands and protrudes from the interior cavity of the cap 602 (as shown in FIG. 6B) for use in cleaning or disinfecting the desired site.

[0031] In some embodiments, the cap 602 may include a flexible and/or domed bottom surface 608, which may be depressed (as shown by the arrow in FIG. 6B) to help
10 to deploy the applicator material 606 from the interior cavity of the cap 602.

[0032] The applicator material 606 in this embodiment may comprise an open cell foam material, a foam material including open cell regions and closed cell regions, a sponge material, an abrasive material, a mesh material, or any other material suitable for cleaning or disinfecting a site. In some embodiments, the applicator material may
15 comprise polyurethane, silicon, silicon rubber, polyethylene, polypropylene, thermoplastic elastomer, or the like and mixtures thereof. Also, while applicator material 606 is illustrated as being a generally cylindrical body, in other embodiments, the applicator material may take on other shapes and/or sizes. Further, the applicator material 606 may include different surface treatments (e.g., siping, slitting, etc.), surface
20 finishes (e.g., macro-, micro-, or nano-structures, etc.), and/or contours (e.g., rounded, ribbed, protrusions, fingers, etc.).

EXAMPLE PACKAGING OF CLEANING DEVICES

[0033] Any of the various port and/or site cleaning devices described above may be packaged individually or in kits of multiple devices in a variety of packages.

[0034] FIGS. 7A and 7B illustrate two example ways of packaging the port and/or site cleaning devices described herein. As shown in FIG. 7A, each device may be individually sealed in a pouch or packet 700 by sandwiching the device between multiple layers of thermoplastic material and sealing the sheets of material to each other around a periphery of the device by, for example, sonic welding, microwave welding, thermal bonding, or the like.

[0035] The approach described in FIG. 7A may be extended to simultaneously package multiple devices in a strip by placing multiple devices between sheets of thermoplastic material and then sealing the sheets of material to each other around the peripheries of each of the devices using any of the sealing methods described above. The result is a strip 702 containing multiple individually sealed devices. Individual devices may then be dispensed by cutting between the devices in the strip 702. Alternatively, the strip 702 may include perforations or score lines between the individual devices in the strip 702.

[0036] FIGS. 8A and 8B illustrate two example packages of port and/or site cleaning devices. As shown in FIG. 8A, a package 800A includes multiple different, individually packaged site cleaning devices, coupled together in a strip 802A or kit. The strip 802A may be packaged according to the methods described with reference to FIGS. 7A and 7B, or other methods. In the illustrated example, the package 800A includes a

soap package 804, a first cap device 806A, a second cap device 806B, and a third cap device 806C (collectively referred to as cap devices 806). The soap pouch 804 may be used to provide an initial cleansing of the site and may comprise any known cleanser used in the medical industry. The different cap devices may comprise port cleaning caps, protective caps, site cleaning caps, or combinations of these. In some examples, the cap devices 806 may correspond to caps having different antimicrobial compositions and/or different concentrations of antimicrobial compositions.

[0037] In one specific example, the first cap device 806A (e.g., a yellow cap) may have a relatively high concentration of hydrogen peroxide, alcohol, and/or chelating agent, the second cap device 806B (e.g., a blue cap) may have lower concentration of hydrogen peroxide, alcohol, and/or chelating agent than the first cap device, and the third cap device 806C (e.g., a green cap) may have a lower concentration of hydrogen peroxide, alcohol, and/or chelating agent than the second cap device. In that case, the first cap device 806A may be used to clean the site first, followed by the second cap device 806B, and finally by the third cap device 806C. The higher concentrations of antimicrobial compositions may provide higher levels of disinfection, but may cause irritation to a patient's tissue especially if allowed to remain in contact with the tissue for a prolonged period. The approach described above may serve to provide high level disinfection using the first cap, followed by removal of the higher concentrations of antimicrobial composition by the second and third caps so as to minimize the risk of irritation of the patient's tissue.

[0038] FIG. 8B illustrates a package 800B, which is the same as package 800A, except that instead of the soap pouch 804, the package 800B includes a fourth cap device 806D. The fourth cap device 806D may include a soap composition similar to the soap pouch 804 or may include an antimicrobial composition having a concentration of
5 hydrogen peroxide, alcohol, and/or chelating agent higher than that of the first cap 806A.

EXAMPLE ANTIMICROBIAL COMPOSITION

[0039] In one example implementation, antimicrobial compositions that may be used in connection with the approaches described herein may include those described in,
10 for example, U.S. Patent Application No. 12/874,188, filed September 1, 2010, to Tennican et al., which is incorporated herein by reference. In that case, the antimicrobial compositions may include water (H_2O), a strong and non-toxic chelating agent such as EDTA (e.g., disodium EDTA, calcium disodium EDTA, magnesium EDTA, gallium EDTA) or sodium citrate (or acids, salts, derivatives, or other forms of EDTA or sodium
15 citrate), a short-chain monohydric alcohol (e.g., ethanol with a molecular formula of C_2H_5OH and an empirical formula of C_2H_6O), and a strong, small molecule oxidizing agent such as hydrogen peroxide (H_2O_2). In one specific example, the compositions may consist essentially of water, EDTA, ethanol, and hydrogen peroxide. However, in other examples, other antimicrobial compositions may be used in combination with the devices
20 described in this application.

[0040] The antimicrobial compositions may be in a liquid form, a gel form, or a foam form, for example, and may be combined with one or more carriers or diluents,

depending on the needs of a specific application. For example, in applications in which the antimicrobial composition is used as a hand sanitizer, the antimicrobial composition may be in a gel form. As another example, if the antimicrobial composition is used as a cleaning agent, a flush solution, or an irritant, the antimicrobial composition may be in a liquid form. In that case, the concentration of the various constituents may depend on, for example, a desired level of disinfection, whether the composition is being applied directly to living tissue or to a medical device, and/or to avoid irritation of tissue to which the composition will be applied directly or indirectly (e.g., via a medical device to which the composition is or was applied). In another example, a liquid form of the antimicrobial compositions may be vaporized or sprayed for application to nasal passages or other airways of a patient. In yet another example, the antimicrobial compositions may include or be combined with a lubricant (e.g., glycerin), surfactant or emulsifier (e.g., glycerol monolaurate (GML)), or the like and may be applied to a catheter, tracheal tube, scope, instrument, or other device that is to be inserted into a patient's body.

15

CONCLUSION

[0041] Although the application describes embodiments having specific structural features and/or methodological acts, it is to be understood that the claims are not necessarily limited to the specific features or acts described. Rather, the specific features and acts are merely illustrative some embodiments that fall within the scope of the claims of the application.

WHAT IS CLAIMED IS:

1. A medical device comprising:
 - 5 a cap comprising:
 - a cylindrical cavity, the cylindrical cavity having an opening and a flange at the opening;
 - an outer surface configured to interface with a user;
 - an inner surface within the cylindrical cavity; and
 - 10 an energy director located on the flange and extending perpendicular to the opening of the cylindrical cavity.
2. The medical device as recited in claim 1, wherein the cap is comprised of a polypropylene, a polyethylene, a copolymer material or mixtures thereof.
- 15 3. The medical device as recited in claim 1, wherein the flange is configured to extend radially from the perimeter of the cylindrical cavity.
4. The medical device as recited in claim 1, further comprising a protective
20 cover attached to at least the energy director and covering at least a portion of the opening.

5. The medical device as recited in claim 4, further comprising a foam insert within the cylindrical cavity wherein the foam insert is maintained in a compressed state while the protective cover is attached and the foam insert is configured to extend outside the opening of the cylindrical cavity when the protective cover is removed.

5

6. The medical device as recited in claim 5, wherein a surface of the foam insert extending outside the opening of the cylindrical cavity comprises different surface treatments, finishes or contours.

10 7. The medical device as recited in claim 1, further comprising an antimicrobial agent disposed within the foam insert.

8. The medical device as recited in claim 7, wherein the antimicrobial agent comprises:

15 about 5 to about 50 mg/ml of ethylenediaminetetraacetic acid (EDTA);
at most about 70% ethanol, by volume;
at most about 7.5% hydrogen peroxide, by volume; and
water.

20 9. The medical device as recited in claim 1, wherein the inner surface of the cylindrical cavity of the cap further comprises at least one of:

a tapered stepped surface;

a tapered smooth surface;

a stepped surface;

a snap fit flange;

one or more threads;

5 one or more internal slits; or

a wire mechanism to aid in attachment of the cap to another object.

10. A medical device comprising:

a cap having an inner surface with a cylindrical cavity and a flange at the opening
10 of the cylindrical cavity to affix a protective cover; and

a foam insert contained within the cylindrical cavity of the cap, the foam insert
compressed by the affixation of the protective cover and configured to extend beyond the
opening of the cylindrical cavity when the protective cover is removed.

15 11. The medical device as recited in claim 10, wherein the foam insert is a cylindrical
shape comprising an inner open-cell layer connecting two outer closed-cell layers at the
top and bottom of the cylindrical shape.

12. The medical device as recited in claim 11, wherein the inner open-cell layer of the
20 foam insert includes an antimicrobial composition.

13. The medical device as recited in claim 12, wherein the antimicrobial composition comprises one or more of a surfactant, water, a low molecular weight alcohol, a peroxide, a peroxide generating agent or a chelating agent.

5 14. The medical device as recited in claim 11, wherein the outer closed-cell layer of the foam insert comprises a course texture.

15. The medical device as recited in claim 10, wherein the foam insert comprises polyurethane, silicon, silicon rubber, polyethylene, polypropylene, thermoplastic
10 elastomer or mixtures thereof.

16. The medical device as recited in claim 10, wherein the flange at the opening of the cylindrical cavity further comprises a raised ridge extending distally from the cylindrical cavity configured to fuse with the removable protective cover.

15

17. A cleaning and disinfecting assembly comprising:

one or more caps, at least one cap having:

an inner surface with a cylindrical cavity and a flange at the opening of the cylindrical cavity; an energy director located on the flange and extending
20 perpendicular to the opening of the cylindrical cavity, the energy director configured to attach to a removable protective cover; and

a foam insert within the cylindrical cavity of the cap, the foam insert compressed by the attachment of the removable protective cover and configured to extend beyond the opening of the cylindrical cavity when the protective cover is removed; and

5 a package for storing the one or more caps, the packaging configured to allow the one or more caps to be stored separately and consecutively.

18. The device as recited in claim 17, wherein the flange at the opening of the cylindrical cavity of the cap is configured to extend radially from the perimeter of the
10 cylindrical cavity.

19. The device as recited in claim 17, wherein the foam insert includes an antimicrobial composition, the antimicrobial composition comprises one or more of a surfactant, water, a low molecular weight alcohol, a peroxide, a peroxide generating
15 agent or a chelating agent.

20. The device as recited in claim 17, wherein the foam insert comprises a course texture.

20 21. The device as recited in claim 17, wherein the cap is comprised of a polypropylene, a polyethylene, a copolymer material or mixtures thereof.

22. A method of preventing the spread of infectious agents comprising:
identifying a surface to be cleansed, sanitized, or disinfected; and
applying a medical applicator to the surface to thereby cleanse, sanitize or disinfect
the surface, the medical applicator comprising:

5 a cap having an inner surface with a cylindrical cavity and a flange at the
opening of the cylindrical cavity;

 a foam insert within the cylindrical cavity of the cap, the foam insert
configured to extend beyond the opening of the cylindrical cavity when the protective
cover is removed; and

10 a cleansing, antimicrobial or antiseptic agent disposed within the foam insert.

23. The method as recited in claim 22, wherein the surface to be cleaned, sanitized or
disinfected is an area of human tissue or an area on a medical device.

15 24. The method as recited in claim 22, wherein the cleansing, antimicrobial or
antiseptic agent comprises at least one of a surfactant, water, a low molecular weight
alcohol, a peroxide, a peroxide-generating agent or a chelating agent.

25. The method as recited in claim 22, wherein the cap includes an energy director
20 located on the flange and extending perpendicular to the opening of the cylindrical cavity.