

DATA REPORTING METHOD AND SYSTEM

The present application claims priority to Chinese Patent Application No. 201710839107.9 filed to the CNIPA on September 18, 2017 and entitled “DATA REPORTING METHOD AND SYSTEM”, the disclosure of which is hereby incorporated herein by reference in its entirety.

Technical Field

The embodiments of the present invention relate to, but are not limited to, the field of wireless network communication, and in particular to a data reporting method and system.

Background

During the data reporting, single-server reporting, single-room cluster reporting or multi-room active/standby reporting are generally employed in the prior art. The multi-room active/standby reporting is mainly cold standby. Here, the cold standby refers to manual switching.

The data reporting methods in the prior art have the following disadvantages:

- (1) the server fails suddenly;
- (2) when a sudden network problem occurs in the computer room where the server is located, the data acquired by the server is incomplete, resulting in data incompleteness;
- (3) when a sudden network problem occurs in the computer room where the server is located, the data reported by the sever fails; and
- (4) after a fault occurs, manual intervention is required to switch between active and standby modes, so that processing time is long and the data timeliness is affected.

Among the above methods, the single-server reporting has the defects in the items (1), (2) and (3), the single-room cluster reporting has the detects in the items (2)

and (3), and the multi-room active/standby reporting has the detect in the above item (4).

Thus, during the data reporting, when the server storing data is faulty, the network condition of the server is poor or the stored data is incomplete, it is usually possible to use a monitoring alarm and manually switch to a standby server to report data. However, in this method, mutual intervention is required, and it will take a long time from the occurrence of a fault, the discovery of the fault to the resolution of the fault, so that long-time data reporting will be affected and the real-time performance of data is greatly reduced.

Therefore, there is a need for a data reporting method and system which can automatically evade faults to complete data reporting and ensure the integrity of data.

Summary of the present invention

In order to solve the problems on data reporting in the prior art, a data reporting method and system are provided, which can automatically evade faults to complete data reporting when a server fails, and ensure the integrity of data.

In accordance with an aspect of the embodiments of the present invention, a data reporting method is provided, including:

step 1: generating a data uploading token by a main network node;

step 2: determining whether each network node being going to upload data has a data uploading qualification; and

step 3: making network nodes with the data uploading qualification compete for the data uploading token, and executing a data uploading operation by a network node that obtains the data uploading token.

The step 2 includes:

acquiring, by each network node, the integrity of data to be uploaded stored thereon, and determining that the network node has a data uploading qualification when the integrity is determined to be greater than or equal to a set threshold.

The step 2 further includes:

acquiring, by each network node, meta-information related to the data to be uploaded, and synchronizing the meta-information with other network nodes; and

selecting a maximum value from the meta-information of each network node, and using a ratio of the meta-information of the network node to the maximum value as the integrity of the data to be uploaded by the network node.

The step 3 includes:

transmitting, by a network node with the data uploading qualification, a request for acquiring the data uploading token to the main network node; and

determining, by the main network node, whether the data uploading token is in a released state, and issuing the data uploading token to a network node that first requests for the data uploading token and then setting the data uploading token to be in an occupied state if the data uploading token is in the released state.

After the step 3, the method further includes:

releasing the data uploading token after the network node that obtains the data uploading token has uploaded data, determining whether data is uploaded successfully, and notifying other network nodes of stopping competition for the data uploading token if the data is uploaded successfully.

The step 3 further includes:

upon transmitting, to the main network node, a request for acquiring the data uploading token, by the network node, transmitting, to the main network node, a time threshold for releasing the data uploading token; and

after the main network node issues the data uploading token to the network node that first requests for the data uploading token, performing timing, and setting, by the main network node, the data uploading token to be in a released state if the timing time reaches the time threshold transmitted by the network node that obtains the data uploading token.

In accordance with another aspect of the embodiments of the present invention, a data reporting system is provided, which is located on a network node, the system including:

a token generation module configured to generate a data uploading token when the network node is a main network node;

a qualification determination module configured to determine whether the network node has a data uploading qualification;

a token competition module configured to compete for the data uploading token; and

a data uploading module configured to execute a data uploading operation when the data uploading token is obtained.

The qualification determination module is further configured to: acquire the integrity of data to be uploaded stored thereon, and determine to have a data uploading qualification when the integrity is determined to be greater than or equal to a set threshold.

The qualification determination module is further configured to: acquire meta-information related to the data to be uploaded, and synchronize the meta-information with other network nodes; and

select a maximum value from the meta-information of each network node, and use a ratio of the meta-information of the network node to the maximum value as the integrity of the data to be uploaded by the network node.

The token competition module is further configured to: transmit, to the main network node, a request for acquiring the data uploading token; and

the system further includes a token management module configured to determine whether the data uploading token is in a released state, and issue the data uploading token to a network node that first requests for the data uploading token and then set the data uploading token to be in an occupied state if the data uploading token is in the released state.

The system further includes:

an uploading management module configured to release the data uploading token after data uploading, determine whether data is uploaded successfully, and notify

other network nodes of stopping competition for the data uploading token if the data is uploaded successfully.

The token competition module is further configured to:

upon transmitting, to the main network node, a request for acquiring the data uploading token, transmit, to the main network node, a time threshold for releasing the data uploading token; and

the token management module is further configured to: after issuing the data uploading token to the network node that first requests for the data uploading token, perform timing, and set, by the main network node, the data uploading token to be in the released state if the timing time reaches the time threshold transmitted by the network node that obtains the data uploading token.

In accordance with the data reporting method and system provided in the embodiments of the present invention, data uploading is performed by a network node with a higher data integrity, so that the integrity of data is ensured. Moreover, when a fault occurs in a server of a network node, data uploading can be automatically switched to a server of another network node without manual intervention, so that the processing time for data uploading is shortened and the data timeliness is ensured.

Brief Description of the Drawings

The drawings incorporated into this specification and constituting a part of this specification show the embodiments of the present invention, and are used together with the description to explain the principles of the embodiments of the present invention. Throughout the drawings, similar reference numerals represent similar elements. The drawings to be described hereinafter are some but not all of the embodiments of the present invention. A person of ordinary skill in the art may obtain other drawings according to these drawings without paying any creative effort. In the drawings:

Fig. 1 is a flowchart of a data reporting method according to an embodiment of the present invention; and

Fig. 2 is a block diagram of a data reporting system according to an embodiment of the present invention.

Detailed Description of the present invention

The technical solutions in the embodiments of the present invention will be clearly and completely described below with reference to the drawings in the embodiments of the present invention. Apparently, the described embodiments are some but not all of the embodiments of the present invention. All other embodiments obtained by a person of ordinary skill in the art based on the embodiments of the present invention without paying any creative effort shall fall into the protection scope of the embodiments of the present invention. It is to be noted that the embodiments in the present application and the features in the embodiments can be combined in any way if not conflicted.

An embodiment of the present invention provides a data reporting method. As shown in Fig. 1, the method includes the following steps.

Step 101: a data uploading token is generated by a main network node.

Step 102: It is determined whether each network node being going to upload data has a data uploading qualification.

Step 103: Network nodes with the data uploading qualification compete for the data uploading token, and a data uploading operation is executed by a network node that obtains the data uploading token.

There are a least three network nodes which may be network nodes across the computer room and the operator. The a plurality of network nodes across the computer room and the operator can ensure that the quality of data uploading will not be affected when the network quality of one network node is poor.

The main network node may be elected by the network nodes, or the system may default one of the network nodes as a main network node, or the main network node may be determined according to a selection rule. If the main network node is elected, when the entire system is started, that is, the data uploading is started, the

network nodes will elect the main network node. During the election, the main network node needs to be voted by majority of the network nodes. The specific election method is known to those skilled in the art and will not be repeated here. The main network node will establish a network connection with other network nodes. The connection may be a persistent ordinary network connection.

The data uploading token is unique. That is, after a network node obtains the data uploading token, other network nodes cannot upload data until the network node that obtains the data uploading token uploads data and releases the data uploading token. At this time, other network nodes may obtain the data uploading token. The state of the data uploading token is set by the main network node. When the main network node issues the data uploading token to other network nodes, the data uploading token is set to be in an occupied state; and, when the network node releases the data uploading token, the main network node is also notified so that the main network node sets the data uploading token to be in a released state.

After it is determined that each network node has its own data uploading qualification, the network node will transmit, to the main network node, a request for acquiring the data uploading token. The main network node issues the data uploading token to the network node that first requests for the data uploading token.

Step 102 includes: acquiring, by each network node, the integrity of data to be uploaded stored thereon, and determining that the network node has a data uploading qualification when the integrity is determined to be greater than or equal to a set threshold.

The step 102 further includes: acquiring, by each network node, meta-information related to the data to be uploaded, and synchronizing the meta-information with other network nodes; and, selecting a maximum value from the meta-information of each network node, and using a ratio of the meta-information of the network node to the maximum value as the integrity of the data to be uploaded by the network node.

The synchronization of the meta-information between each network node being going to upload data and other network nodes is performed in the following ways, where the synchronization means acquiring information of each other:

way 1: if one of two network nodes that synchronize the meta-information with each other is the main network node, the main network node and other network nodes synchronize their respective meta-information through the established connection; and

way 2: if two network nodes that synchronize the meta-information with each other are not the main network node, the two network nodes synchronize their respective meta-information through their respective connections with the main network node.

In other words, each network node only establishes a direct connection with the elected main network node. If the two network nodes are not the main node, there is no direct connection between the two network nodes. Therefore, when information is transmitted between the two network nodes, the information needs to be transferred by the main network node.

The meta-information related to the data to be uploaded may be different according to the type of the data to be uploaded, and is calculated based on the data to be uploaded; and, the integrity of the data to be uploaded on a certain network node can be calculated by using the meta-information. The meta-information may be the sum of the data to be uploaded. For example, when the data to be uploaded is the bandwidth of each network node, the meta-information may be the sum of bandwidths.

Since each network node cannot know the meta-information calculated by the complete data to be uploaded, the integrity of the data to be uploaded is calculated based on the maximum value in the meta-information of the network node. The determination whether a network node has a data uploading qualification is performed based on the integrity. That is, it is determined that the network node has a data uploading qualification when the integrity is greater than or equal to a set threshold. The set threshold may be set as required, for example, 99%.

It is to be noted that the integrity of the data to be uploaded may generally be expressed in form of percentage. When the integrity of the data to be uploaded stored on a network node reaches the set threshold, the network node can upload the stored data and enable a data receiver to receive the quality requirements of the data.

The step 103 includes: transmitting, by a network node with the data uploading qualification, a request for acquiring the data uploading token to the main network node; and, determining, by the main network node, whether the data uploading token is in a released state, and issuing the data uploading token to a network node that first requests for the data uploading token and then setting the data uploading token to be in an occupied state if the data uploading token is in the released state.

After the step 3, the method further includes: releasing the data uploading token after the network node that obtains the data uploading token has uploaded the data, determining whether the data is uploaded successfully, and notifying other network nodes of stopping competition for the data uploading token if the data is uploaded successfully.

The step 103 further includes: upon transmitting, to the main network node, a request for acquiring the data uploading token, by the network node, transmitting, to the main network node, a time threshold for releasing the data uploading token; and, after the main network node issues the data uploading token to the network node that first requests for the data uploading token, performing timing, and setting, by the main network node, the data uploading token to be in a released state if the timing time reaches the time threshold transmitted by the network node that obtains the data uploading token.

This arrangement is to prevent a situation that other network nodes are unable to upload data since the network node that uploads data is unable to upload data and also occupies the token in case of network interruption. Here, the time threshold is general set according to actual requirements, for example, tens of seconds.

If the data is uploaded successfully, other network nodes are notified of stopping competition for the data uploading token in the following ways:

way 1: if the network node that uploads data successfully is the main network node, other network nodes are directly notified of stopping competition; and

way 2: if the network node that uploads data successfully is not the main network node, a message of stopping competition is transmitted to the main network node, and the main network node transmits the message of stopping competition to other network nodes.

As described above, each network node only establishes a direct connection with the main network node. If the network node that uploads data successfully is not the main network node, the information needs to be transferred by the main network node.

Additionally, the transmitting, by a network node with the data uploading qualification, a request for acquiring the data uploading token includes: if the network node with the data uploading qualification is the main network node, transmitting, by the main network node, a request for acquiring the data uploading token to its own token management module; and, if the network node with the data uploading qualification is not the main network node, transmitting, by the network node, a request for acquiring the data uploading token to the token management module of the main network node.

Since the main network node is elected from the network nodes being going to upload data, during the implementation of the data uploading function, the main network node also functions as a data uploading token manager and an information transfer. Thus, when the main network node has a data uploading qualification, the main network node will also transmit, to its own token management module, a request for acquiring the token.

It is to be noted that, in this method, the network nodes that compete for the data uploading token may be network nodes that have the data uploading qualification and never obtain the data uploading token.

The specific steps of the data reporting method provided in this embodiment of the present invention will be described below. In this embodiment, there are five

network nodes A, B, C, D and E, and the data to be uploaded is the reported bandwidths of the five network nodes.

Step 1: From the five network nodes A, B, C, D and E that are going to upload data, the network node B is elected as a main network node, and the main network node B establishes connections with the network nodes A, C, D and E and generates an unique data uploading token.

Step 2: The five network nodes A, B, C, D and E calculate the sum of bandwidths of the network nodes stored thereon as meta-information, and the calculated meta-information of the five network node A, B, C, D and E is 161493570, 160999901, 152964949, 161521593 and 72330513, respectively.

Step 3: The main network node B separately synchronizes the meta-information with the network nodes A, C, D and E, and the network nodes A, C, D and E synchronize the meta-information with each other through the main network node B.

Step 4: For each network node, a maximum value is selected from the meta-information of the five network nodes to calculate the integrity, that is, its own meta-information is divided by the maximum value, where the integrity of the five network nodes A, B, C, D and E is 99.98%, 99.68%, 94.70%, 100.000% and 44.78%, respectively.

Step 5: Each network node determines whether its own integrity is greater than or equal to a preset threshold (i.e., 99%), so that it is determined that the network nodes A, B and D have a data uploading qualification.

Step 6: Each of the network nodes A, B and D with the data uploading qualification transmits, to the main network node, a request for acquiring the data uploading token and a time threshold for releasing the token.

Step 7: Upon receiving the request, the main network node B determines that the data uploading token is in a released state; then, determines that the first received request comes from the network node A so that the data uploading token is issued to the network node A; and, sets the token to be in an occupied state and starts timing.

Step 8: Upon acquiring the token and uploading data, the network node releases the data uploading token, and determines whether the result of data uploading is successful uploading; and, if the result of data uploading is successful uploading, other network nodes are notified of stopping competition for the data uploading token.

If the timing of the main network node B reaches the time threshold transmitted by the network node A and a message of successful uploading or a message of releasing token is still not received, the token is automatically released. In this way, the token can be issued after a request for acquiring the token transmitted by other network nodes is received, and the data uploading can be performed continuously.

Additionally, if a network node fails to upload data, this network node can no longer participate in the subsequent competition for the data uploading token.

An embodiment of the present invention further provides a data reporting system, which is located on a network node. As shown in Fig. 2, the system includes:

a token generation module 201 configured to generate a data uploading token when the network node is a main network node;

a qualification determination module 202 configured to determine whether the network node has a data uploading qualification;

a token competition module 203 configured to compete for the data uploading token; and

a data uploading module 204 configured to execute a data uploading operation when the data uploading token is obtained.

The qualification determination module 202 is further configured to:

acquire the integrity of data to be uploaded stored thereon, and determine to have a data uploading qualification when the integrity is determined to be greater than or equal to a set threshold.

The qualification determination module 202 is further configured to:

acquire meta-information related to the data to be uploaded, and synchronize the meta-information with other network nodes; and

select a maximum value from the meta-information of each network node, and use a ratio of the meta-information of the network node to the maximum value as the integrity of the data to be uploaded by the network node.

The token competition module 203 is further configured to:

transmit, to the main network node, a request for acquiring the data uploading token; and

the system further includes a token management module configured to determine whether the data uploading token is in a released state, and issue the data uploading token to a network node that first requests for the data uploading token and then set the data uploading token to be in an occupied state if the data uploading token is in the released state.

The system further includes:

an uploading management module configured to release the data uploading token after data uploading, determine whether data is uploaded successfully, and notify other network nodes of stopping competition for the data uploading token if the data is uploaded successfully.

The token competition module 203 is further configured to:

upon transmitting, to the main network node, a request for acquiring the data uploading token, transmit, to the main network node, a time threshold for releasing the data uploading token; and

the token management module is further configured to: after issuing the data uploading token to the network node that first requests for the data uploading token, perform timing, and set, by the main network node, the data uploading token to be in the released state if the timing time reaches the time threshold transmitted by the network node that obtains the data uploading token.

In accordance with the data reporting method and system provided in the embodiments of the present invention, data uploading is performed by a network node with higher data integrity, so that the integrity of data is ensured. Moreover, when a fault occurs in a server of a network node, data uploading can be automatically switched

to a server of another network node without manual intervention, so that the processing time for data uploading is shortened and the data timeliness is ensured.

The contents described above can be implemented independently or jointly in various ways, and these variants shall fall into the protection scope of the embodiments of the present invention.

It is to be noted that, as used herein, the term "comprise/comprising", "include/including" or any other variants thereof is intended to encompass a non-exclusive inclusion, so that an object or device including a series of elements not only includes these elements, but also includes other elements not listed clearly, or further includes elements inherent to this object or device. Without more restrictions, an element defined by the phrase "comprising..." does not exclude the presence of other identical elements in the object or device including this element.

The foregoing embodiments are merely used for describing the technical solutions of the present invention and not intended to constitute any limitations thereto. The present invention has been described in detail by the preferred embodiments. It should be understood by a person of ordinary skill in the art that, modifications or equivalent replacements can be made to the technical solutions of the present invention without departing from the spirit and scope of the technical solutions of the present invention, and these modifications or equivalent replacements shall fall into the scope defined by the claims of the present invention.

INDUSTRIAL APPLICABILITY

The embodiments of the present invention provide a data reporting method and system. Data uploading is performed by a network node with higher data integrity, so that the integrity of data is ensured. Moreover, when a fault occurs in a server of a network node, data uploading can be automatically switched to a server of another network node without manual intervention, so that the processing time for data uploading is shortened and the data timeliness is ensured.

CLAIMS

1. A data reporting method, comprising:
 - step 1: generating a data uploading token by a main network node;
 - step 2: determining whether each network node being going to upload data has a data uploading qualification; and
 - step 3: making network nodes with the data uploading qualification compete for the data uploading token, and executing a data uploading operation by a network node that obtains the data uploading token.
2. The data reporting method according to claim 1, wherein the step 2 comprises:
 - acquiring, by each network node, the integrity of data to be uploaded stored thereon, and determining that the network node has a data uploading qualification when the integrity is determined to be greater than or equal to a set threshold.
3. The data reporting method according to claim 2, wherein the step 2 further comprises:
 - acquiring, by each network node, meta-information related to the data to be uploaded, and synchronizing the meta-information with other network nodes; and
 - selecting a maximum value from the meta-information of each network node, and using a ratio of the meta-information of the network node to the maximum value as the integrity of the data to be uploaded by the network node.
4. The data reporting method according to claim 1, wherein the step 3 comprises:
 - transmitting, by a network node with the data uploading qualification, a request for acquiring the data uploading token to the main network node; and
 - determining, by the main network node, whether the data uploading token is in a released state, and issuing the data uploading token to a network node that first requests for the data uploading token and then setting the data uploading token to be in an occupied state if the data uploading token is in the released state.

5. The data reporting method according to claim 1, after the step 3, further comprising:

releasing the data uploading token after the network node that obtains the data uploading token has uploaded data, determining whether data is uploaded successfully, and notifying other network nodes of stopping competition for the data uploading token if the data is uploaded successfully.

6. The data reporting method according to claim 4, wherein the step 3 further comprises:

upon transmitting, to the main network node, a request for acquiring the data uploading token, by the network node, transmitting, to the main network node, a time threshold for releasing the data uploading token; and

after the main network node issues the data uploading token to the network node that first requests for the data uploading token, performing timing, and setting, by the main network node, the data uploading token to be in a released state if the timing time reaches the time threshold transmitted by the network node that obtains the data uploading token.

7. A data reporting system which is located on a network node, the system comprising:

a token generation module configured to generate a data uploading token when the network node is a main network node;

a qualification determination module configured to determine whether the network node has a data uploading qualification;

a token competition module configured to compete for the data uploading token; and

a data uploading module configured to execute a data uploading operation when the data uploading token is obtained.

8. The data reporting system according to claim 7, wherein the qualification determination module is further configured to:

acquire the integrity of data to be uploaded stored thereon, and determine to have a data uploading qualification when the integrity is determined to be greater than or equal to a set threshold.

9. The data reporting system according to claim 8, wherein the qualification determination module is further configured to:

acquire meta-information related to the data to be uploaded, and synchronize the meta-information with other network nodes; and

select a maximum value from the meta-information of each network node, and use a ratio of the meta-information of the network node to the maximum value as the integrity of the data to be uploaded by the network node.

10. The data reporting system according to claim 7, wherein the token competition module is further configured to:

transmit, to the main network node, a request for acquiring the data uploading token; and

the system further comprises a token management module configured to determine whether the data uploading token is in a released state, and issue the data uploading token to a network node that first requests for the data uploading token and then set the data uploading token to be in an occupied state if the data uploading token is in the released state.

11. The data reporting system according to claim 7, further comprising:

an uploading management module configured to release the data uploading token after data uploading, determine whether data is uploaded successfully, and notify

other network nodes of stopping competition for the data uploading token if the data is uploaded successfully.

12. The data reporting system according to claim 10, wherein the token competition module is further configured to:

upon transmitting, to the main network node, a request for acquiring the data uploading token, transmit, to the main network node, a time threshold for releasing the data uploading token; and

the token management module is further configured to: after issuing the data uploading token to the network node that first requests for the data uploading token, perform timing, and set, by the main network node, the data uploading token to be in the released state if the timing time reaches the time threshold transmitted by the network node that obtains the data uploading token.