



- (51) International Patent Classification:
F41F 1/10 (2006.01)
- (21) International Application Number:
PCT/US2014/040626
- (22) International Filing Date:
3 June 2014 (03.06.2014)
- (25) Filing Language: English
- (26) Publication Language: English
- (30) Priority Data:
61/830,553 3 June 2013 (03.06.2013) US
- (71) Applicant: PROFENSE, LLC [US/US]; 142 West Deer Valley Road, Phoenix, AZ 85027 (US).
- (72) Inventors: ROWE, Thomas; 33902 North 23rd Drive, Phoenix, AZ 85085 (US). O'DONNELL, Arthur; 1553 South Malabar Lane, Gilbert, AZ 85296 (US).
- (74) Agent: ONEY, Richard, E.; Tiffany & Bosco, P.A., 2525 E. Camelback Road, 3rd Floor, Phoenix, AZ 85016 (US).

(81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AO, AT, AU, AZ, BA, BB, BG, BH, BN, BR, BW, BY, BZ, CA, CH, CL, CN, CO, CR, CU, CZ, DE, DK, DM, DO, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, GT, HN, HR, HU, ID, IL, IN, IR, IS, JP, KE, KG, KN, KP, KR, KZ, LA, LC, LK, LR, LS, LT, LU, LY, MA, MD, ME, MG, MK, MN, MW, MX, MY, MZ, NA, NG, NI, NO, NZ, OM, PA, PE, PG, PH, PL, PT, QA, RO, RS, RU, RW, SA, SC, SD, SE, SG, SK, SL, SM, ST, SV, SY, TH, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, ZA, ZM, ZW.

(84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LR, LS, MW, MZ, NA, RW, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, RU, TJ, TM), European (AL, AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HR, HU, IE, IS, IT, LT, LU, LV, MC, MK, MT, NL, NO, PL, PT, RO, RS, SE, SI, SK, SM, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, KM, ML, MR, NE, SN, TD, TG).

[Continued on next page]

(54) Title: MINIGUN WITH IMPROVED BARREL CLAMP




FIG. 1A




FIG. 1B

(57) Abstract: An improved barrel clamp assembly for a multi-barreled minigun includes a barrel clamp tube having a front end, a rear end, and a plurality of longitudinal openings extending between the front end and the rear end. An impeller is mounted in the barrel clamp tube between the tube front end and the tube rear end. The impeller includes a plurality of impeller blades that are spaced around a periphery of the impeller and that project forward from a rear flange portion of the impeller and the impeller blades define a plurality of air channels. A barrel assembly includes the barrel clamp tube, a flash suppressor mounted to the front end of the barrel clamp tube, and a barrel clamp collar mounted to the rear end of the barrel clamp tube. The impeller is mounted to the barrel clamp tube between the flash suppressor and the barrel clamp collar.

**Declarations under Rule 4.17:**

- *as to applicant's entitlement to apply for and be granted a patent (Rule 4.17(ii))*
- *of inventorship (Rule 4.17(iv))*

— *with amended claims (Art. 19(1))*

(88) Date of publication of the international search report:
16 April 2015

Published:

- *with international search report (Art. 21(3))*

Date of publication of the amended claims: 4 June 2015