

PCT

WORLD INTELLECTUAL PROPERTY ORGANIZATION
International Bureau



INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification ⁶ : B21D 51/26		(11) International Publication Number: WO 97/12706																				
A1		(43) International Publication Date: 10 April 1997 (10.04.97)																				
(21) International Application Number: PCT/US96/14914		(72) Inventors: HARTMAN, Mark, W. ; 5 Rivers Edge, Lambertville, NJ 08530 (US). SHORE, Zeev, W. ; Unit 402, 18600 Village Drive, Hazel Crest, IL 60429 (US). TANG, James, J. ; 833 S. Elm Street, Palatine, IL 60067 (US). ASCHBERGER, Anton, A. ; 6661 Barrett Street, Downers Grove, IL 60516 (US). GOGOLA, Michael, R. ; 15421 Walnut Road, Oak Forest, IL 60452 (US). IRVINE, William, O. ; 11852 Lillis Lane, Golden, CO 80403 (US). TRNKA, Ralph, J. ; 8917 Mallard Road, Tinley Park, IL 60477 (US). WAHLER, Richard, O. ; 646 East Pompano Lane, Palatine, IL 60067 (US). WINKLESS, Robert, A. ; 10128 Kenton Avenue, Oak Lawn, IL 60453 (US). GOLDING, Richard, Mark, Orlando ; 10 S. 646 Lilac Lane #212, Hinsdale, IL 60521 (US). HARVEY, David, A. ; 43 Woodhill Drive, Grove, Wantage, Oxon OX12 0DE (GB).																				
(22) International Filing Date: 17 September 1996 (17.09.96)																						
(30) Priority Data:																						
<table border="0"> <tr> <td>60/004,679</td> <td>2 October 1995 (02.10.95)</td> <td>US</td> </tr> <tr> <td>08/542,422</td> <td>16 November 1995 (16.11.95)</td> <td>US</td> </tr> <tr> <td>08/551,073</td> <td>12 December 1995 (12.12.95)</td> <td>US</td> </tr> <tr> <td>9603110.9</td> <td>14 February 1996 (14.02.96)</td> <td>GB</td> </tr> <tr> <td>9604784.0</td> <td>6 March 1996 (06.03.96)</td> <td>GB</td> </tr> <tr> <td>08/621,795</td> <td>22 March 1996 (22.03.96)</td> <td>US</td> </tr> <tr> <td>08/683,575</td> <td>15 July 1996 (15.07.96)</td> <td>US</td> </tr> </table>			60/004,679	2 October 1995 (02.10.95)	US	08/542,422	16 November 1995 (16.11.95)	US	08/551,073	12 December 1995 (12.12.95)	US	9603110.9	14 February 1996 (14.02.96)	GB	9604784.0	6 March 1996 (06.03.96)	GB	08/621,795	22 March 1996 (22.03.96)	US	08/683,575	15 July 1996 (15.07.96)
60/004,679	2 October 1995 (02.10.95)	US																				
08/542,422	16 November 1995 (16.11.95)	US																				
08/551,073	12 December 1995 (12.12.95)	US																				
9603110.9	14 February 1996 (14.02.96)	GB																				
9604784.0	6 March 1996 (06.03.96)	GB																				
08/621,795	22 March 1996 (22.03.96)	US																				
08/683,575	15 July 1996 (15.07.96)	US																				
(71) Applicant: CROWN CORK & SEAL COMPANY, INC. [US/US]; 9300 Ashton Road, Philadelphia, PA 19136 (US).		(74) Agents: HEIST, Dale, M. et al. ; Woodcock Washburn Kurtz Mackiewicz & Norris, 46th floor, One Liberty Place, Philadelphia, PA 19103 (US).																				
		(81) Designated States: AL, AM, AT, AU, AZ, BB, BG, BR, BY, CA, CH, CN, CU, CZ, DE, DK, EE, ES, FI, GB, GE, HU, IL, IS, JP, KE, KG, KP, KR, KZ, LK, LR, LS, LT, LU, LV, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, TJ, TM, TR, TT, UA, UG, UZ, VN, ARIPO patent (KE, LS, MW, SD, SZ, UG), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, ML, MR, NE, SN, TD, TG).																				
		Published With international search report.																				

(54) Title: **SYSTEMS AND METHODS FOR MAKING DECORATIVE SHAPED METAL CANS**

(57) Abstract

A method of manufacturing a metallic can body (24) that is shaped distinctively in order to enhance its visual presentation to consumers includes, in one embodiment, steps of providing a can body blank (10) that has a sidewall that is of a substantially constant diameter; providing a mold unit (38) that has at least one mold wall (46) that defines a mold cavity conforming a desired final shape of the can body (24); positioning the can body blank (10) within the mold cavity (46); and supplying a pressurized fluid into the mold cavity so that the can body blank (10) is forced by pressure against the mold wall (46), causing the can body blank (10) to assume the desired final shape of the can body (24). Axial compression is preferably applied to the can body blank in order to reduce internal stresses during molding of the container. A second embodiment includes steps of radially deforming the can body blank in selected areas by selected amounts to achieve an intermediate can body that is radially modified, but is still symmetrical about its axis; and superimposing a preselected pattern of mechanical deformations that have an axial component onto the intermediate can body. Related apparatus and processes are also disclosed.

