

SPECIFICATION

Cork Extracting Apparatus

The present invention pertains to apparatus for extracting corks from bottles. A number of features are desirable in such an apparatus. One of the most important of these is that the corkscrew portion of the apparatus be well centered in the cork during operation, so as to ensure the removal of the entire cork, and minimize the possibility of breaking the cork and permitting the resulting fragments to fall into the wine in the bottle. Another important consideration is that the corkscrew must be pulled in a substantially straight line along its own axis when the cork is being removed, and this axis should ordinarily be substantially aligned with that of the bottle, so as to facilitate removal.

Although numerous types of cork extractors have been designed in the past, they have fallen short of adequately filling the various needs described above in a simple and relatively inexpensive device.

The present invention provides apparatus for extracting a cork from a bottle comprising a holder including

- guide means having a guide passageway extending generally longitudinally therethrough and having a generally radially facing guide surface means;
- stop means engageable with the bottle to limit downward (as hereinafter defined) movement of said holder with respect to the bottle; and
- grip means engageable with the bottle to generally coaxially align said guide means with the bottle and comprising a plurality of longitudinally extending circumferentially spaced, radially deflectable gripping elements connected to and spaced downwardly (as hereinbefore defined) from said guide means and
- approximately equally resiliently biased to a normal unflexed radial position; and
- a cork-engaging member including a corkscrew longitudinally movable in said guide passage selectively with or without simultaneous rotation and having a diameter sized to lie closely adjacent said guide surface means.

Thus, the grip means in conjunction with the stop means of the holder serve to generally radially center and coaxially align the guide means, and thus the corkscrew received therein, with the bottle and its cork. By rotating the cork engaging member and simultaneously exerting a downward force thereon, the corkscrew may be driven into the cork while still properly centered and aligned therewith by the holder. More particularly, the gripping elements provide a relatively inexpensive means for laterally gripping the bottle by its drip ring and/or neck. The approximately equal biasing of the various gripping elements prevents canting of the holder on the bottle thereby assuring that the guide means is properly aligned with the cork. Furthermore, the radial deflectability of the gripping elements enables them to accommodate

bottles of various sizes.

In preferred embodiments, the corkscrew is helical and carries abutment means engageable with the holder to limit downward movement of the cork engaging member with the holder whereby, when the abutment means comes into abutment with the holder, further downward movement of the cork engaging member is prevented and continued rotation of that member in the same direction will cause the cork to rise on the helical corkscrew, the guide means being spaced above the top of the bottle by a sufficient distance to permit such movement.

The aforementioned stop means are preferably in the form of one or more downwardly facing shoulders defining a plane generally transverse to the holder and engageable with the top of the bottle. This contrasts with the various prior art devices in which a bevelled, frusto-conical, paraboloid, or otherwise tapered shoulder is provided, and thereby enhances the tendency of the holder to steadily align itself with the bottle, rather than permitting canting and wobbling as do the prior art devices. To further augment this tendency, the grip means may be provided with bearing surfaces spaced downwardly from the stop shoulders and engageable to urge the stop shoulders downwardly into tight engagement with the top of the bottle. For example, the aforementioned gripping elements may have their outer sides flared radially outwardly near the bottom ends thereof to provide such bearing surfaces.

Another preferred feature of the invention is that the cork engaging member should be completely separable from the holder. This permits the tip of the corkscrew to be used to sever the foil which covers the cork and top of an unopened bottle of wine. The separability of the cork-engaging member also permits it to be used as a simple corkscrew without the holder if, for any reason, such use might be desired. The separability of two main portions of the apparatus also permits each of these portions to be more readily cleaned.

Furthermore, the corkscrew itself may be improved by the provision of a central body, e.g. of high tensile metal, covered by an outer layer of friction reducing material such as polytetrafluoroethylene on at least a portion of the downwardly facing surfaces of the central body. This greatly enhances the ease with which the corkscrew may be driven into the cork. This friction reducing expedient not only virtually eliminates any problem in easily penetrating a tight cork, but also permits the use of design features in the central body, which could not be used without the friction reducing layer, and which themselves enhance the ease of insertion and otherwise improve the corkscrew. Accordingly, the friction reducing layer on the corkscrew is largely instrumental in making the relatively simple apparatus described above effective in easily penetrating and properly removing even extremely hard and/or tight corks.

In most instances, it is preferable to provide the friction reducing layer along substantially the entire length of the central body. However, it is within the scope of this invention to coat only the lowermost portion of the central body, preferably that portion which enters the cork.

The corkscrew preferably is provided with an improved lower pointed tip portion which is formed in such a way that it eliminates the tendency for small cork fragments to be broken away, even when the corkscrew is driven completely through the cork. This effect is further enhanced by the provision of a friction reducing layer, as described above, so that the possibility of contamination of wine by cork fragments is virtually eliminated.

More specifically, the tip portion of a helical corkscrew in the preferred embodiment has its downwardly facing surfaces on lead with the helix of the downwardly facing surfaces of the upper portion of the corkscrew, i.e. the downwardly facing surfaces of the corkscrew from a continuous helix of constant lead or pitch. The aforementioned friction reducing material is included at least one the downwardly facing tip surfaces. However, the tip portion has its thickness reduced along non-downwardly facing surfaces thereof to form the pointed tip.

Embodiments of the invention will now be further described with reference to the accompanying drawings, in which:

Fig. 1 is a longitudinal sectional view, with some parts being shown in elevation, of a first embodiment of the apparatus of the invention positioned on a bottle for extracting the cork therefrom;

Fig. 2 is a view similar to that of Fig. 1 showing the apparatus in another position as the cork is being removed from the bottle;

Fig. 3 is a transverse cross-sectional view taken on line 3—3 of Fig. 1;

Fig. 4 is an elevational view of a preferred embodiment of the cork-engaging member;

Fig. 5 is an enlarged detailed elevational view taken on line 5—5 of Fig. 4;

Fig. 6 is a further enlarged view taken on line 6—6 in Fig. 5;

Fig. 7 is a further enlarged cross-sectional view taken on line 7—7 of Fig. 5; and

Fig. 8 is a rectified longitudinal sectional view through the tip portion of the corkscrew.

Figs. 1, 2, and 3 generally illustrate a cork extracting apparatus according to the invention, while Figs. 4—7 show, in greater detail, a preferred cork-engaging member therefor.

Referring first to Figs. 1 and 2, the apparatus generally comprises two main portions, namely a holder and a cork engaging member. The holder includes a main body member 10 which, in the embodiment shown, is integrally molded from a suitable plastic. The main body member 10 includes a pair of diametrically opposed circumferentially spaced apart, longitudinally extending flexible legs 12, each of which comprises an upper portion 12a and a lower

portion 12b. The main body member 10 of the holder includes an annulus 14 interconnecting and extending upwardly from the upper end of legs 12. Annulus 14 serves as the foundation portion of the guide means of the holder, said guide means further including a bushing member 16 rigidly mounted within annulus 14 in any suitable manner. Bushing member 16 is preferably formed of a friction reducing material such as polytetrafluoroethylene and is in the form of a sleeve which extends longitudinally along the inner surface of annulus 14 and has an annular flange extending radially outwardly from the upper end and abutting the uppermost surface of annulus 14. It is noted that, as used throughout the specification terms such as "upper", "lower", "upwardly", and "downwardly" refer to the apparatus as shown in the drawings and as it would be positioned for use on an upright bottle. Such terms are used for convenience, and should not be constructed in a limiting sense.

The other major portion of the cork extracting apparatus is a cork engaging member including a helical corkscrew 18 and a handle 20. The corkscrew 18 serves as the guide portion of the cork engaging member and is thus removably receivable in bushing 16 of the guide means of the holder. Corkscrew 18 is longitudinally movable in the bore defined by surface 16a either with or without simultaneous rotation. The outer diameter of the helix of corkscrew 18 is sized to lie closely adjacent the cylindrical radially inwardly facing surface 16a of the bushing 16 of the guide means. Additionally, the length of cylindrical surface 16a is at least as long as, and preferably longer than, the pitch of the helix of corkscrew 18. Accordingly, surface 16a serves as the guide surface means of the holder, defining a guide passageway for corkscrew 18 and maintaining it in substantial coaxial alignment with the guide means 14, 16.

The handle 20 includes a lowermost annular hub 20a and a pair of diametrically opposed radially extending arms 20b. Hub 20a is sized and positioned to abut the upper surface of bushing 16 as corkscrew 18 moves downwardly therein to thereby limit downward movement of the cork engaging member 18, 20 with respect to the holder 12, 14, 16.

To use the apparatus, the holder 12, 14, 16 is emplaced over the top of the bottle 22. Each of the legs 12 has a flange 12c extending radially inwardly adjacent the juncture of the upper and lower portions 12a and 12b respectively of the leg. The lower surfaces 12d of the flanges 12c lie in a common plane transverse to the longitudinal axis of the holder. Thus, the surfaces define stop shoulders which abut the top of the bottle 22 and thereby limit downward movement of the holder with respect thereto. Accordingly, when the holder has been thus placed on the bottle 22, as shown in Fig. 1, the holder legs 12 are positioned with the upper portions 12a thereof extending upwardly from the top of the bottle 22 whereby the guide means 14, 16 is spaced from the top of

the bottle and a cork receiving space is formed between the upper portions 12a of the two holder legs and intermediate the guide means 14, 16 and the flanges 12c.

- 5 The lower portions 12b of holder legs 12 extend downwardly along the neck of bottle 22. These portions 12b serve as the gripping elements of the holder. Legs 12 are formed of a suitable lightweight material such as plastic, aluminum, or the like and have sufficient inherent flexibility and resiliency to permit gripping elements 12b to be flexed either inwardly or outwardly from the normal unflexed radial position shown in Fig. 1. Thus, the gripping elements 12b may be grasped and squeezed inwardly by the user with one hand to grip the neck of bottle 22 and firmly position the holder thereon. The flexibility of holder legs 12 also permits the holder to accommodate bottles of different sizes.

- 20 Because holder legs 12 are formed of the same material, are substantially identical in size and configuration, and are symmetrically positioned with respect to annulus 14, they are substantially equally biased to the normal unflexed radial position shown in Fig. 1. Accordingly, when they are urged inwardly by the user, as indicated by the arrows B in Fig. 2, they tend to maintain the guide means 14, 16 in a position which is substantially centered with respect to the bottle 22 and its cork 24, even if the diameter of the drip ring 22a of the bottle neck differs from the distance between the adjacent portions of the gripping elements 12b. Furthermore, such equal resilient biasing further helps to prevent canting of the holder on the bottle and thereby maintain the axis of the guide means 14, 16 substantially coaxially aligned with that of the bottle 22.

- 40 This latter effect is further enhanced by the fact that the stop shoulders 12d define a plane transverse to the two aforementioned axes. In order to take full advantage of this expedient, the gripping elements, i.e. lower portions 12b of the holder legs 12, are flared radially outwardly at their lower ends whereby generally upwardly facing bearing surfaces 12e are formed on their outer sides. This assists the user in squeezing inwardly on gripping elements 12b while simultaneously bearing down on surfaces 12e to thereby hold both shoulders 12d in firm engagement with the top of the bottle.

- 50 When the gripping elements are thus employed, they will engage and grip the bottle neck at least at the drip ring 22a. It is primarily the flexibility of the upper portions 12a of the holder legs which permits radial flexing of gripping elements 12b to accommodate drip rings of differing sizes. However, gripping elements 12b are additionally flexible and resilient within themselves. Thus, depending upon the diameter of the bottle to be gripped and the length and degree of flexibility of gripping elements 12b, the lower ends of the gripping elements 12b may be flexed inwardly to further engage and grip the bottle neck at a second location spaced

- downwardly from drip ring 22a. It has been observed that the tapered necks of most wine bottles reach an outer diameter approximately equal to that of their drip rings at a location around 2 to 2.5 inches (about 5 to 6.5cm.) below the top of the bottle. Accordingly, if the gripping elements 12b are sized so that there is a like distance between stop shoulders 12d and the points at which the gripping elements 12b begin to flare outwardly, this double gripping action may be more readily achieved with a minimum of distortion of the gripping elements. Nevertheless, even where such double gripping is not possible, due to the size of the bottle and/or the length of gripping elements 12b, proper alignment of the guide means 14, 16 with the cork 24 can still be maintained by the combined action of engaging the upper edge of bottle 22 with shoulders 12d and gripping drip ring 22a with gripping elements 12b.

- 85 In any event, it is desirable to make the gripping elements 12b at least long enough to enable the user to firmly grip the holder in an area primarily surrounding and aligned with the bottle neck, as opposed to an area located generally thereabove. It will also be observed that legs 12 are inwardly concave (as shown in Fig. 3) to enhance the gripping ability thereof.

- Referring to Figs. 1 and 2 together, the operation of the cork extractor is as follows. After the holder has been emplaced on the bottle as shown in Fig. 1 and described hereinabove, the corkscrew 18 is inserted in the bushing 16 so that its lower end abuts the top of the cork 24. The user then grasps gripping elements 12b with one hand urging them radially inwardly and downwardly (as indicated by the arrow B) to grip the bottle neck as shown in Fig. 2. With the other hand, the user grasps the handle 20 and rotates the cork engaging member 18, 20 (as indicated by arrow A) while simultaneously bearing down on it to drive the corkscrew 18 into the cork 24. The length of corkscrew 18 is such that when hub 20a comes into engagement with the upper surface of bushing 16 thereby limiting further downward movement of the cork engaging member, the corkscrew 18 ordinarily will have been driven through the lower end of cork 24. With a larger cork, the screw may not pass through lower end of the cork when the cork engaging member ceases its downward movement. However it will, in any event, have penetrated a substantial portion of the length of the cork. The user then continues to rotate the cork engaging member 18, 20 in the direction of arrow A. Since the abutment of hub 20a with bushing 16 prevents further downward movement of the cork engaging member, such rotation will cause cork 24 to climb upwardly on the corkscrew 18. The user can observe the cessation of upward movement of cork 24 through the space between portions 12a of the two holder legs. He can then remove the holder from the bottle neck along with the cork engaging member and cork. Even if a small portion of the

lower end of the cork should still be disposed in the bottle, the cork will at this point have been raised a sufficient distance so that it offers very little resistance to this lifting action. Thus, the user need exert only a very slight upward force to complete the removal of the cork.

The extractor apparatus can then be used to remove the cork 24 from the corkscrew 18. By grasping the holder legs 12 and urging them radially inwardly, the user can grip the cork 24 with the flanges 12c. He can then remove the corkscrew 18 by simply rotating handle 20 in a direction opposite to that used to initially drive the corkscrew 18 into cork 24. Alternatively, cork 24 can be gripped by the user's fingers directly through the spaces between upper portions 12a of the holder legs.

From the foregoing it can be seen that the apparatus of Figs. 1, 2 and 3 provides a relatively simple and economical means by which a user can easily and accurately guide the corkscrew into the cork in a centered and coaxially aligned orientation. The holder of the apparatus permits the user to get a firm grip on the bottle while maintaining the guide means steadily aligned with the cork. The guide means in turn properly directs the corkscrew by guiding it via the O.D. of its own helix. Furthermore, it can be seen that the apparatus substantially reduces the force which must be exerted in extracting the cork from the bottle by the threading interaction between the cork and screw, as opposed to a straight pull.

The fact that the cork engaging member 18, 20 is removable from the holder results in additional advantages. Not only does this removability permit the cork engaging member to be used as an ordinary corkscrew, if and when desired, but also allows the sharp end portion thereof to be used to sever the foil covering the top of the bottle before removal of the cork. Furthermore, the separability of the two major portions of the apparatus permits both portions to be more easily cleaned and permits one cork engaging member 18, 20 to be used alternatively with different holders.

The invention further comprises improvements within the corkscrew per se. As best seen in Figs. 4—8, one embodiment of corkscrew 18' is formed from a length of high tensile metal wire wound into a helix. This wire forms the central metallic body 19 of the corkscrew. The end of the wire destined to be disposed lowermost or distal handle 20 in the finished product is formed into a pointed tip portion 23. As best shown in Figs. 5 and 6, no metal is removed from the downwardly facing surfaces 23a of tip portion 23 whereby they remain on lead with the helix of the downwardly facing surface, 18a of the main portion of the corkscrew thereabove, i.e.

surfaces 18a and 23a define a continuous helix of constant lead or pitch. However, the thickness of tip 23 is reduced along non-downwardly facing surfaces, and preferably substantially upwardly facing surfaces 23b to form the pointed tip. As used herein in relation to the description of Figs.

4—8 a surface will be considered "downwardly" facing if a vector extending away from the surface and normal thereto has a vertically downwardly directed vector component. The reduction in thickness to form surfaces 23b may be performed by any suitable metal removing technique. Fig. 8 is a rectified longitudinal sectional view of the lower part of corkscrew 18', i.e. as if the helical wire were straightforward. The surface 23b preferably extends along a length of said wire sufficient to form a full turn on the helix, although shorter ground surfaces may also be satisfactory.

Finally, the wire or central body 19 is coated with a layer 25 of friction reducing material. For the sake of clarity of illustration, layer 25 is shown only in Figs. 7 and 8. The friction reducing material of layer 25 may be a polytetrafluoroethylene or any other suitable material bonded to central body 19 by techniques known in the art.

As used herein, the term "friction-reducing" will be constructed to cover any material which reduces the friction between the corkscrew and cork to a significantly greater degree than could be achieved by merely polishing the central body.

Although the polytetrafluoroethylenes, and similar plastics produce particularly striking results, other materials such as molybdenum disulfide or silicone coatings could also be used.

The primary purpose of layer 25 is to increase the ease with which the corkscrew may be driven into the cork. Referring again to the embodiment shown at 18 in Fig. 1, the layer 25 is provided only on the lower portion of the corkscrew, terminating at line 27. This lower portion includes the part of the corkscrew which is driven into the cork before the latter begins to rise to the corkscrew, the upper uncoated portion of the corkscrew being spaced from the bottle neck by the holder. When the cork begins to rise in this manner, it also begins to emerge from the bottle, and as it so emerges, it expands so that its friction against the corkscrew is drastically reduced. Thus, the need for the friction reducing material is much less along the upper portion of the corkscrew which, due to the abutment between the handle 20 and the bushing 16 and the spacing of bushing 16 from the upper end of the bottle neck, is permitted to engage the cork only as it emerges from the bottle in an expanded state.

Accordingly, while leaving the upper portion of the corkscrew uncoated does not substantially detract from the performance of the apparatus, it may decrease the cost of production. Additionally, it is primarily the upper portion of the corkscrew which engages the bushing 16. If this upper portion were coated with the friction reducing material, depending on the type of friction reducing material employed, such engagement could facilitate wearing away of the material from the upper portion of the corkscrew thereby detracting from its appearance. Thus, in some embodiments it may actually be preferable to provide the friction reducing material only on the lower portion of the corkscrew.

In other embodiments, however, it may be

preferable to coat a greater portion of the central helical body of the corkscrew. Figs. 4—8 disclose such an embodiment in which the corkscrew 18' has its helical body 19 coated along its entire length, exclusive of the end portion received in handle 20, with the friction reducing layer 25.

To reduce the possibility of wear of such layer 25 from the upper portion of central body 19, the wire of said body is ground to form a radially outwardly facing flat 21 to provide a greater surface for contact with bushing 16.

In any event, it has been found that, where a plastic friction reducing material such as polytetrafluoroethylene is used, even if such material does appear to wear away from the central body (including its lower portion) in use, a certain amount of the plastics remains in the surface of the metal body 19. Thus, such wear does not substantially change the ability of the corkscrew to penetrate a cork. On the contrary, any differences in the ease of penetration due to normal wear is negligible.

In both corkscrew embodiments 18 and 18', the friction reducing layer extends about the entire circumference of the underlying wire. However, good results can still be obtained by coating only the downwardly facing surfaces, such as 18a and 23a. Likewise, while the coating preferably extends over the lower portion of the corkscrew for a length at least approximately equal to the length of an average cork, i.e. about 5cm. a substantial increase in the ease of insertion may be obtained by coating only the tip portion 23 or the lower surfaces 23a thereof.

Friction reducing coatings as described above have been found to dramatically increase the ease with which a corkscrew such as 18 or 18' may be driven into a cork. Indeed, the reduction in friction is so great as to permit the use, in central body 19, of design features and parameters which would not be practicable without layer 25. For example, the wire of which body 19 is formed may be thinner than in conventional screws, and a wider range of helix leads is available. Such design features in turn may even further enhance the ease of insertion. Thus, for example, the use of layer 25, especially in cooperation with other friction reducing features made possible thereby substantially ensures the capability of driving corkscrew 18 to a sufficient depth in cork 24, even where the latter is relatively hard and/or tightly engaged in the bottle neck, and even though the central body 19 of the corkscrew might be so flexible that it would, in the absence of layer 25, be unwound or otherwise distorted in an attempt to drive it into a cork.

The manner in which tip portion 23 is formed, together with the use of friction reducing layer 25, substantially eliminates the tendency for small fragments of cork to be broken off and fall into the bottle even though the tip portion 23 is driven completely through the lower end of the cork. As noted hereinabove, the removal of the material from the tip portion 23 to reduce its thickness and form a point is from non-downwardly facing

surfaces 23b. The surfaces 23a, which do have at least some downward component of orientation, remain on lead with the helix defined by the downwardly facing surfaces 18a of the main upper portion of the corkscrew, i.e. surfaces 18a and 23a define a helix of constant lead or pitch. Thus, surface 23a are also on lead with or parallel to the helical path of movement of the corkscrew through the cork. Accordingly, a tip portion 23 is driven through the cork, the wedging action thereof will exert a compressive force perpendicular to surfaces 23b since they are not on lead with or parallel to the path of movement. It can be seen that a vector perpendicular to non-downwardly facing surfaces 23b will either face directly vertically upwardly, or will at least have a substantial upward component and no downward component, depending on its precise position on surfaces 23b. On the other hand, any vector perpendicular to any portion of surfaces 23a will have a vertically downward component, but no force will be exerted in the directions of these latter vectors for reasons mentioned hereinabove. Accordingly, as tip portion 23 breaks through the lower end of cork 24, there will be no downward compressive force on the cork and thus no tendency to break away any small fragments. On the contrary, the compressive force on the cork by the wedging action of tip portion 23 will be directed substantially vertically upwardly and will thus tend to help pull the cork itself in an upward direction.

This effect is further enhanced by the friction reducing coating 25 along at least surfaces 23a, and preferably along a greater portion of central body 19. This is due not only to the reduction in friction per se but also to the fact that such reduction in turn permits a smaller diameter wire to be used for the central body. Of course, the smaller the diameter of the wire passing through the cork, the less likely is the chance of a piece of cork chipping off. A cork extracting apparatus of the type shown in Figs. 1—3 and having a corkscrew with a tip portion formed in accord with Figs. 5 and 6 and also having a small diameter central body fully coated with a layer of a polytetrafluoroethylene has been used in tests with corks of various ages, densities, etc. These preliminary tests have indicated that there is little or no possibility of a chip or fragment of cork breaking away and falling into the bottle as the lower end of the tip portion of the corkscrew breaks through the lower end of the cork.

The reader's attention is drawn to my co-pending Application No. 7923805 (Serial No. 2027681), from which the present application is divided, and which claims apparatus for extracting a cork from a bottle comprising:

a corkscrew comprising a helical body and an outer layer of friction-reducing material;
guide means receiving said corkscrew and permitting longitudinal and rotative movement of said corkscrew;

bottle-engaging means connected to said guide means for positioning said guide means and

said corkscrew in generally coaxial alignment with the neck of said bottle, said bottle-engaging means including stop means for limiting downward (as hereinbefore defined) movement of

5 said guide means with respect to said bottle;

spacer means interconnecting said guide means and said bottle-engaging means and spacing said guide means upwardly (as hereinbefore defined) from said bottle-engaging

10 means, said spacer means defining an opening for receipt of said cork as it emerges from said bottle;

and abutment means carried by said corkscrew for limiting downward (as hereinbefore defined) movement of said corkscrew with respect to said

15 guide means;

said corkscrew being a length such that, when said abutment means are engaged to so limit downward (as hereinbefore defined) movement of said corkscrew, said corkscrew extends into said

20 cork-receiving opening whereby said cork may move threadedly upwardly (as hereinbefore defined) on said corkscrew as said corkscrew is rotated to withdraw said cork from said bottle.

The reader's attention is also drawn to my co-
25 pending Application No. 8208168, also divided out of Application No. 7923805, and which claims a helical corkscrew including a main portion and a pointed tip portion; said tip portion having its downwardly facing surfaces (as

30 hereinbefore defined) substantially on lead with the helix of the downwardly facing surfaces of said main portion, but having its thickness reduced along non-downwardly facing surfaces to form said pointed tip portion.

35 Claims

1. Apparatus for extracting a cork from a bottle comprising a holder including:

guide means having a guide passageway
40 extending generally longitudinally therethrough and having a generally radially facing guide surface means;

stop means engageable with the bottle to limit
45 downward (as hereinbefore defined) movement of said holder with respect to the bottle; and

grip means engageable with the bottle to
generally coaxially align said guide means with the bottle and comprising a plurality of
50 longitudinally extending, circumferentially spaced, radially deflectable gripping elements connected to and spaced downwardly (as hereinbefore defined) from said guide means and approximately equally resiliently biased to a normal unflexed radial position; and

a cork-engaging member including a corkscrew
55 longitudinally movable in said guide passage selectively with or without simultaneous rotation and having a diameter sized to lie closely adjacent said guide surface means.

2. Apparatus according to Claim 1, wherein
60 said cork engaging member further comprises abutment means carried on said corkscrew and engageable with said holder to limit downward movement of said cork-engaging member with respect to said holder.

65 3. Apparatus according to Claim 1 or Claim 2, wherein said corkscrew is helical and wherein said guide passageway is cylindrical and has a length at least as long as the pitch of the helix of said corkscrew.

70 4. Apparatus according to any preceding claim, wherein said stop means comprise generally downwardly facing stop shoulder means engageable with the top of the bottle, said gripping elements extending generally

75 downwardly below said stop shoulder means.

5. Apparatus according to any preceding claim, wherein said gripping elements are radially resiliently flexible.

6. Apparatus according to any preceding claim,
80 wherein said holder comprises a plurality of longitudinally extending, circumferentially spaced holder legs, each of said holder legs having a lower portion forming a respective one of said gripping elements and an upper portion

85 connecting said respective gripping elements to said guide means.

7. Apparatus according to Claim 6, wherein each of said holder legs defined a respective downwardly facing stop shoulder on its inner side,
90 said stop shoulders being generally coplanar and together comprising said stop shoulder means.

8. Apparatus according to Claim 6 or Claim 7, wherein said upper portion of each of said holder legs is radially resiliently flexible.

95 9. Apparatus according to Claim 8, wherein said lower portion of each of said holder legs is radially resiliently flexible.

10. Apparatus according to any one of Claims 6—9, wherein said holder legs include generally
100 upwardly facing bearing surfaces on their outer sides, said bearing surfaces being engageable to urge said stop shoulder means downwardly into tight engagement with the top of said bottle.

11. Apparatus according to Claim 10, wherein
105 said bearing surfaces are spaced downwardly from said stop shoulder means.

12. Apparatus of Claim 11, wherein each of said holder legs is flared radially outwardly adjacent its lower end to form a respective one of
110 said bearing surfaces.

13. Apparatus according to any one of Claims 6—12, when appendant to Claim 2, wherein said upper portions of said holder legs define therebetween an opening for receipt of said cork as it emerges from said bottle, said corkscrew
115 being of a length such that, when said abutment means are engaged with the holder to limit downward movement of said corkscrew, said corkscrew extends into said opening whereby

120 said cork may move threadedly upward on said corkscrew as said corkscrew is rotated to withdraw said cork from said bottle.

14. Apparatus according to any preceding claim, wherein said cork engaging member is
125 separable from said holder.

15. Apparatus according to any one of Claims 1—12, wherein said corkscrew comprises an outer layer of friction reducing material on at least



said corkscrew in generally coaxial alignment with the neck of said bottle, said bottle-engaging means including stop means for limiting downward (as hereinbefore defined) movement of

5 said guide means with respect to said bottle;

spacer means interconnecting said guide means and said bottle-engaging means and spacing said guide means upwardly (as hereinbefore defined) from said bottle-engaging

10 means, said spacer means defining an opening for receipt of said cork as it emerges from said bottle;

and abutment means carried by said corkscrew for limiting downward (as hereinbefore defined) movement of said corkscrew with respect to said

15 guide means;

said corkscrew being a length such that, when said abutment means are engaged to so limit downward (as hereinbefore defined) movement of

20 said corkscrew, said corkscrew extends into said cork-receiving opening whereby said cork may move threadedly upwardly (as hereinbefore defined) on said corkscrew as said corkscrew is rotated to withdraw said cork from said bottle.

The reader's attention is also drawn to my co-
25 pending Application No. 8208168, also divided out of Application No. 7923805, and which claims a helical corkscrew including a main portion and a pointed tip portion, said tip portion having its downwardly facing surfaces (as
30 hereinbefore defined) substantially on lead with the helix of the downwardly facing surfaces of said main portion, but having its thickness reduced along non-downwardly facing surfaces to form said pointed tip portion.

35 Claims

1. Apparatus for extracting a cork from a bottle comprising a holder including:

guide means having a guide passageway extending generally longitudinally therethrough
40 and having a generally radially facing guide surface means;

stop means engageable with the bottle to limit downward (as hereinbefore defined) movement of said holder with respect to the bottle; and

45 grip means engageable with the bottle to generally coaxially align said guide means with the bottle and comprising a plurality of longitudinally extending, circumferentially spaced, radially deflectable gripping elements connected
50 to and spaced downwardly (as hereinbefore defined) from said guide means and approximately equally resiliently biased to a normal unflexed radial position; and

a cork-engaging member including a corkscrew
55 longitudinally movable in said guide passage selectively with or without simultaneous rotation and having a diameter sized to lie closely adjacent said guide surface means.

2. Apparatus according to Claim 1, wherein
60 said cork engaging member further comprises abutment means carried on said corkscrew and engageable with said holder to limit downward movement of said cork-engaging member with respect to said holder.

65 3. Apparatus according to Claim 1 or Claim 2, wherein said corkscrew is helical and wherein said guide passageway is cylindrical and has a length at least as long as the pitch of the helix of said corkscrew.

70 4. Apparatus according to any preceding claim, wherein said stop means comprise generally downwardly facing stop shoulder means engageable with the top of the bottle, said gripping elements extending generally
75 downwardly below said stop shoulder means.

5. Apparatus according to any preceding claim, wherein said gripping elements are radially resiliently flexible.

6. Apparatus according to any preceding claim,
80 wherein said holder comprises a plurality of longitudinally extending, circumferentially spaced holder legs, each of said holder legs having a lower portion forming a respective one of said gripping elements and an upper portion
85 connecting said respective gripping elements to said guide means.

7. Apparatus according to Claim 6, wherein each of said holder legs defined a respective downwardly facing stop shoulder on its inner side,
90 said stop shoulders being generally coplanar and together comprising said stop shoulder means.

8. Apparatus according to Claim 6 or Claim 7, wherein said upper portion of each of said holder legs is radially resiliently flexible.

95 9. Apparatus according to Claim 8, wherein said lower portion of each of said holder legs is radially resiliently flexible.

10. Apparatus according to any one of Claims 6—9, wherein said holder legs include generally
100 upwardly facing bearing surfaces on their outer sides, said bearing surfaces being engageable to urge said stop shoulder means downwardly into tight engagement with the top of said bottle.

11. Apparatus according to Claim 10, wherein
105 said bearing surfaces are spaced downwardly from said stop shoulder means.

12. Apparatus of Claim 11, wherein each of said holder legs is flared radially outwardly adjacent its lower end to form a respective one of
110 said bearing surfaces.

13. Apparatus according to any one of Claims 6—12, when appendant to Claim 2, wherein said upper portions of said holder legs define therebetween an opening for receipt of said cork as it emerges from said bottle, said corkscrew being of a length such that, when said abutment means are engaged with the holder to limit downward movement of said corkscrew, said
115 corkscrew extends into said opening whereby said cork may move threadedly upward on said corkscrew as said corkscrew is rotated to withdraw said cork from said bottle.

14. Apparatus according to any preceding claim, wherein said cork engaging member is
125 separable from said holder.

15. Apparatus according to any one of Claims 1—12, wherein said corkscrew comprises an outer layer of friction reducing material on at least



a portion of the downwardly facing surfaces thereof.

16. Apparatus according to Claim 15, wherein said friction reducing material extends over substantially the entire surface area of said corkscrew.

17. Apparatus according to Claim 15 or Claim 16, wherein said friction reducing material is a polytetrafluoroethylene.

18. Apparatus according to any preceding claim, wherein said corkscrew is helical and comprises a main portion and a pointed tip portion, said tip portion having its downwardly

- 15 facing surfaces substantially on lead with the helix of the downwardly facing surfaces of said main portion, but having its thickness reduced along non-downwardly facing surfaces to form said pointed tip portion.

19. Apparatus according to any preceding claim, wherein a handle is affixed to the upper end of said corkscrew.

20. Apparatus for extracting a cork from a bottle, according to Claim 1 and substantially as hereinbefore described with reference to the accompanying drawings.