

CHISEL HOLDER, AND CHISEL HOLDER SYSTEM COMPRISING A CHISEL HOLDER AND A BASE PART

Description

The present invention relates to a chisel holder, comprising a body region having a chisel-receiving opening which is open at least toward a chisel-insertion side of the body region and a fastening shank which extends from a supporting side of the body region and which has a shank longitudinal axis, wherein the body region has, on its supporting side, a first supporting surface region.

A chisel holder of said type for a road milling machine or the like is known from DE 43 22 401 C2. The chisel-receiving opening of said known chisel holder is open at its end remote from the chisel-insertion side, that is to say at the supporting side, toward the first supporting surface region. The fastening shank extends from the body region in a region laterally adjacent to that portion of the body region which has the chisel-receiving opening. In a base part which is provided for a chisel holder of said type, which base part is to be fixed to a milling roller or the like by welding, a first counterpart supporting surface region is provided so as to be assigned to the first supporting surface region. When a fastening shank is inserted into a fastening shank receiving opening of the base part,

the first supporting surface region of the chisel holder bears against the first counterpart supporting surface region of the base part, such that a defined positioning of the chisel holder on the base part is basically predetermined. A spacing is provided between that portion of the body region which bears the fastening shank and the opposite side of the base part in order to provide a so-called repositioning space for the chisel holder which allows the fastening shank to penetrate deeper into the fastening shank receiving opening if wear occurs in the region of the first supporting surface region and/or of the first counterpart supporting surface region.

Even though the first supporting surface region and thus also the first counterpart supporting surface region are approximately orthogonal with respect to a chisel-receiving opening longitudinal axis and consequently also to a chisel longitudinal axis, it is possible during milling operation for transverse loads to arise which lead to considerable torsion and shear loading at the location where the fastening shank adjoins the body region, which loading may in unfavorable situations lead to breaking of the fastening shank even if the fastening shank is formed with a relatively large shank cross-sectional area.

Embodiments of the present invention seek to provide a chisel holder and a chisel holder system having a chisel holder and a base part, in which, with optimized introduction

of force, a lower mechanical loading in particular of the fastening shank can be attained.

According to a first aspect of the present invention, there is provided a chisel holder, comprising a body region having a chisel-receiving opening which is open at least toward a chisel-insertion side of the body region, a fastening shank which extends from a supporting side of the body region and which has a shank longitudinal axis, wherein the body region has, on its supporting side, a first supporting surface region, characterized in that the body region, on its supporting side, has a second supporting surface region which is angled in relation to the first supporting surface region, and/or in that the first supporting surface region comprises a first supporting surface and a second supporting surface which is angled in relation to the first supporting surface.

In the chisel holder constructed according to embodiments of the invention, as a result of the support which takes place over a larger area and which has a self-centering effect as a result of the angled configuration, the fastening shank may be relieved of load in its portion adjoining the body region. Alternatively or in addition, in the chisel holder according to embodiments of the invention, as a result of the angled configuration of two supporting surfaces of the first supporting surface region, it is likewise possible to achieve centering of the

chisel holder and consequently a reduction of the transverse forces introduced in the fastening shank. This, too, contributes to a reduced loading of the fastening shank.

In order, in the chisel holder according to embodiments of the invention and with an optimization of the centering characteristic provided therein, to permit easy access to a chisel received in the chisel-receiving opening, it is proposed that the chisel-receiving opening is open toward that supporting side substantially in the region of the first supporting surface region and that the fastening shank extends from the body region substantially in the region of the second supporting surface region.

The centering characteristic of the chisel holder constructed according to embodiments of the invention can be further improved in that the second supporting surface region comprises a first supporting surface and a second supporting surface which is angled in relation to the first supporting surface. In particular if the first supporting surface region also has two supporting surfaces which are angled relative to one another, it is thus the case that, on the chisel holder, a total of four supporting surfaces are provided which are angled relative to one another in pyramid form, in particular so as to result in a funnel-like configuration, which may prevent or at least reduce an introduction of force into the fastening shank and consequently entails a considerable

reduction of the loading thereof, in particular transversely with respect to its shank longitudinal axis.

Here, a highly uniform loading with regard to the introduction of force can be achieved if the first supporting surface and the second supporting surface of the first supporting surface region and/or of the second supporting surface region are arranged substantially symmetrically with respect to a holder central plane. It is pointed out here that the holder central plane may represent substantially the geometric center of the chisel holder and may for example be spanned by the shank longitudinal axis and a longitudinal axis of the chisel-receiving opening.

To optimize the loads occurring during milling operation, it may also be provided that a first angle enclosed between the first supporting surface and/or the second supporting surface of the first supporting surface region and the second supporting surface region lies in the range of 127° to 147° , and is preferably approximately 137° , and/or a second angle enclosed between the first supporting surface and the second supporting surface of the first supporting surface region lies in the range of 120° to 140° , and is preferably approximately 130° , and/or a third angle enclosed between the first supporting surface and the second supporting surface of the second supporting surface region lies in the range of 100° to 120° , and is preferably approximately 110° , and/or an angle enclosed between a

transition region between the first supporting surface and the second supporting surface of the first supporting surface region and a transition region between the first supporting surface and the second supporting surface of the second supporting surface region lies in the range of 121° to 141° , and is preferably approximately 131° .

Since, for manufacturing reasons, the various supporting surfaces of the chisel holder constructed according to embodiments of the invention are substantially planar, that is to say not curved, it is proposed, in order to permit a direct transition of such supporting surfaces into one another, that at least one supporting surface of the first supporting surface region and the second supporting surface region adjoin one another in a first transition region which extends in a linear and/or straight fashion.

According to a further embodiment of the present invention which may be advantageous for manufacturing reasons, it is proposed that the first supporting surface and the second supporting surface of the second supporting surface region adjoin one another in a second transition region which extends in an areal and/or straight fashion. It has been found that, in particular if the chisel holder is manufactured as a forged part, an approximately planar, areal region is formed at the transition region between the two supporting surfaces of the first supporting surface region, which approximately planar, areal region can be machined in a simple manner in terms of

manufacturing to form a second transition region which is areal or extends in straight fashion. It may be provided here in particular that the second transition region comprises a transition surface which is substantially orthogonal with respect to the holder central plane.

To keep the forces which act on the fastening shank transversely with respect to the shank longitudinal axis thereof, and which subject said fastening shank to shear loading in the region adjoining the body region, as low as possible, it is proposed that a longitudinal central axis of the chisel-receiving opening and the shank longitudinal axis are inclined relative to one another at an angle of 10° to 15° , preferably approximately 12.5° . Said angle has proven to be particularly advantageous because it has been found that, during milling operation, the forces acting on a chisel are generally not oriented parallel to the longitudinal axis thereof and are consequently also not oriented in the direction of the longitudinal axis of the chisel-receiving opening, but rather are inclined slightly relative thereto. Said inclination can be allowed for by the angled configuration of the shank longitudinal axis relative to the longitudinal axis of the chisel-receiving opening.

According to a further embodiment of the present invention, it is possible for the fastening element loading region to comprise a fastening element loading surface, and for the shank longitudinal axis and a surface normal of the fastening

element loading surface to be inclined relative to one another at an angle of 50° to 65° , preferably approximately 62.5° . As a result of said relatively shallow angled configuration of the surface normal of the fastening element loading surface relative to the shank longitudinal axis, it may be achieved that a force exerted approximately also in the direction of said surface normal on the fastening element loading surface via a fastening element is inclined as little as possible relative to the shank longitudinal axis, that is to say exerts load on said shank to the greatest possible extent in the direction of the longitudinal axis thereof. It is possible in this way, too, for transverse loads in the shank to be reduced, but nevertheless for such an orientation of a fastening element formed for example as a stud bolt to be ensured, by virtue of engagement with the fastening element being generated when the chisel holder is inserted into a base part.

According to a second aspect of the present invention, there is provided a chisel holder system, comprising a chisel holder constructed preferably according to the first aspect of the present invention, and a base part having a first counterpart supporting surface region for supporting the first supporting surface region, characterized by a second counterpart supporting surface region, which is angled relative to the first counterpart supporting surface region,

for supporting the second supporting surface region, and/or in that the first counterpart supporting surface region comprises a first counterpart supporting surface for supporting the first supporting surface of the first supporting surface region and a second counterpart supporting surface, which is angled relative to the first counterpart supporting surface, for supporting the second supporting surface of the first supporting surface region.

By means of said design of the base part on its counterpart supporting side, a configuration complementary to the form of the chisel holder is attained, such that optimum fitting of said two components into one another may be ensured.

In particular, it may be provided for this purpose that the angle of the first supporting surface region relative to the second supporting surface region and the angle of the first counterpart supporting surface region relative to the second counterpart supporting surface region and/or the angle of the first supporting surface relative to the second supporting surface of the first supporting surface region and the angle of the first counterpart supporting surface relative to the second counterpart supporting surface of the first counterpart supporting surface region are complementary to one another.

As in the case of the chisel holder itself, it is also possible in the case of the chisel holder system for a further improved centering action to be attained in that the

second counterpart supporting surface region comprises a first counterpart supporting surface for supporting the first supporting surface of the second supporting surface region and a second counterpart supporting surface, which is angled relative to the first counterpart supporting surface, for supporting the second supporting surface of the second supporting surface region. In this embodiment, too, in order to obtain an optimum fit of the chisel holder into the base part, it may be provided that the angle of the first supporting surface relative to the second supporting surface of the second supporting surface region and the angle of the first counterpart supporting surface relative to the second counterpart supporting surface of the second counterpart supporting surface region are complementary to one another.

According to a further embodiment of the present invention, it is proposed that the first counterpart supporting surface and the second counterpart supporting surface of at least one counterpart supporting surface region adjoin one another in a depression-like third transition region. Since, as in the case of the various supporting surfaces, it is advantageously also the case that the various counterpart supporting surfaces are in each case provided in a substantially planar, that is to say non-curved configuration, the provision of a depression-like transition region between such counterpart supporting surfaces prevents the occurrence of notch stresses under intense loading.

Likewise, in a depression-like third transition region of said type, a volume is left free into which a for example rectilinearly extending transition region between two supporting surfaces of a supporting surface region or of two supporting surface regions can protrude without the chisel holder and base part abutting against one another in said region. Further volume is thus provided in order to permit an at least slight repositioning of the chisel holder in the event of wear occurring.

To further assist this, it may be provided that the first counterpart supporting surface region and the second counterpart supporting surface region adjoin one another in a depression-like fourth transition region.

To provide a loading direction which deviates as little as possible from the shank longitudinal axis with a fastening force for fixing the fastening shank in the base part, it is also proposed that a fastening shank receiving opening having a fastening shank receiving opening longitudinal axis and a fastening element receiving opening which is open toward the fastening shank receiving opening and which has a fastening element receiving opening longitudinal axis are provided in the base part, and that the fastening shank receiving opening longitudinal axis and the fastening element receiving opening longitudinal axis are inclined relative to one another at an angle of 50° to 65° , preferably approximately 62.5° .

Embodiments of the present invention will be described in detail below with reference to the appended figures, in which:

figure 1 shows a perspective view of a chisel holder in a viewing direction I in figure 2;

figure 2 shows a perspective view of the chisel holder of figure 1 in a viewing direction II in figure 1;

figure 3 shows a view of the chisel holder in a viewing direction III in figure 2;

figure 4 shows a sectional view of the chisel holder sectioned in a holder central plane;

figure 5 shows a view of the chisel holder in a viewing direction V in figure 1;

figure 6 shows a side view of the chisel holder;

figure 7 shows a sectional view of the chisel holder in the region of a fastening shank, sectioned along a line VII-VII in figure 6;

figure 8 shows a sectional view of the chisel holder in the region of a fastening shank, sectioned along a line VIII-VIII in figure 6;

figure 9 shows a perspective view of a chisel holder;

figure 10 shows a view of the chisel holder in figure 9 in a viewing direction X in figure 9;

figure 11 shows a perspective illustration of the chisel and of the chisel holder in the assembled state; and

figure 12 shows a sectional illustration of the assembly of figure 11, sectioned in the holder central plane.

Figures 1 to 6 show a chisel holder, denoted generally by 10, for a milling roller of a road milling machine. The chisel holder 10 comprises a body region 12 with an approximately cylindrical projection 16 which extends therefrom at a chisel-insertion side denoted generally by 14. A chisel-receiving opening 18 is provided in the cylindrical projection 16 so as to extend through the latter and through the entire body region 12. Said chisel-receiving opening is open at the chisel-insertion side 14 in order to receive an exchangeable chisel which can be locked therein with a frictional force fit, and said chisel-receiving opening is open at a supporting side 20, which is situated substantially opposite the chisel-insertion side 14, of the body region 12. From said supporting side, a tool used for the removal of a worn chisel from the chisel-receiving opening 18 can be inserted in order to thereby push the chisel out of the chisel opening 18.

On the body region 12, there are provided on the supporting side 20 a first supporting surface region 22 and a second supporting surface region 24 which is angled relative to said first supporting surface region. It can be seen in the illustrations that the chisel-receiving opening 18 is open toward the supporting side 20 in the region of the first

supporting surface region 22. An elongate fastening shank 26 extends from the body region 12 proceeding substantially from the second supporting surface region 24. The fastening shank 26 is formed with a generally round, for example circular or oval or elliptical, outer circumferential contour. The structural design of the fastening shank 26 will be discussed in more detail below.

The first supporting surface region 22 comprises a first supporting surface 28 and a second supporting surface 30. Said two supporting surfaces 28, 30 of the first supporting surface region 22 are angled relative to one another and are formed so as to be substantially symmetrical, or also inclined at the same angle, relative to a holder central plane which corresponds substantially to the plane of the drawing of figure 4. It is pointed out here that the holder central plane may for example be spanned by a longitudinal axis L_x of the chisel-receiving opening 18 and a shank longitudinal axis L_z of the fastening shank 26.

The second supporting surface region 24 also comprises a first supporting surface 32 and a second supporting surface 34. The two supporting surfaces 32, 34 are angled relative to one another and thus also relative to the holder central plane, wherein here, the configuration relative to the holder central plane may be symmetrical, corresponding to the configuration of the two supporting surfaces 28, 30 of the first supporting surface region 22.

First transition regions 36, 38 which are linear and preferably extend in straight fashion are formed between the first supporting surface 28 of the first supporting surface region 22 and the first supporting surface 32 of the second supporting surface region 24 and likewise between the second supporting surface 30 of the first supporting surface region 22 and the second supporting surface 34 of the second supporting surface region 24, which first transition regions likewise also define a transition between the first supporting surface region 22 and the second supporting surface region 24. It can be clearly seen in particular in figures 1 and 2 that said first transition regions 36, 38 are formed at a region of adjoinment, which is of edge-like form, of the respective supporting surfaces. Owing to the fact that the supporting surfaces 28, 30, 32, 34 are preferably all of planar, that is to say non-curved form, said first transition regions 36, 38 which are thus also of linear form are correspondingly also not curved.

A second transition region 40 formed between the first supporting surface 32 and the second supporting surface 34 of the second supporting surface region 24 is formed with a transition surface 42 which extends in substantially straight fashion. Said transition surface is substantially orthogonal with respect to the holder central plane. Since the two supporting surfaces 32, 34 are substantially planar,

that is to say not curved, said second transition region 40 also extends substantially rectilinearly.

Where the two supporting surface regions 22, 24 or the supporting surfaces 28, 30 and 32, 34 thereof adjoin one another, that is to say at the first transition regions 36, 38, an angle W_1 is formed which lies in the region of approximately 137° . An angle W_2 of approximately 130° is formed between the two supporting surfaces 28, 30 of the first supporting surface region 22, such that each of said supporting surfaces 28, 30 has an angle of inclination of approximately 65° with respect to the holder central plane. An angle W_3 of approximately 110° is formed between the two supporting surfaces 32, 34 of the second supporting surface region 24, such that each of said supporting surfaces 32, 34 has an angle of inclination of approximately 55° with respect to the holder central plane. This means generally that the two supporting surfaces 28, 30 of the first supporting surface region 22 are arranged so as to enclose between them a larger angle than that enclosed between the two supporting surfaces 32, 34 of the second supporting surface region 24. Furthermore, the shank longitudinal axis L_R is oriented relative to the body region 12 such that the fastening shank 26 is inclined relative to the first supporting surface region 22 and relative to the second supporting surface region 24 at an angle W_4 and W_5 respectively, said angle being in each case approximately 65° . The angle W_4 may for

example lie in the region of 67° , while the angle W_1 may be approximately 64° . It is pointed out here that, for the determination of said angles W_1 and W_2 , consideration may be given to a line which connects the respective supporting surfaces 28, 30 and 32, 34 in an imaginary elongation thereof, or in the case of the supporting surfaces 32, 34, the angle W_2 may also be determined relative to the transition surface 42 of the second transition region 40, and in the case of the supporting surfaces 28, 30, the angle W_1 may also be determined relative to a transition surface 43 of a further transition region 41 on the chisel holder 10. The total angle formed by the sum of the two angles W_1 and W_2 may thus lie in a region of approximately 131° and defines the angle of inclination of two prismatic configurations, one of which is defined by the two supporting surfaces 28, 30 of the first supporting region 22 and the other of which is defined by the two supporting surfaces 32, 34 of the second supporting surface region 24. By varying said total angle, that is to say the sum of the two angles W_1 and W_2 , it is thus possible, for example while maintaining the same angles W_1 and W_2 , to manipulate the geometry of the pyramid-like arrangement formed by the four supporting surfaces 28, 30, 32, 34, and in particular for a concentration of the forces in the direction of an imaginary pyramid peak to be assisted.

Owing to said angled orientation of the various supporting surface regions 22, 24 or of the supporting

surfaces 28, 30, 32, 34 thereof, and owing to the orientation of the fastening shank 26 relative to the body region 12, a concentration of the forces introduced into the body region 12 during milling operation is attained in such a way that transverse forces which subject the transition between the body region 12 and the fastening shank 26 to shear loading are significantly reduced. This is also contributed to by the fact that an angle W_k formed between the shank longitudinal axis L_k and the longitudinal axis L_x of the chisel-receiving opening 18 and consequently of a chisel longitudinal axis lies in a region of 12.5° .

Figures 9 and 10 illustrate a base part 44 that can be used in conjunction with the above-described chisel holder 10. Figures 11 and 12 show said base part 44 in an assembled state with the chisel holder 10.

In the base part 44 there is formed a fastening shank receiving opening 46 which is open both at a counterpart supporting side 48, visible at the top in figure 9, and also a connecting side 50, visible in figure 10, of the base part 44. In the region of the connecting side 50, the base part 44 is fixed to a milling roller for example by welding.

On the counterpart supporting side 48, a first counterpart supporting surface region 52 is formed so as to be assigned to the first supporting surface region 22. A second counterpart supporting surface region 54 is formed so as to be assigned to the second supporting surface region 24.

The first counterpart supporting surface region 52 comprises a first counterpart supporting surface 56 assigned to the first supporting surface 28 of the first supporting surface region 22, and comprises a second counterpart supporting surface 58 assigned to the second supporting surface 30 of the first supporting surface region 22. Correspondingly, the second counterpart supporting surface region 54 comprises a first counterpart supporting surface 60 assigned to the first supporting surface 32 of the second supporting surface region 24, and comprises a second counterpart supporting surface 62 assigned to the second supporting surface 34 of the second supporting surface region 24. The respective counterpart supporting surfaces 56, 58, 60, 62 are angled relative to one another corresponding to the respective angles of the supporting surfaces 28, 30, 32, 34 of the chisel holder 10 relative to one another and are of planar form, such that the supporting surfaces and counterpart supporting surfaces which are assigned to one another can bear areally against one another.

In each case one depression-like third transition region 64 and 66 is formed firstly between the first counterpart supporting surface 56 and the second counterpart supporting surface 58 and secondly between the first counterpart supporting surface 60 and the second counterpart supporting surface 62. A depression-like fourth transition region 68, 70 is likewise formed between the two counterpart

supporting surface regions 52, 54, that is to say between the first counterpart supporting surface 56 and the first counterpart supporting surface 60 and between the second counterpart supporting surface 58 and the second counterpart supporting surface 62. Said depression-like transition regions 64, 66, 68, 70, which are formed for example with an at least partially rounded contour, firstly prevent the occurrence of notch stresses during the introduction of milling forces. Secondly, as is clearly shown by the illustrations of figures 11 and 12, space is created in each case at the depression-like transition regions 64, 66, 68, 76 for the various transition regions of the chisel holder 10, where the supporting surfaces thereof merge into one another. This ensures that, even if wear occurs in the region of the mutually adjoining supporting surfaces and counterpart supporting surfaces, it is made possible for the first and second transition regions to reposition, and accordingly penetrate more deeply, into the third and fourth transition regions.

It can be clearly seen from figures 9, 11 and 12 that firstly the supporting side 20 formed on the chisel holder 10 and secondly the counterpart supporting side 48 formed on the base part 44 are in particular of complementary form with the supporting surfaces and counterpart supporting surfaces which come into contact with one another. The plurality of supporting surfaces and counterpart supporting surfaces which

adjoin one another in prismatic fashion thus form a funnel-like configuration which ensures stable support of the chisel holder 10 and base part 44 even in the direction transversely with respect to the fastening shank 26 or the shank longitudinal axis L_s . This leads generally to the fastening shank 26 being relieved of load in particular in the transverse direction, whereby the risk of breakage of the fastening shank is considerably reduced.

In addition to the supporting interaction between the chisel holder 10 and the base part 44 in the region of the supporting side 20 and of the counterpart supporting side 48, as explained in detail above, it is the case in the chisel holder system constructed according to the invention that the fastening shank 26 is further relieved of load as a result of its abutting interaction with the base part 44 in the region of the fastening shank receiving opening 46 thereof. This aspect and the supporting aspect already explained in detail above can in each case, even on their own, achieve a considerable relief of load or more uniform force distribution. It is however particularly advantageous for these to be realized in combination in one and the same chisel holder system.

The fastening shank 26 of the chisel holder 10 has a fastening element loading region 76 on a first side situated approximately below the first supporting surface region 22, and has a supporting region 78 on a second side situated

opposite in relation to the shank longitudinal axis L_B . The fastening element loading region is formed in the manner of a notch with a fastening element loading surface 80, the surface normal F_N of which is inclined relative to the shank longitudinal axis L_S at a relatively shallow angle W of approximately 62.5° . This has the effect that a fastening element 82, which is provided on the base part and whose longitudinal central axis is oriented approximately parallel to the surface normal F_N , that is to say substantially orthogonal with respect to the fastening element loading surface 80, generates a relatively high force component oriented in the direction of the shank longitudinal axis L_B when the fastening shank 26 is subjected to load. It is pointed out here that the fastening element 82 is received in a fastening element receiving opening 84 of the base part 44, which fastening element receiving opening is formed at least in regions with an internal thread, such that the fastening element 82, which is correspondingly formed at least in regions with an external thread, can be moved in the direction of or away from the fastening element loading surface 80 by means of a turning, that is to say screw movement in the direction of a fastening element receiving opening longitudinal axis L_J .

Owing to the geometric relationships discussed above, the fastening element receiving opening longitudinal axis L_J is at the angle W of approximately 62.5° relative to a

fastening shank receiving opening longitudinal axis L_A which, in the assembled state, also substantially corresponds at least with regard to its orientation to the shank longitudinal axis L_B .

If the fastening element 82 is moved into the fastening element receiving opening 84 by means of a screw movement and pressed against the fastening element loading surface 80, the fastening shank 26 is pressed with its supporting region 78 against a counterpart supporting region 86 of the base part 44. The supporting region 78 is formed with two supporting surface regions 88, 90 which run at an angle or inclined relative to one another, and in particular have in each case a preferably circularly curved profile in the circumferential direction around the shank longitudinal axis L_B . In a central region of the supporting region 78, said two supporting surface regions 88, 90 adjoin one another in a fifth transition region 92. Said fifth transition region 92 is formed in the manner of a depression, preferably with a concave depression profile extending in the direction of the shank longitudinal axis L_B .

It can be clearly seen that the supporting surface regions 88, 90 of the supporting region 78 are formed such that they protrude radially in relation to the fastening shank longitudinal axis L_B at least in regions beyond a main outer circumferential surface 94 of the fastening shank 26. The design is such that said radial projecting length is at

its smallest in the central region of the supporting region 78, that is to say where the fifth transition region 92 is formed, such that there, there is for example virtually no radial projection, whereas said radial projecting length increases in the circumferential direction and in the direction away from the fifth transition region 92. It can be seen in particular that in each case one step-like, if appropriate also slightly curved transition to the main outer circumferential surface 94 of the fastening shank 26 is provided both at the axial end regions of the supporting surface regions 88, 90 and also at the end regions remote from the fifth transition region 92 in the circumferential direction.

As a result of the fastening shank 26 being designed in the manner described above, said fastening shank, when subjected to load by the loading element 82, is supported in two surface regions situated laterally with respect to the holder central plane, specifically substantially by means of the supporting surface regions 88, 90, on the base part 44. This leads to a pressure distribution and to the avoidance of linear supporting contact at the circumferential center of the supporting region 78. In particular, owing to the depression-like fifth transition region 92, it is ensured that, at said center of the supporting region 78, no forces or only small forces are transmitted between the fastening shank 26 and the base part 44.

A further significant advantage of the supporting surface regions 88, 90 which protrude radially beyond the main outer circumferential surface 94 is that, there, locally delimited surface regions are utilized in order to generate abutting contact between the fastening shank 26, that is to say the chisel holder 10, and the base part 44. Since both the chisel holder 10 and also the base part 44 are generally provided as forged parts, and consequently the surfaces at which mutual support takes place must be machined or reworked in a material-removing process in order to obtain the required precision, said working step can be restricted to the surface regions actually provided for this purpose, specifically the locations where the supporting surface regions 88, 90 are formed.

The counterpart supporting region 86 is formed on the base part 44 correspondingly to the supporting region 78 on the fastening shank 26. The counterpart supporting region 86 has counterpart supporting surface regions 96, 98 assigned to the supporting surface regions 88, 90. Said counterpart supporting surface regions adjoin one another in a sixth transition region 100, wherein the sixth transition region 100 is of projection-like form, preferably with a projection 102 which is elongate and convexly curved in the direction of the fastening shank receiving opening longitudinal axis L_A . Said projection may, for manufacturing reasons, be provided by an insert part 104 which is inserted into a corresponding

opening 106 of the base part for example with an interference fit and which, in order to provide the projection 102, protrudes with a circumferential region thereof radially inward beyond the two counterpart supporting surface regions 96, 98.

The counterpart supporting surface regions 96, 98 are formed in the fastening shank receiving opening 46 in such a way that they protrude at least in regions radially inward in relation to the fastening shank receiving opening longitudinal axis L_A beyond a main inner circumferential surface 108 of the fastening shank receiving opening 46. Here, the design may be such that said radial projection is at a maximum close to the sixth transition region 100 and decreases in the circumferential direction in the direction away from the sixth transition region 100, such that the counterpart supporting surfaces 96, 98 merge gradually into the main inner circumferential surface 108. As is the case in the embodiment of the fastening shank 100 or of the supporting region 78, it is also the case here that the surface regions to be machined in order to provide precise abutting contact are limited to the counterpart supporting surface regions 96, 98, which, in particular in their two axial end regions, may merge again in a stepped or curved manner into the main inner circumferential surface 108 on the base part 44.

Correspondingly to the inclination of the two supporting surface regions 88, 90 relative to one another attained as a result of the curved profile, the two counterpart supporting surface regions 96, 98 are also inclined relative to one another, that is to say are formed here with a curved profile, wherein said curvature may correspond to the curvature of the two supporting surface regions 88, 90 in order to attain abutting contact over a large area. Since the supporting surface regions 88, 90 and also the counterpart supporting surface regions 96, 98 protrude beyond the main outer circumferential surface 94 or the main inner circumferential surface 108 in each case only in one circumferential region, the fastening shank 26 can basically be inserted with lateral movement play into the fastening shank receiving opening 46, wherein firm abutting contact between the supporting surface regions 88, 90 and the counterpart supporting surface regions 96, 98 is generated only as a result of the movement of the fastening element 82 toward the fastening element loading surface 80. Here, contact of the two transition regions 92, 100, which leads to more intense contact pressure, is avoided. The functionality of said transition regions is substantially that of attaining a defined orientation of the chisel holder 10 relative to the base part 44 already during the insertion movement of the chisel holder 10 into the base part 44, even before the

centering action of the supporting side 20 and the counterpart supporting side 48 comes into effect.

The highly uniform force distribution during the support of the fastening shank 26 on the counterpart supporting region 94 is also contributed to in that both the supporting region 78 and also the counterpart supporting region 86 are formed so as to be symmetrical, in particular point-symmetrical, with respect to the holder central plane or to a plane of symmetry, corresponding to said plane, of the base part 44.

It is pointed out that a solution which is constructed in accordance with the principles of the present invention and which can be realized in a structurally very simple manner with regard to the supporting region 78 and the counterpart supporting region 86 may also be constructed such that the supporting region 78 is basically provided on the outer circumferential surface of the fastening shank 26 without protruding beyond the main outer circumferential surface 94 thereof, that is to say for example the main outer circumferential surface 94, which is provided with an approximately circular circumferential contour, also provides the supporting surface regions 88, 90 at both sides of the transition region 92 which is of depression-like form. In this embodiment, but basically also in the embodiment with supporting surface regions 88, 90 which protrude radially in relation to the main outer circumferential surface 94, said

depression-like transition region 92 may be formed as a for example substantially planar transition surface between the supporting surface regions at both sides thereof in the circumferential direction, that is to say a surface which is recessed in the radially inward direction in relation to a circumferential contour defined by the outer circumference of the fastening shank 26. A substantially planar form, attained for example by means of material-removing machining or else in a casting process, is particularly advantageous owing to its simple producibility. It would however basically also be possible for there to be provided in the transition region 92 a curved transition surface flattened slightly in relation to the curvature of the fastening shank 26. A corresponding geometry may then self-evidently also be provided on the counterpart supporting region 86 in the base part 44. There, too, the counterpart supporting surface regions 96, 98 may be integrated into the main inner circumferential surface 108, that is to say need not necessarily protrude radially inward relative thereto. In coordination with the embodiment of the transition region 92 between the supporting surface regions 88, 90 of the supporting region 78, the transition region 100 between the two counterpart supporting surface regions 96, 98 may then also be formed as a for example substantially planar transition surface, which should then be positioned opposite the correspondingly formed transition surface of the transition region 92. In the case of such an embodiment, it

is possible, similarly to the situation that can be seen in figures 1 and 4, for the supporting region 78 to be provided at the axial free end region of the fastening shank 26, such that, proceeding from a substantially circular circumferential contour of the main outer circumferential surface 94, which then also provides the supporting surface regions 88, 90, a substantially planar transition region 92, which is recessed in the manner of a depression radially inward in relation to the basically provided circular circumferential contour, is then for example provided in the axially free end region of the fastening shank 26. As a result of the provision of said configuration in particular at the axially free end region of the fastening shank 26, that is to say where the fastening shank 26 is pressed more intensely against the base part 44 by the load-exerting action of the fastening element 82, the abovementioned relief of load by means of the avoidance of linear and therefore very highly loaded abutting contact between the fastening shank 26 and the base part 44 is attained.

As a result of the formation of the chisel holder and of the base part with the various supporting surface regions and counterpart supporting surface regions on the supporting side and on the counterpart supporting side and also in the supporting region and in the counterpart supporting region, a defined positioning of the chisel holder is attained while at the same time the chisel holder is relieved of load in

particular in the region of the fastening shank. This is contributed to by the provision of the load distribution between a plurality of supporting surface regions and supporting surfaces and also counterpart supporting surface regions and counterpart supporting surfaces which are in a defined arrangement relative to one another and at which the chisel holder and the base part bear directly against one another. This means that, within the context of the present invention, a supporting surface region or counterpart supporting surface region is formed or machined with the respective surfaces, which serve for mutual support, such that direct metal-on-metal contact can be generated. Since both the base part and also the chisel holder are generally produced as forged parts, the surfaces which serve within the context of the present invention as supporting surface regions and counterpart supporting surface regions are therefore basically produced and/or reworked in a material-removing process. In this way, the high precision of said surfaces required for a substantial relief of load and precise positioning can be ensured, which could not be realized in such a manner with a surface machined only in a forging process.

For the assembly of the above-described system, in the case of a base part which is fixed by welding to a milling drum that can be set in rotation, the chisel holder 10 is inserted with its fastening shank 25 into the fastening

shank receiving opening 46 provided in the base part 44, until the two supporting surface regions 22, 24 of the chisel holder 10 come into contact with the respectively associated counterpart supporting surface regions 52, 54 of the base part. The fastening element 82, which is for example of screw-like form, is thereupon tightened such that it moves further into the fastening element receiving opening 84 and is pressed against the fastening element loading surface 80 on the fastening shank 26. This firstly serves to realize stable abutting interaction between the supporting surface regions 22, 24 and the counterpart supporting surface regions 52, 54. Secondly, stable abutment of the supporting region 78 or of the two supporting surface regions 88, 90 thereof against the counterpart supporting region 86 or the two counterpart supporting surface regions 96, 98 is achieved.

Since, during the operation of a milling machine, not only the chisels held in the chisel holder 10 become worn but rather wear can also occur in the region of the chisel holders 10 themselves, it is possible by reversing the above-described process, that is to say by removing the fastening element 82 from the fastening shank 26 and pulling the chisel holder 10 or the fastening shank 26 thereof out of the base part 44, for a worn chisel holder 10 to be removed and replaced with a new chisel holder or a less worn chisel holder. Said chisel holder is inserted with its fastening shank 26 into the associated fastening shank receiving

opening 46 in the base part 44, and fixed by means of the fastening element 82, in the manner described above. In the case of repeatedly occurring wear, said process may then self-evidently be performed multiple times in conjunction with the same base part fixed to a milling drum. If wear also occurs in the region of a base part, then said base part may self-evidently also be removed from a milling drum, by severing the welded connection which holds it, and replaced with a new base part.

Claims

1. A chisel holder, comprising:
 - a body region having a chisel-receiving opening which is open at least toward a chisel-insertion side of the body region,
 - a fastening shank which extends from a supporting side of the body region and which has a shank longitudinal axis, wherein the body region has, on its supporting side , a first supporting surface region, characterized
 - in that the body region, on its supporting side, has a second supporting surface region which is angled in relation to the first supporting surface region, and/or
 - in that the first supporting surface region comprises a first supporting surface and a second supporting surface which is angled in relation to the first supporting surface.
2. The chisel holder as claimed in claim 1, characterized in that the chisel-receiving opening is open toward that supporting side substantially in the region of the first supporting surface region and in that the fastening shank extends from the body region

substantially in the region of the second supporting surface region.

3. The chisel holder as claimed in claim 1 or 2, characterized in that the second supporting surface region comprises a first supporting surface and a second supporting surface which is angled in relation to the first supporting surface.

4. The chisel holder as claimed in claim 3, characterized in that the first supporting surface and the second supporting surface of the first supporting surface region and/or of the second supporting surface region are arranged substantially symmetrically with respect to a holder central plane.

5. The chisel holder as claimed in claim 3 or 4, characterized in that

- a first angle enclosed between the first supporting surface and/or the second supporting surface of the first supporting surface region and the second supporting surface region lies in the range of 127° to 147° , and is preferably approximately 137° ,

and/or

- a second angle enclosed between the first supporting surface and the second supporting surface

of the first supporting surface region lies in the range of 120° to 140° , and is preferably approximately 130° , and/or

- a third angle enclosed between the first supporting surface and the second supporting surface of the second supporting surface region lies in the range of 100° to 120° , and is preferably approximately 110° , and/or

- an angle enclosed between a transition region between the first supporting surface and the second supporting surface of the first supporting surface region and a transition region between the first supporting surface and the second supporting surface of the second supporting surface region lies in the range of 121° to 141° , and is preferably approximately 131° .

6. The chisel holder as claimed in one of claims 3 to 5, characterized in that at least one supporting surface of the first supporting surface region and the second supporting surface region adjoin one another in a first transition region which extends in a linear and/or straight fashion.

7. The chisel holder as claimed in one of claims 1 to 6, characterized in that the first supporting surface and the second supporting surface of the second supporting

surface region adjoin one another in a second transition region which extends in an areal and/or straight fashion.

8. The chisel holder as claimed in claim 4 and 7, characterized in that the second transition region comprises a transition surface which is substantially orthogonal with respect to the holder central plane.

9. The chisel holder as claimed in one of claims 1 to 8, characterized in that a longitudinal central axis of the chisel-receiving opening and the shank longitudinal axis are inclined relative to one another at an angle of 10° to 15° , preferably approximately 12.5° .

10. The chisel holder as claimed in one of claims 1 to 9, characterized in that a fastening element loading region having a fastening element loading surface is provided on the fastening shank , and in that the shank longitudinal axis and a surface normal of the fastening element loading surface are inclined relative to one another at an angle of 50° to 65° , preferably approximately 62.5° .

11. The chisel holder as claimed in one of claims 1 to 9,

characterized in that an angle of inclination of the shank longitudinal axis relative to the first supporting surface region and an angle of inclination of the shank longitudinal axis relative to the second supporting surface region are substantially identical to one another.

12. A chisel holder system, comprising:

- a chisel holder preferably as claimed in one of the preceding claims,

- a base part having a first counterpart supporting surface region for supporting the first supporting surface region,

characterized

- by a second counterpart supporting surface region , which is angled relative to the first counterpart supporting surface region , for supporting the second supporting surface region ,

and/or

- in that the first counterpart supporting surface region comprises a first counterpart supporting surface for supporting the first supporting surface of the first supporting surface region and a second counterpart supporting surface, which is angled relative to the first counterpart supporting surface, for supporting the

second supporting surface of the first supporting surface region.

13. The chisel holder system as claimed in claim 12, characterized in that the angle of the first supporting surface region relative to the second supporting surface region and the angle of the first counterpart supporting surface region relative to the second counterpart supporting surface region and/or the angle of the first supporting surface relative to the second supporting surface of the first supporting surface region and the angle of the first counterpart supporting surface relative to the second counterpart supporting surface of the first counterpart supporting surface region are complementary to one another.

14. The chisel holder system as claimed in claim 12 or 13, characterized in that the second counterpart supporting surface region comprises a first counterpart supporting surface for supporting the first supporting surface of the second supporting surface region and a second counterpart supporting surface, which is angled relative to the first counterpart supporting surface, for supporting the second supporting surface of the second supporting surface region.

15. The chisel holder system as claimed in claim 14, characterized in that the angle of the first supporting surface relative to the second supporting surface of the second supporting surface region and the angle of the first counterpart supporting surface relative to the second counterpart supporting surface of the second counterpart supporting surface region are complementary to one another.

16. The chisel holder system as claimed in one of claims 12 to 15, characterized in that the first counterpart supporting surface and the second counterpart supporting surface of at least one counterpart supporting surface region adjoin one another in a depression-like third transition region.

17. The chisel holder system as claimed in one of claims 12 to 16, characterized in that the first counterpart supporting surface region and the second counterpart supporting surface region adjoin one another in a depression-like fourth transition region.

18. The chisel holder system as claimed in one of claims 12 to 17,

characterized in that a fastening shank receiving opening having a fastening shank receiving opening longitudinal axis and a fastening element receiving opening which is open toward the fastening shank receiving opening and which has a fastening element receiving opening longitudinal axis are provided in the base part, and in that the fastening shank receiving opening longitudinal axis and the fastening element receiving opening longitudinal axis are inclined relative to one another at an angle of 50° to 65° , preferably approximately 62.5° .