

INTERACTION OBJECT RECONCILIATION IN A PUBLIC LEDGER BLOCKCHAIN ENVIRONMENT

5 CROSS-REFERENCE TO RELATED APPLICATIONS

[0001] This application claims the benefit of, and priority to United States provisional application 62/424,465 titled, "SYSTEM AND METHOD FOR BLOCK RECONCILIATION" filed on November 19, 2016, the entire specification of which is incorporated herein by reference.

10 BACKGROUND OF THE INVENTION

Field of the Art

[0002] The disclosure relates to the field of information security, and more particularly to the field of securely recording, storing and reconciling interactions between a plurality of devices in a distributed public ledger blockchain environment.

15 Discussion of the State of the Art

[0003] In an evolving generation of devices, devices may communicate with each other in an infrastructure generally known as the Internet of Things (IoT). IoT bears similarities to communications on Internet and even shares some of the same infrastructure. That is, the conventional Internet includes wired and wireless communication paths between end-user
20 computing devices, computing servers, network switches, repeaters, modems, access points, and the like. IoT may use the wired and wireless communication paths of the conventional Internet to pass data. Different from the conventional Internet, a portion of endpoint IoT devices often comprise machines that do not have traditional user input and output interfaces. For example, a plurality IoT device communicatively coupled to each other will often be
25 configured without a display, a keyboard, a mouse, or any other human user input and output communication interface often associated with a conventional Internet device (for example, a personal computer, a smart phone, a tablet, a laptop computer, and the like). The IoT device may include certain annunciators, switches, sensors, rudimentary displays, wired or wireless control devices, and the like. Nevertheless, the machine will typically not have the type of
30 human interfaces generally associated with a computing device that communicates via the

conventional Internet. In some applications, an automated IoT interface to physical objects is desirable from an automation and user-less interaction perspective.

[0004] In the art of interaction reconciliation when multiple participants are involved, it is often desirable to ensure agreement and accurate recordation of interactions in a secure way that is resistant to tampering and one that reflects accuracy; maintaining protection of sensitive information associated to the interaction for a variety of purposes, such as companies protecting internal proprietary information, or customer data such as transaction data, financial data, account numbers, identification information, or any of a wide variety of potentially sensitive material that malicious third parties may desire to tamper with; and, reconciliation of interaction details for an interaction involving a plurality of participants for accuracy.

[0005] One particular sensitive area of information security, is that of interaction fulfilment and authentication. First, when multiple participants are involved and recording the same interaction (albeit from different perspectives), and while a large focus is put on protecting information in the sense of preventing unauthorized access (i.e., preventing unwanted individuals or entities from gaining access to files to steal information or for financial gain), an additional area of concern remains - regarding protecting interaction data from being tampered with or falsified or for missing information that can affect interaction outcomes, for example, when an agreement is made and not followed through. Tampering with a file, such as making minor alterations to content data or properties, or falsifying entire files such as substituting a new file with similar properties in an attempt to covertly manipulate data, is a key area of information security concern. For example, when reporting expenses on an income tax return or for a corporate expense report, it is often up to an individual user to enter accurate information. A first step in getting reports that can be trusted is making sure the person entering the data is fully trained and capable of supplying reports. This is often not possible, and when humans are involved, as mistakes happen, or, in some circumstances, an individual may have a propensity to underreport income interactions or overreport expense interactions in an attempt to pay less tax or increase reimbursements.

[0006] While it is important to accurately capture interaction details. It then becomes critical to ensure that the recording of the interaction has not been tampered with or altered, and furthermore that the interaction itself has not been falsified, erased, obfuscated, or otherwise manipulated in any way. Accordingly, it may become desirable for the multiple participants

involved to ensure the authenticity of an interaction and its contents, such as any numbers discussed or funds conveyed will be recorded by the multiple participants. In some cases, for example, when renting an automobile, a participant may not require human interaction and it may be desirable for recordation of the interaction to be performed automatically.

5 [0007] Blockchain technology is much broader than just bitcoin. The sustained levels of robust security achieved by public cryptocurrencies have demonstrated to the world that this new wave of blockchain technologies can provide efficiencies and intangible technological benefits very similar to what the internet has done. Blockchains are a very powerful technology, capable of performing complex operations, capable of understanding much more
10 than just how many bitcoins you have currently have in your digital wallet. The concept of smart contracts enables additional applications to be included as part of the blockchain ledger and enables a secure interaction repository. However, blockchains known in the art to primarily designed to perform a small set of simple operations – mainly, transactions of a currency-like token, where operations are mutually exclusive, the instant invention is able to
15 extend the capability to have fulfilment of agreements in order to capture interactions that have outcomes efficiently, while still enjoying the security of a blockchain system. Because these programs are run on a blockchain, they have unique characteristics compared to other types of programming instructions.

[0008] What is needed is a means to automatically accurately capture, certify and verify any
20 interaction from multiple devices with little or no user interaction and to ensure its authenticity, as well as a system to protect the recording of such interactions (and associated details) against any tampering, unauthorized access or duplication, so that a record exists not only of details of the interaction, but the exact times at which it was created, altered, or any other relevant operation was performed. Furthermore, any such security measures must be
25 effective in securing a file against any potentially interested party, including those that might be responsible for the security of the file itself. Further a system to capture interactions with fulfilment results in this secure environment and reconciliation is needed.

SUMMARY OF THE INVENTION

[0009] Accordingly, the inventor has conceived and reduced to practice, in a preferred
30 embodiment of the invention, a system and method to provide automatic entity information and device intercommunication to provide secure data communications between devices. A

set of objects, rules, and guidelines permit the plurality of devices to initiate and carry out communications with another device when the services associated to one device are used by another. Given that the interactions may hold importance in conducting commercial transactions, according to a preferred embodiment of the invention, interactions between devices are stored on a public ledger blockchain that instead of involving manual processing that may take days, weeks, or months to complete, huge volumes of transactions are validated automatically. Blockchain technology efficiently provides a secure mathematical validation of interactions between devices. Once the interaction is validated, one or more, distributed ledgers provide unified, tamperproof visibility into the interaction record—that is, an immutable version of interaction truth.

[0010] Accordingly, A system and method for block reconciliation of interactions comprise a network-connected block reconciliation computer comprising a memory and a processor and further comprising programmable instructions stored in the memory and operating on the processor, the programmable instructions adapted to reconcile blocks in a public ledger blockchain environment whereby a plurality of connections to a plurality of connected devices and a connection to one or more blockchains enable an object compiler to receive a plurality of criteria from a requesting device. The compiler then receives a plurality of blocks from the public ledger blockchains based on the criteria. Each block corresponding to a preconfigured interaction object previously written by the devices either during or after the completion of a transaction. In a preferred embodiment, the compiler analyzes the preconfigured interaction objects to determine if there is an associated required supplemental object to verify that a contract or fulfilment has occurred. In this regard, the compiler requests the supplemental blocks from the one or more blockchains, each supplemental block corresponding to a required supplemental object then for each requested supplemental object, if the supplemental object type is replacement, replace properties from the supplemental object into the associated interaction object with information, or, if the supplement object type is addendum, add properties from the supplemental object to the associated interaction object of the preconfigured interaction objects, or if no requested supplemental object it found, flag the associated interaction object of the preconfigured interaction objects.

BRIEF DESCRIPTION OF THE DRAWING FIGURES

[0011] The accompanying drawings illustrate several embodiments of the invention and, together with the description, serve to explain the principles of the invention according to the

embodiments. It will be appreciated by one skilled in the art that the particular embodiments illustrated in the drawings are merely exemplary, and are not to be considered as limiting of the scope of the invention or the claims herein in any way.

5 **[0012] Fig. 1** is a block diagram illustrating an exemplary hardware architecture of a computing device used in an embodiment of the invention.

[0013] Fig. 2 is a block diagram illustrating an exemplary logical architecture for a client device, according to an embodiment of the invention.

[0014] Fig. 3 is a block diagram showing an exemplary architectural arrangement of clients, servers, and external services, according to an embodiment of the invention.

10 **[0015] Fig. 4** is another block diagram illustrating an exemplary hardware architecture of a computing device used in various embodiments of the invention.

[0016] Fig. 5 is a block diagram illustrating a blockchain system, according to a preferred embodiment of the invention.

15 **[0017] Fig. 6** is a block diagram illustrating a plurality of exemplary objects for a block reconciliation system, according to a preferred embodiment of the invention.

[0018] Fig. 7 is a block diagram illustrating a block reconciliation system, according to a preferred embodiment of the invention.

[0019] Fig. 8 is a flow diagram illustrating an exemplary method for issuing a rule to a block reconciled blockchain, according to a preferred embodiment of the invention.

20 **[0020] Fig. 9** is a flow diagram illustrating an exemplary method for issuing an object to a block reconciled blockchain, according to a preferred embodiment of the invention.

[0021] Fig. 10 is a flow diagram illustrating an exemplary method for issuing a plurality of interaction objects to a block reconciled blockchain, according to a preferred embodiment of the invention.

25 **[0022] Fig. 11** is a flow diagram illustrating an exemplary method for compiling a plurality of interaction block to a block reconciled blockchain, according to a preferred embodiment of the invention.

DETAILED DESCRIPTION

[0023] The inventor has conceived, and reduced to practice, a system and method for block reconciliation in a multi-party public ledger blockchain environment.

[0024] One or more different inventions may be described in the present application. Further, for one or more of the inventions described herein, numerous alternative embodiments may be described; it should be appreciated that these are presented for illustrative purposes only and are not limiting of the inventions contained herein or the claims presented herein in any way. One or more of the inventions may be widely applicable to numerous embodiments, as may be readily apparent from the disclosure. In general, embodiments are described in sufficient detail to enable those skilled in the art to practice one or more of the inventions, and it should be appreciated that other embodiments may be utilized and that structural, logical, software, electrical and other changes may be made without departing from the scope of the particular inventions. Accordingly, one skilled in the art will recognize that one or more of the inventions may be practiced with various modifications and alterations. Particular features of one or more of the inventions described herein may be described with reference to one or more particular embodiments or figures that form a part of the present disclosure, and in which are shown, by way of illustration, specific embodiments of one or more of the inventions. It should be appreciated, however, that such features are not limited to usage in the one or more particular embodiments or figures with reference to which they are described. The present disclosure is neither a literal description of all embodiments of one or more of the inventions nor a listing of features of one or more of the inventions that must be present in all embodiments.

[0025] Headings of sections provided in this patent application and the title of this patent application are for convenience only, and are not to be taken as limiting the disclosure in any way.

[0026] Devices that are in communication with each other need not be in continuous communication with each other, unless expressly specified otherwise. In addition, devices that are in communication with each other may communicate directly or indirectly through one or more communication means or intermediaries, logical or physical.

[0027] A description of an embodiment with several components in communication with each other does not imply that all such components are required. To the contrary, a variety of optional components may be described to illustrate a wide variety of possible embodiments of one or more of the inventions and in order to more fully illustrate one or more aspects of

the inventions. Similarly, although process steps, method steps, algorithms or the like may be described in a sequential order, such processes, methods and algorithms may generally be configured to work in alternate orders, unless specifically stated to the contrary. In other words, any sequence or order of steps that may be described in this patent application does not, in and of itself, indicate a requirement that the steps be performed in that order. The steps of described processes may be performed in any order practical. Further, some steps may be performed simultaneously despite being described or implied as occurring non-simultaneously (e.g., because one step is described after the other step). Moreover, the illustration of a process by its depiction in a drawing does not imply that the illustrated process is exclusive of other variations and modifications thereto, does not imply that the illustrated process or any of its steps are necessary to one or more of the invention(s), and does not imply that the illustrated process is preferred. Also, steps are generally described once per embodiment, but this does not mean they must occur once, or that they may only occur once each time a process, method, or algorithm is carried out or executed. Some steps may be omitted in some embodiments or some occurrences, or some steps may be executed more than once in a given embodiment or occurrence.

[0028] When a single device or article is described herein, it will be readily apparent that more than one device or article may be used in place of a single device or article. Similarly, where more than one device or article is described herein, it will be readily apparent that a single device or article may be used in place of the more than one device or article.

[0029] The functionality or the features of a device may be alternatively embodied by one or more other devices that are not explicitly described as having such functionality or features. Thus, other embodiments of one or more of the inventions need not include the device itself.

[0030] Techniques and mechanisms described or referenced herein will sometimes be described in singular form for clarity. However, it should be appreciated that particular embodiments may include multiple iterations of a technique or multiple instantiations of a mechanism unless noted otherwise. Process descriptions or blocks in figures should be understood as representing modules, segments, or portions of code which include one or more executable instructions for implementing specific logical functions or steps in the process. Alternate implementations are included within the scope of embodiments of the present invention in which, for example, functions may be executed out of order from that

shown or discussed, including substantially concurrently or in reverse order, depending on the functionality involved, as would be understood by those having ordinary skill in the art.

Hardware Architecture

5 [0031] Generally, the techniques disclosed herein may be implemented on hardware or a combination of software and hardware. For example, they may be implemented in an operating system kernel, in a separate user process, in a library package bound into network applications, on a specially constructed machine, on an application-specific integrated circuit (ASIC), or on a network interface card.

10 [0032] Software/hardware hybrid implementations of at least some of the embodiments disclosed herein may be implemented on a programmable network-resident machine (which should be understood to include intermittently connected network-aware machines) selectively activated or reconfigured by a computer program stored in memory. Such network devices may have multiple network interfaces that may be configured or designed to utilize different types of network communication protocols. A general architecture for some of these machines may be described herein in order to illustrate one or more exemplary means by
15 which a given unit of functionality may be implemented. According to specific embodiments, at least some of the features or functionalities of the various embodiments disclosed herein may be implemented on one or more general-purpose computers associated with one or more networks, such as for example an end-user computer system, a client computer, a network
20 server or other server system, a mobile computing device (e.g., tablet computing device, mobile phone, smartphone, laptop, or other appropriate computing device), a consumer electronic device, a music player, or any other suitable electronic device, router, switch, or other suitable device, or any combination thereof. In at least some embodiments, at least some of the features or functionalities of the various embodiments disclosed herein may be
25 implemented in one or more virtualized computing environments (e.g., network computing clouds, virtual machines hosted on one or more physical computing machines, or other appropriate virtual environments).

[0033] Referring now to **Fig. 1**, there is shown a block diagram depicting an exemplary computing device **100** suitable for implementing at least a portion of the features or
30 functionalities disclosed herein. Computing device **100** may be, for example, any one of the computing machines listed in the previous paragraph, or indeed any other electronic device capable of executing software- or hardware-based instructions according to one or more

programs stored in memory. Computing device **100** may be adapted to communicate with a plurality of other computing devices, such as clients or servers, over communications networks such as a wide area network a metropolitan area network, a local area network, a wireless network, the Internet, or any other network, using known protocols for such communication, whether wireless or wired.

[0034] In one embodiment, computing device **100** includes one or more central processing units (CPU) **102**, one or more interfaces **110**, and one or more busses **106** (such as a peripheral component interconnect (PCI) bus). When acting under the control of appropriate software or firmware, CPU **102** may be responsible for implementing specific functions associated with the functions of a specifically configured computing device or machine. For example, in at least one embodiment, a computing device **100** may be configured or designed to function as a server system utilizing CPU **102**, local memory **101** and/or remote memory **120**, and interface(s) **110**. In at least one embodiment, CPU **102** may be caused to perform one or more of the different types of functions and/or operations under the control of software modules or components, which for example, may include an operating system and any appropriate applications software, drivers, and the like.

[0035] CPU **102** may include one or more processors **103** such as, for example, a processor from one of the Intel, ARM, Qualcomm, and AMD families of microprocessors. In some embodiments, processors **103** may include specially designed hardware such as application-specific integrated circuits (ASICs), electrically erasable programmable read-only memories (EEPROMs), field-programmable gate arrays (FPGAs), and so forth, for controlling operations of computing device **100**. In a specific embodiment, a local memory **101** (such as non-volatile random access memory (RAM) and/or read-only memory (ROM), including for example one or more levels of cached memory) may also form part of CPU **102**. However, there are many different ways in which memory may be coupled to system **100**. Memory **101** may be used for a variety of purposes such as, for example, caching and/or storing data, programming instructions, and the like. It should be further appreciated that CPU **102** may be one of a variety of system-on-a-chip (SOC) type hardware that may include additional hardware such as memory or graphics processing chips, such as a Qualcomm SNAPDRAGON™ or Samsung EXYNOS™ CPU as are becoming increasingly common in the art, such as for use in mobile devices or integrated devices.

[0036] As used herein, the term “processor” is not limited merely to those integrated circuits referred to in the art as a processor, a mobile processor, or a microprocessor, but broadly refers to a microcontroller, a microcomputer, a programmable logic controller, an application-specific integrated circuit, and any other programmable circuit.

5 [0037] In one embodiment, interfaces **110** are provided as network interface cards (NICs). Generally, NICs control the sending and receiving of data packets over a computer network; other types of interfaces **110** may for example support other peripherals used with computing device **100**. Among the interfaces that may be provided are Ethernet interfaces, frame relay
10 interfaces, cable interfaces, DSL interfaces, token ring interfaces, graphics interfaces, and the like. In addition, various types of interfaces may be provided such as, for example, universal serial bus (USB), Serial, Ethernet, FIREWIRE™, THUNDERBOLT™, PCI, parallel, radio frequency (RF), BLUETOOTH™, near-field communications (e.g., using near-field
15 magnetics), 802.11 (WiFi), frame relay, TCP/IP, ISDN, fast Ethernet interfaces, Gigabit Ethernet interfaces, Serial ATA (SATA) or external SATA (ESATA) interfaces, high-definition multimedia interface (HDMI), digital visual interface (DVI), analog or digital audio interfaces, asynchronous transfer mode (ATM) interfaces, high-speed serial interface (HSSI) interfaces, Point of Sale (POS) interfaces, fiber data distributed interfaces (FDDIs), and the like. Generally, such interfaces **110** may include physical ports appropriate for
20 communication with appropriate media. In some cases, they may also include an independent processor (such as a dedicated audio or video processor, as is common in the art for high-fidelity A/V hardware interfaces) and, in some instances, volatile and/or non-volatile memory (e.g., RAM).

[0038] Although the system shown in **Fig. 1** illustrates one specific architecture for a computing device **100** for implementing one or more of the inventions described herein, it is
25 by no means the only device architecture on which at least a portion of the features and techniques described herein may be implemented. For example, architectures having one or any number of processors **103** may be used, and such processors **103** may be present in a single device or distributed among any number of devices. In one embodiment, a single processor **103** handles communications as well as routing computations, while in other
30 embodiments a separate dedicated communications processor may be provided. In various embodiments, different types of features or functionalities may be implemented in a system according to the invention that includes a client device (such as a tablet device or smartphone

running client software) and server systems (such as a server system described in more detail below).

[0039] Regardless of network device configuration, the system of the present invention may employ one or more memories or memory modules (such as, for example, remote memory block **120** and local memory **101**) configured to store data, program instructions for the general-purpose network operations, or other information relating to the functionality of the embodiments described herein (or any combinations of the above). Program instructions may control execution of or comprise an operating system and/or one or more applications, for example. Memory **120** or memories **101**, **120** may also be configured to store data structures, configuration data, encryption data, historical system operations information, or any other specific or generic non-program information described herein.

[0040] Because such information and program instructions may be employed to implement one or more systems or methods described herein, at least some network device embodiments may include nontransitory machine-readable storage media, which, for example, may be configured or designed to store program instructions, state information, and the like for performing various operations described herein. Examples of such nontransitory machine-readable storage media include, but are not limited to, magnetic media such as hard disks, floppy disks, and magnetic tape; optical media such as CD-ROM disks; magneto-optical media such as optical disks, and hardware devices that are specially configured to store and perform program instructions, such as read-only memory devices (ROM), flash memory (as is common in mobile devices and integrated systems), solid state drives (SSD) and “hybrid SSD” storage drives that may combine physical components of solid state and hard disk drives in a single hardware device (as are becoming increasingly common in the art with regard to personal computers), memristor memory, random access memory (RAM), and the like. It should be appreciated that such storage means may be integral and non-removable (such as RAM hardware modules that may be soldered onto a motherboard or otherwise integrated into an electronic device), or they may be removable such as swappable flash memory modules (such as “thumb drives” or other removable media designed for rapidly exchanging physical storage devices), “hot-swappable” hard disk drives or solid state drives, removable optical storage discs, or other such removable media, and that such integral and removable storage media may be utilized interchangeably. Examples of program instructions include both object code, such as may be produced by a compiler, machine code, such as may be produced by an assembler or a linker, byte code, such as may be generated by for example

a Java™ compiler and may be executed using a Java virtual machine or equivalent, or files containing higher level code that may be executed by the computer using an interpreter (for example, scripts written in Python, Perl, Ruby, Groovy, or any other scripting language).

[0041] In some embodiments, systems according to the present invention may be implemented on a standalone computing system. Referring now to **Fig. 2**, there is shown a block diagram depicting a typical exemplary architecture of one or more embodiments or components thereof on a standalone computing system. Computing device **200** includes processors **210** that may run software that carry out one or more functions or applications of embodiments of the invention, such as for example a client application **230**. Processors **210** may carry out computing instructions under control of an operating system **220** such as, for example, a version of Microsoft's WINDOWS™ operating system, Apple's Mac OS/X or iOS operating systems, some variety of the Linux operating system, Google's ANDROID™ operating system, or the like. In many cases, one or more shared services **225** may be operable in system **200**, and may be useful for providing common services to client applications **230**. Services **225** may for example be WINDOWS™ services, user-space common services in a Linux environment, or any other type of common service architecture used with operating system **210**. Input devices **270** may be of any type suitable for receiving user input, including for example a keyboard, touchscreen, microphone (for example, for voice input), mouse, touchpad, trackball, or any combination thereof. Output devices **260** may be of any type suitable for providing output to one or more users, whether remote or local to system **200**, and may include for example one or more screens for visual output, speakers, printers, or any combination thereof. Memory **240** may be random-access memory having any structure and architecture known in the art, for use by processors **210**, for example to run software. Storage devices **250** may be any magnetic, optical, mechanical, memristor, or electrical storage device for storage of data in digital form (such as those described above, referring to **Fig. 1**). Examples of storage devices **250** include flash memory, magnetic hard drive, CD-ROM, and/or the like.

[0042] In some embodiments, systems of the present invention may be implemented on a distributed computing network, such as one having any number of clients and/or servers. Referring now to **Fig. 3**, there is shown a block diagram depicting an exemplary architecture **300** for implementing at least a portion of a system according to an embodiment of the invention on a distributed computing network. According to the embodiment, any number of clients **330** may be provided. Each client **330** may run software for implementing client-side

portions of the present invention; clients may comprise a system **200** such as that illustrated in **Fig. 2**. In addition, any number of servers **320** may be provided for handling requests received from one or more clients **330**. Clients **330** and servers **320** may communicate with one another via one or more electronic networks **310**, which may be in various embodiments
5 any of the Internet, a wide area network, a mobile telephony network (such as CDMA or GSM cellular networks), a wireless network (such as WiFi, Wimax, LTE, and so forth), or a local area network (or indeed any network topology known in the art; the invention does not prefer any one network topology over any other). Networks **310** may be implemented using any known network protocols, including for example wired and/or wireless protocols.

10 **[0043]** In addition, in some embodiments, servers **320** may call external services **370** when needed to obtain additional information, or to refer to additional data concerning a particular call. Communications with external services **370** may take place, for example, via one or more networks **310**. In various embodiments, external services **370** may comprise web-enabled services or functionality related to or installed on the hardware device itself. For
15 example, in an embodiment where client applications **230** are implemented on a smartphone or other electronic device, client applications **230** may obtain information stored in a server system **320** in the cloud or on an external service **370** deployed on one or more of a particular enterprise's or user's premises.

[0044] In some embodiments of the invention, clients **330** or servers **320** (or both) may make
20 use of one or more specialized services or appliances that may be deployed locally or remotely across one or more networks **310**. For example, one or more databases **340** may be used or referred to by one or more embodiments of the invention. It should be understood by one having ordinary skill in the art that databases **340** may be arranged in a wide variety of architectures and using a wide variety of data access and manipulation means. For example,
25 in various embodiments one or more databases **340** may comprise a relational database system using a structured query language (SQL), while others may comprise an alternative data storage technology such as those referred to in the art as "NoSQL" (for example, Hadoop Cassandra, Google BigTable, and so forth). In some embodiments, variant database architectures such as column-oriented databases, in-memory databases, clustered databases,
30 distributed databases, or even flat file data repositories may be used according to the invention. It will be appreciated by one having ordinary skill in the art that any combination of known or future database technologies may be used as appropriate, unless a specific database technology or a specific arrangement of components is specified for a particular

embodiment herein. Moreover, it should be appreciated that the term “database” as used herein may refer to a physical database machine, a cluster of machines acting as a single database system, or a logical database within an overall database management system. Unless a specific meaning is specified for a given use of the term “database”, it should be construed
5 to mean any of these senses of the word, all of which are understood as a plain meaning of the term “database” by those having ordinary skill in the art.

[0045] Similarly, most embodiments of the invention may make use of one or more security systems 360 and configuration systems 350. Security and configuration management are common information technology (IT) and web functions, and some amount of each are
10 generally associated with any IT or web systems. It should be understood by one having ordinary skill in the art that any configuration or security subsystems known in the art now or in the future may be used in conjunction with embodiments of the invention without limitation, unless a specific security 360 or configuration system 350 or approach is specifically required by the description of any specific embodiment.

15 [0046] Fig. 4 shows an exemplary overview of a computer system 400 as may be used in any of the various locations throughout the system. It is exemplary of any computer that may execute code to process data. Various modifications and changes may be made to computer system 400 without departing from the broader spirit and scope of the system and method disclosed herein. CPU 401 is connected to bus 402, to which bus is also connected memory
20 403, nonvolatile memory 404, display 407, I/O unit 408, and network interface card (NIC) 413. I/O unit 408 may, typically, be connected to keyboard 409, pointing device 410, hard disk 412, and real-time clock 411. NIC 413 connects to network 414, which may be the Internet or a local network, which local network may or may not have connections to the Internet. Also, shown as part of system 400 is power supply unit 405 connected, in this
25 example, to ac supply 406. Not shown are batteries that could be present, and many other devices and modifications that are well known but are not applicable to the specific novel functions of the current system and method disclosed herein. It should be appreciated that some or all components illustrated may be combined, such as in various integrated applications (for example, Qualcomm or Samsung SOC-based devices), or whenever it may
30 be appropriate to combine multiple capabilities or functions into a single hardware device (for instance, in mobile devices such as smartphones, video game consoles, in-vehicle computer systems such as navigation or multimedia systems in automobiles, or other integrated hardware devices).

[0047] In various embodiments, functionality for implementing systems or methods of the present invention may be distributed among any number of client and/or server components. For example, various software modules may be implemented for performing various functions in connection with the present invention, and such modules may be variously
5 implemented to run on server and/or client components.

[0048] Fig. 5 is block diagram illustrating an exemplary blockchain, according to a preferred embodiment of the invention. According to the embodiment, blockchain 500 comprises a plurality of blocks 501a..n configured in a form of a distributed database that maintains a continuously growing list of data records (or blocks) that are hardened against tampering and
10 revision, including the operators of peer nodes 550. The most widely known application of a blockchain is the public ledger of transactions for the Bitcoin network, although the concept of blockchains can be implemented for any kind of decentralized record keeping system, as demonstrated by the use of blockchain in other alternate cryptocurrency networks such as Namecoin, Ethereum, NXT, and the like. Most of the well-known implementation of
15 blockchain are as a public ledger of transactions, such that all the interactions recorded on the blockchain is open to scrutiny and examination by anyone. Although it is possible to have other modified implementation of the blockchain including ones where the interactions recorded on the blockchain (or the properties of the interactions) are kept private.

[0049] Accordingly, in a blockchain, “blocks” or sets of completed transactions 510a..n and
20 520a..n (such as transferring cryptocurrency funds from one account to another, as with bitcoin) are periodically updated. During an update, a block is pushed from one node (generally, an originating node where a transaction completed, for example a user device used to receive or send funds) to other nodes rapidly, enabling every node in the system to maintain an up-to-date record of all transactions. Using distributed nodes, data integrity is
25 maintained through general consensus, protecting the blockchain against tampering or errors such as might arise if nodes lose connectivity or are run autonomously and produce errors during unattended operation. The general consensus method may also enable any one node to verify a transaction with other copies of the blockchain, preventing counterfeiting or tampering.

[0050] Using a blockchain arrangement 500, signatures for recordings may be published to a
30 blockchain either using a blockchain specifically configured for such use (for example, where each “transaction” is a single recording’s unique signature), or by “piggybacking” on an

existing blockchain by conducting zero-sum transactions and attaching signature data to them (for example, by using a signature as a destination wallet for a fund transfer, so it is irrevocably stored in the blockchain). In this regard, signatures may be published in a manner that is publicly accessible, easily verified and validated, and resistant to tampering or forgery.

- 5 **[0051]** In an exemplary implementation, blockchain **500** may contains unique identifiers which allow user devices to send and receive various tokens between various participants *that is, devices) on the network. An exact implementation of the address mechanism might change between the different implementations of blockchain **500**. For example, In the bitcoin embodiment of a blockchain, addresses are created and managed using, for example, a SHA-
10 256 based public key/private key mechanism. The following is an example bitcoin address:

1JArS6jzE3AJ9sZ3aFij1BmTcpFGgN86hA

- [0052]** The bitcoin address allows a plurality of user devices to send and receive tokens from a plurality of other user devices on a bitcoin network. Each time any of these tokens are sent from one bitcoin address to another, transaction **540** gets created on blockchain **500**.
15 Transaction **540** then gets validated by the network of peer nodes **550**, to see if it is authentic. If confirmed to be authentic, then transaction **540** gets permanently recorded on blockchain **500**, as part of the latest block **501n**. In this regard, every Bitcoin address has a matching private key, where the bitcoin address itself acts as the public key. The private key is mathematically related to an associated bitcoin address, and is designed so that the bitcoin
20 address can be calculated from the private key, but importantly, the same cannot be done in reverse. A transaction of tokens out of a bitcoin address can only be initiated by the owner of the private key.

- [0053]** Note that a bitcoin address may also be created and operated by programmable instructions on a computer often referred to as smart contracts or smart contract code. These
25 smart contracts can control and operate their bitcoin addresses, in an autonomous manner based on certain conditions as defined by their programming logic. These smart contracts may be used to automate transaction logic that may need to happen on the blockchain.

- [0054]** Although bitcoin is the primary token that gets transferred between users on the bitcoin network, the bitcoin blockchain can be used to issue and transact in several other
30 custom created tokens. These tokens may be collectively referred to as “interaction objects” (as is described later). The creation of interaction objects on the bitcoin blockchain can be

enabled using an overlay network protocols (e.g. Counterparty, Mastercoin, Colored coins, etc.) or using several other alternate techniques including but not limited to side chain implementations.

5 **[0055]** The bitcoin blockchain has been used in a number of instances to explain principles and concepts throughout this document, as it is an exemplary embodiment of a blockchain. The use of blockchain and other related concepts are in no way limited to the bitcoin blockchain. Any number of other related or different implementations of blockchain may be used by a valid embodiment of the present invention, including other alternate implementations of the blockchain such as NXT, Ethereum or other private blockchains.

10 **[0056]** A hash function or a hash algorithm may be any function that can be used to map one or more data inputs of arbitrary size into fixed or varying length data, such that the mapped data acts as a unique identifier for the input data. The values returned by a hash function can be referred to as hash values, hash codes, hash sums, unique hash identifiers or simply hashes. Some of the more common hashing functions that rely on cryptography include
15 SHA1, SHA2, SHA256 and MD5. But hashing function can use several other techniques including non-cryptographic technologies, such as simple merging of all the data inputs, or passing along the input data unaltered provided the input data is already unique.

20 **[0057]** Encryption is a process of coding information which could either be a file or mail message in into cipher text a form unreadable without a decoding key in order to prevent anyone except the intended recipient from reading the encrypted data. Decryption is the reverse process of converting encoded data to its original un-encoded form, for example, plaintext.

25 **[0058]** A key in cryptography is a long sequence of bits used by encryption/decryption algorithms. For example, the following represents a hypothetical 40-bit key:

00001010 01101001 10011110 00011100 01010101

30 **[0059]** An encryption algorithm may take an original message, and a key (for example, a private key), and alters the original message mathematically based on the key's bits to create a new encrypted message. Likewise, a decryption algorithm takes an encrypted message and restores it to its original form using one or more keys. When a user device encodes a piece of information, another user cannot decode and read that piece of information without the decryption key (for example, a public key). Through this mechanism one can add a digital

signature to digital content/information, such that it acts as a form of personal authentication, ensuring the integrity of the original message. To encode plaintext, an encryption key is used to impose an encryption algorithm onto the data. To decode cipher, a user must possess the appropriate decryption key. A decryption key consists of a random string of numbers, for
 5 example, from 40 through 2,000 bits in length. The key imposes a decryption algorithm onto the data. This decryption algorithm reverses the encryption algorithm, returning the data to, for example, plaintext. The longer the encryption key is, the more difficult it is to decode. For a 40-bit encryption key, over one trillion possible decryption keys exist.

[0060] There are two primary approaches to encryption: symmetric and public-key (or
 10 asymmetric). Symmetric encryption is the most common type of encryption and uses the same key for encoding and decoding data. This key is known as a session key. Public-key (or asymmetric) encryption uses two different keys, a public key and a private key. One key encodes the message and the other decodes it. The public key is widely distributed while the private key is secret. Some examples of popular symmetric key algorithms are, AES, 3DES
 15 modes along with the original DES algorithm and its block cipher modes. Some examples of public-key (or asymmetric) encryption algorithms include, DSS, RSA, ECDSA.

[0061] Aside from key length and encryption approach, other factors and variables impact the success of a cryptographic system. For example, different cipher modes, in coordination with initialization vectors and salt values, can be used to modify the encryption method. Cipher
 20 modes define the method in which data is encrypted. The stream cipher mode encodes data one bit at a time. The block cipher mode encodes data one block at a time. Block encryption may be used to implement a digital signature mechanism used to prove authenticity in various scenarios.

[0062] Blockchain **500** may comprises of a series of a plurality of grouped together
 25 transactions (or blocks) **501a..n**, that may be linked to one another in a time linear manner **502a..n**. One or more new transactions **510a..n**, **520a..n**, **530a..n** may be collected into the transaction data part **510a..n**, **520a..n**, and **530a..n** of each respective block **501a..n**. In some embodiments, copies of each transaction may be hashed, and the hashes could then be paired, hashed, paired again, and hashed again until a single hash remains, which could act as the
 30 merkle root **503a** of a merkle tree **503a..n**. A merkle root **503a..n** may be stored in block header **504a..n**. Each block could also store the hash **505a..n** of the previous block's header, chaining the blocks together. Accordingly, a transaction cannot be modified without

modifying the block that records it and all following blocks. Chaining blocks together in this fashion makes it impossible to modify transactions included in any block without modifying all following blocks. Thus, the cost to modify a block increases with every new block added to the blockchain. This system provides a robust way to prevent the tampering of the

5 transactions on blockchain **500**. Blockchain **500** may be collaboratively maintained by anonymous peer nodes **550** on the network, as parts of the blockchain network or, in other embodiments, peer nodes **550** may not be anonymous. The blockchain might be part of a global network via network **310**, as in the case with bitcoin. In other embodiments, network **310** may be a local network.

10 **[0063]** Miners **560** provide a process for adding transaction records to a ledger of transactions (that is, blockchain **500**) as blocks. Blockchain **500** can be seen as chain of blocks **510a..n**, **520a..n**, **530a..n**, etc. Blockchain **500** serves to confirm transactions, for example, transaction **540**) to the rest of the network as having taken place. Nodes use blockchain **500** to distinguish legitimate transactions from attempts to manipulate transactions that have already

15 taken place. Miners **560** are resource-intensive and difficult so that the number of blocks found each day by miners **560** remains steady. Individual blocks must contain a proof of work to be considered valid. This proof of work is verified by other blockchain **500** nodes (for example, peer nodes **550**) each time they receive a block. For example, in a Bitcoin arrangement, a hashcash proof-of-work function is used. In a preferred embodiment, miners

20 **560** allow nodes to reach a secure, tamper-resistant consensus. Miners **560** may also be a mechanism used to introduce blocks into the system (in some embodiments, in conjunction with other components). In some embodiment, miners **560** are compensated with transaction fees as well as a “subsidy” of newly created nodes. This both serves the purpose of disseminating new nodes in a decentralized manner as well as motivating connected devices

25 to provide security for the system.

Conceptual Architecture

[0064] Fig. 6 is a block diagram illustrating a plurality of exemplary objects for a block reconciliation system, according to a preferred embodiment of the invention. According to the embodiment a plurality of data objects **600** are used for a block reconciliation system

30 comprising a plurality of objects **600** associated to a plurality of actors in the system whereby an actor may be a user device, an administrator device, an entity device. According to them embodiment a plurality of global variables **601** define a plurality of global states for the system environment **700** (as in Fig. 7). Global variables **601** comprise an enumerated

InteractionType **602** which may define a list of interaction types available to system **700** to describe what type of interaction is referenced for various interactions of the system. In an exemplary embodiment, InteractionType **602** may comprise, at least: contract/intention **603** which may define a contract or, for example, a memorandum-of-understanding for an

5 interaction. In a preferred embodiment, contract/intention **603** may correspond to a smart contract that programmatically, via programming instructions, facilitates, verifies, or enforces the negotiation or performance of contract/intention **603**. In this regard, a contractual clause in, for example, an associated document, may expect a fulfillment interaction (for example, InteractionType **602** being fulfillment **607**) to finalize it or indicate that the contract had a

10 predicted outcome. InteractionType **602** may further comprise purchase **604** may define an interaction the represents an exchange of value of some sort between, for example, one or more user, provider, or subscriber devices, or with some other connected device. In some embodiments, a purchase may require a fulfillment to indicate that goods were delivered for the purchase. InteractionType **602** may further comprise refund **605** may define an interaction

15 that represents a restoration of exchanged value where an exchange of value may have happened previously between, for example, one or more user, provider, or subscriber devices, or with some other connected device. InteractionType **602** may further comprise expense **606** that may define an interaction type that is an expense category, for example, if an interaction was a reimbursable amount by, for example, a juristic entity associated to a user device **713**

20 associated to the interaction that may, for example, have an agreement in place for reimbursement of any value exchanged. InteractionType **602** may further comprise fulfillment **607** may be an interaction type that defines a fulfillment of a previous interaction type, for example, if a previous InteractionType **602** was a contract **603** (as described earlier), the fulfillment **607** interaction type, may indicate that the contract or agreement was fulfilled.

25 Global Variables **601** may further comprise an array of actors **608** that may define one or more user devices associated to the interaction; global variables **601** may further comprise a pointer to theBlockchain **609** whereby the pointer defines a location to a blockchain (for example, blockchain **500** as in **Fig. 5**) for recordation of interactions, configurations, and other data of system **700**. It should be appreciated that system **700** may use one or more

30 blockchains **500** (referring to **Fig. 5**) or other distributed public (or private) ledger database schemas that may maintain a continuously-growing list of ordered records (for example, as described in **Fig. 5**) for interactions, configurations, and other data of system **700**. It should be appreciated by one with ordinary skill in the art that the interaction types may be different or may describe other global states for system **700**. It should also be appreciated that there

may be other global variables **601** associated defining additional or different global states for system **700** and that this is simply an exemplary subset.

[0065] In a preferred embodiment, blockchain object **610** may define basic information associated to a transaction that is to be recorded to blockchain **500** configured in the global variable theBlockchain **609**. According to the embodiment, blockchain object **610** may comprise objectId **611** that may be a unique identifier identifying the instance of blockchain object **610**. Blockchain object **610** may further comprises name **612** which may comprise a textual name (for example, an ASCII description) for the instance of blockchain object **610**. Blockchain object **610** may further comprise date-time **613** to record a date and time associated to the instance of blockchain object **610**. Blockchain object **610** may further comprise owner_publicBlockchainKey **614** that may define an actor (for example, a device **712** to **715**) associated to the instance of blockchain object **610**. In some embodiments, owner_publicBlockchainKey **614** may be associated to a user object **670**. Blockchain object **610** may further comprise digital_signature **615** defining a sequence of characters that may be used by one of a plurality of miners **560** (as in **Fig. 5**) to verify that the true owner associated to owner_publicBlockchainKey **614** of the given publicBlockChainKey **672** of the instance of blockchain object **610**, is genuine.

[0066] In a preferred embodiment, interaction object **620** comprises properties an information associated to interactions between devices **712** to **715** within system **700**. Interaction object **620** may comprise a pointer to a blockchain object **621** which may be a pointer to one or more theBlockChain **609** (that is, the instant interaction object **620** effectively inheriting the properties and fields of a blockchain object **610**) which may represent blockchain **500** to which the instant interaction objects **620** may be used for recording interactions, or reading prerecorded information. Interaction object **620** may further comprise user **622** which may correspond to a user object **670**, a company object **680**, or a device object **690** that may be involved with an interaction to which the instant interaction object **620** is associated. Interaction object **620** may further comprise interaction_id **624** which may be a unique id associated to the interaction. Interaction object **620** may further comprise other_party_digital_signature **625** which may be a digital signature associated to a digital signature to other parties (for example, another user object **670**, company object **680**, or device object **690**) that may be associated to the instant interaction object **620**. In some embodiments, the validity of the other parties is determined (for example, by miners **560** or in some embodiments, by peer nodes **550**) based on other_party_digital_signature **625** and an

associated publicBlockchainKey **672**. It should be appreciated that other_party_digital_signature **625** may be how the system may know that the “other party” was actually involved in the interaction. Interaction object **620** may further comprise InteractionType **626** which may indicate an interaction type for the instant interaction object

5 **620**. Interaction object **620** may further comprise interaction_event **627** which may be an optional parameter that may be used to categorize the instant interaction object **620** with a certain keyword (for example, “business trip”, “conference 2015”, or the like). Interaction object **620** may further comprise Array<BlockchainObject> interactionItems **628** which may be an array of associated interactions items associated to the instant interaction object **620**.

10 **[0067]** In a preferred embodiment, entity object **630** is associated to an entity device **715** describing properties and functions available to system **700**. In a preferred embodiment, an entity is a physical object that may serve a purpose, for example, a vehicle may be an entity whereby an entity device **715** may be attached thereon and provides information about the physical object such as who may have used the vehicle, how far and locations of the vehicle

15 during a particular timeframe (or other parameter). In this regard, an entity device **715** would be attached (physically or logically) to the physical object to “connect” the services and capabilities to network **310**. In this example, if there was value exchanged between devices **712** to **715** for the use of the vehicle, and the like, then an interaction would occur and be recorded. An entity device **715** can be associated to any physical object whereby the

20 associated entity device **715** captures data on that device for use in system **700**. Entity object **630** may comprise a pointer to blockchain object **631** inheriting all fields and properties of blockchain object **610** (as is known in the art of object-oriented programming). Entity object **630** may further comprise entityCategory **632** which defines what type of entity is associated to the instant entity object **630**. For example, a vehicle, a meeting room, a desk, or some other

25 item to which a device (that is, a device described by device object **690**) is associated to in system **700**, whereby the device defines properties, actions, and other functions that may be performed, such as renting, using, driving, etc. Entity Object **630** may further comprise device_publicBlockchainKey **633** which corresponds to a publicBlockchainKey **672** (as inherited) by an associated device object **690**. Entity Object **630** may further comprise Array

30 entityProperties **634** which may comprise a plurality of properties describing characteristics of the corresponding entity. EntityProperties **634** may comprise description **635**, a description of the entity; units **636**, a number of units associated to the entity (if any); base price/rate **637**, if the entity has an associated cost component (for example a rate for a car rental); duration

638, a numeric value associated to the amount of time an entity is available for use or a duration of how long it may have been used; distance **639**, corresponding to a distance the entity traversed while used (for example, the usage of a vehicle); percentage **640** which may be a percentage amount that may be used for different purposes, such as the use of the entity is only considered at a percentage; and the like. It should be appreciated that these properties are merely exemplary and different properties could describe usage of services associated to entity devices **715** (or in some embodiments, user devices **713**).

[0068] In a preferred embodiment, rules object **644** comprises a set of rules associated to an interaction or an entity, or both, and may dictate how objects are compiled or recorded.

According to the embodiment, rules object **644** may comprise a pointer blockchain object **645** which may be a pointer to a blockchain similar to previous objects. It should be appreciated that a plurality of rules can be created and associated to other objects **600** to define a behavior for the associated objects during issuance, compilation, or reporting. In some embodiments, a plurality of rule sets may be configured such that different instances of system **700** (or different objects sets **600** of system **700**) may use a different set of rules based on preconfigured states to have objects behave in a particular way based on a preconfigured set of rules. For example, rules may be based on jurisdiction, location, time-of-year, or some other identifier. Rules object **644** may further comprise entityCategory **646** which may define a category for an entity, for example, items needed for business transactions, items needed for lodging or travel. Rules object **644** may further comprise companyType **647** which may identify a type of company associated to the rule object **644**. Rules object **644** may further comprise interactionType **648** which identifies which interaction type is associated to the instance of the rule object **644**. Rules object **644** may further comprise ruleProperties **649** which may be an array to optional properties associated to the instant instance of the rule object **644**. For example, rule properties may define specific aspects to the rule outlined in the instant instance of rule object **644**, including, but not limited to, how the rule manipulates values associated to an interaction object (for example, the value is divided into subcomponents whereby each subcomponent is treated differently, whether an associated value is subject to other rules, what sort of category should be associated to the entity, etc.)

[0069] In a preferred embodiment, compilation object **650** associates a plurality of objects **600**, the plurality of objects **600** identified by an array of compObjects **651** that are deemed to be associated to each other by compilation identifier compIdentifier **652** for calculation and reporting purposes. It should be appreciated that compIdentifier **652** may be compiled by

- compiler **701** in a number of ways that includes, but not limited to: objects **600** associated to a particular user object **670**, company object **680**, device object **690**; associated to a specific time period, or some other common element within system **700**. According to the embodiment, compilation object **650** may comprises a pointer to blockchain object **665** to inherit properties, as described earlier. Further according to the embodiment, compilation object **650** may comprise report **652** which may be an identifier associated to a report by report engine **716**. According to the embodiment, compilation object **650** may further comprise subscribers **653** which may be an array identifying one or more user objects **670** or company objects **680** associated to subscriber devices **714** that have access report **652**.
- 10 **[0070]** In a preferred embodiment, supplemental object **660** may comprise an object supplying supplement information associated to a previous object **600** (for example, a previous interaction object **620**) whereby the supplemental information provides additional information including, but not limited to, a fulfilment of fulfilment **607** identified in a previous associated object. Supplemental object **660** may also identify and amend or added
- 15 information for a previous object **600** whereby amended properties are updated or other properties added. According the embodiment, supplemental object **660** may comprise pointer to blockchain object **661**, inheriting all properties, as described earlier. Further according the embodiment, supplemental object **660** may comprise amendedObjectId **662** which may identify the previously associated object, that is the object that is being fulfilled or amended.
- 20 Further, according the embodiment, supplemental object **660** may comprise array amendedProperties **663** which may be an array of properties with associated fulfilment information, or identifying a number of properties that are identified as amended.
- [0071]** In a preferred embodiment, user object **670** describes a user device **713** registered within system **700**. According to the embodiment, user object **670** may comprise name **671**
- 25 which may identify a name or label describing the associated user device **713**. Further, according to the embodiment, user object **670** may comprise publicBlockchainKey **672** which may be a public key associated to a cryptographic system that uses pairs of keys: public keys which may be disseminated widely, and private keys which are known only to the user device **713**. Further, according to the embodiment, user object **670** may comprise
- 30 privateBlockchainKey **673** which may be a private key associated to the cryptographic system that uses pairs of keys: public keys which may be disseminated widely, and private keys which are known only to the user device **713**.

[0072] In a preferred embodiment, company object **680** may be a type of user device associated to a juristic entity or associated to some service provider. In some embodiments, company object **680** may be associated to one or more user objects **670**. In this regard, company object **680** may perform reporting, via report engine **716**, and the one or more user objects **670**. Accordingly, company object **680** may comprise pointer to user object **681** which may be a pointer to user object **670** inheriting all properties, as described earlier. According to the embodiments, company object **680** may further comprise companyType **682** which may identify a company type, for example, a company that provides particular services such as a car rental agency, an office rental company, a restaurant, an entertainment facility, and the like. It should be appreciated that in some embodiments, a company object **680** is associated to a plurality of device objects **690**, each associated to a company device **712** identifying a device that is associated to a plurality of user devices **713** (as described by a plurality of user objects **670**) whereby interaction information associated to the plurality of user devices **713** are accessible by company device **712**. In other embodiments company object **680** is associated to one or more entity device **715** whereby an entity device provides details on services provided by the company object **680**.

[0073] In a preferred embodiment, device object **690** describes an entity device **715**. According to the embodiment, device object **690** may comprise a pointer to User Object **691** inheriting all properties of user object **670**, as described for other objects previously. Further according to the embodiment, device object **690** may comprise owner_publicBlockchainKey **692** which may be a public key associated to a cryptographic system that uses pairs of keys: public keys which may be disseminated widely, and private keys which are known only to the user device **715**.

[0074] Fig. 7 is a block diagram illustrating a block reconciliation system, according to a preferred embodiment of the invention. According to the embodiment, a compiler **701** comprises programming instructions stored in a memory and running on a processor, the instructions configured to compiling a plurality of block objects **600** stored on blockchain **500** (that is, a plurality of objects **600** that may have been previously written as blocks by interaction recorder **702**) based on specific criteria by, for example, a request from a user device **713**, a company device **712**, or a subscriber device **714**, or any combination thereof. In some embodiments, criteria is received from external data source **720**. Compiler **701** may compile objects **600** within a period-of-time, based on objects **600** associated to a specific user object **670**, based on objects **600** associated to a specific company object **680**, or based

on objects **600** associated to a specific device object **690**, or some other identifying criteria. It should be appreciated that objects may be stored as blocks on blockchain **500**. Compiler **701** may also form a compilation object **650** from a collection of objects **600** to create a compiled set of objects **600** available for use by, at least, subscriber device **714**, company device **712**,
5 or user device **713**, or any combination thereof. In some embodiments, compiled objects (that is, compilations objects **650**) are stored on blockchain **500** and made available through an API.

[0075] Further according to a preferred embodiment, interaction recorder **702** comprises programming instructions stored in a memory and running on a processor, the instructions
10 configured to recording a plurality of interaction objects **620** (and in some embodiments, other objects **600**) for interactions between a plurality of user devices **713**, company devices **712**, entity devices **715**, or between any combination thereof. Interactions may be usage of services represented by, for example, entity device **715**, an agreement between a plurality of user devices **713**, or some other transaction between devices. Entity device **715** may be a
15 hardware computing device associated with network **310** and may be typically assigned an Internet Protocol (IP) address. The IP address is sufficient to uniquely identify entity device **715** within network **310** (for example, the Internet). In a preferred embodiment, entity devices **715** may bi-directionally communicate in a one-to-one relationship with another device **715** (or another device **712**, **713**, **714**) coupled to network **310**. Accordingly, network **310** has a
20 plurality of devices coupled to, for example, the Internet, and other connected devices **712**, **713**, **714**, and **715** may communicate together. In some embodiments, entity devices **715** are configured with a transceiver and other hardware and software to enable network communications both wired and wirelessly. In a preferred embodiment, entity devices **715** may provide commercial functions, consumer functions, or other functions. These devices
25 may include vending machines, packaging equipment, utility meters, parking meters, factory automation, restaurants, meeting room facilities, car rentals, hotels, remote antenna monitoring equipment, automotive vehicles, trains, and more.

[0076] Further according to a preferred embodiment, rules engine **703** comprises programming instructions stored in a memory and running on a processor, the instructions
30 configured to define a set of rules associated to objects **600**. A set of rules may define how data (for example, properties within object **600**) is treated at a compilation step by compiler **701** (as described previously). Encrypt/decrypt engine **704** comprises programming instructions stored in a memory and running on a processor, the instructions configured to

function as a cryptographic system that uses pairs of keys: public keys which may be disseminated widely, and private keys which are known only to the owner. Encrypt/decrypt engine **704** may encrypt a plurality of fields of objects **600** before issuance to blockchain **500** so that the contents of objects are only visible by processes with the proper decryption process. Encrypt/decrypt engine **704** may further preforms decryption in a compilation or subscription step. Block processor **705** comprises programming instructions stored in a memory and running on a processor, the instructions configured to process various properties of objects **600** (referring to **Fig. 6**) including, but not limited to, reading and retrieving blocks **600** from blockchain **500**. Report engine **716** comprises programming instructions stored in a memory and running on a processor, the instructions configured to process a plurality of compiled blocks, that is compilation objects **650** (as compiled by compiler **701**) for use in report creation by, for example, as requested by subscriber device **714**. In some embodiments, reports generated by report engine **716** may rely on report specific rules stored as report objects **644** (and associated to at least a portion of objects **600**) in rules database **707** or in blockchain **500** (or both).

[0077] Configuration database **706** manages configuration for the block reconciliation system **700** and may be used by any system **700** component for component, system, and other configuration. Configurations may be created by user devices **713**, company devices **712**, entity devices **715**, or any combination thereof. Rules database **707** stores rules from rules engine **703** available for configuring objects **600**, or for compiling objects **600** by compiler **710**. In some embodiments, rules database **707** is a local copy of the rules stored as rules objects **644** in blockchain **500** and may run independently of any connection to blockchain **500**. In some embodiments, system **700** acts as a failover for configurations or rules stored in blockchain **500**. Object database **708** may hold, at least, a primary configuration of objects **600** and made available in blockchain **500** such that they can be read for use and configuration from blockchain **500** and/or object database **708** by block processor **716** in block reconciliation system **700**.

[0078] Subscriber interface **709** comprises programming instructions stored in a memory and running on a processor, the instructions configured to receive (and send) requests from a subscriber device **714** (for example, requests to view or download contents of compilation objects created by compiler **701**, or for report creation by report engine **716**, or the like). In some embodiments, subscriber interface **709** may be in the form of an API that may integrated into other software applications (for example, number management applications,

financial management applications, and the like). The API may provide access to external programs to access compilation objects **650** (and other objects **600**) via block processor **705** and manage all access rights and configurations to all API connected programs. Block processor **705** can access objects with proper access privileges and provide them to the API
5 or other parts of system **700**.

[0079] Device interface **710** comprises programming instructions stored in a memory and running on a processor, the instructions configured to manage communications with company devices **712**, user devices **713**, and entity devices **715**. In some embodiments, user devices **713** may communicate information directly to blockchain **500**, in other embodiments, devices
10 may communicate with block reconciliation system **700** prior to object issuance by interaction recorder **702**. Blockchain **500** is a public ledger of transactions that have been executed since the birth of block reconciliation system **700**. In a preferred embodiment, it may constantly grow as “completed” blocks **540** (referring to **Fig. 5**) are added by interaction recorder **702** with a new set of object issuances. Objects **600** are added as blocks to
15 blockchain **500** in a linear, chronological order (as described in **Fig. 5**). Company devices **712** are network connected device that comprises programming instructions stored in a memory and running on a processor, the instructions configured to communicate with device interface **710** to retrieve information from object database **708** or from blockchain **500** (or a combination of both, or from some other data source within system **700**) to provide a
20 mechanism for a company user review one or more objects **600** either individually or as compiled by compiler **701**, or a combination of both.

[0080] Entity devices **715** are network-connected devices, each comprising programming instructions stored in a memory and running on a processor, the instructions configured to digitally describe associated services (for example, services available at a location or object
25 to which the entity object **715** is associated) available to user devices **713**. Entity devices **715** further comprise programming instructions configured to provide data (in the form of objects **600**, and particularly including, but not limited to, interaction objects **620** and entity objects **630**, or other objects **600**, or any combination thereof) about usage of services associated to entity devices **715** used by user devices **713** (that is, interactions between a first user object
30 **713** and a first entity object **715**) to device interface **710** whereby interaction recorder **702** issues objects in the form of blocks to blockchain **500**. In some embodiments, entity devices **715** comprise components of system **700** such that entity device **715** can issue objects **600** directly to blockchain **500**. In similar embodiments, entity device **715** comprises an instance

of system 700 such that it can act as a failover or it can perform actions in parallel to system 700. For example, company device 712 may be attached to a rental automobile whereby when a user device 712 utilizes the services of the automobile, interaction object 620 may be issued to blockchain 500 by interaction recorder 702 comprising information on details of the usage of the service are network-capable devices connected to restaurants comprising all available plates and associated costs, professional services with details around such services and associated costs, services or goods available for rental or purchase, and the like. It should be appreciated that according to a preferred embodiment of the invention, that entity devices 715 may be seen as an internetworking of physical devices, vehicles, buildings, and other items that are embedded with electronics, software, sensors, actuators, and network connectivity that enable these objects to collect and exchange data. Entity devices 715 may also referred to as “connected devices” and “smart devices”. Entity devices 715 may be seen as an infrastructure of an information society between a plurality of entity devices 715 registered with system 700. In some embodiments, entity devices 715 allow physical objects to be sensed and/or controlled remotely across network infrastructure 310 creating opportunities for more direct integration of the physical world into systems 700, and resulting in improved efficiency, accuracy and data recordation for interactions between user devices 713, company devices 712, entity devices 715, or between any combination thereof. In some embodiments entity devices 715 may be augmented with sensors and actuators, to form a more general class of cyber-physical systems, which may also encompass technologies such as smart grids, smart homes, intelligent transportation and smart cities. Each entity device 715 is uniquely identifiable through via an associated entity object 630 and able to interoperate within network infrastructure 310 as described. It should be appreciated that according to a preferred embodiment of the invention, a user device 713 may automatically engage an entity device 715 when associated services are available or requested, or both. This communication may happen through a short-range wireless communication protocol, WiFi, or some other communication (for example, as disclosed in **Fig. 1**).

[0081] User device 713 may be a network-connected device that comprises programming instructions stored in a memory and running on a processor, the instructions configured to electronically request services associated to one or more entity devices 715 and generate interactions in the form of interaction objects 620 based on usage of services associated to entity object 715. In this regard, there may be one or more interaction objects 620 issued to

blockchain **500** based on services used, and/or interactions between user devices **713** and entity objects **715**.

[0082] Subscriber devices **714** each comprises programming instructions stored in a memory and running on a processor, the instructions configured to access and subscribe to objects
5 (individual objects as issued by interaction recorder **702** or compiled objects as compiled by compiler **701**) from blockchain **500** via subscriber interface **709**. In some embodiments, a subscriber device **714** is an instance of reconciliation system **700** and can access objects directly from blockchain **500** through network **310**. It should be appreciated that device interface **710** and subscriber interface **709** may manage access permissions for user devices
10 **713**, company devices **712**, entity devices **715**, and subscriber devices **714**.

[0083] External data source **720** may be an additional data source for criteria selection for object compilation by compiler **701** or may be an additional source for rule definition. In some embodiments, external data source **720** may modify rules or add rule components in real-time during compilation or report creation.

[0084] **Fig. 8** is a flow diagram illustrating an exemplary method for issuing a rule to a block reconciled blockchain, according to a preferred embodiment of the invention. According to the embodiment, a system for issuing a plurality of rules to blockchain **500** is disclosed. Rules may define, at least, how objects behave when objects **600** are issued to blockchain
15 **500**, how compilation objects **650** (or any object **600**) behaves when they are compiled by compiler **701**, or how a report is generated by report engine **716**, or other system behavior.
20

[0085] In a first step **801**, a rule issuance function begins. In a next step, **802** a rule type is selected from a plurality of available pre-configured rule types as preconfigured (for example, by a company device **712**) from blockchain **500**, or in some embodiments, from rules database **707**. In some embodiments rule database **707** is a copy of rules and rule types
25 from blockchain **500**. In some embodiments rule database **707** may act as a failover or redundancy process. In some embodiments, a plurality of sets of rule types may be available from a plurality of rule creators/rule publishers (for example, as provided through a plurality of company devices **712**) to provide different behaviors affecting objects **600** or to provide compilation rules to compiler **701** based on, for example, external factors (for example,
30 jurisdictional or legislative rules by region or provider, rules based on company policy, rules based on individual preference, and the like). In a next step **803**, ruleProperties **649** are configured defining the rule and which blocks **600** may use the rule and how it may affect the

data within the object or computations across multiple objects **600**. In some embodiment, the instant rule may be used by compiler **701** or report engine **716**. In some embodiments, rules are further defined by an external calculation program. In a next step **804**, a name is assigned to the rule for convenience and easy identification. Further in step **804**, rules engine **703**

5 assigns a unique ID. In a next step **805**, the instant rule is issued to blockchain **500** and made available for use by, at least, user devices **713**, company devices **712**, entity devices **715**, compiler **701**, report engine **716**, or any other component of system **700** that provides a mechanism to affect the behavior of reporting (that is, functions performed on at least a portion of blocks/objects used in creating a report by, for example, subscriber device **714**),

10 behavior of compilation (that is, computations on a plurality of blocks/objects **600** compiled for a subscriber device **714**, a company device **712**, or for the creation of a compilation object **650**), or behavior of issuance of blocks (that is, including, but not limited to, how properties may be manipulated before object issuance by interaction recorder **702**), or any combination thereof. In a similar embodiment, all elements of the system, for example object

15 configurations, would be created and stored in a similar fashion such that all elements for creating and instantiating, for example, objects **600** that would be available from blockchain **500** (or from an associated database from system **700**).

[0086] Fig. 9 is a flow diagram illustrating an exemplary method for issuing an object to a block reconciled blockchain, according to a preferred embodiment of the invention.

20 According the embodiment, an issuance method comprises a configuration of plurality of objects **600** resulting from interactions between one or more company devices **712**, user devices **713**, subscriber devices **714**, or entity devices **715**, or any combination thereof, beginning in step **901**.

[0087] In a next step **902**, a device, for example a user devices **713** may, for example, be requesting services from an entity device **715** whereby an interaction object **620** is used to journal the interaction between the devices to a public ledger blockchain **500**. As such, an object configuration corresponding to an interaction object **620** is requested from blockchain **500** through network **310** (or in some embodiments, the object configuration is requested from object database **708**). In a next step **903**, fields **621** to **628** for interaction object **620** (as

25 outlined in Fig. 6) are recursively populated until all required details are configured. In this example, interaction object **620** may include an interactionType **602** comprising of a contract/intention **603** whereby a supplemental object **650** is expected at some point in the future to, for example, outlining details of a fulfilment of contract **603**. Once all fields **621** to

30

628 have been populated and configured, the process continues to a next step 904 whereby one or more rules are added based on pre-configuration (as defined in, for example, configuration database 706) or through user intervention (for example from a company device 712. Rules may be assigned automatically by rules engine 703 based on object type 5 600, a specific user device 713, an associated company device 712, an entity device 715 (for example, an entityCategory 632 for entity device 715). Once the object configuration is complete and associated rules have been assigned, the object, for example, interaction object 620 discussed in this example) is issued by interaction recorder 702, in step 905 to blockchain 500 as block 540 to active block 501n. A similar process 900 applies for all blocks 600 that 10 are added to the blockchain based on the device, interaction, and other factors.

[0088] Fig. 10 is a flow diagram illustrating an exemplary method for issuing a plurality of interaction objects to a block reconciled blockchain, according to a preferred embodiment of the invention. According to the embodiment, a process for issuance of an interaction object 620 (referring to Fig. 6) starts at a first step 1001. In a next step 1002, an interaction type 602 15 is determined to a type for the interaction (for example, an interactionType 602 as described in Fig. 6). In a next step 1003, an interaction object 620 configuration is requested from blockchain 500 via network 310. In some embodiments, interaction object 620 configuration (for example, as configured in Fig. 9) is requested from a local object database 708. In some embodiments, object database 708 is a backup of blockchain 500 or a redundant copy for 20 failover purposes, speed of access, or as a backup if network 310 becomes unavailable. In a next step 1004, interactionItems 628 are populated based on details from an associated interaction between an entity device 715 and a user device 713 or interaction between a plurality of user devices 713 on other devices. For example, a first user device 713 requests professional services associated to a second user device 713 that involves a contract and 25 services exchanged for value. Accordingly, a digital signature for the first user device 713 is added to field 615 of interaction object 620 (It should be appreciated that all fields of blockchain object 610 are inherited by interaction object 620 and are thus present within interaction object 620, as described previously). A digital signature for the second user device 713 is recorded in other_party_digital_signature 625. Further according to the example, 30 details surrounding an agreement between the first and second user device 713 are created and an interactionType contract/intention 603 is recorded to interactionType 626 of interaction object 620. Details describing the agreement (for example, cost, duration, start of service, end of service, etc.) are added to interaction items 628. In a next step, 1005,

interactionType **626** of interaction object **620** is analyzed to determine if a fulfilment is required. That is, that compiler **701** or report engine **716** may be expecting an associated supplemental object **660** as further details for the interaction described in the instant interaction object **620**. In some embodiment, some interaction object **620** configurations, a

5 primary interaction object **620** is configured detailing an agreement between a user device **713** and another device, for example, an entity device **715**, in this regard, there may be a plurality of interaction types interactionTypes **602** that would require a supplemental object **660**, for example, an interactionType **602** (as configured by interactionType **626**) configured as purchase **604** may require a supplemental object **660** to indicate that goods were indeed

10 exchanged for value; an interactionType **626** configured as refund **605** may require a supplemental object **660** to indicate that a refund was actually issued; an interactionType **626** configured as expense **606** may require a supplemental object **660** to indicate that an associated expense was reimbursed; an interactionType **626** configured as fulfillment **607** may require a supplemental object **660** to indicate that some other condition expected for

15 compilation by compiler **701** or report engine **716**. It should be appreciated that for other object configurations, supplemental object **660** indicates that a previous interaction had a certain outcome. Once fields for interaction object **620** are configured, in a next step **1006**, a reconciliation process commences to establish a smart contract, collect digital signatures of devices involved in the interaction, and data is recorded to the object to finalize the object to

20 prepare for issuance as a block on blockchain **500** as follows: In a next step **1007**, a smart contract is established to, at least, be used to automate transaction logic that may need to happen on blockchain **500**. It should be appreciated that the smart contract step takes on several meanings from the smart contract code, whereby the code expresses the contract and technical features of blockchain **500**. In some embodiments, smart contracts may be used to

25 create a binding legal agreement, or an effective substitute for a binding legal agreement. With respect to smart contract code, blockchain **500** is capable to run code. While blockchains known in the art to primarily designed to perform a small set of simple operations – mainly, transactions of a currency-like token, techniques have been developed to allow blockchains to perform more complex programming operations, the instant invention is

30 able to extend the capability to have fulfilment of agreements while enjoying the security of a blockchain system. Because smart contract code run on a blockchain, they have unique characteristics compared to other types of programming instructions. First, the programming instructions themselves may be recorded on blockchain **500**, which gives blockchain **500** a characteristic permanence and censorship resistance. Second, the program instructions

themselves may control blockchain assets. That is, transactions can be stored. Third, program instructions are executed by blockchain **500**, meaning that it will always execute as written and no one can interfere with its operation. Accordingly, in a preferred embodiment, smart contract is used to refer to this blockchain code, for example, in an Ethereum arrangement

5 whereby with the Ethereum project, the primary purpose is to be a platform for smart contract code. It should be appreciated however that in many embodiments, the term smart contract is used to refer to any complex programming instructions that are stored and executed on blockchain **500**. Given that this programming code is governing something important and valuable, i.e. interactions between stakeholder devices (such as user devices **713**, company

10 devices **712**, and entity devices **715**), the smart contract code is a mechanism to enforce any terms associated to interactions recorded on blockchain **500**. In some embodiments, the smart contract code may be a governance application that controls account permissions. In many embodiments, smart contract code is not used in isolation but as a small piece in a larger application (for example, an Ethereum arrangement may be primarily comprised of smart

15 contract code). In a next step **1008**, digital signatures are collected from one or more devices associated to interaction object **630** to ensure that items are only written to blockchain **500** if it comprises valid owners (that is, reconcile that the interaction object **620** and the block itself is valid and contains a valid transaction). It should be appreciated that valid owners may be determined by miners **560** (or in some embodiments peer nodes **550**) based on the given

20 digital signature and public key pair. In a next step **1009**, the block is finalized comprising interaction object **620** and other data to make it ready for issuance. In a next step **1010**, interaction object **620** is issued to blockchain **500** via network **310** by interaction recorder **702**. It should be appreciated that with the proper digital signatures in place, blockchain miner **560** will be able to function as intended and see the issuance of the block as valid.

25 **[0089] Fig. 11** is a flow diagram illustrating an exemplary method for compiling a plurality of interaction blocks to a block reconciled blockchain, according to a preferred embodiment of the invention. According to the embodiment, a plurality of objects **600** are compiled by compiler **701** to create reports, calculate values, perform object reconciliation, and the like, starts in a first step **1101**. In a next step **1102**, compilation criteria may be received from a

30 user device **713** (for example, a user device **713** belonging to an administrator), company device **712** (for example, a company device belonging to an individual wanting to compile an expense report associated to a user device **713** or an entity device **715**), subscriber device **714**, or entity device **715**. Compilation criteria may define which objects are of interest to the

requesting device for reconciliation, for example, at least a portion of interaction objects **620** based on a period-of-time, at least a portion of interaction objects **620** belonging to a particular user device **713** or a particular entity device **715**, or at least a portion of interaction objects **620** involving interactions between two (or more) particular user devices **713**. It should be appreciated that compilation criteria may involve any object **600** or selected and collected using any field of any previously issued objects **600**.

[0090] In a next step **1103**, compiler **701** uses the received criteria to identify at least a portion of objects previously issued as blocks to blockchain **500** associated to the criteria from step **1102**. In a next step **1104** received blocks are processed (for example, are access through decryption based on access rights, if any). It should be appreciated that processing can include computation on fields and values stored in objects **600** (that is, objects **600** collected in step **1103**), for example, date ranges may be calculated, percentages on values may be determined, values may be added or subtracted, or other computations based on, for example, the object type for collected objects **600**, the interaction type for collected objects **600**, or in combination with data or rules from external data source **720**. It should also be appreciated that a plurality of preconfigured rules (previously stored as rules objects **644** and associated to the collected objects **600**) may be performed in step **1104**. For example, rules that define a category for processed information, or how particular computations should be carried out, or if some external data source **720** or external rules should be used in processing.

[0091] In a next step **1105** supplemental blocks **660** (if any) are collected from blockchain **500** based on the received criteria (from step **1102**), if, for example, one or more interaction objects **620** identified that an associated supplemental object **660** should be collected. If so, in step **1106** compiler **701** processes the objects requiring supplemental information by modifying, adding, or replacing any previous associated collected objects **600** or by applying a computation to the plurality of values from collected objects **600**, collected supplemental objects **660** or any combination thereof.

[0092] In a next step **1107**, collected supplemental objects **660** may be categorized as replacement objects (if any). In this regard, collected replacement objects **660** are then processed to replace data, in step **1108**, for previous issued objects **600**.

[0093] In a next step **1116**, compiler **701** determines if a previously issued collected object **600** is expecting an associated supplemental object **660** but none were present on blockchain **500**. In this case, compiler **701** (or in some embodiments, reporting engine **716**) may analyze

date specific properties within interactionItems **628** or based on a calculation using date-time **613** (or a combination of both) of, for example, where object **600** is an interaction object **620**, to determine if an associated supplemental object **660** should have already been issued to blockchain **500** or if one is expected at some future point. In the case where a supplemental
5 object **660** should exist and there is not one present, compiler **701** may flag the parent interaction object (that is, the interaction object **620** that has no supplemental object **660** that was expected). In some embodiments, where a supplemental object **660** is expected and a report is being created by report engine **716**, proper reporting considerations may be put in place to identify the missing supplemental object **660**. For example, for an interaction object
10 **620** where an interactionType **626** is configured as refund **605**, and no expected supplemental object **660** exists, it may indicate that the refund was not received or refund process was not completed (or in some configurations, based on, for example, calculations, a refund may still be pending). In this example, and in the case where a compilation is being performed by compiler **701**, interaction **620** will be flagged as not executed, and in the case of reporting by
15 report engine **716**, a resulting report may reflect that no refund was given for an interaction represented by interaction object **620**.

[0094] In a next step **1109**, there may be sub-criteria to take into consideration by compiler **701**, for example, as received from company device **712** or user device **713**. For example, criteria indicating a creation of one or more compilation objects **650** comprising aggregated
20 information from the collected objects **600**. For example, a compilation object **650** may have pre-calculated values present, may have supplemental values replaced (for example, as performed in step **1108**). Compilation sub-criteria that may be received in step **1109** may optionally, as described, produce a compilation object **650** with compiled information. If a compilation object **650** is created, it may be written to blockchain **500** by interaction recorder
25 **702**.

[0095] In some embodiments compiled blocks collected, in step **1111**, are made available through an application programming interface (API) for embedding into other software (and hardware) packages in step **1112**. In some embodiments, the API also receives any compiled objects previously created and issued to blockchain **500**.

30 [0096] In some embodiments, in step **1113**, a viewing device (for example, company device **712**, user device **713**, subscriber device **714**, or entity device **715**) may view compiled information as compiled in process **1100** and may optionally create reports in step **1114**.

Exemplary functions

[0097] According to a preferred embodiment of the invention, exemplary programming instructions to perform at least a portion of the functions described previously are as follows. The accompanying programming instructions are meant as a notation resembling simplified programming instruction and meant to illustrate several embodiments of the invention and, together with the description, serve to explain the principles of the invention according to the embodiments. It will be appreciated by one skilled in the art that the particular programming instructions are only a subset to highlight specific functions and are merely exemplary, and are not to be considered as limiting of the scope of the invention or the claims herein in any way.

[0098] In a preferred embodiment of the invention, exemplary programming instructions for inserting objects **600** to blockchain **500** may be:

```

Function insert(BlockchainObject newObject)
    submits an object 600 to blockchain miners 560 for verification
    if accepted, will eventually be written into the next Block as block 540.

```

[0099] This function may ensure that items are written to the Blockchain if they are submitted by valid owners as described previously. Valid owners are determined by miners **560** (or ins some embodiments by peer nodes **550**) based on associated digital signatures and public key pair.

[0100] In a preferred embodiment of the invention, exemplary programming instructions for retrieving relevant objects **600** based on objectId **611** which may return more than one objects **600** including any amendments (that is, considering supplemental objects **660** or supplemental objects **660** designated as replacement objects), are as follows:

```

Function retrieveObject(String id){
    Array<BlockchainObject> return_value = []
    anObject = theBlockchain.getFinalizedBlocks().search(objectId == id)
    returnValue.add(anObject)
    ammendedObjects =
    theBlockchain.getFinalizedBlocks().search(BlockchainObject.type == Supplemental
    &&                                ammendedObjectId == anObject.objectId)
    returnValue.add(ammendedObjects)

```

```

return return_value
}

```

- [0101]** In a preferred embodiment of the invention, exemplary programming instructions for retrieving relevant interaction objects **620** based on, for example, a company and a date range, for example, to retrieve a set of items for a compilation step by compiler **701**, based on the properties: date range and company. In some embodiments, a similar search based on interaction_event & user device **713** (such as, interaction objects **620** associated to, for example, “European business trip for John Doe”) may be performed, are as follows:

```

Function retrieveObject(String company_name, DateTime start_date, DateTime
10 end_date){
    Array<BlockchainObject> return_value = []
    someObjects = theBlockchain.getFinalizedBlocks().search(BlockchainObject.type
    == Interaction &&
    company == company_name &&
15 start_date <= date_time <= end_date)
    returnValue.add(someObjects)
    for each (BlockchainObject b in someObjects) {
        ammendedObjects =
    theBlockchain.getFinalizedBlocks().search(BlockchainObject.type == Supplemental
20 && ammendedObjectId == anObject.objectId)
    returnValue.add(ammendedObjects)
    }
    return return_value
}

```

- [0102]** In a preferred embodiment of the invention, exemplary programming instructions to retrieve associated rules for a given interaction object **620**, are as follows:

```

Function retrieveObject(String a_interaction_type, String a_company_type, String
an_entity_type, DateTime start_date, DateTime end_date){
    Array<BlockchainObject> return_value = []
30 ruleObject = theBlockchain.getFinalizedBlocks().search(BlockchainObject.type
    == Rules && type == a_interaction_type &&
    companyType == a_company_type &&

```

```

        entityCategory == an_entity_type &&
        start_date <= date_time <= end_date)
        returnValue.add(ruleObject)
        ammendedObjects =
5      theBlockchain.getFinalizedBlocks().search(BlockchainObject.type == Supplemental
        && ammendedObjectId == anObject.objectId)
        returnValue.add(ammendedObjects)
        return return_value
    }

```

- 10 **[0103]** In a preferred embodiment of the invention, exemplary programming instructions for generating a new interaction object **620** to be submitted to the blockchain **500** by interaction recorder **702**, may be as follows:

```

        Function newInteraction(User consumer, User device_or_company, String
        an_interaction_id, String signature, String event_name, InteractionType t,
15      Array<BlockchainObject> objects, Bool encrypt?){
            interactionObject = new Interaction (consumer = consumer.name,
            company = device_or_company.name,
                interaction_id = an_interaction_id,
                other_party_digital_signature = signature,
20            interaction_event = event_name
            type = t,
            interactionItems = objects)
            if (encrypt?) {
                InteractionObject = encryptBlockchainObject(interactionObject,
25            consumer.privateBlockchainKey, company.privateBlockchainKey)    }

            this.insert(InteractionObject)
        }

```

- 30 **[0104]** In a preferred embodiment of the invention, exemplary programming instructions for compilation of objects by compiler **701** based on received criteria (for example, as in step **1102** referring to **Fig. 11**) may takes at least a portion of associated interaction objects **620** for a given company device **712**; compiler **701** may then compile at least a portion of associated rule objects **644** and at least a portion of associated supplemental objects **660** (i.e.

process any required amendments or replacements) and may be used to calculate a report by report engine **716** (for example, a tax or an expense report). In some embodiments, compilation objects **650** may be added into blockchain **500** for access by, for example, subscriber devices **714** (or other devices). For example, a subscriber device **714** may be a

5 company compiling an expense report for user device **713** for a specific business trip given a specific start date and end date. The exemplary programming instructions are as follows:

```

Function compileReportObjects(String company, DateTime start_date, DateTime
end_date){
    Array<BlockchainObject interaction, BlockchainObject rules> return_value = []
10    interactions = retrieveObject(company, start_date, end_date)
    interactions = decrypt(interactions) //if the items are encrypted, then they have to
be decrypted.
    for each (BlockchainObject t in interactions) {
        //look up the relevant rules and amendments, and link it to each interaction
15    rules = retrieveObject(t.type, t.company.company_type, t.entity.entity_type,
start_date, end_date)
        returnValue.add(t, Rules)
    }
    return_value = reconcile(return_value) // perform the reconciliation step
20    compilationObject = createCompilationObject(return_value, subscribers) //Create a
CompilationObject and record which subscribers are allowed to access the report
    this.insert(compilationObject) //Insert the compilation into the Blockchain
    return compilationObject
}

```

25 **[0105]** In some embodiments, with respect to the retrieveObject function (as above) may be based on interaction_event **627**. In some embodiments, a reconciliation result may be issued into the blockchain **500**. Further, a definition of an additional blockchain object **610** type may be performed, and instead of returning return_value, the instructions may instead make a call to the method: insert(BlockchainObject) as described above.

30 **[0106]** In a preferred embodiment of the invention, exemplary programming instructions may encrypt any objects **600** (for example, blockchain object **610**): using multi-party encryption so that only certain devices involved may read the contents of encrypted objects **600**:

```

Function encryptBlockchainObject(BlockchainObject b, String
private_key_consumer, String private_key_device_or_company){
    BlockchainObject return_value = []
    return_value = applyMultiPartyEncryption(b, private_key_consumer,
5    private_key_device_or_company)
    return return_value
}

```

[0107] In some embodiments, the above function applyMultiPartyEncryption may use multi-party encryption methods such as SHA-256 (or others), so that at least one of either of two private keys associated to the blockchain object **610** will be necessary in order to read the contents of the blockchain object **610**. In some embodiments, public keys, blockchain_id, date range of the block, and digital signatures may not be encrypted. It should be appreciated that in different embodiments, different fields, blocks, or objects may be encrypted while others are not based on the specific requirements of the implementation or sensitivity of data within objects **600**.

[0108] In a preferred embodiment of the invention, exemplary programming instructions to decrypt BlockchainObject may takes any object **600** to decrypt it if the provided privateKey is valid, may be as follows:

```

Function decryptBlockchainObject(BlockchainObject b, String public_key, String
20    private_key){
    BlockchainObject return_value = []
    return_value = decryptBlock(b, public_key, private_key)
    return return_value
}

```

[0109] In some embodiments, the above function decryptBlock may use encryption methods such as SHA-256 (or others) so that if the provided private key satisfies the specified public key, the contents of the BlockchainObject may be decrypted.

[0110] In a preferred embodiment of the invention, exemplary programming instructions to take a set of interaction objects **620** for a given compilation to perform a reconciliation, may be as follows:

```

Function reconciliation(Array<BlockchainObject> objects){

```

For each, for example, for example, interaction object **620** with interactionType **603** (i.e. contract), ensure that there is a matching object that contains the same interaction_id, thus ensuring that both parties agreed to the Contract/Intention. If not, flag these interactions as incomplete.

5 Next, for each valid, for example, interaction object **620** with interactionType **603** (i.e. contract) identified in the previous step, check to see if the associated fulfillment object is present:

If present and fulfilled amicably, the apply appropriate, for example, credit/expenses

10 If present and fulfilled non-amicably (for example, one party did not pay, or the other part did not complete the work, i.e. no supplemental object **660** issued), calculations may result to apply appropriate losses
If not present, then flag as unresolved (in which case a fulfillment could be submitted or could be considered a loss)

15 return results
 }

[0111] It should be appreciated that object type in the above function may be any interactionType **602** (for example refund **605**) that may require reconciliation.

20 **[0112]** The skilled person will be aware of a range of possible modifications of the various embodiments described above. Accordingly, the present invention is defined by the claims and their equivalents.

What is claimed is:

1. A system for block reconciliation, comprising:

a network-connected block reconciliation computer comprising a memory and a processor and further comprising programmable instructions stored in the memory and operating on the processor, the programmable instructions adapted to reconcile blocks in a blockchain environment comprising:

a plurality of connections to a plurality of connected devices;

a connection to one or more blockchains;

an object compiler;

wherein a plurality of criteria is received from a first connected device;

wherein the compiler is configured to receive a plurality of blocks from the one or more blockchains based on the received criteria, each block corresponding to a preconfigured interaction object;

wherein the compiler is configured to analyze the preconfigured interaction objects to determine if there is an associated required supplemental object, an association based on the plurality of criteria;

wherein the compiler is configured to request a plurality of supplemental blocks from the one or more blockchains, each supplemental block corresponding to a required supplemental object;

for each requested supplemental object:

if a first requested supplemental object is not found, the compiler flags the associated interaction object of the preconfigured interaction objects;

otherwise:

if the first requested supplemental object type is replacement, the compiler replaces properties of an associated interaction object with information from properties of the supplemental object;

if the supplemental object type is addendum, the compiler adds properties from the supplemental object to the associated interaction object of the preconfigured interaction objects;

wherein the compiler receives one or more preconfigured rules from the one or more blockchains associated to the preconfigured interaction objects;

wherein the compiler creates one or more compilation objects comprising interaction objects and supplemental objects associated to the plurality of criteria based on the one or more preconfigured rules;

wherein the one or more compilation objects is stored on the one or more blockchains.

2. The system of claim 1, further comprising:

a report engine;

wherein the report engine creates a report based on at least a portion of the one or more compilation objects.

3. The system of claim 1, further comprising:

an external data source;

wherein the compiler uses the external data source to receive additional preconfigured rules to supplement the one or more preconfigured rules from the one or more blockchains.

4. The system of claim 1, further comprising:

an application programming interface;

wherein the application programming interface provides access to the one or more compilation objects to at least a portion of the plurality of connected devices.

5. A method for block reconciliation, comprising the steps of:

receiving, from a first connected device of a plurality of connected devices, a plurality of criteria;

receiving, at a compiler, a plurality of blocks from the one or more blockchains based on the received criteria, each block corresponding to a preconfigured interaction object;

analyzing, at the compiler, the preconfigured interaction objects to determine if there is an associated required supplemental object;

requesting, at the compiler, a plurality of supplemental blocks from the one or more blockchains, each supplemental block corresponding to an associated required supplemental object, an association based on the plurality of criteria;

for each requested supplemental block:

if a first associated required supplemental object does not exist, flagging the associated interaction object of the preconfigured interaction objects;

otherwise:

if an associated object type of the first associated required supplemental object is replacement, replacing, by the compiler, properties from the supplemental object into the associated interaction object with information the properties;

if an associated object type of the corresponding required supplemental object is addendum, adding, by the compiler, properties from the supplemental object to properties of the associated interaction object of the preconfigured interaction object;

receiving, at the compiler, one or more preconfigured rules from the one or more blockchain associated to the preconfigured interaction objects;

creating, at the compiler, one or more compilation objects comprising interaction objects and supplemental objects based on the plurality of criteria and based on the one or more preconfigured rules;

storing, by the compiler, the one or more compilation objects on the one or more blockchains.

6. The method of claim 5, further comprising the step of:

creating, at a report engine, a report based on at least a portion of the one or more compilation objects.

7. The method of claim 5, further comprising the step of:

receiving, at the compiler, additional preconfigured rules, from an external data source, to supplement the one or more preconfigured rules from the one or more blockchains.

8. The method of claim 5, further comprising the step of:

providing access to the one or more compilation objects, by an application programming interface, to at least a portion of the plurality of connected devices.